

FflasFfpack

Generated on Wed Nov 29 2023 00:00:00 for FflasFfpack by Doxygen 1.9.7

Wed Nov 29 2023 00:00:00

1 FFLAS-FFPACK Documentation.	1
1.1 Introduction	1
1.2 Goals	1
1.3 Design	1
1.4 Using FFLAS-FFPACK.	1
1.5 Contributing to fflas-ffpack, getting assistance.	2
1.6 Copying and Licence	2
1.7 Tutorial	2
1.8 Configuring and Installing FFLAS-FFPACK	2
1.9 Architecture of the library.	2
2 Bug List	3
3 Bibliography	7
4 Todo List	9
5 Module Index	13
5.1 Modules	13
6 Namespace Index	15
6.1 Namespace List	15
7 Hierarchical Index	17
7.1 Class Hierarchy	17
8 Data Structure Index	25
8.1 Data Structures	25
9 File Index	33
9.1 File List	33
10 Module Documentation	41
10.1 CHECKER	41
10.2 FFLAS-FFPACK	41
10.2.1 Detailed Description	41
10.2.2 FFLAS	42
10.2.3 Interfaces	42
10.3 Matrix Multiplication Algorithms	42
10.3.1 Detailed Description	42
10.4 SIMD wrapper	42
10.5 FFPACK	43
10.5.1 Detailed Description	43
10.6 FFLAS-FFPACK fields	43
10.6.1 Detailed Description	43
10.7 RNS	43

11 Namespace Documentation	45
11.1 FFLAS Namespace Reference	45
11.1.1 Typedef Documentation	72
11.1.1.1 Checker_fgemm	72
11.1.1.2 Checker_ftrsm	72
11.1.1.3 ForceCheck_fgemm	72
11.1.1.4 ForceCheck_ftrsm	72
11.1.1.5 ZOSparseMatrix	72
11.1.1.6 NotZOSparseMatrix	72
11.1.1.7 SimdSparseMatrix	73
11.1.1.8 NoSimdSparseMatrix	73
11.1.1.9 MKLSparseMatrixFormat	73
11.1.1.10 NotMKLSparseMatrixFormat	73
11.1.1.11 has_plus	73
11.1.1.12 has_minus	73
11.1.1.13 has_equal	73
11.1.1.14 has_plus_eq	73
11.1.1.15 has_minus_eq	73
11.1.1.16 has_mul	74
11.1.1.17 has_mul_eq	74
11.1.1.18 Timer	74
11.1.1.19 BaseTimer	74
11.1.1.20 UserTimer	74
11.1.1.21 SysTimer	74
11.1.2 Enumeration Type Documentation	74
11.1.2.1 FFLAS_ORDER	74
11.1.2.2 FFLAS_TRANSPOSE	75
11.1.2.3 FFLAS_UPLO	75
11.1.2.4 FFLAS_DIAG	75
11.1.2.5 FFLAS_SIDE	75
11.1.2.6 FFLAS_BASE	76
11.1.2.7 number_kind	76
11.1.2.8 SparseMatrix_t	76
11.1.2.9 FFLAS_FORMAT	77
11.1.3 Function Documentation	77
11.1.3.1 InfNorm()	77
11.1.3.2 min3()	77
11.1.3.3 max3()	77
11.1.3.4 min4()	77
11.1.3.5 max4()	78
11.1.3.6 fadd() [1/8]	78
11.1.3.7 faddin() [1/5]	78

11.1.3.8 fsub() [1/4]	78
11.1.3.9 fsubin() [1/3]	78
11.1.3.10 fadd() [2/8]	79
11.1.3.11 pfadd()	79
11.1.3.12 pfsub()	79
11.1.3.13 pfaddin()	80
11.1.3.14 pfsubin()	80
11.1.3.15 fadd() [3/8]	80
11.1.3.16 fsub() [2/4]	81
11.1.3.17 faddin() [2/5]	81
11.1.3.18 faddin() [3/5]	81
11.1.3.19 fsubin() [2/3]	82
11.1.3.20 fadd() [4/8]	82
11.1.3.21 fassign() [1/10]	83
11.1.3.22 fassign() [2/10]	83
11.1.3.23 fassign() [3/10]	83
11.1.3.24 fassign() [4/10]	84
11.1.3.25 fassign() [5/10]	84
11.1.3.26 fassign() [6/10]	84
11.1.3.27 fassign() [7/10]	84
11.1.3.28 fassign() [8/10]	85
11.1.3.29 faxpy() [1/6]	86
11.1.3.30 faxpy() [2/6]	86
11.1.3.31 faxpy() [3/6]	86
11.1.3.32 faxpy() [4/6]	87
11.1.3.33 fdot() [1/11]	87
11.1.3.34 fdot() [2/11]	87
11.1.3.35 fdot() [3/11]	88
11.1.3.36 fdot() [4/11]	88
11.1.3.37 fdot() [5/11]	88
11.1.3.38 fdot() [6/11]	88
11.1.3.39 fdot() [7/11]	89
11.1.3.40 fdot() [8/11]	89
11.1.3.41 fgemm() [1/23]	89
11.1.3.42 fgemm() [2/23]	90
11.1.3.43 fgemm() [3/23]	90
11.1.3.44 fgemm() [4/23]	90
11.1.3.45 fgemm() [5/23]	91
11.1.3.46 fgemm() [6/23]	92
11.1.3.47 fsquare() [1/6]	92
11.1.3.48 fsquare() [2/6]	93
11.1.3.49 fsquare() [3/6]	93

11.1.3.50 fsquare() [4/6]	93
11.1.3.51 fsquare() [5/6]	93
11.1.3.52 fgemm() [7/23]	94
11.1.3.53 fgemm() [8/23]	94
11.1.3.54 fgemm() [9/23]	94
11.1.3.55 fgemm() [10/23]	95
11.1.3.56 fgemm() [11/23]	95
11.1.3.57 fgemm() [12/23]	96
11.1.3.58 fgemm() [13/23]	96
11.1.3.59 fgemm() [14/23]	96
11.1.3.60 fgemm() [15/23]	97
11.1.3.61 fgemm() [16/23]	97
11.1.3.62 fgemm() [17/23]	97
11.1.3.63 fgemm() [18/23]	98
11.1.3.64 fgemv() [1/19]	98
11.1.3.65 fgemv() [2/19]	99
11.1.3.66 fgemv() [3/19]	99
11.1.3.67 fgemv() [4/19]	99
11.1.3.68 fgemv() [5/19]	100
11.1.3.69 fgemv() [6/19]	100
11.1.3.70 fgemv() [7/19]	101
11.1.3.71 fgemv() [8/19]	101
11.1.3.72 fgemv() [9/19]	101
11.1.3.73 fgemv() [10/19]	102
11.1.3.74 fgemv() [11/19]	102
11.1.3.75 fgemv() [12/19]	102
11.1.3.76 fgemv() [13/19]	103
11.1.3.77 fgemv() [14/19]	103
11.1.3.78 fgemv() [15/19]	103
11.1.3.79 fgemv() [16/19]	104
11.1.3.80 fger() [1/12]	104
11.1.3.81 fger() [2/12]	105
11.1.3.82 fger() [3/12]	105
11.1.3.83 fger() [4/12]	105
11.1.3.84 fger() [5/12]	106
11.1.3.85 fger() [6/12]	106
11.1.3.86 fger() [7/12]	106
11.1.3.87 fger() [8/12]	107
11.1.3.88 fger() [9/12]	107
11.1.3.89 fger() [10/12]	107
11.1.3.90 fger() [11/12]	108
11.1.3.91 freduce() [1/11]	108

11.1.3.92 <code>freduce()</code> [2/11]	108
11.1.3.93 <code>freduce_constoverride()</code> [1/2]	109
11.1.3.94 <code>finit()</code> [1/8]	109
11.1.3.95 <code>finit()</code> [2/8]	109
11.1.3.96 <code>freduce()</code> [3/11]	110
11.1.3.97 <code>freduce()</code> [4/11]	110
11.1.3.98 <code>pfreduce()</code>	110
11.1.3.99 <code>freduce()</code> [5/11]	110
11.1.3.100 <code>freduce_constoverride()</code> [2/2]	112
11.1.3.101 <code>finit()</code> [3/8]	112
11.1.3.102 <code>finit()</code> [4/8]	112
11.1.3.103 <code>freduce()</code> [6/11]	113
11.1.3.104 <code>freduce()</code> [7/11]	113
11.1.3.105 <code>freivalds()</code>	113
11.1.3.106 <code>fscalin()</code> [1/10]	114
11.1.3.107 <code>fscal()</code> [1/10]	114
11.1.3.108 <code>fscal()</code> [2/10]	115
11.1.3.109 <code>fscal()</code> [3/10]	115
11.1.3.110 <code>fscalin()</code> [2/10]	115
11.1.3.111 <code>fscalin()</code> [3/10]	116
11.1.3.112 <code>fscalin()</code> [4/10]	116
11.1.3.113 <code>fscal()</code> [4/10]	116
11.1.3.114 <code>fscalin()</code> [5/10]	117
11.1.3.115 <code>fscal()</code> [5/10]	117
11.1.3.116 <code>fscalin()</code> [6/10]	117
11.1.3.117 <code>fscal()</code> [6/10]	117
11.1.3.118 <code>fscalin()</code> [7/10]	118
11.1.3.119 <code>fscal()</code> [7/10]	118
11.1.3.120 <code>fscalin()</code> [8/10]	118
11.1.3.121 <code>fscal()</code> [8/10]	118
11.1.3.122 <code>fsyr2k()</code>	119
11.1.3.123 <code>fsyrk()</code> [1/16]	119
11.1.3.124 <code>fsyrk()</code> [2/16]	120
11.1.3.125 <code>fsyrk()</code> [3/16]	120
11.1.3.126 <code>fsyrk()</code> [4/16]	121
11.1.3.127 <code>fsyrk()</code> [5/16]	121
11.1.3.128 <code>fsyrk()</code> [6/16]	121
11.1.3.129 <code>fsyrk()</code> [7/16]	122
11.1.3.130 <code>fsyrk()</code> [8/16]	122
11.1.3.131 <code>fsyrk()</code> [9/16]	122
11.1.3.132 <code>fsyrk()</code> [10/16]	123
11.1.3.133 <code>fsyrk()</code> [11/16]	123

11.1.3.134 fsyrk() [12/16]	124
11.1.3.135 fsyrk() [13/16]	124
11.1.3.136 fsyrk() [14/16]	125
11.1.3.137 computeS1S2()	126
11.1.3.138 fsyrk() [15/16]	126
11.1.3.139 fsyrk() [16/16]	126
11.1.3.140 fsyrk_strassen() [1/2]	127
11.1.3.141 ftrmm() [1/3]	127
11.1.3.142 ftrmm() [2/3]	128
11.1.3.143 ftrsm() [1/9]	128
11.1.3.144 ftrsm() [2/9]	129
11.1.3.145 ftrsm() [3/9]	129
11.1.3.146 ftrsm() [4/9]	129
11.1.3.147 ftrsm() [5/9]	130
11.1.3.148 cblas_imptrsm()	130
11.1.3.149 ftrsv() [1/2]	130
11.1.3.150 igemm_()	131
11.1.3.151 finit() [5/8]	131
11.1.3.152 fconvert() [1/3]	132
11.1.3.153 fnegin() [1/4]	132
11.1.3.154 fneg() [1/4]	133
11.1.3.155 fzero() [1/5]	133
11.1.3.156 frand() [1/2]	133
11.1.3.157 fiszero() [1/4]	134
11.1.3.158 fequal() [1/4]	134
11.1.3.159 faxpby() [1/2]	135
11.1.3.160 fdot() [9/11]	135
11.1.3.161 fswap() [1/2]	135
11.1.3.162 fzero() [2/5]	137
11.1.3.163 fzero() [3/5]	137
11.1.3.164 frand() [2/2]	138
11.1.3.165 fequal() [2/4]	138
11.1.3.166 fiszero() [2/4]	139
11.1.3.167 fidentity() [1/4]	139
11.1.3.168 fidentity() [2/4]	139
11.1.3.169 finit() [6/8]	139
11.1.3.170 fconvert() [2/3]	140
11.1.3.171 fnegin() [2/4]	140
11.1.3.172 fneg() [2/4]	141
11.1.3.173 faxpby() [2/2]	141
11.1.3.174 fmove() [1/2]	142
11.1.3.175 bitsize()	142

11.1.3.176 <code>bitsize< Givaro::ZRing< Givaro::Integer > >()</code>	143
11.1.3.177 <code>ftrmv()</code>	143
11.1.3.178 <code>ftsm()</code> [6/9]	143
11.1.3.179 <code>fsyrk_strassen()</code> [2/2]	144
11.1.3.180 <code>pfgemm()</code> [1/7]	144
11.1.3.181 <code>pfgemm_1D_rec()</code>	145
11.1.3.182 <code>pfgemm_2D_rec()</code>	145
11.1.3.183 <code>pfgemm_3D_rec()</code>	146
11.1.3.184 <code>pfgemm_3D_rec2()</code>	146
11.1.3.185 <code>fgemm()</code> [19/23]	146
11.1.3.186 <code>ftsm()</code> [7/9]	147
11.1.3.187 <code>ftsm()</code> [8/9]	147
11.1.3.188 <code>fspm()</code> [1/2]	147
11.1.3.189 <code>fspm()</code>	148
11.1.3.190 <code>sparse_init()</code> [1/16]	148
11.1.3.191 <code>sparse_init()</code> [2/16]	148
11.1.3.192 <code>sparse_delete()</code> [1/12]	148
11.1.3.193 <code>sparse_delete()</code> [2/12]	148
11.1.3.194 <code>sparse_init()</code> [3/16]	149
11.1.3.195 <code>sparse_init()</code> [4/16]	149
11.1.3.196 <code>sparse_delete()</code> [3/12]	149
11.1.3.197 <code>sparse_delete()</code> [4/12]	149
11.1.3.198 <code>sparse_print()</code> [1/3]	149
11.1.3.199 <code>sparse_init()</code> [5/16]	150
11.1.3.200 <code>sparse_init()</code> [6/16]	150
11.1.3.201 <code>sparse_init()</code> [7/16]	150
11.1.3.202 <code>sparse_init()</code> [8/16]	150
11.1.3.203 <code>sparse_delete()</code> [5/12]	151
11.1.3.204 <code>sparse_init()</code> [9/16]	151
11.1.3.205 <code>sparse_init()</code> [10/16]	151
11.1.3.206 <code>sparse_init()</code> [11/16]	151
11.1.3.207 <code>sparse_delete()</code> [6/12]	151
11.1.3.208 <code>sparse_delete()</code> [7/12]	152
11.1.3.209 <code>sparse_init()</code> [12/16]	152
11.1.3.210 <code>sparse_init()</code> [13/16]	152
11.1.3.211 <code>sparse_delete()</code> [8/12]	152
11.1.3.212 <code>sparse_delete()</code> [9/12]	152
11.1.3.213 <code>sparse_print()</code> [2/3]	152
11.1.3.214 <code>sparse_delete()</code> [10/12]	153
11.1.3.215 <code>sparse_init()</code> [14/16]	153
11.1.3.216 <code>operator<<()</code>	153
11.1.3.217 <code>readSmsFormat()</code>	153

11.1.3.218 readSprFormat()	153
11.1.3.219 getDataType() [1/4]	154
11.1.3.220 getDataType() [2/4]	154
11.1.3.221 getDataType() [3/4]	154
11.1.3.222 getDataType() [4/4]	154
11.1.3.223 readMachineType()	154
11.1.3.224 readDnsFormat()	154
11.1.3.225 writeDnsFormat()	154
11.1.3.226 fspmv() [2/2]	155
11.1.3.227 sparse_delete() [11/12]	155
11.1.3.228 sparse_delete() [12/12]	155
11.1.3.229 sparse_print() [3/3]	155
11.1.3.230 sparse_init() [15/16]	155
11.1.3.231 sparse_init() [16/16]	155
11.1.3.232 computeDeviation()	156
11.1.3.233 getStat()	156
11.1.3.234 maxCardinality()	156
11.1.3.235 maxCardinality< Givaro::Modular< int64_t > >()	156
11.1.3.236 maxCardinality< Givaro::Modular< int32_t > >()	156
11.1.3.237 minCardinality()	156
11.1.3.238 fflas_delete() [1/4]	156
11.1.3.239 fflas_delete() [2/4]	157
11.1.3.240 fflas_new() [1/7]	157
11.1.3.241 fflas_new() [2/7]	157
11.1.3.242 finit_rns() [1/2]	157
11.1.3.243 finit_trans_rns()	157
11.1.3.244 fconvert_rns() [1/2]	158
11.1.3.245 fconvert_trans_rns()	158
11.1.3.246 fflas_new() [3/7]	158
11.1.3.247 fflas_new() [4/7]	158
11.1.3.248 finit_rns() [2/2]	158
11.1.3.249 fconvert_rns() [2/2]	159
11.1.3.250 freduce() [8/11]	159
11.1.3.251 freduce() [9/11]	159
11.1.3.252 finit() [7/8]	160
11.1.3.253 fconvert() [3/3]	160
11.1.3.254 fnegin() [3/4]	161
11.1.3.255 fneg() [3/4]	161
11.1.3.256 fzero() [4/5]	161
11.1.3.257 fiszero() [3/4]	162
11.1.3.258 fequal() [3/4]	162
11.1.3.259 fassign() [9/10]	163

11.1.3.260 fscaln()	[9/10]	163
11.1.3.261 fscal()	[9/10]	164
11.1.3.262 faxpy()	[5/6]	164
11.1.3.263 fdot()	[10/11]	165
11.1.3.264 fswap()	[2/2]	165
11.1.3.265 fadd()	[5/8]	166
11.1.3.266 fsub()	[3/4]	166
11.1.3.267 faddin()	[4/5]	166
11.1.3.268 fadd()	[6/8]	166
11.1.3.269 fassign()	[10/10]	167
11.1.3.270 fzero()	[5/5]	167
11.1.3.271 fequal()	[4/4]	167
11.1.3.272 fiszero()	[4/4]	168
11.1.3.273 fidentity()	[3/4]	168
11.1.3.274 fidentity()	[4/4]	169
11.1.3.275 freduce()	[10/11]	169
11.1.3.276 freduce()	[11/11]	169
11.1.3.277 finit()	[8/8]	170
11.1.3.278 fnegin()	[4/4]	170
11.1.3.279 fneg()	[4/4]	170
11.1.3.280 fscaln()	[10/10]	171
11.1.3.281 fscal()	[10/10]	171
11.1.3.282 faxpy()	[6/6]	172
11.1.3.283 fmove()	[2/2]	172
11.1.3.284 fadd()	[7/8]	173
11.1.3.285 fsub()	[4/4]	174
11.1.3.286 fsubin()	[3/3]	174
11.1.3.287 fadd()	[8/8]	175
11.1.3.288 faddin()	[5/5]	175
11.1.3.289 fgemv()	[17/19]	175
11.1.3.290 fger()	[12/12]	176
11.1.3.291 ftrsv()	[2/2]	177
11.1.3.292 ftrsm()	[9/9]	177
11.1.3.293 ftrmm()	[3/3]	178
11.1.3.294 fgemm()	[20/23]	179
11.1.3.295 fgemm()	[21/23]	180
11.1.3.296 fgemm()	[22/23]	180
11.1.3.297 fgemm()	[23/23]	180
11.1.3.298 fsquare()	[6/6]	181
11.1.3.299 BlockCuts()	[1/2]	181
11.1.3.300 BlockCuts< CuttingStrategy::Single, StrategyParameter::Threads >()		181
11.1.3.301 BlockCuts< CuttingStrategy::Row, StrategyParameter::Fixed >()		182

11.1.3.302 BlockCuts< CuttingStrategy::Row, StrategyParameter::Grain >()	182
11.1.3.303 BlockCuts< CuttingStrategy::Block, StrategyParameter::Grain >()	182
11.1.3.304 BlockCuts< CuttingStrategy::Column, StrategyParameter::Fixed >()	182
11.1.3.305 BlockCuts< CuttingStrategy::Column, StrategyParameter::Grain >()	183
11.1.3.306 BlockCuts< CuttingStrategy::Block, StrategyParameter::Fixed >()	183
11.1.3.307 BlockCuts< CuttingStrategy::Row, StrategyParameter::Threads >()	183
11.1.3.308 BlockCuts< CuttingStrategy::Column, StrategyParameter::Threads >()	183
11.1.3.309 BlockCuts< CuttingStrategy::Block, StrategyParameter::Threads >()	183
11.1.3.310 BlockCuts() [2/2]	184
11.1.3.311 pfzero()	184
11.1.3.312 pfrand()	184
11.1.3.313 fdot() [11/11]	184
11.1.3.314 pfgemm() [2/7]	185
11.1.3.315 pfgemm() [3/7]	185
11.1.3.316 pfgemm() [4/7]	185
11.1.3.317 pfgemm() [5/7]	186
11.1.3.318 pfgemm() [6/7]	186
11.1.3.319 pfgemm() [7/7]	187
11.1.3.320 fgemv() [18/19]	187
11.1.3.321 fgemv() [19/19]	187
11.1.3.322 parseArguments()	188
11.1.3.323 getArgumentValue()	188
11.1.3.324 writeCommandString()	188
11.1.3.325 WriteMatrix() [1/2]	188
11.1.3.326 preamble()	190
11.1.3.327 ReadMatrix() [1/2]	190
11.1.3.328 ReadMatrix() [2/2]	190
11.1.3.329 WriteMatrix() [2/2]	191
11.1.3.330 WritePermutation()	191
11.1.3.331 alignable()	192
11.1.3.332 alignable< Givaro::Integer * >()	192
11.1.3.333 fflas_new() [5/7]	192
11.1.3.334 fflas_new() [6/7]	192
11.1.3.335 fflas_new() [7/7]	192
11.1.3.336 fflas_delete() [3/4]	192
11.1.3.337 fflas_delete() [4/4]	192
11.1.3.338 prefetch()	193
11.1.3.339 getTLBSize()	193
11.1.3.340 queryCacheSizes()	193
11.1.3.341 queryL1CacheSize()	193
11.1.3.342 queryTopLevelCacheSize()	193
11.1.3.343 getSeed()	193

11.2 FFLAS::_ftranspose_impl Namespace Reference	194
11.2.1 Function Documentation	194
11.2.1.1 not_inplace()	194
11.2.1.2 square_inplace()	194
11.2.1.3 nonsquare_inplace_v1()	194
11.2.1.4 nonsquare_inplace_v2()	195
11.3 FFLAS::BLAS3 Namespace Reference	195
11.3.1 Function Documentation	196
11.3.1.1 Bini()	196
11.3.1.2 WinoPar()	197
11.3.1.3 Winograd()	197
11.3.1.4 WinogradAcc_3_23()	197
11.3.1.5 WinogradAcc_3_21()	198
11.3.1.6 WinogradAcc_2_24()	198
11.3.1.7 WinogradAcc_2_27()	199
11.3.1.8 WinogradAcc_LR()	199
11.3.1.9 WinogradAcc_R_S()	199
11.3.1.10 WinogradAcc_L_S()	200
11.3.1.11 Winograd_LR_S()	200
11.3.1.12 Winograd_L_S()	200
11.3.1.13 Winograd_R_S()	201
11.4 FFLAS::csr_hyb_details Namespace Reference	201
11.5 FFLAS::CuttingStrategy Namespace Reference	201
11.5.1 Typedef Documentation	202
11.5.1.1 RNSModulus	202
11.6 FFLAS::details Namespace Reference	202
11.6.1 Function Documentation	203
11.6.1.1 fadd() [1/5]	203
11.6.1.2 fadd() [2/5]	204
11.6.1.3 fadd() [3/5]	204
11.6.1.4 fadd() [4/5]	204
11.6.1.5 fadd() [5/5]	205
11.6.1.6 faxpy() [1/2]	205
11.6.1.7 faxpy() [2/2]	205
11.6.1.8 freduce() [1/4]	205
11.6.1.9 freduce() [2/4]	206
11.6.1.10 freduce() [3/4]	206
11.6.1.11 freduce() [4/4]	206
11.6.1.12 fscaln() [1/2]	206
11.6.1.13 fscal() [1/2]	207
11.6.1.14 fscaln() [2/2]	207
11.6.1.15 fscal() [2/2]	207

11.6.1.16 igebb44()	207
11.6.1.17 igebb24()	208
11.6.1.18 igebb14()	208
11.6.1.19 igebb41()	208
11.6.1.20 igebb21()	208
11.6.1.21 igebb11()	209
11.6.1.22 igebp()	209
11.6.1.23 pack_lhs()	209
11.6.1.24 pack_rhs()	210
11.6.1.25 gebp()	210
11.6.1.26 BlockingFactor()	210
11.7 FFLAS::details_spmv Namespace Reference	210
11.8 FFLAS::ElementCategories Namespace Reference	211
11.9 FFLAS::FieldCategories Namespace Reference	211
11.9.1 Detailed Description	211
11.10 FFLAS::MMHelperAlgo Namespace Reference	211
11.11 FFLAS::ModeCategories Namespace Reference	212
11.11.1 Detailed Description	212
11.12 FFLAS::ParSeqHelper Namespace Reference	212
11.12.1 Detailed Description	212
11.13 FFLAS::Protected Namespace Reference	213
11.13.1 Function Documentation	216
11.13.1.1 computeFactorClassic() [1/3]	216
11.13.1.2 computeFactorClassic() [2/3]	216
11.13.1.3 computeFactorClassic() [3/3]	216
11.13.1.4 DotProdBoundClassic()	216
11.13.1.5 TRSMBound() [1/3]	217
11.13.1.6 TRSMBound() [2/3]	217
11.13.1.7 TRSMBound() [3/3]	217
11.13.1.8 fgemm_convert()	218
11.13.1.9 NeedPreAddReduction() [1/2]	218
11.13.1.10 NeedPreAddReduction() [2/2]	218
11.13.1.11 NeedPreSubReduction() [1/2]	218
11.13.1.12 NeedPreSubReduction() [2/2]	219
11.13.1.13 NeedDoublePreAddReduction() [1/2]	219
11.13.1.14 NeedDoublePreAddReduction() [2/2]	219
11.13.1.15 ScalAndReduce() [1/3]	219
11.13.1.16 ScalAndReduce() [2/3]	220
11.13.1.17 fsquareCommon()	220
11.13.1.18 WinogradThreshold() [1/4]	220
11.13.1.19 WinogradThreshold() [2/4]	220
11.13.1.20 WinogradThreshold() [3/4]	220

11.13.1.21 WinogradThreshold() [4/4]	221
11.13.1.22 WinogradSteps()	221
11.13.1.23 DynamicPeeling()	221
11.13.1.24 DynamicPeeling2()	221
11.13.1.25 WinogradCalc()	222
11.13.1.26 fgemv_convert()	222
11.13.1.27 fger_convert()	223
11.13.1.28 fsyrk_convert()	223
11.13.1.29 ScalAndReduce() [3/3]	223
11.13.1.30 NeedPreScalReduction() [1/2]	224
11.13.1.31 NeedPreScalReduction() [2/2]	224
11.13.1.32 NeedPreAxyReduction() [1/2]	224
11.13.1.33 NeedPreAxyReduction() [2/2]	224
11.13.1.34 min_types() [1/7]	224
11.13.1.35 min_types() [2/7]	225
11.13.1.36 min_types() [3/7]	225
11.13.1.37 min_types() [4/7]	225
11.13.1.38 min_types() [5/7]	225
11.13.1.39 min_types() [6/7]	225
11.13.1.40 min_types() [7/7]	225
11.13.1.41 unfit() [1/4]	225
11.13.1.42 unfit() [2/4]	225
11.13.1.43 unfit() [3/4]	226
11.13.1.44 unfit() [4/4]	226
11.13.1.45 igemm_colmajor() [1/2]	226
11.13.1.46 igemm_colmajor() [2/2]	226
11.13.1.47 igemm()	226
11.13.1.48 MatF2MatD_Triangular()	227
11.13.1.49 MatF2MatFI_Triangular()	227
11.14 FFLAS::sell_details Namespace Reference	227
11.15 FFLAS::sparse_details Namespace Reference	228
11.15.1 Function Documentation	231
11.15.1.1 init_y() [1/2]	231
11.15.1.2 init_y() [2/2]	231
11.15.1.3 fspmv_dispatch() [1/2]	231
11.15.1.4 fspmv_dispatch() [2/2]	231
11.15.1.5 fspmv() [1/12]	232
11.15.1.6 fspmv() [2/12]	232
11.15.1.7 fspmv() [3/12]	232
11.15.1.8 fspmv() [4/12]	232
11.15.1.9 fspmv() [5/12]	232
11.15.1.10 fspmv() [6/12]	233

11.15.1.11 fspmv()	[7/12]	233
11.15.1.12 fspmv()	[8/12]	233
11.15.1.13 fspmv()	[9/12]	233
11.15.1.14 fspmm_dispatch()	[1/2]	234
11.15.1.15 fspmm_dispatch()	[2/2]	234
11.15.1.16 fspmm()	[1/9]	234
11.15.1.17 fspmm()	[2/9]	234
11.15.1.18 fspmm()	[3/9]	235
11.15.1.19 fspmm()	[4/9]	235
11.15.1.20 fspmm()	[5/9]	235
11.15.1.21 fspmm()	[6/9]	236
11.15.1.22 fspmm()	[7/9]	236
11.15.1.23 fspmm()	[8/9]	236
11.15.1.24 fspmm()	[9/9]	236
11.15.1.25 pfspmm_dispatch()	[1/2]	237
11.15.1.26 pfspmm_dispatch()	[2/2]	237
11.15.1.27 pfspmm()	[1/9]	237
11.15.1.28 pfspmm()	[2/9]	237
11.15.1.29 pfspmm()	[3/9]	238
11.15.1.30 pfspmm()	[4/9]	238
11.15.1.31 pfspmm()	[5/9]	238
11.15.1.32 pfspmm()	[6/9]	239
11.15.1.33 pfspmm()	[7/9]	239
11.15.1.34 pfspmm()	[8/9]	239
11.15.1.35 pfspmm()	[9/9]	239
11.15.1.36 pfspmv()	[1/6]	240
11.15.1.37 pfspmv()	[2/6]	240
11.15.1.38 pfspmv()	[3/6]	240
11.15.1.39 pfspmv()	[4/6]	240
11.15.1.40 pfspmv()	[5/6]	240
11.15.1.41 pfspmv()	[6/6]	241
11.15.1.42 fspmv()	[10/12]	241
11.15.1.43 fspmv()	[11/12]	241
11.15.1.44 fspmv()	[12/12]	241
11.16 FFLAS::sparse_details_impl Namespace Reference		242
11.16.1 Function Documentation		250
11.16.1.1 fspmm()	[1/15]	250
11.16.1.2 fspmm()	[2/15]	250
11.16.1.3 fspmm()	[3/15]	251
11.16.1.4 fspmm_simd_aligned()	[1/2]	251
11.16.1.5 fspmm_simd_unaligned()	[1/2]	251
11.16.1.6 fspmm_one()	[1/4]	251

11.16.1.7 fspmm_mone() [1/4]	252
11.16.1.8 fspmm_one_simd_aligned() [1/3]	252
11.16.1.9 fspmm_one_simd_unaligned() [1/3]	252
11.16.1.10 fspmm_mone_simd_aligned() [1/3]	252
11.16.1.11 fspmm_mone_simd_unaligned() [1/3]	253
11.16.1.12 fspmv() [1/21]	253
11.16.1.13 fspmv() [2/21]	253
11.16.1.14 fspmv() [3/21]	253
11.16.1.15 fspmv_one() [1/10]	253
11.16.1.16 fspmv_mone() [1/10]	254
11.16.1.17 fspmv_one() [2/10]	254
11.16.1.18 fspmv_mone() [2/10]	254
11.16.1.19 pfspmm() [1/18]	254
11.16.1.20 pfspmm() [2/18]	254
11.16.1.21 pfspmm() [3/18]	255
11.16.1.22 pfspmm_one() [1/2]	255
11.16.1.23 pfspmm_mone() [1/2]	255
11.16.1.24 pfspmm_one() [2/2]	255
11.16.1.25 pfspmm_mone() [2/2]	256
11.16.1.26 pfspmv() [1/18]	256
11.16.1.27 pfspmv_task()	256
11.16.1.28 pfspmv() [2/18]	256
11.16.1.29 pfspmv() [3/18]	256
11.16.1.30 pfspmv_one() [1/8]	257
11.16.1.31 pfspmv_mone() [1/8]	257
11.16.1.32 pfspmv_one() [2/8]	257
11.16.1.33 pfspmv_mone() [2/8]	257
11.16.1.34 fspmm() [4/15]	257
11.16.1.35 fspmm() [5/15]	258
11.16.1.36 fspmm_simd_aligned() [2/2]	258
11.16.1.37 fspmm_simd_unaligned() [2/2]	258
11.16.1.38 fspmm() [6/15]	258
11.16.1.39 fspmm_one() [2/4]	259
11.16.1.40 fspmm_mone() [2/4]	259
11.16.1.41 fspmm_one_simd_aligned() [2/3]	259
11.16.1.42 fspmm_one_simd_unaligned() [2/3]	259
11.16.1.43 fspmm_mone_simd_aligned() [2/3]	260
11.16.1.44 fspmm_mone_simd_unaligned() [2/3]	260
11.16.1.45 fspmv() [4/21]	260
11.16.1.46 fspmv() [5/21]	260
11.16.1.47 fspmv() [6/21]	260
11.16.1.48 fspmv_one() [3/10]	261

11.16.1.49 fspmv_mone()	[3/10]	261
11.16.1.50 fspmv_one()	[4/10]	261
11.16.1.51 fspmv_mone()	[4/10]	261
11.16.1.52 pfsppmm()	[4/18]	261
11.16.1.53 pfsppmm()	[5/18]	262
11.16.1.54 pfsppmm()	[6/18]	262
11.16.1.55 pfsppmm()	[7/18]	262
11.16.1.56 pfsppmm()	[8/18]	262
11.16.1.57 pfsppmm()	[9/18]	263
11.16.1.58 pfsppmv()	[4/18]	263
11.16.1.59 pfsppmv()	[5/18]	263
11.16.1.60 pfsppmv()	[6/18]	263
11.16.1.61 fspmm()	[7/15]	263
11.16.1.62 fspmm()	[8/15]	264
11.16.1.63 fspmm()	[9/15]	264
11.16.1.64 fspmv()	[7/21]	264
11.16.1.65 fspmv()	[8/21]	264
11.16.1.66 fspmv()	[9/21]	264
11.16.1.67 pfsppmm()	[10/18]	265
11.16.1.68 pfsppmm()	[11/18]	265
11.16.1.69 pfsppmm()	[12/18]	265
11.16.1.70 pfsppmm()	[13/18]	265
11.16.1.71 pfsppmm()	[14/18]	266
11.16.1.72 pfsppmm()	[15/18]	266
11.16.1.73 pfsppmm_zo()	[1/2]	266
11.16.1.74 pfsppmm_zo()	[2/2]	266
11.16.1.75 pfsppmv()	[7/18]	267
11.16.1.76 pfsppmv()	[8/18]	267
11.16.1.77 pfsppmv()	[9/18]	267
11.16.1.78 pfsppmv_one()	[3/8]	267
11.16.1.79 pfsppmv_mone()	[3/8]	267
11.16.1.80 pfsppmv_one()	[4/8]	268
11.16.1.81 pfsppmv_mone()	[4/8]	268
11.16.1.82 fspmm()	[10/15]	268
11.16.1.83 fspmm()	[11/15]	268
11.16.1.84 fspmm()	[12/15]	269
11.16.1.85 fspmm_mone()	[3/4]	269
11.16.1.86 fspmm_one()	[3/4]	269
11.16.1.87 fspmm_mone()	[4/4]	269
11.16.1.88 fspmm_one()	[4/4]	270
11.16.1.89 fspmm_one_simd_aligned()	[3/3]	270
11.16.1.90 fspmm_one_simd_unaligned()	[3/3]	270

11.16.1.91 fspmm_mone_simd_aligned() [3/3]	270
11.16.1.92 fspmm_mone_simd_unaligned() [3/3]	271
11.16.1.93 fspmv() [10/21]	271
11.16.1.94 fspmv() [11/21]	271
11.16.1.95 fspmv() [12/21]	271
11.16.1.96 fspmv_one() [5/10]	271
11.16.1.97 fspmv_mone() [5/10]	272
11.16.1.98 fspmv_one() [6/10]	272
11.16.1.99 fspmv_mone() [6/10]	272
11.16.1.100 pfspmv() [10/18]	272
11.16.1.101 pfspmv() [11/18]	272
11.16.1.102 pfspmv() [12/18]	273
11.16.1.103 pfspmv_one() [5/8]	273
11.16.1.104 pfspmv_mone() [5/8]	273
11.16.1.105 pfspmv_one() [6/8]	273
11.16.1.106 pfspmv_mone() [6/8]	273
11.16.1.107 fspmv() [13/21]	274
11.16.1.108 fspmv_simd() [1/4]	274
11.16.1.109 fspmv() [14/21]	274
11.16.1.110 fspmv_simd() [2/4]	274
11.16.1.111 fspmv() [15/21]	274
11.16.1.112 fspmv_one() [7/10]	275
11.16.1.113 fspmv_mone() [7/10]	275
11.16.1.114 fspmv_one() [8/10]	275
11.16.1.115 fspmv_mone() [8/10]	275
11.16.1.116 fspmv_one_simd() [1/2]	275
11.16.1.117 fspmv_mone_simd() [1/2]	276
11.16.1.118 pfspm() [16/18]	276
11.16.1.119 pfspm() [17/18]	276
11.16.1.120 pfspm() [18/18]	276
11.16.1.121 pfspmv() [13/18]	277
11.16.1.122 pfspmv() [14/18]	277
11.16.1.123 pfspmv() [15/18]	277
11.16.1.124 fspmm() [13/15]	277
11.16.1.125 fspmm() [14/15]	277
11.16.1.126 fspmm() [15/15]	278
11.16.1.127 fspmv() [16/21]	278
11.16.1.128 fspmv() [17/21]	278
11.16.1.129 fspmv() [18/21]	278
11.16.1.130 pfspmv() [16/18]	278
11.16.1.131 pfspmv() [17/18]	279
11.16.1.132 pfspmv() [18/18]	279

11.16.1.133 pfspmv_one() [7/8]	279
11.16.1.134 pfspmv_mone() [7/8]	279
11.16.1.135 pfspmv_one() [8/8]	279
11.16.1.136 pfspmv_mone() [8/8]	280
11.16.1.137 fspmv() [19/21]	280
11.16.1.138 fspmv_simd() [3/4]	280
11.16.1.139 fspmv() [20/21]	280
11.16.1.140 fspmv_simd() [4/4]	280
11.16.1.141 fspmv() [21/21]	281
11.16.1.142 fspmv_one() [9/10]	281
11.16.1.143 fspmv_mone() [9/10]	281
11.16.1.144 fspmv_one_simd() [2/2]	281
11.16.1.145 fspmv_mone_simd() [2/2]	281
11.16.1.146 fspmv_one() [10/10]	282
11.16.1.147 fspmv_mone() [10/10]	282
11.17 FFLAS::StrategyParameter Namespace Reference	282
11.18 FFLAS::StructureHelper Namespace Reference	282
11.18.1 Detailed Description	282
11.19 FFLAS::vectorised Namespace Reference	283
11.19.1 Function Documentation	284
11.19.1.1 VEC_ADD()	284
11.19.1.2 addp()	284
11.19.1.3 VEC_SUB()	285
11.19.1.4 subp()	285
11.19.1.5 add()	285
11.19.1.6 sub()	285
11.19.1.7 axpyp() [1/2]	285
11.19.1.8 axpyp() [2/2]	286
11.19.1.9 reduce() [1/9]	286
11.19.1.10 reduce() [2/9]	286
11.19.1.11 reduce() [3/9]	286
11.19.1.12 reduce() [4/9]	286
11.19.1.13 reduce() [5/9]	286
11.19.1.14 reduce() [6/9]	287
11.19.1.15 reduce() [7/9]	287
11.19.1.16 reduce() [8/9]	287
11.19.1.17 reduce() [9/9]	287
11.19.1.18 modp() [1/2]	287
11.19.1.19 modp() [2/2]	287
11.19.1.20 scalp() [1/3]	288
11.19.1.21 scalp() [2/3]	288
11.19.1.22 scalp() [3/3]	288

11.20 FFLAS::vectorised::unswitch Namespace Reference	288
11.20.1 Function Documentation	289
11.20.1.1 axpyp() [1/2]	289
11.20.1.2 axpyp() [2/2]	289
11.20.1.3 modp() [1/2]	290
11.20.1.4 modp() [2/2]	290
11.20.1.5 scalp() [1/3]	290
11.20.1.6 scalp() [2/3]	290
11.20.1.7 scalp() [3/3]	291
11.21 FFPACK Namespace Reference	291
11.21.1 Detailed Description	307
11.21.2 Typedef Documentation	307
11.21.2.1 Checker_PLUQ	307
11.21.2.2 Checker_Det	308
11.21.2.3 Checker_invert	308
11.21.2.4 Checker_charpoly	308
11.21.2.5 ForceCheck_PLUQ	308
11.21.2.6 ForceCheck_Det	308
11.21.2.7 ForceCheck_invert	308
11.21.2.8 ForceCheck_charpoly	308
11.21.3 Function Documentation	308
11.21.3.1 LAPACKPerm2MathPerm()	308
11.21.3.2 MathPerm2LAPACKPerm()	309
11.21.3.3 applyP() [1/4]	309
11.21.3.4 applyP() [2/4]	310
11.21.3.5 applyP() [3/4]	310
11.21.3.6 MonotonicApplyP()	310
11.21.3.7 fgetrs() [1/4]	311
11.21.3.8 fgetrs() [2/4]	312
11.21.3.9 fgesv() [1/4]	313
11.21.3.10 fgesv() [2/4]	313
11.21.3.11 ftrtri() [1/2]	314
11.21.3.12 trinv_left() [1/2]	314
11.21.3.13 ftrtrm() [1/2]	315
11.21.3.14 ftrstr()	315
11.21.3.15 ftrssyr2k()	316
11.21.3.16 fsytrf() [1/3]	316
11.21.3.17 fsytrf() [2/3]	317
11.21.3.18 fsytrf() [3/3]	317
11.21.3.19 fsytrf_nonunit() [1/3]	318
11.21.3.20 PLUQ() [1/6]	318
11.21.3.21 pPLUQ()	319

11.21.3.22 PLUQ()	[2/6]	319
11.21.3.23 PLUQ()	[3/6]	320
11.21.3.24 LUdivine()	[1/4]	320
11.21.3.25 ColumnEchelonForm()	[1/3]	321
11.21.3.26 pColumnEchelonForm()		321
11.21.3.27 ColumnEchelonForm()	[2/3]	322
11.21.3.28 RowEchelonForm()	[1/3]	322
11.21.3.29 pRowEchelonForm()		322
11.21.3.30 RowEchelonForm()	[2/3]	323
11.21.3.31 ReducedColumnEchelonForm()	[1/3]	323
11.21.3.32 pReducedColumnEchelonForm()		324
11.21.3.33 ReducedColumnEchelonForm()	[2/3]	324
11.21.3.34 ReducedRowEchelonForm()	[1/3]	324
11.21.3.35 pReducedRowEchelonForm()		325
11.21.3.36 ReducedRowEchelonForm()	[2/3]	325
11.21.3.37 Invert()	[1/4]	325
11.21.3.38 Invert()	[2/4]	326
11.21.3.39 Invert2()	[1/2]	326
11.21.3.40 CharPoly()	[1/8]	327
11.21.3.41 CharPoly()	[2/8]	328
11.21.3.42 CharPoly()	[3/8]	328
11.21.3.43 MinPoly()	[1/4]	329
11.21.3.44 MinPoly()	[2/4]	329
11.21.3.45 MatVecMinPoly()	[1/2]	330
11.21.3.46 Rank()	[1/3]	330
11.21.3.47 pRank()		331
11.21.3.48 Rank()	[2/3]	331
11.21.3.49 IsSingular()	[1/2]	331
11.21.3.50 Det()	[1/6]	332
11.21.3.51 pDet()		332
11.21.3.52 Det()	[2/6]	333
11.21.3.53 Solve()	[1/3]	333
11.21.3.54 Solve()	[2/3]	333
11.21.3.55 pSolve()		334
11.21.3.56 RandomNullSpaceVector()	[1/3]	334
11.21.3.57 NullSpaceBasis()	[1/2]	335
11.21.3.58 RowRankProfile()	[1/3]	335
11.21.3.59 pRowRankProfile()		336
11.21.3.60 RowRankProfile()	[2/3]	336
11.21.3.61 ColumnRankProfile()	[1/3]	336
11.21.3.62 pColumnRankProfile()		337
11.21.3.63 ColumnRankProfile()	[2/3]	337

11.21.3.64 RankProfileFromLU()	337
11.21.3.65 LeadingSubmatrixRankProfiles()	338
11.21.3.66 RowRankProfileSubmatrixIndices() [1/2]	338
11.21.3.67 ColRankProfileSubmatrixIndices() [1/2]	339
11.21.3.68 RowRankProfileSubmatrix() [1/2]	340
11.21.3.69 ColRankProfileSubmatrix() [1/2]	340
11.21.3.70 getTriangular() [1/2]	341
11.21.3.71 getTriangular() [2/2]	342
11.21.3.72 getEchelonForm() [1/2]	342
11.21.3.73 getEchelonForm() [2/2]	343
11.21.3.74 getEchelonTransform()	344
11.21.3.75 getReducedEchelonForm() [1/2]	345
11.21.3.76 getReducedEchelonForm() [2/2]	345
11.21.3.77 getReducedEchelonTransform()	346
11.21.3.78 PLUQtoEchelonPermutation()	347
11.21.3.79 LTBruhatGen()	347
11.21.3.80 getLTBruhatGen() [1/2]	347
11.21.3.81 getLTBruhatGen() [2/2]	348
11.21.3.82 LTQSorder()	349
11.21.3.83 CompressToBlockBiDiagonal()	349
11.21.3.84 ExpandBlockBiDiagonalToBruhat()	350
11.21.3.85 Bruhat2EchelonPermutation()	350
11.21.3.86 TInverter() [1/2]	351
11.21.3.87 ComputeRPermutation() [1/2]	351
11.21.3.88 productBruhatxTS() [1/2]	351
11.21.3.89 LQUPtoInverseOfFullRankMinor() [1/2]	352
11.21.3.90 RandomNullSpaceVector() [2/3]	352
11.21.3.91 solveLB() [1/2]	353
11.21.3.92 solveLB2() [1/2]	353
11.21.3.93 TInverter() [2/2]	354
11.21.3.94 ComputeRPermutation() [2/2]	354
11.21.3.95 expandLCRE()	354
11.21.3.96 productBruhatxTS() [2/2]	354
11.21.3.97 Danilevski()	356
11.21.3.98 buildMatrix()	356
11.21.3.99 CharPoly() [4/8]	356
11.21.3.100 CharPoly() [5/8]	356
11.21.3.101 Det() [3/6]	357
11.21.3.102 Det() [4/6]	357
11.21.3.103 fsytrf_BC_Crout()	357
11.21.3.104 fsytrf_BC_RL()	357
11.21.3.105 fsytrf_UP_RPM_BC_RL()	358

11.21.3.106 fsytrf_LOW_RPM_BC_Crout()	358
11.21.3.107 fsytrf_UP_RPM_BC_Crout()	358
11.21.3.108 fsytrf_UP_RPM()	358
11.21.3.109 fsytrf_nonunit() [2/3]	359
11.21.3.110 fsytrf_nonunit() [3/3]	359
11.21.3.111 fsytrf_RPM()	359
11.21.3.112 getTridiagonal()	359
11.21.3.113 LUdivine_gauss() [1/2]	360
11.21.3.114 LUdivine_small() [1/2]	360
11.21.3.115 LUdivine() [2/4]	360
11.21.3.116 LUdivine() [3/4]	361
11.21.3.117 MonotonicCompress()	361
11.21.3.118 MonotonicCompressMorePivots()	361
11.21.3.119 MonotonicCompressCycles()	361
11.21.3.120 MonotonicExpand()	362
11.21.3.121 applyP_block()	362
11.21.3.122 doApplyS()	362
11.21.3.123 MatrixApplyS() [1/3]	363
11.21.3.124 MatrixApplyS() [2/3]	363
11.21.3.125 MatrixApplyS() [3/3]	363
11.21.3.126 PermApplyS()	363
11.21.3.127 doApplyT()	364
11.21.3.128 MatrixApplyT() [1/3]	364
11.21.3.129 MatrixApplyT() [2/3]	364
11.21.3.130 MatrixApplyT() [3/3]	364
11.21.3.131 PermApplyT()	365
11.21.3.132 composePermutationsLLL()	365
11.21.3.133 composePermutationsLLM()	365
11.21.3.134 composePermutationsMLM()	366
11.21.3.135 cyclic_shift_mathPerm()	366
11.21.3.136 cyclic_shift_row_col() [1/2]	366
11.21.3.137 cyclic_shift_row() [1/3]	366
11.21.3.138 cyclic_shift_row() [2/3]	367
11.21.3.139 cyclic_shift_col() [1/3]	367
11.21.3.140 cyclic_shift_col() [2/3]	367
11.21.3.141 PLUQ_basecaseV3()	367
11.21.3.142 PLUQ_basecaseV2()	367
11.21.3.143 PLUQ_basecaseCrout()	368
11.21.3.144 _PLUQ()	368
11.21.3.145 PLUQ() [4/6]	368
11.21.3.146 threads_fgemm()	368
11.21.3.147 threads_ftrsm()	369

11.21.3.148 PLUQ() [5/6]	369
11.21.3.149 fflas_const_cast() [1/3]	369
11.21.3.150 fflas_const_cast() [2/3]	369
11.21.3.151 cyclic_shift_row_col() [2/2]	369
11.21.3.152 cyclic_shift_row() [3/3]	370
11.21.3.153 cyclic_shift_col() [3/3]	370
11.21.3.154 applyP() [4/4]	370
11.21.3.155 fgetrs() [3/4]	370
11.21.3.156 fgetrs() [4/4]	371
11.21.3.157 fgesv() [3/4]	371
11.21.3.158 fgesv() [4/4]	371
11.21.3.159 ftrtri() [2/2]	371
11.21.3.160 trinv_left() [2/2]	372
11.21.3.161 ftrtrm() [2/2]	372
11.21.3.162 PLUQ() [6/6]	372
11.21.3.163 LUdivine() [4/4]	372
11.21.3.164 LUdivine_small() [2/2]	373
11.21.3.165 LUdivine_gauss() [2/2]	373
11.21.3.166 RowEchelonForm() [3/3]	373
11.21.3.167 ReducedRowEchelonForm() [3/3]	373
11.21.3.168 ColumnEchelonForm() [3/3]	374
11.21.3.169 ReducedColumnEchelonForm() [3/3]	374
11.21.3.170 Invert() [3/4]	374
11.21.3.171 Invert() [4/4]	374
11.21.3.172 Invert2() [2/2]	374
11.21.3.173 CharPoly() [6/8]	375
11.21.3.174 CharPoly() [7/8]	375
11.21.3.175 CharPoly() [8/8]	375
11.21.3.176 MinPoly() [3/4]	375
11.21.3.177 MinPoly() [4/4]	375
11.21.3.178 MatVecMinPoly() [2/2]	376
11.21.3.179 KrylovElim()	376
11.21.3.180 SpecRankProfile()	376
11.21.3.181 Rank() [3/3]	376
11.21.3.182 IsSingular() [2/2]	376
11.21.3.183 Det() [5/6]	377
11.21.3.184 Det() [6/6]	377
11.21.3.185 Solve() [3/3]	377
11.21.3.186 solveLB() [2/2]	377
11.21.3.187 solveLB2() [2/2]	378
11.21.3.188 RandomNullSpaceVector() [3/3]	378
11.21.3.189 NullSpaceBasis() [2/2]	378

11.21.3.190 RowRankProfile()	[3/3]	378
11.21.3.191 ColumnRankProfile()	[3/3]	379
11.21.3.192 RowRankProfileSubmatrixIndices()	[2/2]	379
11.21.3.193 ColRankProfileSubmatrixIndices()	[2/2]	379
11.21.3.194 RowRankProfileSubmatrix()	[2/2]	379
11.21.3.195 ColRankProfileSubmatrix()	[2/2]	379
11.21.3.196 getTriangular< FFLAS_FIELD< FFLAS_ELT > >()	[1/2]	380
11.21.3.197 getTriangular< FFLAS_FIELD< FFLAS_ELT > >()	[2/2]	380
11.21.3.198 getEchelonForm< FFLAS_FIELD< FFLAS_ELT > >()	[1/2]	380
11.21.3.199 getEchelonForm< FFLAS_FIELD< FFLAS_ELT > >()	[2/2]	380
11.21.3.200 getEchelonTransform< FFLAS_FIELD< FFLAS_ELT > >()		381
11.21.3.201 getReducedEchelonForm< FFLAS_FIELD< FFLAS_ELT > >()	[1/2]	381
11.21.3.202 getReducedEchelonForm< FFLAS_FIELD< FFLAS_ELT > >()	[2/2]	381
11.21.3.203 getReducedEchelonTransform< FFLAS_FIELD< FFLAS_ELT > >()		381
11.21.3.204 LQUPtoInverseOfFullRankMinor()	[2/2]	382
11.21.3.205 fflas_const_cast()	[3/3]	382
11.21.3.206 failure()		382
11.21.3.207 isOdd()	[1/3]	382
11.21.3.208 isOdd()	[2/3]	382
11.21.3.209 isOdd()	[3/3]	382
11.21.3.210 NonZeroRandomMatrix()	[1/2]	383
11.21.3.211 NonZeroRandomMatrix()	[2/2]	383
11.21.3.212 RandomMatrix()	[1/2]	384
11.21.3.213 RandomMatrix()	[2/2]	384
11.21.3.214 RandomTriangularMatrix()	[1/2]	385
11.21.3.215 RandomTriangularMatrix()	[2/2]	385
11.21.3.216 RandInt()		386
11.21.3.217 RandomSymmetricMatrix()		386
11.21.3.218 RandomMatrixWithRank()	[1/2]	387
11.21.3.219 RandomMatrixWithRank()	[2/2]	387
11.21.3.220 RandomIndexSubset()		388
11.21.3.221 RandomPermutation()		388
11.21.3.222 RandomRankProfileMatrix()		388
11.21.3.223 swapval()		389
11.21.3.224 RandomSymmetricRankProfileMatrix()		389
11.21.3.225 RandomLTQSRankProfileMatrix()		389
11.21.3.226 RandomMatrixWithRankandRPM()	[1/2]	389
11.21.3.227 RandomMatrixWithRankandRPM()	[2/2]	390
11.21.3.228 RandomSymmetricMatrixWithRankandRPM()	[1/2]	390
11.21.3.229 RandomSymmetricMatrixWithRankandRPM()	[2/2]	391
11.21.3.230 RandomMatrixWithRankandRandomRPM()	[1/2]	392
11.21.3.231 RandomMatrixWithRankandRandomRPM()	[2/2]	392

11.21.3.232 RandomSymmetricMatrixWithRankandRandomRPM() [1/2]	393
11.21.3.233 RandomSymmetricMatrixWithRankandRandomRPM() [2/2]	393
11.21.3.234 RandomMatrixWithDet() [1/2]	394
11.21.3.235 RandomMatrixWithDet() [2/2]	394
11.21.3.236 RandomLTQSMMatrixWithRankandQSorder()	395
11.21.3.237 chooseField()	395
11.21.3.238 chooseField< Givaro::ZRing< int32_t > >()	395
11.21.3.239 chooseField< Givaro::ZRing< int64_t > >()	395
11.21.3.240 chooseField< Givaro::ZRing< float > >()	395
11.21.3.241 chooseField< Givaro::ZRing< double > >()	396
11.22 FFPACK::Protected Namespace Reference	396
11.22.1 Function Documentation	397
11.22.1.1 LUdivine_construct() [1/2]	397
11.22.1.2 GaussJordan()	398
11.22.1.3 KellerGehrig()	398
11.22.1.4 KGFast()	399
11.22.1.5 KGFast_generalized()	399
11.22.1.6 fgemv_kgf()	399
11.22.1.7 LUKrylov()	399
11.22.1.8 Danilevski()	399
11.22.1.9 RandomKrylovPrecond()	400
11.22.1.10 ArithProg()	400
11.22.1.11 LUKrylov_KGFast()	400
11.22.1.12 MatVecMinPoly()	400
11.22.1.13 Hybrid_KGF_LUK_MinPoly()	401
11.22.1.14 updateD()	401
11.22.1.15 newD()	401
11.22.1.16 CompressRows()	401
11.22.1.17 CompressRowsQK()	402
11.22.1.18 DeCompressRows()	402
11.22.1.19 DeCompressRowsQK()	402
11.22.1.20 CompressRowsQA()	402
11.22.1.21 DeCompressRowsQA()	403
11.22.1.22 LUdivine_construct() [2/2]	403
11.23 Givaro Namespace Reference	403
11.24 MKL_CONFIG Namespace Reference	403
11.25 Reclnt Namespace Reference	403
12 Data Structure Documentation	405
12.1 AlgoChooser< ModeT, ParSeq > Struct Template Reference	405
12.1.1 Member Typedef Documentation	405
12.1.1.1 value	405

12.2 AlgoChooser< ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeq > Struct Template Reference	405
12.2.1 Member Typedef Documentation	405
12.2.1.1 value	405
12.3 ALL< v > Struct Template Reference	405
12.4 ALL< false, v... > Struct Template Reference	406
12.4.1 Field Documentation	406
12.4.1.1 value	406
12.5 ALL< true, v... > Struct Template Reference	406
12.5.1 Field Documentation	406
12.5.1.1 value	406
12.6 ALL<> Struct Reference	406
12.6.1 Field Documentation	406
12.6.1.1 value	406
12.7 ArbitraryPrecIntTag Struct Reference	406
12.7.1 Detailed Description	406
12.8 AreEqual< X, Y > Class Template Reference	407
12.8.1 Field Documentation	407
12.8.1.1 value	407
12.9 AreEqual< X, X > Class Template Reference	407
12.9.1 Field Documentation	407
12.9.1.1 value	407
12.10 Argument Struct Reference	407
12.10.1 Field Documentation	407
12.10.1.1 c	407
12.10.1.2 example	407
12.10.1.3 helpString	408
12.10.1.4 type	408
12.10.1.5 data	408
12.11 associatedDelayedField< Field > Struct Template Reference	408
12.11.1 Member Typedef Documentation	408
12.11.1.1 field	408
12.11.1.2 type	408
12.12 associatedDelayedField< const FFPACK::RNSIntegerMod< RNS > > Struct Template Reference	408
12.12.1 Member Typedef Documentation	408
12.12.1.1 field	408
12.12.1.2 type	409
12.13 associatedDelayedField< const Givaro::Modular< T, X > > Struct Template Reference	409
12.13.1 Member Typedef Documentation	409
12.13.1.1 field	409
12.13.1.2 type	409
12.14 associatedDelayedField< const Givaro::ModularBalanced< T > > Struct Template Reference	409

12.14.1 Member Typedef Documentation	409
12.14.1.1 field	409
12.14.1.2 type	409
12.15 associatedDelayedField< const Givaro::ZRing< T > > Struct Template Reference	410
12.15.1 Member Typedef Documentation	410
12.15.1.1 field	410
12.15.1.2 type	410
12.16 Auto Struct Reference	410
12.17 Bench< Elt > Class Template Reference	410
12.17.1 Member Typedef Documentation	411
12.17.1.1 Field	411
12.17.1.2 Elt_ptr	411
12.17.1.3 Residu	411
12.17.1.4 enable_if_t	411
12.17.1.5 is_same_element	411
12.17.1.6 enable_if_no_simd_t	411
12.17.1.7 enable_if_simd128_t	411
12.17.1.8 enable_if_simd256_t	411
12.17.1.9 enable_if_simd512_t	412
12.17.2 Constructor & Destructor Documentation	412
12.17.2.1 Bench()	412
12.17.3 Member Function Documentation	412
12.17.3.1 cardinality() [1/2]	412
12.17.3.2 cardinality() [2/2]	412
12.17.3.3 doBenches()	412
12.17.3.4 run()	412
12.17.4 Field Documentation	412
12.17.4.1 F	412
12.17.4.2 m	412
12.17.4.3 n	413
12.17.4.4 iters	413
12.17.4.5 inplace	413
12.18 Bini Struct Reference	413
12.19 Block Struct Reference	413
12.20 BlockTransposeSIMD< Field, Simd, > Struct Template Reference	413
12.20.1 Member Function Documentation	413
12.20.1.1 size()	413
12.20.1.2 info()	414
12.20.1.3 transpose() [1/5]	414
12.20.1.4 transpose() [2/5]	414
12.20.1.5 transpose() [3/5]	414
12.20.1.6 transpose() [4/5]	414

12.20.1.7 transpose() [5/5]	414
12.21 callLUdivine_small< Element > Class Template Reference	415
12.21.1 Member Function Documentation	415
12.21.1.1 operator()()	415
12.22 callLUdivine_small< double > Class Reference	415
12.22.1 Member Function Documentation	415
12.22.1.1 operator()()	415
12.23 callLUdivine_small< float > Class Reference	416
12.23.1 Member Function Documentation	416
12.23.1.1 operator()()	416
12.24 CharpolyFailed Class Reference	416
12.25 Checker_Empty< Field > Struct Template Reference	416
12.25.1 Constructor & Destructor Documentation	417
12.25.1.1 Checker_Empty()	417
12.25.2 Member Function Documentation	417
12.25.2.1 check()	417
12.26 CheckerImplem_charpoly< Field, Polynomial > Class Template Reference	417
12.26.1 Constructor & Destructor Documentation	417
12.26.1.1 CheckerImplem_charpoly() [1/2]	417
12.26.1.2 CheckerImplem_charpoly() [2/2]	417
12.26.1.3 ~CheckerImplem_charpoly()	417
12.26.2 Member Function Documentation	418
12.26.2.1 check()	418
12.27 CheckerImplem_charpoly< Givaro::ZRing< Givaro::Integer >, Polynomial > Class Template Reference	418
12.27.1 Member Typedef Documentation	418
12.27.1.1 Ring	418
12.27.2 Constructor & Destructor Documentation	418
12.27.2.1 CheckerImplem_charpoly() [1/2]	418
12.27.2.2 CheckerImplem_charpoly() [2/2]	418
12.27.2.3 ~CheckerImplem_charpoly()	418
12.27.3 Member Function Documentation	419
12.27.3.1 check()	419
12.28 CheckerImplem_Det< Field > Class Template Reference	419
12.28.1 Constructor & Destructor Documentation	419
12.28.1.1 CheckerImplem_Det() [1/2]	419
12.28.1.2 CheckerImplem_Det() [2/2]	419
12.28.1.3 ~CheckerImplem_Det()	419
12.28.2 Member Function Documentation	419
12.28.2.1 check()	419
12.29 CheckerImplem_fgemm< Field > Class Template Reference	421
12.29.1 Constructor & Destructor Documentation	421

12.29.1.1 CheckerImplem_fgemm() [1/2]	421
12.29.1.2 CheckerImplem_fgemm() [2/2]	421
12.29.1.3 ~CheckerImplem_fgemm()	421
12.29.2 Member Function Documentation	422
12.29.2.1 check()	422
12.30 CheckerImplem_ftsm< Field > Class Template Reference	422
12.30.1 Constructor & Destructor Documentation	422
12.30.1.1 CheckerImplem_ftsm() [1/2]	422
12.30.1.2 CheckerImplem_ftsm() [2/2]	422
12.30.1.3 ~CheckerImplem_ftsm()	422
12.30.2 Member Function Documentation	423
12.30.2.1 check()	423
12.31 CheckerImplem_invert< Field > Class Template Reference	423
12.31.1 Constructor & Destructor Documentation	423
12.31.1.1 CheckerImplem_invert() [1/2]	423
12.31.1.2 CheckerImplem_invert() [2/2]	423
12.31.1.3 ~CheckerImplem_invert()	423
12.31.2 Member Function Documentation	423
12.31.2.1 check()	423
12.32 CheckerImplem_PLUQ< Field > Class Template Reference	424
12.32.1 Constructor & Destructor Documentation	424
12.32.1.1 CheckerImplem_PLUQ() [1/2]	424
12.32.1.2 CheckerImplem_PLUQ() [2/2]	424
12.32.1.3 ~CheckerImplem_PLUQ()	424
12.32.2 Member Function Documentation	424
12.32.2.1 check()	424
12.33 Classic Struct Reference	425
12.34 Column Struct Reference	425
12.35 CompactElement< Element > Struct Template Reference	425
12.35.1 Member Typedef Documentation	425
12.35.1.1 type	425
12.36 CompactElement< double > Struct Reference	425
12.36.1 Member Typedef Documentation	425
12.36.1.1 type	425
12.37 CompactElement< float > Struct Reference	426
12.37.1 Member Typedef Documentation	426
12.37.1.1 type	426
12.38 CompactElement< int16_t > Struct Reference	426
12.38.1 Member Typedef Documentation	426
12.38.1.1 type	426
12.39 CompactElement< int32_t > Struct Reference	426
12.39.1 Member Typedef Documentation	426

12.39.1.1 type	426
12.40 CompactElement< int64_t > Struct Reference	426
12.40.1 Member Typedef Documentation	426
12.40.1.1 type	426
12.41 compatible_data_type< Field > Struct Template Reference	427
12.41.1 Field Documentation	427
12.41.1.1 value	427
12.42 compatible_data_type< Givaro::ZRing< double > > Struct Reference	427
12.42.1 Field Documentation	427
12.42.1.1 value	427
12.43 compatible_data_type< Givaro::ZRing< float > > Struct Reference	427
12.43.1 Field Documentation	427
12.43.1.1 value	427
12.44 Compose< H1, H2 > Struct Template Reference	427
12.44.1 Constructor & Destructor Documentation	428
12.44.1.1 Compose() [1/5]	428
12.44.1.2 Compose() [2/5]	428
12.44.1.3 Compose() [3/5]	428
12.44.1.4 Compose() [4/5]	428
12.44.1.5 Compose() [5/5]	428
12.44.2 Member Function Documentation	428
12.44.2.1 first_component()	428
12.44.2.2 second_component()	428
12.44.3 Friends And Related Symbol Documentation	428
12.44.3.1 operator<<	428
12.45 Simd128_impl< true, true, false, 2 >::Converter Union Reference	429
12.45.1 Field Documentation	429
12.45.1.1 v	429
12.45.1.2 t	429
12.46 Simd128_impl< true, true, false, 4 >::Converter Union Reference	429
12.46.1 Field Documentation	429
12.46.1.1 v	429
12.46.1.2 t	429
12.47 Simd128_impl< true, true, false, 8 >::Converter Union Reference	429
12.47.1 Field Documentation	429
12.47.1.1 v	429
12.47.1.2 t	429
12.48 Simd128_impl< true, true, true, 2 >::Converter Union Reference	430
12.48.1 Field Documentation	430
12.48.1.1 v	430
12.48.1.2 t	430
12.49 Simd128_impl< true, true, true, 4 >::Converter Union Reference	430

12.49.1 Field Documentation	430
12.49.1.1 v	430
12.49.1.2 t	430
12.50 Simd128_impl< true, true, true, 8 >::Converter Union Reference	430
12.50.1 Field Documentation	430
12.50.1.1 v	430
12.50.1.2 t	430
12.51 Simd256_impl< true, false, true, 8 >::Converter Union Reference	431
12.51.1 Field Documentation	431
12.51.1.1 v	431
12.51.1.2 t	431
12.52 Simd256_impl< true, true, false, 2 >::Converter Union Reference	431
12.52.1 Field Documentation	431
12.52.1.1 v	431
12.52.1.2 t	431
12.53 Simd256_impl< true, true, false, 4 >::Converter Union Reference	431
12.53.1 Field Documentation	431
12.53.1.1 v	431
12.53.1.2 t	431
12.54 Simd256_impl< true, true, false, 8 >::Converter Union Reference	432
12.54.1 Field Documentation	432
12.54.1.1 v	432
12.54.1.2 t	432
12.55 Simd256_impl< true, true, true, 2 >::Converter Union Reference	432
12.55.1 Field Documentation	432
12.55.1.1 v	432
12.55.1.2 t	432
12.56 Simd256_impl< true, true, true, 4 >::Converter Union Reference	432
12.56.1 Field Documentation	432
12.56.1.1 v	432
12.56.1.2 t	432
12.57 Simd256_impl< true, true, true, 8 >::Converter Union Reference	433
12.57.1 Field Documentation	433
12.57.1.1 v	433
12.57.1.2 t	433
12.58 Simd512_impl< true, true, false, 8 >::Converter Union Reference	433
12.58.1 Field Documentation	433
12.58.1.1 v	433
12.58.1.2 t	433
12.59 Simd512_impl< true, true, true, 8 >::Converter Union Reference	433
12.59.1 Field Documentation	433
12.59.1.1 v	433

12.59.1.2 t	433
12.60 ConvertTo< T > Struct Template Reference	434
12.60.1 Detailed Description	434
12.61 Coo< ValT, IdxT > Struct Template Reference	434
12.61.1 Member Typedef Documentation	434
12.61.1.1 Self	434
12.61.2 Constructor & Destructor Documentation	434
12.61.2.1 Coo() [1/4]	434
12.61.2.2 Coo() [2/4]	435
12.61.2.3 Coo() [3/4]	435
12.61.2.4 Coo() [4/4]	435
12.61.3 Member Function Documentation	435
12.61.3.1 operator=() [1/2]	435
12.61.3.2 operator=() [2/2]	435
12.61.4 Field Documentation	435
12.61.4.1 val	435
12.61.4.2 row	435
12.61.4.3 col	435
12.62 Coo< Field > Struct Template Reference	435
12.62.1 Constructor & Destructor Documentation	436
12.62.1.1 Coo() [1/4]	436
12.62.1.2 Coo() [2/4]	436
12.62.1.3 Coo() [3/4]	436
12.62.1.4 Coo() [4/4]	436
12.62.2 Member Function Documentation	436
12.62.2.1 operator=() [1/2]	436
12.62.2.2 operator=() [2/2]	436
12.62.3 Field Documentation	436
12.62.3.1 val	436
12.62.3.2 col	437
12.62.3.3 row	437
12.62.3.4 deleted	437
12.63 Coo< ValT, IdxT > Struct Template Reference	437
12.63.1 Member Typedef Documentation	437
12.63.1.1 Self	437
12.63.2 Constructor & Destructor Documentation	437
12.63.2.1 Coo() [1/4]	437
12.63.2.2 Coo() [2/4]	437
12.63.2.3 Coo() [3/4]	438
12.63.2.4 Coo() [4/4]	438
12.63.3 Member Function Documentation	438
12.63.3.1 operator=() [1/2]	438

12.63.3.2 operator=() [2/2]	438
12.63.4 Field Documentation	438
12.63.4.1 val	438
12.63.4.2 row	438
12.63.4.3 col	438
12.64 CooMat< Field > Struct Template Reference	438
12.64.1 Field Documentation	439
12.64.1.1 _coo16	439
12.64.1.2 _coo32	439
12.64.1.3 _coo64	439
12.64.1.4 _coo16_zo	439
12.64.1.5 _coo32_zo	439
12.64.1.6 _coo64_zo	439
12.65 count_nonconst_lvalue_reference< T > Struct Template Reference	439
12.66 count_nonconst_lvalue_reference< const T &, O... > Struct Template Reference	439
12.66.1 Field Documentation	439
12.66.1.1 n	439
12.67 count_nonconst_lvalue_reference< T &, O... > Struct Template Reference	440
12.67.1 Field Documentation	440
12.67.1.1 n	440
12.68 count_nonconst_lvalue_reference< T, O... > Struct Template Reference	440
12.68.1 Field Documentation	440
12.68.1.1 n	440
12.69 count_nonconst_lvalue_reference<> Struct Reference	440
12.69.1 Field Documentation	440
12.69.1.1 n	440
12.70 CsrMat< Field > Struct Template Reference	440
12.70.1 Field Documentation	441
12.70.1.1 _csr16	441
12.70.1.2 _csr32	441
12.70.1.3 _csr64	441
12.70.1.4 _csr16_zo	441
12.70.1.5 _csr32_zo	441
12.70.1.6 _csr64_zo	441
12.71 DefaultBoundedTag Struct Reference	441
12.71.1 Detailed Description	441
12.72 DefaultTag Struct Reference	441
12.72.1 Detailed Description	442
12.73 DelayedTag Struct Reference	442
12.73.1 Detailed Description	442
12.74 DivideAndConquer Struct Reference	442
12.75 ElementTraits< Element > Struct Template Reference	442

12.75.1 Detailed Description	442
12.75.2 Member Typedef Documentation	442
12.75.2.1 value	442
12.76 ElementTraits< double > Struct Reference	442
12.76.1 Member Typedef Documentation	443
12.76.1.1 value	443
12.77 ElementTraits< FFPACK::rns_double_elt > Struct Reference	443
12.77.1 Member Typedef Documentation	443
12.77.1.1 value	443
12.78 ElementTraits< float > Struct Reference	443
12.78.1 Member Typedef Documentation	443
12.78.1.1 value	443
12.79 ElementTraits< Givaro::Integer > Struct Reference	443
12.79.1 Member Typedef Documentation	443
12.79.1.1 value	443
12.80 ElementTraits< int16_t > Struct Reference	444
12.80.1 Member Typedef Documentation	444
12.80.1.1 value	444
12.81 ElementTraits< int32_t > Struct Reference	444
12.81.1 Member Typedef Documentation	444
12.81.1.1 value	444
12.82 ElementTraits< int64_t > Struct Reference	444
12.82.1 Member Typedef Documentation	444
12.82.1.1 value	444
12.83 ElementTraits< int8_t > Struct Reference	444
12.83.1 Member Typedef Documentation	445
12.83.1.1 value	445
12.84 ElementTraits< RecInt::rint< K > > Struct Template Reference	445
12.84.1 Member Typedef Documentation	445
12.84.1.1 value	445
12.85 ElementTraits< RecInt::rmint< K, MG > > Struct Template Reference	445
12.85.1 Member Typedef Documentation	445
12.85.1.1 value	445
12.86 ElementTraits< RecInt::ruint< K > > Struct Template Reference	445
12.86.1 Member Typedef Documentation	446
12.86.1.1 value	446
12.87 ElementTraits< uint16_t > Struct Reference	446
12.87.1 Member Typedef Documentation	446
12.87.1.1 value	446
12.88 ElementTraits< uint32_t > Struct Reference	446
12.88.1 Member Typedef Documentation	446
12.88.1.1 value	446

12.89 ElementTraits< uint64_t > Struct Reference	446
12.89.1 Member Typedef Documentation	446
12.89.1.1 value	446
12.90 ElementTraits< uint8_t > Struct Reference	447
12.90.1 Member Typedef Documentation	447
12.90.1.1 value	447
12.91 EllMat< Field > Struct Template Reference	447
12.91.1 Field Documentation	447
12.91.1.1 _ell16	447
12.91.1.2 _ell32	447
12.91.1.3 _ell64	447
12.91.1.4 _ell16_zo	447
12.91.1.5 _ell32_zo	447
12.91.1.6 _ell64_zo	448
12.92 Failure Class Reference	448
12.92.1 Detailed Description	448
12.92.2 Constructor & Destructor Documentation	448
12.92.2.1 Failure()	448
12.92.3 Member Function Documentation	448
12.92.3.1 operator>() [1/2]	448
12.92.3.2 operator>() [2/2]	448
12.92.3.3 setErrorStream()	449
12.92.3.4 print()	449
12.92.4 Field Documentation	449
12.92.4.1 _errorStream	449
12.93 FailureCharpolyCheck Class Reference	449
12.94 FailureDetCheck Class Reference	449
12.95 FailureFgemmCheck Class Reference	449
12.96 FailureInvertCheck Class Reference	450
12.97 FailurePLUQCheck Class Reference	450
12.98 FailureTrsmCheck Class Reference	450
12.99 FieldSimd< _Field > Class Template Reference	450
12.99.1 Member Typedef Documentation	451
12.99.1.1 Field	451
12.99.1.2 Element	451
12.99.1.3 simd	451
12.99.1.4 vect_t	451
12.99.1.5 scalar_t	451
12.99.2 Constructor & Destructor Documentation	451
12.99.2.1 FieldSimd() [1/3]	451
12.99.2.2 FieldSimd() [2/3]	452
12.99.2.3 FieldSimd() [3/3]	452

12.99.3 Member Function Documentation	452
12.99.3.1 operator=() [1/2]	452
12.99.3.2 operator=() [2/2]	452
12.99.3.3 init() [1/2]	452
12.99.3.4 init() [2/2]	452
12.99.3.5 add() [1/2]	452
12.99.3.6 add() [2/2]	452
12.99.3.7 addin()	452
12.99.3.8 add_r() [1/2]	453
12.99.3.9 add_r() [2/2]	453
12.99.3.10 addin_r()	453
12.99.3.11 sub() [1/2]	453
12.99.3.12 sub() [2/2]	453
12.99.3.13 subin()	453
12.99.3.14 sub_r() [1/2]	453
12.99.3.15 sub_r() [2/2]	453
12.99.3.16 subin_r()	454
12.99.3.17 zero() [1/2]	454
12.99.3.18 zero() [2/2]	454
12.99.3.19 mod()	454
12.99.3.20 mul() [1/2]	454
12.99.3.21 mul() [2/2]	454
12.99.3.22 mulin()	454
12.99.3.23 mul_r() [1/2]	454
12.99.3.24 mul_r() [2/2]	454
12.99.3.25 axpy() [1/2]	455
12.99.3.26 axpy() [2/2]	455
12.99.3.27 axpyin()	455
12.99.3.28 axpy_r() [1/2]	455
12.99.3.29 axpy_r() [2/2]	455
12.99.3.30 axpyin_r()	455
12.99.3.31 maxpy() [1/2]	455
12.99.3.32 maxpy() [2/2]	456
12.99.3.33 maxpyin()	456
12.99.4 Field Documentation	456
12.99.4.1 vect_size	456
12.99.4.2 alignment	456
12.100 FieldTraits< Field > Struct Template Reference	456
12.100.1 Detailed Description	456
12.100.2 Member Typedef Documentation	456
12.100.2.1 category	456
12.100.3 Field Documentation	457

12.100.3.1 balanced	457
12.101 FieldTraits< FFPACK::RNSInteger< T > > Struct Template Reference	457
12.101.1 Member Typedef Documentation	457
12.101.1.1 category	457
12.101.2 Field Documentation	457
12.101.2.1 balanced	457
12.102 FieldTraits< FFPACK::RNSIntegerMod< T > > Struct Template Reference	457
12.102.1 Member Typedef Documentation	457
12.102.1.1 category	457
12.102.2 Field Documentation	458
12.102.2.1 balanced	458
12.103 FieldTraits< Givaro::Modular< Element > > Struct Template Reference	458
12.103.1 Member Typedef Documentation	458
12.103.1.1 category	458
12.103.2 Field Documentation	458
12.103.2.1 balanced	458
12.104 FieldTraits< Givaro::ModularBalanced< Element > > Struct Template Reference	458
12.104.1 Member Typedef Documentation	458
12.104.1.1 category	458
12.104.2 Field Documentation	459
12.104.2.1 balanced	459
12.105 FieldTraits< Givaro::ZRing< double > > Struct Reference	459
12.105.1 Member Typedef Documentation	459
12.105.1.1 category	459
12.105.2 Field Documentation	459
12.105.2.1 balanced	459
12.106 FieldTraits< Givaro::ZRing< float > > Struct Reference	459
12.106.1 Member Typedef Documentation	459
12.106.1.1 category	459
12.106.2 Field Documentation	460
12.106.2.1 balanced	460
12.107 FieldTraits< Givaro::ZRing< Givaro::Integer > > Struct Reference	460
12.107.1 Member Typedef Documentation	460
12.107.1.1 category	460
12.107.2 Field Documentation	460
12.107.2.1 balanced	460
12.108 FieldTraits< Givaro::ZRing< int16_t > > Struct Reference	460
12.108.1 Member Typedef Documentation	460
12.108.1.1 category	460
12.108.2 Field Documentation	461
12.108.2.1 balanced	461
12.109 FieldTraits< Givaro::ZRing< int32_t > > Struct Reference	461

12.109.1 Member Typedef Documentation	461
12.109.1.1 category	461
12.109.2 Field Documentation	461
12.109.2.1 balanced	461
12.110 FieldTraits< Givaro::ZRing< int64_t > > Struct Reference	461
12.110.1 Member Typedef Documentation	461
12.110.1.1 category	461
12.110.2 Field Documentation	461
12.110.2.1 balanced	461
12.111 FieldTraits< Givaro::ZRing< Reclnt::ruint< K > > > Struct Template Reference	462
12.111.1 Member Typedef Documentation	462
12.111.1.1 category	462
12.111.2 Field Documentation	462
12.111.2.1 balanced	462
12.112 FieldTraits< Givaro::ZRing< uint16_t > > Struct Reference	462
12.112.1 Member Typedef Documentation	462
12.112.1.1 category	462
12.112.2 Field Documentation	462
12.112.2.1 balanced	462
12.113 FieldTraits< Givaro::ZRing< uint32_t > > Struct Reference	462
12.113.1 Member Typedef Documentation	463
12.113.1.1 category	463
12.113.2 Field Documentation	463
12.113.2.1 balanced	463
12.114 FieldTraits< Givaro::ZRing< uint64_t > > Struct Reference	463
12.114.1 Member Typedef Documentation	463
12.114.1.1 category	463
12.114.2 Field Documentation	463
12.114.2.1 balanced	463
12.115 Fixed Struct Reference	463
12.116 FixedPreclntTag Struct Reference	463
12.116.1 Detailed Description	464
12.117 ScalFunctionsBase< Element, typename enable_if< is_floating_point< Element >::value >::type >::FloatingPointTestDistribution Class Reference	464
12.117.1 Member Typedef Documentation	464
12.117.1.1 IntType	464
12.117.2 Constructor & Destructor Documentation	464
12.117.2.1 FloatingPointTestDistribution()	464
12.117.3 Member Function Documentation	464
12.117.3.1 operator>()	464
12.118 ForStrategy1D< blocksize_t, Cut, Param > Struct Template Reference	464
12.118.1 Constructor & Destructor Documentation	465

12.118.1.1 ForStrategy1D() [1/2]	465
12.118.1.2 ForStrategy1D() [2/2]	465
12.118.2 Member Function Documentation	465
12.118.2.1 build()	465
12.118.2.2 initialize()	465
12.118.2.3 isTerminated()	465
12.118.2.4 begin()	466
12.118.2.5 end()	466
12.118.2.6 numblocks()	466
12.118.2.7 blockindex()	466
12.118.2.8 operator++()	466
12.118.3 Field Documentation	466
12.118.3.1 ibeg	466
12.118.3.2 iend	466
12.118.3.3 current	466
12.118.3.4 firstBlockSize	466
12.118.3.5 lastBlockSize	466
12.118.3.6 changeBS	467
12.118.3.7 numBlock	467
12.119 ForStrategy2D< blocksize_t, Cut, Param > Struct Template Reference	467
12.119.1 Constructor & Destructor Documentation	468
12.119.1.1 ForStrategy2D()	468
12.119.2 Member Function Documentation	468
12.119.2.1 initialize()	468
12.119.2.2 isTerminated()	468
12.119.2.3 ibegin()	468
12.119.2.4 jbegin()	468
12.119.2.5 iend()	468
12.119.2.6 jend()	468
12.119.2.7 operator++()	468
12.119.2.8 rownumblocks()	468
12.119.2.9 colnumblocks()	469
12.119.2.10 blockindex()	469
12.119.2.11 rowblockindex()	469
12.119.2.12 colblockindex()	469
12.119.3 Friends And Related Symbol Documentation	469
12.119.3.1 operator<<	469
12.119.4 Field Documentation	469
12.119.4.1 _ibeg	469
12.119.4.2 _iend	469
12.119.4.3 _jbeg	469
12.119.4.4 _jend	469

12.119.4.5 rowBlockSize	470
12.119.4.6 colBlockSize	470
12.119.4.7 current	470
12.119.4.8 lastRBS	470
12.119.4.9 lastCBS	470
12.119.4.10 changeRBS	470
12.119.4.11 changeCBS	470
12.119.4.12 numRowsBlock	470
12.119.4.13 numColBlock	470
12.119.4.14 BLOCKS	470
12.120 ftrmmLeftLowerNoTransNonUnit< Element > Class Template Reference	471
12.121 ftrmmLeftLowerNoTransUnit< Element > Class Template Reference	471
12.122 ftrmmLeftLowerTransNonUnit< Element > Class Template Reference	471
12.123 ftrmmLeftLowerTransUnit< Element > Class Template Reference	471
12.124 ftrmmLeftUpperNoTransNonUnit< Element > Class Template Reference	471
12.125 ftrmmLeftUpperNoTransUnit< Element > Class Template Reference	471
12.126 ftrmmLeftUpperTransNonUnit< Element > Class Template Reference	471
12.127 ftrmmLeftUpperTransUnit< Element > Class Template Reference	472
12.128 ftrmmRightLowerNoTransNonUnit< Element > Class Template Reference	472
12.129 ftrmmRightLowerNoTransUnit< Element > Class Template Reference	472
12.130 ftrmmRightLowerTransNonUnit< Element > Class Template Reference	472
12.131 ftrmmRightLowerTransUnit< Element > Class Template Reference	472
12.132 ftrmmRightUpperNoTransNonUnit< Element > Class Template Reference	472
12.133 ftrmmRightUpperNoTransUnit< Element > Class Template Reference	472
12.134 ftrmmRightUpperTransNonUnit< Element > Class Template Reference	472
12.135 ftrmmRightUpperTransUnit< Element > Class Template Reference	473
12.136 frsmLeftLowerNoTransNonUnit< Element > Class Template Reference	473
12.137 frsmLeftLowerNoTransUnit< Element > Class Template Reference	473
12.138 frsmLeftLowerTransNonUnit< Element > Class Template Reference	473
12.139 frsmLeftLowerTransUnit< Element > Class Template Reference	473
12.140 frsmLeftUpperNoTransNonUnit< Element > Class Template Reference	473
12.140.1 Detailed Description	473
12.141 frsmLeftUpperNoTransUnit< Element > Class Template Reference	474
12.142 frsmLeftUpperTransNonUnit< Element > Class Template Reference	474
12.143 frsmLeftUpperTransUnit< Element > Class Template Reference	474
12.144 frsmRightLowerNoTransNonUnit< Element > Class Template Reference	474
12.145 frsmRightLowerNoTransUnit< Element > Class Template Reference	474
12.146 frsmRightLowerTransNonUnit< Element > Class Template Reference	474
12.147 frsmRightLowerTransUnit< Element > Class Template Reference	474
12.148 frsmRightUpperNoTransNonUnit< Element > Class Template Reference	475
12.149 frsmRightUpperNoTransUnit< Element > Class Template Reference	475
12.150 frsmRightUpperTransNonUnit< Element > Class Template Reference	475

12.151 frsmRightUpperTransUnit< Element > Class Template Reference	475
12.152 GenericTag Struct Reference	475
12.152.1 Detailed Description	475
12.153 GenericTag Struct Reference	475
12.153.1 Detailed Description	475
12.154 Grain Struct Reference	475
12.155 has_minus_eq_impl< C > Struct Template Reference	476
12.155.1 Field Documentation	476
12.155.1.1 value	476
12.156 has_minus_impl< C > Struct Template Reference	476
12.156.1 Field Documentation	476
12.156.1.1 value	476
12.157 has_mul_eq_impl< C > Struct Template Reference	476
12.157.1 Field Documentation	476
12.157.1.1 value	476
12.158 has_mul_impl< C > Struct Template Reference	476
12.158.1 Field Documentation	477
12.158.1.1 value	477
12.159 has_operation< T > Struct Template Reference	477
12.159.1 Field Documentation	477
12.159.1.1 value	477
12.160 has_plus_eq_impl< C > Struct Template Reference	477
12.160.1 Field Documentation	477
12.160.1.1 value	477
12.161 has_plus_impl< C > Struct Template Reference	477
12.161.1 Field Documentation	478
12.161.1.1 value	478
12.162 HelperFlag Struct Reference	478
12.162.1 Field Documentation	478
12.162.1.1 none	478
12.162.1.2 coo	478
12.162.1.3 csr	478
12.162.1.4 ell	478
12.162.1.5 aut	478
12.162.1.6 pm1	478
12.163 HelperMod< Field, ElementTraits > Struct Template Reference	478
12.164 HelperMod< Field, ElementCategories::MachineIntTag > Struct Template Reference	479
12.164.1 Constructor & Destructor Documentation	479
12.164.1.1 HelperMod() [1/2]	479
12.164.1.2 HelperMod() [2/2]	479
12.164.2 Field Documentation	479
12.164.2.1 p	479

12.164.2.2 invp	479
12.164.2.3 min	479
12.164.2.4 max	479
12.164.2.5 pow50rem	479
12.165 HelperMod< Field, FFLAS::ElementCategories::ArbitraryPrecIntTag > Struct Template Reference	480
12.165.1 Constructor & Destructor Documentation	480
12.165.1.1 HelperMod() [1/2]	480
12.165.1.2 HelperMod() [2/2]	480
12.165.2 Field Documentation	480
12.165.2.1 p	480
12.166 HelperMod< Field, FFLAS::ElementCategories::FixedPrecIntTag > Struct Template Reference	480
12.166.1 Constructor & Destructor Documentation	480
12.166.1.1 HelperMod() [1/2]	480
12.166.1.2 HelperMod() [2/2]	480
12.166.2 Field Documentation	481
12.166.2.1 p	481
12.167 HelperMod< Field, FFLAS::ElementCategories::MachineFloatTag > Struct Template Reference	481
12.167.1 Constructor & Destructor Documentation	481
12.167.1.1 HelperMod() [1/2]	481
12.167.1.2 HelperMod() [2/2]	481
12.167.2 Field Documentation	481
12.167.2.1 p	481
12.167.2.2 invp	481
12.167.2.3 min	481
12.167.2.4 max	481
12.168 Hybrid Struct Reference	482
12.169 Info Struct Reference	482
12.169.1 Constructor & Destructor Documentation	482
12.169.1.1 Info() [1/4]	482
12.169.1.2 Info() [2/4]	482
12.169.1.3 Info() [3/4]	482
12.169.1.4 Info() [4/4]	482
12.169.2 Member Function Documentation	482
12.169.2.1 operator=() [1/2]	482
12.169.2.2 operator=() [2/2]	482
12.169.3 Field Documentation	483
12.169.3.1 size	483
12.169.3.2 perm	483
12.169.3.3 begin	483
12.170 Info Struct Reference	483
12.170.1 Constructor & Destructor Documentation	483
12.170.1.1 Info() [1/4]	483

12.170.1.2 Info() [2/4]	483
12.170.1.3 Info() [3/4]	483
12.170.1.4 Info() [4/4]	483
12.170.2 Member Function Documentation	484
12.170.2.1 operator=() [1/2]	484
12.170.2.2 operator=() [2/2]	484
12.170.3 Field Documentation	484
12.170.3.1 size	484
12.170.3.2 perm	484
12.170.3.3 begin	484
12.171 is_all_same< Args > Struct Template Reference	484
12.172 is_all_same< T, Args... > Struct Template Reference	484
12.172.1 Field Documentation	484
12.172.1.1 value	484
12.173 is_all_same<> Struct Reference	484
12.173.1 Field Documentation	485
12.173.1.1 value	485
12.174 is_simd< T > Struct Template Reference	485
12.174.1 Member Typedef Documentation	485
12.174.1.1 type	485
12.174.2 Field Documentation	485
12.174.2.1 value	485
12.175 isSparseMatrix< Field, M > Struct Template Reference	485
12.176 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO > > Struct Template Reference	485
12.177 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO_ZO > > Struct Template Reference	486
12.178 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR > > Struct Template Reference	486
12.179 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_HYB > > Struct Template Reference	486
12.180 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_ZO > > Struct Template Reference	487
12.181 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL > > Struct Template Reference	487
12.182 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd > > Struct Template Reference	487
12.183 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > > Struct Template Reference	488
12.184 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_ZO > > Struct Template Reference	488
12.185 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::HYB_ZO > > Struct Template Reference	488
12.186 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL > > Struct Template Reference	488
12.187 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL_ZO > > Struct Template Reference	489
12.188 isSparseMatrixMKLFormat< F, M > Struct Template Reference	489
12.189 isSparseMatrixSimdFormat< F, M > Struct Template Reference	489
12.190 isZOSparseMatrix< F, M > Struct Template Reference	490
12.191 isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO_ZO > > Struct Template Reference	490
12.192 isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_ZO > > Struct Template Reference	490

12.193 isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > > Struct Template Reference	490
12.194 isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_ZO > > Struct Template Reference	491
12.195 isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL_ZO > > Struct Template Reference	491
12.196 Iterative Struct Reference	491
12.197 LazyTag Struct Reference	491
12.197.1 Detailed Description	492
12.198 limits< T > Struct Template Reference	492
12.199 limits< char > Struct Reference	492
12.199.1 Member Typedef Documentation	492
12.199.1.1 T	492
12.199.2 Member Function Documentation	492
12.199.2.1 max()	492
12.199.2.2 min()	492
12.199.2.3 digits()	492
12.200 limits< double > Struct Reference	492
12.200.1 Member Typedef Documentation	493
12.200.1.1 T	493
12.200.2 Member Function Documentation	493
12.200.2.1 max()	493
12.200.2.2 min()	493
12.200.2.3 digits()	493
12.201 limits< float > Struct Reference	493
12.201.1 Member Typedef Documentation	493
12.201.1.1 T	493
12.201.2 Member Function Documentation	493
12.201.2.1 max()	493
12.201.2.2 min()	493
12.201.2.3 digits()	494
12.202 limits< Givaro::Integer > Struct Reference	494
12.202.1 Member Typedef Documentation	494
12.202.1.1 T	494
12.202.2 Member Function Documentation	494
12.202.2.1 max()	494
12.202.2.2 min()	494
12.203 limits< int > Struct Reference	494
12.203.1 Member Typedef Documentation	494
12.203.1.1 T	494
12.203.2 Member Function Documentation	495
12.203.2.1 max()	495
12.203.2.2 min()	495
12.203.2.3 digits()	495

12.204 limits< long > Struct Reference	495
12.204.1 Member Typedef Documentation	495
12.204.1.1 T	495
12.204.2 Member Function Documentation	495
12.204.2.1 max()	495
12.204.2.2 min()	495
12.204.2.3 digits()	495
12.205 limits< long long > Struct Reference	495
12.205.1 Member Typedef Documentation	496
12.205.1.1 T	496
12.205.2 Member Function Documentation	496
12.205.2.1 max()	496
12.205.2.2 min()	496
12.205.2.3 digits()	496
12.206 limits< Reclnt::rint< K > > Struct Template Reference	496
12.206.1 Member Typedef Documentation	496
12.206.1.1 T	496
12.206.2 Member Function Documentation	496
12.206.2.1 max()	496
12.206.2.2 min()	497
12.207 limits< Reclnt::ruint< K > > Struct Template Reference	497
12.207.1 Member Typedef Documentation	497
12.207.1.1 T	497
12.207.2 Member Function Documentation	497
12.207.2.1 max()	497
12.207.2.2 min()	497
12.208 limits< short int > Struct Reference	497
12.208.1 Member Typedef Documentation	498
12.208.1.1 T	498
12.208.2 Member Function Documentation	498
12.208.2.1 max()	498
12.208.2.2 min()	498
12.208.2.3 digits()	498
12.209 limits< signed char > Struct Reference	498
12.209.1 Member Typedef Documentation	498
12.209.1.1 T	498
12.209.2 Member Function Documentation	498
12.209.2.1 max()	498
12.209.2.2 min()	498
12.209.2.3 digits()	498
12.210 limits< unsigned char > Struct Reference	499
12.210.1 Member Typedef Documentation	499

12.210.1.1 T	499
12.210.2 Member Function Documentation	499
12.210.2.1 max()	499
12.210.2.2 min()	499
12.210.2.3 digits()	499
12.211 limits< unsigned int > Struct Reference	499
12.211.1 Member Typedef Documentation	499
12.211.1.1 T	499
12.211.2 Member Function Documentation	500
12.211.2.1 max()	500
12.211.2.2 min()	500
12.211.2.3 digits()	500
12.212 limits< unsigned long > Struct Reference	500
12.212.1 Member Typedef Documentation	500
12.212.1.1 T	500
12.212.2 Member Function Documentation	500
12.212.2.1 max()	500
12.212.2.2 min()	500
12.212.2.3 digits()	500
12.213 limits< unsigned long long > Struct Reference	500
12.213.1 Member Typedef Documentation	501
12.213.1.1 T	501
12.213.2 Member Function Documentation	501
12.213.2.1 max()	501
12.213.2.2 min()	501
12.213.2.3 digits()	501
12.214 limits< unsigned short int > Struct Reference	501
12.214.1 Member Typedef Documentation	501
12.214.1.1 T	501
12.214.2 Member Function Documentation	501
12.214.2.1 max()	501
12.214.2.2 min()	501
12.214.2.3 digits()	502
12.215 MachineFloatTag Struct Reference	502
12.215.1 Detailed Description	502
12.216 MachineIntTag Struct Reference	502
12.216.1 Detailed Description	502
12.217 MMHelper< Field, AlgoTrait, ModeTrait, ParSeqTrait > Struct Template Reference	502
12.217.1 Member Typedef Documentation	503
12.217.1.1 Self_t	503
12.217.1.2 DelayedField_t	503
12.217.1.3 DelayedField	503

12.217.1.4 DFElt	503
12.217.2 Constructor & Destructor Documentation	503
12.217.2.1 MMHelper() [1/5]	503
12.217.2.2 MMHelper() [2/5]	504
12.217.2.3 MMHelper() [3/5]	504
12.217.2.4 MMHelper() [4/5]	504
12.217.2.5 MMHelper() [5/5]	504
12.217.3 Member Function Documentation	504
12.217.3.1 initC()	504
12.217.3.2 initA()	504
12.217.3.3 initB()	504
12.217.3.4 initOut()	504
12.217.3.5 MaxDelayedDim()	505
12.217.3.6 Aunfit()	505
12.217.3.7 Bunfit()	505
12.217.3.8 setOutBounds()	505
12.217.3.9 checkA()	505
12.217.3.10 checkB()	505
12.217.3.11 checkOut() [1/2]	505
12.217.3.12 checkOut() [2/2]	505
12.217.4 Friends And Related Symbol Documentation	506
12.217.4.1 operator<<	506
12.217.5 Field Documentation	506
12.217.5.1 recLevel	506
12.217.5.2 FieldMin	506
12.217.5.3 FieldMax	506
12.217.5.4 Amin	506
12.217.5.5 Amax	506
12.217.5.6 Bmin	506
12.217.5.7 Bmax	506
12.217.5.8 Cmin	506
12.217.5.9 Cmax	507
12.217.5.10 Outmin	507
12.217.5.11 Outmax	507
12.217.5.12 MaxStorableValue	507
12.217.5.13 delayedField	507
12.217.5.14 parseq	507
12.218 MMHelper< FFPACK::RNSInteger< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait > Struct Template Reference	507
12.218.1 Member Typedef Documentation	508
12.218.1.1 Self_t	508
12.218.2 Constructor & Destructor Documentation	508

12.218.2.1 MMHelper() [1/5]	508
12.218.2.2 MMHelper() [2/5]	508
12.218.2.3 MMHelper() [3/5]	508
12.218.2.4 MMHelper() [4/5]	508
12.218.2.5 MMHelper() [5/5]	508
12.218.3 Member Function Documentation	508
12.218.3.1 setNorm()	508
12.218.4 Friends And Related Symbol Documentation	509
12.218.4.1 operator<<	509
12.218.5 Field Documentation	509
12.218.5.1 normA	509
12.218.5.2 normB	509
12.218.5.3 recLevel	509
12.218.5.4 parseq	509
12.219 MMHelper< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeq← Trait > Struct Template Reference	509
12.219.1 Member Typedef Documentation	510
12.219.1.1 Self_t	510
12.219.2 Constructor & Destructor Documentation	510
12.219.2.1 MMHelper() [1/5]	510
12.219.2.2 MMHelper() [2/5]	510
12.219.2.3 MMHelper() [3/5]	510
12.219.2.4 MMHelper() [4/5]	510
12.219.2.5 MMHelper() [5/5]	510
12.219.3 Member Function Documentation	510
12.219.3.1 setNorm()	510
12.219.4 Friends And Related Symbol Documentation	511
12.219.4.1 operator<<	511
12.219.5 Field Documentation	511
12.219.5.1 normA	511
12.219.5.2 normB	511
12.219.5.3 recLevel	511
12.219.5.4 parseq	511
12.220 MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< Dest >, ParSeqTrait > Struct Tem- plate Reference	511
12.220.1 Member Typedef Documentation	512
12.220.1.1 Self_t	512
12.220.2 Constructor & Destructor Documentation	512
12.220.2.1 MMHelper() [1/4]	512
12.220.2.2 MMHelper() [2/4]	512
12.220.2.3 MMHelper() [3/4]	512
12.220.2.4 MMHelper() [4/4]	512
12.220.3 Friends And Related Symbol Documentation	512

12.220.3.1 operator<<	512
12.220.4 Field Documentation	512
12.220.4.1 recLevel	512
12.220.4.2 parseq	512
12.221 MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeqTrait > Struct Template Reference	513
12.221.1 Member Typedef Documentation	513
12.221.1.1 Self_t	513
12.221.2 Constructor & Destructor Documentation	513
12.221.2.1 MMHelper() [1/5]	513
12.221.2.2 MMHelper() [2/5]	513
12.221.2.3 MMHelper() [3/5]	513
12.221.2.4 MMHelper() [4/5]	514
12.221.2.5 MMHelper() [5/5]	514
12.221.3 Member Function Documentation	514
12.221.3.1 setNorm()	514
12.221.4 Friends And Related Symbol Documentation	514
12.221.4.1 operator<<	514
12.221.5 Field Documentation	514
12.221.5.1 normA	514
12.221.5.2 normB	514
12.221.5.3 recLevel	514
12.221.5.4 parseq	514
12.222 MMHelper< Field, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait > Struct Template Reference	515
12.222.1 Detailed Description	515
12.222.2 Member Typedef Documentation	515
12.222.2.1 Self_t	515
12.222.3 Constructor & Destructor Documentation	515
12.222.3.1 MMHelper() [1/4]	515
12.222.3.2 MMHelper() [2/4]	515
12.222.3.3 MMHelper() [3/4]	516
12.222.3.4 MMHelper() [4/4]	516
12.222.4 Friends And Related Symbol Documentation	516
12.222.4.1 operator<<	516
12.222.5 Field Documentation	516
12.222.5.1 recLevel	516
12.222.5.2 parseq	516
12.223 ModeTraits< Field > Struct Template Reference	516
12.223.1 Detailed Description	516
12.223.2 Member Typedef Documentation	516
12.223.2.1 value	516
12.224 ModeTraits< Givaro::Modular< Element, Compute > > Struct Template Reference	517

12.224.1 Member Typedef Documentation	517
12.224.1.1 value	517
12.225 ModeTraits< Givaro::Modular< Givaro::Integer, Compute > > Struct Template Reference	517
12.225.1 Member Typedef Documentation	517
12.225.1.1 value	517
12.226 ModeTraits< Givaro::Modular< int16_t, Compute > > Struct Template Reference	517
12.226.1 Member Typedef Documentation	517
12.226.1.1 value	517
12.227 ModeTraits< Givaro::Modular< int32_t, Compute > > Struct Template Reference	518
12.227.1 Member Typedef Documentation	518
12.227.1.1 value	518
12.228 ModeTraits< Givaro::Modular< int64_t, uint64_t > > Struct Reference	518
12.228.1 Member Typedef Documentation	518
12.228.1.1 value	518
12.229 ModeTraits< Givaro::Modular< int8_t, Compute > > Struct Template Reference	518
12.229.1 Member Typedef Documentation	518
12.229.1.1 value	518
12.230 ModeTraits< Givaro::Modular< RecInt::ruint< K >, Compute > > Struct Template Reference	519
12.230.1 Member Typedef Documentation	519
12.230.1.1 value	519
12.231 ModeTraits< Givaro::Modular< uint16_t, Compute > > Struct Template Reference	519
12.231.1 Member Typedef Documentation	519
12.231.1.1 value	519
12.232 ModeTraits< Givaro::Modular< uint32_t, Compute > > Struct Template Reference	519
12.232.1 Member Typedef Documentation	519
12.232.1.1 value	519
12.233 ModeTraits< Givaro::Modular< uint8_t, Compute > > Struct Template Reference	520
12.233.1 Member Typedef Documentation	520
12.233.1.1 value	520
12.234 ModeTraits< Givaro::ModularBalanced< Element > > Struct Template Reference	520
12.234.1 Member Typedef Documentation	520
12.234.1.1 value	520
12.235 ModeTraits< Givaro::ModularBalanced< Givaro::Integer > > Struct Reference	520
12.235.1 Member Typedef Documentation	520
12.235.1.1 value	520
12.236 ModeTraits< Givaro::ModularBalanced< int16_t > > Struct Reference	521
12.236.1 Member Typedef Documentation	521
12.236.1.1 value	521
12.237 ModeTraits< Givaro::ModularBalanced< int32_t > > Struct Reference	521
12.237.1 Member Typedef Documentation	521
12.237.1.1 value	521
12.238 ModeTraits< Givaro::ModularBalanced< int8_t > > Struct Reference	521

12.238.1 Member Typedef Documentation	521
12.238.1.1 value	521
12.239 ModeTraits< Givaro::Montgomery< T > > Struct Template Reference	521
12.239.1 Member Typedef Documentation	522
12.239.1.1 value	522
12.240 ModeTraits< Givaro::ZRing< double > > Struct Reference	522
12.240.1 Member Typedef Documentation	522
12.240.1.1 value	522
12.241 ModeTraits< Givaro::ZRing< float > > Struct Reference	522
12.241.1 Member Typedef Documentation	522
12.241.1.1 value	522
12.242 ModeTraits< Givaro::ZRing< Givaro::Integer > > Struct Reference	522
12.242.1 Member Typedef Documentation	523
12.242.1.1 value	523
12.243 ModularBalanced< T > Class Template Reference	523
12.244 ModularTag Struct Reference	523
12.244.1 Detailed Description	523
12.245 Montgomery< T > Class Template Reference	523
12.246 need_field_characteristic< Field > Struct Template Reference	523
12.246.1 Field Documentation	523
12.246.1.1 value	523
12.247 need_field_characteristic< Givaro::Modular< Field > > Struct Template Reference	523
12.247.1 Field Documentation	524
12.247.1.1 value	524
12.248 need_field_characteristic< Givaro::ModularBalanced< Field > > Struct Template Reference	524
12.248.1 Field Documentation	524
12.248.1.1 value	524
12.249 NoSimd< T > Struct Template Reference	524
12.249.1 Member Typedef Documentation	524
12.249.1.1 vect_t	524
12.249.1.2 scalar_t	525
12.249.1.3 aligned_allocator	525
12.249.1.4 aligned_vector	525
12.249.1.5 is_same_element	525
12.249.2 Member Function Documentation	525
12.249.2.1 type_string()	525
12.249.2.2 valid()	525
12.249.2.3 compliant()	525
12.249.3 Field Documentation	525
12.249.3.1 vect_size	525
12.249.3.2 alignment	525
12.250 Parallel< C, P > Struct Template Reference	526

12.250.1 Member Typedef Documentation	526
12.250.1.1 Cut	526
12.250.1.2 Param	526
12.250.2 Constructor & Destructor Documentation	526
12.250.2.1 Parallel()	526
12.250.3 Member Function Documentation	526
12.250.3.1 numthreads()	526
12.250.3.2 set_numthreads()	526
12.250.4 Friends And Related Symbol Documentation	526
12.250.4.1 operator<<	526
12.251 RNSInteger< RNS >::RandIter Class Reference	527
12.251.1 Constructor & Destructor Documentation	527
12.251.1.1 RandIter()	527
12.251.2 Member Function Documentation	527
12.251.2.1 random() [1/2]	527
12.251.2.2 random() [2/2]	527
12.251.2.3 operator>() [1/2]	527
12.251.2.4 operator>() [2/2]	527
12.251.2.5 ring()	528
12.252 RNSIntegerMod< RNS >::RandIter Class Reference	528
12.252.1 Constructor & Destructor Documentation	528
12.252.1.1 RandIter()	528
12.252.2 Member Function Documentation	528
12.252.2.1 random() [1/2]	528
12.252.2.2 random() [2/2]	528
12.252.2.3 operator>() [1/2]	528
12.252.2.4 operator>() [2/2]	528
12.252.2.5 ring()	529
12.253 readMyMachineType< Field, T > Struct Template Reference	529
12.253.1 Member Typedef Documentation	529
12.253.1.1 Element	529
12.253.1.2 Element_ptr	529
12.253.2 Member Function Documentation	529
12.253.2.1 operator>()	529
12.254 readMyMachineType< Field, mpz_t > Struct Template Reference	529
12.254.1 Member Typedef Documentation	530
12.254.1.1 Element	530
12.254.1.2 Element_ptr	530
12.254.2 Member Function Documentation	530
12.254.2.1 operator>()	530
12.255 Recursive Struct Reference	530
12.256 Recursive Struct Reference	530

12.257 rint< K > Class Template Reference	530
12.258 rns_double Struct Reference	530
12.258.1 Member Typedef Documentation	531
12.258.1.1 integer	531
12.258.1.2 ModField	532
12.258.1.3 BasisElement	532
12.258.1.4 Element	532
12.258.1.5 Element_ptr	532
12.258.1.6 ConstElement_ptr	532
12.258.2 Constructor & Destructor Documentation	532
12.258.2.1 rns_double() [1/4]	532
12.258.2.2 rns_double() [2/4]	532
12.258.2.3 rns_double() [3/4]	532
12.258.2.4 rns_double() [4/4]	532
12.258.3 Member Function Documentation	532
12.258.3.1 precompute_cst()	532
12.258.3.2 init() [1/3]	533
12.258.3.3 init() [2/3]	533
12.258.3.4 init_transpose()	533
12.258.3.5 convert() [1/2]	533
12.258.3.6 convert_transpose()	533
12.258.3.7 reduce()	534
12.258.3.8 init() [3/3]	534
12.258.3.9 convert() [2/2]	534
12.258.4 Field Documentation	534
12.258.4.1 _basis	534
12.258.4.2 _basisMax	534
12.258.4.3 _negbasis	534
12.258.4.4 _invbasis	534
12.258.4.5 _field_rns	534
12.258.4.6 _M	534
12.258.4.7 _Mi	535
12.258.4.8 _MMi	535
12.258.4.9 _crt_in	535
12.258.4.10 _crt_out	535
12.258.4.11 _size	535
12.258.4.12 _pbits	535
12.258.4.13 _ldm	535
12.258.4.14 _mi_sum	535
12.259 rns_double_elt Struct Reference	535
12.259.1 Constructor & Destructor Documentation	536
12.259.1.1 rns_double_elt() [1/3]	536

12.259.1.2 <code>~rns_double_elt()</code>	536
12.259.1.3 <code>rns_double_elt()</code> [2/3]	536
12.259.1.4 <code>rns_double_elt()</code> [3/3]	536
12.259.2 Member Function Documentation	536
12.259.2.1 <code>operator&()</code> [1/2]	536
12.259.2.2 <code>operator&()</code> [2/2]	536
12.259.3 Field Documentation	536
12.259.3.1 <code>_ptr</code>	536
12.259.3.2 <code>_stride</code>	536
12.259.3.3 <code>_alloc</code>	536
12.260 <code>rns_double_elt_cstptr</code> Struct Reference	537
12.260.1 Constructor & Destructor Documentation	537
12.260.1.1 <code>rns_double_elt_cstptr()</code> [1/5]	537
12.260.1.2 <code>rns_double_elt_cstptr()</code> [2/5]	537
12.260.1.3 <code>rns_double_elt_cstptr()</code> [3/5]	537
12.260.1.4 <code>rns_double_elt_cstptr()</code> [4/5]	538
12.260.1.5 <code>rns_double_elt_cstptr()</code> [5/5]	538
12.260.2 Member Function Documentation	538
12.260.2.1 <code>operator&()</code> [1/2]	538
12.260.2.2 <code>operator*()</code>	538
12.260.2.3 <code>operator[]()</code> [1/2]	538
12.260.2.4 <code>operator[]()</code> [2/2]	538
12.260.2.5 <code>operator++()</code>	538
12.260.2.6 <code>operator--()</code>	538
12.260.2.7 <code>operator+()</code>	538
12.260.2.8 <code>operator-()</code>	538
12.260.2.9 <code>operator+=()</code>	538
12.260.2.10 <code>operator-=()</code>	538
12.260.2.11 <code>operator=()</code>	539
12.260.2.12 <code>operator<()</code>	539
12.260.2.13 <code>operator"!=()</code>	539
12.260.2.14 <code>operator&()</code> [2/2]	539
12.260.3 Field Documentation	539
12.260.3.1 <code>other</code>	539
12.260.3.2 <code>_ptr</code>	539
12.260.3.3 <code>_stride</code>	539
12.260.3.4 <code>_alloc</code>	539
12.261 <code>rns_double_elt_ptr</code> Struct Reference	539
12.261.1 Constructor & Destructor Documentation	540
12.261.1.1 <code>rns_double_elt_ptr()</code> [1/5]	540
12.261.1.2 <code>rns_double_elt_ptr()</code> [2/5]	540
12.261.1.3 <code>rns_double_elt_ptr()</code> [3/5]	540

12.261.1.4 rns_double_elt_ptr() [4/5]	540
12.261.1.5 rns_double_elt_ptr() [5/5]	540
12.261.2 Member Function Documentation	540
12.261.2.1 operator&() [1/2]	540
12.261.2.2 operator*()	540
12.261.2.3 operator[]() [1/2]	541
12.261.2.4 operator[]() [2/2]	541
12.261.2.5 operator++()	541
12.261.2.6 operator--()	541
12.261.2.7 operator+()	541
12.261.2.8 operator-()	541
12.261.2.9 operator+=()	541
12.261.2.10 operator-=()	541
12.261.2.11 operator=()	541
12.261.2.12 operator<()	541
12.261.2.13 operator"!=(	541
12.261.2.14 operator&() [2/2]	541
12.261.3 Field Documentation	542
12.261.3.1 other	542
12.261.3.2 _ptr	542
12.261.3.3 _stride	542
12.261.3.4 _alloc	542
12.262 rns_double_extended Struct Reference	542
12.262.1 Member Typedef Documentation	543
12.262.1.1 integer	543
12.262.1.2 ModField	543
12.262.1.3 BasisElement	543
12.262.1.4 Element	543
12.262.1.5 Element_ptr	543
12.262.1.6 ConstElement_ptr	543
12.262.2 Constructor & Destructor Documentation	543
12.262.2.1 rns_double_extended() [1/3]	543
12.262.2.2 rns_double_extended() [2/3]	543
12.262.2.3 rns_double_extended() [3/3]	543
12.262.3 Member Function Documentation	544
12.262.3.1 precompute_cst()	544
12.262.3.2 init() [1/3]	544
12.262.3.3 init() [2/3]	544
12.262.3.4 convert() [1/2]	544
12.262.3.5 init() [3/3]	544
12.262.3.6 convert() [2/2]	544
12.262.3.7 reduce()	544

12.262.4 Field Documentation	545
12.262.4.1 <code>_basis</code>	545
12.262.4.2 <code>_basisMax</code>	545
12.262.4.3 <code>_negbasis</code>	545
12.262.4.4 <code>_invbasis</code>	545
12.262.4.5 <code>_field_rns</code>	545
12.262.4.6 <code>_M</code>	545
12.262.4.7 <code>_Mi</code>	545
12.262.4.8 <code>_MMi</code>	545
12.262.4.9 <code>_crt_in</code>	545
12.262.4.10 <code>_crt_out</code>	545
12.262.4.11 <code>_size</code>	545
12.262.4.12 <code>_pbits</code>	545
12.262.4.13 <code>_ldm</code>	545
12.263 RNSElementTag Struct Reference	546
12.263.1 Detailed Description	546
12.264 RNSInteger< RNS > Class Template Reference	546
12.264.1 Member Typedef Documentation	547
12.264.1.1 <code>BasisElement</code>	547
12.264.1.2 <code>integer</code>	547
12.264.1.3 <code>Element</code>	547
12.264.1.4 <code>Element_ptr</code>	547
12.264.1.5 <code>ConstElement_ptr</code>	547
12.264.2 Constructor & Destructor Documentation	547
12.264.2.1 <code>RNSInteger()</code> [1/2]	547
12.264.2.2 <code>RNSInteger()</code> [2/2]	547
12.264.3 Member Function Documentation	547
12.264.3.1 <code>rns()</code>	547
12.264.3.2 <code>size()</code>	547
12.264.3.3 <code>isOne()</code>	548
12.264.3.4 <code>isMOne()</code>	548
12.264.3.5 <code>isZero()</code>	548
12.264.3.6 <code>characteristic()</code>	548
12.264.3.7 <code>cardinality()</code>	548
12.264.3.8 <code>init()</code> [1/2]	548
12.264.3.9 <code>init()</code> [2/2]	548
12.264.3.10 <code>reduce()</code> [1/2]	548
12.264.3.11 <code>reduce()</code> [2/2]	548
12.264.3.12 <code>convert()</code>	549
12.264.3.13 <code>assign()</code>	549
12.264.3.14 <code>write()</code> [1/2]	549
12.264.3.15 <code>write()</code> [2/2]	549

12.264.4 Field Documentation	549
12.264.4.1 _rns	549
12.264.4.2 one	549
12.264.4.3 mOne	549
12.264.4.4 zero	549
12.265 RNSIntegerMod< RNS > Class Template Reference	549
12.265.1 Member Typedef Documentation	551
12.265.1.1 Element	551
12.265.1.2 Element_ptr	551
12.265.1.3 ConstElement_ptr	551
12.265.1.4 BasisElement	551
12.265.1.5 ModField	551
12.265.1.6 integer	551
12.265.2 Constructor & Destructor Documentation	551
12.265.2.1 RNSIntegerMod()	551
12.265.3 Member Function Documentation	551
12.265.3.1 rns()	551
12.265.3.2 delayed()	551
12.265.3.3 size()	552
12.265.3.4 isOne()	552
12.265.3.5 isMOne()	552
12.265.3.6 isZero()	552
12.265.3.7 characteristic() [1/2]	552
12.265.3.8 characteristic() [2/2]	552
12.265.3.9 cardinality() [1/2]	552
12.265.3.10 cardinality() [2/2]	552
12.265.3.11 minElement()	552
12.265.3.12 maxElement()	552
12.265.3.13 init() [1/3]	552
12.265.3.14 init() [2/3]	553
12.265.3.15 reduce() [1/2]	553
12.265.3.16 reduce() [2/2]	553
12.265.3.17 init() [3/3]	553
12.265.3.18 convert()	553
12.265.3.19 assign()	553
12.265.3.20 add()	553
12.265.3.21 sub()	553
12.265.3.22 neg()	554
12.265.3.23 mul()	554
12.265.3.24 axpyin()	554
12.265.3.25 inv()	554
12.265.3.26 areEqual()	554

12.265.3.27 write() [1/2]	554
12.265.3.28 write() [2/2]	554
12.265.3.29 reduce_modp() [1/2]	554
12.265.3.30 write_matrix()	555
12.265.3.31 write_matrix_long()	555
12.265.3.32 reduce_modp() [2/2]	555
12.265.3.33 reduce_modp_rnsmajor()	555
12.265.4 Field Documentation	555
12.265.4.1 _p	555
12.265.4.2 _Mi_modp_rns	555
12.265.4.3 _iM_modp_rns	555
12.265.4.4 _rns	555
12.265.4.5 _F	556
12.265.4.6 _RNSdelayed	556
12.265.4.7 one	556
12.265.4.8 mOne	556
12.265.4.9 zero	556
12.266 rnsRandIter< RNS > Class Template Reference	556
12.266.1 Constructor & Destructor Documentation	556
12.266.1.1 rnsRandIter()	556
12.266.2 Member Function Documentation	557
12.266.2.1 random() [1/2]	557
12.266.2.2 operator>() [1/2]	557
12.266.2.3 operator>() [2/2]	557
12.266.2.4 random() [2/2]	557
12.266.2.5 ring()	557
12.267 Row Struct Reference	557
12.268 ruint< K > Class Template Reference	557
12.269 ScalFunctions< Element > Struct Template Reference	557
12.269.1 Member Typedef Documentation	558
12.269.1.1 vectElt	558
12.269.2 Member Function Documentation	558
12.269.2.1 genInputs()	558
12.269.2.2 genInputsWithZero()	559
12.269.2.3 zero()	559
12.269.2.4 vand()	559
12.269.2.5 vor()	559
12.269.2.6 vxor()	559
12.269.2.7 vandnot()	559
12.269.2.8 add()	559
12.269.2.9 addin()	559
12.269.2.10 sub()	559

12.269.2.11 subin()	560
12.269.2.12 mul()	560
12.269.2.13 mulin()	560
12.269.2.14 div()	560
12.269.2.15 fmadd()	560
12.269.2.16 fmaddin()	560
12.269.2.17 fmsub()	560
12.269.2.18 fmsubin()	560
12.269.2.19 fnmadd()	561
12.269.2.20 fnmaddin()	561
12.269.2.21 lesser()	561
12.269.2.22 lesser_eq()	561
12.269.2.23 greater()	561
12.269.2.24 greater_eq()	561
12.269.2.25 eq()	561
12.269.2.26 unpacklo()	561
12.269.2.27 unpackhi()	562
12.269.2.28 unpacklohi()	562
12.269.2.29 pack_even()	562
12.269.2.30 pack_odd()	562
12.269.2.31 pack()	562
12.269.2.32 blend()	562
12.270 ScalFunctionsBase< Element, Enable > Struct Template Reference	562
12.271 ScalFunctionsBase< Element, typename enable_if< is_floating_point< Element >::value >::type > Struct Template Reference	563
12.271.1 Member Function Documentation	563
12.271.1.1 get_default_random_generator()	563
12.271.1.2 ceil()	563
12.271.1.3 floor()	563
12.271.1.4 round()	563
12.271.1.5 blendv()	564
12.271.1.6 fma()	564
12.271.2 Field Documentation	564
12.271.2.1 _zero	564
12.271.2.2 cmp_true	564
12.271.2.3 cmp_false	564
12.272 ScalFunctionsBase< Element, typename enable_if< is_integral< Element >::value >::type > Struct Template Reference	564
12.272.1 Member Function Documentation	565
12.272.1.1 get_default_random_generator()	565
12.272.1.2 round()	565
12.272.1.3 fma()	565
12.272.1.4 mullo()	565

12.272.1.5 mulhi()	565
12.272.1.6 mulx()	565
12.272.1.7 fmaddx()	565
12.272.1.8 fmaddxin()	566
12.272.1.9 fmsubx()	566
12.272.1.10 fmsubxin()	566
12.272.1.11 fnmaddx()	566
12.272.1.12 fnmaddxin()	566
12.272.1.13 sra()	566
12.272.1.14 srl()	566
12.272.1.15 sll()	566
12.272.2 Field Documentation	567
12.272.2.1 _zero	567
12.272.2.2 cmp_true	567
12.272.2.3 cmp_false	567
12.273 Sequential Struct Reference	567
12.273.1 Constructor & Destructor Documentation	567
12.273.1.1 Sequential() [1/3]	567
12.273.1.2 Sequential() [2/3]	567
12.273.1.3 Sequential() [3/3]	567
12.273.2 Member Function Documentation	567
12.273.2.1 numthreads()	567
12.273.3 Friends And Related Symbol Documentation	568
12.273.3.1 operator<<	568
12.274 Simd128_impl< ArithType, Int, Signed, Size > Struct Template Reference	568
12.275 Simd128_impl< true, false, true, 4 > Struct Reference	568
12.276 Simd128_impl< true, false, true, 8 > Struct Reference	568
12.277 Simd128_impl< true, true, false, 2 > Struct Reference	568
12.277.1 Member Typedef Documentation	570
12.277.1.1 scalar_t	570
12.277.1.2 aligned_allocator	570
12.277.1.3 aligned_vector	570
12.277.1.4 is_same_element	570
12.277.1.5 vect_t	570
12.277.2 Member Function Documentation	571
12.277.2.1 type_string()	571
12.277.2.2 set1() [1/2]	571
12.277.2.3 set() [1/2]	571
12.277.2.4 gather() [1/2]	571
12.277.2.5 load() [1/2]	571
12.277.2.6 loadu() [1/2]	571
12.277.2.7 store() [1/2]	571

12.277.2.8 storeu() [1/2]	571
12.277.2.9 stream() [1/2]	571
12.277.2.10 sra()	572
12.277.2.11 greater()	572
12.277.2.12 lesser()	572
12.277.2.13 greater_eq()	572
12.277.2.14 lesser_eq()	572
12.277.2.15 mulhi()	572
12.277.2.16 mulx()	572
12.277.2.17 fmaddx()	572
12.277.2.18 fmaddxin()	572
12.277.2.19 fnmaddx()	573
12.277.2.20 fnmaddxin()	573
12.277.2.21 fmsubx()	573
12.277.2.22 fmsubxin()	573
12.277.2.23 hadd_to_scal()	573
12.277.2.24 valid()	573
12.277.2.25 compliant()	573
12.277.2.26 set1() [2/2]	573
12.277.2.27 set() [2/2]	573
12.277.2.28 gather() [2/2]	574
12.277.2.29 load() [2/2]	574
12.277.2.30 loadu() [2/2]	574
12.277.2.31 store() [2/2]	574
12.277.2.32 storeu() [2/2]	574
12.277.2.33 stream() [2/2]	574
12.277.2.34 sll()	574
12.277.2.35 srl()	574
12.277.2.36 shuffle()	574
12.277.2.37 unpacklo_intrinsic()	575
12.277.2.38 unpackhi_intrinsic()	575
12.277.2.39 unpacklo()	575
12.277.2.40 unpackhi()	575
12.277.2.41 unpacklohi()	575
12.277.2.42 pack_even()	575
12.277.2.43 pack_odd()	575
12.277.2.44 pack()	575
12.277.2.45 transpose()	575
12.277.2.46 blend()	576
12.277.2.47 add()	576
12.277.2.48 addin()	576
12.277.2.49 sub()	576

12.277.2.50 subin()	576
12.277.2.51 mullo()	576
12.277.2.52 mul()	576
12.277.2.53 fmadd()	576
12.277.2.54 fmaddin()	576
12.277.2.55 fnmadd()	577
12.277.2.56 fnmaddin()	577
12.277.2.57 fmsub()	577
12.277.2.58 fmsubin()	577
12.277.2.59 eq()	577
12.277.2.60 round()	577
12.277.2.61 mod()	577
12.277.2.62 zero()	577
12.277.2.63 sll128()	577
12.277.2.64 srl128()	578
12.277.2.65 vand()	578
12.277.2.66 vor()	578
12.277.2.67 vxor()	578
12.277.2.68 vandnot()	578
12.277.3 Field Documentation	578
12.277.3.1 vect_size	578
12.277.3.2 alignment	578
12.278 Simd128_impl< true, true, false, 4 > Struct Reference	578
12.278.1 Member Typedef Documentation	580
12.278.1.1 scalar_t	580
12.278.1.2 aligned_allocator	580
12.278.1.3 aligned_vector	580
12.278.1.4 is_same_element	581
12.278.1.5 vect_t	581
12.278.2 Member Function Documentation	581
12.278.2.1 type_string()	581
12.278.2.2 set1() [1/2]	581
12.278.2.3 set() [1/2]	581
12.278.2.4 gather() [1/2]	581
12.278.2.5 load() [1/2]	581
12.278.2.6 loadu() [1/2]	581
12.278.2.7 store() [1/2]	581
12.278.2.8 storeu() [1/2]	581
12.278.2.9 stream() [1/2]	582
12.278.2.10 sra()	582
12.278.2.11 greater()	582
12.278.2.12 lesser()	582

12.278.2.13 greater_eq()	582
12.278.2.14 lesser_eq()	582
12.278.2.15 mulhi()	582
12.278.2.16 mulx()	582
12.278.2.17 fmaddx()	582
12.278.2.18 fmaddxin()	582
12.278.2.19 fnmaddx()	583
12.278.2.20 fnmaddxin()	583
12.278.2.21 fmsubx()	583
12.278.2.22 fmsubxin()	583
12.278.2.23 hadd_to_scal()	583
12.278.2.24 valid()	583
12.278.2.25 compliant()	583
12.278.2.26 set1() [2/2]	583
12.278.2.27 set() [2/2]	583
12.278.2.28 gather() [2/2]	584
12.278.2.29 load() [2/2]	584
12.278.2.30 loadu() [2/2]	584
12.278.2.31 store() [2/2]	584
12.278.2.32 storeu() [2/2]	584
12.278.2.33 stream() [2/2]	584
12.278.2.34 sll()	584
12.278.2.35 srl()	584
12.278.2.36 shuffle()	584
12.278.2.37 unpacklo_intrinsic()	584
12.278.2.38 unpackhi_intrinsic()	585
12.278.2.39 unpacklo()	585
12.278.2.40 unpackhi()	585
12.278.2.41 unpacklohi()	585
12.278.2.42 pack_even()	585
12.278.2.43 pack_odd()	585
12.278.2.44 pack()	585
12.278.2.45 transpose()	585
12.278.2.46 blend()	585
12.278.2.47 add()	586
12.278.2.48 addin()	586
12.278.2.49 sub()	586
12.278.2.50 subin()	586
12.278.2.51 mullo()	586
12.278.2.52 mul()	586
12.278.2.53 fmadd()	586
12.278.2.54 fmaddin()	586

12.278.2.55 fnmadd()	586
12.278.2.56 fnmaddin()	587
12.278.2.57 fmsub()	587
12.278.2.58 fmsubin()	587
12.278.2.59 eq()	587
12.278.2.60 round()	587
12.278.2.61 mod()	587
12.278.2.62 zero()	587
12.278.2.63 sll128()	587
12.278.2.64 srl128()	587
12.278.2.65 vand()	588
12.278.2.66 vor()	588
12.278.2.67 vxor()	588
12.278.2.68 vandnot()	588
12.278.3 Field Documentation	588
12.278.3.1 vect_size	588
12.278.3.2 alignment	588
12.279 Simd128_impl< true, true, false, 8 > Struct Reference	588
12.279.1 Member Typedef Documentation	590
12.279.1.1 scalar_t	590
12.279.1.2 aligned_allocator	590
12.279.1.3 aligned_vector	590
12.279.1.4 is_same_element	591
12.279.1.5 vect_t	591
12.279.2 Member Function Documentation	591
12.279.2.1 type_string()	591
12.279.2.2 set1() [1/2]	591
12.279.2.3 set() [1/2]	591
12.279.2.4 gather() [1/2]	591
12.279.2.5 load() [1/2]	591
12.279.2.6 loadu() [1/2]	591
12.279.2.7 store() [1/2]	591
12.279.2.8 storeu() [1/2]	591
12.279.2.9 stream() [1/2]	591
12.279.2.10 sra()	592
12.279.2.11 greater()	592
12.279.2.12 lesser()	592
12.279.2.13 greater_eq()	592
12.279.2.14 lesser_eq()	592
12.279.2.15 mullo()	592
12.279.2.16 mulhi()	592
12.279.2.17 mulx()	592

12.279.2.18 fmaddx()	592
12.279.2.19 fmaddxin()	592
12.279.2.20 fnmaddx()	593
12.279.2.21 fnmaddxin()	593
12.279.2.22 fmsubx()	593
12.279.2.23 fmsubxin()	593
12.279.2.24 hadd_to_scal()	593
12.279.2.25 valid()	593
12.279.2.26 compliant()	593
12.279.2.27 set1() [2/2]	593
12.279.2.28 set() [2/2]	593
12.279.2.29 gather() [2/2]	594
12.279.2.30 get()	594
12.279.2.31 load() [2/2]	594
12.279.2.32 loadu() [2/2]	594
12.279.2.33 store() [2/2]	594
12.279.2.34 storeu() [2/2]	594
12.279.2.35 stream() [2/2]	594
12.279.2.36 sll()	594
12.279.2.37 srl()	594
12.279.2.38 shuffle()	594
12.279.2.39 unpacklo_intrinsic()	595
12.279.2.40 unpackhi_intrinsic()	595
12.279.2.41 unpacklo()	595
12.279.2.42 unpackhi()	595
12.279.2.43 unpacklohi()	595
12.279.2.44 pack_even()	595
12.279.2.45 pack_odd()	595
12.279.2.46 pack()	595
12.279.2.47 transpose()	595
12.279.2.48 blend()	596
12.279.2.49 add()	596
12.279.2.50 addin()	596
12.279.2.51 sub()	596
12.279.2.52 subin()	596
12.279.2.53 mul()	596
12.279.2.54 fmadd()	596
12.279.2.55 fmaddin()	596
12.279.2.56 fnmadd()	596
12.279.2.57 fnmaddin()	597
12.279.2.58 fmsub()	597
12.279.2.59 fmsubin()	597

12.279.2.60 eq()	597
12.279.2.61 round()	597
12.279.2.62 mask_high()	597
12.279.2.63 mulhi_fast()	597
12.279.2.64 mod()	597
12.279.2.65 signbits()	597
12.279.2.66 zero()	598
12.279.2.67 sll128()	598
12.279.2.68 srl128()	598
12.279.2.69 vand()	598
12.279.2.70 vor()	598
12.279.2.71 vxor()	598
12.279.2.72 vandnot()	598
12.279.3 Field Documentation	598
12.279.3.1 vect_size	598
12.279.3.2 alignment	598
12.280 Simd128_impl< true, true, true, 2 > Struct Reference	598
12.280.1 Member Typedef Documentation	600
12.280.1.1 vect_t	600
12.280.1.2 scalar_t	600
12.280.1.3 aligned_allocator	601
12.280.1.4 aligned_vector	601
12.280.1.5 is_same_element	601
12.280.2 Member Function Documentation	601
12.280.2.1 type_string()	601
12.280.2.2 valid()	601
12.280.2.3 compliant()	601
12.280.2.4 set1()	601
12.280.2.5 set()	601
12.280.2.6 gather()	601
12.280.2.7 load()	601
12.280.2.8 loadu()	602
12.280.2.9 store()	602
12.280.2.10 storeu()	602
12.280.2.11 stream()	602
12.280.2.12 sll()	602
12.280.2.13 srl()	602
12.280.2.14 sra()	602
12.280.2.15 shuffle()	602
12.280.2.16 unpacklo_intrinsic()	602
12.280.2.17 unpackhi_intrinsic()	602
12.280.2.18 unpacklo()	603

12.280.2.19 unpackhi()	603
12.280.2.20 unpacklohi()	603
12.280.2.21 pack_even()	603
12.280.2.22 pack_odd()	603
12.280.2.23 pack()	603
12.280.2.24 transpose()	603
12.280.2.25 blend()	603
12.280.2.26 add()	604
12.280.2.27 addin()	604
12.280.2.28 sub()	604
12.280.2.29 subin()	604
12.280.2.30 mullo()	604
12.280.2.31 mul()	604
12.280.2.32 mulhi()	604
12.280.2.33 mulx()	604
12.280.2.34 fmadd()	604
12.280.2.35 fmaddin()	604
12.280.2.36 fmaddx()	605
12.280.2.37 fmaddxin()	605
12.280.2.38 fnmadd()	605
12.280.2.39 fnmaddin()	605
12.280.2.40 fnmaddx()	605
12.280.2.41 fnmaddxin()	605
12.280.2.42 fmsub()	605
12.280.2.43 fmsubin()	605
12.280.2.44 fmsubx()	605
12.280.2.45 fmsubxin()	606
12.280.2.46 eq()	606
12.280.2.47 greater()	606
12.280.2.48 lesser()	606
12.280.2.49 greater_eq()	606
12.280.2.50 lesser_eq()	606
12.280.2.51 hadd_to_scal()	606
12.280.2.52 round()	606
12.280.2.53 mod()	606
12.280.2.54 zero()	607
12.280.2.55 sll128()	607
12.280.2.56 srl128()	607
12.280.2.57 vand()	607
12.280.2.58 vor()	607
12.280.2.59 vxor()	607
12.280.2.60 vandnot()	607

12.280.3 Field Documentation	607
12.280.3.1 vect_size	607
12.280.3.2 alignment	607
12.281 Simd128_impl< true, true, true, 4 > Struct Reference	608
12.281.1 Member Typedef Documentation	609
12.281.1.1 vect_t	609
12.281.1.2 scalar_t	609
12.281.1.3 aligned_allocator	610
12.281.1.4 aligned_vector	610
12.281.1.5 is_same_element	610
12.281.2 Member Function Documentation	610
12.281.2.1 type_string()	610
12.281.2.2 valid()	610
12.281.2.3 compliant()	610
12.281.2.4 set1()	610
12.281.2.5 set()	610
12.281.2.6 gather()	610
12.281.2.7 load()	610
12.281.2.8 loadu()	610
12.281.2.9 store()	611
12.281.2.10 storeu()	611
12.281.2.11 stream()	611
12.281.2.12 sll()	611
12.281.2.13 srl()	611
12.281.2.14 sra()	611
12.281.2.15 shuffle()	611
12.281.2.16 unpacklo_intrinsic()	611
12.281.2.17 unpackhi_intrinsic()	611
12.281.2.18 unpacklo()	611
12.281.2.19 unpackhi()	612
12.281.2.20 unpacklohi()	612
12.281.2.21 pack_even()	612
12.281.2.22 pack_odd()	612
12.281.2.23 pack()	612
12.281.2.24 transpose()	612
12.281.2.25 blend()	612
12.281.2.26 add()	612
12.281.2.27 addin()	612
12.281.2.28 sub()	613
12.281.2.29 subin()	613
12.281.2.30 mullo()	613
12.281.2.31 mul()	613

12.281.2.32 mulhi()	613
12.281.2.33 mulx()	613
12.281.2.34 fmadd()	613
12.281.2.35 fmaddin()	613
12.281.2.36 fmaddx()	613
12.281.2.37 fmaddxin()	614
12.281.2.38 fnmadd()	614
12.281.2.39 fnmaddin()	614
12.281.2.40 fnmaddx()	614
12.281.2.41 fnmaddxin()	614
12.281.2.42 fmsub()	614
12.281.2.43 fmsubin()	614
12.281.2.44 fmsubx()	614
12.281.2.45 fmsubxin()	614
12.281.2.46 eq()	615
12.281.2.47 greater()	615
12.281.2.48 lesser()	615
12.281.2.49 greater_eq()	615
12.281.2.50 lesser_eq()	615
12.281.2.51 hadd_to_scal()	615
12.281.2.52 round()	615
12.281.2.53 mod()	615
12.281.2.54 zero()	615
12.281.2.55 sll128()	616
12.281.2.56 srl128()	616
12.281.2.57 vand()	616
12.281.2.58 vor()	616
12.281.2.59 vxor()	616
12.281.2.60 vandnot()	616
12.281.3 Field Documentation	616
12.281.3.1 vect_size	616
12.281.3.2 alignment	616
12.282 Simd128_impl< true, true, true, 8 > Struct Reference	616
12.282.1 Member Typedef Documentation	618
12.282.1.1 vect_t	618
12.282.1.2 scalar_t	619
12.282.1.3 aligned_allocator	619
12.282.1.4 aligned_vector	619
12.282.1.5 is_same_element	619
12.282.2 Member Function Documentation	619
12.282.2.1 type_string()	619
12.282.2.2 valid()	619

12.282.2.3 compliant()	619
12.282.2.4 set1()	619
12.282.2.5 set()	619
12.282.2.6 gather()	619
12.282.2.7 get()	619
12.282.2.8 load()	620
12.282.2.9 loadu()	620
12.282.2.10 store()	620
12.282.2.11 storeu()	620
12.282.2.12 stream()	620
12.282.2.13 sll()	620
12.282.2.14 srl()	620
12.282.2.15 sra()	620
12.282.2.16 shuffle()	620
12.282.2.17 unpacklo_intrinsic()	620
12.282.2.18 unpackhi_intrinsic()	621
12.282.2.19 unpacklo()	621
12.282.2.20 unpackhi()	621
12.282.2.21 unpacklohi()	621
12.282.2.22 pack_even()	621
12.282.2.23 pack_odd()	621
12.282.2.24 pack()	621
12.282.2.25 transpose()	621
12.282.2.26 blend()	621
12.282.2.27 add()	622
12.282.2.28 addin()	622
12.282.2.29 sub()	622
12.282.2.30 subin()	622
12.282.2.31 mullo()	622
12.282.2.32 mul()	622
12.282.2.33 mulhi()	622
12.282.2.34 mulx()	622
12.282.2.35 fmadd()	622
12.282.2.36 fmaddin()	622
12.282.2.37 fmaddx()	623
12.282.2.38 fmaddxin()	623
12.282.2.39 fnmadd()	623
12.282.2.40 fnmaddin()	623
12.282.2.41 fnmaddx()	623
12.282.2.42 fnmaddxin()	623
12.282.2.43 fmsub()	623
12.282.2.44 fmsubin()	623

12.282.2.45 fmsubx()	623
12.282.2.46 fmsubxin()	624
12.282.2.47 eq()	624
12.282.2.48 greater()	624
12.282.2.49 lesser()	624
12.282.2.50 greater_eq()	624
12.282.2.51 lesser_eq()	624
12.282.2.52 hadd_to_scal()	624
12.282.2.53 round()	624
12.282.2.54 mask_high()	624
12.282.2.55 mulhi_fast()	624
12.282.2.56 mod()	625
12.282.2.57 signbits()	625
12.282.2.58 zero()	625
12.282.2.59 sll128()	625
12.282.2.60 srl128()	625
12.282.2.61 vand()	625
12.282.2.62 vor()	625
12.282.2.63 vxor()	625
12.282.2.64 vandnot()	625
12.282.3 Field Documentation	626
12.282.3.1 vect_size	626
12.282.3.2 alignment	626
12.283 Simd128i_base Struct Reference	626
12.283.1 Member Typedef Documentation	626
12.283.1.1 vect_t	626
12.283.2 Member Function Documentation	626
12.283.2.1 zero()	626
12.283.2.2 sll128()	626
12.283.2.3 srl128()	627
12.283.2.4 vand()	627
12.283.2.5 vor()	627
12.283.2.6 vxor()	627
12.283.2.7 vandnot()	627
12.284 Simd256_impl< ArithType, Int, Signed, Size > Struct Template Reference	627
12.285 Simd256_impl< true, false, true, 4 > Struct Reference	627
12.286 Simd256_impl< true, false, true, 8 > Struct Reference	628
12.286.1 Member Typedef Documentation	629
12.286.1.1 vect_t	629
12.286.1.2 scalar_t	629
12.286.1.3 aligned_allocator	629
12.286.1.4 aligned_vector	629

12.286.1.5 is_same_element	629
12.286.2 Member Function Documentation	629
12.286.2.1 type_string()	629
12.286.2.2 valid()	630
12.286.2.3 compliant()	630
12.286.2.4 zero()	630
12.286.2.5 set1()	630
12.286.2.6 set()	630
12.286.2.7 gather()	630
12.286.2.8 load()	630
12.286.2.9 loadu()	630
12.286.2.10 store()	630
12.286.2.11 storeu()	630
12.286.2.12 stream()	631
12.286.2.13 unpacklo_intrinsic()	631
12.286.2.14 unpackhi_intrinsic()	631
12.286.2.15 unpacklo()	631
12.286.2.16 unpackhi()	631
12.286.2.17 unpacklohi()	631
12.286.2.18 pack_even()	631
12.286.2.19 pack_odd()	631
12.286.2.20 pack()	631
12.286.2.21 transpose()	632
12.286.2.22 blend()	632
12.286.2.23 blendv()	632
12.286.2.24 add()	632
12.286.2.25 addin()	632
12.286.2.26 sub()	632
12.286.2.27 subin()	632
12.286.2.28 mul()	632
12.286.2.29 mulin()	632
12.286.2.30 div()	633
12.286.2.31 fmadd()	633
12.286.2.32 fmaddin()	633
12.286.2.33 fnmadd()	633
12.286.2.34 fnmaddin()	633
12.286.2.35 fmsub()	633
12.286.2.36 fmsubin()	633
12.286.2.37 eq()	633
12.286.2.38 lesser()	633
12.286.2.39 lesser_eq()	634
12.286.2.40 greater()	634

12.286.2.41 greater_eq()	634
12.286.2.42 vand()	634
12.286.2.43 vor()	634
12.286.2.44 vxor()	634
12.286.2.45 vandnot()	634
12.286.2.46 floor()	634
12.286.2.47 ceil()	634
12.286.2.48 round()	634
12.286.2.49 hadd()	635
12.286.2.50 hadd_to_scal()	635
12.286.2.51 mod()	635
12.286.3 Field Documentation	635
12.286.3.1 vect_size	635
12.286.3.2 alignment	635
12.287 Simd256_impl< true, true, false, 2 > Struct Reference	635
12.287.1 Member Typedef Documentation	637
12.287.1.1 scalar_t	637
12.287.1.2 aligned_allocator	637
12.287.1.3 aligned_vector	637
12.287.1.4 is_same_element	637
12.287.1.5 simdHalf	638
12.287.1.6 vect_t	638
12.287.1.7 half_t	638
12.287.2 Member Function Documentation	638
12.287.2.1 type_string()	638
12.287.2.2 set1() [1/2]	638
12.287.2.3 set() [1/2]	638
12.287.2.4 gather() [1/2]	638
12.287.2.5 load() [1/2]	638
12.287.2.6 loadu() [1/2]	638
12.287.2.7 store() [1/2]	639
12.287.2.8 storeu() [1/2]	639
12.287.2.9 stream() [1/2]	639
12.287.2.10 sra()	639
12.287.2.11 greater()	639
12.287.2.12 lesser()	639
12.287.2.13 greater_eq()	639
12.287.2.14 lesser_eq()	639
12.287.2.15 mulhi()	639
12.287.2.16 mulx()	639
12.287.2.17 fmaddx()	640
12.287.2.18 fmaddxin()	640

12.287.2.19 fnmaddx()	640
12.287.2.20 fnmaddxin()	640
12.287.2.21 fmsubx()	640
12.287.2.22 fmsubxin()	640
12.287.2.23 hadd_to_scal()	640
12.287.2.24 valid()	640
12.287.2.25 compliant()	640
12.287.2.26 set1() [2/2]	641
12.287.2.27 set() [2/2]	641
12.287.2.28 gather() [2/2]	641
12.287.2.29 load() [2/2]	641
12.287.2.30 loadu() [2/2]	641
12.287.2.31 store() [2/2]	641
12.287.2.32 storeu() [2/2]	641
12.287.2.33 stream() [2/2]	641
12.287.2.34 sll()	642
12.287.2.35 srl()	642
12.287.2.36 shuffle()	642
12.287.2.37 unpacklo_intrinsic()	642
12.287.2.38 unpackhi_intrinsic()	642
12.287.2.39 unpacklo()	642
12.287.2.40 unpackhi()	642
12.287.2.41 unpacklohi()	642
12.287.2.42 pack_even()	642
12.287.2.43 pack_odd()	642
12.287.2.44 pack()	643
12.287.2.45 transpose()	643
12.287.2.46 blend() [1/2]	643
12.287.2.47 blend() [2/2]	643
12.287.2.48 add()	643
12.287.2.49 addin()	643
12.287.2.50 sub()	643
12.287.2.51 subin()	644
12.287.2.52 mullo()	644
12.287.2.53 mul()	644
12.287.2.54 fmadd()	644
12.287.2.55 fmaddin()	644
12.287.2.56 fnmadd()	644
12.287.2.57 fnmaddin()	644
12.287.2.58 fmsub()	644
12.287.2.59 fmsubin()	644
12.287.2.60 eq()	645

12.287.2.61 round()	645
12.287.2.62 mod()	645
12.287.2.63 zero()	645
12.287.3 Field Documentation	645
12.287.3.1 vect_size	645
12.287.3.2 alignment	645
12.288 Simd256_impl< true, true, false, 4 > Struct Reference	645
12.288.1 Member Typedef Documentation	649
12.288.1.1 scalar_t [1/2]	649
12.288.1.2 aligned_allocator [1/2]	649
12.288.1.3 aligned_vector [1/2]	649
12.288.1.4 is_same_element [1/2]	649
12.288.1.5 simdHalf [1/2]	649
12.288.1.6 scalar_t [2/2]	649
12.288.1.7 aligned_allocator [2/2]	649
12.288.1.8 aligned_vector [2/2]	649
12.288.1.9 is_same_element [2/2]	649
12.288.1.10 simdHalf [2/2]	649
12.288.1.11 vect_t [1/2]	649
12.288.1.12 vect_t [2/2]	650
12.288.1.13 half_t [1/2]	650
12.288.1.14 half_t [2/2]	650
12.288.2 Member Function Documentation	650
12.288.2.1 type_string() [1/2]	650
12.288.2.2 set1() [1/3]	650
12.288.2.3 set() [1/4]	650
12.288.2.4 gather() [1/3]	650
12.288.2.5 load() [1/3]	650
12.288.2.6 loadu() [1/3]	650
12.288.2.7 store() [1/3]	650
12.288.2.8 storeu() [1/3]	651
12.288.2.9 stream() [1/3]	651
12.288.2.10 sra() [1/2]	651
12.288.2.11 greater() [1/2]	651
12.288.2.12 lesser() [1/2]	651
12.288.2.13 greater_eq() [1/2]	651
12.288.2.14 lesser_eq() [1/2]	651
12.288.2.15 mulhi() [1/2]	651
12.288.2.16 mulx() [1/2]	651
12.288.2.17 fmaddx() [1/2]	651
12.288.2.18 fmaddxin() [1/2]	652
12.288.2.19 fnmaddx() [1/2]	652

12.288.2.20 <code>fnmaddxin()</code> [1/2]	652
12.288.2.21 <code>fmsubx()</code> [1/2]	652
12.288.2.22 <code>fmsubxin()</code> [1/2]	652
12.288.2.23 <code>hadd_to_scal()</code> [1/2]	652
12.288.2.24 <code>type_string()</code> [2/2]	652
12.288.2.25 <code>set1()</code> [2/3]	652
12.288.2.26 <code>set()</code> [2/4]	652
12.288.2.27 <code>gather()</code> [2/3]	653
12.288.2.28 <code>load()</code> [2/3]	653
12.288.2.29 <code>loadu()</code> [2/3]	653
12.288.2.30 <code>store()</code> [2/3]	653
12.288.2.31 <code>storeu()</code> [2/3]	653
12.288.2.32 <code>stream()</code> [2/3]	653
12.288.2.33 <code>sra()</code> [2/2]	653
12.288.2.34 <code>greater()</code> [2/2]	653
12.288.2.35 <code>lesser()</code> [2/2]	653
12.288.2.36 <code>greater_eq()</code> [2/2]	653
12.288.2.37 <code>lesser_eq()</code> [2/2]	654
12.288.2.38 <code>mulhi()</code> [2/2]	654
12.288.2.39 <code>mulx()</code> [2/2]	654
12.288.2.40 <code>fmaddx()</code> [2/2]	654
12.288.2.41 <code>fmaddxin()</code> [2/2]	654
12.288.2.42 <code>fnmaddx()</code> [2/2]	654
12.288.2.43 <code>fnmaddxin()</code> [2/2]	654
12.288.2.44 <code>fmsubx()</code> [2/2]	654
12.288.2.45 <code>fmsubxin()</code> [2/2]	654
12.288.2.46 <code>hadd_to_scal()</code> [2/2]	655
12.288.2.47 <code>valid()</code> [1/2]	655
12.288.2.48 <code>valid()</code> [2/2]	655
12.288.2.49 <code>compliant()</code> [1/2]	655
12.288.2.50 <code>compliant()</code> [2/2]	655
12.288.2.51 <code>set1()</code> [3/3]	655
12.288.2.52 <code>set()</code> [3/4]	655
12.288.2.53 <code>set()</code> [4/4]	655
12.288.2.54 <code>gather()</code> [3/3]	656
12.288.2.55 <code>load()</code> [3/3]	656
12.288.2.56 <code>loadu()</code> [3/3]	656
12.288.2.57 <code>store()</code> [3/3]	656
12.288.2.58 <code>storeu()</code> [3/3]	656
12.288.2.59 <code>stream()</code> [3/3]	656
12.288.2.60 <code>sll()</code> [1/2]	656
12.288.2.61 <code>sll()</code> [2/2]	656

12.288.2.62 srl() [1/2]	656
12.288.2.63 srl() [2/2]	657
12.288.2.64 shuffle_twice() [1/2]	657
12.288.2.65 shuffle_twice() [2/2]	657
12.288.2.66 shuffle() [1/2]	657
12.288.2.67 shuffle() [2/2]	657
12.288.2.68 unpacklo_intrinsic() [1/2]	657
12.288.2.69 unpacklo_intrinsic() [2/2]	657
12.288.2.70 unpackhi_intrinsic() [1/2]	657
12.288.2.71 unpackhi_intrinsic() [2/2]	657
12.288.2.72 unpacklo() [1/2]	657
12.288.2.73 unpacklo() [2/2]	658
12.288.2.74 unpackhi() [1/2]	658
12.288.2.75 unpackhi() [2/2]	658
12.288.2.76 unpacklohi() [1/2]	658
12.288.2.77 unpacklohi() [2/2]	658
12.288.2.78 pack_even() [1/2]	658
12.288.2.79 pack_even() [2/2]	658
12.288.2.80 pack_odd() [1/2]	658
12.288.2.81 pack_odd() [2/2]	658
12.288.2.82 pack() [1/2]	659
12.288.2.83 pack() [2/2]	659
12.288.2.84 transpose() [1/2]	659
12.288.2.85 transpose() [2/2]	659
12.288.2.86 blend() [1/2]	659
12.288.2.87 blend() [2/2]	659
12.288.2.88 add() [1/2]	660
12.288.2.89 add() [2/2]	660
12.288.2.90 addin() [1/2]	660
12.288.2.91 addin() [2/2]	660
12.288.2.92 sub() [1/2]	660
12.288.2.93 sub() [2/2]	660
12.288.2.94 subin() [1/2]	660
12.288.2.95 subin() [2/2]	660
12.288.2.96 mullo() [1/2]	660
12.288.2.97 mullo() [2/2]	661
12.288.2.98 mul() [1/2]	661
12.288.2.99 mul() [2/2]	661
12.288.2.100 fmadd() [1/2]	661
12.288.2.101 fmadd() [2/2]	661
12.288.2.102 fmaddin() [1/2]	661
12.288.2.103 fmaddin() [2/2]	661

12.288.2.104 fnmadd() [1/2]	661
12.288.2.105 fnmadd() [2/2]	661
12.288.2.106 fnmaddin() [1/2]	662
12.288.2.107 fnmaddin() [2/2]	662
12.288.2.108 fmsub() [1/2]	662
12.288.2.109 fmsub() [2/2]	662
12.288.2.110 fmsubin() [1/2]	662
12.288.2.111 fmsubin() [2/2]	662
12.288.2.112 eq() [1/2]	662
12.288.2.113 eq() [2/2]	662
12.288.2.114 round() [1/2]	662
12.288.2.115 round() [2/2]	663
12.288.2.116 mod() [1/2]	663
12.288.2.117 mod() [2/2]	663
12.288.2.118 zero() [1/2]	663
12.288.2.119 zero() [2/2]	663
12.288.2.120 vor()	663
12.288.2.121 vxor()	663
12.288.2.122 vand()	663
12.288.2.123 vandnot()	663
12.288.3 Field Documentation	664
12.288.3.1 vect_size	664
12.288.3.2 alignment	664
12.289 Simd256_impl< true, true, false, 8 > Struct Reference	664
12.289.1 Member Typedef Documentation	666
12.289.1.1 scalar_t	666
12.289.1.2 aligned_allocator	666
12.289.1.3 aligned_vector	666
12.289.1.4 is_same_element	666
12.289.1.5 simdHalf	666
12.289.1.6 vect_t	666
12.289.1.7 half_t	666
12.289.2 Member Function Documentation	666
12.289.2.1 type_string()	666
12.289.2.2 set1() [1/2]	666
12.289.2.3 set() [1/2]	667
12.289.2.4 gather() [1/2]	667
12.289.2.5 load() [1/2]	667
12.289.2.6 loadu() [1/2]	667
12.289.2.7 store() [1/2]	667
12.289.2.8 storeu() [1/2]	667
12.289.2.9 stream() [1/2]	667

12.289.2.10 sra()	667
12.289.2.11 greater()	667
12.289.2.12 lesser()	667
12.289.2.13 greater_eq()	668
12.289.2.14 lesser_eq()	668
12.289.2.15 mullo()	668
12.289.2.16 mulhi()	668
12.289.2.17 mulx()	668
12.289.2.18 fmaddx()	668
12.289.2.19 fmaddxin()	668
12.289.2.20 fnmaddx()	668
12.289.2.21 fnmaddxin()	668
12.289.2.22 fmsubx()	669
12.289.2.23 fmsubxin()	669
12.289.2.24 hadd_to_scal()	669
12.289.2.25 valid()	669
12.289.2.26 compliant()	669
12.289.2.27 set1() [2/2]	669
12.289.2.28 set() [2/2]	669
12.289.2.29 gather() [2/2]	669
12.289.2.30 get()	669
12.289.2.31 load() [2/2]	669
12.289.2.32 loadu() [2/2]	670
12.289.2.33 store() [2/2]	670
12.289.2.34 storeu() [2/2]	670
12.289.2.35 stream() [2/2]	670
12.289.2.36 sll()	670
12.289.2.37 srl()	670
12.289.2.38 shuffle()	670
12.289.2.39 unpacklo_intrinsic()	670
12.289.2.40 unpackhi_intrinsic()	670
12.289.2.41 unpacklo()	670
12.289.2.42 unpackhi()	671
12.289.2.43 unpacklohi()	671
12.289.2.44 pack_even()	671
12.289.2.45 pack_odd()	671
12.289.2.46 pack()	671
12.289.2.47 transpose()	671
12.289.2.48 blend()	671
12.289.2.49 add()	671
12.289.2.50 addin()	671
12.289.2.51 sub()	672

12.289.2.52 subin()	672
12.289.2.53 mul()	672
12.289.2.54 fmadd()	672
12.289.2.55 fmaddin()	672
12.289.2.56 fnmadd()	672
12.289.2.57 fnmaddin()	672
12.289.2.58 fmsub()	672
12.289.2.59 fmsubin()	672
12.289.2.60 eq()	673
12.289.2.61 round()	673
12.289.2.62 mask_high()	673
12.289.2.63 mulhi_fast()	673
12.289.2.64 mod()	673
12.289.2.65 signbits()	673
12.289.2.66 zero()	673
12.289.3 Field Documentation	673
12.289.3.1 vect_size	673
12.289.3.2 alignment	673
12.290 Simd256_impl< true, true, true, 2 > Struct Reference	674
12.290.1 Member Typedef Documentation	675
12.290.1.1 vect_t	675
12.290.1.2 half_t	675
12.290.1.3 scalar_t	676
12.290.1.4 simdHalf	676
12.290.1.5 aligned_allocator	676
12.290.1.6 aligned_vector	676
12.290.1.7 is_same_element	676
12.290.2 Member Function Documentation	676
12.290.2.1 type_string()	676
12.290.2.2 valid()	676
12.290.2.3 compliant()	676
12.290.2.4 set1()	676
12.290.2.5 set()	676
12.290.2.6 gather()	677
12.290.2.7 load()	677
12.290.2.8 loadu()	677
12.290.2.9 store()	677
12.290.2.10 storeu()	677
12.290.2.11 stream()	677
12.290.2.12 sll()	677
12.290.2.13 srl()	677
12.290.2.14 sra()	677

12.290.2.15 shuffle()	678
12.290.2.16 unpacklo_intrinsic()	678
12.290.2.17 unpackhi_intrinsic()	678
12.290.2.18 unpacklo()	678
12.290.2.19 unpackhi()	678
12.290.2.20 unpacklohi()	678
12.290.2.21 pack_even()	678
12.290.2.22 pack_odd()	678
12.290.2.23 pack()	678
12.290.2.24 transpose()	679
12.290.2.25 blend() [1/2]	679
12.290.2.26 blend() [2/2]	679
12.290.2.27 add()	679
12.290.2.28 addin()	679
12.290.2.29 sub()	679
12.290.2.30 subin()	679
12.290.2.31 mullo()	680
12.290.2.32 mul()	680
12.290.2.33 mulhi()	680
12.290.2.34 mulx()	680
12.290.2.35 fmadd()	680
12.290.2.36 fmaddin()	680
12.290.2.37 fmaddx()	680
12.290.2.38 fmaddxin()	680
12.290.2.39 fnmadd()	680
12.290.2.40 fnmaddin()	681
12.290.2.41 fnmaddx()	681
12.290.2.42 fnmaddxin()	681
12.290.2.43 fmsub()	681
12.290.2.44 fmsubin()	681
12.290.2.45 fmsubx()	681
12.290.2.46 fmsubxin()	681
12.290.2.47 eq()	681
12.290.2.48 greater()	681
12.290.2.49 lesser()	682
12.290.2.50 greater_eq()	682
12.290.2.51 lesser_eq()	682
12.290.2.52 hadd_to_scal()	682
12.290.2.53 round()	682
12.290.2.54 mod()	682
12.290.2.55 zero()	682
12.290.3 Field Documentation	682

12.290.3.1 vect_size	682
12.290.3.2 alignment	682
12.291 Simd256_impl< true, true, true, 4 > Struct Reference	683
12.291.1 Member Typedef Documentation	686
12.291.1.1 vect_t [1/2]	686
12.291.1.2 half_t [1/2]	686
12.291.1.3 scalar_t [1/2]	686
12.291.1.4 simdHalf [1/2]	686
12.291.1.5 aligned_allocator [1/2]	686
12.291.1.6 aligned_vector [1/2]	686
12.291.1.7 is_same_element [1/2]	686
12.291.1.8 vect_t [2/2]	686
12.291.1.9 half_t [2/2]	686
12.291.1.10 scalar_t [2/2]	687
12.291.1.11 simdHalf [2/2]	687
12.291.1.12 aligned_allocator [2/2]	687
12.291.1.13 aligned_vector [2/2]	687
12.291.1.14 is_same_element [2/2]	687
12.291.2 Member Function Documentation	687
12.291.2.1 type_string() [1/2]	687
12.291.2.2 valid() [1/2]	687
12.291.2.3 compliant() [1/2]	687
12.291.2.4 set1() [1/2]	687
12.291.2.5 set() [1/2]	687
12.291.2.6 gather() [1/2]	688
12.291.2.7 load() [1/2]	688
12.291.2.8 loadu() [1/2]	688
12.291.2.9 store() [1/2]	688
12.291.2.10 storeu() [1/2]	688
12.291.2.11 stream() [1/2]	688
12.291.2.12 sll() [1/2]	688
12.291.2.13 srl() [1/2]	688
12.291.2.14 sra() [1/2]	688
12.291.2.15 shuffle_twice() [1/2]	688
12.291.2.16 shuffle() [1/2]	689
12.291.2.17 unpacklo_intrinsic() [1/2]	689
12.291.2.18 unpackhi_intrinsic() [1/2]	689
12.291.2.19 unpacklo() [1/2]	689
12.291.2.20 unpackhi() [1/2]	689
12.291.2.21 unpacklohi() [1/2]	689
12.291.2.22 pack_even() [1/2]	689
12.291.2.23 pack_odd() [1/2]	689

12.291.2.24 pack() [1/2]	689
12.291.2.25 transpose() [1/2]	690
12.291.2.26 blend() [1/2]	690
12.291.2.27 add() [1/2]	690
12.291.2.28 addin() [1/2]	690
12.291.2.29 sub() [1/2]	690
12.291.2.30 subin() [1/2]	690
12.291.2.31 mullo() [1/2]	690
12.291.2.32 mul() [1/2]	690
12.291.2.33 mulhi() [1/2]	690
12.291.2.34 mulx() [1/2]	691
12.291.2.35 fmadd() [1/2]	691
12.291.2.36 fmaddin() [1/2]	691
12.291.2.37 fmaddx() [1/2]	691
12.291.2.38 fmaddxin() [1/2]	691
12.291.2.39 fnmadd() [1/2]	691
12.291.2.40 fnmaddin() [1/2]	691
12.291.2.41 fnmaddx() [1/2]	691
12.291.2.42 fnmaddxin() [1/2]	691
12.291.2.43 fmsub() [1/2]	692
12.291.2.44 fmsubin() [1/2]	692
12.291.2.45 fmsubx() [1/2]	692
12.291.2.46 fmsubxin() [1/2]	692
12.291.2.47 eq() [1/2]	692
12.291.2.48 greater() [1/2]	692
12.291.2.49 lesser() [1/2]	692
12.291.2.50 greater_eq() [1/2]	692
12.291.2.51 lesser_eq() [1/2]	692
12.291.2.52 hadd_to_scal() [1/2]	693
12.291.2.53 round() [1/2]	693
12.291.2.54 mod() [1/2]	693
12.291.2.55 type_string() [2/2]	693
12.291.2.56 valid() [2/2]	693
12.291.2.57 compliant() [2/2]	693
12.291.2.58 set1() [2/2]	693
12.291.2.59 set() [2/2]	693
12.291.2.60 gather() [2/2]	694
12.291.2.61 load() [2/2]	694
12.291.2.62 loadu() [2/2]	694
12.291.2.63 store() [2/2]	694
12.291.2.64 storeu() [2/2]	694
12.291.2.65 stream() [2/2]	694

12.291.2.66 sll() [2/2]	694
12.291.2.67 srl() [2/2]	694
12.291.2.68 sra() [2/2]	694
12.291.2.69 shuffle_twice() [2/2]	695
12.291.2.70 shuffle() [2/2]	695
12.291.2.71 unpacklo_intrinsic() [2/2]	695
12.291.2.72 unpackhi_intrinsic() [2/2]	695
12.291.2.73 unpacklo() [2/2]	695
12.291.2.74 unpackhi() [2/2]	695
12.291.2.75 unpacklohi() [2/2]	695
12.291.2.76 pack_even() [2/2]	695
12.291.2.77 pack_odd() [2/2]	695
12.291.2.78 pack() [2/2]	696
12.291.2.79 transpose() [2/2]	696
12.291.2.80 blend() [2/2]	696
12.291.2.81 add() [2/2]	696
12.291.2.82 addin() [2/2]	696
12.291.2.83 sub() [2/2]	696
12.291.2.84 subin() [2/2]	696
12.291.2.85 mullo() [2/2]	697
12.291.2.86 mul() [2/2]	697
12.291.2.87 mulhi() [2/2]	697
12.291.2.88 mulx() [2/2]	697
12.291.2.89 fmadd() [2/2]	697
12.291.2.90 fmaddin() [2/2]	697
12.291.2.91 fmaddx() [2/2]	697
12.291.2.92 fmaddxin() [2/2]	697
12.291.2.93 fnmadd() [2/2]	697
12.291.2.94 fnmaddin() [2/2]	698
12.291.2.95 fnmaddx() [2/2]	698
12.291.2.96 fnmaddxin() [2/2]	698
12.291.2.97 fmsub() [2/2]	698
12.291.2.98 fmsubin() [2/2]	698
12.291.2.99 fmsubx() [2/2]	698
12.291.2.100 fmsubxin() [2/2]	698
12.291.2.101 eq() [2/2]	698
12.291.2.102 greater() [2/2]	698
12.291.2.103 lesser() [2/2]	699
12.291.2.104 greater_eq() [2/2]	699
12.291.2.105 lesser_eq() [2/2]	699
12.291.2.106 hadd_to_scal() [2/2]	699
12.291.2.107 round() [2/2]	699

12.291.2.108 mod() [2/2]	699
12.291.2.109 zero() [1/2]	699
12.291.2.110 zero() [2/2]	699
12.291.2.111 vor()	699
12.291.2.112 vxor()	699
12.291.2.113 vand()	700
12.291.2.114 vandnot()	700
12.291.3 Field Documentation	700
12.291.3.1 vect_size	700
12.291.3.2 alignment	700
12.292 Simd256_impl< true, true, true, 8 > Struct Reference	700
12.292.1 Member Typedef Documentation	702
12.292.1.1 vect_t	702
12.292.1.2 half_t	702
12.292.1.3 scalar_t	702
12.292.1.4 simdHalf	702
12.292.1.5 aligned_allocator	702
12.292.1.6 aligned_vector	702
12.292.1.7 is_same_element	702
12.292.2 Member Function Documentation	702
12.292.2.1 type_string()	702
12.292.2.2 valid()	703
12.292.2.3 compliant()	703
12.292.2.4 set1()	703
12.292.2.5 set()	703
12.292.2.6 gather()	703
12.292.2.7 get()	703
12.292.2.8 load()	703
12.292.2.9 loadu()	703
12.292.2.10 store()	703
12.292.2.11 storeu()	703
12.292.2.12 stream()	704
12.292.2.13 sll()	704
12.292.2.14 srl()	704
12.292.2.15 sra()	704
12.292.2.16 shuffle()	704
12.292.2.17 unpacklo_intrinsic()	704
12.292.2.18 unpackhi_intrinsic()	704
12.292.2.19 unpacklo()	704
12.292.2.20 unpackhi()	704
12.292.2.21 unpacklohi()	704
12.292.2.22 pack_even()	705

12.292.2.23	pack_odd()	705
12.292.2.24	pack()	705
12.292.2.25	transpose()	705
12.292.2.26	blend()	705
12.292.2.27	add()	705
12.292.2.28	addin()	705
12.292.2.29	sub()	705
12.292.2.30	subin()	705
12.292.2.31	mullo()	706
12.292.2.32	mul()	706
12.292.2.33	mulhi()	706
12.292.2.34	mulx()	706
12.292.2.35	fmadd()	706
12.292.2.36	fmaddin()	706
12.292.2.37	fmaddx()	706
12.292.2.38	fmaddxin()	706
12.292.2.39	fnmadd()	706
12.292.2.40	fnmaddin()	707
12.292.2.41	fnmaddx()	707
12.292.2.42	fnmaddxin()	707
12.292.2.43	fmsub()	707
12.292.2.44	fmsubin()	707
12.292.2.45	fmsubx()	707
12.292.2.46	fmsubxin()	707
12.292.2.47	eq()	707
12.292.2.48	greater()	707
12.292.2.49	lesser()	708
12.292.2.50	greater_eq()	708
12.292.2.51	lesser_eq()	708
12.292.2.52	hadd_to_scal()	708
12.292.2.53	round()	708
12.292.2.54	mask_high()	708
12.292.2.55	mulhi_fast()	708
12.292.2.56	mod()	708
12.292.2.57	signbits()	708
12.292.2.58	zero()	708
12.292.3	Field Documentation	709
12.292.3.1	vect_size	709
12.292.3.2	alignment	709
12.293	Simd256fp_base Struct Reference	709
12.294	Simd256i_base Struct Reference	709
12.294.1	Member Typedef Documentation	709

12.294.1.1 vect_t	709
12.294.2 Member Function Documentation	709
12.294.2.1 zero()	709
12.295 Simd512_impl< ArithType, Int, Signed, Size > Struct Template Reference	710
12.296 Simd512_impl< true, false, true, 4 > Struct Reference	710
12.297 Simd512_impl< true, false, true, 8 > Struct Reference	710
12.297.1 Member Typedef Documentation	711
12.297.1.1 vect_t	711
12.297.1.2 scalar_t	711
12.297.1.3 aligned_allocator	711
12.297.1.4 aligned_vector	711
12.297.1.5 is_same_element	711
12.297.2 Member Function Documentation	711
12.297.2.1 type_string()	711
12.297.2.2 valid()	712
12.297.2.3 compliant()	712
12.297.2.4 zero()	712
12.297.2.5 set1()	712
12.297.2.6 set()	712
12.297.2.7 gather()	712
12.297.2.8 load()	712
12.297.2.9 loadu()	712
12.297.2.10 store()	712
12.297.2.11 storeu()	712
12.297.2.12 stream()	713
12.297.2.13 shuffle()	713
12.297.2.14 unpacklo_intrinsic()	713
12.297.2.15 unpackhi_intrinsic()	713
12.297.2.16 unpacklo()	713
12.297.2.17 unpackhi()	713
12.297.2.18 unpacklohi()	713
12.297.2.19 pack_even()	713
12.297.2.20 pack_odd()	713
12.297.2.21 pack()	714
12.297.2.22 transpose()	714
12.297.2.23 blend()	714
12.297.2.24 blendv()	714
12.297.2.25 add()	714
12.297.2.26 addin()	714
12.297.2.27 sub()	714
12.297.2.28 subin()	714
12.297.2.29 mul()	715

12.297.2.30	mulin()	715
12.297.2.31	div()	715
12.297.2.32	fmadd()	715
12.297.2.33	fmaddin()	715
12.297.2.34	fnmadd()	715
12.297.2.35	fnmaddin()	715
12.297.2.36	fmsub()	715
12.297.2.37	fmsubin()	715
12.297.2.38	eq()	716
12.297.2.39	lesser()	716
12.297.2.40	lesser_eq()	716
12.297.2.41	greater()	716
12.297.2.42	greater_eq()	716
12.297.2.43	floor()	716
12.297.2.44	ceil()	716
12.297.2.45	round()	716
12.297.2.46	hadd()	716
12.297.2.47	hadd_to_scal()	716
12.297.3	Field Documentation	716
12.297.3.1	vect_size	716
12.297.3.2	alignment	717
12.298	Simd512_impl< true, true, false, 8 > Struct Reference	717
12.298.1	Member Typedef Documentation	719
12.298.1.1	scalar_t	719
12.298.1.2	aligned_allocator	719
12.298.1.3	aligned_vector	719
12.298.1.4	is_same_element	719
12.298.1.5	simdHalf	719
12.298.1.6	vect_t	719
12.298.1.7	half_t	719
12.298.2	Member Function Documentation	719
12.298.2.1	type_string()	719
12.298.2.2	set1() [1/2]	720
12.298.2.3	set() [1/3]	720
12.298.2.4	gather() [1/2]	720
12.298.2.5	load() [1/2]	720
12.298.2.6	loadu() [1/2]	720
12.298.2.7	store() [1/2]	720
12.298.2.8	maskstore() [1/2]	720
12.298.2.9	storeu() [1/2]	720
12.298.2.10	stream() [1/2]	720
12.298.2.11	sra()	721

12.298.2.12 greater()	721
12.298.2.13 lesser()	721
12.298.2.14 greater_eq()	721
12.298.2.15 lesser_eq()	721
12.298.2.16 mullo()	721
12.298.2.17 mulhi()	721
12.298.2.18 mulx()	721
12.298.2.19 fmaddx()	721
12.298.2.20 fmaddxin()	721
12.298.2.21 fnmaddx()	722
12.298.2.22 fnmaddxin()	722
12.298.2.23 fmsubx()	722
12.298.2.24 fmsubxin()	722
12.298.2.25 hadd_to_scal()	722
12.298.2.26 valid()	722
12.298.2.27 compliant()	722
12.298.2.28 set1() [2/2]	722
12.298.2.29 set() [2/3]	722
12.298.2.30 set() [3/3]	723
12.298.2.31 gather() [2/2]	723
12.298.2.32 load() [2/2]	723
12.298.2.33 loadu() [2/2]	723
12.298.2.34 store() [2/2]	723
12.298.2.35 maskstore() [2/2]	723
12.298.2.36 storeu() [2/2]	723
12.298.2.37 stream() [2/2]	723
12.298.2.38 sll()	723
12.298.2.39 srl()	724
12.298.2.40 shuffle()	724
12.298.2.41 unpacklo_intrinsic()	724
12.298.2.42 unpackhi_intrinsic()	724
12.298.2.43 unpacklo()	724
12.298.2.44 unpackhi()	724
12.298.2.45 unpacklohi()	724
12.298.2.46 pack_even()	724
12.298.2.47 pack_odd()	724
12.298.2.48 pack()	725
12.298.2.49 transpose()	725
12.298.2.50 blend()	725
12.298.2.51 add()	725
12.298.2.52 addin()	725
12.298.2.53 sub()	725

12.298.2.54 subin()	725
12.298.2.55 mul()	725
12.298.2.56 fmadd()	726
12.298.2.57 fmaddin()	726
12.298.2.58 fnmadd()	726
12.298.2.59 fnmaddin()	726
12.298.2.60 fmsub()	726
12.298.2.61 fmsubin()	726
12.298.2.62 eq()	726
12.298.2.63 round()	726
12.298.2.64 mask_high()	726
12.298.2.65 mulhi_fast()	727
12.298.2.66 mod()	727
12.298.2.67 signbits()	727
12.298.2.68 zero()	727
12.298.2.69 vor()	727
12.298.2.70 vxor()	727
12.298.2.71 vand()	727
12.298.2.72 vandnot()	727
12.298.3 Field Documentation	727
12.298.3.1 vect_size	727
12.298.3.2 alignment	728
12.299 Simd512_impl< true, true, true, 8 > Struct Reference	728
12.299.1 Member Typedef Documentation	730
12.299.1.1 vect_t	730
12.299.1.2 half_t	730
12.299.1.3 scalar_t	730
12.299.1.4 simdHalf	730
12.299.1.5 aligned_allocator	730
12.299.1.6 aligned_vector	730
12.299.1.7 is_same_element	730
12.299.2 Member Function Documentation	730
12.299.2.1 type_string()	730
12.299.2.2 valid()	730
12.299.2.3 compliant()	730
12.299.2.4 set1()	731
12.299.2.5 set() [1/2]	731
12.299.2.6 set() [2/2]	731
12.299.2.7 gather()	731
12.299.2.8 load()	731
12.299.2.9 loadu()	731
12.299.2.10 store()	731

12.299.2.11 maskstore()	731
12.299.2.12 storeu()	731
12.299.2.13 stream()	732
12.299.2.14 sll()	732
12.299.2.15 srl()	732
12.299.2.16 sra()	732
12.299.2.17 shuffle()	732
12.299.2.18 unpacklo_intrinsic()	732
12.299.2.19 unpackhi_intrinsic()	732
12.299.2.20 unpacklo()	732
12.299.2.21 unpackhi()	732
12.299.2.22 unpacklohi()	732
12.299.2.23 pack_even()	733
12.299.2.24 pack_odd()	733
12.299.2.25 pack()	733
12.299.2.26 transpose()	733
12.299.2.27 blend()	733
12.299.2.28 add()	733
12.299.2.29 addin()	733
12.299.2.30 sub()	733
12.299.2.31 subin()	734
12.299.2.32 mullo()	734
12.299.2.33 mul()	734
12.299.2.34 mulhi()	734
12.299.2.35 mulx()	734
12.299.2.36 fmadd()	734
12.299.2.37 fmaddin()	734
12.299.2.38 fmaddx()	734
12.299.2.39 fmaddxin()	734
12.299.2.40 fnmadd()	735
12.299.2.41 fnmaddin()	735
12.299.2.42 fnmaddx()	735
12.299.2.43 fnmaddxin()	735
12.299.2.44 fmsub()	735
12.299.2.45 fmsubin()	735
12.299.2.46 fmsubx()	735
12.299.2.47 fmsubxin()	735
12.299.2.48 eq()	736
12.299.2.49 greater()	736
12.299.2.50 lesser()	736
12.299.2.51 greater_eq()	736
12.299.2.52 lesser_eq()	736

12.299.2.53 hadd_to_scal()	736
12.299.2.54 round()	736
12.299.2.55 mask_high()	736
12.299.2.56 mulhi_fast()	736
12.299.2.57 mod()	736
12.299.2.58 signbits()	737
12.299.2.59 zero()	737
12.299.2.60 vor()	737
12.299.2.61 vxor()	737
12.299.2.62 vand()	737
12.299.2.63 vandnot()	737
12.299.3 Field Documentation	737
12.299.3.1 vect_size	737
12.299.3.2 alignment	737
12.300 Simd512i_base Struct Reference	737
12.300.1 Member Typedef Documentation	738
12.300.1.1 vect_t	738
12.300.2 Member Function Documentation	738
12.300.2.1 zero()	738
12.300.2.2 vor()	738
12.300.2.3 vxor()	738
12.300.2.4 vand()	738
12.300.2.5 vandnot()	738
12.301 SimdChooser< T, bool, bool > Struct Template Reference	739
12.302 SimdChooser< T, false, b > Struct Template Reference	739
12.302.1 Member Typedef Documentation	739
12.302.1.1 value	739
12.303 SimdChooser< T, true, false > Struct Template Reference	739
12.303.1 Member Typedef Documentation	739
12.303.1.1 value	739
12.304 SimdChooser< T, true, true > Struct Template Reference	739
12.304.1 Member Typedef Documentation	739
12.304.1.1 value	739
12.305 simdToType< T > Struct Template Reference	740
12.306 Single Struct Reference	740
12.307 Sparse< Field, SparseMatrix_t, IdxT, PtrT > Struct Template Reference	740
12.308 Sparse< _Field, SparseMatrix_t::COO > Struct Template Reference	740
12.308.1 Member Typedef Documentation	740
12.308.1.1 Field	740
12.308.2 Field Documentation	741
12.308.2.1 col	741
12.308.2.2 row	741

12.308.2.3 dat	741
12.308.2.4 delayed	741
12.308.2.5 kmax	741
12.308.2.6 m	741
12.308.2.7 n	741
12.308.2.8 nnz	741
12.308.2.9 nElements	741
12.308.2.10 maxrow	741
12.309 Sparse< _Field, SparseMatrix_t::COO_ZO > Struct Template Reference	741
12.309.1 Member Typedef Documentation	742
12.309.1.1 Field	742
12.309.2 Field Documentation	742
12.309.2.1 cst	742
12.309.2.2 col	742
12.309.2.3 row	742
12.309.2.4 dat	742
12.309.2.5 delayed	742
12.309.2.6 kmax	743
12.309.2.7 m	743
12.309.2.8 n	743
12.309.2.9 nnz	743
12.309.2.10 nElements	743
12.309.2.11 maxrow	743
12.310 Sparse< _Field, SparseMatrix_t::CSR > Struct Template Reference	743
12.310.1 Member Typedef Documentation	744
12.310.1.1 Field	744
12.310.2 Field Documentation	744
12.310.2.1 delayed	744
12.310.2.2 kmax	744
12.310.2.3 m	744
12.310.2.4 n	744
12.310.2.5 nnz	744
12.310.2.6 nElements	744
12.310.2.7 maxrow	744
12.310.2.8 col	744
12.310.2.9 st	744
12.310.2.10 stend	745
12.310.2.11 dat	745
12.311 Sparse< _Field, SparseMatrix_t::CSR_HYB > Struct Template Reference	745
12.311.1 Member Typedef Documentation	745
12.311.1.1 Field	745
12.311.2 Field Documentation	745

12.311.2.1 delayed	745
12.311.2.2 col	745
12.311.2.3 st	746
12.311.2.4 dat	746
12.311.2.5 kmax	746
12.311.2.6 m	746
12.311.2.7 n	746
12.311.2.8 nnz	746
12.311.2.9 nElements	746
12.311.2.10 maxrow	746
12.311.2.11 nOnes	746
12.311.2.12 nMOnes	746
12.311.2.13 nOthers	746
12.312 Sparse< _Field, SparseMatrix_t::CSR_ZO > Struct Template Reference	747
12.312.1 Member Typedef Documentation	747
12.312.1.1 Field	747
12.312.2 Field Documentation	747
12.312.2.1 cst	747
12.312.2.2 delayed	747
12.312.2.3 kmax	747
12.312.2.4 m	747
12.312.2.5 n	748
12.312.2.6 nnz	748
12.312.2.7 nElements	748
12.312.2.8 maxrow	748
12.312.2.9 col	748
12.312.2.10 st	748
12.312.2.11 stend	748
12.312.2.12 dat	748
12.313 Sparse< _Field, SparseMatrix_t::ELL > Struct Template Reference	748
12.313.1 Member Typedef Documentation	749
12.313.1.1 Field	749
12.313.2 Field Documentation	749
12.313.2.1 delayed	749
12.313.2.2 kmax	749
12.313.2.3 m	749
12.313.2.4 n	749
12.313.2.5 ld	749
12.313.2.6 nnz	749
12.313.2.7 nElements	749
12.313.2.8 maxrow	749
12.313.2.9 col	750

12.313.2.10 dat	750
12.314 Sparse< _Field, SparseMatrix_t::ELL_simd > Struct Template Reference	750
12.314.1 Field Documentation	750
12.314.1.1 delayed	750
12.314.1.2 chunk	750
12.314.1.3 m	750
12.314.1.4 n	751
12.314.1.5 ld	751
12.314.1.6 kmax	751
12.314.1.7 nnz	751
12.314.1.8 nElements	751
12.314.1.9 maxrow	751
12.314.1.10 nChunks	751
12.314.1.11 col	751
12.314.1.12 dat	751
12.315 Sparse< _Field, SparseMatrix_t::ELL_simd_ZO > Struct Template Reference	751
12.315.1 Field Documentation	752
12.315.1.1 cst	752
12.315.1.2 delayed	752
12.315.1.3 chunk	752
12.315.1.4 m	752
12.315.1.5 n	752
12.315.1.6 ld	752
12.315.1.7 kmax	752
12.315.1.8 nnz	752
12.315.1.9 nElements	753
12.315.1.10 maxrow	753
12.315.1.11 nChunks	753
12.315.1.12 col	753
12.315.1.13 dat	753
12.316 Sparse< _Field, SparseMatrix_t::ELL_ZO > Struct Template Reference	753
12.316.1 Member Typedef Documentation	754
12.316.1.1 Field	754
12.316.2 Field Documentation	754
12.316.2.1 cst	754
12.316.2.2 delayed	754
12.316.2.3 kmax	754
12.316.2.4 m	754
12.316.2.5 n	754
12.316.2.6 ld	754
12.316.2.7 nnz	754
12.316.2.8 nElements	754

12.316.2.9 maxrow	754
12.316.2.10 col	754
12.316.2.11 dat	755
12.317 Sparse< _Field, SparseMatrix_t::HYB_ZO > Struct Template Reference	755
12.317.1 Member Typedef Documentation	755
12.317.1.1 Field	755
12.317.1.2 Self_t	755
12.317.2 Field Documentation	755
12.317.2.1 delayed	755
12.317.2.2 kmax	755
12.317.2.3 m	755
12.317.2.4 n	756
12.317.2.5 nnz	756
12.317.2.6 maxrow	756
12.317.2.7 nElements	756
12.317.2.8 dat	756
12.317.2.9 one	756
12.317.2.10 mone	756
12.318 Sparse< _Field, SparseMatrix_t::SELL > Struct Template Reference	756
12.318.1 Member Typedef Documentation	757
12.318.1.1 Field	757
12.318.2 Field Documentation	757
12.318.2.1 delayed	757
12.318.2.2 chunk	757
12.318.2.3 kmax	757
12.318.2.4 m	757
12.318.2.5 n	757
12.318.2.6 maxrow	757
12.318.2.7 sigma	758
12.318.2.8 nChunks	758
12.318.2.9 nnz	758
12.318.2.10 nElements	758
12.318.2.11 perm	758
12.318.2.12 st	758
12.318.2.13 chunkSize	758
12.318.2.14 col	758
12.318.2.15 dat	758
12.319 Sparse< _Field, SparseMatrix_t::SELL_ZO > Struct Template Reference	758
12.319.1 Member Typedef Documentation	759
12.319.1.1 Field	759
12.319.2 Field Documentation	759
12.319.2.1 cst	759

12.319.2.2 delayed	759
12.319.2.3 chunk	759
12.319.2.4 kmax	759
12.319.2.5 m	759
12.319.2.6 n	760
12.319.2.7 maxrow	760
12.319.2.8 sigma	760
12.319.2.9 nChunks	760
12.319.2.10 nnz	760
12.319.2.11 nElements	760
12.319.2.12 perm	760
12.319.2.13 st	760
12.319.2.14 chunkSize	760
12.319.2.15 col	760
12.319.2.16 dat	760
12.320 SpMat< Field, flag > Struct Template Reference	760
12.320.1 Field Documentation	761
12.320.1.1 _coo	761
12.320.1.2 _csr	761
12.320.1.3 _ell	761
12.321 StatsMatrix Struct Reference	761
12.321.1 Field Documentation	762
12.321.1.1 rowdim	762
12.321.1.2 coldim	762
12.321.1.3 nOnes	762
12.321.1.4 nMOnes	762
12.321.1.5 nOthers	762
12.321.1.6 nnz	762
12.321.1.7 maxRow	762
12.321.1.8 minRow	762
12.321.1.9 averageRow	762
12.321.1.10 deviationRow	762
12.321.1.11 maxCol	762
12.321.1.12 minCol	762
12.321.1.13 averageCol	762
12.321.1.14 deviationCol	763
12.321.1.15 minColDifference	763
12.321.1.16 maxColDifference	763
12.321.1.17 averageColDifference	763
12.321.1.18 deviationColDifference	763
12.321.1.19 minRowDifference	763
12.321.1.20 maxRowDifference	763

12.321.1.21 averageRowDifference	763
12.321.1.22 deviationRowDifference	763
12.321.1.23 nDenseRows	763
12.321.1.24 nDenseCols	763
12.321.1.25 nEmptyRows	763
12.321.1.26 nEmptyCols	763
12.321.1.27 nEmptyColsEnd	763
12.321.1.28 denseRows	763
12.321.1.29 denseCols	764
12.322 support_fast_mod< T > Struct Template Reference	764
12.323 support_fast_mod< double > Struct Reference	764
12.324 support_fast_mod< float > Struct Reference	764
12.325 support_fast_mod< int64_t > Struct Reference	764
12.326 support_simd< T > Struct Template Reference	765
12.327 support_simd_add< T > Struct Template Reference	765
12.328 support_simd_mod< T > Struct Template Reference	765
12.329 Test< Elt > Class Template Reference	766
12.329.1 Member Typedef Documentation	766
12.329.1.1 Field	766
12.329.1.2 Elt_ptr	766
12.329.1.3 Residu	766
12.329.1.4 enable_if_t	767
12.329.1.5 is_same_element	767
12.329.1.6 enable_if_no_simd_t	767
12.329.1.7 enable_if_simd128_t	767
12.329.1.8 enable_if_simd256_t	767
12.329.1.9 enable_if_simd512_t	767
12.329.2 Constructor & Destructor Documentation	767
12.329.2.1 Test()	767
12.329.3 Member Function Documentation	767
12.329.3.1 cardinality() [1/2]	767
12.329.3.2 cardinality() [2/2]	767
12.329.3.3 test_ftranspose()	768
12.329.3.4 doTests()	768
12.329.3.5 run()	768
12.329.4 Field Documentation	768
12.329.4.1 F	768
12.329.4.2 _mm	768
12.329.4.3 _nn	768
12.330 TestOneMethod< Simd > Class Template Reference	768
12.330.1 Member Typedef Documentation	769
12.330.1.1 Element	769

12.330.1.2 vect_t	769
12.330.1.3 vectElt	769
12.330.1.4 enable_if_t	770
12.330.2 Constructor & Destructor Documentation	770
12.330.2.1 TestOneMethod()	770
12.330.3 Member Function Documentation	770
12.330.3.1 evaluate_scalar_method() [1/3]	770
12.330.3.2 evaluate_scalar_method() [2/3]	770
12.330.3.3 evaluate_scalar_method() [3/3]	770
12.330.3.4 evaluate_simd_method() [1/2]	770
12.330.3.5 evaluate_simd_method() [2/2]	770
12.330.3.6 getStatus()	771
12.330.3.7 getTestName()	771
12.330.3.8 writeResultLine()	771
12.330.3.9 writeDebugData()	771
12.330.4 Field Documentation	771
12.330.4.1 vect_size	771
12.330.4.2 nb_lref	771
12.330.4.3 name	771
12.330.4.4 inputs	771
12.330.4.5 outputs_simd	771
12.330.4.6 outputs_scalar	771
12.331 tfn_minus Struct Reference	772
12.331.1 Member Function Documentation	772
12.331.1.1 operator>()	772
12.332 tfn_minus_eq Struct Reference	772
12.332.1 Member Function Documentation	772
12.332.1.1 operator>()	772
12.333 tfn_mul Struct Reference	772
12.333.1 Member Function Documentation	772
12.333.1.1 operator>()	772
12.334 tfn_mul_eq Struct Reference	773
12.334.1 Member Function Documentation	773
12.334.1.1 operator>()	773
12.335 tfn_plus Struct Reference	773
12.335.1 Member Function Documentation	773
12.335.1.1 operator>()	773
12.336 tfn_plus_eq Struct Reference	773
12.336.1 Member Function Documentation	773
12.336.1.1 operator>()	773
12.337 Threads Struct Reference	774
12.338 ThreeD Struct Reference	774

12.339 ThreeDAdaptive Struct Reference	774
12.340 ThreeDInPlace Struct Reference	774
12.341 TRSMHelper< ReclterTrait, ParSeqTrait > Struct Template Reference	774
12.341.1 Detailed Description	775
12.341.2 Constructor & Destructor Documentation	775
12.341.2.1 TRSMHelper() [1/3]	775
12.341.2.2 TRSMHelper() [2/3]	775
12.341.2.3 TRSMHelper() [3/3]	775
12.341.3 Member Function Documentation	775
12.341.3.1 pMMH() [1/2]	775
12.341.3.2 pMMH() [2/2]	775
12.341.4 Field Documentation	776
12.341.4.1 parseq	776
12.342 TwoD Struct Reference	776
12.343 TwoDAdaptive Struct Reference	776
12.344 UnparametricTag Struct Reference	776
12.344.1 Detailed Description	776
12.345 width< T > Struct Template Reference	776
12.345.1 Field Documentation	776
12.345.1.1 value	776
12.346 width< double > Struct Reference	776
12.346.1 Field Documentation	777
12.346.1.1 value	777
12.347 width< float > Struct Reference	777
12.347.1 Field Documentation	777
12.347.1.1 value	777
12.348 Winograd Struct Reference	777
12.349 WinogradPar Struct Reference	777
13 File Documentation	779
13.1 arithprog.C File Reference	779
13.1.1 Macro Definition Documentation	779
13.1.1.1 CUBE	779
13.1.1.2 GFOPS	779
13.1.2 Typedef Documentation	779
13.1.2.1 TTimer	779
13.1.3 Function Documentation	780
13.1.3.1 main()	780
13.2 fsyrk.C File Reference	780
13.2.1 Macro Definition Documentation	780
13.2.1.1 CUBE	780
13.2.1.2 GFOPS	780

13.2.2 Typedef Documentation	780
13.2.2.1 TTimer	780
13.2.3 Function Documentation	780
13.2.3.1 main()	780
13.3 fsytrf.C File Reference	781
13.3.1 Macro Definition Documentation	781
13.3.1.1 CUBE	781
13.3.1.2 GFOPS	781
13.3.2 Typedef Documentation	781
13.3.2.1 TTimer	781
13.3.3 Function Documentation	781
13.3.3.1 main()	781
13.4 ftrtri.C File Reference	781
13.4.1 Macro Definition Documentation	782
13.4.1.1 CUBE	782
13.4.1.2 GFOPS	782
13.4.2 Typedef Documentation	782
13.4.2.1 TTimer	782
13.4.3 Function Documentation	782
13.4.3.1 main()	782
13.5 winograd.C File Reference	782
13.5.1 Macro Definition Documentation	783
13.5.1.1 DOUBLE_TO_FLOAT_CROSSOVER	783
13.5.1.2 GFOPS	783
13.5.2 Typedef Documentation	783
13.5.2.1 TTimer	783
13.5.3 Function Documentation	783
13.5.3.1 balanced() [1/2]	783
13.5.3.2 balanced() [2/2]	783
13.5.3.3 main()	783
13.6 benchmark-charpoly-mp.C File Reference	783
13.6.1 Macro Definition Documentation	784
13.6.1.1 __FFLASFFPACK_FORCE_SEQ	784
13.6.2 Function Documentation	784
13.6.2.1 main()	784
13.7 benchmark-charpoly.C File Reference	784
13.7.1 Macro Definition Documentation	784
13.7.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	784
13.7.2 Function Documentation	784
13.7.2.1 run_with_field()	784
13.7.2.2 main()	785
13.8 benchmark-checkers.C File Reference	785

13.8.1 Macro Definition Documentation	785
13.8.1.1 ENABLE_ALL_CHECKINGS	785
13.8.1.2 _NR_TESTS	785
13.8.1.3 _MAX_SIZE_MATRICES	785
13.8.1.4 CUBE	785
13.8.2 Function Documentation	786
13.8.2.1 main()	786
13.9 benchmark-dgemm.C File Reference	786
13.9.1 Macro Definition Documentation	786
13.9.1.1 CBLAS_GEMM	786
13.9.2 Typedef Documentation	786
13.9.2.1 TTimer	786
13.9.2.2 Floats	786
13.9.3 Function Documentation	786
13.9.3.1 main()	786
13.10 benchmark-dgetrf.C File Reference	787
13.10.1 Macro Definition Documentation	787
13.10.1.1 __FFLASFFPACK_HAVE_DGETRF	787
13.10.2 Typedef Documentation	787
13.10.2.1 TTimer	787
13.10.3 Function Documentation	787
13.10.3.1 main()	787
13.11 benchmark-dgetri.C File Reference	787
13.11.1 Typedef Documentation	788
13.11.1.1 TTimer	788
13.11.2 Function Documentation	788
13.11.2.1 main()	788
13.12 benchmark-dsytrf.C File Reference	788
13.12.1 Macro Definition Documentation	788
13.12.1.1 EFFGFF	788
13.12.2 Typedef Documentation	788
13.12.2.1 TTimer	788
13.12.3 Function Documentation	789
13.12.3.1 main()	789
13.13 benchmark-dtrsm.C File Reference	789
13.13.1 Typedef Documentation	789
13.13.1.1 TTimer	789
13.13.2 Function Documentation	789
13.13.2.1 main()	789
13.14 benchmark-dtrtri.C File Reference	789
13.14.1 Macro Definition Documentation	790
13.14.1.1 __FFLASFFPACK_HAVE_DTRTRI	790

13.14.2 Typedef Documentation	790
13.14.2.1 TTimer	790
13.14.3 Function Documentation	790
13.14.3.1 main()	790
13.15 benchmark-fadd-lvl2.C File Reference	790
13.15.1 Macro Definition Documentation	790
13.15.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	790
13.15.2 Function Documentation	790
13.15.2.1 main()	790
13.16 benchmark-fdot.C File Reference	791
13.16.1 Macro Definition Documentation	791
13.16.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	791
13.16.2 Function Documentation	791
13.16.2.1 run_with_field()	791
13.16.2.2 main()	791
13.17 benchmark-fgemm-mp.C File Reference	791
13.17.1 Macro Definition Documentation	792
13.17.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	792
13.17.1.2 MG_DEFAULT	792
13.17.1.3 STD_RECINT_SIZE	792
13.17.2 Function Documentation	792
13.17.2.1 tmain()	792
13.17.2.2 main()	792
13.18 benchmark-fgemm-rns.C File Reference	792
13.18.1 Macro Definition Documentation	793
13.18.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	793
13.18.2 Typedef Documentation	793
13.18.2.1 RNS	793
13.18.2.2 Field	793
13.18.2.3 Element_ptr	793
13.18.2.4 ConstElement_ptr	793
13.18.2.5 THREADS	793
13.18.2.6 GRAIN	793
13.18.2.7 TWOD	793
13.18.2.8 TWODA	793
13.18.2.9 THREED	794
13.18.2.10 THREEDA	794
13.18.2.11 THREEDIP	794
13.18.2.12 PSeq	794
13.18.3 Function Documentation	794
13.18.3.1 main()	794
13.19 benchmark-fgemm.C File Reference	794

13.19.1 Macro Definition Documentation	794
13.19.1.1 CLASSIC_HYBRID	794
13.19.2 Function Documentation	794
13.19.2.1 main()	794
13.20 benchmark-fgemv-mp.C File Reference	795
13.20.1 Macro Definition Documentation	795
13.20.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	795
13.20.1.2 MG_DEFAULT	795
13.20.1.3 STD_RECINT_SIZE	795
13.20.2 Function Documentation	795
13.20.2.1 write_matrix()	795
13.20.2.2 tmain()	795
13.20.2.3 main()	796
13.21 benchmark-fgemv.C File Reference	796
13.21.1 Macro Definition Documentation	797
13.21.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	797
13.21.2 Function Documentation	797
13.21.2.1 fill_value()	797
13.21.2.2 genData()	797
13.21.2.3 check_result()	797
13.21.2.4 benchmark_with_timer()	797
13.21.2.5 benchmark_disp()	798
13.21.2.6 benchmark_in_Field()	798
13.21.2.7 benchmark_with_field() [1/2]	798
13.21.2.8 benchmark_with_field() [2/2]	799
13.21.2.9 main()	799
13.22 benchmark-fgesv.C File Reference	799
13.22.1 Macro Definition Documentation	799
13.22.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	799
13.22.2 Function Documentation	799
13.22.2.1 main()	799
13.23 benchmark-fsyr2k.C File Reference	799
13.23.1 Function Documentation	800
13.23.1.1 main()	800
13.24 benchmark-fsyrr.C File Reference	800
13.24.1 Macro Definition Documentation	800
13.24.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	800
13.24.2 Function Documentation	800
13.24.2.1 main()	800
13.25 benchmark-fsytrf.C File Reference	800
13.25.1 Macro Definition Documentation	801
13.25.1.1 __FFPACK_FSYTRF_BC_CROUT	801

13.25.1.2	__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	801
13.25.1.3	CUBE	801
13.25.2	Function Documentation	801
13.25.2.1	main()	801
13.26	benchmark-ftsrm-mp.C File Reference	801
13.26.1	Macro Definition Documentation	802
13.26.1.1	__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	802
13.26.2	Function Documentation	802
13.26.2.1	main()	802
13.27	benchmark-ftsrm.C File Reference	802
13.27.1	Macro Definition Documentation	802
13.27.1.1	__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	802
13.27.2	Function Documentation	802
13.27.2.1	main()	802
13.28	benchmark-ftsrv.C File Reference	802
13.28.1	Macro Definition Documentation	803
13.28.1.1	__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	803
13.28.2	Function Documentation	803
13.28.2.1	main()	803
13.29	benchmark-ftsrti.C File Reference	803
13.29.1	Macro Definition Documentation	803
13.29.1.1	__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	803
13.29.1.2	CUBE	803
13.29.2	Function Documentation	803
13.29.2.1	main()	803
13.30	benchmark-inverse.C File Reference	804
13.30.1	Macro Definition Documentation	804
13.30.1.1	CUBE	804
13.30.2	Function Documentation	804
13.30.2.1	main()	804
13.31	benchmark-lqup-mp.C File Reference	804
13.31.1	Function Documentation	804
13.31.1.1	main()	804
13.32	benchmark-lqup.C File Reference	805
13.32.1	Macro Definition Documentation	805
13.32.1.1	CUBE	805
13.32.2	Function Documentation	805
13.32.2.1	main()	805
13.33	benchmark-pluq.C File Reference	805
13.33.1	Macro Definition Documentation	806
13.33.1.1	__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	806
13.33.1.2	CUBE	806

13.33.2 Typedef Documentation	806
13.33.2.1 Field	806
13.33.3 Function Documentation	806
13.33.3.1 verification_PLUQ()	806
13.33.3.2 Rec_Initialize()	806
13.33.3.3 main()	806
13.34 benchmark-quasisep.C File Reference	806
13.34.1 Macro Definition Documentation	807
13.34.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET	807
13.34.2 Function Documentation	807
13.34.2.1 run_with_field()	807
13.34.2.2 main()	807
13.35 benchmark-storage-transpose.C File Reference	807
13.35.1 Function Documentation	808
13.35.1.1 main()	808
13.36 benchmark-wino.C File Reference	808
13.36.1 Macro Definition Documentation	808
13.36.1.1 CUBE	808
13.36.2 Function Documentation	808
13.36.2.1 launch_wino()	808
13.36.2.2 main()	809
13.37 config.h File Reference	809
13.37.1 Macro Definition Documentation	809
13.37.1.1 HAVE_BLAS	809
13.37.1.2 HAVE_CBLAS	810
13.37.1.3 HAVE_CXX11	810
13.37.1.4 HAVE_DLFCN_H	810
13.37.1.5 HAVE_FLOAT_H	810
13.37.1.6 HAVE_INT128	810
13.37.1.7 HAVE_INTTYPES_H	810
13.37.1.8 HAVE_LAPACK	810
13.37.1.9 HAVE_LIMITS_H	810
13.37.1.10 HAVE_LITTLE_ENDIAN	810
13.37.1.11 HAVE_PTHREAD_H	810
13.37.1.12 HAVE_STDDEF_H	810
13.37.1.13 HAVE_STDINT_H	810
13.37.1.14 HAVE_STDIO_H	810
13.37.1.15 HAVE_STDLIB_H	810
13.37.1.16 HAVE_STRINGS_H	810
13.37.1.17 HAVE_STRING_H	811
13.37.1.18 HAVE_SYS_STAT_H	811
13.37.1.19 HAVE_SYS_TIME_H	811

13.37.1.20 HAVE_SYS_TYPES_H	811
13.37.1.21 HAVE_UNISTD_H	811
13.37.1.22 LT_OBJDIR	811
13.37.1.23 OPENBLAS_NUM_THREADS	811
13.37.1.24 PACKAGE	811
13.37.1.25 PACKAGE_BUGREPORT	811
13.37.1.26 PACKAGE_NAME	811
13.37.1.27 PACKAGE_STRING	811
13.37.1.28 PACKAGE_TARNAME	811
13.37.1.29 PACKAGE_URL	811
13.37.1.30 PACKAGE_VERSION	811
13.37.1.31 SIZEOF_CHAR	811
13.37.1.32 SIZEOF_INT	812
13.37.1.33 SIZEOF_LONG	812
13.37.1.34 SIZEOF_LONG_LONG	812
13.37.1.35 SIZEOF_SHORT	812
13.37.1.36 SIZEOF__INT64_T	812
13.37.1.37 STDC_HEADERS	812
13.37.1.38 USE_OPENMP	812
13.37.1.39 VERSION	812
13.38 config.h File Reference	812
13.38.1 Macro Definition Documentation	813
13.38.1.1 __FFLASFFPACK_HAVE_BLAS	813
13.38.1.2 __FFLASFFPACK_HAVE_CBLAS	813
13.38.1.3 __FFLASFFPACK_HAVE_CXX11	813
13.38.1.4 __FFLASFFPACK_HAVE_DLFCN_H	813
13.38.1.5 __FFLASFFPACK_HAVE_FLOAT_H	813
13.38.1.6 __FFLASFFPACK_HAVE_INT128	813
13.38.1.7 __FFLASFFPACK_HAVE_INTPYPES_H	813
13.38.1.8 __FFLASFFPACK_HAVE_LAPACK	813
13.38.1.9 __FFLASFFPACK_HAVE_LIMITS_H	813
13.38.1.10 __FFLASFFPACK_HAVE_LITTLE_ENDIAN	813
13.38.1.11 __FFLASFFPACK_HAVE_PTHREAD_H	814
13.38.1.12 __FFLASFFPACK_HAVE_STDDEF_H	814
13.38.1.13 __FFLASFFPACK_HAVE_STDINT_H	814
13.38.1.14 __FFLASFFPACK_HAVE_STDIO_H	814
13.38.1.15 __FFLASFFPACK_HAVE_STDLIB_H	814
13.38.1.16 __FFLASFFPACK_HAVE_STRINGS_H	814
13.38.1.17 __FFLASFFPACK_HAVE_STRING_H	814
13.38.1.18 __FFLASFFPACK_HAVE_SYS_STAT_H	814
13.38.1.19 __FFLASFFPACK_HAVE_SYS_TIME_H	814
13.38.1.20 __FFLASFFPACK_HAVE_SYS_TYPES_H	814

13.38.1.21	__FFLASFFPACK_HAVE_UNISTD_H	814
13.38.1.22	__FFLASFFPACK_LT_OBJDIR	814
13.38.1.23	__FFLASFFPACK_OPENBLAS_NUM_THREADS	814
13.38.1.24	__FFLASFFPACK_PACKAGE	814
13.38.1.25	__FFLASFFPACK_PACKAGE_BUGREPORT	814
13.38.1.26	__FFLASFFPACK_PACKAGE_NAME	815
13.38.1.27	__FFLASFFPACK_PACKAGE_STRING	815
13.38.1.28	__FFLASFFPACK_PACKAGE_TARNAME	815
13.38.1.29	__FFLASFFPACK_PACKAGE_URL	815
13.38.1.30	__FFLASFFPACK_PACKAGE_VERSION	815
13.38.1.31	__FFLASFFPACK_SIZEOF_CHAR	815
13.38.1.32	__FFLASFFPACK_SIZEOF_INT	815
13.38.1.33	__FFLASFFPACK_SIZEOF_LONG	815
13.38.1.34	__FFLASFFPACK_SIZEOF_LONG_LONG	815
13.38.1.35	__FFLASFFPACK_SIZEOF_SHORT	815
13.38.1.36	__FFLASFFPACK_SIZEOF__INT64_T	815
13.38.1.37	__FFLASFFPACK_STDC_HEADERS	815
13.38.1.38	__FFLASFFPACK_USE_OPENMP	815
13.38.1.39	__FFLASFFPACK_VERSION	815
13.39	mainpage.doxy File Reference	816
13.40	charpoly.C File Reference	816
13.40.1	Macro Definition Documentation	816
13.40.1.1	CUBE	816
13.40.1.2	GFOPS	816
13.40.2	Typedef Documentation	816
13.40.2.1	TTimer	816
13.40.3	Function Documentation	816
13.40.3.1	main()	816
13.41	charpoly.C File Reference	816
13.41.1	Function Documentation	817
13.41.1.1	main()	817
13.42	det.C File Reference	817
13.42.1	Function Documentation	817
13.42.1.1	main()	817
13.43	matmul.C File Reference	817
13.43.1	Function Documentation	817
13.43.1.1	main()	817
13.44	pluq.C File Reference	818
13.44.1	Macro Definition Documentation	818
13.44.1.1	CUBE	818
13.44.1.2	GFOPS	818
13.44.2	Typedef Documentation	818

13.44.2.1 TTimer	818
13.44.3 Function Documentation	818
13.44.3.1 main()	818
13.45 pluq.C File Reference	818
13.45.1 Function Documentation	819
13.45.1.1 main()	819
13.46 rank.C File Reference	819
13.46.1 Function Documentation	819
13.46.1.1 main()	819
13.47 solve.C File Reference	819
13.47.1 Function Documentation	819
13.47.1.1 main()	819
13.48 checker_charpoly.inl File Reference	820
13.48.1 Macro Definition Documentation	820
13.48.1.1 __FFLASFFPACK_checker_charpoly_INL	820
13.49 checker_det.inl File Reference	820
13.49.1 Macro Definition Documentation	820
13.49.1.1 __FFLASFFPACK_checker_det_INL	820
13.50 checker_empty.h File Reference	820
13.51 checker_fgemm.inl File Reference	821
13.51.1 Macro Definition Documentation	821
13.51.1.1 __FFLASFFPACK_checker_fgemm_INL	821
13.52 checker_ftsm.inl File Reference	821
13.52.1 Macro Definition Documentation	821
13.52.1.1 __FFLASFFPACK_checker_ftsm_INL	821
13.53 checker_invert.inl File Reference	821
13.53.1 Macro Definition Documentation	822
13.53.1.1 __FFLASFFPACK_checker_invert_INL	822
13.54 checker_pluq.inl File Reference	822
13.54.1 Macro Definition Documentation	822
13.54.1.1 __FFLASFFPACK_checker_pluq_INL	822
13.55 checkers.doxy File Reference	822
13.56 checkers_fflas.h File Reference	822
13.57 checkers_fflas.inl File Reference	823
13.57.1 Macro Definition Documentation	823
13.57.1.1 FFLASFFPACK_checkers_fflas_inl_H	823
13.58 checkers_ffpack.h File Reference	823
13.59 checkers_ffpack.inl File Reference	824
13.59.1 Macro Definition Documentation	824
13.59.1.1 FFLASFFPACK_checkers_ffpack_inl_H	824
13.60 config-blas.h File Reference	824
13.60.1 Macro Definition Documentation	825

13.60.1.1 CBLAS_INT	825
13.60.1.2 CBLAS_ENUM_DEFINED_H	825
13.60.1.3 CBLAS_EXTERNALS	825
13.60.1.4 blas_enum	825
13.60.2 Enumeration Type Documentation	825
13.60.2.1 CBLAS_ORDER	825
13.60.2.2 CBLAS_TRANSPOSE	826
13.60.2.3 CBLAS_UPLO	826
13.60.2.4 CBLAS_DIAG	826
13.60.2.5 CBLAS_SIDE	826
13.60.3 Function Documentation	826
13.60.3.1 daxpy_()	826
13.60.3.2 saxpy_()	826
13.60.3.3 ddot_()	827
13.60.3.4 sdot_()	827
13.60.3.5 dasum_()	827
13.60.3.6 idamax_()	827
13.60.3.7 dnrm2_()	827
13.60.3.8 dgemv_()	827
13.60.3.9 sgemv_()	828
13.60.3.10 dger_()	828
13.60.3.11 sger_()	828
13.60.3.12 dcopy_()	828
13.60.3.13 scopy_()	828
13.60.3.14 dscal_()	829
13.60.3.15 sscal_()	829
13.60.3.16 dtrsm_()	829
13.60.3.17 strsm_()	829
13.60.3.18 dtrmm_()	829
13.60.3.19 strmm_()	830
13.60.3.20 sgemm_()	830
13.60.3.21 dgemm_()	830
13.60.3.22 cblas_dsyrk()	830
13.61 fflas-ffpack-config.h File Reference	831
13.61.1 Detailed Description	831
13.61.2 Macro Definition Documentation	831
13.61.2.1 GCC_VERSION	831
13.62 fflas-ffpack-default-thresholds.h File Reference	831
13.62.1 Macro Definition Documentation	831
13.62.1.1 __FFLASFFPACK_WINOTHRESHOLD	831
13.62.1.2 __FFLASFFPACK_WINOTHRESHOLD_FLT	831
13.62.1.3 __FFLASFFPACK_WINOTHRESHOLD_BAL	832

13.62.1.4	__FFLASFFPACK_WINOTHRESHOLD_BAL_FLT	832
13.62.1.5	__FFLASFFPACK_PLUQ_THRESHOLD	832
13.62.1.6	__FFLASFFPACK_CHARPOLY_LUKrylov_ArithProg_THRESHOLD	832
13.62.1.7	__FFLASFFPACK_CHARPOLY_Danilevskii_LUKrylov_THRESHOLD	832
13.62.1.8	__FFLASFFPACK_ARITHPROG_THRESHOLD	832
13.62.1.9	__FFLASFFPACK_FTRTRI_THRESHOLD	832
13.62.1.10	__FFLASFFPACK_FSYTRF_THRESHOLD	832
13.62.1.11	__FFLASFFPACK_FSYRK_THRESHOLD	832
13.63	fflas-ffpack-thresholds.h File Reference	832
13.64	fflas-ffpack.doxy File Reference	832
13.65	fflas-ffpack.h File Reference	832
13.65.1	Detailed Description	832
13.66	fflas.doxy File Reference	832
13.67	fflas.h File Reference	832
13.67.1	Detailed Description	833
13.67.2	Macro Definition Documentation	834
13.67.2.1	WINOTHRESHOLD	834
13.67.2.2	DOUBLE_TO_FLOAT_CROSSOVER	834
13.68	fflas_bounds.inl File Reference	834
13.68.1	Macro Definition Documentation	835
13.68.1.1	__FFLASFFPACK_fflas_bounds_INL	835
13.68.1.2	FFLAS_INT_TYPE	835
13.69	fflas_enum.h File Reference	835
13.70	fflas_fadd.h File Reference	835
13.71	fflas_fadd.inl File Reference	837
13.71.1	Macro Definition Documentation	838
13.71.1.1	__FFLASFFPACK_fadd_INL	838
13.72	fflas_fassign.h File Reference	838
13.73	fflas_fassign.inl File Reference	838
13.73.1	Macro Definition Documentation	839
13.73.1.1	__FFLASFFPACK_fassign_INL	839
13.74	fflas_faxpy.inl File Reference	839
13.74.1	Macro Definition Documentation	840
13.74.1.1	__FFLASFFPACK_faxpy_INL	840
13.75	fflas_fdot.inl File Reference	840
13.75.1	Macro Definition Documentation	841
13.75.1.1	__FFLASFFPACK_fdot_INL	841
13.76	fflas_fgemm.inl File Reference	841
13.76.1	Macro Definition Documentation	843
13.76.1.1	__FFLASFFPACK_fgemm_INL	843
13.77	fgemm_classical.inl File Reference	843
13.78	fgemm_classical_mp.inl File Reference	843

13.78.1 Detailed Description	844
13.78.2 Macro Definition Documentation	845
13.78.2.1 __FFPACK_fgemm_classical_INL	845
13.79 fgemm_winograd.inl File Reference	845
13.79.1 Macro Definition Documentation	846
13.79.1.1 __FFLASFFPACK_fflas_fflas_fgemm_winograd_INL	846
13.79.1.2 NEWWINO	846
13.80 matmul.doxy File Reference	846
13.81 schedule_bini.inl File Reference	846
13.81.1 Detailed Description	846
13.81.2 Macro Definition Documentation	847
13.81.2.1 __FFLASFFPACK_fgemm_bini_INL	847
13.82 schedule_winograd.inl File Reference	847
13.82.1 Macro Definition Documentation	847
13.82.1.1 __FFLASFFPACK_fgemm_winograd_INL	847
13.83 schedule_winograd_acc.inl File Reference	847
13.83.1 Macro Definition Documentation	848
13.83.1.1 __FFLASFFPACK_fgemm_winograd_acc_INL	848
13.84 schedule_winograd_acc_ip.inl File Reference	848
13.84.1 Macro Definition Documentation	849
13.84.1.1 __FFLASFFPACK_fgemm_winograd_acc_ip_INL	849
13.85 schedule_winograd_ip.inl File Reference	849
13.85.1 Macro Definition Documentation	849
13.85.1.1 __FFLASFFPACK_fgemm_winograd_ip_INL	849
13.86 fflas_fgemv.inl File Reference	849
13.86.1 Macro Definition Documentation	851
13.86.1.1 __FFLASFFPACK_fgemv_INL	851
13.87 fflas_fgemv_mp.inl File Reference	851
13.87.1 Macro Definition Documentation	852
13.87.1.1 __FFLASFFPACK_fgemv_mp_INL	852
13.88 fflas_fger.inl File Reference	852
13.88.1 Macro Definition Documentation	853
13.88.1.1 __FFLASFFPACK_fger_INL	853
13.89 fflas_fger_mp.inl File Reference	853
13.89.1 Macro Definition Documentation	853
13.89.1.1 __FFPACK_fger_mp_INL	853
13.90 fflas_freduce.h File Reference	854
13.91 fflas_freduce.inl File Reference	855
13.91.1 Macro Definition Documentation	856
13.91.1.1 __FFLASFFPACK_fflas_freduce_INL	856
13.91.1.2 FFLASFFPACK_COPY_REDUCE	856
13.92 fflas_freduce_mp.inl File Reference	856

13.92.1 Macro Definition Documentation	856
13.92.1.1 __FFLASFFPACK_fflas_freduce_mp_INL	856
13.93 fflas_freivalds.inl File Reference	857
13.93.1 Macro Definition Documentation	857
13.93.1.1 __FFLASFFPACK_freivalds_INL	857
13.94 fflas_fscal.h File Reference	857
13.95 fflas_fscal.inl File Reference	857
13.95.1 Macro Definition Documentation	858
13.95.1.1 __FFLASFFPACK_fscal_INL	858
13.96 fflas_fscal_mp.inl File Reference	859
13.96.1 Macro Definition Documentation	859
13.96.1.1 __FFLASFFPACK_fscal_mp_INL	859
13.97 fflas_fsyr2k.inl File Reference	859
13.97.1 Macro Definition Documentation	860
13.97.1.1 __FFLASFFPACK_fflas_fsyr2k_INL	860
13.98 fflas_fsyrk.inl File Reference	860
13.98.1 Macro Definition Documentation	862
13.98.1.1 __FFLASFFPACK_fflas_fsyrk_INL	862
13.99 fflas_fsyrk_strassen.inl File Reference	862
13.99.1 Macro Definition Documentation	863
13.99.1.1 __FFLASFFPACK_fflas_fsyrk_strassen_INL	863
13.100 fflas_ftrmm.inl File Reference	863
13.100.1 Macro Definition Documentation	863
13.100.1.1 __FFLASFFPACK_ftrmm_INL	863
13.101 fflas_ftrsm.inl File Reference	863
13.101.1 Macro Definition Documentation	864
13.101.1.1 __FFLASFFPACK_ftrsm_INL	864
13.102 fflas_ftrsm_mp.inl File Reference	864
13.102.1 Detailed Description	864
13.102.2 Macro Definition Documentation	864
13.102.2.1 __FFPACK_ftrsm_mp_INL	864
13.103 fflas_ftrsv.inl File Reference	865
13.103.1 Macro Definition Documentation	865
13.103.1.1 __FFLASFFPACK_ftrsv_INL	865
13.104 fflas_helpers.inl File Reference	865
13.104.1 Macro Definition Documentation	866
13.104.1.1 __FFLASFFPACK_fflas_mmmhelper_INL	866
13.105 igemm.dox File Reference	866
13.106 igemm.h File Reference	866
13.107 igemm.inl File Reference	867
13.107.1 Macro Definition Documentation	867
13.107.1.1 __FFLASFFPACK_fflas_igemm_igemm_INL	867

13.108 igemm_kernels.h File Reference	867
13.109 igemm_kernels.inl File Reference	868
13.109.1 Macro Definition Documentation	869
13.109.1.1 __FFLASFFPACK_fflas_igemm_igemm_kernels_INL	869
13.110 igemm_tools.h File Reference	869
13.111 igemm_tools.inl File Reference	869
13.111.1 Macro Definition Documentation	869
13.111.1.1 __FFLASFFPACK_fflas_igemm_igemm_tools_INL	869
13.112 fflas_level1.inl File Reference	869
13.112.1 Macro Definition Documentation	872
13.112.1.1 __FFLASFFPACK_fflas_fflas_level1_INL	872
13.113 fflas_level2.inl File Reference	872
13.113.1 Macro Definition Documentation	874
13.113.1.1 __FFLASFFPACK_fflas_fflas_level2_INL	874
13.114 fflas_level3.inl File Reference	874
13.114.1 Macro Definition Documentation	877
13.114.1.1 __FFLASFFPACK_fflas_fflas_level3_INL	877
13.114.1.2 __FFLAS__TRSM_READONLY	877
13.115 fflas_pfgemm.inl File Reference	877
13.115.1 Macro Definition Documentation	877
13.115.1.1 __FFLASFFPACK_fflas_pfgemm_INL	877
13.115.1.2 __FFLASFFPACK_SEQPARTHRESHOLD	877
13.115.1.3 __FFLASFFPACK_DIMKPENALTY	878
13.116 fflas_pftrsm.inl File Reference	878
13.116.1 Macro Definition Documentation	878
13.116.1.1 __FFLASFFPACK_fflas_pftrsm_INL	878
13.116.1.2 PTRSM_HYBRID_THRESHOLD	878
13.117 fflas_simd.h File Reference	878
13.117.1 Macro Definition Documentation	879
13.117.1.1 SIMD_INT	879
13.117.1.2 INLINE	879
13.117.1.3 CONST	879
13.117.1.4 PURE	879
13.117.1.5 NORML_MOD	879
13.117.1.6 FLOAT_MOD	880
13.117.2 Typedef Documentation	880
13.117.2.1 Simd	880
13.118 simd.doxy File Reference	880
13.119 simd128.inl File Reference	880
13.119.1 Macro Definition Documentation	880
13.119.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd128_INL	880
13.119.2 Typedef Documentation	881

13.119.2.1 Simd128	881
13.120 simd128_double.inl File Reference	881
13.120.1 Macro Definition Documentation	881
13.120.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd128_double_INL	881
13.121 simd128_float.inl File Reference	881
13.121.1 Macro Definition Documentation	881
13.121.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd128_float_INL	881
13.122 simd128_int16.inl File Reference	881
13.122.1 Macro Definition Documentation	882
13.122.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd128_int16_INL	882
13.123 simd128_int32.inl File Reference	882
13.123.1 Macro Definition Documentation	882
13.123.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd128_int32_INL	882
13.124 simd128_int64.inl File Reference	882
13.124.1 Macro Definition Documentation	883
13.124.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd128_int64_INL	883
13.124.1.2 vect_t	883
13.125 simd256.inl File Reference	883
13.125.1 Macro Definition Documentation	883
13.125.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd256_INL	883
13.125.2 Typedef Documentation	883
13.125.2.1 Simd256	883
13.126 simd256_double.inl File Reference	883
13.126.1 Macro Definition Documentation	884
13.126.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd256_double_INL	884
13.127 simd256_float.inl File Reference	884
13.127.1 Macro Definition Documentation	884
13.127.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd256_float_INL	884
13.128 simd256_int16.inl File Reference	884
13.128.1 Macro Definition Documentation	885
13.128.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd256_int16_INL	885
13.129 simd256_int32.inl File Reference	885
13.129.1 Macro Definition Documentation	885
13.129.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd256_int32_INL	885
13.130 simd256_int64.inl File Reference	885
13.130.1 Macro Definition Documentation	885
13.130.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd256_int64_INL	885
13.130.1.2 vect_t	886
13.131 simd512.inl File Reference	886
13.131.1 Macro Definition Documentation	886
13.131.1.1 __FFLASFFPACK_simd512_INL	886
13.131.2 Typedef Documentation	886

13.131.2.1 Simd512	886
13.132 simd512_double.inl File Reference	886
13.132.1 Macro Definition Documentation	886
13.132.1.1 __FFLASFFPACK_simd512_double_INL	886
13.133 simd512_float.inl File Reference	887
13.133.1 Macro Definition Documentation	887
13.133.1.1 __FFLASFFPACK_simd512_float_INL	887
13.134 simd512_int32.inl File Reference	887
13.134.1 Macro Definition Documentation	887
13.134.1.1 __FFLASFFPACK_simd512_int32_INL	887
13.135 simd512_int64.inl File Reference	887
13.135.1 Macro Definition Documentation	888
13.135.1.1 _simd512_int64_INL	888
13.135.1.2 vect_t	888
13.136 simd_modular.inl File Reference	888
13.137 fflas_sparse.h File Reference	888
13.137.1 Macro Definition Documentation	892
13.137.1.1 index_t	892
13.137.1.2 ROUND_DOWN	892
13.137.1.3 __FFLASFFPACK_CACHE_LINE_SIZE	892
13.137.1.4 assume_aligned	892
13.137.1.5 DENSE_THRESHOLD	892
13.138 fflas_sparse.inl File Reference	892
13.138.1 Macro Definition Documentation	894
13.138.1.1 __FFLASFFPACK_fflas_fflas_sparse_INL	894
13.139 coo.h File Reference	894
13.140 coo_spmv.inl File Reference	895
13.140.1 Macro Definition Documentation	896
13.140.1.1 __FFLASFFPACK_fflas_sparse_coo_spmv_INL	896
13.141 coo_spmv.inl File Reference	896
13.141.1 Macro Definition Documentation	897
13.141.1.1 __FFLASFFPACK_fflas_sparse_coo_spmv_INL	897
13.142 coo_utils.inl File Reference	897
13.142.1 Macro Definition Documentation	897
13.142.1.1 __FFLASFFPACK_fflas_sparse_coo_utils_INL	897
13.143 csr.h File Reference	897
13.144 csr_pspmm.inl File Reference	898
13.144.1 Macro Definition Documentation	898
13.144.1.1 __FFLASFFPACK_fflas_sparse_CSR_pspmm_INL	898
13.145 csr_pspmv.inl File Reference	899
13.145.1 Macro Definition Documentation	899
13.145.1.1 __FFLASFFPACK_fflas_sparse_CSR_pspmv_INL	899

13.146 csr_spm্ম.inl File Reference	899
13.146.1 Macro Definition Documentation	900
13.146.1.1 __FFLASFFPACK_fflas_sparse_CSR_spm্ম_INL	900
13.147 csr_spmv.inl File Reference	900
13.147.1 Macro Definition Documentation	901
13.147.1.1 __FFLASFFPACK_fflas_sparse_CSR_spmv_INL	901
13.148 csr_utils.inl File Reference	901
13.149 csr_hyb.h File Reference	902
13.150 csr_hyb_pspmm.inl File Reference	902
13.150.1 Macro Definition Documentation	903
13.150.1.1 __FFLASFFPACK_fflas_sparse_CSR_HYB_pspmm_INL	903
13.151 csr_hyb_pspmv.inl File Reference	903
13.151.1 Macro Definition Documentation	903
13.151.1.1 __FFLASFFPACK_fflas_sparse_CSR_HYB_pspmv_INL	903
13.152 csr_hyb_spm্ম.inl File Reference	903
13.152.1 Macro Definition Documentation	904
13.152.1.1 __FFLASFFPACK_fflas_sparse_CSR_HYB_spm্ম_INL	904
13.153 csr_hyb_spmv.inl File Reference	904
13.153.1 Macro Definition Documentation	904
13.153.1.1 __FFLASFFPACK_fflas_sparse_CSR_HYB_spmv_INL	904
13.154 csr_hyb_utils.inl File Reference	904
13.154.1 Macro Definition Documentation	905
13.154.1.1 __FFLASFFPACK_fflas_sparse_CSR_HYB_utils_INL	905
13.155 ell.h File Reference	905
13.156 ell_pspmm.inl File Reference	905
13.156.1 Macro Definition Documentation	906
13.156.1.1 __FFLASFFPACK_fflas_sparse_ELL_pspmm_INL	906
13.157 ell_pspmv.inl File Reference	906
13.157.1 Macro Definition Documentation	907
13.157.1.1 __FFLASFFPACK_fflas_sparse_ELL_pspmv_INL	907
13.158 ell_spm্ম.inl File Reference	907
13.158.1 Macro Definition Documentation	908
13.158.1.1 __FFLASFFPACK_fflas_sparse_ELL_spm্ম_INL	908
13.159 ell_spmv.inl File Reference	908
13.159.1 Macro Definition Documentation	909
13.159.1.1 __FFLASFFPACK_fflas_sparse_ELL_spmv_INL	909
13.160 ell_utils.inl File Reference	909
13.160.1 Macro Definition Documentation	909
13.160.1.1 __FFLASFFPACK_fflas_sparse_ELL_utils_INL	909
13.161 ell_simd.h File Reference	909
13.162 ell_simd_pspmv.inl File Reference	910
13.162.1 Macro Definition Documentation	910

13.162.1.1 __FFLASFFPACK_fflas_sparse_ELL_simd_pspmv_INL	910
13.163 ell_simd_spmv.inl File Reference	910
13.163.1 Macro Definition Documentation	911
13.163.1.1 __FFLASFFPACK_fflas_sparse_ELL_simd_spmv_INL	911
13.164 ell_simd_utils.inl File Reference	911
13.164.1 Macro Definition Documentation	912
13.164.1.1 __FFLASFFPACK_fflas_sparse_ELL_simd_utils_INL	912
13.165 hyb_zo.h File Reference	912
13.166 hyb_zo_pspmm.inl File Reference	912
13.166.1 Macro Definition Documentation	913
13.166.1.1 __FFLASFFPACK_fflas_sparse_HYB_ZO_pspmm_INL	913
13.167 hyb_zo_pspmv.inl File Reference	913
13.167.1 Macro Definition Documentation	913
13.167.1.1 __FFLASFFPACK_fflas_sparse_HYB_ZO_pspmv_INL	913
13.168 hyb_zo_spm.inl File Reference	913
13.168.1 Macro Definition Documentation	914
13.168.1.1 __FFLASFFPACK_fflas_sparse_HYB_ZO_spm_INL	914
13.169 hyb_zo_spmv.inl File Reference	914
13.169.1 Macro Definition Documentation	914
13.169.1.1 __FFLASFFPACK_fflas_sparse_HYB_ZO_spmv_INL	914
13.170 hyb_zo_utils.inl File Reference	914
13.170.1 Macro Definition Documentation	914
13.170.1.1 __FFLASFFPACK_fflas_sparse_HYB_ZO_utils_INL	914
13.171 read_sparse.h File Reference	915
13.171.1 Macro Definition Documentation	915
13.171.1.1 DNS_BIN_VER	915
13.171.1.2 mask_t	916
13.172 sell.h File Reference	916
13.173 sell_pspmv.inl File Reference	916
13.173.1 Macro Definition Documentation	916
13.173.1.1 __FFLASFFPACK_fflas_sparse_sell_pspmv_INL	916
13.174 sell_spmv.inl File Reference	917
13.174.1 Macro Definition Documentation	917
13.174.1.1 __FFLASFFPACK_fflas_sparse_sell_spmv_INL	917
13.175 sell_utils.inl File Reference	917
13.175.1 Macro Definition Documentation	918
13.175.1.1 __FFLASFFPACK_fflas_sparse_sell_utils_INL	918
13.176 sparse_matrix_traits.h File Reference	918
13.177 utils.h File Reference	920
13.178 fflas_transpose.h File Reference	920
13.178.1 Detailed Description	921
13.178.2 Macro Definition Documentation	921

13.178.2.1 FFLAS_TRANSPOSE_BLOCKSIZE	921
13.178.2.2 LD	921
13.178.2.3 ST	921
13.179 fpack.dox File Reference	921
13.180 fpack.h File Reference	921
13.180.1 Detailed Description	930
13.180.2 Macro Definition Documentation	930
13.180.2.1 __FFLASFFPACK_FTRSTR_THRESHOLD	930
13.180.2.2 __FFLASFFPACK_FTRSSYR2K_THRESHOLD	930
13.181 fpack.inl File Reference	930
13.181.1 Macro Definition Documentation	931
13.181.1.1 __FFLASFFPACK_fpack_INL	931
13.182 fpack_bruhatgen.inl File Reference	931
13.182.1 Macro Definition Documentation	933
13.182.1.1 __FFLASFFPACK_fpack_bruhatgen_inl	933
13.183 fpack_charpoly.inl File Reference	933
13.183.1 Macro Definition Documentation	933
13.183.1.1 __FFLASFFPACK_charpoly_INL	933
13.184 fpack_charpoly_danilevski.inl File Reference	933
13.184.1 Macro Definition Documentation	934
13.184.1.1 __FFLASFFPACK_fpack_charpoly_danilveski_INL	934
13.185 fpack_charpoly_kgfast.inl File Reference	934
13.185.1 Macro Definition Documentation	934
13.185.1.1 __FFLASFFPACK_fpack_charpoly_kgfast_INL	934
13.186 fpack_charpoly_kgfastgeneralized.inl File Reference	934
13.186.1 Macro Definition Documentation	935
13.186.1.1 __FFLASFFPACK_fpack_charpoly_kgfastgeneralized_INL	935
13.187 fpack_charpoly_kglu.inl File Reference	935
13.187.1 Macro Definition Documentation	935
13.187.1.1 __FFLASFFPACK_fpack_charpoly_kglu_INL	935
13.188 fpack_charpoly_mp.inl File Reference	935
13.188.1 Macro Definition Documentation	936
13.188.1.1 __FFPACK_charpoly_mp_INL	936
13.189 fpack_det_mp.inl File Reference	936
13.189.1 Macro Definition Documentation	936
13.189.1.1 __FFPACK_det_mp_INL	936
13.190 fpack_echelonforms.inl File Reference	937
13.190.1 Macro Definition Documentation	938
13.190.1.1 __FFLASFFPACK_fpack_echelon_forms_INL	938
13.190.1.2 __FFLASFFPACK_GAUSSJORDAN_BASECASE	938
13.191 fpack_fgesv.inl File Reference	938
13.191.1 Macro Definition Documentation	938

13.191.1.1 __FFLASFFPACK_ffpack_fgesv_INL	938
13.192 ffpack_fgetrs.inl File Reference	938
13.192.1 Macro Definition Documentation	939
13.192.1.1 __FFLASFFPACK_ffpack_fgetrs_INL	939
13.193 ffpack_frobenius.inl File Reference	939
13.194 ffpack_fsytrf.inl File Reference	940
13.194.1 Macro Definition Documentation	941
13.194.1.1 __FFLASFFPACK_ffpack_fsytrf_INL	941
13.195 ffpack_ftrssyr2k.inl File Reference	941
13.195.1 Macro Definition Documentation	941
13.195.1.1 __FFLASFFPACK_ffpack_ftrssyr2k_INL	941
13.196 ffpack_ftrstr.inl File Reference	941
13.196.1 Macro Definition Documentation	942
13.196.1.1 __FFLASFFPACK_ffpack_ftrstr_INL	942
13.197 ffpack_ftrtr.inl File Reference	942
13.197.1 Macro Definition Documentation	942
13.197.1.1 ENABLE_ALL_CHECKINGS	942
13.197.1.2 __FFLASFFPACK_ffpack_ftrtr_INL	942
13.198 ffpack_invert.inl File Reference	942
13.198.1 Macro Definition Documentation	943
13.198.1.1 __FFLASFFPACK_ffpack_invert_INL	943
13.199 ffpack_krylovelim.inl File Reference	943
13.199.1 Macro Definition Documentation	943
13.199.1.1 __FFLASFFPACK_ffpack_krylovelim_INL	943
13.200 ffpack_ludivine.inl File Reference	943
13.200.1 Macro Definition Documentation	944
13.200.1.1 __FFLASFFPACK_ffpack_ludivine_INL	944
13.201 ffpack_ludivine_mp.inl File Reference	944
13.201.1 Macro Definition Documentation	944
13.201.1.1 __FFPACK_ludivine_mp_INL	944
13.202 ffpack_minpoly.inl File Reference	945
13.202.1 Macro Definition Documentation	945
13.202.1.1 __FFLASFFPACK_ffpack_minpoly_INL	945
13.203 ffpack_permutation.inl File Reference	945
13.203.1 Macro Definition Documentation	947
13.203.1.1 __FFLASFFPACK_ffpack_permutation_INL	947
13.203.1.2 FFLASFFPACK_PERM_BKSIZE	947
13.204 ffpack_pluq.inl File Reference	948
13.204.1 Macro Definition Documentation	948
13.204.1.1 __FFLASFFPACK_ffpack_pluq_INL	948
13.204.1.2 CROUT	948
13.205 ffpack_pluq_mp.inl File Reference	948

13.205.1 Macro Definition Documentation	949
13.205.1.1 __FFPACK_pluq_mp_INL	949
13.206 ffpack_ppluq.inl File Reference	949
13.206.1 Macro Definition Documentation	949
13.206.1.1 __FFLASFFPACK_ffpack_ppluq_INL	949
13.206.1.2 __FFLAS__TRSM_READONLY	949
13.206.1.3 PBASECASE_K	949
13.207 ffpack_rankprofiles.inl File Reference	950
13.207.1 Macro Definition Documentation	951
13.207.1.1 __FFLASFFPACK_ffpack_rank_profiles_INL	951
13.208 field-traits.h File Reference	951
13.208.1 Detailed Description	953
13.209 field.doxy File Reference	953
13.210 rns-double-elt.h File Reference	953
13.210.1 Detailed Description	953
13.211 rns-double-recint.inl File Reference	954
13.211.1 Macro Definition Documentation	954
13.211.1.1 __FFLASFFPACK_field_rns_double_recint_INL	954
13.212 rns-double.h File Reference	954
13.212.1 Detailed Description	955
13.212.2 Macro Definition Documentation	955
13.212.2.1 ROUND_DOWN	955
13.213 rns-double.inl File Reference	955
13.213.1 Macro Definition Documentation	955
13.213.1.1 __FFLASFFPACK_field_rns_double_INL	955
13.214 rns-integer-mod.h File Reference	955
13.214.1 Detailed Description	956
13.215 rns-integer.h File Reference	956
13.215.1 Detailed Description	957
13.216 rns.h File Reference	957
13.217 rns.inl File Reference	957
13.217.1 Macro Definition Documentation	957
13.217.1.1 __FFLASFFPACK_field_rns_INL	957
13.218 interfaces.doxy File Reference	957
13.219 fflas_c.h File Reference	957
13.219.1 Macro Definition Documentation	959
13.219.1.1 FFLAS_COMPILED	959
13.219.2 Enumeration Type Documentation	959
13.219.2.1 FFLAS_C_ORDER	959
13.219.2.2 FFLAS_C_TRANSPOSE	959
13.219.2.3 FFLAS_C_UPLO	960
13.219.2.4 FFLAS_C_DIAG	960

13.219.2.5 FFLAS_C_SIDE	960
13.219.2.6 FFLAS_C_BASE	960
13.219.3 Function Documentation	961
13.219.3.1 freducein_1_modular_double()	961
13.219.3.2 freduce_1_modular_double()	961
13.219.3.3 fnegin_1_modular_double()	961
13.219.3.4 fneg_1_modular_double()	961
13.219.3.5 fzero_1_modular_double()	961
13.219.3.6 fiszero_1_modular_double()	961
13.219.3.7 fequal_1_modular_double()	962
13.219.3.8 fassign_1_modular_double()	962
13.219.3.9 fscal_1_modular_double()	962
13.219.3.10 fscal_1_modular_double()	962
13.219.3.11 faxpy_1_modular_double()	962
13.219.3.12 fdot_1_modular_double()	962
13.219.3.13 fswap_1_modular_double()	963
13.219.3.14 fadd_1_modular_double()	963
13.219.3.15 fsub_1_modular_double()	963
13.219.3.16 faddin_1_modular_double()	963
13.219.3.17 fsubin_1_modular_double()	963
13.219.3.18 fassign_2_modular_double()	964
13.219.3.19 fzero_2_modular_double()	964
13.219.3.20 fequal_2_modular_double()	964
13.219.3.21 fiszero_2_modular_double()	964
13.219.3.22 fidentity_2_modular_double()	964
13.219.3.23 freducein_2_modular_double()	965
13.219.3.24 freduce_2_modular_double()	965
13.219.3.25 fnegin_2_modular_double()	965
13.219.3.26 fneg_2_modular_double()	965
13.219.3.27 fscal_2_modular_double()	965
13.219.3.28 fscal_2_modular_double()	966
13.219.3.29 faxpy_2_modular_double()	966
13.219.3.30 fmove_2_modular_double()	966
13.219.3.31 fadd_2_modular_double()	966
13.219.3.32 fsub_2_modular_double()	966
13.219.3.33 fsubin_2_modular_double()	967
13.219.3.34 faddin_2_modular_double()	967
13.219.3.35 fgemv_2_modular_double()	967
13.219.3.36 fger_2_modular_double()	967
13.219.3.37 ftrsv_2_modular_double()	968
13.219.3.38 ftrsm_3_modular_double()	968
13.219.3.39 ftrmm_3_modular_double()	968

13.219.3.40 fgemm_3_modular_double()	968
13.219.3.41 fsquare_3_modular_double()	969
13.220 fflas_L1_inst.C File Reference	969
13.220.1 Macro Definition Documentation	969
13.220.1.1 __FFLAS_L1_INST_C	969
13.220.1.2 INST_OR_DECL	969
13.220.1.3 FFLAS_FIELD [1/2]	970
13.220.1.4 FFLAS_ELT [1/6]	970
13.220.1.5 FFLAS_ELT [2/6]	970
13.220.1.6 FFLAS_ELT [3/6]	970
13.220.1.7 FFLAS_FIELD [2/2]	970
13.220.1.8 FFLAS_ELT [4/6]	970
13.220.1.9 FFLAS_ELT [5/6]	970
13.220.1.10 FFLAS_ELT [6/6]	970
13.221 fflas_L1_inst.h File Reference	970
13.221.1 Macro Definition Documentation	970
13.221.1.1 INST_OR_DECL	970
13.221.1.2 FFLAS_FIELD [1/2]	971
13.221.1.3 FFLAS_ELT [1/6]	971
13.221.1.4 FFLAS_ELT [2/6]	971
13.221.1.5 FFLAS_ELT [3/6]	971
13.221.1.6 FFLAS_FIELD [2/2]	971
13.221.1.7 FFLAS_ELT [4/6]	971
13.221.1.8 FFLAS_ELT [5/6]	971
13.221.1.9 FFLAS_ELT [6/6]	971
13.222 fflas_L1_inst_implem.inl File Reference	971
13.223 fflas_L2_inst.C File Reference	972
13.223.1 Macro Definition Documentation	973
13.223.1.1 __FFLAS_L2_INST_C	973
13.223.1.2 INST_OR_DECL	973
13.223.1.3 FFLAS_FIELD [1/2]	973
13.223.1.4 FFLAS_ELT [1/6]	973
13.223.1.5 FFLAS_ELT [2/6]	973
13.223.1.6 FFLAS_ELT [3/6]	973
13.223.1.7 FFLAS_FIELD [2/2]	973
13.223.1.8 FFLAS_ELT [4/6]	973
13.223.1.9 FFLAS_ELT [5/6]	973
13.223.1.10 FFLAS_ELT [6/6]	973
13.224 fflas_L2_inst.h File Reference	973
13.224.1 Macro Definition Documentation	974
13.224.1.1 INST_OR_DECL	974
13.224.1.2 FFLAS_FIELD [1/2]	974

13.224.1.3 FFLAS_ELT [1/6]	974
13.224.1.4 FFLAS_ELT [2/6]	974
13.224.1.5 FFLAS_ELT [3/6]	974
13.224.1.6 FFLAS_FIELD [2/2]	974
13.224.1.7 FFLAS_ELT [4/6]	974
13.224.1.8 FFLAS_ELT [5/6]	974
13.224.1.9 FFLAS_ELT [6/6]	974
13.225 fflas_L2_inst_implem.inl File Reference	974
13.226 fflas_L3_inst.C File Reference	976
13.226.1 Macro Definition Documentation	976
13.226.1.1 __FFLAS_L3_INST_C	976
13.226.1.2 INST_OR_DECL	977
13.226.1.3 FFLAS_FIELD [1/2]	977
13.226.1.4 FFLAS_ELT [1/6]	977
13.226.1.5 FFLAS_ELT [2/6]	977
13.226.1.6 FFLAS_ELT [3/6]	977
13.226.1.7 FFLAS_FIELD [2/2]	977
13.226.1.8 FFLAS_ELT [4/6]	977
13.226.1.9 FFLAS_ELT [5/6]	977
13.226.1.10 FFLAS_ELT [6/6]	977
13.227 fflas_L3_inst.h File Reference	977
13.227.1 Macro Definition Documentation	978
13.227.1.1 INST_OR_DECL	978
13.227.1.2 FFLAS_FIELD [1/2]	978
13.227.1.3 FFLAS_ELT [1/6]	978
13.227.1.4 FFLAS_ELT [2/6]	978
13.227.1.5 FFLAS_ELT [3/6]	978
13.227.1.6 FFLAS_FIELD [2/2]	978
13.227.1.7 FFLAS_ELT [4/6]	978
13.227.1.8 FFLAS_ELT [5/6]	978
13.227.1.9 FFLAS_ELT [6/6]	978
13.228 fflas_L3_inst_implem.inl File Reference	978
13.228.1 Macro Definition Documentation	979
13.228.1.1 __FFLAS__TRSM_READONLY	979
13.229 fflas_lvl1.C File Reference	979
13.229.1 Detailed Description	980
13.229.2 Function Documentation	980
13.229.2.1 freducein_1_modular_double()	980
13.229.2.2 freduce_1_modular_double()	980
13.229.2.3 fnegin_1_modular_double()	980
13.229.2.4 fneg_1_modular_double()	981
13.229.2.5 fzero_1_modular_double()	981

13.229.2.6	fiszero_1_modular_double()	981
13.229.2.7	fequal_1_modular_double()	981
13.229.2.8	fassign_1_modular_double()	981
13.229.2.9	fscaln_1_modular_double()	981
13.229.2.10	fscal_1_modular_double()	982
13.229.2.11	faxpy_1_modular_double()	982
13.229.2.12	fdot_1_modular_double()	982
13.229.2.13	fswap_1_modular_double()	982
13.229.2.14	fadd_1_modular_double()	982
13.229.2.15	fsub_1_modular_double()	983
13.229.2.16	faddin_1_modular_double()	983
13.229.2.17	fsubin_1_modular_double()	983
13.230	fflas_lvl2.C File Reference	983
13.230.1	Detailed Description	984
13.230.2	Function Documentation	984
13.230.2.1	fassign_2_modular_double()	984
13.230.2.2	fzero_2_modular_double()	985
13.230.2.3	fequal_2_modular_double()	985
13.230.2.4	fiszero_2_modular_double()	985
13.230.2.5	fidentity_2_modular_double()	985
13.230.2.6	freducein_2_modular_double()	985
13.230.2.7	freduce_2_modular_double()	985
13.230.2.8	fnegin_2_modular_double()	986
13.230.2.9	fneg_2_modular_double()	986
13.230.2.10	fscaln_2_modular_double()	986
13.230.2.11	fscal_2_modular_double()	986
13.230.2.12	faxpy_2_modular_double()	986
13.230.2.13	fmove_2_modular_double()	987
13.230.2.14	fadd_2_modular_double()	987
13.230.2.15	fsub_2_modular_double()	987
13.230.2.16	fsubin_2_modular_double()	987
13.230.2.17	faddin_2_modular_double()	988
13.230.2.18	fgemv_2_modular_double()	988
13.230.2.19	fger_2_modular_double()	988
13.230.2.20	ftsv_2_modular_double()	988
13.231	fflas_lvl3.C File Reference	989
13.231.1	Detailed Description	989
13.231.2	Function Documentation	989
13.231.2.1	ftsm_3_modular_double()	989
13.231.2.2	ftmm_3_modular_double()	990
13.231.2.3	fgemm_3_modular_double()	990
13.231.2.4	fsquare_3_modular_double()	990

13.232 fflas_sparse.C File Reference	990
13.232.1 Detailed Description	990
13.233 ffpack.C File Reference	991
13.233.1 Detailed Description	994
13.233.2 Function Documentation	994
13.233.2.1 LAPACKPerm2MathPerm()	994
13.233.2.2 MathPerm2LAPACKPerm()	994
13.233.2.3 MatrixApplyS_modular_double()	994
13.233.2.4 PermApplyS_double()	995
13.233.2.5 MatrixApplyT_modular_double()	995
13.233.2.6 PermApplyT_double()	995
13.233.2.7 composePermutationsLLM()	995
13.233.2.8 composePermutationsLLL()	995
13.233.2.9 composePermutationsMLM()	996
13.233.2.10 cyclic_shift_mathPerm()	996
13.233.2.11 cyclic_shift_row_modular_double()	996
13.233.2.12 cyclic_shift_col_modular_double()	996
13.233.2.13 applyP_modular_double()	996
13.233.2.14 fgetrsin_modular_double()	996
13.233.2.15 fgetrsv_modular_double()	997
13.233.2.16 fgesvin_modular_double()	997
13.233.2.17 fgesv_modular_double()	997
13.233.2.18 ftrtri_modular_double()	998
13.233.2.19 trinv_left_modular_double()	998
13.233.2.20 ftrtrm_modular_double()	998
13.233.2.21 PLUQ_modular_double()	998
13.233.2.22 LUdivine_modular_double()	998
13.233.2.23 ColumnEchelonForm_modular_double()	999
13.233.2.24 RowEchelonForm_modular_double()	999
13.233.2.25 ReducedColumnEchelonForm_modular_double()	999
13.233.2.26 ReducedRowEchelonForm_modular_double()	999
13.233.2.27 ColumnEchelonForm_modular_float()	1000
13.233.2.28 RowEchelonForm_modular_float()	1000
13.233.2.29 ReducedColumnEchelonForm_modular_float()	1000
13.233.2.30 ReducedRowEchelonForm_modular_float()	1000
13.233.2.31 ColumnEchelonForm_modular_int32_t()	1000
13.233.2.32 RowEchelonForm_modular_int32_t()	1001
13.233.2.33 ReducedColumnEchelonForm_modular_int32_t()	1001
13.233.2.34 ReducedRowEchelonForm_modular_int32_t()	1001
13.233.2.35 pColumnEchelonForm_modular_double()	1001
13.233.2.36 pRowEchelonForm_modular_double()	1002
13.233.2.37 pReducedColumnEchelonForm_modular_double()	1002

13.233.2.38	pReducedRowEchelonForm_modular_double()	1002
13.233.2.39	pColumnEchelonForm_modular_float()	1002
13.233.2.40	pRowEchelonForm_modular_float()	1003
13.233.2.41	pReducedColumnEchelonForm_modular_float()	1003
13.233.2.42	pReducedRowEchelonForm_modular_float()	1003
13.233.2.43	pColumnEchelonForm_modular_int32_t()	1003
13.233.2.44	pRowEchelonForm_modular_int32_t()	1004
13.233.2.45	pReducedColumnEchelonForm_modular_int32_t()	1004
13.233.2.46	pReducedRowEchelonForm_modular_int32_t()	1004
13.233.2.47	Invertin_modular_double()	1004
13.233.2.48	Invert_modular_double()	1004
13.233.2.49	Invert2_modular_double()	1005
13.233.2.50	KrylovElim_modular_double()	1005
13.233.2.51	SpecRankProfile_modular_double()	1005
13.233.2.52	Rank_modular_double()	1005
13.233.2.53	IsSingular_modular_double()	1005
13.233.2.54	Det_modular_double()	1006
13.233.2.55	Solve_modular_double()	1006
13.233.2.56	solveLB_modular_double()	1006
13.233.2.57	solveLB2_modular_double()	1006
13.233.2.58	RandomNullSpaceVector_modular_double()	1007
13.233.2.59	NullSpaceBasis_modular_double()	1007
13.233.2.60	RowRankProfile_modular_double()	1007
13.233.2.61	ColumnRankProfile_modular_double()	1007
13.233.2.62	RankProfileFromLU()	1007
13.233.2.63	LeadingSubmatrixRankProfiles()	1008
13.233.2.64	RowRankProfileSubmatrixIndices_modular_double()	1008
13.233.2.65	ColRankProfileSubmatrixIndices_modular_double()	1008
13.233.2.66	RowRankProfileSubmatrix_modular_double()	1008
13.233.2.67	ColRankProfileSubmatrix_modular_double()	1008
13.233.2.68	getTriangular_modular_double()	1009
13.233.2.69	getTriangularin_modular_double()	1009
13.233.2.70	getEchelonForm_modular_double()	1009
13.233.2.71	getEchelonFormin_modular_double()	1009
13.233.2.72	getEchelonTransform_modular_double()	1010
13.233.2.73	getReducedEchelonForm_modular_double()	1010
13.233.2.74	getReducedEchelonFormin_modular_double()	1010
13.233.2.75	getReducedEchelonTransform_modular_double()	1010
13.233.2.76	PLUQtoEchelonPermutation()	1011
13.234	ffpack_c.h File Reference	1011
13.234.1	Macro Definition Documentation	1014
13.234.1.1	FFPACK_COMPILED	1014

13.234.2 Enumeration Type Documentation	1014
13.234.2.1 FFLAS_C_ORDER	1014
13.234.2.2 FFLAS_C_TRANSPOSE	1014
13.234.2.3 FFLAS_C_UPLO	1014
13.234.2.4 FFLAS_C_DIAG	1015
13.234.2.5 FFLAS_C_SIDE	1015
13.234.2.6 FFPACK_C_LU_TAG	1015
13.234.2.7 FFPACK_C_CHARPOLY_TAG	1015
13.234.2.8 FFPACK_C_MINPOLY_TAG	1015
13.234.3 Function Documentation	1016
13.234.3.1 LAPACKPerm2MathPerm()	1016
13.234.3.2 MathPerm2LAPACKPerm()	1016
13.234.3.3 MatrixApplyS_modular_double()	1016
13.234.3.4 PermApplyS_double()	1016
13.234.3.5 MatrixApplyT_modular_double()	1016
13.234.3.6 PermApplyT_double()	1017
13.234.3.7 composePermutationsLLM()	1017
13.234.3.8 composePermutationsLLL()	1017
13.234.3.9 composePermutationsMLM()	1017
13.234.3.10 cyclic_shift_mathPerm()	1017
13.234.3.11 cyclic_shift_row_modular_double()	1017
13.234.3.12 cyclic_shift_col_modular_double()	1017
13.234.3.13 applyP_modular_double()	1018
13.234.3.14 fgetrsin_modular_double()	1018
13.234.3.15 fgetrs_modular_double()	1018
13.234.3.16 fgesvin_modular_double()	1019
13.234.3.17 fgesv_modular_double()	1019
13.234.3.18 ftrtri_modular_double()	1019
13.234.3.19 trinv_left_modular_double()	1019
13.234.3.20 ftrtrm_modular_double()	1019
13.234.3.21 PLUQ_modular_double()	1020
13.234.3.22 LUdivine_modular_double()	1020
13.234.3.23 LUdivine_small_modular_double()	1020
13.234.3.24 LUdivine_gauss_modular_double()	1020
13.234.3.25 ColumnEchelonForm_modular_double()	1021
13.234.3.26 RowEchelonForm_modular_double()	1021
13.234.3.27 ColumnEchelonForm_modular_float()	1021
13.234.3.28 RowEchelonForm_modular_float()	1021
13.234.3.29 ColumnEchelonForm_modular_int32_t()	1022
13.234.3.30 RowEchelonForm_modular_int32_t()	1022
13.234.3.31 ReducedColumnEchelonForm_modular_double()	1022
13.234.3.32 ReducedRowEchelonForm_modular_double()	1022

13.234.3.33 ReducedColumnEchelonForm_modular_float()	1022
13.234.3.34 ReducedRowEchelonForm_modular_float()	1023
13.234.3.35 ReducedColumnEchelonForm_modular_int32_t()	1023
13.234.3.36 ReducedRowEchelonForm_modular_int32_t()	1023
13.234.3.37 ReducedRowEchelonForm2_modular_double()	1023
13.234.3.38 REF_modular_double()	1024
13.234.3.39 Invertin_modular_double()	1024
13.234.3.40 Invert_modular_double()	1024
13.234.3.41 Invert2_modular_double()	1024
13.234.3.42 KrylovElim_modular_double()	1024
13.234.3.43 SpecRankProfile_modular_double()	1025
13.234.3.44 Rank_modular_double()	1025
13.234.3.45 IsSingular_modular_double()	1025
13.234.3.46 Det_modular_double()	1025
13.234.3.47 Solve_modular_double()	1025
13.234.3.48 solveLB_modular_double()	1026
13.234.3.49 solveLB2_modular_double()	1026
13.234.3.50 RandomNullSpaceVector_modular_double()	1026
13.234.3.51 NullSpaceBasis_modular_double()	1026
13.234.3.52 RowRankProfile_modular_double()	1027
13.234.3.53 ColumnRankProfile_modular_double()	1027
13.234.3.54 RankProfileFromLU()	1027
13.234.3.55 LeadingSubmatrixRankProfiles()	1027
13.234.3.56 RowRankProfileSubmatrixIndices_modular_double()	1027
13.234.3.57 ColRankProfileSubmatrixIndices_modular_double()	1028
13.234.3.58 RowRankProfileSubmatrix_modular_double()	1028
13.234.3.59 ColRankProfileSubmatrix_modular_double()	1028
13.234.3.60 getTriangular_modular_double()	1028
13.234.3.61 getTriangularin_modular_double()	1029
13.234.3.62 getEchelonForm_modular_double()	1029
13.234.3.63 getEchelonFormin_modular_double()	1029
13.234.3.64 getEchelonTransform_modular_double()	1029
13.234.3.65 getReducedEchelonForm_modular_double()	1030
13.234.3.66 getReducedEchelonFormin_modular_double()	1030
13.234.3.67 getReducedEchelonTransform_modular_double()	1030
13.234.3.68 PLUQtoEchelonPermutation()	1030
13.235 fpack_inst.C File Reference	1031
13.235.1 Macro Definition Documentation	1031
13.235.1.1 __FFPACK_INST_C	1031
13.235.1.2 FFLAS_COMPILED	1031
13.235.1.3 INST_OR_DECL	1031
13.235.1.4 FFLAS_FIELD [1/2]	1031

13.235.1.5 FFLAS_ELT [1/6]	1031
13.235.1.6 FFLAS_ELT [2/6]	1031
13.235.1.7 FFLAS_ELT [3/6]	1031
13.235.1.8 FFLAS_FIELD [2/2]	1031
13.235.1.9 FFLAS_ELT [4/6]	1032
13.235.1.10 FFLAS_ELT [5/6]	1032
13.235.1.11 FFLAS_ELT [6/6]	1032
13.236 fpack_inst.h File Reference	1032
13.236.1 Macro Definition Documentation	1032
13.236.1.1 FFLAS_COMPILED	1032
13.236.1.2 INST_OR_DECL	1032
13.236.1.3 FFLAS_FIELD [1/2]	1032
13.236.1.4 FFLAS_ELT [1/6]	1032
13.236.1.5 FFLAS_ELT [2/6]	1032
13.236.1.6 FFLAS_ELT [3/6]	1032
13.236.1.7 FFLAS_FIELD [2/2]	1033
13.236.1.8 FFLAS_ELT [4/6]	1033
13.236.1.9 FFLAS_ELT [5/6]	1033
13.236.1.10 FFLAS_ELT [6/6]	1033
13.237 fpack_inst_implem.inl File Reference	1033
13.238 blockcuts.inl File Reference	1036
13.238.1 Macro Definition Documentation	1037
13.238.1.1 __FFLASFFPACK_fflas_blockcuts_INL	1037
13.238.1.2 __FFLASFFPACK_MINBLOCKCUTS	1037
13.239 fflas_plevel1.h File Reference	1038
13.240 kaapi_routines.inl File Reference	1038
13.240.1 Macro Definition Documentation	1038
13.240.1.1 __FFLASFFPACK_KAAPI_ROUTINES_INL	1038
13.241 parallel.h File Reference	1038
13.241.1 Macro Definition Documentation	1039
13.241.1.1 __FFLASFFPACK_SEQUENTIAL	1039
13.241.1.2 index_t	1039
13.241.1.3 TASK	1039
13.241.1.4 WAIT	1039
13.241.1.5 CHECK_DEPENDENCIES	1039
13.241.1.6 BARRIER	1039
13.241.1.7 PAR_BLOCK	1040
13.241.1.8 SYNCH_GROUP	1040
13.241.1.9 THREAD_INDEX	1040
13.241.1.10 NUM_THREADS	1040
13.241.1.11 SET_THREADS	1040
13.241.1.12 MAX_THREADS	1040

13.241.1.13 READ	1040
13.241.1.14 WRITE	1040
13.241.1.15 READWRITE	1040
13.241.1.16 CONSTREFERENCE	1040
13.241.1.17 VALUE	1040
13.241.1.18 BEGIN_PARALLEL_MAIN	1040
13.241.1.19 END_PARALLEL_MAIN	1040
13.241.1.20 FORBLOCK1D	1041
13.241.1.21 FOR1D	1041
13.241.1.22 PARFORBLOCK1D	1041
13.241.1.23 PARFOR1D	1041
13.241.1.24 FORBLOCK2D	1041
13.241.1.25 FOR2D	1041
13.241.1.26 PARFORBLOCK2D	1042
13.241.1.27 PARFOR2D	1042
13.241.1.28 COMMA	1042
13.241.1.29 MODE	1042
13.241.1.30 RETURNPARAM	1042
13.241.1.31 NUMARGS	1042
13.241.1.32 PP_NARG_	1042
13.241.1.33 PP_ARG_N	1042
13.241.1.34 PP_RSEQ_N	1044
13.241.1.35 NOSPLIT	1044
13.241.1.36 splitting_0	1044
13.241.1.37 splitting_1	1044
13.241.1.38 splitting_2	1044
13.241.1.39 splitting_3	1044
13.241.1.40 splitt	1044
13.241.1.41 SPLITTER	1044
13.242 pfgemm_variants.inl File Reference	1045
13.243 pfgemv.inl File Reference	1045
13.244 align-allocator.h File Reference	1046
13.245 args-parser.h File Reference	1046
13.245.1 Macro Definition Documentation	1047
13.245.1.1 TYPE_BOOL	1047
13.245.1.2 END_OF_ARGUMENTS	1047
13.245.1.3 type_integer	1047
13.245.2 Enumeration Type Documentation	1047
13.245.2.1 ArgumentType	1047
13.245.3 Function Documentation	1047
13.245.3.1 printHelpMessage()	1047
13.245.3.2 findArgument()	1047

13.245.3.3 <code>getListArgs()</code>	1047
13.246 <code>bit_manipulation.h</code> File Reference	1048
13.246.1 Macro Definition Documentation	1048
13.246.1.1 <code>__has_builtin</code>	1048
13.246.2 Function Documentation	1048
13.246.2.1 <code>clz()</code> [1/2]	1048
13.246.2.2 <code>clz()</code> [2/2]	1048
13.246.2.3 <code>ctz()</code> [1/2]	1048
13.246.2.4 <code>ctz()</code> [2/2]	1048
13.247 <code>cast.h</code> File Reference	1049
13.248 <code>debug.h</code> File Reference	1049
13.248.1 Detailed Description	1049
13.248.2 Macro Definition Documentation	1049
13.248.2.1 <code>FFLASFFPACK_check</code>	1049
13.248.2.2 <code>FFLASFFPACK_abort</code>	1050
13.249 <code>fflas_intrinsic.h</code> File Reference	1050
13.250 <code>fflas_io.h</code> File Reference	1050
13.251 <code>fflas_memory.h</code> File Reference	1051
13.252 <code>fflas_randommatrix.h</code> File Reference	1051
13.253 <code>flimits.h</code> File Reference	1053
13.253.1 Function Documentation	1054
13.253.1.1 <code>in_range()</code> [1/3]	1054
13.253.1.2 <code>in_range()</code> [2/3]	1054
13.253.1.3 <code>in_range()</code> [3/3]	1054
13.254 <code>Matio.h</code> File Reference	1054
13.254.1 Function Documentation	1055
13.254.1.1 <code>read_field()</code>	1055
13.254.1.2 <code>write_field()</code>	1055
13.255 <code>test-utils.h</code> File Reference	1055
13.256 <code>timer.h</code> File Reference	1056
13.257 <code>cblas.C</code> File Reference	1056
13.257.1 Macro Definition Documentation	1056
13.257.1.1 <code>__FFLASFFPACK_CONFIGURATION</code>	1056
13.257.1.2 <code>__FFLASFFPACK_HAVE_CBLAS</code>	1056
13.257.2 Function Documentation	1056
13.257.2.1 <code>main()</code>	1056
13.258 <code>clapack.C</code> File Reference	1056
13.258.1 Macro Definition Documentation	1057
13.258.1.1 <code>__FFLASFFPACK_CONFIGURATION</code>	1057
13.258.1.2 <code>__FFLASFFPACK_HAVE_LAPACK</code>	1057
13.258.1.3 <code>__FFLASFFPACK_HAVE_CLAPACK</code>	1057
13.258.2 Function Documentation	1057

13.258.2.1 main()	1057
13.259 cuda.C File Reference	1057
13.259.1 Function Documentation	1057
13.259.1.1 main()	1057
13.260 fblas.C File Reference	1057
13.260.1 Macro Definition Documentation	1058
13.260.1.1 __FFLASFFPACK_CONFIGURATION	1058
13.260.2 Function Documentation	1058
13.260.2.1 dgemm_()	1058
13.260.2.2 main()	1058
13.261 lapack.C File Reference	1058
13.261.1 Macro Definition Documentation	1058
13.261.1.1 __FFLASFFPACK_CONFIGURATION	1058
13.261.1.2 __FFLASFFPACK_HAVE_LAPACK	1058
13.261.2 Function Documentation	1058
13.261.2.1 main()	1058
13.262 regression-check.C File Reference	1059
13.262.1 Function Documentation	1059
13.262.1.1 check1()	1059
13.262.1.2 check2()	1059
13.262.1.3 check3()	1059
13.262.1.4 check4()	1059
13.262.1.5 checkZeroDimCharpoly()	1059
13.262.1.6 checkZeroDimMinPoly()	1059
13.262.1.7 gf2ModularBalanced()	1059
13.262.1.8 main()	1059
13.263 test-charpoly-check.C File Reference	1060
13.263.1 Macro Definition Documentation	1060
13.263.1.1 ENABLE_CHECKER_charpoly	1060
13.263.1.2 TIME_CHECKER_CHARPOLY	1060
13.263.2 Function Documentation	1060
13.263.2.1 printPolynomial()	1060
13.263.2.2 main()	1060
13.264 test-charpoly.C File Reference	1060
13.264.1 Function Documentation	1061
13.264.1.1 launch_test()	1061
13.264.1.2 run_with_field()	1061
13.264.1.3 main()	1061
13.265 test-compressQ.C File Reference	1061
13.265.1 Typedef Documentation	1062
13.265.1.1 Field	1062
13.265.2 Function Documentation	1062

13.265.2.1 printvect()	1062
13.265.2.2 main()	1062
13.266 test-det-check.C File Reference	1062
13.266.1 Macro Definition Documentation	1062
13.266.1.1 ENABLE_CHECKER_Det	1062
13.266.1.2 TIME_CHECKER_Det	1063
13.266.2 Function Documentation	1063
13.266.2.1 main()	1063
13.267 test-det.C File Reference	1063
13.267.1 Function Documentation	1063
13.267.1.1 test_det()	1063
13.267.1.2 main()	1063
13.268 test-echelon.C File Reference	1063
13.268.1 Macro Definition Documentation	1064
13.268.1.1 __FFLASFFPACK_SEQUENTIAL	1064
13.268.1.2 __FFLASFFPACK_GAUSSJORDAN_BASECASE	1064
13.268.1.3 __FFLASFFPACK_PLUQ_THRESHOLD	1064
13.268.2 Function Documentation	1064
13.268.2.1 test_colechelon()	1064
13.268.2.2 test_rowechelon()	1065
13.268.2.3 test_redcoechelon()	1065
13.268.2.4 test_redrowechelon()	1065
13.268.2.5 run_with_field()	1065
13.268.2.6 main()	1066
13.269 test-fadd.C File Reference	1066
13.269.1 Function Documentation	1066
13.269.1.1 test_fadd()	1066
13.269.1.2 test_faddin()	1066
13.269.1.3 test_fsub()	1066
13.269.1.4 test_fsubin()	1067
13.269.1.5 main()	1067
13.270 test-fdot.C File Reference	1067
13.270.1 Macro Definition Documentation	1067
13.270.1.1 ENABLE_ALL_CHECKINGS	1067
13.270.2 Function Documentation	1068
13.270.2.1 check_fdot()	1068
13.270.2.2 run_with_field()	1068
13.270.2.3 run_with_Integer()	1068
13.270.2.4 main()	1068
13.271 test-fgemm-check.C File Reference	1068
13.271.1 Macro Definition Documentation	1069
13.271.1.1 ENABLE_ALL_CHECKINGS	1069

13.271.2 Function Documentation	1069
13.271.2.1 launch_MM_dispatch()	1069
13.271.2.2 run_with_field()	1069
13.271.2.3 main()	1069
13.272 test-fgemv.C File Reference	1069
13.272.1 Macro Definition Documentation	1070
13.272.1.1 ENABLE_CHECKER_fgemv	1070
13.272.2 Function Documentation	1070
13.272.2.1 check_MM()	1070
13.272.2.2 launch_MM()	1070
13.272.2.3 launch_MM_dispatch()	1071
13.272.2.4 run_with_field()	1071
13.272.2.5 main()	1071
13.273 test-fgemv.C File Reference	1072
13.273.1 Function Documentation	1072
13.273.1.1 check_MV()	1072
13.273.1.2 launch_MV()	1072
13.273.1.3 launch_MV_dispatch()	1073
13.273.1.4 run_with_field()	1073
13.273.1.5 main()	1073
13.274 test-fger.C File Reference	1073
13.274.1 Macro Definition Documentation	1074
13.274.1.1 TIME	1074
13.274.2 Function Documentation	1074
13.274.2.1 check_fger()	1074
13.274.2.2 launch_fger()	1074
13.274.2.3 launch_fger_dispatch()	1074
13.274.2.4 run_with_field()	1075
13.274.2.5 main()	1075
13.275 test-fgesv.C File Reference	1075
13.275.1 Function Documentation	1076
13.275.1.1 test_square_fgesv()	1076
13.275.1.2 test_rect_fgesv()	1076
13.275.1.3 run_with_field()	1076
13.275.1.4 main()	1076
13.276 test-finit.C File Reference	1076
13.276.1 Function Documentation	1077
13.276.1.1 test_freduce()	1077
13.276.1.2 run_with_field()	1077
13.276.1.3 main()	1077
13.277 test-fscal.C File Reference	1077
13.277.1 Function Documentation	1078

13.277.1.1 test_fscal() [1/2]	1078
13.277.1.2 test_fscal() [2/2]	1078
13.277.1.3 test_fscaln() [1/2]	1078
13.277.1.4 test_fscaln() [2/2]	1078
13.277.1.5 main()	1079
13.278 test-fsyr2k.C File Reference	1079
13.278.1 Macro Definition Documentation	1079
13.278.1.1 ENABLE_ALL_CHECKINGS	1079
13.278.2 Function Documentation	1079
13.278.2.1 check_fsyr2k()	1079
13.278.2.2 run_with_field()	1080
13.278.2.3 main()	1080
13.279 test-fsyrk.C File Reference	1080
13.279.1 Macro Definition Documentation	1081
13.279.1.1 ENABLE_ALL_CHECKINGS	1081
13.279.2 Function Documentation	1081
13.279.2.1 check_fsyrk()	1081
13.279.2.2 check_fsyrk_diag()	1081
13.279.2.3 check_fsyrk_bkdiag()	1081
13.279.2.4 check_computeS1S2()	1081
13.279.2.5 run_with_field()	1082
13.279.2.6 main()	1082
13.280 test-fsytrf.C File Reference	1082
13.280.1 Function Documentation	1082
13.280.1.1 operator<<()	1082
13.280.1.2 test_RPM_fsytrf()	1083
13.280.1.3 test_generic_fsytrf()	1083
13.280.1.4 run_with_field()	1083
13.280.1.5 main()	1083
13.281 test-ftmrm.C File Reference	1083
13.281.1 Macro Definition Documentation	1084
13.281.1.1 __FFLASFFPACK_SEQUENTIAL	1084
13.281.2 Function Documentation	1084
13.281.2.1 check_ftmrm()	1084
13.281.2.2 run_with_field()	1084
13.281.2.3 main()	1084
13.282 test-ftrmv.C File Reference	1084
13.282.1 Macro Definition Documentation	1085
13.282.1.1 __FFLASFFPACK_SEQUENTIAL	1085
13.282.1.2 ENABLE_ALL_CHECKINGS	1085
13.282.2 Function Documentation	1085
13.282.2.1 check_ftrmv()	1085

13.282.2.2 run_with_field()	1085
13.282.2.3 main()	1086
13.283 test-ftsrm-check.C File Reference	1086
13.283.1 Macro Definition Documentation	1086
13.283.1.1 ENABLE_ALL_CHECKINGS	1086
13.283.2 Function Documentation	1086
13.283.2.1 main()	1086
13.284 test-ftsrm.C File Reference	1086
13.284.1 Macro Definition Documentation	1087
13.284.1.1 __FFLASFFPACK_SEQUENTIAL	1087
13.284.1.2 ENABLE_ALL_CHECKINGS	1087
13.284.2 Function Documentation	1087
13.284.2.1 check_ftsrm()	1087
13.284.2.2 run_with_field()	1087
13.284.2.3 main()	1087
13.285 test-ftsrsyr2k.C File Reference	1087
13.285.1 Macro Definition Documentation	1088
13.285.1.1 ENABLE_ALL_CHECKINGS	1088
13.285.2 Function Documentation	1088
13.285.2.1 check_ftsrsyr2k()	1088
13.285.2.2 run_with_field()	1088
13.285.2.3 main()	1088
13.286 test-ftsstr.C File Reference	1089
13.286.1 Macro Definition Documentation	1089
13.286.1.1 ENABLE_ALL_CHECKINGS	1089
13.286.2 Function Documentation	1089
13.286.2.1 check_ftsstr()	1089
13.286.2.2 run_with_field()	1089
13.286.2.3 main()	1090
13.287 test-ftsrv.C File Reference	1090
13.287.1 Macro Definition Documentation	1090
13.287.1.1 __FFLASFFPACK_SEQUENTIAL	1090
13.287.1.2 ENABLE_ALL_CHECKINGS	1090
13.287.2 Function Documentation	1090
13.287.2.1 check_ftsrv()	1090
13.287.2.2 run_with_field()	1091
13.287.2.3 main()	1091
13.288 test-ftsrti.C File Reference	1091
13.288.1 Macro Definition Documentation	1091
13.288.1.1 __FFLASFFPACK_SEQUENTIAL	1091
13.288.1.2 ENABLE_ALL_CHECKINGS	1091
13.288.2 Function Documentation	1091

13.288.2.1 check_ftrtri()	1091
13.288.2.2 run_with_field()	1092
13.288.2.3 main()	1092
13.289 test-interfaces-c.c File Reference	1092
13.289.1 Function Documentation	1092
13.289.1.1 main()	1092
13.290 test-invert-check.C File Reference	1092
13.290.1 Macro Definition Documentation	1093
13.290.1.1 ENABLE_ALL_CHECKINGS	1093
13.290.2 Function Documentation	1093
13.290.2.1 main()	1093
13.291 test-io.C File Reference	1093
13.291.1 Function Documentation	1093
13.291.1.1 run_with_field()	1093
13.291.1.2 main()	1093
13.292 test-lu.C File Reference	1094
13.292.1 Macro Definition Documentation	1094
13.292.1.1 BASECASE_K	1094
13.292.1.2 __FFLASFFPACK_SEQUENTIAL	1095
13.292.1.3 __LUDIVINE_CUTOFF	1095
13.292.2 Function Documentation	1095
13.292.2.1 test_LUdivine()	1095
13.292.2.2 verifPLUQ()	1095
13.292.2.3 test_pluq()	1096
13.292.2.4 launch_test()	1096
13.292.2.5 run_with_field()	1097
13.292.2.6 main()	1097
13.292.3 Variable Documentation	1097
13.292.3.1 tperm	1097
13.292.3.2 tgemm	1097
13.292.3.3 tBC	1097
13.292.3.4 ttrsm	1097
13.292.3.5 trest	1097
13.292.3.6 timtot	1097
13.292.3.7 mvcnt	1097
13.293 test-maxdelayeddim.C File Reference	1098
13.293.1 Macro Definition Documentation	1098
13.293.1.1 MAX_WITH_SIZE_T	1098
13.293.2 Function Documentation	1098
13.293.2.1 test()	1098
13.293.2.2 main()	1098
13.294 test-minpoly.C File Reference	1098

13.294.1 Function Documentation	1099
13.294.1.1 check_minpoly()	1099
13.294.1.2 run_with_field()	1099
13.294.1.3 main()	1099
13.295 test-multifile1.C File Reference	1099
13.296 test-multifile2.C File Reference	1099
13.296.1 Function Documentation	1099
13.296.1.1 main()	1099
13.297 test-nullspace.C File Reference	1100
13.297.1 Function Documentation	1100
13.297.1.1 checkingMessage()	1100
13.297.1.2 readOrRandomMatrixWithRankAndRandomRPM()	1100
13.297.1.3 test_nullspace()	1100
13.297.1.4 run_with_field()	1101
13.297.1.5 main()	1101
13.298 test-permutations.C File Reference	1101
13.298.1 Function Documentation	1101
13.298.1.1 checkMonotonicApplyP()	1101
13.298.1.2 main()	1101
13.298.2 Variable Documentation	1102
13.298.2.1 tperm	1102
13.298.2.2 tgemm	1102
13.298.2.3 tBC	1102
13.298.2.4 ttrsm	1102
13.298.2.5 trest	1102
13.298.2.6 timtot	1102
13.299 test-pluq-check.C File Reference	1102
13.299.1 Macro Definition Documentation	1102
13.299.1.1 ENABLE_ALL_CHECKINGS	1102
13.299.2 Function Documentation	1102
13.299.2.1 main()	1102
13.300 test-quasisep.C File Reference	1103
13.300.1 Function Documentation	1103
13.300.1.1 test_BruhatGenerator()	1103
13.300.1.2 launch_test()	1103
13.300.1.3 testLTQSRPM()	1103
13.300.1.4 run_with_field()	1104
13.300.1.5 main()	1104
13.301 test-rankprofiles.C File Reference	1104
13.301.1 Macro Definition Documentation	1104
13.301.1.1 __FFLASFFPACK_SEQUENTIAL	1104
13.301.2 Function Documentation	1104

13.301.2.1 run_with_field()	1104
13.301.2.2 main()	1105
13.302 test-rpm.C File Reference	1105
13.302.1 Function Documentation	1105
13.302.1.1 checkRPM()	1105
13.302.1.2 checkSymmetricRPM()	1105
13.302.1.3 main()	1105
13.303 test-simd.C File Reference	1105
13.303.1 Macro Definition Documentation	1107
13.303.1.1 _TEST_ONE	1107
13.303.1.2 TEST_ONE_OP	1107
13.303.1.3 TEST_ONE_OP_WZ	1107
13.303.1.4 TEST_IMPL	1107
13.303.2 Function Documentation	1107
13.303.2.1 check_eq() [1/2]	1107
13.303.2.2 check_eq() [2/2]	1108
13.303.2.3 cmp()	1108
13.303.2.4 eval_func_on_array() [1/3]	1108
13.303.2.5 eval_func_on_array() [2/3]	1108
13.303.2.6 eval_func_on_array() [3/3]	1108
13.303.2.7 operator<<()	1108
13.303.2.8 test_impl_base() [1/2]	1108
13.303.2.9 test_impl_base() [2/2]	1108
13.303.2.10 test_impl()	1108
13.303.2.11 main()	1109
13.304 test-solve.C File Reference	1109
13.304.1 Function Documentation	1109
13.304.1.1 check_solve()	1109
13.304.1.2 run_with_field()	1109
13.304.1.3 main()	1109
13.305 test-storage-transpose.C File Reference	1109
13.305.1 Function Documentation	1110
13.305.1.1 main()	1110
13.306 101-fgemm.C File Reference	1110
13.306.1 Function Documentation	1110
13.306.1.1 main()	1110
13.307 2x2-fgemm.C File Reference	1110
13.307.1 Function Documentation	1111
13.307.1.1 main()	1111
13.308 2x2-ftsv.C File Reference	1111
13.308.1 Function Documentation	1111
13.308.1.1 main()	1111

13.309 2x2-pluq.C File Reference	1111
13.309.1 Function Documentation	1111
13.309.1.1 main()	1111
13.310 fflas-101_1.C File Reference	1112
13.310.1 Function Documentation	1112
13.310.1.1 main()	1112
13.311 fflas-101_3.C File Reference	1112
13.311.1 Function Documentation	1112
13.311.1.1 main()	1112
13.312 fflas_101.C File Reference	1112
13.312.1 Function Documentation	1113
13.312.1.1 main()	1113
13.313 fflas_101_lvl1.C File Reference	1113
13.313.1 Function Documentation	1113
13.313.1.1 main()	1113
13.314 ffpack-fgesv.C File Reference	1113
13.314.1 Function Documentation	1113
13.314.1.1 main()	1113
13.315 ffpack-solve.C File Reference	1113
13.315.1 Function Documentation	1114
13.315.1.1 main()	1114
Index	1115

Chapter 1

FFLAS-FFPACK Documentation.

1.1 Introduction

FFLAS-FFPACK is a LGPL-2.1+ source code library for basic linear algebra operations over a finite field. It is inspired by BLAS interface (Basic Linear Algebra Subprograms) and the LAPACK library for numerical linear algebra, and shares part of their design. Yet it differs in many aspects due to the specifics of computing over a finite field:

- it is generic with respect to the finite field, so as to accomodate a large variety of field sizes and implementations;
- it is a pure source code library, to be included and compiled in the user's software. Its build system is only used for tests and benchmarks.

1.2 Goals

1.3 Design

1.4 Using FFLAS-FFPACK.

- [Copying and Licence](#).
- [Tutorial](#). This is a brief introduction to FFLAS-FFPACK capabilities.
- [Configuring and Installing FFLAS-FFPACK](#). Explains how to configure/install from sources or from the latest svn version.
- [Architecture of the library](#).. Describes how FFLAS-FFPACK is organized
- [Documentation for Users](#). If everything around is blue, then you are reading the lighter, user-oriented, documentation.
- [Documentation for Developers](#). If everything around is green, then you can get to everything (not necessarily yet) documented.

1.5 Contributing to fflas-ffpack, getting assistance.

Version

2.5.0

1.6 Copying and Licence

The FFLAS-FFPACK library is licensed under the terms of the GNU LGPL v2.1 or later.

See <https://www.gnu.org/licenses/lgpl-2.1.html>

1.7 Tutorial

no doc.

1.8 Configuring and Installing FFLAS-FFPACK

FFLAS-FFPACK is a header-only package.

Howver configuration process can be tweaked a lot. Configure looks for BLAS routines and [Givaro](#) library which are both mandatory dependencies. See the output of `./configure -help` for information about the LAPACK/↔ BLAS discovering strategies.

1.9 Architecture of the library.

no doc.

Chapter 2

Bug List

Global **DOUBLE_TO_FLOAT_CROSSOVER**

to be benchmarked.

Global **FFLAS::details::pack_lhs** (int64_t *XX, const int64_t *X, size_t ldx, size_t rows, size_t cols)

this is fassign

this is fassign

Global **FFLAS::details::pack_rhs** (int64_t *XX, const int64_t *X, size_t ldx, size_t rows, size_t cols)

this is fassign

this is fassign

Global **FFLAS::fconvert** (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t n, FFLAS_ELT *X, const size_t incX, const FFLAS_ELT *Y, const size_t incY)

use cblas_(d)scal when possible

Global **FFLAS::fconvert** (const Field &F, const size_t n, OtherElement_ptr X, const size_t incX, typename Field::ConstElement_ptr Y, const size_t incY)

use cblas_(d)scal when possible

Global **FFLAS::finit** (const Field &F, const size_t n, const OtherElement_ptr Y, const size_t incY, typename Field::Element_ptr X, const size_t incX)

use cblas_(d)scal when possible

Global **FFLAS::finit** (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t n, const FFLAS_ELT *Y, const size_t incY, FFLAS_ELT *X, const size_t incX)

use cblas_(d)scal when possible

Global **FFLAS::fneg** (const Field &F, const size_t n, typename Field::ConstElement_ptr Y, const size_t incY, typename Field::Element_ptr X, const size_t incX)

use cblas_(d)scal when possible

Global **FFLAS::fneg** (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t n, const FFLAS_ELT *Y, const size_t incY, FFLAS_ELT *X, const size_t incX)

use cblas_(d)scal when possible

Global **FFLAS::fnegin** (const Field &F, const size_t n, typename Field::Element_ptr X, const size_t incX)

use cblas_(d)scal when possible

Global **FFLAS::fnegin** (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t n, FFLAS_ELT *X, const size_t incX)

use cblas_(d)scal when possible

Global **FFLAS::freduce** (const Field &F, const size_t n, typename Field::ConstElement_ptr Y, const size_t incY, typename Field::Element_ptr X, const size_t incX)

use cblas_(d)scal when possible

- Global **FFLAS::reduce** (const Field &F, const size_t n, typename **Field::Element_ptr** X, const size_t incX)
use cblas_(d)scal when possible
- Global **FFLAS::reduce** (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t n, FFLAS_ELT *X, const size_t incX)
use cblas_(d)scal when possible
- Global **FFLAS::reduce** (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t n, const FFLAS_ELT *Y, const size_t incY, FFLAS_ELT *X, const size_t incX)
use cblas_(d)scal when possible
- Global **FFLAS::fscal** (const Field &F, const size_t n, const typename **Field::Element** alpha, typename **Field::ConstElement_ptr** X, const size_t incX, typename **Field::Element_ptr** Y, const size_t incY)
use cblas_(d)scal when possible
- Global **FFLAS::fscal** (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t n, const FFLAS_ELT alpha, const FFLAS_ELT *X, const size_t incX, FFLAS_ELT *Y, const size_t incY)
use cblas_(d)scal when possible
- Global **FFLAS::fscaln** (const Field &F, const size_t n, const typename **Field::Element** alpha, typename **Field::Element_ptr** X, const size_t incX)
use cblas_(d)scal when possible
- Global **FFLAS::fscaln** (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t n, const FFLAS_ELT alpha, FFLAS_ELT *X, const size_t incX)
use cblas_(d)scal when possible
- Global **FFLAS::fsquare** (const Field &F, const FFLAS_TRANSPOSE ta, const size_t n, const typename **Field::Element** alpha, typename **Field::ConstElement_ptr** A, const size_t lda, const typename **Field::Element** beta, typename **Field::Element_ptr** C, const size_t ldc)
why double ?
- Global **FFLAS::fswap** (const Field &F, const size_t N, typename **Field::Element_ptr** X, const size_t incX, typename **Field::Element_ptr** Y, const size_t incY)
use cblas_dswap when double
- Global **FFLAS::fswap** (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t N, FFLAS_ELT *X, const size_t incX, FFLAS_ELT *Y, const size_t incY)
use cblas_dswap when double
- Global **FFLAS::ftrsm** (const Field &F, const FFLAS_SIDE Side, const FFLAS_UPLO Uplo, const FFLAS_TRANSPOSE TransA, const FFLAS_DIAG Diag, const size_t M, const size_t N, const typename **Field::Element** alpha, typename **Field::ConstElement_ptr** A, const size_t lda, typename **Field::Element_ptr** B, const size_t ldb)
 α must be non zero.
- Global **FFLAS::ftrsm** (const FFLAS_FIELD< FFLAS_ELT > &F, const FFLAS_SIDE Side, const FFLAS_UPLO Uplo, const FFLAS_TRANSPOSE TransA, const FFLAS_DIAG Diag, const size_t M, const size_t N, const FFLAS_ELT alpha, const FFLAS_ELT *A, const size_t lda, FFLAS_ELT *B, const size_t ldb)
 α must be non zero.
- Global **FFPACK::buildMatrix** (const Field &F, typename **Field::ConstElement_ptr** E, typename **Field::ConstElement_ptr** C, const size_t lda, const size_t *B, const size_t *T, const size_t me, const size_t mc, const size_t lambda, const size_t mu)
is this :
- Global **FFPACK::invert2** (const Field &F, const size_t M, typename **Field::Element_ptr** A, const size_t lda, typename **Field::Element_ptr** X, const size_t ldx, int &nullity)
not tested.
- Global **launch_fger_dispatch** (const Field &F, const size_t nn, const typename **Field::Element** alpha, const size_t iters, RandIter &G)
test for transpo
test for incx equal

Global `launch_MM_dispatch` (const Field &F, const int mm, const int nn, const int kk, const typename `Field::Element` alpha, const typename `Field::Element` beta, const size_t iters, RandIter &G)

Global `launch_MM_dispatch` (const Field &F, const int mm, const int nn, const int kk, const typename `Field::Element` alpha, const typename `Field::Element` beta, const size_t iters, const int nbw, const bool par, RandIter &G)

test for IdX equal

test for transpo

Global `launch_MM_dispatch` (const Field &F, const int mm, const int nn, const int kk, const typename `Field::Element` alpha, const typename `Field::Element` beta, const size_t iters, RandIter &G)

test for transpo

test for IdX equal

Global `printvect` (std::ostream &o, vector< T > &vect)

does not belong here

Chapter 3

Bibliography

- Global **FFLAS::Protected::TRSMBound** (const Givaro::ModularBalanced< Element > &F) .
Dumas Giorgi Pernet 06, arXiv:cs/0601133
- Global **FFPACK::LeadingSubmatrixRankProfiles** (const size_t M, const size_t N, const size_t R, const size_t LSm, const size_t LSn, const size_t *P, const size_t *Q, size_t *RRP, size_t *CRP) .
Dumas J-G., Pernet C., and Sultan Z. *Simultaneous computation of the row and column rank profiles*, ISSAC'13.
- Global **FFPACK::LUdivine** (const Field &F, const **FFLAS::FFLAS_DIAG** Diag, const **FFLAS::FFLAS_TRANSPOSE** trans, const size_t M, const size_t N, typename **Field::Element_ptr** A, const size_t lda, size_t *P, size_t *Qt, const FFPACK_LU_TAG LuTag=FfpackSlabRecursive, const size_t cutoff=__FFLASFFPACK_LUDIVINE_THRESHOLD) .
Jeannerod C-P, Pernet, C. and Storjohann, A. *Rank-profile revealing Gaussian elimination and the CUP matrix decomposition*, J. of Symbolic Comp., 2013
• Pernet C, Brassel M *LUdivine, une divine factorisation LU*, 2002
- Global **FFPACK::PLUQ** (const Field &F, const **FFLAS::FFLAS_DIAG** Diag, const size_t M, const size_t N, typename **Field::Element_ptr** A, const size_t lda, size_t *P, size_t *Q) .
Dumas J-G., Pernet C., and Sultan Z. *Simultaneous computation of the row and column rank profiles*, ISSAC'13, 2013
- Global **FFPACK::productBruhatxTS** (const Field &Fi, size_t N, size_t s, size_t r, size_t t, const size_t *P, const size_t *Q, typename **Field::ConstElement_ptr** Xu, size_t ldu, size_t NbBlocksU, const size_t *Ku, const size_t *Tu, const size_t *MU, typename **Field::ConstElement_ptr** XI, size_t ldl, size_t NbBlocksL, const size_t *KI, const size_t *TI, const size_t *ML, typename **Field::Element_ptr** B, size_t ldb, const typename **Field::Element** beta, typename **Field::Element_ptr** D, size_t ldd) .
Pernet C. and Storjohann A. *Time and space efficient generators for quasiseparable matrices*, JSC (85), 2018, doi:10.1016/j.jsc.2017.07.010
- Global **FFPACK::Protected::GaussJordan** (const Field &F, const size_t M, const size_t N, typename **Field::Element_ptr** A, const size_t lda, const size_t colbeg, const size_t rowbeg, const size_t colsize, size_t *P, size_t *Q, const FFPACK::FFPACK_LU_TAG LuTag) .
Algorithm 2.8 of A. Storjohann Thesis 2000,
• Algorithm 11 of Jeannerod C-P, Pernet, C. and Storjohann, A. *Rank-profile revealing Gaussian elimination and the CUP matrix decomposition*, J. of Symbolic Comp., 2013
- Class **ftrsmLeftUpperNoTransNonUnit**< Element > .
Dumas, Giorgi, Pernet 06, arXiv:cs/0601133.

Chapter 4

Todo List

File `debug.h`

we should put vector printing elsewhere.

Global `FFLAS::fadd` (const Field &F, const size_t N, typename `Field::ConstElement_ptr` A, const size_t incA, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` B, const size_t incB, typename `Field::Element_ptr` C, const size_t incC)

optimise here

Global `FFLAS::fassign` (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t N, const FFLAS_ELT *Y, const size_t incY, FFLAS_ELT *X, const size_t incX)

variant for triangular matrix

Global `FFLAS::fassign` (const Field &F, const size_t N, typename `Field::ConstElement_ptr` Y, const size_t incY, typename `Field::Element_ptr` X, const size_t incX)

variant for triangular matrix

Global `FFLAS::fconvert` (const Field &F, const size_t m, const size_t n, OtherElement_ptr A, const size_t lda, typename `Field::ConstElement_ptr` B, const size_t ldb)

check if n == lda

Global `FFLAS::fneg` (const Field &F, const size_t m, const size_t n, typename `Field::ConstElement_ptr` B, const size_t ldb, typename `Field::Element_ptr` A, const size_t lda)

check if n == lda

Global `FFLAS::fnegin` (const Field &F, const size_t m, const size_t n, typename `Field::Element_ptr` A, const size_t lda)

check if n == lda

Global `FFLAS::fscal` (const Field &F, const size_t n, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` X, const size_t incX, typename `Field::Element_ptr` Y, const size_t incY)

check if comparison with +/-1,0 is necessary.

Global `FFLAS::fscal` (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t n, const FFLAS_ELT alpha, const FFLAS_ELT *X, const size_t incX, FFLAS_ELT *Y, const size_t incY)

check if comparison with +/-1,0 is necessary.

Global `FFLAS::fscaln` (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t n, const FFLAS_ELT alpha, FFLAS_ELT *X, const size_t incX)

check if comparison with +/-1,0 is necessary.

Global `FFLAS::fscaln` (const Field &F, const size_t n, const typename `Field::Element` alpha, typename `Field::Element_ptr` X, const size_t incX)

check if comparison with +/-1,0 is necessary.

Global **FFLAS::Protected::igemm** (const enum FFLAS_TRANSPOSE TransA, const enum FFLAS_TRANSPOSE TransB, size_t rows, size_t cols, size_t depth, const int64_t alpha, const int64_t *A, size_t lda, const int64_t *B, size_t ldb, const int64_t beta, int64_t *C, size_t ldc)
use primitive (no **Field()**) and specialise for int64.

Global **FFLAS::Protected::MatF2MatFI_Triangular** (const **Field** &F, **Givaro::FloatDomain::Element_ptr** S, const size_t lds, typename **Field::ConstElement_ptr** const E, const size_t lde, const size_t m, const size_t n)
do finit(...,FFLAS_TRANS,FFLAS_DIAG)
do fconvert(...,FFLAS_TRANS,FFLAS_DIAG)

Global **FFPACK::getTriangular** (const **Field** &F, const **FFLAS::FFLAS_UPLO** Uplo, const **FFLAS::FFLAS_DIAG** diag, const size_t M, const size_t N, const size_t R, typename **Field::ConstElement_ptr** A, const size_t lda, typename **Field::Element_ptr** T, const size_t ldt, const bool OnlyNonZeroVectors=false)
just one triangular fzero+fassign ?

Global **FFPACK::getTriangular** (const **Field** &F, const **FFLAS::FFLAS_UPLO** Uplo, const **FFLAS::FFLAS_DIAG** diag, const size_t M, const size_t N, const size_t R, typename **Field::Element_ptr** A, const size_t lda)
just one triangular fzero+fassign ?

Global **FFPACK::invert2** (const **Field** &F, const size_t M, typename **Field::Element_ptr** A, const size_t lda, typename **Field::Element_ptr** X, const size_t ldx, int &>nullity)
this init is not all necessary (done after ftrtri)

Global **FFPACK::LUdivine** (const **Field** &F, const **FFLAS::FFLAS_DIAG** Diag, const **FFLAS::FFLAS_TRANSPOSE** trans, const size_t M, const size_t N, typename **Field::Element_ptr** A, const size_t lda, size_t *P, size_t *Q, const **FFPACK::FFPACK_LU_TAG** LuTag, const size_t cutoff)
std::swap ?

Global **FFPACK::Protected::RandomKrylovPrecond** (const **PolRing** &PR, std::list< typename **PolRing::Element** > &completedFactors, const size_t N, typename **PolRing::Domain_t::Element_ptr** A, const size_t lda, size_t &Nb, typename **PolRing::Domain_t::Element_ptr** &B, size_t &ldb, typename **PolRing::Domain_t::RandIter** &g, const size_t degree=__FFLASFFPACK_ARITHPROG_THRESHOLD)
don't assing K2 c*noc x N but only mas (c,noc) x N and store each one after the other

swap to save space ??

Module **field**

biblio

Global **launch_fger_dispatch** (const **Field** &F, const size_t nn, const typename **Field::Element** alpha, const size_t iters, **RandIter** &G)
does nbw actually do nbw recursive calls and then call blas (check ?) ?

Global **launch_MM_dispatch** (const **Field** &F, const int mm, const int nn, const int kk, const typename **Field::Element** alpha, const typename **Field::Element** beta, const size_t iters, **RandIter** &G)
does nbw actually do nbw recursive calls and then call blas (check ?) ?

Global **launch_MM_dispatch** (const **Field** &F, const int mm, const int nn, const int kk, const typename **Field::Element** alpha, const typename **Field::Element** beta, const size_t iters, const int nbw, const bool par, **RandIter** &G)
does nbw actually do nbw recursive calls and then call blas (check ?) ?

Module **MMalgos**

biblio

Module **simd**

biblio

Global **test_colechelon** (**Field** &F, size_t m, size_t n, size_t r, size_t iters, **FFPACK::FFPACK_LU_TAG** LuTag, **RandIter** &G, bool par)
check lda

Global **test_det** (Field &F, size_t n, int iter, RandIter &G)

test with stride

Global **test_redcochelon** (Field &F, size_t m, size_t n, size_t r, size_t iters, FFPACK::FFPACK_LU_TAG LuTag, RandIter &G, bool par)

check Ida

Global **test_redrowechelon** (Field &F, size_t m, size_t n, size_t r, size_t iters, FFPACK::FFPACK_LU_TAG LuTag, RandIter &G, bool par)

check Ida

Global **test_rowechelon** (Field &F, size_t m, size_t n, size_t r, size_t iters, FFPACK::FFPACK_LU_TAG LuTag, RandIter &G, bool par)

check Ida

Chapter 5

Module Index

5.1 Modules

Here is a list of all modules:

CHECKER	41
FFLAS-FFPACK	41
FFLAS	42
Interfaces	42
Matrix Multiplication Algorithms	42
SIMD wrapper	42
FFPACK	43
FFLAS-FFPACK fields	43
RNS	43

Chapter 6

Namespace Index

6.1 Namespace List

Here is a list of all namespaces with brief descriptions:

FFLAS	45
FFLAS::_ftranspose_impl	194
FFLAS::BLAS3	195
FFLAS::csr_hyb_details	201
FFLAS::CuttingStrategy	201
FFLAS::details	202
FFLAS::details_spmv	210
FFLAS::ElementCategories	211
FFLAS::FieldCategories	
Traits and categories will need to be placed in a proper file later	211
FFLAS::MMHelperAlgo	211
FFLAS::ModeCategories	
Specifies the mode of action for an algorithm w.r.t	212
FFLAS::ParSeqHelper	
ParSeqHelper for both fgemm and ftrsm	212
FFLAS::Protected	213
FFLAS::sell_details	227
FFLAS::sparse_details	228
FFLAS::sparse_details_impl	242
FFLAS::StrategyParameter	282
FFLAS::StructureHelper	
StructureHelper for ftrsm	282
FFLAS::vectorised	283
FFLAS::vectorised::unswitch	288
FFPACK	
Finite Field PACK Set of elimination based routines for dense linear algebra	291
FFPACK::Protected	396
Givaro	403
MKL_CONFIG	403
RecInt	403

Chapter 7

Hierarchical Index

7.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

AlgoChooser< ModeT, ParSeq >	405
AlgoChooser< ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeq >	405
ALL< v >	405
ALL< false, v... >	406
ALL< true, v... >	406
ALL<>	406
ArbitraryPrecIntTag	406
AreEqual< X, Y >	407
AreEqual< X, X >	407
Argument	407
associatedDelayedField< Field >	408
associatedDelayedField< const FFPACK::RNSIntegerMod< RNS > >	408
associatedDelayedField< const Givaro::Modular< T, X > >	409
associatedDelayedField< const Givaro::ModularBalanced< T > >	409
associatedDelayedField< const Givaro::ZRing< T > >	410
Auto	410
Bench< Elt >	410
Bini	413
Block	413
BlockTransposeSIMD< Field, Simd, >	413
callLUdivine_small< Element >	415
callLUdivine_small< double >	415
callLUdivine_small< float >	416
CharpolyFailed	416
Checker_Empty< Field >	416
CheckerImplem_charpoly< Field, Polynomial >	417
CheckerImplem_charpoly< Givaro::ZRing< Givaro::Integer >, Polynomial >	418
CheckerImplem_Det< Field >	419
CheckerImplem_fgemm< Field >	421
CheckerImplem_ftrsm< Field >	422
CheckerImplem_invert< Field >	423
CheckerImplem_PLUQ< Field >	424
Classic	425
Column	425
CompactElement< Element >	425

CompactElement< double >	425
CompactElement< float >	426
CompactElement< int16_t >	426
CompactElement< int32_t >	426
CompactElement< int64_t >	426
compatible_data_type< Field >	427
compatible_data_type< Givaro::ZRing< double > >	427
compatible_data_type< Givaro::ZRing< float > >	427
Compose< H1, H2 >	427
Simd128_impl< true, true, false, 2 >::Converter	429
Simd128_impl< true, true, false, 4 >::Converter	429
Simd128_impl< true, true, false, 8 >::Converter	429
Simd128_impl< true, true, true, 2 >::Converter	430
Simd128_impl< true, true, true, 4 >::Converter	430
Simd128_impl< true, true, true, 8 >::Converter	430
Simd256_impl< true, false, true, 8 >::Converter	431
Simd256_impl< true, true, false, 2 >::Converter	431
Simd256_impl< true, true, false, 4 >::Converter	431
Simd256_impl< true, true, false, 8 >::Converter	432
Simd256_impl< true, true, true, 2 >::Converter	432
Simd256_impl< true, true, true, 4 >::Converter	432
Simd256_impl< true, true, true, 8 >::Converter	433
Simd512_impl< true, true, false, 8 >::Converter	433
Simd512_impl< true, true, true, 8 >::Converter	433
ConvertTo< T >	434
Coo< ValT, IdxT >	434
Coo< Field >	435
Coo< ValT, IdxT >	437
CooMat< Field >	438
CooMat< FFPACK::RNSInteger >	438
count_nonconst_lvalue_reference< T >	439
count_nonconst_lvalue_reference< const T &, O... >	439
count_nonconst_lvalue_reference< T &, O... >	440
count_nonconst_lvalue_reference< T, O... >	440
count_nonconst_lvalue_reference<>	440
CsrMat< Field >	440
CsrMat< FFPACK::RNSInteger >	440
DefaultBoundedTag	441
DefaultTag	441
DelayedTag	442
DivideAndConquer	442
ElementTraits< Element >	442
ElementTraits< double >	442
ElementTraits< FFPACK::rns_double_elt >	443
ElementTraits< float >	443
ElementTraits< Givaro::Integer >	443
ElementTraits< int16_t >	444
ElementTraits< int32_t >	444
ElementTraits< int64_t >	444
ElementTraits< int8_t >	444
ElementTraits< Reclnt::rint< K > >	445
ElementTraits< Reclnt::rmint< K, MG > >	445
ElementTraits< Reclnt::ruint< K > >	445
ElementTraits< uint16_t >	446
ElementTraits< uint32_t >	446
ElementTraits< uint64_t >	446
ElementTraits< uint8_t >	447
ElMat< Field >	447

EllMat< FFPACK::RNSInteger >	447
Failure	448
FailureCharpolyCheck	449
FailureDetCheck	449
FailureFgemmCheck	449
FailureInvertCheck	450
FailurePLUQCheck	450
FailureTrsmCheck	450
false_type	
isSparseMatrix< Field, M >	485
isSparseMatrixMKLFormat< F, M >	489
isSparseMatrixSimdFormat< F, M >	489
isZOSparseMatrix< F, M >	490
support_fast_mod< T >	764
support_simd< T >	765
support_simd_add< T >	765
support_simd_mod< T >	765
FieldSimd< _Field >	450
FieldTraits< Field >	456
FieldTraits< FFPACK::RNSInteger< T > >	457
FieldTraits< FFPACK::RNSIntegerMod< T > >	457
FieldTraits< Givaro::Modular< Element > >	458
FieldTraits< Givaro::ModularBalanced< Element > >	458
FieldTraits< Givaro::ZRing< double > >	459
FieldTraits< Givaro::ZRing< float > >	459
FieldTraits< Givaro::ZRing< Givaro::Integer > >	460
FieldTraits< Givaro::ZRing< int16_t > >	460
FieldTraits< Givaro::ZRing< int32_t > >	461
FieldTraits< Givaro::ZRing< int64_t > >	461
FieldTraits< Givaro::ZRing< Reclnt::ruint< K > > >	462
FieldTraits< Givaro::ZRing< uint16_t > >	462
FieldTraits< Givaro::ZRing< uint32_t > >	462
FieldTraits< Givaro::ZRing< uint64_t > >	463
Fixed	463
FixedPreclntTag	463
ScalFunctionsBase< Element, typename enable_if< is_floating_point< Element >::value >::type >← ::FloatingPointTestDistribution	464
ForStrategy1D< blocksize_t, Cut, Param >	464
ForStrategy2D< blocksize_t, Cut, Param >	467
ftmmLeftLowerNoTransNonUnit< Element >	471
ftmmLeftLowerNoTransUnit< Element >	471
ftmmLeftLowerTransNonUnit< Element >	471
ftmmLeftLowerTransUnit< Element >	471
ftmmLeftUpperNoTransNonUnit< Element >	471
ftmmLeftUpperNoTransUnit< Element >	471
ftmmLeftUpperTransNonUnit< Element >	471
ftmmLeftUpperTransUnit< Element >	472
ftmmRightLowerNoTransNonUnit< Element >	472
ftmmRightLowerNoTransUnit< Element >	472
ftmmRightLowerTransNonUnit< Element >	472
ftmmRightLowerTransUnit< Element >	472
ftmmRightUpperNoTransNonUnit< Element >	472
ftmmRightUpperNoTransUnit< Element >	472
ftmmRightUpperTransNonUnit< Element >	472
ftmmRightUpperTransUnit< Element >	473
ftsmLeftLowerNoTransNonUnit< Element >	473
ftsmLeftLowerNoTransUnit< Element >	473
ftsmLeftLowerTransNonUnit< Element >	473

ftsmLeftLowerTransUnit< Element >	473
ftsmLeftUpperNoTransNonUnit< Element >	473
ftsmLeftUpperNoTransUnit< Element >	474
ftsmLeftUpperTransNonUnit< Element >	474
ftsmLeftUpperTransUnit< Element >	474
ftsmRightLowerNoTransNonUnit< Element >	474
ftsmRightLowerNoTransUnit< Element >	474
ftsmRightLowerTransNonUnit< Element >	474
ftsmRightLowerTransUnit< Element >	474
ftsmRightUpperNoTransNonUnit< Element >	475
ftsmRightUpperNoTransUnit< Element >	475
ftsmRightUpperTransNonUnit< Element >	475
ftsmRightUpperTransUnit< Element >	475
GenericTag	475
GenericTag	475
Grain	475
has_minus_eq_impl< C >	476
has_minus_impl< C >	476
has_mul_eq_impl< C >	476
has_mul_impl< C >	476
has_operation< T >	477
has_plus_eq_impl< C >	477
has_plus_impl< C >	477
HelperFlag	478
HelperMod< Field, ElementTraits >	478
HelperMod< Field, ElementCategories::MachineIntTag >	479
HelperMod< Field, FFLAS::ElementCategories::ArbitraryPrecIntTag >	480
HelperMod< Field, FFLAS::ElementCategories::FixedPrecIntTag >	480
HelperMod< Field, FFLAS::ElementCategories::MachineFloatTag >	481
Hybrid	482
Info	482
Info	483
is_all_same< Args >	484
is_all_same< T, Args... >	484
is_all_same<>	484
is_simd< T >	485
Iterative	491
LazyTag	491
limits< T >	492
limits< char >	492
limits< double >	492
limits< float >	493
limits< Givaro::Integer >	494
limits< int >	494
limits< long >	495
limits< long long >	495
limits< Reclnt::rint< K > >	496
limits< Reclnt::ruint< K > >	497
limits< short int >	497
limits< signed char >	498
limits< unsigned char >	499
limits< unsigned int >	499
limits< unsigned long >	500
limits< unsigned long long >	500
limits< unsigned short int >	501
MachineFloatTag	502
MachineIntTag	502
MMHelper< Field, AlgoTrait, ModeTrait, ParSeqTrait >	502

MMHelper< FFPACK::RNSInteger< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >	507
MMHelper< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >	509
MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< Dest >, ParSeqTrait >	511
MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeqTrait >	513
MMHelper< Field, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >	515
ModeTraits< Field >	516
ModeTraits< Givaro::Modular< Element, Compute > >	517
ModeTraits< Givaro::Modular< Givaro::Integer, Compute > >	517
ModeTraits< Givaro::Modular< int16_t, Compute > >	517
ModeTraits< Givaro::Modular< int32_t, Compute > >	518
ModeTraits< Givaro::Modular< int64_t, uint64_t > >	518
ModeTraits< Givaro::Modular< int8_t, Compute > >	518
ModeTraits< Givaro::Modular< Reclnt::ruint< K >, Compute > >	519
ModeTraits< Givaro::Modular< uint16_t, Compute > >	519
ModeTraits< Givaro::Modular< uint32_t, Compute > >	519
ModeTraits< Givaro::Modular< uint8_t, Compute > >	520
ModeTraits< Givaro::ModularBalanced< Element > >	520
ModeTraits< Givaro::ModularBalanced< Givaro::Integer > >	520
ModeTraits< Givaro::ModularBalanced< int16_t > >	521
ModeTraits< Givaro::ModularBalanced< int32_t > >	521
ModeTraits< Givaro::ModularBalanced< int8_t > >	521
ModeTraits< Givaro::Montgomery< T > >	521
ModeTraits< Givaro::ZRing< double > >	522
ModeTraits< Givaro::ZRing< float > >	522
ModeTraits< Givaro::ZRing< Givaro::Integer > >	522
ModularBalanced< T >	523
ModularTag	523
Montgomery< T >	523
need_field_characteristic< Field >	523
need_field_characteristic< Givaro::Modular< Field > >	523
need_field_characteristic< Givaro::ModularBalanced< Field > >	524
NoSimd< T >	524
Parallel< C, P >	526
readMyMachineType< Field, T >	529
readMyMachineType< Field, mpz_t >	529
Recursive	530
Recursive	530
rint< K >	530
rns_double	530
rns_double_elt	535
rns_double_elt_cstptr	537
rns_double_elt_ptr	539
rns_double_extended	542
RNSElementTag	546
RNSInteger< RNS >	546
RNSInteger< FFPACK::rns_double >	546
RNSIntegerMod< RNS >	549
RNSIntegerMod< FFPACK::rns_double >	549
rnsRandIter< RNS >	556
RNSInteger< RNS >::RandIter	527
RNSIntegerMod< RNS >::RandIter	528
Row	557
ruint< K >	557
ScalFunctionsBase< Element, Enable >	562
ScalFunctions< Element >	557
ScalFunctionsBase< Element, typename enable_if< is_floating_point< Element >::value >::type >	563

ScalFunctionsBase< Element, typename enable_if< is_integral< Element >::value >::type >	564
Sequential	567
Simd128_impl< ArithType, Int, Signed, Size >	568
Simd128_impl< true, false, true, 4 >	568
Simd128_impl< true, false, true, 8 >	568
Simd128i_base	626
Simd128_impl< true, true, true, 2 >	598
Simd128_impl< true, true, false, 2 >	568
Simd128_impl< true, true, true, 4 >	608
Simd128_impl< true, true, false, 4 >	578
Simd128_impl< true, true, true, 8 >	616
Simd128_impl< true, true, false, 8 >	588
Simd256_impl< ArithType, Int, Signed, Size >	627
Simd256fp_base	709
Simd256_impl< true, false, true, 4 >	627
Simd256_impl< true, false, true, 8 >	628
Simd256i_base	709
Simd256_impl< true, true, true, 2 >	674
Simd256_impl< true, true, false, 2 >	635
Simd256_impl< true, true, true, 4 >	683
Simd256_impl< true, true, false, 4 >	645
Simd256_impl< true, true, true, 8 >	700
Simd256_impl< true, true, false, 8 >	664
Simd512_impl< ArithType, Int, Signed, Size >	710
Simd512_impl< true, false, true, 4 >	710
Simd512_impl< true, false, true, 8 >	710
Simd512i_base	737
Simd256_impl< true, true, true, 4 >	683
Simd512_impl< true, true, true, 8 >	728
Simd512_impl< true, true, false, 8 >	717
SimdChooser< T, bool, bool >	739
SimdChooser< T, false, b >	739
SimdChooser< T, true, false >	739
SimdChooser< T, true, true >	739
simdToType< T >	740
Single	740
Sparse< Field, SparseMatrix_t, IdxT, PtrT >	740
Sparse< _Field, SparseMatrix_t::COO >	740
Sparse< _Field, SparseMatrix_t::COO_ZO >	741
Sparse< _Field, SparseMatrix_t::CSR >	743
Sparse< _Field, SparseMatrix_t::CSR_ZO >	747
Sparse< _Field, SparseMatrix_t::CSR_HYB >	745
Sparse< _Field, SparseMatrix_t::ELL >	748
Sparse< _Field, SparseMatrix_t::ELL_ZO >	753
Sparse< _Field, SparseMatrix_t::ELL_simd >	750
Sparse< _Field, SparseMatrix_t::ELL_simd_ZO >	751
Sparse< _Field, SparseMatrix_t::HYB_ZO >	755
Sparse< _Field, SparseMatrix_t::SELL >	756
Sparse< _Field, SparseMatrix_t::SELL_ZO >	758
Sparse< FFPACK::RNSInteger, SparseMatrix_t::COO, int16_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::COO, int32_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::COO, int64_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::COO_ZO, int16_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::COO_ZO, int32_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::COO_ZO, int64_t >	740

Sparse< FFPACK::RNSInteger, SparseMatrix_t::CSR, int16_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::CSR, int32_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::CSR, int64_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::CSR_ZO, int16_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::CSR_ZO, int32_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::CSR_ZO, int64_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::ELL, int16_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::ELL, int32_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::ELL, int64_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::ELL_ZO, int16_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::ELL_ZO, int32_t >	740
Sparse< FFPACK::RNSInteger, SparseMatrix_t::ELL_ZO, int64_t >	740
SpMat< Field, flag >	760
StatsMatrix	761
Test< Elt >	766
TestOneMethod< Simd >	768
tfn_minus	772
tfn_minus_eq	772
tfn_mul	772
tfn_mul_eq	773
tfn_plus	773
tfn_plus_eq	773
Threads	774
ThreeD	774
ThreeDAdaptive	774
ThreeDInPlace	774
TRSMHelper< ReclterTrait, ParSeqTrait >	774
true_type	
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO > >	485
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO_ZO > >	486
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR > >	486
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_HYB > >	486
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_ZO > >	487
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL > >	487
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_ZO > >	488
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd > >	487
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > >	488
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::HYB_ZO > >	488
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL > >	488
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL_ZO > >	489
isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO_ZO > >	490
isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_ZO > >	490
isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_ZO > >	491
isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > >	490
isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL_ZO > >	491
support_fast_mod< double >	764
support_fast_mod< float >	764
support_fast_mod< int64_t >	764
TwoD	776
TwoDAdaptive	776
UnparametricTag	776
width< T >	776
width< double >	776
width< float >	777
Winograd	777
WinogradPar	777

Chapter 8

Data Structure Index

8.1 Data Structures

Here are the data structures with brief descriptions:

AlgoChooser< ModeT, ParSeq >	405
AlgoChooser< ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeq >	405
ALL< v >	405
ALL< false, v... >	406
ALL< true, v... >	406
ALL<>	406
ArbitraryPrecIntTag	
Arbitrary precision integers: GMP	406
AreEqual< X, Y >	407
AreEqual< X, X >	407
Argument	407
associatedDelayedField< Field >	408
associatedDelayedField< const FFPACK::RNSIntegerMod< RNS > >	408
associatedDelayedField< const Givaro::Modular< T, X > >	409
associatedDelayedField< const Givaro::ModularBalanced< T > >	409
associatedDelayedField< const Givaro::ZRing< T > >	410
Auto	410
Bench< Elt >	410
Bini	413
Block	413
BlockTransposeSIMD< Field, Simd, >	413
callLUdivine_small< Element >	415
callLUdivine_small< double >	415
callLUdivine_small< float >	416
CharpolyFailed	416
Checker_Empty< Field >	416
CheckerImplem_charpoly< Field, Polynomial >	417
CheckerImplem_charpoly< Givaro::ZRing< Givaro::Integer >, Polynomial >	418
CheckerImplem_Det< Field >	419
CheckerImplem_fgemm< Field >	421
CheckerImplem_ftdsm< Field >	422
CheckerImplem_invert< Field >	423
CheckerImplem_PLUQ< Field >	424
Classic	425
Column	425

CompactElement< Element >	425
CompactElement< double >	425
CompactElement< float >	426
CompactElement< int16_t >	426
CompactElement< int32_t >	426
CompactElement< int64_t >	426
compatible_data_type< Field >	427
compatible_data_type< Givaro::ZRing< double > >	427
compatible_data_type< Givaro::ZRing< float > >	427
Compose< H1, H2 >	427
Simd128_impl< true, true, false, 2 >::Converter	429
Simd128_impl< true, true, false, 4 >::Converter	429
Simd128_impl< true, true, false, 8 >::Converter	429
Simd128_impl< true, true, true, 2 >::Converter	430
Simd128_impl< true, true, true, 4 >::Converter	430
Simd128_impl< true, true, true, 8 >::Converter	430
Simd256_impl< true, false, true, 8 >::Converter	431
Simd256_impl< true, true, false, 2 >::Converter	431
Simd256_impl< true, true, false, 4 >::Converter	431
Simd256_impl< true, true, false, 8 >::Converter	432
Simd256_impl< true, true, true, 2 >::Converter	432
Simd256_impl< true, true, true, 4 >::Converter	432
Simd256_impl< true, true, true, 8 >::Converter	433
Simd512_impl< true, true, false, 8 >::Converter	433
Simd512_impl< true, true, true, 8 >::Converter	433
ConvertTo< T >	
Force conversion to appropriate element type of ElementCategory T	434
Coo< ValT, IdxT >	434
Coo< Field >	435
Coo< ValT, IdxT >	437
CooMat< Field >	438
count_nonconst_lvalue_reference< T >	439
count_nonconst_lvalue_reference< const T &, O... >	439
count_nonconst_lvalue_reference< T &, O... >	440
count_nonconst_lvalue_reference< T, O... >	440
count_nonconst_lvalue_reference<>	440
CsrMat< Field >	440
DefaultBoundedTag	
Use standard field operations, but keeps track of bounds on input and output	441
DefaultTag	
No specific mode of action: use standard field operations	441
DelayedTag	
Performs field operations with delayed mod reductions. Ensures result is reduced	442
DivideAndConquer	442
ElementTraits< Element >	
ElementTraits	442
ElementTraits< double >	442
ElementTraits< FFPACK::rns_double_elt >	443
ElementTraits< float >	443
ElementTraits< Givaro::Integer >	443
ElementTraits< int16_t >	444
ElementTraits< int32_t >	444
ElementTraits< int64_t >	444
ElementTraits< int8_t >	444
ElementTraits< Reclnt::rint< K > >	445
ElementTraits< Reclnt::rmint< K, MG > >	445
ElementTraits< Reclnt::ruint< K > >	445
ElementTraits< uint16_t >	446

ElementTraits< uint32_t >	446
ElementTraits< uint64_t >	446
ElementTraits< uint8_t >	447
ElMat< Field >	447
Failure	
A precondition failed	448
FailureCharpolyCheck	449
FailureDetCheck	449
FailureFgemmCheck	449
FailureInvertCheck	450
FailurePLUQCheck	450
FailureTrsmCheck	450
FieldSimd< _Field >	450
FieldTraits< Field >	
FieldTrait	456
FieldTraits< FFPACK::RNSInteger< T > >	457
FieldTraits< FFPACK::RNSIntegerMod< T > >	457
FieldTraits< Givaro::Modular< Element > >	458
FieldTraits< Givaro::ModularBalanced< Element > >	458
FieldTraits< Givaro::ZRing< double > >	459
FieldTraits< Givaro::ZRing< float > >	459
FieldTraits< Givaro::ZRing< Givaro::Integer > >	460
FieldTraits< Givaro::ZRing< int16_t > >	460
FieldTraits< Givaro::ZRing< int32_t > >	461
FieldTraits< Givaro::ZRing< int64_t > >	461
FieldTraits< Givaro::ZRing< Reclnt::ruint< K > > >	462
FieldTraits< Givaro::ZRing< uint16_t > >	462
FieldTraits< Givaro::ZRing< uint32_t > >	462
FieldTraits< Givaro::ZRing< uint64_t > >	463
Fixed	463
FixedPrecIntTag	
Fixed precision integers above machine precision: Givaro::reclnt	463
ScalFunctionsBase< Element, typename enable_if< is_floating_point< Element >::value >::type >::FloatingPointTestDistribution	
464	
ForStrategy1D< blocksize_t, Cut, Param >	464
ForStrategy2D< blocksize_t, Cut, Param >	467
ftmmLeftLowerNoTransNonUnit< Element >	471
ftmmLeftLowerNoTransUnit< Element >	471
ftmmLeftLowerTransNonUnit< Element >	471
ftmmLeftLowerTransUnit< Element >	471
ftmmLeftUpperNoTransNonUnit< Element >	471
ftmmLeftUpperNoTransUnit< Element >	471
ftmmLeftUpperTransNonUnit< Element >	471
ftmmLeftUpperTransUnit< Element >	472
ftmmRightLowerNoTransNonUnit< Element >	472
ftmmRightLowerNoTransUnit< Element >	472
ftmmRightLowerTransNonUnit< Element >	472
ftmmRightLowerTransUnit< Element >	472
ftmmRightUpperNoTransNonUnit< Element >	472
ftmmRightUpperNoTransUnit< Element >	472
ftmmRightUpperTransNonUnit< Element >	472
ftmmRightUpperTransUnit< Element >	473
ftsmLeftLowerNoTransNonUnit< Element >	473
ftsmLeftLowerNoTransUnit< Element >	473
ftsmLeftLowerTransNonUnit< Element >	473
ftsmLeftLowerTransUnit< Element >	473
ftsmLeftUpperNoTransNonUnit< Element >	
Computes the maximal size for delaying the modular reduction in a triangular system resolution	473

ftsmLeftUpperNoTransUnit< Element >	474
ftsmLeftUpperTransNonUnit< Element >	474
ftsmLeftUpperTransUnit< Element >	474
ftsmRightLowerNoTransNonUnit< Element >	474
ftsmRightLowerNoTransUnit< Element >	474
ftsmRightLowerTransNonUnit< Element >	474
ftsmRightLowerTransUnit< Element >	474
ftsmRightUpperNoTransNonUnit< Element >	475
ftsmRightUpperNoTransUnit< Element >	475
ftsmRightUpperTransNonUnit< Element >	475
ftsmRightUpperTransUnit< Element >	475
GenericTag	
Default is generic	475
GenericTag	
Generic ring	475
Grain	475
has_minus_eq_impl< C >	476
has_minus_impl< C >	476
has_mul_eq_impl< C >	476
has_mul_impl< C >	476
has_operation< T >	477
has_plus_eq_impl< C >	477
has_plus_impl< C >	477
HelperFlag	478
HelperMod< Field, ElementTraits >	478
HelperMod< Field, ElementCategories::MachineIntTag >	479
HelperMod< Field, FFLAS::ElementCategories::ArbitraryPrecIntTag >	480
HelperMod< Field, FFLAS::ElementCategories::FixedPrecIntTag >	480
HelperMod< Field, FFLAS::ElementCategories::MachineFloatTag >	481
Hybrid	482
Info	482
Info	483
is_all_same< Args >	484
is_all_same< T, Args... >	484
is_all_same<>	484
is_simd< T >	485
isSparseMatrix< Field, M >	485
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO > >	485
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO_ZO > >	486
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR > >	486
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_HYB > >	486
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_ZO > >	487
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL > >	487
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd > >	487
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > >	488
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_ZO > >	488
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::HYB_ZO > >	488
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL > >	488
isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL_ZO > >	489
isSparseMatrixMKLFormat< F, M >	489
isSparseMatrixSimdFormat< F, M >	489
isZOSparseMatrix< F, M >	490
isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO_ZO > >	490
isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_ZO > >	490
isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > >	490
isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_ZO > >	491
isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL_ZO > >	491
Iterative	491

LazyTag	
Performs field operations with delayed mod only when necessary. Result may not be reduced	491
limits< T >	492
limits< char >	492
limits< double >	492
limits< float >	493
limits< Givaro::Integer >	494
limits< int >	494
limits< long >	495
limits< long long >	495
limits< RecInt::rint< K > >	496
limits< RecInt::ruint< K > >	497
limits< short int >	497
limits< signed char >	498
limits< unsigned char >	499
limits< unsigned int >	499
limits< unsigned long >	500
limits< unsigned long long >	500
limits< unsigned short int >	501
MachineFloatTag	
Float or double	502
MachineIntTag	
Short, int, long, long long, and unsigned variants	502
MMHelper< Field, AlgoTrait, ModeTrait, ParSeqTrait >	502
MMHelper< FFPACK::RNSInteger< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >	507
MMHelper< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >	509
MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< Dest >, ParSeqTrait >	511
MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeqTrait >	513
MMHelper< Field, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >	
FGEMM Helper for Default and ConvertTo modes of operation	515
ModeTraits< Field >	
ModeTraits	516
ModeTraits< Givaro::Modular< Element, Compute > >	517
ModeTraits< Givaro::Modular< Givaro::Integer, Compute > >	517
ModeTraits< Givaro::Modular< int16_t, Compute > >	517
ModeTraits< Givaro::Modular< int32_t, Compute > >	518
ModeTraits< Givaro::Modular< int64_t, uint64_t > >	518
ModeTraits< Givaro::Modular< int8_t, Compute > >	518
ModeTraits< Givaro::Modular< RecInt::ruint< K >, Compute > >	519
ModeTraits< Givaro::Modular< uint16_t, Compute > >	519
ModeTraits< Givaro::Modular< uint32_t, Compute > >	519
ModeTraits< Givaro::Modular< uint8_t, Compute > >	520
ModeTraits< Givaro::ModularBalanced< Element > >	520
ModeTraits< Givaro::ModularBalanced< Givaro::Integer > >	520
ModeTraits< Givaro::ModularBalanced< int16_t > >	521
ModeTraits< Givaro::ModularBalanced< int32_t > >	521
ModeTraits< Givaro::ModularBalanced< int8_t > >	521
ModeTraits< Givaro::Montgomery< T > >	521
ModeTraits< Givaro::ZRing< double > >	522
ModeTraits< Givaro::ZRing< float > >	522
ModeTraits< Givaro::ZRing< Givaro::Integer > >	522
ModularBalanced< T >	523
ModularTag	
This is a modular field like e.g. Modular<T> or ModularBalanced<T>	523
Montgomery< T >	523
need_field_characteristic< Field >	523
need_field_characteristic< Givaro::Modular< Field > >	523

need_field_characteristic< Givaro::ModularBalanced< Field > >	524
NoSimd< T >	524
Parallel< C, P >	526
RNSInteger< RNS >::RandIter	527
RNSIntegerMod< RNS >::RandIter	528
readMyMachineType< Field, T >	529
readMyMachineType< Field, mpz_t >	529
Recursive	530
Recursive	530
rint< K >	530
rns_double	530
rns_double_elt	535
rns_double_elt_cstptr	537
rns_double_elt_ptr	539
rns_double_extended	542
RNSElementTag	
Representation in a Residue Number System	546
RNSInteger< RNS >	546
RNSIntegerMod< RNS >	549
rnsRandIter< RNS >	556
Row	557
ruint< K >	557
ScalFunctions< Element >	557
ScalFunctionsBase< Element, Enable >	562
ScalFunctionsBase< Element, typename enable_if< is_floating_point< Element >::value >::type >	563
ScalFunctionsBase< Element, typename enable_if< is_integral< Element >::value >::type >	564
Sequential	567
Simd128_impl< ArithType, Int, Signed, Size >	568
Simd128_impl< true, false, true, 4 >	568
Simd128_impl< true, false, true, 8 >	568
Simd128_impl< true, true, false, 2 >	568
Simd128_impl< true, true, false, 4 >	578
Simd128_impl< true, true, false, 8 >	588
Simd128_impl< true, true, true, 2 >	598
Simd128_impl< true, true, true, 4 >	608
Simd128_impl< true, true, true, 8 >	616
Simd128i_base	626
Simd256_impl< ArithType, Int, Signed, Size >	627
Simd256_impl< true, false, true, 4 >	627
Simd256_impl< true, false, true, 8 >	628
Simd256_impl< true, true, false, 2 >	635
Simd256_impl< true, true, false, 4 >	645
Simd256_impl< true, true, false, 8 >	664
Simd256_impl< true, true, true, 2 >	674
Simd256_impl< true, true, true, 4 >	683
Simd256_impl< true, true, true, 8 >	700
Simd256fp_base	709
Simd256i_base	709
Simd512_impl< ArithType, Int, Signed, Size >	710
Simd512_impl< true, false, true, 4 >	710
Simd512_impl< true, false, true, 8 >	710
Simd512_impl< true, true, false, 8 >	717
Simd512_impl< true, true, true, 8 >	728
Simd512i_base	737
SimdChooser< T, bool, bool >	739
SimdChooser< T, false, b >	739
SimdChooser< T, true, false >	739
SimdChooser< T, true, true >	739

<code>simdToType< T ></code>	740
<code>Single</code>	740
<code>Sparse< Field, SparseMatrix_t, IdxT, PtrT ></code>	740
<code>Sparse< _Field, SparseMatrix_t::COO ></code>	740
<code>Sparse< _Field, SparseMatrix_t::COO_ZO ></code>	741
<code>Sparse< _Field, SparseMatrix_t::CSR ></code>	743
<code>Sparse< _Field, SparseMatrix_t::CSR_HYB ></code>	745
<code>Sparse< _Field, SparseMatrix_t::CSR_ZO ></code>	747
<code>Sparse< _Field, SparseMatrix_t::ELL ></code>	748
<code>Sparse< _Field, SparseMatrix_t::ELL_simd ></code>	750
<code>Sparse< _Field, SparseMatrix_t::ELL_simd_ZO ></code>	751
<code>Sparse< _Field, SparseMatrix_t::ELL_ZO ></code>	753
<code>Sparse< _Field, SparseMatrix_t::HYB_ZO ></code>	755
<code>Sparse< _Field, SparseMatrix_t::SELL ></code>	756
<code>Sparse< _Field, SparseMatrix_t::SELL_ZO ></code>	758
<code>SpMat< Field, flag ></code>	760
<code>StatsMatrix</code>	761
<code>support_fast_mod< T ></code>	764
<code>support_fast_mod< double ></code>	764
<code>support_fast_mod< float ></code>	764
<code>support_fast_mod< int64_t ></code>	764
<code>support_simd< T ></code>	765
<code>support_simd_add< T ></code>	765
<code>support_simd_mod< T ></code>	765
<code>Test< Elt ></code>	766
<code>TestOneMethod< Simd ></code>	768
<code>tfn_minus</code>	772
<code>tfn_minus_eq</code>	772
<code>tfn_mul</code>	772
<code>tfn_mul_eq</code>	773
<code>tfn_plus</code>	773
<code>tfn_plus_eq</code>	773
<code>Threads</code>	774
<code>ThreeD</code>	774
<code>ThreeDAdaptive</code>	774
<code>ThreeDInPlace</code>	774
<code>TRSMHelper< ReclterTrait, ParSeqTrait ></code>	
TRSM Helper	774
<code>TwoD</code>	776
<code>TwoDAdaptive</code>	776
<code>UnparametricTag</code>	
If the field uses a representation with infix operators	776
<code>width< T ></code>	776
<code>width< double ></code>	776
<code>width< float ></code>	777
<code>Winograd</code>	777
<code>WinogradPar</code>	777

Chapter 9

File Index

9.1 File List

Here is a list of all files with brief descriptions:

arithprog.C	779
fsyrk.C	780
fsytrf.C	781
ftrtri.C	781
winograd.C	782
benchmark-charpoly-mp.C	783
benchmark-charpoly.C	784
benchmark-checkers.C	785
benchmark-dgemm.C	786
benchmark-dgetrf.C	787
benchmark-dgetri.C	787
benchmark-dsytrf.C	788
benchmark-dtrsm.C	789
benchmark-dtrtri.C	789
benchmark-fadd-lvl2.C	790
benchmark-fdot.C	791
benchmark-fgemm-mp.C	791
benchmark-fgemm-rns.C	792
benchmark-fgemm.C	794
benchmark-fgemv-mp.C	795
benchmark-fgemv.C	796
benchmark-fgesv.C	799
benchmark-fsyr2k.C	799
benchmark-fsyrk.C	800
benchmark-fsytrf.C	800
benchmark-ftrsm-mp.C	801
benchmark-ftrsm.C	802
benchmark-ftrsv.C	802
benchmark-ftrtri.C	803
benchmark-inverse.C	804
benchmark-lqup-mp.C	804
benchmark-lqup.C	805
benchmark-pluq.C	805
benchmark-quasisep.C	806
benchmark-storage-transpose.C	807

benchmark-wino.C	808
config.h	809
fflas-ffpack/config.h	812
mainpage.doxy	816
autotune/charpoly.C	816
examples/charpoly.C	816
det.C	817
matmul.C	817
autotune/pluq.C	818
examples/pluq.C	818
rank.C	819
solve.C	819
checker_charpoly.inl	820
checker_det.inl	820
checker_empty.h	820
checker_fgemm.inl	821
checker_ftrsm.inl	821
checker_invert.inl	821
checker_pluq.inl	822
checkers.doxy	822
checkers_fflas.h	822
checkers_fflas.inl	823
checkers_ffpack.h	823
checkers_ffpack.inl	824
config-blas.h	824
fflas-ffpack-config.h	
Defaults for optimised values	831
fflas-ffpack-default-thresholds.h	831
fflas-ffpack-thresholds.h	832
fflas-ffpack.doxy	832
fflas-ffpack.h	
Includes FFLAS and FFPACK	832
fflas.doxy	832
fflas.h	
Finite Field Linear Algebra Subroutines	832
fflas_bounds.inl	834
fflas_enum.h	835
fflas_fadd.h	835
fflas_fadd.inl	837
fflas_fassign.h	838
fflas_fassign.inl	838
fflas_faxpy.inl	839
fflas_fdot.inl	840
fflas_fgemm.inl	841
fgemm_classical.inl	843
fgemm_classical_mp.inl	
Matrix multiplication with multiprecision input (either over $\mathbb{Z}$ or over $\mathbb{Z}/p\mathbb{Z}$)	843
fgemm_winograd.inl	845
matmul.doxy	846
schedule_bini.inl	
Bini implementation	846
schedule_winograd.inl	847
schedule_winograd_acc.inl	847
schedule_winograd_acc_ip.inl	848
schedule_winograd_ip.inl	849
fflas_fgmv.inl	849
fflas_fgmv_mp.inl	851
fflas_fger.inl	852

fflas_fger_mp.inl	853
fflas_freduce.h	854
fflas_freduce.inl	855
fflas_freduce_mp.inl	856
fflas_freivalds.inl	857
fflas_fscal.h	857
fflas_fscal.inl	857
fflas_fscal_mp.inl	859
fflas_fsyr2k.inl	859
fflas_fsyrk.inl	860
fflas_fsyrk_strassen.inl	862
fflas_ftmm.inl	863
fflas_ftsm.inl	863
fflas_ftsm_mp.inl	
Triangular system with matrix right hand side over multiprecision domain (either over $\mathbb{Z}$ or over $\mathbb{Z}/p\mathbb{Z}$)	864
fflas_ftsv.inl	865
fflas_helpers.inl	865
igemm.doxy	866
igemm.h	866
igemm.inl	867
igemm_kernels.h	867
igemm_kernels.inl	868
igemm_tools.h	869
igemm_tools.inl	869
fflas_level1.inl	869
fflas_level2.inl	872
fflas_level3.inl	874
fflas_pfgemm.inl	877
fflas_pftsm.inl	878
fflas_simd.h	878
simd.doxy	880
simd128.inl	880
simd128_double.inl	881
simd128_float.inl	881
simd128_int16.inl	881
simd128_int32.inl	882
simd128_int64.inl	882
simd256.inl	883
simd256_double.inl	883
simd256_float.inl	884
simd256_int16.inl	884
simd256_int32.inl	885
simd256_int64.inl	885
simd512.inl	886
simd512_double.inl	886
simd512_float.inl	887
simd512_int32.inl	887
simd512_int64.inl	887
simd_modular.inl	888
fflas_sparse.h	888
fflas_sparse.inl	892
coo.h	894
coo_spm.inl	895
coo_spmv.inl	896
coo_utils.inl	897
csr.h	897
csr_pspm.inl	898

csr_pspmv.inl	899
csr_spmm.inl	899
csr_spmv.inl	900
csr_utils.inl	901
csr_hyb.h	902
csr_hyb_pspmm.inl	902
csr_hyb_pspmv.inl	903
csr_hyb_spmm.inl	903
csr_hyb_spmv.inl	904
csr_hyb_utils.inl	904
ell.h	905
ell_pspmm.inl	905
ell_pspmv.inl	906
ell_spmm.inl	907
ell_spmv.inl	908
ell_utils.inl	909
ell_simd.h	909
ell_simd_pspmv.inl	910
ell_simd_spmv.inl	910
ell_simd_utils.inl	911
hyb_zo.h	912
hyb_zo_pspmm.inl	912
hyb_zo_pspmv.inl	913
hyb_zo_spmm.inl	913
hyb_zo_spmv.inl	914
hyb_zo_utils.inl	914
read_sparse.h	915
sell.h	916
sell_pspmv.inl	916
sell_spmv.inl	917
sell_utils.inl	917
sparse_matrix_traits.h	918
utils.h	920
fflas_transpose.h	
Transpose the storage of the matrix (switch between row and col major mode)	920
ffpack.dox	921
ffpack.h	
Set of elimination based routines for dense linear algebra	921
ffpack.inl	930
ffpack_bruhatgen.inl	931
ffpack_charpoly.inl	933
ffpack_charpoly_danilevski.inl	933
ffpack_charpoly_kgfast.inl	934
ffpack_charpoly_kgfastgeneralized.inl	934
ffpack_charpoly_kglu.inl	935
ffpack_charpoly_mp.inl	935
ffpack_det_mp.inl	936
ffpack_echelonforms.inl	937
ffpack_fgesv.inl	938
ffpack_fgetrs.inl	938
ffpack_frobenius.inl	939
ffpack_fsytrf.inl	940
ffpack_ftrssyr2k.inl	941
ffpack_ftrstr.inl	941
ffpack_ftrtr.inl	942
ffpack_invert.inl	942
ffpack_krylovelim.inl	943
ffpack_ludivine.inl	943

ffpack_ludivine_mp.inl	944
ffpack_minpoly.inl	945
ffpack_permutation.inl	945
ffpack_pluq.inl	948
ffpack_pluq_mp.inl	948
ffpack_ppluq.inl	949
ffpack_rankprofiles.inl	950
field-traits.h	
Field Traits	951
field.doxy	953
rns-double-elt.h	
Rns elt structure with double support	953
rns-double-recint.inl	954
rns-double.h	
Rns structure with double support	954
rns-double.inl	955
rns-integer-mod.h	
Representation of $\mathbb{Z}/p\mathbb{Z}$ using RNS representation (note: fixed precision)	955
rns-integer.h	
Representation of $\mathbb{Z}$ using RNS representation (note: fixed precision)	956
rns.h	957
rns.inl	957
interfaces.doxy	957
fflas_c.h	957
fflas_L1_inst.C	969
fflas_L1_inst.h	970
fflas_L1_inst_implem.inl	971
fflas_L2_inst.C	972
fflas_L2_inst.h	973
fflas_L2_inst_implem.inl	974
fflas_L3_inst.C	976
fflas_L3_inst.h	977
fflas_L3_inst_implem.inl	978
fflas_lv1.C	
C functions calls for level 1 FFLAS in flas-c.h	979
fflas_lv2.C	
C functions calls for level 2 FFLAS in flas-c.h	983
fflas_lv3.C	
C functions calls for level 3 FFLAS in flas-c.h	989
fflas_sparse.C	
C functions calls for level 1.5 and 2.5 FFLAS in flas-c.h	990
ffpack.C	
C functions calls for FFPACK in ffpack-c.h	991
ffpack_c.h	1011
ffpack_inst.C	1031
ffpack_inst.h	1032
ffpack_inst_implem.inl	1033
blockcuts.inl	1036
fflas_plevel1.h	1038
kaapi_routines.inl	1038
parallel.h	1038
pfgemm_variants.inl	1045
pfgemv.inl	1045
align-allocator.h	1046
args-parser.h	1046
bit_manipulation.h	1048
cast.h	1049

debug.h	
Various utilities for debugging	1049
fflas_intrinsic.h	1050
fflas_io.h	1050
fflas_memory.h	1051
fflas_randommatrix.h	1051
flimits.h	1053
Matio.h	1054
test-utils.h	1055
timer.h	1056
cblas.C	1056
clapack.C	1056
cuda.C	1057
fblas.C	1057
lapack.C	1058
regression-check.C	1059
test-charpoly-check.C	1060
test-charpoly.C	1060
test-compressQ.C	1061
test-det-check.C	1062
test-det.C	1063
test-echelon.C	1063
test-fadd.C	1066
test-fdot.C	1067
test-fgemm-check.C	1068
test-fgemm.C	1069
test-fgemv.C	1072
test-fger.C	1073
test-fgesv.C	1075
test-finit.C	1076
test-fscal.C	1077
test-fsyr2k.C	1079
test-fsyrk.C	1080
test-fsytrf.C	1082
test-ftrmm.C	1083
test-ftrmv.C	1084
test-ftrsm-check.C	1086
test-ftrsm.C	1086
test-ftrssyr2k.C	1087
test-ftrstr.C	1089
test-ftrsv.C	1090
test-ftrtri.C	1091
test-interfaces-c.c	1092
test-invert-check.C	1092
test-io.C	1093
test-lu.C	1094
test-maxdelayeddim.C	1098
test-minpoly.C	1098
test-multifile1.C	1099
test-multifile2.C	1099
test-nullspace.C	1100
test-permutations.C	1101
test-pluq-check.C	1102
test-quasisep.C	1103
test-rankprofiles.C	1104
test-rpm.C	1105
test-simd.C	1105
test-solve.C	1109

test-storage-transpose.C	1109
101-fgemm.C	1110
2x2-fgemm.C	1110
2x2-ftrsv.C	1111
2x2-pluq.C	1111
fflas-101_1.C	1112
fflas-101_3.C	1112
fflas_101.C	1112
fflas_101_lvl1.C	1113
ffpack-fgesv.C	1113
ffpack-solve.C	1113

Chapter 10

Module Documentation

10.1 CHECKER

Class CHECKER provides functions to verify computations in [FFLAS](#) and [FFPACK](#).

Class CHECKER provides functions to verify computations in [FFLAS](#) and [FFPACK](#).

10.2 FFLAS-FFPACK

the [FFLAS FFPACK](#) library

Modules

- [FFLAS](#)
The C-style wrapper of BLAS for finite field linear algebra.
- [Interfaces](#)
Interfaces for FFLAS-FFPACK.

10.2.1 Detailed Description

the [FFLAS FFPACK](#) library

C++ header library for fast exact dense linear algebra

See also

[FFLAS](#)
[FFPACK](#)

10.2.2 FFLAS

The C-style wrapper of BLAS for finite field linear algebra.

The C-style wrapper of BLAS for finite field linear algebra.

[FFLAS](#), Finite Field Linear Algebra Subroutines, provide basic linear algebra subroutines based on the BLAS interface. Therefore, the specifications are in C style; only the field given as a template parameter requires C++.

As much as possible, these routines use `ATLAS/BLAS` computations and achieve therefore high efficiency.

10.2.3 Interfaces

Interfaces for FFLAS-FFPACK.

Interfaces for FFLAS-FFPACK.

C interface in folder

See also

`libs`

10.3 Matrix Multiplication Algorithms

Matrix Multiplication (level 3) algorithms.

Files

- file [schedule_bini.inl](#)
Bini implementation.

10.3.1 Detailed Description

Matrix Multiplication (level 3) algorithms.

[Todo](#) biblio

10.4 SIMD wrapper

wraps SIMD functions Supportst SSE4.1, AVX, AVX2.

wraps SIMD functions Supportst SSE4.1, AVX, AVX2.

[Todo](#) biblio

10.5 FFPACK

Class [FFPACK](#) provides functions using fflas much as Lapack uses BLAS.

Namespaces

- namespace [FFPACK](#)
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

10.5.1 Detailed Description

Class [FFPACK](#) provides functions using fflas much as Lapack uses BLAS.

10.6 FFLAS-FFPACK fields

fields in the FFLAS-FFPACK library

Files

- file [rns-double-elt.h](#)
rns elt structure with double support
- file [rns-double.h](#)
rns structure with double support
- file [rns-integer-mod.h](#)
representation of $\mathbb{Z}/p\mathbb{Z}$ using RNS representation (note: fixed precision)
- file [rns-integer.h](#)
representation of $\mathbb{Z}$ using RNS representation (note: fixed precision)
- file [rns.h](#)

10.6.1 Detailed Description

fields in the FFLAS-FFPACK library

Unparametric/Random elements

[Todo](#) biblio

10.7 RNS

just include them all

just include them all

Chapter 11

Namespace Documentation

11.1 FFLAS Namespace Reference

Namespaces

- namespace [_frtranspose_impl](#)
- namespace [BLAS3](#)
- namespace [csr_hyb_details](#)
- namespace [CuttingStrategy](#)
- namespace [details](#)
- namespace [details_spmv](#)
- namespace [ElementCategories](#)
- namespace [FieldCategories](#)

Traits and categories will need to be placed in a proper file later.

- namespace [MMHelperAlgo](#)
- namespace [ModeCategories](#)

Specifies the mode of action for an algorithm w.r.t.

- namespace [ParSeqHelper](#)

ParSeqHelper for both fgemm and ftrsm.

- namespace [Protected](#)
- namespace [sell_details](#)
- namespace [sparse_details](#)
- namespace [sparse_details_impl](#)
- namespace [StrategyParameter](#)
- namespace [StructureHelper](#)

StructureHelper for ftrsm.

- namespace [vectorised](#)

Data Structures

- struct [AlgoChooser](#)
- struct [AlgoChooser< ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeq >](#)
- struct [associatedDelayedField](#)
- struct [associatedDelayedField< const FFPACK::RNSIntegerMod< RNS > >](#)
- struct [associatedDelayedField< const Givaro::Modular< T, X > >](#)
- struct [associatedDelayedField< const Givaro::ModularBalanced< T > >](#)
- struct [associatedDelayedField< const Givaro::ZRing< T > >](#)

- struct [BlockTransposeSIMD](#)
- struct [Checker_Empty](#)
- class [CheckerImplem_fgemm](#)
- class [CheckerImplem_ftsm](#)
- struct [CooMat](#)
- struct [CsrMat](#)
- struct [ElementTraits](#)
 - ElementTraits.*
- struct [ElementTraits< double >](#)
- struct [ElementTraits< FFPACK::rns_double_elt >](#)
- struct [ElementTraits< float >](#)
- struct [ElementTraits< Givaro::Integer >](#)
- struct [ElementTraits< int16_t >](#)
- struct [ElementTraits< int32_t >](#)
- struct [ElementTraits< int64_t >](#)
- struct [ElementTraits< int8_t >](#)
- struct [ElementTraits< Reclnt::rint< K > >](#)
- struct [ElementTraits< Reclnt::rmint< K, MG > >](#)
- struct [ElementTraits< Reclnt::ruint< K > >](#)
- struct [ElementTraits< uint16_t >](#)
- struct [ElementTraits< uint32_t >](#)
- struct [ElementTraits< uint64_t >](#)
- struct [ElementTraits< uint8_t >](#)
- struct [ElIMat](#)
- struct [FieldTraits](#)
 - FieldTrait.*
- struct [FieldTraits< FFPACK::RNSInteger< T > >](#)
- struct [FieldTraits< FFPACK::RNSIntegerMod< T > >](#)
- struct [FieldTraits< Givaro::Modular< Element > >](#)
- struct [FieldTraits< Givaro::ModularBalanced< Element > >](#)
- struct [FieldTraits< Givaro::ZRing< double > >](#)
- struct [FieldTraits< Givaro::ZRing< float > >](#)
- struct [FieldTraits< Givaro::ZRing< Givaro::Integer > >](#)
- struct [FieldTraits< Givaro::ZRing< int16_t > >](#)
- struct [FieldTraits< Givaro::ZRing< int32_t > >](#)
- struct [FieldTraits< Givaro::ZRing< int64_t > >](#)
- struct [FieldTraits< Givaro::ZRing< Reclnt::ruint< K > > >](#)
- struct [FieldTraits< Givaro::ZRing< uint16_t > >](#)
- struct [FieldTraits< Givaro::ZRing< uint32_t > >](#)
- struct [FieldTraits< Givaro::ZRing< uint64_t > >](#)
- struct [ForStrategy1D](#)
- struct [ForStrategy2D](#)
- struct [has_minus_eq_impl](#)
- struct [has_minus_impl](#)
- struct [has_mul_eq_impl](#)
- struct [has_mul_impl](#)
- struct [has_operation](#)
- struct [has_plus_eq_impl](#)
- struct [has_plus_impl](#)
- struct [HelperFlag](#)
- struct [isSparseMatrix](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO > >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO_ZO > >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR > >](#)

- struct [isSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::CSR_HYB > >
- struct [isSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::CSR_ZO > >
- struct [isSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::ELL > >
- struct [isSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::ELL_simd > >
- struct [isSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > >
- struct [isSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::ELL_ZO > >
- struct [isSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::HYB_ZO > >
- struct [isSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::SELL > >
- struct [isSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::SELL_ZO > >
- struct [isSparseMatrixMKLFormat](#)
- struct [isSparseMatrixSimdFormat](#)
- struct [isZOSparseMatrix](#)
- struct [isZOSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::COO_ZO > >
- struct [isZOSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::CSR_ZO > >
- struct [isZOSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > >
- struct [isZOSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::ELL_ZO > >
- struct [isZOSparseMatrix](#)< Field, Sparse< Field, SparseMatrix_t::SELL_ZO > >
- struct [MMHelper](#)
- struct [MMHelper](#)< FFPACK::RNSInteger< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >
- struct [MMHelper](#)< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >
- struct [MMHelper](#)< Field, AlgoTrait, ModeCategories::ConvertTo< Dest >, ParSeqTrait >
- struct [MMHelper](#)< Field, AlgoTrait, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeqTrait >
- struct [MMHelper](#)< Field, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >
- *FGEMM Helper for Default and ConvertTo modes of operation.*
- struct [ModeTraits](#)
- *ModeTraits.*
- struct [ModeTraits](#)< Givaro::Modular< Element, Compute > >
- struct [ModeTraits](#)< Givaro::Modular< Givaro::Integer, Compute > >
- struct [ModeTraits](#)< Givaro::Modular< int16_t, Compute > >
- struct [ModeTraits](#)< Givaro::Modular< int32_t, Compute > >
- struct [ModeTraits](#)< Givaro::Modular< int64_t, uint64_t > >
- struct [ModeTraits](#)< Givaro::Modular< int8_t, Compute > >
- struct [ModeTraits](#)< Givaro::Modular< RecInt::ruint< K >, Compute > >
- struct [ModeTraits](#)< Givaro::Modular< uint16_t, Compute > >
- struct [ModeTraits](#)< Givaro::Modular< uint32_t, Compute > >
- struct [ModeTraits](#)< Givaro::Modular< uint8_t, Compute > >
- struct [ModeTraits](#)< Givaro::ModularBalanced< Element > >
- struct [ModeTraits](#)< Givaro::ModularBalanced< Givaro::Integer > >
- struct [ModeTraits](#)< Givaro::ModularBalanced< int16_t > >
- struct [ModeTraits](#)< Givaro::ModularBalanced< int32_t > >
- struct [ModeTraits](#)< Givaro::ModularBalanced< int8_t > >
- struct [ModeTraits](#)< Givaro::Montgomery< T > >
- struct [ModeTraits](#)< Givaro::ZRing< double > >
- struct [ModeTraits](#)< Givaro::ZRing< float > >
- struct [ModeTraits](#)< Givaro::ZRing< Givaro::Integer > >
- struct [readMyMachineType](#)
- struct [readMyMachineType](#)< Field, mpz_t >
- struct [Sparse](#)
- struct [Sparse](#)< _Field, SparseMatrix_t::COO >
- struct [Sparse](#)< _Field, SparseMatrix_t::COO_ZO >
- struct [Sparse](#)< _Field, SparseMatrix_t::CSR >
- struct [Sparse](#)< _Field, SparseMatrix_t::CSR_HYB >
- struct [Sparse](#)< _Field, SparseMatrix_t::CSR_ZO >
- struct [Sparse](#)< _Field, SparseMatrix_t::ELL >

- struct [Sparse<_Field, SparseMatrix_t::ELL_simd>](#)
- struct [Sparse<_Field, SparseMatrix_t::ELL_simd_ZO>](#)
- struct [Sparse<_Field, SparseMatrix_t::ELL_ZO>](#)
- struct [Sparse<_Field, SparseMatrix_t::HYB_ZO>](#)
- struct [Sparse<_Field, SparseMatrix_t::SELL>](#)
- struct [Sparse<_Field, SparseMatrix_t::SELL_ZO>](#)
- struct [SpMat](#)
- struct [StatsMatrix](#)
- struct [support_fast_mod](#)
- struct [support_fast_mod<double>](#)
- struct [support_fast_mod<float>](#)
- struct [support_fast_mod<int64_t>](#)
- struct [support_simd](#)
- struct [support_simd_add](#)
- struct [support_simd_mod](#)
- struct [tfn_minus](#)
- struct [tfn_minus_eq](#)
- struct [tfn_mul](#)
- struct [tfn_mul_eq](#)
- struct [tfn_plus](#)
- struct [tfn_plus_eq](#)
- struct [TRSMHelper](#)

TRSM Helper.

Typedefs

- template<class [Field](#)>
using [Checker_fgemm](#) = [FFLAS::Checker_Empty<Field>](#)
- template<class [Field](#)>
using [Checker_ftrsm](#) = [FFLAS::Checker_Empty<Field>](#)
- template<class [Field](#)>
using [ForceCheck_fgemm](#) = [CheckerImplem_fgemm<Field>](#)
- template<class [Field](#)>
using [ForceCheck_ftrsm](#) = [CheckerImplem_ftrsm<Field>](#)
- using [ZOSparseMatrix](#) = std::true_type
- using [NotZOSparseMatrix](#) = std::false_type
- using [SimdSparseMatrix](#) = std::true_type
- using [NoSimdSparseMatrix](#) = std::false_type
- using [MKLSparseMatrixFormat](#) = std::true_type
- using [NotMKLSparseMatrixFormat](#) = std::false_type
- template<class T>
using [has_plus](#) = typename std::conditional<std::is_arithmetic<T>::value, std::true_type, [has_plus_impl<T>](#)>::type
- template<class T>
using [has_minus](#) = typename std::conditional<std::is_arithmetic<T>::value, std::true_type, [has_minus_impl<T>](#)>::type
- template<class T>
using [has_equal](#) = typename std::conditional<std::is_arithmetic<T>::value, std::true_type, std::is_copyable_& assignable<T>::type
- template<class T>
using [has_plus_eq](#) = typename std::conditional<std::is_arithmetic<T>::value, std::true_type, [has_plus_eq_impl<T>](#)>::type
- template<class T>
using [has_minus_eq](#) = typename std::conditional<std::is_arithmetic<T>::value, std::true_type, [has_minus_eq_impl<T>](#)>::type

- `template<class T >`
using `has_mul` = `typename std::conditional< std::is_arithmetic< T >::value, std::true_type, has_mul_impl< T > >::type`
- `template<class T >`
using `has_mul_eq` = `typename std::conditional< std::is_arithmetic< T >::value, std::true_type, has_mul_eq_impl< T > >::type`
- `typedef Givaro::Timer` `Timer`
- `typedef Givaro::BaseTimer` `BaseTimer`
- `typedef Givaro::UserTimer` `UserTimer`
- `typedef Givaro::SysTimer` `SysTimer`

Enumerations

- enum `FFLAS_ORDER` { `FflasRowMajor` = 101 , `FflasColMajor` = 102 }
Storage by row or col ?
- enum `FFLAS_TRANSPOSE` { `FflasNoTrans` = 111 , `FflasTrans` = 112 }
Is matrix transposed ?
- enum `FFLAS_UPLO` { `FflasUpper` = 121 , `FflasLower` = 122 , `FflasLeftTri` = 123 , `FflasRightTri` = 124 }
Is triangular matrix's shape upper ?
- enum `FFLAS_DIAG` { `FflasNonUnit` = 131 , `FflasUnit` = 132 }
Is the triangular matrix implicitly unit diagonal ?
- enum `FFLAS_SIDE` { `FflasLeft` = 141 , `FflasRight` = 142 }
On what side ?
- enum `FFLAS_BASE` { `FflasDouble` = 151 , `FflasFloat` = 152 , `FflasGeneric` = 153 }
FFLAS_BASE determines the type of the element representation for Matrix Mult kernel.
- enum `number_kind` { `zero` = 0 , `one` = 1 , `mone` = -1 , `other` = 2 }
- enum class `SparseMatrix_t` {
 `CSR` , `CSR_ZO` , `CSC` , `CSC_ZO` ,
 `COO` , `COO_ZO` , `ELL` , `ELL_ZO` ,
 `SELL` , `SELL_ZO` , `ELL_simd` , `ELL_simd_ZO` ,
 `CSR_HYB` , `HYB_ZO` }
- enum `FFLAS_FORMAT` {
 `FflasAuto` = 0 , `FflasDense` = 1 , `FflasSMS` = 2 , `FflasBinary` = 3 ,
 `FflasMath` = 4 , `FflasMaple` = 5 , `FflasSageMath` = 6 }

Functions

- `Givaro::Integer` `InfNorm` (`const size_t M`, `const size_t N`, `const Givaro::Integer *A`, `const size_t Ida`)
- `template<class T >`
`const T & min3` (`const T &m`, `const T &n`, `const T &k`)
- `template<class T >`
`const T & max3` (`const T &m`, `const T &n`, `const T &k`)
- `template<class T >`
`const T & min4` (`const T &m`, `const T &n`, `const T &k`, `const T &l`)
- `template<class T >`
`const T & max4` (`const T &m`, `const T &n`, `const T &k`, `const T &l`)
- `template<class Field >`
void `fadd` (`const Field &F`, `const size_t N`, `typename Field::ConstElement_ptr A`, `const size_t inca`, `typename Field::ConstElement_ptr B`, `const size_t incb`, `typename Field::Element_ptr C`, `const size_t incc`)
- `template<class Field >`
void `faddin` (`const Field &F`, `const size_t N`, `typename Field::ConstElement_ptr B`, `const size_t incb`, `typename Field::Element_ptr C`, `const size_t incc`)

- `template<class Field >`
`void fsub (const Field &F, const size_t N, typename Field::ConstElement_ptr A, const size_t inca, typename Field::ConstElement_ptr B, const size_t incb, typename Field::Element_ptr C, const size_t incc)`
- `template<class Field >`
`void fsubin (const Field &F, const size_t N, typename Field::ConstElement_ptr B, const size_t incb, typename Field::Element_ptr C, const size_t incc)`
- `template<class Field >`
`void fadd (const Field &F, const size_t N, typename Field::ConstElement_ptr A, const size_t inca, const typename Field::Element alpha, typename Field::ConstElement_ptr B, const size_t incb, typename Field::Element_ptr C, const size_t incc)`
- `template<class Field >`
`void pfadd (const Field &F, const size_t M, const size_t N, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, typename Field::Element_ptr C, const size_t ldc, const size_t numths)`
- `template<class Field >`
`void pfsub (const Field &F, const size_t M, const size_t N, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, typename Field::Element_ptr C, const size_t ldc, const size_t numths)`
- `template<class Field >`
`void pfaddin (const Field &F, const size_t M, const size_t N, typename Field::ConstElement_ptr B, const size_t ldb, typename Field::Element_ptr C, const size_t ldc, size_t numths)`
- `template<class Field >`
`void pfsubin (const Field &F, const size_t M, const size_t N, typename Field::ConstElement_ptr B, const size_t ldb, typename Field::Element_ptr C, const size_t ldc, size_t numths)`
- `template<class Field >`
`void fadd (const Field &F, const size_t M, const size_t N, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, typename Field::Element_ptr C, const size_t ldc)`
fadd : matrix addition.
- `template<class Field >`
`void fsub (const Field &F, const size_t M, const size_t N, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, typename Field::Element_ptr C, const size_t ldc)`
fsub : matrix subtraction.
- `template<class Field >`
`void faddin (const Field &F, const size_t M, const size_t N, typename Field::ConstElement_ptr B, const size_t ldb, typename Field::Element_ptr C, const size_t ldc)`
faddin
- `template<class Field >`
`void faddin (const Field &F, const FFLAS_UPLO uplo, const size_t N, typename Field::ConstElement_ptr B, const size_t ldb, typename Field::Element_ptr C, const size_t ldc)`
fadding for symmetric matrices
- `template<class Field >`
`void fsubin (const Field &F, const size_t M, const size_t N, typename Field::ConstElement_ptr B, const size_t ldb, typename Field::Element_ptr C, const size_t ldc)`
fsubin $C = C - B$
- `template<class Field >`
`void fadd (const Field &F, const size_t M, const size_t N, typename Field::ConstElement_ptr A, const size_t lda, const typename Field::Element alpha, typename Field::ConstElement_ptr B, const size_t ldb, typename Field::Element_ptr C, const size_t ldc)`
fadd : matrix addition with scaling.
- `template<class Field >`
`void fassign (const Field &F, const size_t N, typename Field::ConstElement_ptr Y, const size_t incY, typename Field::Element_ptr X, const size_t incX)`
fassign : $x \leftarrow y$.
- `template<> void fassign (const Givaro::Modular< float > &F, const size_t N, const float *Y, const size_t incY, float *X, const size_t incX)`

- `template<> void fassign (const Givaro::ModularBalanced< float > &F, const size_t N, const float *Y, const size_t incY, float *X, const size_t incX)`
- `template<> void fassign (const Givaro::ZRing< float > &F, const size_t N, const float *Y, const size_t incY, float *X, const size_t incX)`
- `template<> void fassign (const Givaro::Modular< double > &F, const size_t N, const double *Y, const size_t incY, double *X, const size_t incX)`
- `template<> void fassign (const Givaro::ModularBalanced< double > &F, const size_t N, const double *Y, const size_t incY, double *X, const size_t incX)`
- `template<> void fassign (const Givaro::ZRing< double > &F, const size_t N, const double *Y, const size_t incY, double *X, const size_t incX)`
- `template<class Field >`
`void fassign (const Field &F, const size_t m, const size_t n, typename Field::ConstElement_ptr B, const size_t ldb, typename Field::Element_ptr A, const size_t lda)`

$$fassign : A \leftarrow B.$$
- `template<class Field >`
`void faxpy (const Field &F, const size_t N, const typename Field::Element alpha, typename Field::ConstElement_ptr X, const size_t incX, typename Field::Element_ptr Y, const size_t incY)`

$$faxpy : y \leftarrow \alpha \cdot x + y.$$
- `template<> void faxpy (const Givaro::DoubleDomain &, const size_t N, const Givaro::DoubleDomain::Element a, Givaro::DoubleDomain::ConstElement_ptr x, const size_t incx, Givaro::DoubleDomain::Element_ptr y, const size_t incy)`
- `template<> void faxpy (const Givaro::FloatDomain &, const size_t N, const Givaro::FloatDomain::Element a, Givaro::FloatDomain::ConstElement_ptr x, const size_t incx, Givaro::FloatDomain::Element_ptr y, const size_t incy)`
- `template<class Field >`
`void faxpy (const Field &F, const size_t m, const size_t n, const typename Field::Element alpha, typename Field::ConstElement_ptr X, const size_t idx, typename Field::Element_ptr Y, const size_t idy)`

$$faxpy : y \leftarrow \alpha \cdot x + y.$$
- `template<class Field >`
`Field::Element fdot (const Field &F, const size_t N, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, ModeCategories::DefaultTag &MT)`
- `template<class Field >`
`Field::Element fdot (const Field &F, const size_t N, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, ModeCategories::DelayedTag &MT)`
- `template<> Givaro::DoubleDomain::Element fdot (const Givaro::DoubleDomain &, const size_t N, Givaro::DoubleDomain::ConstElement_ptr x, const size_t incx, Givaro::DoubleDomain::ConstElement_ptr y, const size_t incy, ModeCategories::DefaultTag &MT)`
- `template<> Givaro::FloatDomain::Element fdot (const Givaro::FloatDomain &, const size_t N, Givaro::FloatDomain::ConstElement_ptr x, const size_t incx, Givaro::FloatDomain::ConstElement_ptr y, const size_t incy, ModeCategories::DefaultTag &MT)`
- `template<class Field, class T >`
`Field::Element fdot (const Field &F, const size_t N, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, ModeCategories::ConvertTo< T > &MT)`
- `template<class Field >`
`Field::Element fdot (const Field &F, const size_t N, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, ModeCategories::DefaultBoundedTag &dbt)`
- `template<class Field >`
`Field::Element fdot (const Field &F, const size_t N, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, const ParSeqHelper::Sequential seq)`
- `template<class Field >`
`Field::Element fdot (const Field &F, const size_t N, typename Field::ConstElement_ptr X, const size_t incX, typename Field::ConstElement_ptr Y, const size_t incY)`

$$fdot: \text{dot product } x^T y.$$
- `template<class Field >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, typename`

- `Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, ModeCategories::ConvertTo< ElementCategories::MachineFloatTag >, ParSeqHelper::Sequential > &H)`
- `template<typename Field >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const ParSeqHelper::Sequential seq)`
 - `template<typename Field, class Cut, class Param >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const ParSeqHelper::Parallel< Cut, Param > par)`
 - `template<typename Field >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc)`
fgemm: Field GENERAL Matrix Multiply.
 - `template<typename Field, class ModeT, class ParSeq >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Auto, ModeT, ParSeq > &H)`
 - `template<class Field >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, ModeCategories::DelayedTag, ParSeqHelper::Sequential > &H)`
 - `template<class Field >`
`Field::Element_ptr fsquare (const Field &F, const FFLAS_TRANSPOSE ta, const size_t n, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc)`
fsquare: Squares a matrix.
 - `template<> double * fsquare (const Givaro::ModularBalanced< double > &F, const FFLAS_TRANSPOSE ta, const size_t n, const double alpha, const double *A, const size_t lda, const double beta, double *C, const size_t ldc)`
 - `template<> float * fsquare (const Givaro::ModularBalanced< float > &F, const FFLAS_TRANSPOSE ta, const size_t n, const float alpha, const float *A, const size_t lda, const float beta, float *C, const size_t ldc)`
 - `template<> double * fsquare (const Givaro::Modular< double > &F, const FFLAS_TRANSPOSE ta, const size_t n, const double alpha, const double *A, const size_t lda, const double beta, double *C, const size_t ldc)`
 - `template<> float * fsquare (const Givaro::Modular< float > &F, const FFLAS_TRANSPOSE ta, const size_t n, const float alpha, const float *A, const size_t lda, const float beta, float *C, const size_t ldc)`
 - `template<typename RNS, typename ParSeqTrait >`
`FFPACK::RNSInteger< RNS >::Element_ptr fgemm (const FFPACK::RNSInteger< RNS > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename FFPACK::RNSInteger< RNS >::Element alpha, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Ad, const size_t lda, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Bd, const size_t ldb, const typename FFPACK::RNSInteger< RNS >::Element beta, typename FFPACK::RNSInteger< RNS >::Element_ptr Cd, const size_t ldc, MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag, ParSeqHelper::Compose< ParSeqHelper::Sequential, ParSeqTrait > > &H)`

- `template<typename RNS >`
`FFPACK::RNSInteger< RNS >::Element_ptr fgemm (const FFPACK::RNSInteger< RNS > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename FFPACK::RNSInteger< RNS >::Element alpha, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Ad, const size_t lda, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Bd, const size_t ldb, const typename FFPACK::RNSInteger< RNS >::Element beta, typename FFPACK::RNSInteger< RNS >::Element_ptr Cd, const size_t ldc, MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag, ParSeqHelper::Sequential > &H)`
- `template<typename RNS, typename ParSeqTrait >`
`FFPACK::RNSInteger< RNS >::Element_ptr fgemm (const FFPACK::RNSInteger< RNS > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename FFPACK::RNSInteger< RNS >::Element alpha, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Ad, const size_t lda, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Bd, const size_t ldb, const typename FFPACK::RNSInteger< RNS >::Element beta, typename FFPACK::RNSInteger< RNS >::Element_ptr Cd, const size_t ldc, MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag, ParSeqHelper::Compose< ParSeqHelper::Parallel< CuttingStrategy::RNSModulus, StrategyParameter::Threads >, ParSeqTrait > > &H)`
- `template<typename RNS, typename Cut, typename Param >`
`FFPACK::RNSInteger< RNS >::Element_ptr fgemm (const FFPACK::RNSInteger< RNS > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename FFPACK::RNSInteger< RNS >::Element alpha, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Ad, const size_t lda, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Bd, const size_t ldb, const typename FFPACK::RNSInteger< RNS >::Element beta, typename FFPACK::RNSInteger< RNS >::Element_ptr Cd, const size_t ldc, MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag, ParSeqHelper::Parallel< Cut, Param > > &H)`
- `template<class ParSeq >`
`Givaro::Integer * fgemm (const Givaro::ZRing< Givaro::Integer > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const Givaro::Integer alpha, const Givaro::Integer *A, const size_t lda, const Givaro::Integer *B, const size_t ldb, Givaro::Integer beta, Givaro::Integer *C, const size_t ldc, MMHelper< Givaro::ZRing< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeq > &H)`
- `template<typename RNS, class ModeT >`
`RNS::Element_ptr fgemm (const FFPACK::RNSInteger< RNS > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename RNS::Element alpha, typename RNS::ConstElement_ptr Ad, const size_t lda, typename RNS::ConstElement_ptr Bd, const size_t ldb, const typename RNS::Element beta, typename RNS::Element_ptr Cd, const size_t ldc, MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Winograd, ModeT, ParSeqHelper::Sequential > &H)`
- `template<typename RNS >`
`RNS::Element_ptr fgemm (const FFPACK::RNSIntegerMod< RNS > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename RNS::Element alpha, typename RNS::ConstElement_ptr Ad, const size_t lda, typename RNS::ConstElement_ptr Bd, const size_t ldb, const typename RNS::Element beta, typename RNS::Element_ptr Cd, const size_t ldc, MMHelper< FFPACK::RNSIntegerMod< RNS >, MMHelperAlgo::Winograd > &H)`
- `Givaro::Integer * fgemm (const Givaro::Modular< Givaro::Integer > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const Givaro::Integer alpha, const Givaro::Integer *A, const size_t lda, const Givaro::Integer *B, const size_t ldb, const Givaro::Integer beta, Givaro::Integer *C, const size_t ldc, MMHelper< Givaro::Modular< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo< ElementCategories::RNSElementTag > > &H)`
- `template<class ParSeq >`
`Givaro::Integer * fgemm (const Givaro::Modular< Givaro::Integer > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const Givaro::Integer alpha, const Givaro::Integer *A, const size_t lda, const Givaro::Integer *B, const size_t ldb, const Givaro::Integer beta, Givaro::Integer *C, const size_t ldc, MMHelper< Givaro::Modular< Givaro::Integer >, MMHelperAlgo::Auto, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeq > &H)`
- `template<size_t K1, size_t K2, class ParSeq >`
`Reclnt::ruint< K1 > * fgemm (const Givaro::Modular< Reclnt::ruint< K1 >, Reclnt::ruint< K2 > > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n,`

- const size_t k, const [RecInt::ruint](#)< K1 > alpha, const [RecInt::ruint](#)< K1 > *A, const size_t lda, const [RecInt::ruint](#)< K1 > *B, const size_t ldb, [RecInt::ruint](#)< K1 > beta, [RecInt::ruint](#)< K1 > *C, const size_t ldc, [MMHelper](#)< [Givaro::Modular](#)< [RecInt::ruint](#)< K1 >, [RecInt::ruint](#)< K2 > >, [MMHelperAlgo::Classic](#), [ModeCategories::ConvertTo](#)< [ElementCategories::RNSElementTag](#) >, [ParSeq](#) > &H)
- `template<class Field , class ModeT >`
[Field::Element_ptr](#) [fgemm](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), ModeT > &H)
 - `template<class Field , class ModeT , class Cut , class Param >`
[Field::Element_ptr](#) [fgemm](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::WinogradPar](#), ModeT, [ParSeqHelper::Parallel](#)< Cut, Param > > &H)
 - `template<class Field >`
[Field::Element_ptr](#) [fgemv](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) X, const size_t incX, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) Y, const size_t incY, [MMHelper](#)< [Field](#), [MMHelperAlgo::Classic](#), [ModeCategories::ConvertTo](#)< [ElementCategories::MachineFloatTag](#) > > &H)
 - `template<class Field >`
[Field::Element_ptr](#) [fgemv](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) X, const size_t incX, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) Y, const size_t incY, [MMHelper](#)< [Field](#), [MMHelperAlgo::Classic](#), [ModeCategories::DelayedTag](#) > &H)
 - `template<class Field >`
[Field::Element_ptr](#) [fgemv](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) X, const size_t incX, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) Y, const size_t incY, [MMHelper](#)< [Field](#), [MMHelperAlgo::Classic](#), [ModeCategories::DefaultTag](#) > &H)
 - `template<class Field >`
[Field::Element_ptr](#) [fgemv](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) X, const size_t incX, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) Y, const size_t incY, [MMHelper](#)< [Field](#), [MMHelperAlgo::Classic](#), [ModeCategories::LazyTag](#) > &H)
 - `template<class Field >`
[Field::Element_ptr](#) [fgemv](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) TransA, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) X, const size_t incX, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) Y, const size_t incY)
finite prime Field GEneral Matrix Vector multiplication.
 - `Givaro::ZRing< int64_t >::Element_ptr` [fgemv](#) (const [Givaro::ZRing](#)< int64_t > &F, const [FFLAS_TRANSPOSE](#) ta, const size_t M, const size_t N, const int64_t alpha, const int64_t *A, const size_t lda, const int64_t *X, const size_t incX, const int64_t beta, const int64_t *Y, const size_t incY, [MMHelper](#)< [Givaro::ZRing](#)< int64_t >, [MMHelperAlgo::Classic](#), [ModeCategories::DefaultTag](#) > &H)
 - `Givaro::DoubleDomain::Element_ptr` [fgemv](#) (const [Givaro::DoubleDomain](#) &F, const [FFLAS_TRANSPOSE](#) ta, const size_t M, const size_t N, const [Givaro::DoubleDomain::Element](#) alpha, const [Givaro::DoubleDomain::ConstElement_ptr](#) A, const size_t lda, const [Givaro::DoubleDomain::ConstElement_ptr](#) X, const size_t incX, const [Givaro::DoubleDomain::Element](#) beta, [Givaro::DoubleDomain::Element_ptr](#) Y, const size_t incY, [MMHelper](#)< [Givaro::DoubleDomain](#), [MMHelperAlgo::Classic](#), [ModeCategories::DefaultTag](#) > &H)
 - `template<class Field >`
[Field::Element_ptr](#) [fgemv](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) X, const size_t incX, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) Y, const size_t incY, [MMHelper](#)< [Field](#), [MMHelperAlgo::Classic](#), [ModeCategories::DefaultTag](#) > &H)

- `_t N, const typename Field::Element alpha, const typename Field::ConstElement_ptr A, const size_t`
`_t lda, const typename Field::ConstElement_ptr X, const size_t incX, const typename Field::Element`
`beta, typename Field::Element_ptr Y, const size_t incY, MMHelper< Field, MMHelperAlgo::Classic,`
`ModeCategories::DefaultBoundedTag > &H)`
- `Givaro::FloatDomain::Element_ptr fgemv (const Givaro::FloatDomain &F, const FFLAS_TRANSPOSE ta,`
`const size_t M, const size_t N, const Givaro::FloatDomain::Element alpha, const Givaro::FloatDomain::`
`ConstElement_ptr A, const size_t lda, const Givaro::FloatDomain::ConstElement_ptr X, const size_t`
`incX, const Givaro::FloatDomain::Element beta, Givaro::FloatDomain::Element_ptr Y, const size_t incY,`
`MMHelper< Givaro::FloatDomain, MMHelperAlgo::Classic, ModeCategories::DefaultTag > &H)`
- `template<class Field, class Cut, class Param >`
`Field::Element_ptr fgemv (const Field &F, const FFLAS_TRANSPOSE ta, const size_t m, const size_t n,`
`const typename Field::Element alpha, const typename Field::ConstElement_ptr A, const size_t lda, const`
`typename Field::ConstElement_ptr X, const size_t incX, const typename Field::Element beta, typename`
`Field::Element_ptr Y, const size_t incY, ParSeqHelper::Parallel< Cut, Param > &parH)`
- `template<class Field >`
`Field::Element_ptr fgemv (const Field &F, const FFLAS_TRANSPOSE ta, const size_t m, const size_t n,`
`const typename Field::Element alpha, const typename Field::ConstElement_ptr A, const size_t lda, const`
`typename Field::ConstElement_ptr X, const size_t incX, const typename Field::Element beta, typename`
`Field::Element_ptr Y, const size_t incY, ParSeqHelper::Sequential &seqH)`
- `FFPACK::rns_double::Element_ptr fgemv (const FFPACK::RNSInteger< FFPACK::rns_double > &F, const`
`FFLAS_TRANSPOSE ta, const size_t M, const size_t N, const FFPACK::rns_double::Element alpha,`
`FFPACK::rns_double::ConstElement_ptr A, const size_t lda, FFPACK::rns_double::ConstElement_ptr`
`X, const size_t incX, const FFPACK::rns_double::Element beta, FFPACK::rns_double::Element_ptr Y,`
`const size_t incY, MMHelper< FFPACK::RNSInteger< FFPACK::rns_double >, MMHelperAlgo::Classic,`
`ModeCategories::DefaultTag > &H)`
- `FFPACK::rns_double::Element_ptr fgemv (const FFPACK::RNSIntegerMod< FFPACK::rns_double > &F,`
`const FFLAS_TRANSPOSE ta, const size_t M, const size_t N, const FFPACK::rns_double::Element alpha,`
`FFPACK::rns_double::ConstElement_ptr A, const size_t lda, FFPACK::rns_double::ConstElement_ptr X,`
`const size_t incX, const FFPACK::rns_double::Element beta, FFPACK::rns_double::Element_ptr Y, const`
`size_t incY, MMHelper< FFPACK::RNSIntegerMod< FFPACK::rns_double >, MMHelperAlgo::Classic,`
`ModeCategories::DefaultTag > &H)`
- `Givaro::Integer * fgemv (const Givaro::ZRing< Givaro::Integer > &F, const FFLAS_TRANSPOSE`
`ta, const size_t m, const size_t n, const Givaro::Integer alpha, Givaro::Integer *A, const size_t`
`lda, Givaro::Integer *X, const size_t ldx, Givaro::Integer beta, Givaro::Integer *Y, const size_t ldy,`
`MMHelper< Givaro::ZRing< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo<`
`ElementCategories::RNSElementTag > > &H)`
- `Givaro::Integer * fgemv (const Givaro::Modular< Givaro::Integer > &F, const FFLAS_TRANSPOSE`
`ta, const size_t m, const size_t n, const Givaro::Integer alpha, Givaro::Integer *A, const size_t`
`lda, Givaro::Integer *X, const size_t ldx, Givaro::Integer beta, Givaro::Integer *Y, const size_t ldy,`
`MMHelper< Givaro::Modular< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo<`
`ElementCategories::RNSElementTag > > &H)`
- `template<size_t K1, size_t K2, class ParSeq >`
`RecInt::ruint< K1 > * fgemv (const Givaro::Modular< RecInt::ruint< K1 >, RecInt::ruint< K2 > >`
`&F, const FFLAS_TRANSPOSE ta, const size_t m, const size_t n, const RecInt::ruint< K1 > al-`
`pha, const RecInt::ruint< K1 > *A, const size_t lda, const RecInt::ruint< K1 > *X, const size_t incx,`
`RecInt::ruint< K1 > beta, RecInt::ruint< K1 > *Y, const size_t incy, MMHelper< Givaro::Modular<`
`RecInt::ruint< K1 >, RecInt::ruint< K2 > >, MMHelperAlgo::Classic, ModeCategories::ConvertTo<`
`ElementCategories::RNSElementTag >, ParSeq > &H)`
- `template<class Field >`
`void fger (const Field &F, const size_t M, const size_t N, const typename Field::Element alpha, typename`
`Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, type-`
`name Field::Element_ptr A, const size_t lda)`

fger: rank one update of a general matrix
- `template<class Field >`
`void fger (const Field &F, const size_t M, const size_t N, const typename Field::Element alpha, type-`
`name Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t`
`incy, typename Field::Element_ptr A, const size_t lda, MMHelper< Field, MMHelperAlgo::Classic,`
`ModeCategories::ConvertTo< ElementCategories::MachineFloatTag > > &H)`

- `template<class Field, class AnyTag >`
`void fger (const Field &F, const size_t M, const size_t N, const typename Field::Element alpha, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, typename Field::Element_ptr A, const size_t lda, MMHelper< Field, MMHelperAlgo::Classic, AnyTag > &H)`
- `void fger (const Givaro::DoubleDomain &F, const size_t M, const size_t N, const Givaro::DoubleDomain::Element alpha, const Givaro::DoubleDomain::ConstElement_ptr x, const size_t incx, const Givaro::DoubleDomain::ConstElement_ptr y, const size_t incy, Givaro::DoubleDomain::Element_ptr A, const size_t lda, MMHelper< Givaro::DoubleDomain, MMHelperAlgo::Classic, ModeCategories::DefaultTag > &H)`
- `template<class Field >`
`void fger (const Field &F, const size_t M, const size_t N, const typename Field::Element alpha, const typename Field::ConstElement_ptr x, const size_t incx, const typename Field::ConstElement_ptr y, const size_t incy, typename Field::Element_ptr A, const size_t lda, MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::DefaultBoundedTag > &H)`
- `void fger (const Givaro::FloatDomain &F, const size_t M, const size_t N, const Givaro::FloatDomain::Element alpha, const Givaro::FloatDomain::ConstElement_ptr x, const size_t incx, const Givaro::FloatDomain::ConstElement_ptr y, const size_t incy, Givaro::FloatDomain::Element_ptr A, const size_t lda, MMHelper< Givaro::FloatDomain, MMHelperAlgo::Classic, ModeCategories::DefaultTag > &H)`
- `template<class Field >`
`void fger (const Field &F, const size_t M, const size_t N, const typename Field::Element alpha, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, typename Field::Element_ptr A, const size_t lda, MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::LazyTag > &H)`
- `template<class Field >`
`void fger (const Field &F, const size_t M, const size_t N, const typename Field::Element alpha, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, typename Field::Element_ptr A, const size_t lda, MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::DelayedTag > &H)`
- `void fger (const Givaro::Modular< Givaro::Integer > &F, const size_t M, const size_t N, const typename Givaro::Integer alpha, typename Givaro::Integer *x, const size_t incx, typename Givaro::Integer *y, const size_t incy, typename Givaro::Integer *A, const size_t lda, MMHelper< Givaro::Modular< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo< ElementCategories::RNSElementTag > > &H)`
- `template<typename RNS >`
`void fger (const FFPACK::RNSInteger< RNS > &F, const size_t M, const size_t N, const typename FFPACK::RNSInteger< RNS >::Element alpha, typename FFPACK::RNSInteger< RNS >::Element_ptr x, const size_t incx, typename FFPACK::RNSInteger< RNS >::Element_ptr y, const size_t incy, typename FFPACK::RNSInteger< RNS >::Element_ptr A, const size_t lda, MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag > &H)`
- `template<typename RNS >`
`void fger (const FFPACK::RNSIntegerMod< RNS > &F, const size_t M, const size_t N, const typename FFPACK::RNSIntegerMod< RNS >::Element alpha, typename FFPACK::RNSIntegerMod< RNS >::Element_ptr x, const size_t incx, typename FFPACK::RNSIntegerMod< RNS >::Element_ptr y, const size_t incy, typename FFPACK::RNSIntegerMod< RNS >::Element_ptr A, const size_t lda, MMHelper< FFPACK::RNSIntegerMod< RNS >, MMHelperAlgo::Classic > &H)`
- `template<class Field >`
`void freduce (const Field &F, const size_t n, typename Field::ConstElement_ptr Y, const size_t incY, typename Field::Element_ptr X, const size_t incX)`

$$\text{freduce } x \leftarrow y \bmod F.$$
- `template<class Field >`
`void freduce (const Field &F, const size_t n, typename Field::Element_ptr X, const size_t incX)`

$$\text{freduce } x \leftarrow x \bmod F.$$
- `template<class Field >`
`void freduce_constoverride (const Field &F, const size_t m, typename Field::ConstElement_ptr A, const size_t incX)`
- `template<class Field, class ConstOtherElement_ptr >`
`void finit (const Field &F, const size_t n, ConstOtherElement_ptr Y, const size_t incY, typename Field::Element_ptr X, const size_t incX)`

- template<class [Field](#) >
void [finit](#) (const [Field](#) &F, const size_t n, typename [Field::Element_ptr](#) X, const size_t incX)
finit Initializes X in $F^{\$}$.
- template<class [Field](#) >
void [freduce](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
freduce $A \leftarrow A \bmod F$.
- template<class [Field](#) >
void [freduce](#) (const [Field](#) &F, const [FFLAS_UPLO](#) uplo, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda)
freduce for square symmetric matrices
- template<class [Field](#) >
void [pfreduce](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda, const size_t numths)
- template<class [Field](#) >
void [freduce](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) A, const size_t lda)
freduce $A \leftarrow B \bmod F$.
- template<class [Field](#) >
void [freduce_constoverride](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::ConstElement_ptr](#) A, const size_t lda)
- template<class [Field](#) , class OtherElement_ptr >
void [finit](#) (const [Field](#) &F, const size_t m, const size_t n, const OtherElement_ptr B, const size_t ldb, typename [Field::Element_ptr](#) A, const size_t lda)
finit $A \leftarrow B \bmod F$.
- template<class [Field](#) >
void [finit](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
- template<> void [freduce](#) (const [FFPACK::RNSIntegerMod](#)< [FFPACK::rns_double](#) > &F, const size_t n, [FFPACK::RNSIntegerMod](#)< [FFPACK::rns_double](#) >::Element_ptr A, size_t inc)
- template<> void [freduce](#) (const [FFPACK::RNSIntegerMod](#)< [FFPACK::rns_double](#) > &F, const size_t m, const size_t n, [FFPACK::rns_double::Element_ptr](#) A, size_t lda)
- template<class [Field](#) >
bool [freivalds](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::ConstElement_ptr](#) C, const size_t ldc)
*freivalds: **Freivalds G**eneral **M**atrix **M**ultiply **R**andom **C**heck.*
- template<class [Field](#) >
void [fscal](#) (const [Field](#) &F, const size_t n, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) X, const size_t incX)
fscal $x \leftarrow \alpha \cdot x$.
- template<class [Field](#) >
void [fscal](#) (const [Field](#) &F, const size_t n, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::Element_ptr](#) Y, const size_t incY)
fscal $y \leftarrow \alpha \cdot x$.
- template<> void [fscal](#) (const Givaro::DoubleDomain &, const size_t N, const Givaro::DoubleDomain::Element a, Givaro::DoubleDomain::ConstElement_ptr x, const size_t incx, Givaro::DoubleDomain::Element_ptr y, const size_t incy)
- template<> void [fscal](#) (const Givaro::FloatDomain &, const size_t N, const Givaro::FloatDomain::Element a, Givaro::FloatDomain::ConstElement_ptr x, const size_t incx, Givaro::FloatDomain::Element_ptr y, const size_t incy)
- template<> void [fscal](#) (const Givaro::DoubleDomain &, const size_t N, const Givaro::DoubleDomain::Element a, Givaro::DoubleDomain::Element_ptr y, const size_t incy)
- template<> void [fscal](#) (const Givaro::FloatDomain &, const size_t N, const Givaro::FloatDomain::Element a, Givaro::FloatDomain::Element_ptr y, const size_t incy)

- `template<class Field >`
`void fscaln (const Field &F, const size_t m, const size_t n, const typename Field::Element alpha, typename Field::Element_ptr A, const size_t lda)`

$$fscaln\ A \leftarrow a \cdot A.$$
- `template<class Field >`
`void fscal (const Field &F, const size_t m, const size_t n, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr B, const size_t ldb)`

$$fscal\ B \leftarrow a \cdot A.$$
- `template<> void fscaln (const FFPACK::RNSInteger< FFPACK::rns_double > &F, const size_t n, const FFPACK::rns_double::Element alpha, FFPACK::rns_double::Element_ptr A, const size_t inc)`
- `template<> void fscal (const FFPACK::RNSInteger< FFPACK::rns_double > &F, const size_t n, const FFPACK::rns_double::Element alpha, FFPACK::rns_double::ConstElement_ptr A, const size_t Ainc, FFPACK::rns_double::Element_ptr B, const size_t Binc)`
- `template<> void fscaln (const FFPACK::RNSInteger< FFPACK::rns_double > &F, const size_t m, const size_t n, const FFPACK::rns_double::Element alpha, FFPACK::rns_double::Element_ptr A, const size_t lda)`
- `template<> void fscal (const FFPACK::RNSInteger< FFPACK::rns_double > &F, const size_t m, const size_t n, const FFPACK::rns_double::Element alpha, FFPACK::rns_double::ConstElement_ptr A, const size_t Ainc, FFPACK::rns_double::Element_ptr B, const size_t Binc)`
- `template<> void fscaln (const FFPACK::RNSIntegerMod< FFPACK::rns_double > &F, const size_t n, const typename FFPACK::RNSIntegerMod< FFPACK::rns_double >::Element alpha, typename FFPACK::RNSIntegerMod< FFPACK::rns_double >::Element_ptr A, const size_t inc)`
- `template<> void fscal (const FFPACK::RNSIntegerMod< FFPACK::rns_double > &F, const size_t n, const FFPACK::rns_double::Element alpha, FFPACK::rns_double::ConstElement_ptr A, const size_t Ainc, FFPACK::rns_double::Element_ptr B, const size_t Binc)`
- `template<> void fscaln (const FFPACK::RNSIntegerMod< FFPACK::rns_double > &F, const size_t m, const size_t n, const FFPACK::rns_double::Element alpha, FFPACK::rns_double::Element_ptr A, const size_t lda)`
- `template<> void fscal (const FFPACK::RNSIntegerMod< FFPACK::rns_double > &F, const size_t m, const size_t n, const FFPACK::rns_double::Element alpha, FFPACK::rns_double::ConstElement_ptr A, const size_t Ainc, FFPACK::rns_double::Element_ptr B, const size_t Binc)`
- `template<class Field >`
`Field::Element_ptr fsyr2k (const Field &F, const FFLAS_UPLO UpLo, const FFLAS_TRANSPOSE trans, const size_t n, const size_t k, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc)`
fsyr2k: Symmetric Rank 2K update
- `template<class Field >`
`Field::Element_ptr fsyrk (const Field &F, const FFLAS_UPLO UpLo, const FFLAS_TRANSPOSE trans, const size_t n, const size_t k, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc)`
fsyrk: Symmetric Rank K update
- `template<class Field >`
`Field::Element_ptr fsyrk (const Field &F, const FFLAS_UPLO UpLo, const FFLAS_TRANSPOSE trans, const size_t N, const size_t K, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const ParSeqHelper::Sequential seq)`
- `template<class Field >`
`Field::Element_ptr fsyrk (const Field &F, const FFLAS_UPLO UpLo, const FFLAS_TRANSPOSE trans, const size_t N, const size_t K, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::DefaultTag > &H)`
- `template<class Field >`
`Field::Element_ptr fsyrk (const Field &F, const FFLAS_UPLO UpLo, const FFLAS_TRANSPOSE trans, const size_t N, const size_t K, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::ConvertTo< ElementCategories::MachineFloatTag >, ParSeqHelper::Sequential > &H)`

- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `ModeCategories::DelayedTag` > &H)
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `ModeCategories::LazyTag` > &H)
- `template<class Field , typename Mode >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Field`, `MMHelperAlgo::DivideAndConquer`, `Mode` > &H)
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `ModeCategories::DefaultBoundedTag` > &H)
- `Givaro::FloatDomain::Element_ptr fsyrk` (const `Givaro::FloatDomain` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const `Givaro::FloatDomain::Element` alpha, `Givaro::FloatDomain::ConstElement_ptr` A, const `size_t` lda, const `Givaro::FloatDomain::Element` beta, `Givaro::FloatDomain::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Givaro::FloatDomain`, `MMHelperAlgo::Classic`, `ModeCategories::DefaultTag` > &H)
- `Givaro::DoubleDomain::Element_ptr fsyrk` (const `Givaro::DoubleDomain` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const `Givaro::DoubleDomain::Element` alpha, `Givaro::DoubleDomain::ConstElement_ptr` A, const `size_t` lda, const `Givaro::DoubleDomain::Element` beta, `Givaro::DoubleDomain::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Givaro::DoubleDomain`, `MMHelperAlgo::Classic`, `ModeCategories::DefaultTag` > &H)
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, typename `Field::Element_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` D, const `size_t` incD, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `size_t` threshold=`__FFLASFFPACK_FSYRK_THRESHOLD`)
fsyrk: Symmetric Rank K update with diagonal scaling
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::Element_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` D, const `size_t` incD, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `ParSeqHelper::Sequential` seq, const `size_t` threshold)
- `template<class Field , class Cut , class Param >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::Element_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` D, const `size_t` incD, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `ParSeqHelper::Parallel`< `Cut`, `Param` > par, const `size_t` threshold)
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, typename `Field::Element_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` D, const `size_t` incD, const `std::vector< bool >` &twoBlock, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `size_t` threshold=`__FFLASFFPACK_FSYRK_THRESHOLD`)
fsyrk: Symmetric Rank K update with diagonal scaling
- `template<class Field , class FieldTrait >`
void `computeS1S2` (const `Field` &F, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const

- typename [Field::Element](#) x, const typename [Field::Element](#) y, typename [Field::Element_ptr](#) A, const size_t Ida, typename [Field::Element_ptr](#) S, const size_t Ids, typename [Field::Element_ptr](#) T, const size_t Idt, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldTrait](#) > &WH)
- template<class [Field](#) >
[Field::Element_ptr](#) fsyrk (const [Field](#) &F, const [FFLAS_UPLO](#) UpLo, const [FFLAS_TRANSPOSE](#) trans, const size_t N, const size_t K, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t Ida, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t Idc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [ModeCategories::DelayedTag](#), [ParSeqHelper::Sequential](#) > &H)
 - template<class [Field](#) , class Mode >
[Field::Element_ptr](#) fsyrk (const [Field](#) &F, const [FFLAS_UPLO](#) UpLo, const [FFLAS_TRANSPOSE](#) trans, const size_t N, const size_t K, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t Ida, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t Idc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), Mode > &H)
 - template<class [Field](#) , class [FieldTrait](#) >
[Field::Element_ptr](#) fsyrk_strassen (const [Field](#) &F, const [FFLAS_UPLO](#) uplo, const [FFLAS_TRANSPOSE](#) trans, const size_t N, const size_t K, const typename [Field::Element](#) y1, const typename [Field::Element](#) y2, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t Ida, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t Idc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldTrait](#) > &WH)
 - template<class [Field](#) >
void ftrmm (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t Ida, typename [Field::Element_ptr](#) B, const size_t ldb)
*ftrmm: **TRI**angular **M**atrix **M**ultiply.*
 - template<class [Field](#) >
void ftrmm (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t Ida, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc)
*ftrmm: **TRI**angular **M**atrix **M**ultiply with 3 operands Computes $C \leftarrow \alpha \text{op}(A)B + \text{beta}C$ or $C \leftarrow \alpha \text{Bop}(A) + \text{beta}C$.*
 - template<class [Field](#) >
void ftrsm (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t Ida, typename [Field::Element_ptr](#) B, const size_t ldb)
 - template<class [Field](#) >
void ftrsm (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t Ida, typename [Field::Element_ptr](#) B, const size_t ldb, const [ParSeqHelper::Sequential](#) &PSH)
 - template<class [Field](#) , class Cut , class Param >
void ftrsm (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t Ida, typename [Field::Element_ptr](#) B, const size_t ldb, const [ParSeqHelper::Parallel](#)< Cut, Param > &PSH)
 - template<class [Field](#) , class [ParSeqTrait](#) = [ParSeqHelper::Sequential](#)>
void ftrsm (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t Ida, typename [Field::Element_ptr](#) B, const size_t ldb, [TRSMHelper](#)< [StructureHelper::Recursive](#), [ParSeqTrait](#) > &H)
 - void ftrsm (const [Givaro::Modular](#)< [Givaro::Integer](#) > &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const [Givaro::Integer](#) alpha, const [Givaro::Integer](#) *A, const size_t Ida, [Givaro::Integer](#) *B, const size_t ldb)
 - void cblas_imptrsm (const enum [FFLAS_ORDER](#) Order, const enum [FFLAS_SIDE](#) Side, const enum [FFLAS_UPLO](#) Uplo, const enum [FFLAS_TRANSPOSE](#) TransA, const enum [FFLAS_DIAG](#) Diag, const int M, const int N, const [FFPACK::rns_double_elt](#) alpha, [FFPACK::rns_double_elt_cstptr](#) A, const int Ida, [FFPACK::rns_double_elt_ptr](#) B, const int ldb)

- template<class [Field](#) >
void [ftrsv](#) (const [Field](#) &F, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) X, int incX)
ftrsv: TRIangular System solve with Vector Computes $X \leftarrow \text{op}(A^{-1})X$
- void [igemm](#) (const enum [FFLAS_ORDER](#) Order, const enum [FFLAS_TRANSPOSE](#) TransA, const enum [FFLAS_TRANSPOSE](#) TransB, const size_t M, const size_t N, const size_t K, const int64_t alpha, const int64_t *A, const size_t lda, const int64_t *B, const size_t ldb, const int64_t beta, int64_t *C, const size_t ldc)
- template<class [Field](#) , class OtherElement_ptr >
void [finit](#) (const [Field](#) &F, const size_t n, const OtherElement_ptr Y, const size_t incY, typename [Field::Element_ptr](#) X, const size_t incX)
finit $x \leftarrow y \bmod F$.
- template<class [Field](#) , class OtherElement_ptr >
void [fconvert](#) (const [Field](#) &F, const size_t n, OtherElement_ptr X, const size_t incX, typename [Field::ConstElement_ptr](#) Y, const size_t incY)
fconvert $x \leftarrow y \bmod F$.
- template<class [Field](#) >
void [fnegin](#) (const [Field](#) &F, const size_t n, typename [Field::Element_ptr](#) X, const size_t incX)
fnegin $x \leftarrow -x$.
- template<class [Field](#) >
void [fneg](#) (const [Field](#) &F, const size_t n, typename [Field::ConstElement_ptr](#) Y, const size_t incY, typename [Field::Element_ptr](#) X, const size_t incX)
fneg $x \leftarrow -y$.
- template<class [Field](#) >
void [fzero](#) (const [Field](#) &F, const size_t n, typename [Field::Element_ptr](#) X, const size_t incX)
fzero : $A \leftarrow 0$.
- template<class [Field](#) , class Randlter >
void [frand](#) (const [Field](#) &F, Randlter &G, const size_t n, typename [Field::Element_ptr](#) X, const size_t incX)
frand : $A \leftarrow \text{random}$.
- template<class [Field](#) >
bool [fiszero](#) (const [Field](#) &F, const size_t n, typename [Field::ConstElement_ptr](#) X, const size_t incX)
fiszero : test $X = 0$.
- template<class [Field](#) >
bool [fequal](#) (const [Field](#) &F, const size_t n, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::ConstElement_ptr](#) Y, const size_t incY)
fequal : test $X = Y$.
- template<class [Field](#) >
void [faxpby](#) (const [Field](#) &F, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) X, const size_t incX, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) Y, const size_t incY)
faxpby : $y \leftarrow \alpha \cdot x + \beta \cdot y$.
- template<typename [Field](#) , class Cut , class Param >
[Field::Element](#) [fdot](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::ConstElement_ptr](#) Y, const size_t incY, const [ParSeqHelper::Parallel](#)< Cut, Param > par)
- template<class [Field](#) >
void [fswap](#) (const [Field](#) &F, const size_t N, typename [Field::Element_ptr](#) X, const size_t incX, typename [Field::Element_ptr](#) Y, const size_t incY)
fswap: $X \leftrightarrow Y$.
- template<class [Field](#) >
void [fzero](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
fzero : $A \leftarrow 0$.
- template<class [Field](#) >
void [fzero](#) (const [Field](#) &F, const [FFLAS_UPLO](#) shape, const [FFLAS_DIAG](#) diag, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)

- $fzero : A \leftarrow 0$ for a triangular matrix.
- template<class [Field](#) , class Randlter >
 void [frand](#) (const [Field](#) &F, Randlter &G, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
 $frand : A \leftarrow random.$
- template<class [Field](#) >
 bool [fequal](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb)
 $fequal : test A = B.$
- template<class [Field](#) >
 bool [fiszero](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::ConstElement_ptr](#) A, const size_t lda)
 $fiszero : test A = 0.$
- template<class [Field](#) >
 void [fidentity](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda, const typename [Field::Element](#) &d)
 $creates a diagonal matrix$
- template<class [Field](#) >
 void [fidentity](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
 $creates a diagonal matrix$
- template<class [Field](#) , class OtherElement_ptr >
 void [finit](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
 $finit$ Initializes A in $F\mathbb{F}$.
- template<class [Field](#) , class OtherElement_ptr >
 void [fconvert](#) (const [Field](#) &F, const size_t m, const size_t n, OtherElement_ptr A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb)
 $fconvert A \leftarrow BmodF.$
- template<class [Field](#) >
 void [fnegin](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
 $fnegin A \leftarrow -A.$
- template<class [Field](#) >
 void [fneg](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) A, const size_t lda)
 $fneg A \leftarrow -B.$
- template<class [Field](#) >
 void [faxpby](#) (const [Field](#) &F, const size_t m, const size_t n, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) X, const size_t ldx, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) Y, const size_t ldy)
 $faxpby : y \leftarrow \alpha \cdot x + \beta \cdot y.$
- template<class [Field](#) >
 void [fmove](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb)
 $fmove : A \leftarrow B \text{ and } B \leftarrow 0.$
- template<class [Field](#) >
 size_t [bitsize](#) (const [Field](#) &F, size_t M, size_t N, const typename [Field::ConstElement_ptr](#) A, size_t lda)
 $bitsize$: Computes the largest bitsize of the matrix' coefficients.
- template<> size_t [bitsize](#)< [Givaro::ZRing](#)< [Givaro::Integer](#) > > (const [Givaro::ZRing](#)< [Givaro::Integer](#) > &F, size_t M, size_t N, const [Givaro::Integer](#) *A, size_t lda)
- template<class [Field](#) >
 void [ftsmv](#) (const [Field](#) &F, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) X, int incX)
 $ftsm$: $TRiangular$ Matrix Vector prodcut Computes $X \leftarrow op(A)X$

- template<class [Field](#) >
void [ftrsm](#) (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb)
*ftrsm: **TRI**angular **S**ystem solve with **M**atrix.*
- template<class [Field](#) , typename [FieldTrait](#) >
[Field::Element_ptr](#) [fsyrk_strassen](#) (const [Field](#) &F, const [FFLAS_UPLO](#) UpLo, const [FFLAS_TRANSPOSE](#) trans, const size_t N, const size_t K, const typename [Field::Element](#) y1, const typename [Field::Element](#) y2, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldTrait](#) > &H)
- template<typename [Field](#) >
[Field::Element_ptr](#) [pfgemm](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, size_t numthreads=0)
- template<class [Field](#) >
[Field::Element](#) * [pfgemm_1D_rec](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const typename [Field::Element](#) alpha, const typename [Field::Element_ptr](#) A, const size_t lda, const typename [Field::Element_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element](#) *C, const size_t ldc, size_t seuil)
- template<class [Field](#) >
[Field::Element](#) * [pfgemm_2D_rec](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const typename [Field::Element](#) alpha, const typename [Field::Element_ptr](#) A, const size_t lda, const typename [Field::Element_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element](#) *C, const size_t ldc, size_t seuil)
- template<class [Field](#) >
[Field::Element](#) * [pfgemm_3D_rec](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const typename [Field::Element](#) alpha, const typename [Field::Element_ptr](#) A, const size_t lda, const typename [Field::Element_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, size_t seuil, size_t *x)
- template<class [Field](#) >
[Field::Element_ptr](#) [pfgemm_3D_rec2](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const typename [Field::Element](#) alpha, const typename [Field::Element_ptr](#) A, const size_t lda, const typename [Field::Element_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, size_t seuil, size_t *x)
- template<class [Field](#) , class [ModeTrait](#) , class [Strat](#) , class [Param](#) >
std::enable_if<!std::is_same< [ModeTrait](#), [ModeCategories::ConvertTo](#)< [ElementCategories::RNSElementTag](#) >::value, typename [Field::Element_ptr](#) >::type [fgemm](#) (const [Field](#) &F, const [FFLAS::FFLAS_TRANSPOSE](#) ta, const [FFLAS::FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [ModeTrait](#), [ParSeqHelper::Parallel](#)< [Strat](#), [Param](#) > > &H)
- template<class [Field](#) , class [Cut](#) , class [Param](#) >
[Field::Element_ptr](#) [ftrsm](#) (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) Side, const [FFLAS::FFLAS_UPLO](#) UpLo, const [FFLAS::FFLAS_TRANSPOSE](#) TA, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t m, const size_t n, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb, [TRSMHelper](#)< [StructureHelper::Iterative](#), [ParSeqHelper::Parallel](#)< [Cut](#), [Param](#) > > &H)
- template<class [Field](#) , class [Cut](#) , class [Param](#) >
[Field::Element_ptr](#) [ftrsm](#) (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) Side, const [FFLAS::FFLAS_UPLO](#) UpLo, const [FFLAS::FFLAS_TRANSPOSE](#) TA, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t m, const size_t n, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb, [TRSMHelper](#)< [StructureHelper::Hybrid](#), [ParSeqHelper::Parallel](#)< [Cut](#), [Param](#) > > &H)

- `template<class Field , class SM >`
`void fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, const typename Field::Element &beta, typename Field::Element_ptr y)`
- `template<class Field , class SM >`
`void fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, const typename Field::Element &beta, typename Field::Element_ptr y, int ldy)`
- `template<class Field , class IndexT >`
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::COO > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field , class IndexT >`
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::COO_ZO > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field >`
`void sparse_delete (const Sparse< Field, SparseMatrix_t::COO > &A)`
- `template<class Field >`
`void sparse_delete (const Sparse< Field, SparseMatrix_t::COO_ZO > &A)`
- `template<class Field , class IndexT >`
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::CSR > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field , class IndexT >`
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::CSR_ZO > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field >`
`void sparse_delete (const Sparse< Field, SparseMatrix_t::CSR > &A)`
- `template<class Field >`
`void sparse_delete (const Sparse< Field, SparseMatrix_t::CSR_ZO > &A)`
- `template<class Field >`
`std::ostream & sparse_print (std::ostream &os, const Sparse< Field, SparseMatrix_t::CSR > &A)`
- `template<class IndexT >`
`void sparse_init (const Givaro::Modular< Givaro::Integer > &F, Sparse< Givaro::Modular< Givaro::Integer >, SparseMatrix_t::CSR > &A, const IndexT *row, const IndexT *col, Givaro::Integer *dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class IndexT >`
`void sparse_init (const Givaro::ZRing< Givaro::Integer > &F, Sparse< Givaro::ZRing< Givaro::Integer >, SparseMatrix_t::CSR_ZO > &A, const IndexT *row, const IndexT *col, Givaro::Integer *dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class IndexT , size_t RECINT_SIZE>`
`void sparse_init (const Givaro::ZRing< RecInt::rmint< RECINT_SIZE > > &F, Sparse< Givaro::ZRing< RecInt::rmint< RECINT_SIZE > >, SparseMatrix_t::CSR_ZO > &A, const IndexT *row, const IndexT *col, typename Givaro::ZRing< RecInt::rmint< RECINT_SIZE > >::Element_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class IndexT , size_t RECINT_SIZE>`
`void sparse_init (const Givaro::ZRing< RecInt::rmint< RECINT_SIZE > > &F, Sparse< Givaro::ZRing< RecInt::rmint< RECINT_SIZE > >, SparseMatrix_t::CSR > &A, const IndexT *row, const IndexT *col, typename Givaro::ZRing< RecInt::rmint< RECINT_SIZE > >::Element_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field >`
`void sparse_delete (const Sparse< Field, SparseMatrix_t::CSR_HYB > &A)`
- `template<class Field , class IndexT >`
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::CSR_HYB > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field , class IndexT >`
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::ELL > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field , class IndexT >`
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::ELL_ZO > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`

- `template<class Field >`
`void sparse_delete (const Sparse< Field, SparseMatrix_t::ELL > &A)`
- `template<class Field >`
`void sparse_delete (const Sparse< Field, SparseMatrix_t::ELL_ZO > &A)`
- `template<class Field , class IndexT >`
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::ELL_simd > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field , class IndexT >`
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field >`
`void sparse_delete (const Sparse< Field, SparseMatrix_t::ELL_simd > &A)`
- `template<class Field >`
`void sparse_delete (const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A)`
- `template<class Field >`
`void sparse_print (const Sparse< Field, SparseMatrix_t::ELL_simd > &A)`
- `template<class Field >`
`void sparse_delete (const Sparse< Field, SparseMatrix_t::HYB_ZO > &A)`
- `template<class Field , class IndexT >`
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::HYB_ZO > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<typename _Field >`
`std::ostream & operator<< (std::ostream &os, const Sparse< _Field, SparseMatrix_t::HYB_ZO > &A)`
- `template<class Field , bool sorted = true, bool read_integer = false>`
`void readSmsFormat (const std::string &path, const Field &f, index_t *&row, index_t *&col, typename Field::Element_ptr &val, index_t &rowdim, index_t &coldim, uint64_t &nnz)`
- `template<class Field >`
`void readSprFormat (const std::string &path, const Field &f, index_t *&row, index_t *&col, typename Field::Element_ptr &val, index_t &rowdim, index_t &coldim, uint64_t &nnz)`
- `template<class T >`
`std::enable_if< std::is_integral< T >::value, int > getDataType ()`
- `template<class T >`
`std::enable_if< std::is_floating_point< T >::value, int > getDataType ()`
- `template<class T >`
`std::enable_if< std::is_same< T, mpz_t >::value, int > getDataType ()`
- `template<class T >`
`int getDataType ()`
- `template<class Field >`
`void readMachineType (const Field &F, typename Field::Element &modulo, typename Field::Element_ptr val, std::ifstream &file, const uint64_t dims, const mask_t data_type, const mask_t field_desc)`
- `template<class Field >`
`void readDnsFormat (const std::string &path, const Field &F, index_t &rowdim, index_t &coldim, typename Field::Element_ptr &val)`
- `template<class Field >`
`void writeDnsFormat (const std::string &path, const Field &F, const index_t &rowdim, const index_t &coldim, typename Field::Element_ptr A, index_t ldA)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::SELL_ZO > &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::ModularTag)`
- `template<class Field >`
`void sparse_delete (const Sparse< Field, SparseMatrix_t::SELL > &A)`
- `template<class Field >`
`void sparse_delete (const Sparse< Field, SparseMatrix_t::SELL_ZO > &A)`
- `template<class Field >`
`void sparse_print (const Sparse< Field, SparseMatrix_t::SELL > &A)`

- `template<class Field , class IndexT >`
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::SELL > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz, uint64_t sigma=0)`
- `template<class Field , class IndexT >`
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::SELL_ZO > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class It >`
`double computeDeviation (It begin, It end)`
- `template<class Field >`
`StatsMatrix getStat (const Field &F, const index_t *row, const index_t *col, typename Field::ConstElement_ptr val, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field , class enable = void>`
`Field::Residu_t maxCardinality ()`
- `template<> uint64_t maxCardinality< Givaro::Modular< int64_t > > ()`
- `template<> uint32_t maxCardinality< Givaro::Modular< int32_t > > ()`
- `template<class Field >`
`Field::Residu_t minCardinality ()`
- `template<> void fflas_delete (FFPACK::rns_double_elt_ptr A)`
- `template<> void fflas_delete (FFPACK::rns_double_elt_cstptr A)`
- `template<> FFPACK::rns_double_elt_ptr fflas_new (const FFPACK::RNSIntegerMod< FFPACK::rns_double > &F, const size_t m, const Alignment align)`
- `template<> FFPACK::rns_double_elt_ptr fflas_new (const FFPACK::RNSIntegerMod< FFPACK::rns_double > &F, const size_t m, const size_t n, const Alignment align)`
- `template<typename RNS >`
`void finit_rns (const FFPACK::RNSIntegerMod< RNS > &F, const size_t m, const size_t n, size_t k, const Givaro::Integer *B, const size_t ldb, typename RNS::Element_ptr A)`
- `template<typename RNS >`
`void finit_trans_rns (const FFPACK::RNSIntegerMod< RNS > &F, const size_t m, const size_t n, size_t k, const Givaro::Integer *B, const size_t ldb, typename RNS::Element_ptr A)`
- `template<typename RNS >`
`void fconvert_rns (const FFPACK::RNSIntegerMod< RNS > &F, const size_t m, const size_t n, Givaro::Integer alpha, Givaro::Integer *B, const size_t ldb, typename RNS::ConstElement_ptr A)`
- `template<typename RNS >`
`void fconvert_trans_rns (const FFPACK::RNSIntegerMod< RNS > &F, const size_t m, const size_t n, Givaro::Integer alpha, Givaro::Integer *B, const size_t ldb, typename RNS::ConstElement_ptr A)`
- `template<> FFPACK::rns_double_elt_ptr fflas_new (const FFPACK::RNSInteger< FFPACK::rns_double > &F, const size_t m, const Alignment align)`
- `template<> FFPACK::rns_double_elt_ptr fflas_new (const FFPACK::RNSInteger< FFPACK::rns_double > &F, const size_t m, const size_t n, const Alignment align)`
- `template<typename RNS >`
`void finit_rns (const FFPACK::RNSInteger< RNS > &F, const size_t m, const size_t n, size_t k, const Givaro::Integer *B, const size_t ldb, typename FFPACK::RNSInteger< RNS >::Element_ptr A)`
- `template<typename RNS >`
`void fconvert_rns (const FFPACK::RNSInteger< RNS > &F, const size_t m, const size_t n, Givaro::Integer alpha, Givaro::Integer *B, const size_t ldb, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr A)`
- `template INST_OR_DECL void freduce (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t n, const FFLAS_ELT *Y, const size_t incY, FFLAS_ELT *X, const size_t incX)`

$$\text{freduce } x \leftarrow x \bmod F.$$
- `template INST_OR_DECL void freduce (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t n, const FFLAS_ELT *Y, const size_t incY, FFLAS_ELT *X, const size_t incX)`

$$\text{freduce } x \leftarrow y \bmod F.$$
- `template INST_OR_DECL void finit (const FFLAS_FIELD< FFLAS_ELT > &F, const size_t n, const FFLAS_ELT *Y, const size_t incY, FFLAS_ELT *X, const size_t incX)`

$$\text{finit } x \leftarrow y \bmod F.$$

- template `INST_OR_DECL` void `fconvert` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` n, `FFLAS_ELT` *X, const `size_t` incX, const `FFLAS_ELT` *Y, const `size_t` incY)

$$fconvert\ x \leftarrow y \bmod F.$$
- template `INST_OR_DECL` void `fnegin` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` n, `FFLAS_ELT` *X, const `size_t` incX)

$$fnegin\ x \leftarrow -x.$$
- template `INST_OR_DECL` void `fneg` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` n, const `FFLAS_ELT` *Y, const `size_t` incY, `FFLAS_ELT` *X, const `size_t` incX)

$$fneg\ x \leftarrow -y.$$
- template `INST_OR_DECL` void `fzero` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` n, `FFLAS_ELT` *X, const `size_t` incX)

$$fzero : A \leftarrow 0.$$
- template `INST_OR_DECL` bool `fiszero` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` n, const `FFLAS_ELT` *X, const `size_t` incX)

$$fiszero : test\ X = 0.$$
- template `INST_OR_DECL` bool `fequal` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` n, const `FFLAS_ELT` *X, const `size_t` incX, const `FFLAS_ELT` *Y, const `size_t` incY)

$$fequal : test\ X = Y.$$
- template `INST_OR_DECL` void `fassign` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` N, const `FFLAS_ELT` *Y, const `size_t` incY, `FFLAS_ELT` *X, const `size_t` incX)

$$fassign : x \leftarrow y.$$
- template `INST_OR_DECL` void `fscaln` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` n, const `FFLAS_ELT` alpha, `FFLAS_ELT` *X, const `size_t` incX)

$$fscaln\ x \leftarrow \alpha \cdot x.$$
- template `INST_OR_DECL` void `fscal` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` n, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *X, const `size_t` incX, `FFLAS_ELT` *Y, const `size_t` incY)

$$fscal\ y \leftarrow \alpha \cdot x.$$
- template `INST_OR_DECL` void `faxpy` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` N, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *X, const `size_t` incX, `FFLAS_ELT` *Y, const `size_t` incY)

$$faxpy : y \leftarrow \alpha \cdot x + y.$$
- template `INST_OR_DECL` `FFLAS_ELT` `fdot` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` N, const `FFLAS_ELT` *X, const `size_t` incX, const `FFLAS_ELT` *Y, const `size_t` incY)

$$faxpby : y \leftarrow \alpha \cdot x + \beta \cdot y.$$
- template `INST_OR_DECL` void `fswap` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` N, `FFLAS_ELT` *X, const `size_t` incX, `FFLAS_ELT` *Y, const `size_t` incY)

$$fswap : X \leftrightarrow Y.$$
- template `INST_OR_DECL` void `fadd` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` N, const `FFLAS_ELT` *A, const `size_t` inca, const `FFLAS_ELT` *B, const `size_t` incb, `FFLAS_ELT` *C, const `size_t` incc)
- template `INST_OR_DECL` void `fsub` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` N, const `FFLAS_ELT` *A, const `size_t` inca, const `FFLAS_ELT` *B, const `size_t` incb, `FFLAS_ELT` *C, const `size_t` incc)
- template `INST_OR_DECL` void `faddn` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` N, const `FFLAS_ELT` *B, const `size_t` incb, `FFLAS_ELT` *C, const `size_t` incc)
- template `INST_OR_DECL` void `fadd` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` N, const `FFLAS_ELT` *A, const `size_t` inca, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *B, const `size_t` incb, `FFLAS_ELT` *C, const `size_t` incc)
- template `INST_OR_DECL` void `fassign` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` m, const `size_t` n, const `FFLAS_ELT` *B, const `size_t` ldb, `FFLAS_ELT` *A, const `size_t` lda)

$$fassign : A \leftarrow B.$$
- template `INST_OR_DECL` void `fzero` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` m, const `size_t` n, `FFLAS_ELT` *A, const `size_t` lda)

$$fzero : A \leftarrow 0.$$

- template `INST_OR_DECL` bool `fequal` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t m, const size_t n, const `FFLAS_ELT` *A, const size_t lda, const `FFLAS_ELT` *B, const size_t ldb)

$$fequal : test A = B.$$
- template `INST_OR_DECL` bool `fiszero` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t m, const size_t n, const `FFLAS_ELT` *A, const size_t lda)

$$fiszero : test A = 0.$$
- template `INST_OR_DECL` void `fidentity` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t m, const size_t n, `FFLAS_ELT` *A, const size_t lda, const `FFLAS_ELT` &d)

$$creates a diagonal matrix$$
- template `INST_OR_DECL` void `fidentity` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t m, const size_t n, `FFLAS_ELT` *A, const size_t lda)

$$creates a diagonal matrix$$
- template `INST_OR_DECL` void `freduce` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t m, const size_t n, `FFLAS_ELT` *A, const size_t lda)

$$freduce A \leftarrow A mod F.$$
- template `INST_OR_DECL` void `freduce` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t m, const size_t n, const `FFLAS_ELT` *B, const size_t ldb, `FFLAS_ELT` *A, const size_t lda)

$$freduce A \leftarrow B mod F.$$
- template `INST_OR_DECL` void `finit` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t m, const size_t n, const `FFLAS_ELT` *B, const size_t ldb, `FFLAS_ELT` *A, const size_t lda)

$$finit A \leftarrow B mod F.$$
- template `INST_OR_DECL` void `fnegin` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t m, const size_t n, `FFLAS_ELT` *A, const size_t lda)

$$fnegin A \leftarrow -A.$$
- template `INST_OR_DECL` void `fneg` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t m, const size_t n, const `FFLAS_ELT` *B, const size_t ldb, `FFLAS_ELT` *A, const size_t lda)

$$fneg A \leftarrow -B.$$
- template `INST_OR_DECL` void `fscal` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t m, const size_t n, const `FFLAS_ELT` alpha, `FFLAS_ELT` *A, const size_t lda)

$$fscal A \leftarrow a \cdot A.$$
- template `INST_OR_DECL` void `fscal` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t m, const size_t n, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *A, const size_t lda, `FFLAS_ELT` *B, const size_t ldb)

$$fscal B \leftarrow a \cdot A.$$
- template `INST_OR_DECL` void `faxpy` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t m, const size_t n, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *X, const size_t idx, `FFLAS_ELT` *Y, const size_t ldy)

$$faxpy : y \leftarrow \alpha \cdot x + y.$$
- template `INST_OR_DECL` void `fmove` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t m, const size_t n, `FFLAS_ELT` *A, const size_t lda, `FFLAS_ELT` *B, const size_t ldb)

$$faxpy : y \leftarrow \alpha \cdot x + \beta \cdot y.$$
- template `INST_OR_DECL` void `fadd` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t M, const size_t N, const `FFLAS_ELT` *A, const size_t lda, const `FFLAS_ELT` *B, const size_t ldb, `FFLAS_ELT` *C, const size_t ldc)

$$fadd : matrix addition.$$
- template `INST_OR_DECL` void `fsub` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t M, const size_t N, const `FFLAS_ELT` *A, const size_t lda, const `FFLAS_ELT` *B, const size_t ldb, `FFLAS_ELT` *C, const size_t ldc)

$$fsub : matrix subtraction.$$
- template `INST_OR_DECL` void `fsubin` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t M, const size_t N, const `FFLAS_ELT` *B, const size_t ldb, `FFLAS_ELT` *C, const size_t ldc)

$$fsubin C = C - B$$
- template `INST_OR_DECL` void `fadd` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t M, const size_t N, const `FFLAS_ELT` *A, const size_t lda, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *B, const size_t ldb, `FFLAS_ELT` *C, const size_t ldc)

fadd : matrix addition with scaling.

- template `INST_OR_DECL` void `faddin` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t M, const size_t N, const `FFLAS_ELT` *B, const size_t ldb, `FFLAS_ELT` *C, const size_t ldc)

faddin

- template `INST_OR_DECL` `FFLAS_ELT` * `fgemv` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS_TRANSPOSE` TransA, const size_t M, const size_t N, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *A, const size_t lda, const `FFLAS_ELT` *X, const size_t incX, const `FFLAS_ELT` beta, `FFLAS_ELT` *Y, const size_t incY)

finite prime FFLAS_FIELD<*FFLAS_ELT*> *GEneral Matrix Vector multiplication.*

- template `INST_OR_DECL` void `fger` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size_t M, const size_t N, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *x, const size_t incx, const `FFLAS_ELT` *y, const size_t incy, `FFLAS_ELT` *A, const size_t lda)

fger: rank one update of a general matrix

- template `INST_OR_DECL` void `ftsv` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS_UPLO` Uplo, const `FFLAS_TRANSPOSE` TransA, const `FFLAS_DIAG` Diag, const size_t N, const `FFLAS_ELT` *A, const size_t lda, `FFLAS_ELT` *X, int incX)

ftsv: *TRI*angular System solve with Vector Computes $X \leftarrow \text{op}(A^{-1})X$

- template `INST_OR_DECL` void `ftsm` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS_SIDE` Side, const `FFLAS_UPLO` Uplo, const `FFLAS_TRANSPOSE` TransA, const `FFLAS_DIAG` Diag, const size_t M, const size_t N, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *A, const size_t lda, `FFLAS_ELT` *B, const size_t ldb)

ftsm: *TRI*angular System solve with *Matrix*.

- template `INST_OR_DECL` void `ftmm` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS_SIDE` Side, const `FFLAS_UPLO` Uplo, const `FFLAS_TRANSPOSE` TransA, const `FFLAS_DIAG` Diag, const size_t M, const size_t N, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *A, const size_t lda, `FFLAS_ELT` *B, const size_t ldb)

ftmm: *TRI*angular *Matrix Multiply*.

- template `INST_OR_DECL` `FFLAS_ELT` * `fgemm` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const size_t m, const size_t n, const size_t k, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *A, const size_t lda, const `FFLAS_ELT` *B, const size_t ldb, const `FFLAS_ELT` beta, `FFLAS_ELT` *C, const size_t ldc)

fgemm: *Field GEneral Matrix Multiply*.

- template `INST_OR_DECL` `FFLAS_ELT` * `fgemm` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const size_t m, const size_t n, const size_t k, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *A, const size_t lda, const `FFLAS_ELT` *B, const size_t ldb, const `FFLAS_ELT` beta, `FFLAS_ELT` *C, const size_t ldc, const `ParSeqHelper::Sequential` seq)

- template `INST_OR_DECL` `FFLAS_ELT` * `fgemm` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const size_t m, const size_t n, const size_t k, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *A, const size_t lda, const `FFLAS_ELT` *B, const size_t ldb, const `FFLAS_ELT` beta, `FFLAS_ELT` *C, const size_t ldc, const `ParSeqHelper::Parallel`< `CuttingStrategy::Recursive`, `StrategyParameter::TwoDAdaptive` > par)

- template `INST_OR_DECL` `FFLAS_ELT` * `fgemm` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const size_t m, const size_t n, const size_t k, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *A, const size_t lda, const `FFLAS_ELT` *B, const size_t ldb, const `FFLAS_ELT` beta, `FFLAS_ELT` *C, const size_t ldc, const `ParSeqHelper::Parallel`< `CuttingStrategy::Block`, `StrategyParameter::Threads` > par)

- template `INST_OR_DECL` `FFLAS_ELT` * `fsquare` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS_TRANSPOSE` ta, const size_t n, const `FFLAS_ELT` alpha, const `FFLAS_ELT` *A, const size_t lda, const `FFLAS_ELT` beta, `FFLAS_ELT` *C, const size_t ldc)

fsquare: Squares a matrix.

- template<class Cut = `CuttingStrategy::Block`, class Strat = `StrategyParameter::Threads`>
void `BlockCuts` (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)
- template<> void `BlockCuts`< `CuttingStrategy::Single`, `StrategyParameter::Threads` > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)

- `template<> void BlockCuts< CuttingStrategy::Row, StrategyParameter::Fixed > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<> void BlockCuts< CuttingStrategy::Row, StrategyParameter::Grain > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t grainsize)`
- `template<> void BlockCuts< CuttingStrategy::Block, StrategyParameter::Grain > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t grainsize)`
- `template<> void BlockCuts< CuttingStrategy::Column, StrategyParameter::Fixed > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<> void BlockCuts< CuttingStrategy::Column, StrategyParameter::Grain > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t grainsize)`
- `template<> void BlockCuts< CuttingStrategy::Block, StrategyParameter::Fixed > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<> void BlockCuts< CuttingStrategy::Row, StrategyParameter::Threads > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<> void BlockCuts< CuttingStrategy::Column, StrategyParameter::Threads > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<> void BlockCuts< CuttingStrategy::Block, StrategyParameter::Threads > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<class Cut = CuttingStrategy::Block, class Param = StrategyParameter::Threads>
void BlockCuts (size_t &rowBlockSize, size_t &colBlockSize, size_t &lastRBS, size_t &lastCBS, size_t &changeRBS, size_t &changeCBS, size_t &numRowBlock, size_t &numColBlock, size_t m, size_t n, const size_t numthreads)`
- `template<class Field >
void pfzero (const Field &F, size_t m, size_t n, typename Field::Element_ptr C, size_t BS=0)`
- `template<class Field, class RandIter >
void pfrand (const Field &F, RandIter &G, size_t m, size_t n, typename Field::Element_ptr C, size_t BS=0)`
- `template<class Field, class Cut, class Param >
Field::Element &fdot (const Field &F, const size_t N, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, typename Field::Element &d, const ParSeqHelper::Parallel< Cut, Param > par)`
- `template<class Field, class AlgoT, class FieldTrait >
Field::Element * pfgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, const typename Field::ConstElement_ptr A, const size_t lda, const typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element *C, const size_t ldc, MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Block, StrategyParameter::Threads > > &H)`
- `template<class Field, class AlgoT, class FieldTrait >
Field::Element * pfgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, const typename Field::ConstElement_ptr AA, const size_t lda, const typename Field::ConstElement_ptr BB, const size_t ldb, const typename Field::Element beta, typename Field::Element *C, const size_t ldc, MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive, StrategyParameter::ThreeDAdaptive > > &H)`
- `template<class Field, class AlgoT, class FieldTrait >
Field::Element * pfgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, const typename Field::ConstElement_ptr AA, const size_t lda, const typename Field::ConstElement_ptr BB, const size_t ldb, const typename Field::Element beta, typename Field::Element *C, const size_t ldc, MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive, StrategyParameter::TwoDAdaptive > > &H)`
- `template<class Field, class AlgoT, class FieldTrait >
Field::Element * pfgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, const typename Field::ConstElement_ptr AA, const size_t lda, const typename Field::ConstElement_ptr BB, const size_t ldb, const typename Field::Element beta, typename Field::Element *C, const size_t ldc, MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive, StrategyParameter::TwoD > > &H)`

- `template<class Field, class AlgoT, class FieldTrait >`
`Field::Element_ptr pfgemm` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const `size_t` m, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, const typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::ConstElement_ptr` B, const `size_t` ldb, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Field`, `AlgoT`, `FieldTrait`, `ParSeqHelper::Parallel`< `CuttingStrategy::Recursive`, `StrategyParameter::ThreeD` > > &H)
- `template<class Field, class AlgoT, class FieldTrait >`
`Field::Element * pfgemm` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const `size_t` m, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, const typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::ConstElement_ptr` B, const `size_t` ldb, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Field`, `AlgoT`, `FieldTrait`, `ParSeqHelper::Parallel`< `CuttingStrategy::Recursive`, `StrategyParameter::ThreeDInPlace` > > &H)
- `template<class Field, class AlgoT, class FieldTrait >`
`Field::Element_ptr fgemv` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `size_t` m, const `size_t` n, const typename `Field::Element` alpha, const typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::ConstElement_ptr` X, const `size_t` incX, const typename `Field::Element` beta, typename `Field::Element_ptr` Y, const `size_t` incY, `MMHelper`< `Field`, `AlgoT`, `FieldTrait`, `ParSeqHelper::Parallel`< `CuttingStrategy::Recursive`, `StrategyParameter::Threads` > > &H)
- `template<class Field, class AlgoT, class FieldTrait, class Cut >`
`Field::Element_ptr fgemv` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `size_t` m, const `size_t` n, const typename `Field::Element` alpha, const typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::ConstElement_ptr` X, const `size_t` incX, const typename `Field::Element` beta, typename `Field::Element_ptr` Y, const `size_t` incY, `MMHelper`< `Field`, `AlgoT`, `FieldTrait`, `ParSeqHelper::Parallel`< `CuttingStrategy::Row`, `Cut` > > &H)
- `void parseArguments` (int argc, char **argv, `Argument` *args, bool printDefaults=true)
- `char * getArgumentsValue` (int argc, char **argv, int i)
Get the value of an argument and avoid core dump when no value was given after an argument.
- `std::ostream & writeCommandString` (std::ostream &os, `Argument` *args, const char *programName=nullptr)
writes the values of all arguments, preceded by the programName
- `template<class Field >`
`std::ostream & WriteMatrix` (std::ostream &c, const `Field` &F, `size_t` m, `size_t` n, typename `Field::ConstElement_ptr` A, `size_t` lda, `FFLAS_FORMAT` format, bool column_major)
WriteMatrix: write a matrix to an output stream.
- `void preamble` (std::ifstream &ifs, `FFLAS_FORMAT` &format)
- `template<class Field >`
`Field::Element_ptr ReadMatrix` (std::ifstream &ifs, `Field` &F, `size_t` &m, `size_t` &n, typename `Field::Element_ptr` &A, `FFLAS_FORMAT` format=`FflasAuto`)
ReadMatrix: read a matrix from an input stream.
- `template<class Field >`
`Field::Element_ptr ReadMatrix` (const std::string &matrix_file, `Field` &F, `size_t` &m, `size_t` &n, typename `Field::Element_ptr` &A, `FFLAS_FORMAT` format=`FflasAuto`)
ReadMatrix: read a matrix from a file.
- `template<class Field >`
`void WriteMatrix` (std::string &matrix_file, const `Field` &F, int m, int n, typename `Field::ConstElement_ptr` A, `size_t` lda, `FFLAS_FORMAT` format=`FflasDense`, bool column_major=false)
WriteMatrix: write a matrix to a file.
- `std::ostream & WritePermutation` (std::ostream &c, const `size_t` *P, `size_t` N)
WritePermutation: write a permutation matrix to an output stream.
- `template<class Element >`
`bool alignable` ()
- `template<> bool alignable`< `Givaro::Integer` * > ()
- `template<class Field >`
`Field::Element_ptr fflas_new` (const `Field` &F, const `size_t` m, const `Alignment` align=`Alignment::DEFAULT`)

- `template<class Field >`
`Field::Element_ptr fflas_new` (const Field &F, const size_t m, const size_t n, const Alignment align=Alignment::DEFAULT)
- `template<class Element >`
`Element * fflas_new` (const size_t m, const Alignment align=Alignment::DEFAULT)
- `template<class Element_ptr >`
`void fflas_delete` (Element_ptr A)
- `template<class Ptr, class ... Args>`
`void fflas_delete` (Ptr p, Args ... args)
- `void prefetch` (const int64_t *)
- `void getTLBSize` (int &tlb)
- `void queryCacheSizes` (int &l1, int &l2, int &l3)
- `int queryL1CacheSize` ()
- `int queryTopLevelCacheSize` ()
- `uint64_t getSeed` ()

11.1.1 Typedef Documentation

11.1.1.1 Checker_fgemm

```
template<class Field >
using Checker_fgemm = FFLAS::Checker_Empty<Field>
```

11.1.1.2 Checker_ftrsm

```
template<class Field >
using Checker_ftrsm = FFLAS::Checker_Empty<Field>
```

11.1.1.3 ForceCheck_fgemm

```
template<class Field >
using ForceCheck_fgemm = CheckerImplem_fgemm<Field>
```

11.1.1.4 ForceCheck_ftrsm

```
template<class Field >
using ForceCheck_ftrsm = CheckerImplem_ftrsm<Field>
```

11.1.1.5 ZOSparseMatrix

```
using ZOSparseMatrix = std::true_type
```

11.1.1.6 NotZOSparseMatrix

```
using NotZOSparseMatrix = std::false_type
```


11.1.1.7 SimdSparseMatrix

```
using SimdSparseMatrix = std::true_type
```

11.1.1.8 NoSimdSparseMatrix

```
using NoSimdSparseMatrix = std::false_type
```

11.1.1.9 MKLSparseMatrixFormat

```
using MKLSparseMatrixFormat = std::true_type
```

11.1.1.10 NotMKLSparseMatrixFormat

```
using NotMKLSparseMatrixFormat = std::false_type
```

11.1.1.11 has_plus

```
template<class T >
using has_plus = typename std::conditional<std::is_arithmetic<T>::value, std::true_type,
has_plus_impl<T> >::type
```

11.1.1.12 has_minus

```
template<class T >
using has_minus = typename std::conditional<std::is_arithmetic<T>::value, std::true_type,
has_minus_impl<T> >::type
```

11.1.1.13 has_equal

```
template<class T >
using has_equal = typename std::conditional<std::is_arithmetic<T>::value, std::true_type,
std::is_copy_assignable<T> >::type
```

11.1.1.14 has_plus_eq

```
template<class T >
using has_plus_eq = typename std::conditional<std::is_arithmetic<T>::value, std::true_type,
has_plus_eq_impl<T> >::type
```

11.1.1.15 has_minus_eq

```
template<class T >
using has_minus_eq = typename std::conditional<std::is_arithmetic<T>::value, std::true_type,
has_minus_eq_impl<T> >::type
```

11.1.1.16 has_mul

```
template<class T >
using has_mul = typename std::conditional<std::is_arithmetic<T>::value, std::true_type, has_mul_impl<T>
>::type
```

11.1.1.17 has_mul_eq

```
template<class T >
using has_mul_eq = typename std::conditional<std::is_arithmetic<T>::value, std::true_type,
has_mul_eq_impl<T> >::type
```

11.1.1.18 Timer

```
typedef Givaro::Timer Timer
```

11.1.1.19 BaseTimer

```
typedef Givaro::BaseTimer BaseTimer
```

11.1.1.20 UserTimer

```
typedef Givaro::UserTimer UserTimer
```

11.1.1.21 SysTimer

```
typedef Givaro::SysTimer SysTimer
```

11.1.2 Enumeration Type Documentation**11.1.2.1 FFLAS_ORDER**

```
enum FFLAS_ORDER
```

Storage by row or col ?

Enumerator

FflasRowMajor	row major
FflasColMajor	col major

11.1.2.2 FFLAS_TRANSPOSE

enum [FFLAS_TRANSPOSE](#)

Is matrix transposed ?

Enumerator

FflasNoTrans	Matrix is not transposed.
FflasTrans	Matrix is transposed.

11.1.2.3 FFLAS_UPLO

enum [FFLAS_UPLO](#)

Is triangular matrix's shape upper ?

Enumerator

FflasUpper	Triangular matrix is Upper triangular (if $i > j$ then $T_{i,j} = 0$)
FflasLower	Triangular matrix is Lower triangular (if $i < j$ then $T_{i,j} = 0$)
FflasLeftTri	Triangular matrix is Left triangular (if $j > n - i - 1$ then $T_{i,j} = 0$)
FflasRightTri	Triangular matrix is Right triangular (if $j < n - i - 1$ then $T_{i,j} = 0$)

11.1.2.4 FFLAS_DIAG

enum [FFLAS_DIAG](#)

Is the triangular matrix implicitly unit diagonal ?

Enumerator

FflasNonUnit	Triangular matrix has an explicit arbitrary diagonal.
FflasUnit	Triangular matrix has an implicit unit diagonal ($T_{i,i} = 1$)

11.1.2.5 FFLAS_SIDE

enum [FFLAS_SIDE](#)

On what side ?

Enumerator

FflasLeft	Operator applied on the left.
FflasRight	Operator applied on the righth.

11.1.2.6 FFLAS_BASE

enum `FFLAS_BASE`

`FFLAS_BASE` determines the type of the element representation for Matrix Mult kernel.

(deprecated, should not be used)

Enumerator

<code>FflasDouble</code>	to use the double precision BLAS
<code>FflasFloat</code>	to use the single precison BLAS
<code>FflasGeneric</code>	for any other domain, that can not be converted to floating point integers

11.1.2.7 number_kind

enum `number_kind`

Enumerator

<code>zero</code>	
<code>one</code>	
<code>mone</code>	
<code>other</code>	

11.1.2.8 SparseMatrix_t

enum class `SparseMatrix_t` [strong]

Enumerator

<code>CSR</code>	
<code>CSR_ZO</code>	
<code>CSC</code>	
<code>CSC_ZO</code>	
<code>COO</code>	
<code>COO_ZO</code>	
<code>ELL</code>	
<code>ELL_ZO</code>	
<code>SELL</code>	
<code>SELL_ZO</code>	
<code>ELL_simd</code>	
<code>ELL_simd_ZO</code>	
<code>CSR_HYB</code>	
<code>HYB_ZO</code>	

11.1.2.9 FFLAS_FORMAT

enum [FFLAS_FORMAT](#)

Enumerator

FflasAuto	
FflasDense	
FflasSMS	
FflasBinary	
FflasMath	
FflasMaple	
FflasSageMath	

11.1.3 Function Documentation

11.1.3.1 InfNorm()

```
Givaro::Integer InfNorm (
    const size_t M,
    const size_t N,
    const Givaro::Integer * A,
    const size_t lda ) [inline]
```

11.1.3.2 min3()

```
template<class T >
const T & min3 (
    const T & m,
    const T & n,
    const T & k )
```

11.1.3.3 max3()

```
template<class T >
const T & max3 (
    const T & m,
    const T & n,
    const T & k )
```

11.1.3.4 min4()

```
template<class T >
const T & min4 (
    const T & m,
    const T & n,
    const T & k,
    const T & l )
```

11.1.3.5 max4()

```
template<class T >
const T & max4 (
    const T & m,
    const T & n,
    const T & k,
    const T & l )
```

11.1.3.6 fadd() [1/8]

```
template<class Field >
void fadd (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t inca,
    typename Field::ConstElement_ptr B,
    const size_t incb,
    typename Field::Element_ptr C,
    const size_t incc )
```

11.1.3.7 faddin() [1/5]

```
template<class Field >
void faddin (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr B,
    const size_t incb,
    typename Field::Element_ptr C,
    const size_t incc )
```

11.1.3.8 fsub() [1/4]

```
template<class Field >
void fsub (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t inca,
    typename Field::ConstElement_ptr B,
    const size_t incb,
    typename Field::Element_ptr C,
    const size_t incc )
```

11.1.3.9 fsubin() [1/3]

```
template<class Field >
void fsubin (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr B,
    const size_t incb,
    typename Field::Element_ptr C,
    const size_t incc )
```

11.1.3.10 fadd() [2/8]

```
template<class Field >
void fadd (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t inca,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr B,
    const size_t incb,
    typename Field::Element_ptr C,
    const size_t incc )
```

Todo optimise here

11.1.3.11 pfadd()

```
template<class Field >
void pfadd (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    typename Field::Element_ptr C,
    const size_t ldc,
    const size_t numths )
```

11.1.3.12 pfsub()

```
template<class Field >
void pfsub (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    typename Field::Element_ptr C,
    const size_t ldc,
    const size_t numths )
```

11.1.3.13 pfaddin()

```
template<class Field >
void pfaddin (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    typename Field::Element_ptr C,
    const size_t ldc,
    size_t numths )
```

11.1.3.14 pfsubin()

```
template<class Field >
void pfsubin (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    typename Field::Element_ptr C,
    const size_t ldc,
    size_t numths )
```

11.1.3.15 fadd() [3/8]

```
template<class Field >
void fadd (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    typename Field::Element_ptr C,
    const size_t ldc )
```

fadd : matrix addition.

Computes $C = A + B$.

Parameters

<i>F</i>	field
<i>M</i>	rows
<i>N</i>	cols
<i>A</i>	dense matrix of size MxN
<i>lda</i>	leading dimension of A
<i>B</i>	dense matrix of size MxN
<i>ldb</i>	leading dimension of B
<i>C</i>	dense matrix of size MxN
<i>ldc</i>	leading dimension of C

11.1.3.16 fsub() [2/4]

```
template<class Field >
void fsub (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    typename Field::Element_ptr C,
    const size_t ldc )
```

fsub : matrix subtraction.

Computes $C = A - B$.

Parameters

<i>F</i>	field
<i>M</i>	rows
<i>N</i>	cols
<i>A</i>	dense matrix of size MxN
<i>lda</i>	leading dimension of A
<i>B</i>	dense matrix of size MxN
<i>ldb</i>	leading dimension of B
<i>C</i>	dense matrix of size MxN
<i>ldc</i>	leading dimension of C

11.1.3.17 faddin() [2/5]

```
template<class Field >
void faddin (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    typename Field::Element_ptr C,
    const size_t ldc )
```

faddin

11.1.3.18 faddin() [3/5]

```
template<class Field >
void faddin (
    const Field & F,
    const FFLAS_UPLO uplo,
    const size_t N,
```

```

typename Field::ConstElement_ptr B,
const size_t ldb,
typename Field::Element_ptr C,
const size_t ldc )

```

fadding for symmetric matrices

11.1.3.19 fsubin() [2/3]

```

template<class Field >
void fsubin (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    typename Field::Element_ptr C,
    const size_t ldc )

```

fsubin $C = C - B$

11.1.3.20 fadd() [4/8]

```

template<class Field >
void fadd (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    typename Field::Element_ptr C,
    const size_t ldc )

```

fadd : matrix addition with scaling.

Computes $C = A + \text{alpha } B$.

Parameters

<i>F</i>	field
<i>M</i>	rows
<i>N</i>	cols
<i>A</i>	dense matrix of size MxN
<i>lda</i>	leading dimension of A
<i>alpha</i>	some scalar
<i>B</i>	dense matrix of size MxN
<i>ldb</i>	leading dimension of B
<i>C</i>	dense matrix of size MxN
<i>ldc</i>	leading dimension of C

11.1.3.21 fassign() [1/10]

```
template<class Field >
void fassign (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr Y,
    const size_t incY,
    typename Field::Element_ptr X,
    const size_t incX ) [inline]
```

$\text{fassign} : x \leftarrow y.$

X is preallocated

Todo variant for triangular matrix

Parameters

	F	field
	N	size of the vectors
out	X	vector in F
	$incX$	stride of X
in	Y	vector in F
	$incY$	stride of Y

11.1.3.22 fassign() [2/10]

```
template<>
void fassign (
    const Givaro::Modular< float > & F,
    const size_t N,
    const float * Y,
    const size_t incY,
    float * X,
    const size_t incX ) [inline]
```

11.1.3.23 fassign() [3/10]

```
template<>
void fassign (
    const Givaro::ModularBalanced< float > & F,
    const size_t N,
    const float * Y,
    const size_t incY,
    float * X,
    const size_t incX ) [inline]
```

11.1.3.24 fassign() [4/10]

```
template<>
void fassign (
    const Givaro::ZRing< float > & F,
    const size_t N,
    const float * Y,
    const size_t incY,
    float * X,
    const size_t incX ) [inline]
```

11.1.3.25 fassign() [5/10]

```
template<>
void fassign (
    const Givaro::Modular< double > & F,
    const size_t N,
    const double * Y,
    const size_t incY,
    double * X,
    const size_t incX ) [inline]
```

11.1.3.26 fassign() [6/10]

```
template<>
void fassign (
    const Givaro::ModularBalanced< double > & F,
    const size_t N,
    const double * Y,
    const size_t incY,
    double * X,
    const size_t incX ) [inline]
```

11.1.3.27 fassign() [7/10]

```
template<>
void fassign (
    const Givaro::ZRing< double > & F,
    const size_t N,
    const double * Y,
    const size_t incY,
    double * X,
    const size_t incX ) [inline]
```

11.1.3.28 fassign() [8/10]

```
template<class Field >
void fassign (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    typename Field::Element_ptr A,
    const size_t lda )
```

fassign : $A \leftarrow B$.

Parameters

F	field
m	number of rows to copy
n	number of cols to copy
A	matrix in F
lda	stride of A
B	vector in F
ldb	stride of B

11.1.3.29 faxpy() [1/6]

```
template<class Field >
void faxpy (
    const Field & F,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    typename Field::Element_ptr Y,
    const size_t incY ) [inline]
```

$\text{faxpy} : y \leftarrow \alpha \cdot x + y.$

Parameters

	F	field
	N	size of the vectors
	α	scalar
in	X	vector in F
	incX	stride of X
in, out	Y	vector in F
	incY	stride of Y

11.1.3.30 faxpy() [2/6]

```
template<>
void faxpy (
    const Givaro::DoubleDomain & ,
    const size_t N,
    const Givaro::DoubleDomain::Element a,
    Givaro::DoubleDomain::ConstElement_ptr x,
    const size_t incx,
    Givaro::DoubleDomain::Element_ptr y,
    const size_t incy ) [inline]
```

11.1.3.31 faxpy() [3/6]

```
template<>
void faxpy (
```

```

const Givaro::FloatDomain & ,
const size_t N,
const Givaro::FloatDomain::Element a,
Givaro::FloatDomain::ConstElement_ptr x,
const size_t incx,
Givaro::FloatDomain::Element_ptr y,
const size_t incy ) [inline]

```

11.1.3.32 faxpy() [4/6]

```

template<class Field >
void faxpy (
    const Field & F,
    const size_t m,
    const size_t n,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr X,
    const size_t ldx,
    typename Field::Element_ptr Y,
    const size_t ldy ) [inline]

```

faxpy : $y \leftarrow \alpha \cdot x + y$.

Parameters

	F	field
	m	row dimension
	n	column dimension
	α	scalar
in	X	vector in F
	ldx	leading dimension of X
in, out	Y	vector in F
	ldy	leading dimension of Y

11.1.3.33 fdot() [1/11]

```

template<class Field >
Field::Element fdot (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr x,
    const size_t incx,
    typename Field::ConstElement_ptr y,
    const size_t incy,
    ModeCategories::DefaultTag & MT ) [inline]

```

11.1.3.34 fdot() [2/11]

```

template<class Field >
Field::Element fdot (

```

```

    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr x,
    const size_t incx,
    typename Field::ConstElement_ptr y,
    const size_t incy,
    ModeCategories::DelayedTag & MT ) [inline]

```

11.1.3.35 fdot() [3/11]

```

template<>
Givaro::DoubleDomain::Element fdot (
    const Givaro::DoubleDomain & ,
    const size_t N,
    Givaro::DoubleDomain::ConstElement_ptr x,
    const size_t incx,
    Givaro::DoubleDomain::ConstElement_ptr y,
    const size_t incy,
    ModeCategories::DefaultTag & MT ) [inline]

```

11.1.3.36 fdot() [4/11]

```

template<>
Givaro::FloatDomain::Element fdot (
    const Givaro::FloatDomain & ,
    const size_t N,
    Givaro::FloatDomain::ConstElement_ptr x,
    const size_t incx,
    Givaro::FloatDomain::ConstElement_ptr y,
    const size_t incy,
    ModeCategories::DefaultTag & MT ) [inline]

```

11.1.3.37 fdot() [5/11]

```

template<class Field , class T >
Field::Element fdot (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr x,
    const size_t incx,
    typename Field::ConstElement_ptr y,
    const size_t incy,
    ModeCategories::ConvertTo< T > & MT ) [inline]

```

11.1.3.38 fdot() [6/11]

```

template<class Field >
Field::Element fdot (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr x,
    const size_t incx,
    typename Field::ConstElement_ptr y,
    const size_t incy,
    ModeCategories::DefaultBoundedTag & dbt ) [inline]

```


11.1.3.39 fdot() [7/11]

```
template<class Field >
Field::Element fdot (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr x,
    const size_t incx,
    typename Field::ConstElement_ptr y,
    const size_t incy,
    const ParSeqHelper::Sequential seq ) [inline]
```

11.1.3.40 fdot() [8/11]

```
template<class Field >
Field::Element fdot (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    typename Field::ConstElement_ptr Y,
    const size_t incY ) [inline]
```

fdot: dot product $x^T y$.

Parameters

F	field
N	size of the vectors
X	vector in F
$incX$	stride of X
Y	vector in F
$incY$	stride of Y

11.1.3.41 fgemm() [1/23]

```
template<class Field >
Field::Element_ptr fgemm (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
```

```

        MMHelper< Field, MMHelperAlgo::Winograd, ModeCategories::ConvertTo< ElementCategories::MachineFl
>, ParSeqHelper::Sequential > & H ) [inline]

```

11.1.3.42 fgemm() [2/23]

```

template<typename Field >
Field::Element_ptr fgemm (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    const ParSeqHelper::Sequential seq ) [inline]

```

11.1.3.43 fgemm() [3/23]

```

template<typename Field , class Cut , class Param >
Field::Element_ptr fgemm (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    const ParSeqHelper::Parallel< Cut, Param > par ) [inline]

```

11.1.3.44 fgemm() [4/23]

```

template<typename Field >
Field::Element_ptr fgemm (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,

```

```

const typename Field::Element alpha,
typename Field::ConstElement_ptr A,
const size_t lda,
typename Field::ConstElement_ptr B,
const size_t ldb,
const typename Field::Element beta,
typename Field::Element_ptr C,
const size_t ldc ) [inline]

```

fgemm: Field **G**eneral **M**atrix **M**ultiply.

Computes $C = \alpha \text{op}(A) \times \text{op}(B) + \beta C$ Automatically set Winograd recursion level

Parameters

<i>F</i>	field.
<i>ta</i>	if $\text{ta} == \text{FflasTrans}$ then $\text{op}(A) = A^t$, else $\text{op}(A) = A$,
<i>tb</i>	same for matrix B
<i>m</i>	see A
<i>n</i>	see B
<i>k</i>	see A
<i>alpha</i>	scalar
<i>beta</i>	scalar
<i>A</i>	$\text{op}(A)$ is $m \times k$
<i>B</i>	$\text{op}(B)$ is $k \times n$
<i>C</i>	C is $m \times n$
<i>lda</i>	leading dimension of A
<i>ldb</i>	leading dimension of B
<i>ldc</i>	leading dimension of C
<i>w</i>	recursive levels of Winograd's algorithm are used. No argument (or -1) does auto computation of w .

Warning

α must be invertible

11.1.3.45 fgemm() [5/23]

```

template<typename Field , class ModeT , class ParSeq >
Field::Element_ptr fgemm (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Auto, ModeT, ParSeq > & H ) [inline]

```

11.1.3.46 fgemm() [6/23]

```
template<class Field >
Field::Element_ptr fgemm (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, ModeCategories::DelayedTag, ParSeqHelper::Sequential
> & H ) [inline]
```

11.1.3.47 fsquare() [1/6]

```
template<class Field >
Field::Element_ptr fsquare (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const size_t n,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc ) [inline]
```

fsquare: Squares a matrix.

compute $C \leftarrow \alpha \text{op}(A) \text{op}(A) + \beta C$ over a Field F Avoid the conversion of B

Parameters

<i>ta</i>	if $ta == \text{FflasTrans}$, $\text{op}(A) = A^T$.
<i>F</i>	field
<i>n</i>	size of A
<i>alpha</i>	scalar
<i>beta</i>	scalar
<i>A</i>	dense matrix of size $n \times n$
<i>lda</i>	leading dimension of A
<i>C</i>	dense matrix of size $n \times n$
<i>ldc</i>	leading dimension of C

Bug why double ?

11.1.3.48 fsquare() [2/6]

```
template<>
double * fsquare (
    const Givaro::ModularBalanced< double > & F,
    const FFLAS_TRANSPOSE ta,
    const size_t n,
    const double alpha,
    const double * A,
    const size_t lda,
    const double beta,
    double * C,
    const size_t ldc ) [inline]
```

11.1.3.49 fsquare() [3/6]

```
template<>
float * fsquare (
    const Givaro::ModularBalanced< float > & F,
    const FFLAS_TRANSPOSE ta,
    const size_t n,
    const float alpha,
    const float * A,
    const size_t lda,
    const float beta,
    float * C,
    const size_t ldc ) [inline]
```

11.1.3.50 fsquare() [4/6]

```
template<>
double * fsquare (
    const Givaro::Modular< double > & F,
    const FFLAS_TRANSPOSE ta,
    const size_t n,
    const double alpha,
    const double * A,
    const size_t lda,
    const double beta,
    double * C,
    const size_t ldc ) [inline]
```

11.1.3.51 fsquare() [5/6]

```
template<>
float * fsquare (
    const Givaro::Modular< float > & F,
    const FFLAS_TRANSPOSE ta,
    const size_t n,
    const float alpha,
    const float * A,
    const size_t lda,
    const float beta,
    float * C,
    const size_t ldc ) [inline]
```

11.1.3.52 fgemm() [7/23]

```

template<typename RNS , typename ParSeqTrait >
FFPACK::RNSInteger< RNS >::Element_ptr fgemm (
    const FFPACK::RNSInteger< RNS > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename FFPACK::RNSInteger< RNS >::Element alpha,
    typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Ad,
    const size_t lda,
    typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Bd,
    const size_t ldb,
    const typename FFPACK::RNSInteger< RNS >::Element beta,
    typename FFPACK::RNSInteger< RNS >::Element_ptr Cd,
    const size_t ldc,
    MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag,
    ParSeqHelper::Compose< ParSeqHelper::Sequential, ParSeqTrait > > & H ) [inline]

```

11.1.3.53 fgemm() [8/23]

```

template<typename RNS >
FFPACK::RNSInteger< RNS >::Element_ptr fgemm (
    const FFPACK::RNSInteger< RNS > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename FFPACK::RNSInteger< RNS >::Element alpha,
    typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Ad,
    const size_t lda,
    typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Bd,
    const size_t ldb,
    const typename FFPACK::RNSInteger< RNS >::Element beta,
    typename FFPACK::RNSInteger< RNS >::Element_ptr Cd,
    const size_t ldc,
    MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag,
    ParSeqHelper::Sequential > & H ) [inline]

```

11.1.3.54 fgemm() [9/23]

```

template<typename RNS , typename ParSeqTrait >
FFPACK::RNSInteger< RNS >::Element_ptr fgemm (
    const FFPACK::RNSInteger< RNS > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename FFPACK::RNSInteger< RNS >::Element alpha,
    typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Ad,

```

```

    const size_t lda,
    typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Bd,
    const size_t ldb,
    const typename FFPACK::RNSInteger< RNS >::Element beta,
    typename FFPACK::RNSInteger< RNS >::Element_ptr Cd,
    const size_t ldc,
    MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag,
    ParSeqHelper::Compose< ParSeqHelper::Parallel< CuttingStrategy::RNSModulus, StrategyParameter::Threads
    >, ParSeqTrait > > & H ) [inline]

```

11.1.3.55 fgemm() [10/23]

```

template<typename RNS , typename Cut , typename Param >
FFPACK::RNSInteger< RNS >::Element_ptr fgemm (
    const FFPACK::RNSInteger< RNS > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename FFPACK::RNSInteger< RNS >::Element alpha,
    typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Ad,
    const size_t lda,
    typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Bd,
    const size_t ldb,
    const typename FFPACK::RNSInteger< RNS >::Element beta,
    typename FFPACK::RNSInteger< RNS >::Element_ptr Cd,
    const size_t ldc,
    MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag,
    ParSeqHelper::Parallel< Cut, Param > > & H ) [inline]

```

11.1.3.56 fgemm() [11/23]

```

template<class ParSeq >
Givaro::Integer * fgemm (
    const Givaro::ZRing< Givaro::Integer > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const Givaro::Integer alpha,
    const Givaro::Integer * A,
    const size_t lda,
    const Givaro::Integer * B,
    const size_t ldb,
    Givaro::Integer beta,
    Givaro::Integer * C,
    const size_t ldc,
    MMHelper< Givaro::ZRing< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo<
    ElementCategories::RNSElementTag >, ParSeq > & H ) [inline]

```

11.1.3.57 fgemm() [12/23]

```

template<typename RNS , class ModeT >
RNS::Element_ptr fgemm (
    const FFPACK::RNSInteger< RNS > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename RNS::Element alpha,
    typename RNS::ConstElement_ptr Ad,
    const size_t lda,
    typename RNS::ConstElement_ptr Bd,
    const size_t ldb,
    const typename RNS::Element beta,
    typename RNS::Element_ptr Cd,
    const size_t ldc,
    MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Winograd, ModeT, ParSeqHelper::Sequential
> & H ) [inline]

```

11.1.3.58 fgemm() [13/23]

```

template<typename RNS >
RNS::Element_ptr fgemm (
    const FFPACK::RNSIntegerMod< RNS > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename RNS::Element alpha,
    typename RNS::ConstElement_ptr Ad,
    const size_t lda,
    typename RNS::ConstElement_ptr Bd,
    const size_t ldb,
    const typename RNS::Element beta,
    typename RNS::Element_ptr Cd,
    const size_t ldc,
    MMHelper< FFPACK::RNSIntegerMod< RNS >, MMHelperAlgo::Winograd > & H ) [inline]

```

11.1.3.59 fgemm() [14/23]

```

Givaro::Integer * fgemm (
    const Givaro::Modular< Givaro::Integer > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const Givaro::Integer alpha,
    const Givaro::Integer * A,
    const size_t lda,
    const Givaro::Integer * B,

```



```

    const size_t ldb,
    const Givaro::Integer beta,
    Givaro::Integer * C,
    const size_t ldc,
    MMHelper< Givaro::Modular< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo<
ElementCategories::RNSElementTag > > & H ) [inline]

```

11.1.3.60 fgemm() [15/23]

```

template<class ParSeq >
Givaro::Integer * fgemm (
    const Givaro::Modular< Givaro::Integer > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const Givaro::Integer alpha,
    const Givaro::Integer * A,
    const size_t lda,
    const Givaro::Integer * B,
    const size_t ldb,
    const Givaro::Integer beta,
    Givaro::Integer * C,
    const size_t ldc,
    MMHelper< Givaro::Modular< Givaro::Integer >, MMHelperAlgo::Auto, ModeCategories::ConvertTo<
ElementCategories::RNSElementTag >, ParSeq > & H ) [inline]

```

11.1.3.61 fgemm() [16/23]

```

template<size_t K1, size_t K2, class ParSeq >
RecInt::ruint< K1 > * fgemm (
    const Givaro::Modular< RecInt::ruint< K1 >, RecInt::ruint< K2 > > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const RecInt::ruint< K1 > alpha,
    const RecInt::ruint< K1 > * A,
    const size_t lda,
    const RecInt::ruint< K1 > * B,
    const size_t ldb,
    RecInt::ruint< K1 > beta,
    RecInt::ruint< K1 > * C,
    const size_t ldc,
    MMHelper< Givaro::Modular< RecInt::ruint< K1 >, RecInt::ruint< K2 > >, MMHelperAlgo::Classic,
ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeq > & H ) [inline]

```

11.1.3.62 fgemm() [17/23]

```

template<class Field , class ModeT >
Field::Element_ptr fgemm (

```

```

    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, ModeT > & H ) [inline]

```

11.1.3.63 fgemm() [18/23]

```

template<class Field , class ModeT , class Cut , class Param >
Field::Element_ptr fgemm (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::WinogradPar, ModeT, ParSeqHelper::Parallel< Cut,
Param > > & H ) [inline]

```

11.1.3.64 fgemv() [1/19]

```

template<class Field >
Field::Element_ptr fgemv (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    const typename Field::Element beta,
    typename Field::Element_ptr Y,
    const size_t incY,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::ConvertTo< ElementCategories::MachineFlo
> > & H ) [inline]

```

11.1.3.65 fgemv() [2/19]

```

template<class Field >
Field::Element_ptr fgemv (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    const typename Field::Element beta,
    typename Field::Element_ptr Y,
    const size_t incY,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::DelayedTag > & H ) [inline]

```

11.1.3.66 fgemv() [3/19]

```

template<class Field >
Field::Element_ptr fgemv (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    const typename Field::Element beta,
    typename Field::Element_ptr Y,
    const size_t incY,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::DefaultTag > & H ) [inline]

```

11.1.3.67 fgemv() [4/19]

```

template<class Field >
Field::Element_ptr fgemv (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    const typename Field::Element beta,
    typename Field::Element_ptr Y,
    const size_t incY,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::LazyTag > & H ) [inline]

```

11.1.3.68 fgemv() [5/19]

```
template<class Field >
Field::Element_ptr fgemv (
    const Field & F,
    const FFLAS_TRANSPOSE TransA,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    const typename Field::Element beta,
    typename Field::Element_ptr Y,
    const size_t incY ) [inline]
```

finite prime Field GEneral Matrix Vector multiplication.

Computes $Y \leftarrow \alpha \text{op}(A)X + \beta Y$.

Parameters

	F	field
	$TransA$	if $TransA == FflasTrans$ then $\text{op}(A) = A^t$.
	M	rows
	N	cols
	$alpha$	scalar
	A	dense matrix of size $M \times N$
	lda	leading dimension of A
	X	dense vector of size N
	$incX$	stride of X
	$beta$	scalar
out	Y	dense vector of size M
	$incY$	stride of Y

11.1.3.69 fgemv() [6/19]

```
Givaro::ZRing< int64_t >::Element_ptr fgemv (
    const Givaro::ZRing< int64_t > & F,
    const FFLAS_TRANSPOSE ta,
    const size_t M,
    const size_t N,
    const int64_t alpha,
    const int64_t * A,
    const size_t lda,
    const int64_t * X,
    const size_t incX,
    const int64_t beta,
    int64_t * Y,
    const size_t incY,
    MMHelper< Givaro::ZRing< int64_t >, MMHelperAlgo::Classic, ModeCategories::DefaultTag
> & H ) [inline]
```

11.1.3.70 fgemv() [7/19]

```
Givaro::DoubleDomain::Element_ptr fgemv (
    const Givaro::DoubleDomain & F,
    const FFLAS_TRANSPOSE ta,
    const size_t M,
    const size_t N,
    const Givaro::DoubleDomain::Element alpha,
    const Givaro::DoubleDomain::ConstElement_ptr A,
    const size_t lda,
    const Givaro::DoubleDomain::ConstElement_ptr X,
    const size_t incX,
    const Givaro::DoubleDomain::Element beta,
    Givaro::DoubleDomain::Element_ptr Y,
    const size_t incY,
    MMHelper< Givaro::DoubleDomain, MMHelperAlgo::Classic, ModeCategories::DefaultTag
> & H ) [inline]
```

11.1.3.71 fgemv() [8/19]

```
template<class Field >
Field::Element_ptr fgemv (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::ConstElement_ptr X,
    const size_t incX,
    const typename Field::Element beta,
    typename Field::Element_ptr Y,
    const size_t incY,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::DefaultBoundedTag > & H )
[inline]
```

11.1.3.72 fgemv() [9/19]

```
Givaro::FloatDomain::Element_ptr fgemv (
    const Givaro::FloatDomain & F,
    const FFLAS_TRANSPOSE ta,
    const size_t M,
    const size_t N,
    const Givaro::FloatDomain::Element alpha,
    const Givaro::FloatDomain::ConstElement_ptr A,
    const size_t lda,
    const Givaro::FloatDomain::ConstElement_ptr X,
    const size_t incX,
    const Givaro::FloatDomain::Element beta,
    Givaro::FloatDomain::Element_ptr Y,
    const size_t incY,
    MMHelper< Givaro::FloatDomain, MMHelperAlgo::Classic, ModeCategories::DefaultTag
> & H ) [inline]
```

11.1.3.73 fgemv() [10/19]

```

template<class Field , class Cut , class Param >
Field::Element_ptr fgemv (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const size_t m,
    const size_t n,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::ConstElement_ptr X,
    const size_t incX,
    const typename Field::Element beta,
    typename Field::Element_ptr Y,
    const size_t incY,
    ParSeqHelper::Parallel< Cut, Param > & parH )

```

11.1.3.74 fgemv() [11/19]

```

template<class Field >
Field::Element_ptr fgemv (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const size_t m,
    const size_t n,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::ConstElement_ptr X,
    const size_t incX,
    const typename Field::Element beta,
    typename Field::Element_ptr Y,
    const size_t incY,
    ParSeqHelper::Sequential & seqH )

```

11.1.3.75 fgemv() [12/19]

```

FFPACK::rns_double::Element_ptr fgemv (
    const FFPACK::RNSInteger< FFPACK::rns_double > & F,
    const FFLAS_TRANSPOSE ta,
    const size_t M,
    const size_t N,
    const FFPACK::rns_double::Element alpha,
    FFPACK::rns_double::ConstElement_ptr A,
    const size_t lda,
    FFPACK::rns_double::ConstElement_ptr X,
    const size_t incX,
    const FFPACK::rns_double::Element beta,
    FFPACK::rns_double::Element_ptr Y,
    const size_t incY,
    MMHelper< FFPACK::RNSInteger< FFPACK::rns_double >, MMHelperAlgo::Classic, ModeCategories::Default > & H ) [inline]

```

11.1.3.76 fgemv() [13/19]

```
FFPACK::rns_double::Element_ptr fgemv (
    const FFPACK::RNSIntegerMod< FFPACK::rns_double > & F,
    const FFLAS_TRANSPOSE ta,
    const size_t M,
    const size_t N,
    const FFPACK::rns_double::Element alpha,
    FFPACK::rns_double::ConstElement_ptr A,
    const size_t lda,
    FFPACK::rns_double::ConstElement_ptr X,
    const size_t incX,
    const FFPACK::rns_double::Element beta,
    FFPACK::rns_double::Element_ptr Y,
    const size_t incY,
    MMHelper< FFPACK::RNSIntegerMod< FFPACK::rns_double >, MMHelperAlgo::Classic,
    ModeCategories::DefaultTag > & H ) [inline]
```

11.1.3.77 fgemv() [14/19]

```
Givaro::Integer * fgemv (
    const Givaro::ZRing< Givaro::Integer > & F,
    const FFLAS_TRANSPOSE ta,
    const size_t m,
    const size_t n,
    const Givaro::Integer alpha,
    Givaro::Integer * A,
    const size_t lda,
    Givaro::Integer * X,
    const size_t ldx,
    Givaro::Integer beta,
    Givaro::Integer * Y,
    const size_t ldy,
    MMHelper< Givaro::ZRing< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo<
    ElementCategories::RNSElementTag > > & H ) [inline]
```

11.1.3.78 fgemv() [15/19]

```
Givaro::Integer * fgemv (
    const Givaro::Modular< Givaro::Integer > & F,
    const FFLAS_TRANSPOSE ta,
    const size_t m,
    const size_t n,
    const Givaro::Integer alpha,
    Givaro::Integer * A,
    const size_t lda,
    Givaro::Integer * X,
    const size_t ldx,
    Givaro::Integer beta,
    Givaro::Integer * Y,
    const size_t ldy,
    MMHelper< Givaro::Modular< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo<
    ElementCategories::RNSElementTag > > & H ) [inline]
```

11.1.3.79 fgemv() [16/19]

```
template<size_t K1, size_t K2, class ParSeq >
RecInt::ruint< K1 > * fgemv (
    const Givaro::Modular< RecInt::ruint< K1 >, RecInt::ruint< K2 > > & F,
    const FFLAS_TRANSPOSE ta,
    const size_t m,
    const size_t n,
    const RecInt::ruint< K1 > alpha,
    const RecInt::ruint< K1 > * A,
    const size_t lda,
    const RecInt::ruint< K1 > * X,
    const size_t incx,
    RecInt::ruint< K1 > beta,
    RecInt::ruint< K1 > * Y,
    const size_t incy,
    MMHelper< Givaro::Modular< RecInt::ruint< K1 >, RecInt::ruint< K2 > >, MMHelperAlgo::Classic,
    ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeq > & H ) [inline]
```

11.1.3.80 fger() [1/12]

```
template<class Field >
void fger (
    const Field & F,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr x,
    const size_t incx,
    typename Field::ConstElement_ptr y,
    const size_t incy,
    typename Field::Element_ptr A,
    const size_t lda ) [inline]
```

fger: rank one update of a general matrix

Computes $A \leftarrow \alpha x y^T + A$

Parameters

	F	field
	M	rows
	N	cols
	α	scalar
in, out	A	dense matrix of size MxN and leading dimension lda
	lda	leading dimension of A
	x	dense vector of size M
	$incx$	stride of X
	y	dense vector of size N
	$incy$	stride of Y

11.1.3.81 fger() [2/12]

```

template<class Field >
void fger (
    const Field & F,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr x,
    const size_t incx,
    typename Field::ConstElement_ptr y,
    const size_t incy,
    typename Field::Element_ptr A,
    const size_t lda,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::ConvertTo< ElementCategories::MachineFlo
> > & H ) [inline]

```

11.1.3.82 fger() [3/12]

```

template<class Field , class AnyTag >
void fger (
    const Field & F,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr x,
    const size_t incx,
    typename Field::ConstElement_ptr y,
    const size_t incy,
    typename Field::Element_ptr A,
    const size_t lda,
    MMHelper< Field, MMHelperAlgo::Classic, AnyTag > & H ) [inline]

```

11.1.3.83 fger() [4/12]

```

void fger (
    const Givaro::DoubleDomain & F,
    const size_t M,
    const size_t N,
    const Givaro::DoubleDomain::Element alpha,
    const Givaro::DoubleDomain::ConstElement_ptr x,
    const size_t incx,
    const Givaro::DoubleDomain::ConstElement_ptr y,
    const size_t incy,
    Givaro::DoubleDomain::Element_ptr A,
    const size_t lda,
    MMHelper< Givaro::DoubleDomain, MMHelperAlgo::Classic, ModeCategories::DefaultTag
> & H ) [inline]

```

11.1.3.84 fger() [5/12]

```

template<class Field >
void fger (
    const Field & F,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr x,
    const size_t incx,
    const typename Field::ConstElement_ptr y,
    const size_t incy,
    typename Field::Element_ptr A,
    const size_t lda,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::DefaultBoundedTag > & H )
[inline]

```

11.1.3.85 fger() [6/12]

```

void fger (
    const Givaro::FloatDomain & F,
    const size_t M,
    const size_t N,
    const Givaro::FloatDomain::Element alpha,
    const Givaro::FloatDomain::ConstElement_ptr x,
    const size_t incx,
    const Givaro::FloatDomain::ConstElement_ptr y,
    const size_t incy,
    Givaro::FloatDomain::Element_ptr A,
    const size_t lda,
    MMHelper< Givaro::FloatDomain, MMHelperAlgo::Classic, ModeCategories::DefaultTag
> & H ) [inline]

```

11.1.3.86 fger() [7/12]

```

template<class Field >
void fger (
    const Field & F,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr x,
    const size_t incx,
    typename Field::ConstElement_ptr y,
    const size_t incy,
    typename Field::Element_ptr A,
    const size_t lda,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::LazyTag > & H ) [inline]

```

11.1.3.87 fger() [8/12]

```

template<class Field >
void fger (
    const Field & F,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr x,
    const size_t incx,
    typename Field::ConstElement_ptr y,
    const size_t incy,
    typename Field::Element_ptr A,
    const size_t lda,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::DelayedTag > & H ) [inline]

```

11.1.3.88 fger() [9/12]

```

void fger (
    const Givaro::Modular< Givaro::Integer > & F,
    const size_t M,
    const size_t N,
    const typename Givaro::Integer alpha,
    typename Givaro::Integer * x,
    const size_t incx,
    typename Givaro::Integer * y,
    const size_t incy,
    typename Givaro::Integer * A,
    const size_t lda,
    MMHelper< Givaro::Modular< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo<
ElementCategories::RNSElementTag > > & H ) [inline]

```

11.1.3.89 fger() [10/12]

```

template<typename RNS >
void fger (
    const FFPACK::RNSInteger< RNS > & F,
    const size_t M,
    const size_t N,
    const typename FFPACK::RNSInteger< RNS >::Element alpha,
    typename FFPACK::RNSInteger< RNS >::Element_ptr x,
    const size_t incx,
    typename FFPACK::RNSInteger< RNS >::Element_ptr y,
    const size_t incy,
    typename FFPACK::RNSInteger< RNS >::Element_ptr A,
    const size_t lda,
    MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag
> & H ) [inline]

```

11.1.3.90 fger() [11/12]

```

template<typename RNS >
void fger (
    const FFPACK::RNSIntegerMod< RNS > & F,
    const size_t M,
    const size_t N,
    const typename FFPACK::RNSIntegerMod< RNS >::Element alpha,
    typename FFPACK::RNSIntegerMod< RNS >::Element_ptr x,
    const size_t incx,
    typename FFPACK::RNSIntegerMod< RNS >::Element_ptr y,
    const size_t incy,
    typename FFPACK::RNSIntegerMod< RNS >::Element_ptr A,
    const size_t lda,
    MMHelper< FFPACK::RNSIntegerMod< RNS >, MMHelperAlgo::Classic > & H ) [inline]

```

11.1.3.91 freduce() [1/11]

```

template<class Field >
void freduce (
    const Field & F,
    const size_t n,
    typename Field::ConstElement_ptr Y,
    const size_t incY,
    typename Field::Element_ptr X,
    const size_t incX )

```

$\text{freduce } x \leftarrow y \bmod F.$

Parameters

F	field
n	size of the vectors
Y	vector of Element
$incY$	stride of Y
X	vector in F
$incX$	stride of X

Bug use cblas_(d)scal when possible

11.1.3.92 freduce() [2/11]

```

template<class Field >
void freduce (
    const Field & F,
    const size_t n,
    typename Field::Element_ptr X,
    const size_t incX )

```

$\text{freduce } x \leftarrow x \bmod F.$

Parameters

F	field
n	size of the vectors
X	vector in F
$incX$	stride of X

Bug use `cblas_(d)scal` when possible

11.1.3.93 `freduce_constoverride()` [1/2]

```
template<class Field >
void freduce_constoverride (
    const Field & F,
    const size_t m,
    typename Field::ConstElement_ptr A,
    const size_t incX )
```

11.1.3.94 `finit()` [1/8]

```
template<class Field , class ConstOtherElement_ptr >
void finit (
    const Field & F,
    const size_t n,
    ConstOtherElement_ptr Y,
    const size_t incY,
    typename Field::Element_ptr X,
    const size_t incX )
```

11.1.3.95 `finit()` [2/8]

```
template<class Field >
void finit (
    const Field & F,
    const size_t n,
    typename Field::Element_ptr X,
    const size_t incX )
```

`finit` Initializes X in F .

Parameters

F	field
n	size of the vectors
X	vector in F
$incX$	stride of X

11.1.3.96 freduce() [3/11]

```
template<class Field >
void freduce (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::Element_ptr A,
    const size_t lda )
```

$\text{freduce } A \leftarrow A \bmod F.$

Parameters

F	field
m	number of rows
n	number of cols
A	matrix in F
lda	stride of A

11.1.3.97 freduce() [4/11]

```
template<class Field >
void freduce (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda )
```

freduce for square symmetric matrices

11.1.3.98 pfreduce()

```
template<class Field >
void pfreduce (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t numths )
```

11.1.3.99 freduce() [5/11]

```
template<class Field >
void freduce (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::ConstElement_ptr B,
```

```
const size_t ldb,  
typename Field::Element_ptr A,  
const size_t lda )
```

freduce $A \leftarrow B \bmod F$.

Parameters

F	field
m	number of rows
n	number of cols
A	matrix in F
lda	stride of A
B	matrix in <code>Element</code>
ldb	stride of B

11.1.3.100 `freduce_constoverride()` [2/2]

```
template<class Field >
void freduce_constoverride (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::ConstElement_ptr A,
    const size_t lda )
```

11.1.3.101 `finit()` [3/8]

```
template<class Field , class OtherElement_ptr >
void finit (
    const Field & F,
    const size_t m,
    const size_t n,
    const OtherElement_ptr B,
    const size_t ldb,
    typename Field::Element_ptr A,
    const size_t lda )
```

$\text{finit } A \leftarrow B \bmod F.$

Parameters

F	field
m	number of rows
n	number of cols
A	matrix in F
lda	stride of A
B	matrix in <code>OtherElement</code>
ldb	stride of B

11.1.3.102 `finit()` [4/8]

```
template<class Field >
void finit (
    const Field & F,
```



```

    const size_t m,
    const size_t n,
    typename Field::Element_ptr A,
    const size_t lda )

```

11.1.3.103 freduce() [6/11]

```

template<>
void freduce (
    const FFPACK::RNSIntegerMod< FFPACK::rns_double > & F,
    const size_t n,
    FFPACK::RNSIntegerMod< FFPACK::rns_double >::Element_ptr A,
    size_t inc ) [inline]

```

11.1.3.104 freduce() [7/11]

```

template<>
void freduce (
    const FFPACK::RNSIntegerMod< FFPACK::rns_double > & F,
    const size_t m,
    const size_t n,
    FFPACK::rns_double::Element_ptr A,
    size_t lda ) [inline]

```

11.1.3.105 freivalds()

```

template<class Field >
bool freivalds (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    typename Field::ConstElement_ptr C,
    const size_t ldc ) [inline]

```

freivalds: Freivalds **GE**neral **M**atrix **M**ultiply **R**andom **C**heck.

Randomly Checks $C = \alpha \text{op}(A) \times \text{op}(B)$

Parameters

F	field.
ta	if $ta == \text{FflasTrans}$ then $\text{op}(A) = A^t$, else $\text{op}(A) = A$,
tb	same for matrix B
m	see A
n	see B

Parameters

k	see A
α	scalar
A	$\text{op}(A)$ is $m \times k$
B	$\text{op}(B)$ is $k \times n$
C	C is $m \times n$
lda	leading dimension of A
ldb	leading dimension of B
ldc	leading dimension of C

11.1.3.106 fscaln() [1/10]

```
template<class Field >
void fscaln (
    const Field & F,
    const size_t n,
    const typename Field::Element alpha,
    typename Field::Element_ptr X,
    const size_t incX ) [inline]
```

$\text{fscaln } x \leftarrow \alpha \cdot x.$

Parameters

F	field
n	size of the vectors
α	scalar
X	vector in F
$incX$	stride of X

Bug use `cblas_(d)scal` when possible

Todo check if comparison with $\pm 1, 0$ is necessary.

11.1.3.107 fscal() [1/10]

```
template<class Field >
void fscal (
    const Field & F,
    const size_t n,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    typename Field::Element_ptr Y,
    const size_t incY ) [inline]
```

$\text{fscal } y \leftarrow \alpha \cdot x.$

Parameters

	F	field
	n	size of the vectors
	α	scalar
in	X	vector in F
	$incX$	stride of X
out	Y	vector in F
	$incY$	stride of Y

Bug use `cblas_(d)scal` when possible

Todo check if comparison with $\pm 1, 0$ is necessary.

11.1.3.108 fscal() [2/10]

```
template<>
void fscal (
    const Givaro::DoubleDomain & ,
    const size_t N,
    const Givaro::DoubleDomain::Element a,
    Givaro::DoubleDomain::ConstElement_ptr x,
    const size_t incx,
    Givaro::DoubleDomain::Element_ptr y,
    const size_t incy ) [inline]
```

11.1.3.109 fscal() [3/10]

```
template<>
void fscal (
    const Givaro::FloatDomain & ,
    const size_t N,
    const Givaro::FloatDomain::Element a,
    Givaro::FloatDomain::ConstElement_ptr x,
    const size_t incx,
    Givaro::FloatDomain::Element_ptr y,
    const size_t incy ) [inline]
```

11.1.3.110 fscaln() [2/10]

```
template<>
void fscaln (
    const Givaro::DoubleDomain & ,
    const size_t N,
    const Givaro::DoubleDomain::Element a,
    Givaro::DoubleDomain::Element_ptr y,
    const size_t incy ) [inline]
```

11.1.3.111 fscaln() [3/10]

```
template<>
void fscaln (
    const Givaro::FloatDomain & ,
    const size_t N,
    const Givaro::FloatDomain::Element a,
    Givaro::FloatDomain::Element_ptr y,
    const size_t incy ) [inline]
```

11.1.3.112 fscaln() [4/10]

```
template<class Field >
void fscaln (
    const Field & F,
    const size_t m,
    const size_t n,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda ) [inline]
```

$\text{fscaln } A \leftarrow a \cdot A.$

Parameters

F	field
m	number of rows
n	number of cols
α	homotecie scalar
A	matrix in F
lda	stride of A

11.1.3.113 fscal() [4/10]

```
template<class Field >
void fscal (
    const Field & F,
    const size_t m,
    const size_t n,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb ) [inline]
```

$\text{fscal } B \leftarrow a \cdot A.$

Parameters

	F	field
	m	number of rows
	n	number of cols

Parameters

	<i>alpha</i>	homotecie scalar
in	<i>A</i>	matrix in F
	<i>lda</i>	stride of A
out	<i>B</i>	matrix in F
	<i>ldb</i>	stride of B

11.1.3.114 fscaln() [5/10]

```
template<>
void fscaln (
    const FFPACK::RNSInteger< FFPACK::rns_double > & F,
    const size_t n,
    const FFPACK::rns_double::Element alpha,
    FFPACK::rns_double::Element_ptr A,
    const size_t inc ) [inline]
```

11.1.3.115 fscal() [5/10]

```
template<>
void fscal (
    const FFPACK::RNSInteger< FFPACK::rns_double > & F,
    const size_t n,
    const FFPACK::rns_double::Element alpha,
    FFPACK::rns_double::ConstElement_ptr A,
    const size_t Ainc,
    FFPACK::rns_double::Element_ptr B,
    const size_t Binc ) [inline]
```

11.1.3.116 fscaln() [6/10]

```
template<>
void fscaln (
    const FFPACK::RNSInteger< FFPACK::rns_double > & F,
    const size_t m,
    const size_t n,
    const FFPACK::rns_double::Element alpha,
    FFPACK::rns_double::Element_ptr A,
    const size_t lda ) [inline]
```

11.1.3.117 fscal() [6/10]

```
template<>
void fscal (
    const FFPACK::RNSInteger< FFPACK::rns_double > & F,
    const size_t m,
    const size_t n,
    const FFPACK::rns_double::Element alpha,
    FFPACK::rns_double::ConstElement_ptr A,
    const size_t lda,
    FFPACK::rns_double::Element_ptr B,
    const size_t ldb ) [inline]
```

11.1.3.118 fscaln() [7/10]

```

template<>
void fscaln (
    const FFPACK::RNSIntegerMod< FFPACK::rns_double > & F,
    const size_t n,
    const typename FFPACK::RNSIntegerMod< FFPACK::rns_double >::Element alpha,
    typename FFPACK::RNSIntegerMod< FFPACK::rns_double >::Element_ptr A,
    const size_t inc ) [inline]

```

11.1.3.119 fscal() [7/10]

```

template<>
void fscal (
    const FFPACK::RNSIntegerMod< FFPACK::rns_double > & F,
    const size_t n,
    const FFPACK::rns_double::Element alpha,
    FFPACK::rns_double::ConstElement_ptr A,
    const size_t Ainc,
    FFPACK::rns_double::Element_ptr B,
    const size_t Binc ) [inline]

```

11.1.3.120 fscaln() [8/10]

```

template<>
void fscaln (
    const FFPACK::RNSIntegerMod< FFPACK::rns_double > & F,
    const size_t m,
    const size_t n,
    const FFPACK::rns_double::Element alpha,
    FFPACK::rns_double::Element_ptr A,
    const size_t lda ) [inline]

```

11.1.3.121 fscal() [8/10]

```

template<>
void fscal (
    const FFPACK::RNSIntegerMod< FFPACK::rns_double > & F,
    const size_t m,
    const size_t n,
    const FFPACK::rns_double::Element alpha,
    FFPACK::rns_double::ConstElement_ptr A,
    const size_t lda,
    FFPACK::rns_double::Element_ptr B,
    const size_t ldb ) [inline]

```

11.1.3.122 fsyr2k()

```
template<class Field >
Field::Element_ptr fsyr2k (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc ) [inline]
```

fsyr2k: Symmetric Rank 2K update

Computes the Lower or Upper triangular part of $C = \alpha(A \times B^T + B \times A^T) + \beta C$ or $C = \alpha(A^T \times B + B^T \times A) + \beta C$

Parameters

<i>F</i>	field.
<i>UpLo</i>	whether to compute the upper or the lower triangular part of the symmetric matrix C
<i>trans</i>	if <code>ta==FflasNoTrans</code> then compute $C = \alpha(A \times B^T + B \times A^T) + \beta C$, else $C = \alpha(A^T \times B + B^T \times A) + \beta C$
<i>n</i>	order of matrix C
<i>k</i>	see A
<i>alpha</i>	scalar
<i>A</i>	A is $n \times k$ (FflasNoTrans) or A is $k \times n$ (FflasTrans)
<i>lda</i>	leading dimension of A
<i>beta</i>	scalar
<i>C</i>	C is $n \times n$
<i>ldc</i>	leading dimension of C

Warning

α must be invertible

11.1.3.123 fsyrk() [1/16]

```
template<class Field >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
```

```

const size_t lda,
const typename Field::Element beta,
typename Field::Element_ptr C,
const size_t ldc ) [inline]

```

fsyrk: Symmetric Rank K update

Computes the Lower or Upper triangular part of $C = \alpha A \times A^T + \beta C$ or $C = \alpha A^T \times A + \beta C$

Parameters

<i>F</i>	field.
<i>UpLo</i>	whether to compute the upper or the lower triangular part of the symmetric matrix C
<i>trans</i>	if <code>ta==FflasNoTrans</code> then compute $C = \alpha A \times A^T + \beta C$, else $C = \alpha A^T \times A + \beta C$
<i>n</i>	order of matrix C
<i>k</i>	see A
<i>alpha</i>	scalar
<i>A</i>	<i>A</i> is $n \times k$ or <i>A</i> is $k \times n$
<i>lda</i>	leading dimension of A
<i>beta</i>	scalar
<i>C</i>	<i>C</i> is $n \times n$
<i>ldc</i>	leading dimension of C

Warning

α must be invertible

11.1.3.124 fsyrk() [2/16]

```

template<class Field >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    const ParSeqHelper::Sequential seq ) [inline]

```

11.1.3.125 fsyrk() [3/16]

```

template<class Field >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,

```



```

    const size_t N,
    const size_t K,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::DefaultTag > & H ) [inline]

```

11.1.3.126 fsyrk() [4/16]

```

template<class Field >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::ConvertTo< ElementCategories::MachineFlo
>, ParSeqHelper::Sequential > & H ) [inline]

```

11.1.3.127 fsyrk() [5/16]

```

template<class Field >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::DelayedTag > & H ) [inline]

```

11.1.3.128 fsyrk() [6/16]

```

template<class Field >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,

```

```

    const size_t K,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::LazyTag > & H ) [inline]

```

11.1.3.129 fsyrk() [7/16]

```

template<class Field , typename Mode >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::DivideAndConquer, Mode > & H ) [inline]

```

11.1.3.130 fsyrk() [8/16]

```

template<class Field >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Classic, ModeCategories::DefaultBoundedTag > & H )
[inline]

```

11.1.3.131 fsyrk() [9/16]

```

Givaro::FloatDomain::Element_ptr fsyrk (
    const Givaro::FloatDomain & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const Givaro::FloatDomain::Element alpha,

```

```

    Givaro::FloatDomain::ConstElement_ptr A,
    const size_t lda,
    const Givaro::FloatDomain::Element beta,
    Givaro::FloatDomain::Element_ptr C,
    const size_t ldc,
    MMHelper< Givaro::FloatDomain, MMHelperAlgo::Classic, ModeCategories::DefaultTag
> & H ) [inline]

```

11.1.3.132 fsyrk() [10/16]

```

Givaro::DoubleDomain::Element_ptr fsyrk (
    const Givaro::DoubleDomain & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const Givaro::DoubleDomain::Element alpha,
    Givaro::DoubleDomain::ConstElement_ptr A,
    const size_t lda,
    const Givaro::DoubleDomain::Element beta,
    Givaro::DoubleDomain::Element_ptr C,
    const size_t ldc,
    MMHelper< Givaro::DoubleDomain, MMHelperAlgo::Classic, ModeCategories::DefaultTag
> & H ) [inline]

```

11.1.3.133 fsyrk() [11/16]

```

template<class Field >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr D,
    const size_t incD,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    const size_t threshold = __FFLASFFPACK_FSYRK_THRESHOLD ) [inline]

```

fsyrk: Symmetric Rank K update with diagonal scaling

Computes the Lower or Upper triangular part of $C = \alpha A \times D \times A^T + \beta C$ or $C = \alpha A^T \times D \times A + \beta C$ where D is a diagonal matrix. Matrix A is updated into $D \times A$ (if trans = FflasTrans) or $A \times D$ (if trans = FflasNoTrans).

Parameters

<i>F</i>	field.
<i>UpLo</i>	whether to compute the upper or the lower triangular part of the symmetric matrix C
<i>trans</i>	if ta==FflasNoTrans then compute $C = \alpha A \times A^T + \beta C$, else $C = \alpha A^T \times A + \beta C$

Parameters

n	order of matrix C
k	see A
α	scalar
A	A is $n \times k$ or A is $k \times n$
lda	leading dimension of A
D	D is $k \times k$ diagonal matrix, stored as a vector of k coefficients
lda	leading dimension of A
β	scalar
C	C is $n \times n$
ldc	leading dimension of C

Warning

α must be invertible

11.1.3.134 fsyrk() [12/16]

```
template<class Field >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr D,
    const size_t incD,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    const ParSeqHelper::Sequential seq,
    const size_t threshold ) [inline]
```

11.1.3.135 fsyrk() [13/16]

```
template<class Field , class Cut , class Param >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr D,
    const size_t incD,
```

```

const typename Field::Element beta,
typename Field::Element_ptr C,
const size_t ldc,
const ParSeqHelper::Parallel< Cut, Param > par,
const size_t threshold ) [inline]

```

11.1.3.136 fsyrk() [14/16]

```

template<class Field >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr D,
    const size_t incD,
    const std::vector< bool > & twoBlock,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    const size_t threshold = __FFLASFFPACK_FSYRK_THRESHOLD ) [inline]

```

fsyrk: Symmetric Rank K update with diagonal scaling

Computes the Lower or Upper triangular part of $C = \alpha A \times \text{Delta} D \times A^T + \beta C$ or $C = \alpha A^T \times \text{Delta} D \times A + \beta C$ where D is a diagonal matrix and Delta is a block diagonal with either 1 on the diagonal or 2x2 swap blocks Matrix A is updated into $D \times A$ (if trans = FflasTrans) or $A \times D$ (if trans = FflasNoTrans).

Parameters

<i>F</i>	field.
<i>UpLo</i>	whether to compute the upper or the lower triangular part of the symmetric matrix C
<i>trans</i>	if ta==FflasNoTrans then compute $C = \alpha A \text{Delta} D \times A^T + \beta C$, else $C = \alpha A^T \text{Delta} D \times A + \beta C$
<i>n</i>	see B
<i>k</i>	see A
<i>alpha</i>	scalar
<i>A</i>	A is $n \times k$ or A is $k \times n$
<i>lda</i>	leading dimension of A
<i>D</i>	D is $k \times k$ diagonal matrix, stored as a vector of k coefficients
<i>twoBlocks</i>	a vector boolean indicating the beginning of each 2x2 blocs in Delta
<i>lda</i>	leading dimension of A
<i>beta</i>	scalar
<i>C</i>	C is $n \times n$
<i>ldc</i>	leading dimension of C

Warning

α must be invertible

11.1.3.137 computeS1S2()

```

template<class Field , class FieldTrait >
void computeS1S2 (
    const Field & F,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const typename Field::Element x,
    const typename Field::Element y,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr S,
    const size_t lds,
    typename Field::Element_ptr T,
    const size_t ldt,
    MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & WH ) [inline]

```

11.1.3.138 fsyrk() [15/16]

```

template<class Field >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, ModeCategories::DelayedTag, ParSeqHelper::Sequential
> & H ) [inline]

```

11.1.3.139 fsyrk() [16/16]

```

template<class Field , class Mode >
Field::Element_ptr fsyrk (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, Mode > & H ) [inline]

```

11.1.3.140 fsyrk_strassen() [1/2]

```
template<class Field , class FieldTrait >
Field::Element_ptr fsyrk_strassen (
    const Field & F,
    const FFLAS_UPLO uplo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const typename Field::Element y1,
    const typename Field::Element y2,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & WH ) [inline]
```

11.1.3.141 ftrmm() [1/3]

```
template<class Field >
void ftrmm (
    const Field & F,
    const FFLAS_SIDE Side,
    const FFLAS_UPLO Uplo,
    const FFLAS_TRANSPOSE TransA,
    const FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb ) [inline]
```

ftrmm: **T**Riangular **M**atrix **M**ultiply.

Computes $B \leftarrow \alpha \text{op}(A)B$ or $B \leftarrow \alpha B \text{op}(A)$.

Parameters

<i>F</i>	field
<i>Side</i>	if Side==FflasLeft then $B \leftarrow \alpha \text{op}(A)B$ is computed.
<i>Uplo</i>	if Uplo==FflasUpper then A is upper triangular
<i>TransA</i>	if TransA==FflasTrans then $\text{op}(A) = A^t$.
<i>Diag</i>	if Diag==FflasUnit then A is implicitly unit.
<i>M</i>	rows of B
<i>N</i>	cols of B
<i>alpha</i>	scalar
<i>A</i>	triangular matrix. If Side==FflasLeft then A is $N \times N$, otherwise A is $M \times M$
<i>lda</i>	leading dim of A
<i>B</i>	matrix of size MxN
<i>ldb</i>	leading dim of B

11.1.3.142 ftrmm() [2/3]

```

template<class Field >
void ftrmm (
    const Field & F,
    const FFLAS_SIDE Side,
    const FFLAS_UPLO Uplo,
    const FFLAS_TRANSPOSE TransA,
    const FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc ) [inline]

```

ftrmm: **TR**iangular **M**atrix **M**ultiply with 3 operands Computes $C \leftarrow \alpha \text{op}(A)B + \beta C$ or $C \leftarrow \alpha B \text{op}(A) + \beta C$.

Parameters

<i>F</i>	field
<i>Side</i>	if Side==FflasLeft then $B \leftarrow \alpha \text{op}(A)B$ is computed.
<i>Uplo</i>	if Uplo==FflasUpper then A is upper triangular
<i>TransA</i>	if TransA==FflasTrans then $\text{op}(A) = A^t$.
<i>Diag</i>	if Diag==FflasUnit then A is implicitly unit.
<i>M</i>	rows of B
<i>N</i>	cols of B
<i>alpha</i>	scalar
<i>A</i>	triangular matrix. If Side==FflasLeft then A is $N \times N$, otherwise A is $M \times M$
<i>lda</i>	leading dim of A
<i>B</i>	matrix of size MxN
<i>ldb</i>	leading dim of B
<i>beta</i>	scalar
<i>C</i>	matrix of size MxN
<i>ldc</i>	leading dim of C

11.1.3.143 ftrsm() [1/9]

```

template<class Field >
void ftrsm (
    const Field & F,
    const FFLAS_SIDE Side,
    const FFLAS_UPLO Uplo,
    const FFLAS_TRANSPOSE TransA,
    const FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,

```



```

typename Field::Element_ptr A,
const size_t lda,
typename Field::Element_ptr B,
const size_t ldb ) [inline]

```

11.1.3.144 ftrsm() [2/9]

```

template<class Field >
void ftrsm (
    const Field & F,
    const FFLAS_SIDE Side,
    const FFLAS_UPLO Uplo,
    const FFLAS_TRANSPOSE TransA,
    const FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb,
    const ParSeqHelper::Sequential & PSH ) [inline]

```

11.1.3.145 ftrsm() [3/9]

```

template<class Field , class Cut , class Param >
void ftrsm (
    const Field & F,
    const FFLAS_SIDE Side,
    const FFLAS_UPLO Uplo,
    const FFLAS_TRANSPOSE TransA,
    const FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb,
    const ParSeqHelper::Parallel< Cut, Param > & PSH ) [inline]

```

11.1.3.146 ftrsm() [4/9]

```

template<class Field , class ParSeqTrait = ParSeqHelper::Sequential>
void ftrsm (
    const Field & F,
    const FFLAS_SIDE Side,
    const FFLAS_UPLO Uplo,
    const FFLAS_TRANSPOSE TransA,
    const FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,

```

```

typename Field::Element_ptr A,
const size_t lda,
typename Field::Element_ptr B,
const size_t ldb,
TRSMHelper< StructureHelper::Recursive, ParSeqTrait > & H ) [inline]

```

11.1.3.147 ftrsm() [5/9]

```

void ftrsm (
    const Givaro::Modular< Givaro::Integer > & F,
    const FFLAS_SIDE Side,
    const FFLAS_UPLO Uplo,
    const FFLAS_TRANSPOSE TransA,
    const FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    const Givaro::Integer alpha,
    const Givaro::Integer * A,
    const size_t lda,
    Givaro::Integer * B,
    const size_t ldb ) [inline]

```

11.1.3.148 cblas_impstrsm()

```

void cblas_impstrsm (
    const enum FFLAS_ORDER Order,
    const enum FFLAS_SIDE Side,
    const enum FFLAS_UPLO Uplo,
    const enum FFLAS_TRANSPOSE TransA,
    const enum FFLAS_DIAG Diag,
    const int M,
    const int N,
    const FFPACK::rns_double_elt alpha,
    FFPACK::rns_double_elt_cstptr A,
    const int lda,
    FFPACK::rns_double_elt_ptr B,
    const int ldb ) [inline]

```

11.1.3.149 ftrsv() [1/2]

```

template<class Field >
void ftrsv (
    const Field & F,
    const FFLAS_UPLO Uplo,
    const FFLAS_TRANSPOSE TransA,
    const FFLAS_DIAG Diag,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr X,
    int incX ) [inline]

```

ftrsv: TRIangular System solve with Vector Computes $X \leftarrow \text{op}(A^{-1})X$

Parameters

<i>F</i>	field
<i>X</i>	vector of size N on a field F
<i>incX</i>	stride of X
<i>A</i>	a matrix of leading dimension lda and size N
<i>lda</i>	leading dimension of A
<i>N</i>	number of rows or columns of A according to TransA
<i>TransA</i>	if TransA==FflasTrans then $\text{op}(A) = A^t$.
<i>Diag</i>	if Diag==FflasUnit then A is unit.
<i>Uplo</i>	if Uplo==FflasUpper then A is upper triangular

11.1.3.150 igemm_()

```
void igemm_ (
    const enum FFLAS_ORDER Order,
    const enum FFLAS_TRANSPOSE TransA,
    const enum FFLAS_TRANSPOSE TransB,
    const size_t M,
    const size_t N,
    const size_t K,
    const int64_t alpha,
    const int64_t * A,
    const size_t lda,
    const int64_t * B,
    const size_t ldb,
    const int64_t beta,
    int64_t * C,
    const size_t ldc ) [inline]
```

11.1.3.151 finit() [5/8]

```
template<class Field , class OtherElement_ptr >
void finit (
    const Field & F,
    const size_t n,
    const OtherElement_ptr Y,
    const size_t incY,
    typename Field::Element_ptr X,
    const size_t incX )
```

$\text{finit } x \leftarrow y \bmod F.$

Parameters

<i>F</i>	field
<i>n</i>	size of the vectors
<i>Y</i>	vector of OtherElement
<i>incY</i>	stride of Y
<i>X</i>	vector in F
<i>incX</i>	stride of X

Bug use cblas_(d)scal when possible

11.1.3.152 fconvert() [1/3]

```
template<class Field , class OtherElement_ptr >
void fconvert (
    const Field & F,
    const size_t n,
    OtherElement_ptr X,
    const size_t incX,
    typename Field::ConstElement_ptr Y,
    const size_t incY )
```

$\text{fconvert } x \leftarrow y \bmod F.$

Parameters

F	field
n	size of the vectors
Y	vector of F
$incY$	stride of Y
X	vector in $OtherElement$
$incX$	stride of X

Bug use cblas_(d)scal when possible

11.1.3.153 fnegin() [1/4]

```
template<class Field >
void fnegin (
    const Field & F,
    const size_t n,
    typename Field::Element_ptr X,
    const size_t incX )
```

$\text{fnegin } x \leftarrow -x.$

Parameters

F	field
n	size of the vectors
X	vector in F
$incX$	stride of X

Bug use cblas_(d)scal when possible

11.1.3.154 fneg() [1/4]

```
template<class Field >
void fneg (
    const Field & F,
    const size_t n,
    typename Field::ConstElement_ptr Y,
    const size_t incY,
    typename Field::Element_ptr X,
    const size_t incX )
```

$\text{fneg } x \leftarrow -y.$

Parameters

F	field
n	size of the vectors
X	vector in F
$incX$	stride of X
Y	vector in F
$incY$	stride of Y

Bug use `cblas_(d)scal` when possible

11.1.3.155 fzero() [1/5]

```
template<class Field >
void fzero (
    const Field & F,
    const size_t n,
    typename Field::Element_ptr X,
    const size_t incX )
```

$\text{fzero} : A \leftarrow 0.$

Parameters

F	field
n	number of elements to zero
X	vector in F
$incX$	stride of X

11.1.3.156 frand() [1/2]

```
template<class Field , class RandIter >
void frand (
    const Field & F,
    RandIter & G,
    const size_t n,
```

```

typename Field::Element_ptr X,
const size_t incX )

```

frand : $A \leftarrow \text{random}$.

Parameters

F	field
G	randomiterator
n	number of elements to randomize
X	vector in F
$incX$	stride of X

11.1.3.157 fiszero() [1/4]

```

template<class Field >
bool fiszero (
    const Field & F,
    const size_t n,
    typename Field::ConstElement_ptr X,
    const size_t incX )

```

fiszero : test $X = 0$.

Parameters

F	field
n	vector dimension
X	vector in F
$incX$	increment of X

11.1.3.158 fequal() [1/4]

```

template<class Field >
bool fequal (
    const Field & F,
    const size_t n,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    typename Field::ConstElement_ptr Y,
    const size_t incY )

```

fequal : test $X = Y$.

Parameters

F	field
n	vector dimension
X	vector in F
$incX$	increment of X
Y	vector in F
$incY$	increment of Y

11.1.3.159 faxpby() [1/2]

```
template<class Field >
void faxpby (
    const Field & F,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    const typename Field::Element beta,
    typename Field::Element_ptr Y,
    const size_t incY )
```

$\text{faxpby} : y \leftarrow \alpha \cdot x + \beta \cdot y.$

Parameters

	F	field
	N	size of the vectors
	α	scalar
in	X	vector in F
	incX	stride of X
	β	scalar
in, out	Y	vector in F
	incY	stride of Y

Note

this is a catlas function

11.1.3.160 fdot() [9/11]

```
template<typename Field , class Cut , class Param >
Field::Element fdot (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    typename Field::ConstElement_ptr Y,
    const size_t incY,
    const ParSeqHelper::Parallel< Cut, Param > par ) [inline]
```

11.1.3.161 fswap() [1/2]

```
template<class Field >
void fswap (
    const Field & F,
    const size_t N,
    typename Field::Element_ptr X,
    const size_t incX,
    typename Field::Element_ptr Y,
    const size_t incY )
```

$\text{fswap} : X \leftrightarrow Y.$

Bug use cblas_dswap when double

Parameters

F	field
N	size of the vectors
X	vector in F
$incX$	stride of X
Y	vector in F
$incY$	stride of Y

11.1.3.162 fzero() [2/5]

```
template<class Field >
void fzero (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::Element_ptr A,
    const size_t lda )
```

$fzero : A \leftarrow 0$.

Parameters

F	field
m	number of rows to zero
n	number of cols to zero
A	matrix in F
lda	stride of A

Warning

may be buggy if Element is larger than int

11.1.3.163 fzero() [3/5]

```
template<class Field >
void fzero (
    const Field & F,
    const FFLAS_UPLO shape,
    const FFLAS_DIAG diag,
    const size_t n,
    typename Field::Element_ptr A,
    const size_t lda )
```

$fzero : A \leftarrow 0$ for a triangular matrix.

Parameters

F	field
$shape$	shape of the triangular matrix
m	number of rows to zero
n	number of cols to zero
A	matrix in F
lda	stride of A

Warning

may be buggy if Element is larger than int

11.1.3.164 frand() [2/2]

```
template<class Field , class RandIter >
void frand (
    const Field & F,
    RandIter & G,
    const size_t m,
    const size_t n,
    typename Field::Element_ptr A,
    const size_t lda )
```

frand : $A \leftarrow \text{random}.$

Parameters

F	field
G	randomiterator
m	number of rows to randomize
n	number of cols to randomize
A	matrix in F
lda	stride of A

11.1.3.165 fequal() [2/4]

```
template<class Field >
bool fequal (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb )
```

fequal : test $A = B.$

Parameters

F	field
m	row dimension
n	column dimension
A	m x n matrix in F
lda	leading dimension of A
B	m x n matrix in F
ldb	leading dimension of B

11.1.3.166 fiszero() [2/4]

```
template<class Field >
bool fiszero (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::ConstElement_ptr A,
    const size_t lda )
```

fiszero : test $A = 0$.

Parameters

F	field
m	row dimension
n	column dimension
A	m x n matrix in F
lda	leading dimension of A

11.1.3.167 fidentity() [1/4]

```
template<class Field >
void fidentity (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::Element_ptr A,
    const size_t lda,
    const typename Field::Element & d )
```

creates a diagonal matrix

11.1.3.168 fidentity() [2/4]

```
template<class Field >
void fidentity (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::Element_ptr A,
    const size_t lda )
```

creates a diagonal matrix

11.1.3.169 finit() [6/8]

```
template<class Field , class OtherElement_ptr >
void finit (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::Element_ptr A,
    const size_t lda )
```

finit Initializes A in F^S .

Parameters

F	field
m	number of rows
n	number of cols
A	matrix in F
lda	stride of A

11.1.3.170 fconvert() [2/3]

```
template<class Field , class OtherElement_ptr >
void fconvert (
    const Field & F,
    const size_t m,
    const size_t n,
    OtherElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb )
```

$\text{fconvert } A \leftarrow B \bmod F.$

Parameters

F	field
m	number of rows
n	number of cols
A	matrix in OtherElement
lda	stride of A
B	matrix in F
ldb	stride of B

Todo check if $n == lda$

11.1.3.171 fnegin() [2/4]

```
template<class Field >
void fnegin (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::Element_ptr A,
    const size_t lda )
```

$\text{fnegin } A \leftarrow -A.$

Parameters

F	field
m	number of rows
n	number of cols
A	matrix in F
lda	stride of A

Todo check if $n == lda$

11.1.3.172 fneg() [2/4]

```
template<class Field >
void fneg (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    typename Field::Element_ptr A,
    const size_t lda )
```

$\text{fneg } A \leftarrow -B.$

Parameters

F	field
m	number of rows
n	number of cols
A	matrix in F
lda	stride of A

Todo check if $n == lda$

11.1.3.173 faxpby() [2/2]

```
template<class Field >
void faxpby (
    const Field & F,
    const size_t m,
    const size_t n,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr X,
    const size_t ldx,
    const typename Field::Element beta,
    typename Field::Element_ptr Y,
    const size_t ldy )
```

$\text{faxpby} : y \leftarrow \alpha \cdot x + \beta \cdot y.$

Parameters

	F	field
	m	row dimension
	n	column dimension
	α	scalar
in	X	vector in F
	ldx	leading dimension of X
	β	scalar
	ldy	leading dimension of Y

Note

this is a catlas function

11.1.3.174 fmove() [1/2]

```
template<class Field >
void fmove (
    const Field & F,
    const size_t m,
    const size_t n,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb )
```

$\text{fmove} : A \leftarrow B \text{ and } B \leftarrow 0.$

Parameters

F	field
m	number of rows to copy
n	number of cols to copy
A	matrix in F
lda	stride of A
B	matrix in F
ldb	stride of B

11.1.3.175 bitsize()

```
template<class Field >
size_t bitsize (
    const Field & F,
    size_t M,
    size_t N,
    const typename Field::ConstElement_ptr A,
    size_t lda ) [inline]
```

bitsize: Computes the largest bitsize of the matrix' coefficients.

If the matrix is over a modular prime field, it returns the bitsize of the largest element (in a bsolute value)

Parameters

F	field
M	rows
N	cols
$incX$	stride of X
A	a matrix of leading dimension lda and size $M \times N$
lda	leading dimension of A

11.1.3.176 `bitsize< Givaro::ZRing< Givaro::Integer > >()`

```
template<>
size_t bitsize< Givaro::ZRing< Givaro::Integer > > (
    const Givaro::ZRing< Givaro::Integer > & F,
    size_t M,
    size_t N,
    const Givaro::Integer * A,
    size_t lda ) [inline]
```

11.1.3.177 `ftmv()`

```
template<class Field >
void ftrmv (
    const Field & F,
    const FFLAS_UPLO Uplo,
    const FFLAS_TRANSPOSE TransA,
    const FFLAS_DIAG Diag,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr X,
    int incX )
```

ftsm: TRIangular Matrix Vector prodcut Computes $X \leftarrow \text{op}(A)X$

Parameters

<i>F</i>	field
<i>X</i>	vector of size N on a field F
<i>incX</i>	stride of X
<i>A</i>	a matrix of leading dimension lda and size N
<i>lda</i>	leading dimension of A
<i>N</i>	number of rows and columns of A
<i>TransA</i>	if TransA==FflasTrans then $\text{op}(A) = A^T$.
<i>Diag</i>	if Diag==FflasUnit then A is unit diagonal.
<i>Uplo</i>	if Uplo==FflasUpper then A is upper triangular

11.1.3.178 `ftsm()` [6/9]

```
template<class Field >
void ftasm (
    const Field & F,
    const FFLAS_SIDE Side,
    const FFLAS_UPLO Uplo,
    const FFLAS_TRANSPOSE TransA,
    const FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
```

```

const size_t lda,
typename Field::Element_ptr B,
const size_t ldb )

```

ftsrsm: **TR**angular **S**ystem solve with **M**atrix.

Computes $B \leftarrow \alpha \text{op}(A^{-1})B$ or $B \leftarrow \alpha B \text{op}(A^{-1})$.

Parameters

<i>F</i>	field
<i>Side</i>	if Side==FflasLeft then $B \leftarrow \alpha \text{op}(A^{-1})B$ is computed.
<i>Uplo</i>	if Uplo==FflasUpper then A is upper triangular
<i>TransA</i>	if TransA==FflasTrans then $\text{op}(A) = A^t$.
<i>Diag</i>	if Diag==FflasUnit then A is unit.
<i>M</i>	rows of B
<i>N</i>	cols of B
<i>alpha</i>	scalar
<i>A</i>	triangular invertible matrix. If Side==FflasLeft then A is $N \times N$, otherwise A is $M \times M$
<i>lda</i>	leading dim of A
<i>B</i>	matrix of size MxN
<i>ldb</i>	leading dim of B

Bug α must be non zero.

11.1.3.179 fsyrk_strassen() [2/2]

```

template<class Field , typename FieldTrait >
Field::Element_ptr fsyrk_strassen (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const typename Field::Element y1,
    const typename Field::Element y2,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & H ) [inline]

```

11.1.3.180 pfgemm() [1/7]

```

template<typename Field >
Field::Element_ptr pfgemm (
    const Field & F,

```



```

const FFLAS_TRANSPOSE ta,
const FFLAS_TRANSPOSE tb,
const size_t m,
const size_t n,
const size_t k,
const typename Field::Element alpha,
typename Field::ConstElement_ptr A,
const size_t lda,
typename Field::ConstElement_ptr B,
const size_t ldb,
const typename Field::Element beta,
typename Field::Element_ptr C,
const size_t ldc,
size_t numthreads = 0 )

```

11.1.3.181 pfgemm_1D_rec()

```

template<class Field >
Field::Element * pfgemm_1D_rec (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    const typename Field::Element_ptr A,
    const size_t lda,
    const typename Field::Element_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element * C,
    const size_t ldc,
    size_t seuil )

```

11.1.3.182 pfgemm_2D_rec()

```

template<class Field >
Field::Element * pfgemm_2D_rec (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    const typename Field::Element_ptr A,
    const size_t lda,
    const typename Field::Element_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element * C,
    const size_t ldc,
    size_t seuil )

```

11.1.3.183 pfgemm_3D_rec()

```

template<class Field >
Field::Element * pfgemm_3D_rec (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    const typename Field::Element_ptr A,
    const size_t lda,
    const typename Field::Element_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    size_t seuil,
    size_t * x )

```

11.1.3.184 pfgemm_3D_rec2()

```

template<class Field >
Field::Element_ptr pfgemm_3D_rec2 (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    const typename Field::Element_ptr A,
    const size_t lda,
    const typename Field::Element_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    size_t seuil,
    size_t * x )

```

11.1.3.185 fgemm() [19/23]

```

template<class Field , class ModeTrait , class Strat , class Param >
std::enable_if<!std::is_same< ModeTrait, ModeCategories::ConvertTo< ElementCategories::RNSElementTag
> >::value, typename Field::Element_ptr >::type fgemm (
    const Field & F,
    const FFLAS::FFLAS_TRANSPOSE ta,
    const FFLAS::FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,

```

```

    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, ModeTrait, ParSeqHelper::Parallel< Strat,
Param > > & H ) [inline]

```

11.1.3.186 ftrsm() [7/9]

```

template<class Field , class Cut , class Param >
Field::Element_ptr ftrsm (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const FFLAS::FFLAS_UPLO UpLo,
    const FFLAS::FFLAS_TRANSPOSE TA,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t m,
    const size_t n,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb,
    TRSMHelper< StructureHelper::Iterative, ParSeqHelper::Parallel< Cut, Param > > &
H ) [inline]

```

11.1.3.187 ftrsm() [8/9]

```

template<class Field , class Cut , class Param >
Field::Element_ptr ftrsm (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const FFLAS::FFLAS_UPLO UpLo,
    const FFLAS::FFLAS_TRANSPOSE TA,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t m,
    const size_t n,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb,
    TRSMHelper< StructureHelper::Hybrid, ParSeqHelper::Parallel< Cut, Param > > & H
) [inline]

```

11.1.3.188 fspmv() [1/2]

```

template<class Field , class SM >
void fspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    const typename Field::Element & beta,
    typename Field::Element_ptr y ) [inline]

```

11.1.3.189 fspmm()

```
template<class Field , class SM >
void fspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    const typename Field::Element & beta,
    typename Field::Element_ptr y,
    int ldy ) [inline]
```

11.1.3.190 sparse_init() [1/16]

```
template<class Field , class IndexT >
void sparse_init (
    const Field & F,
    Sparse< Field, SparseMatrix_t::COO > & A,
    const IndexT * row,
    const IndexT * col,
    typename Field::ConstElement_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.191 sparse_init() [2/16]

```
template<class Field , class IndexT >
void sparse_init (
    const Field & F,
    Sparse< Field, SparseMatrix_t::COO_ZO > & A,
    const IndexT * row,
    const IndexT * col,
    typename Field::ConstElement_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.192 sparse_delete() [1/12]

```
template<class Field >
void sparse_delete (
    const Sparse< Field, SparseMatrix_t::COO > & A ) [inline]
```

11.1.3.193 sparse_delete() [2/12]

```
template<class Field >
void sparse_delete (
    const Sparse< Field, SparseMatrix_t::COO_ZO > & A ) [inline]
```

11.1.3.194 sparse_init() [3/16]

```
template<class Field , class IndexT >
void sparse_init (
    const Field & F,
    Sparse< Field, SparseMatrix_t::CSR > & A,
    const IndexT * row,
    const IndexT * col,
    typename Field::ConstElement_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.195 sparse_init() [4/16]

```
template<class Field , class IndexT >
void sparse_init (
    const Field & F,
    Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    const IndexT * row,
    const IndexT * col,
    typename Field::ConstElement_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.196 sparse_delete() [3/12]

```
template<class Field >
void sparse_delete (
    const Sparse< Field, SparseMatrix_t::CSR > & A ) [inline]
```

11.1.3.197 sparse_delete() [4/12]

```
template<class Field >
void sparse_delete (
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A ) [inline]
```

11.1.3.198 sparse_print() [1/3]

```
template<class Field >
std::ostream & sparse_print (
    std::ostream & os,
    const Sparse< Field, SparseMatrix_t::CSR > & A ) [inline]
```

11.1.3.199 sparse_init() [5/16]

```
template<class IndexT >
void sparse_init (
    const Givaro::Modular< Givaro::Integer > & F,
    Sparse< Givaro::Modular< Givaro::Integer >, SparseMatrix_t::CSR > & A,
    const IndexT * row,
    const IndexT * col,
    Givaro::Integer * dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.200 sparse_init() [6/16]

```
template<class IndexT >
void sparse_init (
    const Givaro::ZRing< Givaro::Integer > & F,
    Sparse< Givaro::ZRing< Givaro::Integer >, SparseMatrix_t::CSR_ZO > & A,
    const IndexT * row,
    const IndexT * col,
    Givaro::Integer * dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.201 sparse_init() [7/16]

```
template<class IndexT , size_t RECINT_SIZE>
void sparse_init (
    const Givaro::ZRing< RecInt::rmint< RECINT_SIZE > > & F,
    Sparse< Givaro::ZRing< RecInt::rmint< RECINT_SIZE > >, SparseMatrix_t::CSR_ZO >
    & A,
    const IndexT * row,
    const IndexT * col,
    typename Givaro::ZRing< RecInt::rmint< RECINT_SIZE > >::Element_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.202 sparse_init() [8/16]

```
template<class IndexT , size_t RECINT_SIZE>
void sparse_init (
    const Givaro::ZRing< RecInt::rmint< RECINT_SIZE > > & F,
    Sparse< Givaro::ZRing< RecInt::rmint< RECINT_SIZE > >, SparseMatrix_t::CSR > &
    A,
    const IndexT * row,
    const IndexT * col,
    typename Givaro::ZRing< RecInt::rmint< RECINT_SIZE > >::Element_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.203 sparse_delete() [5/12]

```
template<class Field >
void sparse_delete (
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A ) [inline]
```

11.1.3.204 sparse_init() [9/16]

```
template<class Field , class IndexT >
void sparse_init (
    const Field & F,
    Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    const IndexT * row,
    const IndexT * col,
    typename Field::ConstElement_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.205 sparse_init() [10/16]

```
template<class Field , class IndexT >
void sparse_init (
    const Field & F,
    Sparse< Field, SparseMatrix_t::ELL > & A,
    const IndexT * row,
    const IndexT * col,
    typename Field::ConstElement_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.206 sparse_init() [11/16]

```
template<class Field , class IndexT >
void sparse_init (
    const Field & F,
    Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    const IndexT * row,
    const IndexT * col,
    typename Field::ConstElement_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.207 sparse_delete() [6/12]

```
template<class Field >
void sparse_delete (
    const Sparse< Field, SparseMatrix_t::ELL > & A ) [inline]
```

11.1.3.208 sparse_delete() [7/12]

```
template<class Field >
void sparse_delete (
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A ) [inline]
```

11.1.3.209 sparse_init() [12/16]

```
template<class Field , class IndexT >
void sparse_init (
    const Field & F,
    Sparse< Field, SparseMatrix_t::ELL_simd > & A,
    const IndexT * row,
    const IndexT * col,
    typename Field::ConstElement_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.210 sparse_init() [13/16]

```
template<class Field , class IndexT >
void sparse_init (
    const Field & F,
    Sparse< Field, SparseMatrix_t::ELL_simd_ZO > & A,
    const IndexT * row,
    const IndexT * col,
    typename Field::ConstElement_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.211 sparse_delete() [8/12]

```
template<class Field >
void sparse_delete (
    const Sparse< Field, SparseMatrix_t::ELL_simd > & A ) [inline]
```

11.1.3.212 sparse_delete() [9/12]

```
template<class Field >
void sparse_delete (
    const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > & A ) [inline]
```

11.1.3.213 sparse_print() [2/3]

```
template<class Field >
void sparse_print (
    const Sparse< Field, SparseMatrix_t::ELL_simd > & A ) [inline]
```


11.1.3.214 sparse_delete() [10/12]

```
template<class Field >
void sparse_delete (
    const Sparse< Field, SparseMatrix_t::HYB_ZO > & A ) [inline]
```

11.1.3.215 sparse_init() [14/16]

```
template<class Field , class IndexT >
void sparse_init (
    const Field & F,
    Sparse< Field, SparseMatrix_t::HYB_ZO > & A,
    const IndexT * row,
    const IndexT * col,
    typename Field::ConstElement_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.216 operator<<()

```
template<typename _Field >
std::ostream & operator<< (
    std::ostream & os,
    const Sparse< _Field, SparseMatrix_t::HYB_ZO > & A )
```

11.1.3.217 readSmsFormat()

```
template<class Field , bool sorted = true, bool read_integer = false>
void readSmsFormat (
    const std::string & path,
    const Field & f,
    index_t *& row,
    index_t *& col,
    typename Field::Element_ptr & val,
    index_t & rowdim,
    index_t & coldim,
    uint64_t & nnz )
```

11.1.3.218 readSprFormat()

```
template<class Field >
void readSprFormat (
    const std::string & path,
    const Field & f,
    index_t *& row,
    index_t *& col,
    typename Field::Element_ptr & val,
    index_t & rowdim,
    index_t & coldim,
    uint64_t & nnz )
```

11.1.3.219 `getDataType()` [1/4]

```
template<class T >
std::enable_if< std::is_integral< T >::value, int > getDataType ( )
```

11.1.3.220 `getDataType()` [2/4]

```
template<class T >
std::enable_if< std::is_floating_point< T >::value, int > getDataType ( )
```

11.1.3.221 `getDataType()` [3/4]

```
template<class T >
std::enable_if< std::is_same< T, mpz_t >::value, int > getDataType ( )
```

11.1.3.222 `getDataType()` [4/4]

```
template<class T >
int getDataType ( )
```

11.1.3.223 `readMachineType()`

```
template<class Field >
void readMachineType (
    const Field & F,
    typename Field::Element & modulo,
    typename Field::Element_ptr val,
    std::ifstream & file,
    const uint64_t dims,
    const mask_t data_type,
    const mask_t field_desc )
```

11.1.3.224 `readDnsFormat()`

```
template<class Field >
void readDnsFormat (
    const std::string & path,
    const Field & F,
    index_t & rowdim,
    index_t & coldim,
    typename Field::Element_ptr & val )
```

11.1.3.225 `writeDnsFormat()`

```
template<class Field >
void writeDnsFormat (
    const std::string & path,
    const Field & F,
    const index_t & rowdim,
    const index_t & coldim,
    typename Field::Element_ptr A,
    index_t ldA )
```

11.1.3.226 fspmv() [2/2]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL_ZO > & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::ModularTag ) [inline]
```

11.1.3.227 sparse_delete() [11/12]

```
template<class Field >
void sparse_delete (
    const Sparse< Field, SparseMatrix_t::SELL > & A ) [inline]
```

11.1.3.228 sparse_delete() [12/12]

```
template<class Field >
void sparse_delete (
    const Sparse< Field, SparseMatrix_t::SELL_ZO > & A ) [inline]
```

11.1.3.229 sparse_print() [3/3]

```
template<class Field >
void sparse_print (
    const Sparse< Field, SparseMatrix_t::SELL > & A ) [inline]
```

11.1.3.230 sparse_init() [15/16]

```
template<class Field , class IndexT >
void sparse_init (
    const Field & F,
    Sparse< Field, SparseMatrix_t::SELL > & A,
    const IndexT * row,
    const IndexT * col,
    typename Field::ConstElement_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz,
    uint64_t sigma = 0 ) [inline]
```

11.1.3.231 sparse_init() [16/16]

```
template<class Field , class IndexT >
void sparse_init (
    const Field & F,
    Sparse< Field, SparseMatrix_t::SELL_ZO > & A,
    const IndexT * row,
    const IndexT * col,
    typename Field::ConstElement_ptr dat,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz ) [inline]
```

11.1.3.232 computeDeviation()

```
template<class It >
double computeDeviation (
    It begin,
    It end )
```

11.1.3.233 getStat()

```
template<class Field >
StatsMatrix getStat (
    const Field & F,
    const index_t * row,
    const index_t * col,
    typename Field::ConstElement_ptr val,
    uint64_t rowdim,
    uint64_t coldim,
    uint64_t nnz )
```

11.1.3.234 maxCardinality()

```
template<class Field , class enable = void>
Field::Residu_t maxCardinality ( ) [inline]
```

11.1.3.235 maxCardinality< Givaro::Modular< int64_t > >()

```
template<>
uint64_t maxCardinality< Givaro::Modular< int64_t > > ( ) [inline]
```

11.1.3.236 maxCardinality< Givaro::Modular< int32_t > >()

```
template<>
uint32_t maxCardinality< Givaro::Modular< int32_t > > ( ) [inline]
```

11.1.3.237 minCardinality()

```
template<class Field >
Field::Residu_t minCardinality ( ) [inline]
```

11.1.3.238 fflas_delete() [1/4]

```
template<>
void fflas_delete (
    FFPACK::rns_double_elt_ptr A ) [inline]
```

11.1.3.239 fflas_delete() [2/4]

```
template<>
void fflas_delete (
    FFPACK::rns_double_elt_cstptr A ) [inline]
```

11.1.3.240 fflas_new() [1/7]

```
template<>
FFPACK::rns_double_elt_ptr fflas_new (
    const FFPACK::RNSIntegerMod< FFPACK::rns_double > & F,
    const size_t m,
    const Alignment align ) [inline]
```

11.1.3.241 fflas_new() [2/7]

```
template<>
FFPACK::rns_double_elt_ptr fflas_new (
    const FFPACK::RNSIntegerMod< FFPACK::rns_double > & F,
    const size_t m,
    const size_t n,
    const Alignment align ) [inline]
```

11.1.3.242 finit_rns() [1/2]

```
template<typename RNS >
void finit_rns (
    const FFPACK::RNSIntegerMod< RNS > & F,
    const size_t m,
    const size_t n,
    size_t k,
    const Givaro::Integer * B,
    const size_t ldb,
    typename RNS::Element_ptr A )
```

11.1.3.243 finit_trans_rns()

```
template<typename RNS >
void finit_trans_rns (
    const FFPACK::RNSIntegerMod< RNS > & F,
    const size_t m,
    const size_t n,
    size_t k,
    const Givaro::Integer * B,
    const size_t ldb,
    typename RNS::Element_ptr A )
```

11.1.3.244 fconvert_rns() [1/2]

```

template<typename RNS >
void fconvert_rns (
    const FFPACK::RNSIntegerMod< RNS > & F,
    const size_t m,
    const size_t n,
    Givaro::Integer alpha,
    Givaro::Integer * B,
    const size_t ldb,
    typename RNS::ConstElement_ptr A )

```

11.1.3.245 fconvert_trans_rns()

```

template<typename RNS >
void fconvert_trans_rns (
    const FFPACK::RNSIntegerMod< RNS > & F,
    const size_t m,
    const size_t n,
    Givaro::Integer alpha,
    Givaro::Integer * B,
    const size_t ldb,
    typename RNS::ConstElement_ptr A )

```

11.1.3.246 fflas_new() [3/7]

```

template<>
FFPACK::rns_double_elt_ptr fflas_new (
    const FFPACK::RNSInteger< FFPACK::rns_double > & F,
    const size_t m,
    const Alignment align ) [inline]

```

11.1.3.247 fflas_new() [4/7]

```

template<>
FFPACK::rns_double_elt_ptr fflas_new (
    const FFPACK::RNSInteger< FFPACK::rns_double > & F,
    const size_t m,
    const size_t n,
    const Alignment align ) [inline]

```

11.1.3.248 finit_rns() [2/2]

```

template<typename RNS >
void finit_rns (
    const FFPACK::RNSInteger< RNS > & F,
    const size_t m,
    const size_t n,
    size_t k,
    const Givaro::Integer * B,
    const size_t ldb,
    typename FFPACK::RNSInteger< RNS >::Element_ptr A )

```

11.1.3.249 fconvert_rns() [2/2]

```
template<typename RNS >
void fconvert_rns (
    const FFPACK::RNSInteger< RNS > & F,
    const size_t m,
    const size_t n,
    Givaro::Integer alpha,
    Givaro::Integer * B,
    const size_t ldb,
    typename FFPACK::RNSInteger< RNS >::ConstElement_ptr A )
```

11.1.3.250 freduce() [8/11]

```
template INST_OR_DECL void freduce (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t n,
    FFLAS_ELT * X,
    const size_t incX )
```

freduce $x \leftarrow x \bmod F$.

Parameters

F	field
n	size of the vectors
X	vector in F
$incX$	stride of X

Bug use cblas_(d)scal when possible

11.1.3.251 freduce() [9/11]

```
template INST_OR_DECL void freduce (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t n,
    const FFLAS_ELT * Y,
    const size_t incY,
    FFLAS_ELT * X,
    const size_t incX )
```

freduce $x \leftarrow y \bmod F$.

Parameters

F	field
n	size of the vectors
Y	vector of Element
$incY$	stride of Y
X	vector in F
$incX$	stride of X

Bug use cblas_(d)scal when possible

11.1.3.252 finit() [7/8]

```
template INST_OR_DECL void finit (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t n,
    const FFLAS_ELT * Y,
    const size_t incY,
    FFLAS_ELT * X,
    const size_t incX )
```

$\text{finit } x \leftarrow y \bmod F.$

Parameters

F	field
n	size of the vectors
Y	vector of OtherElement
$incY$	stride of Y
X	vector in F
$incX$	stride of X

Bug use cblas_(d)scal when possible

11.1.3.253 fconvert() [3/3]

```
template INST_OR_DECL void fconvert (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t n,
    FFLAS_ELT * X,
    const size_t incX,
    const FFLAS_ELT * Y,
    const size_t incY )
```

$\text{fconvert } x \leftarrow y \bmod F.$

Parameters

F	field
n	size of the vectors
Y	vector of F
$incY$	stride of Y
X	vector in OtherElement
$incX$	stride of X

Bug use cblas_(d)scal when possible

11.1.3.254 fnegin() [3/4]

```
template INST_OR_DECL void fnegin (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t n,
    FFLAS_ELT * X,
    const size_t incX )
```

$\text{fnegin } x \leftarrow -x.$

Parameters

F	field
n	size of the vectors
X	vector in F
incX	stride of X

Bug use `cblas_(d)scal` when possible

11.1.3.255 fneg() [3/4]

```
template INST_OR_DECL void fneg (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t n,
    const FFLAS_ELT * Y,
    const size_t incY,
    FFLAS_ELT * X,
    const size_t incX )
```

$\text{fneg } x \leftarrow -y.$

Parameters

F	field
n	size of the vectors
X	vector in F
incX	stride of X
Y	vector in F
incY	stride of Y

Bug use `cblas_(d)scal` when possible

11.1.3.256 fzero() [4/5]

```
template INST_OR_DECL void fzero (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t n,
```

```

FFLAS_ELT * X,
const size_t incX )

```

fzero : $A \leftarrow 0$.

Parameters

F	field
n	number of elements to zero
X	vector in F
$incX$	stride of X

11.1.3.257 fiszero() [3/4]

```

template INST_OR_DECL bool fiszero (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t n,
    const FFLAS_ELT * X,
    const size_t incX )

```

fiszero : test $X = 0$.

Parameters

F	field
n	vector dimension
X	vector in F
$incX$	increment of X

11.1.3.258 fequal() [3/4]

```

template INST_OR_DECL bool fequal (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t n,
    const FFLAS_ELT * X,
    const size_t incX,
    const FFLAS_ELT * Y,
    const size_t incY )

```

fequal : test $X = Y$.

Parameters

F	field
n	vector dimension
X	vector in F
$incX$	increment of X
Y	vector in F
$incY$	increment of Y

11.1.3.259 fassign() [9/10]

```
template INST_OR_DECL void fassign (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t N,
    const FFLAS_ELT * Y,
    const size_t incY,
    FFLAS_ELT * X,
    const size_t incX )
```

fassign : $x \leftarrow y$.

X is preallocated

Todo variant for triangular matrix

Parameters

	F	field
	N	size of the vectors
out	X	vector in F
	$incX$	stride of X
in	Y	vector in F
	$incY$	stride of Y

11.1.3.260 fscaln() [9/10]

```
template INST_OR_DECL void fscaln (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t n,
    const FFLAS_ELT alpha,
    FFLAS_ELT * X,
    const size_t incX )
```

fscaln $x \leftarrow \alpha \cdot x$.

Parameters

F	field
n	size of the vectors
$alpha$	scalar
X	vector in F
$incX$	stride of X

Bug use cblas_(d)scal when possible

Todo check if comparison with +/-1,0 is necessary.

11.1.3.261 fscal() [9/10]

```
template INST_OR_DECL void fscal (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t n,
    const FFLAS_ELT alpha,
    const FFLAS_ELT * X,
    const size_t incX,
    FFLAS_ELT * Y,
    const size_t incY )
```

$\text{fscal } y \leftarrow \alpha \cdot x.$

Parameters

	F	field
	n	size of the vectors
	α	scalar
in	X	vector in F
	incX	stride of X
out	Y	vector in F
	incY	stride of Y

Bug use cblas_(d)scal when possible

Todo check if comparison with +/-1,0 is necessary.

11.1.3.262 faxpy() [5/6]

```
template INST_OR_DECL void faxpy (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t N,
    const FFLAS_ELT alpha,
    const FFLAS_ELT * X,
    const size_t incX,
    FFLAS_ELT * Y,
    const size_t incY )
```

$\text{faxpy} : y \leftarrow \alpha \cdot x + y.$

Parameters

	F	field
	N	size of the vectors
	α	scalar
in	X	vector in F
	incX	stride of X
in, out	Y	vector in F
	incY	stride of Y

11.1.3.263 fdot() [10/11]

```
template INST_OR_DECL FFLAS_ELT fdot (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t N,
    const FFLAS_ELT * X,
    const size_t incX,
    const FFLAS_ELT * Y,
    const size_t incY )
```

faxpby : $y \leftarrow \alpha \cdot x + \beta \cdot y$.

Parameters

	F	field
	N	size of the vectors
	α	scalar
in	X	vector in F
	$incX$	stride of X
	β	scalar
in, out	Y	vector in F
	$incY$	stride of Y

Note

this is a catlas function

fdot: dot product $x^T y$.

Parameters

F	field
N	size of the vectors
X	vector in F
$incX$	stride of X
Y	vector in F
$incY$	stride of Y

11.1.3.264 fswap() [2/2]

```
template INST_OR_DECL void fswap (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t N,
    FFLAS_ELT * X,
    const size_t incX,
    FFLAS_ELT * Y,
    const size_t incY )
```

fswap: $X \leftrightarrow Y$.

Bug use cblas_dswap when double

Parameters

F	field
N	size of the vectors
X	vector in F
$incX$	stride of X
Y	vector in F
$incY$	stride of Y

11.1.3.265 fadd() [5/8]

```
template INST_OR_DECL void fadd (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t N,
    const FFLAS_ELT * A,
    const size_t inca,
    const FFLAS_ELT * B,
    const size_t incb,
    FFLAS_ELT * C,
    const size_t incc )
```

11.1.3.266 fsub() [3/4]

```
template INST_OR_DECL void fsub (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t N,
    const FFLAS_ELT * A,
    const size_t inca,
    const FFLAS_ELT * B,
    const size_t incb,
    FFLAS_ELT * C,
    const size_t incc )
```

11.1.3.267 faddin() [4/5]

```
template INST_OR_DECL void faddin (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t N,
    const FFLAS_ELT * B,
    const size_t incb,
    FFLAS_ELT * C,
    const size_t incc )
```

11.1.3.268 fadd() [6/8]

```
template INST_OR_DECL void fadd (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t N,
    const FFLAS_ELT * A,
    const size_t inca,
    const FFLAS_ELT alpha,
    const FFLAS_ELT * B,
    const size_t incb,
    FFLAS_ELT * C,
    const size_t incc )
```

11.1.3.269 fassign() [10/10]

```
template INST_OR_DECL void fassign (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    const FFLAS_ELT * B,
    const size_t ldb,
    FFLAS_ELT * A,
    const size_t lda )
```

fassign : $A \leftarrow B$.

Parameters

F	field
m	number of rows to copy
n	number of cols to copy
A	matrix in F
lda	stride of A
B	vector in F
ldb	stride of B

11.1.3.270 fzero() [5/5]

```
template INST_OR_DECL void fzero (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    FFLAS_ELT * A,
    const size_t lda )
```

fzero : $A \leftarrow 0$.

Parameters

F	field
m	number of rows to zero
n	number of cols to zero
A	matrix in F
lda	stride of A

Warning

may be buggy if Element is larger than int

11.1.3.271 fequal() [4/4]

```
template INST_OR_DECL bool fequal (
    const FFLAS_FIELD< FFLAS_ELT > & F,
```

```

    const size_t m,
    const size_t n,
    const FFLAS_ELT * A,
    const size_t lda,
    const FFLAS_ELT * B,
    const size_t ldb )

```

fequal : test $A = B$.

Parameters

F	field
m	row dimension
n	column dimension
A	m x n matrix in F
lda	leading dimension of A
B	m x n matrix in F
ldb	leading dimension of B

11.1.3.272 fiszero() [4/4]

```

template INST_OR_DECL bool fiszero (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    const FFLAS_ELT * A,
    const size_t lda )

```

fiszero : test $A = 0$.

Parameters

F	field
m	row dimension
n	column dimension
A	m x n matrix in F
lda	leading dimension of A

11.1.3.273 fidentity() [3/4]

```

template INST_OR_DECL void fidentity (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    FFLAS_ELT * A,
    const size_t lda,
    const FFLAS_ELT & d )

```

creates a diagonal matrix

11.1.3.274 fidentity() [4/4]

```
template INST_OR_DECL void fidentity (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    FFLAS_ELT * A,
    const size_t lda )
```

creates a diagonal matrix

11.1.3.275 freduce() [10/11]

```
template INST_OR_DECL void freduce (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    FFLAS_ELT * A,
    const size_t lda )
```

freduce $A \leftarrow A \bmod F$.

Parameters

F	field
m	number of rows
n	number of cols
A	matrix in F
lda	stride of A

11.1.3.276 freduce() [11/11]

```
template INST_OR_DECL void freduce (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    const FFLAS_ELT * B,
    const size_t ldb,
    FFLAS_ELT * A,
    const size_t lda )
```

freduce $A \leftarrow B \bmod F$.

Parameters

F	field
m	number of rows
n	number of cols
A	matrix in F
lda	stride of A
B	matrix in Element
ldb	stride of B

11.1.3.277 finit() [8/8]

```
template INST_OR_DECL void finit (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    const FFLAS_ELT * B,
    const size_t ldb,
    FFLAS_ELT * A,
    const size_t lda )
```

$\text{finit } A \leftarrow B \bmod F.$

Parameters

F	field
m	number of rows
n	number of cols
A	matrix in F
lda	stride of A
B	matrix in F
ldb	stride of B

11.1.3.278 fnegin() [4/4]

```
template INST_OR_DECL void fnegin (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    FFLAS_ELT * A,
    const size_t lda )
```

$\text{fnegin } A \leftarrow -A.$

Parameters

F	field
m	number of rows
n	number of cols
A	matrix in F
lda	stride of A

11.1.3.279 fneg() [4/4]

```
template INST_OR_DECL void fneg (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    const FFLAS_ELT * B,
    const size_t ldb,
```

```

FFLAS_ELT * A,
const size_t lda )

```

$\text{fneg } A \leftarrow -B.$

Parameters

F	field
m	number of rows
n	number of cols
A	matrix in F
lda	stride of A

11.1.3.280 fscalin() [10/10]

```

template INST_OR_DECL void fscalin (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    const FFLAS_ELT alpha,
    FFLAS_ELT * A,
    const size_t lda )

```

$\text{fscal } A \leftarrow a \cdot A.$

Parameters

F	field
m	number of rows
n	number of cols
$alpha$	homotecie scalar
A	matrix in F
lda	stride of A

11.1.3.281 fsca() [10/10]

```

template INST_OR_DECL void fsca (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    const FFLAS_ELT alpha,
    const FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * B,
    const size_t ldb )

```

$\text{fsca } B \leftarrow a \cdot A.$

Parameters

	F	field

Parameters

	m	number of rows
	n	number of cols
	α	homotecie scalar
in	A	matrix in F
	lda	stride of A
out	B	matrix in F
	ldb	stride of B

11.1.3.282 faxpy() [6/6]

```
template INST_OR_DECL void faxpy (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    const FFLAS_ELT alpha,
    const FFLAS_ELT * X,
    const size_t ldx,
    FFLAS_ELT * Y,
    const size_t ldy )
```

$\text{faxpy} : y \leftarrow \alpha \cdot x + y.$

Parameters

	F	field
	m	row dimension
	n	column dimension
	α	scalar
in	X	vector in F
	ldx	leading dimension of X
in, out	Y	vector in F
	ldy	leading dimension of Y

11.1.3.283 fmove() [2/2]

```
template INST_OR_DECL void fmove (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t m,
    const size_t n,
    FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * B,
    const size_t ldb )
```

$\text{faxpby} : y \leftarrow \alpha \cdot x + \beta \cdot y.$

Parameters

	F	field

Parameters

	m	row dimension
	n	column dimension
	α	scalar
in	X	vector in F
	ldx	leading dimension of X
	β	scalar
in, out	Y	vector in F
	ldy	leading dimension of Y

Note

this is a catlas function

fmove : $A \leftarrow B$ and $B \leftarrow 0$.

Parameters

F	field
m	number of rows to copy
n	number of cols to copy
A	matrix in F
lda	stride of A
B	vector in F
ldb	stride of B

11.1.3.284 fadd() [7/8]

```
template INST_OR_DECL void fadd (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    const FFLAS_ELT * A,
    const size_t lda,
    const FFLAS_ELT * B,
    const size_t ldb,
    FFLAS_ELT * C,
    const size_t ldc )
```

fadd : matrix addition.

Computes $C = A + B$.

Parameters

F	field
M	rows
N	cols
A	dense matrix of size $M \times N$
lda	leading dimension of A

Parameters

<i>B</i>	dense matrix of size $M \times N$
<i>ldb</i>	leading dimension of B
<i>C</i>	dense matrix of size $M \times N$
<i>ldc</i>	leading dimension of C

11.1.3.285 fsub() [4/4]

```
template INST_OR_DECL void fsub (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    const FFLAS_ELT * A,
    const size_t lda,
    const FFLAS_ELT * B,
    const size_t ldb,
    FFLAS_ELT * C,
    const size_t ldc )
```

fsub : matrix subtraction.

Computes $C = A - B$.

Parameters

<i>F</i>	field
<i>M</i>	rows
<i>N</i>	cols
<i>A</i>	dense matrix of size $M \times N$
<i>lda</i>	leading dimension of A
<i>B</i>	dense matrix of size $M \times N$
<i>ldb</i>	leading dimension of B
<i>C</i>	dense matrix of size $M \times N$
<i>ldc</i>	leading dimension of C

11.1.3.286 fsubin() [3/3]

```
template INST_OR_DECL void fsubin (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    const FFLAS_ELT * B,
    const size_t ldb,
    FFLAS_ELT * C,
    const size_t ldc )
```

fsubin $C = C - B$

11.1.3.287 fadd() [8/8]

```
template INST_OR_DECL void fadd (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    const FFLAS_ELT * A,
    const size_t lda,
    const FFLAS_ELT alpha,
    const FFLAS_ELT * B,
    const size_t ldb,
    FFLAS_ELT * C,
    const size_t ldc )
```

fadd : matrix addition with scaling.

Computes $C = A + \alpha B$.

Parameters

<i>F</i>	field
<i>M</i>	rows
<i>N</i>	cols
<i>A</i>	dense matrix of size MxN
<i>lda</i>	leading dimension of A
<i>alpha</i>	some scalar
<i>B</i>	dense matrix of size MxN
<i>ldb</i>	leading dimension of B
<i>C</i>	dense matrix of size MxN
<i>ldc</i>	leading dimension of C

11.1.3.288 faddin() [5/5]

```
template INST_OR_DECL void faddin (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    const FFLAS_ELT * B,
    const size_t ldb,
    FFLAS_ELT * C,
    const size_t ldc )
```

faddin

11.1.3.289 fgemv() [17/19]

```
template INST_OR_DECL FFLAS_ELT * fgemv (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS_TRANSPOSE TransA,
    const size_t M,
    const size_t N,
```

```

const FFLAS_ELT alpha,
const FFLAS_ELT * A,
const size_t lda,
const FFLAS_ELT * X,
const size_t incX,
const FFLAS_ELT beta,
FFLAS_ELT * Y,
const size_t incY )

```

finite prime FFLAS_FIELD<FFLAS_ELT> GEneral Matrix Vector multiplication.

Computes $Y \leftarrow \alpha \text{op}(A)X + \beta Y$.

Parameters

	<i>F</i>	field
	<i>TransA</i>	if TransA==FflasTrans then $\text{op}(A) = A^t$.
	<i>M</i>	rows
	<i>N</i>	cols
	<i>alpha</i>	scalar
	<i>A</i>	dense matrix of size MxN
	<i>lda</i>	leading dimension of A
	<i>X</i>	dense vector of size N
	<i>incX</i>	stride of X
	<i>beta</i>	scalar
out	<i>Y</i>	dense vector of size M
	<i>incY</i>	stride of Y

11.1.3.290 fger() [12/12]

```

template INST_OR_DECL void fger (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    const FFLAS_ELT alpha,
    const FFLAS_ELT * x,
    const size_t incx,
    const FFLAS_ELT * y,
    const size_t incy,
    FFLAS_ELT * A,
    const size_t lda )

```

fger: rank one update of a general matrix

Computes $A \leftarrow \alpha x y^T + A$

Parameters

	<i>F</i>	field
	<i>M</i>	rows
	<i>N</i>	cols
	<i>alpha</i>	scalar
in, out	<i>A</i>	dense matrix of size MxN and leading dimension lda

Parameters

	<i>lda</i>	leading dimension of A
	<i>x</i>	dense vector of size M
	<i>incx</i>	stride of X
	<i>y</i>	dense vector of size N
	<i>incy</i>	stride of Y

11.1.3.291 ftrsv() [2/2]

```
template INST_OR_DECL void ftrsv (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS_UPLO Uplo,
    const FFLAS_TRANSPOSE TransA,
    const FFLAS_DIAG Diag,
    const size_t N,
    const FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * X,
    int incX )
```

ftrsv: TRIangular System solve with Vector Computes $X \leftarrow \text{op}(A^{-1})X$

Parameters

<i>F</i>	field
<i>X</i>	vector of size N on a field F
<i>incX</i>	stride of X
<i>A</i>	a matrix of leading dimension lda and size N
<i>lda</i>	leading dimension of A
<i>N</i>	number of rows or columns of A according to TransA
<i>TransA</i>	if TransA==FflasTrans then $\text{op}(A) = A^t$.
<i>Diag</i>	if Diag==FflasUnit then A is unit.
<i>Uplo</i>	if Uplo==FflasUpper then A is upper triangular

11.1.3.292 ftrsm() [9/9]

```
template INST_OR_DECL void ftrsm (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS_SIDE Side,
    const FFLAS_UPLO Uplo,
    const FFLAS_TRANSPOSE TransA,
    const FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    const FFLAS_ELT alpha,
    const FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * B,
    const size_t ldb )
```

ftfrm: **TR**angular **S**ystem solve with **M**atrix.

Computes $B \leftarrow \alpha \text{op}(A^{-1})B$ or $B \leftarrow \alpha B \text{op}(A^{-1})$.

Parameters

<i>F</i>	field
<i>Side</i>	if Side==FflasLeft then $B \leftarrow \alpha \text{op}(A^{-1})B$ is computed.
<i>Uplo</i>	if Uplo==FflasUpper then A is upper triangular
<i>TransA</i>	if TransA==FflasTrans then $\text{op}(A) = A^t$.
<i>Diag</i>	if Diag==FflasUnit then A is unit.
<i>M</i>	rows of B
<i>N</i>	cols of B
<i>alpha</i>	scalar
<i>A</i>	triangular invertible matrix. If Side==FflasLeft then A is $N \times N$, otherwise A is $M \times M$
<i>lda</i>	leading dim of A
<i>B</i>	matrix of size MxN
<i>ldb</i>	leading dim of B

Bug α must be non zero.

11.1.3.293 ftfrm() [3/3]

```
template INST_OR_DECL void ftfrm (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS_SIDE Side,
    const FFLAS_UPLO Uplo,
    const FFLAS_TRANSPOSE TransA,
    const FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    const FFLAS_ELT alpha,
    const FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * B,
    const size_t ldb )
```

ftfrm: **TR**angular **M**atrix **M**ultiply.

Computes $B \leftarrow \alpha \text{op}(A)B$ or $B \leftarrow \alpha B \text{op}(A)$.

Parameters

<i>F</i>	field
<i>Side</i>	if Side==FflasLeft then $B \leftarrow \alpha \text{op}(A)B$ is computed.
<i>Uplo</i>	if Uplo==FflasUpper then A is upper triangular
<i>TransA</i>	if TransA==FflasTrans then $\text{op}(A) = A^t$.
<i>Diag</i>	if Diag==FflasUnit then A is implicitly unit.
<i>M</i>	rows of B
<i>N</i>	cols of B

Parameters

<i>alpha</i>	scalar
<i>A</i>	triangular matrix. If Side==FflasLeft then A is $N \times N$, otherwise A is $M \times M$
<i>lda</i>	leading dim of A
<i>B</i>	matrix of size $M \times N$
<i>ldb</i>	leading dim of B

11.1.3.294 fgemm() [20/23]

```
template INST_OR_DECL FFLAS_ELT * fgemm (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const FFLAS_ELT alpha,
    const FFLAS_ELT * A,
    const size_t lda,
    const FFLAS_ELT * B,
    const size_t ldb,
    const FFLAS_ELT beta,
    FFLAS_ELT * C,
    const size_t ldc )
```

fgemm: Field **GE**neral **M**atrix **M**ultiply.

Computes $C = \alpha \text{op}(A) \times \text{op}(B) + \beta C$ Automatically set Winograd recursion level

Parameters

<i>F</i>	field.
<i>ta</i>	if $ta == \text{FflasTrans}$ then $\text{op}(A) = A^t$, else $\text{op}(A) = A$,
<i>tb</i>	same for matrix B
<i>m</i>	see A
<i>n</i>	see B
<i>k</i>	see A
<i>alpha</i>	scalar
<i>beta</i>	scalar
<i>A</i>	$\text{op}(A)$ is $m \times k$
<i>B</i>	$\text{op}(B)$ is $k \times n$
<i>C</i>	C is $m \times n$
<i>lda</i>	leading dimension of A
<i>ldb</i>	leading dimension of B
<i>ldc</i>	leading dimension of C
<i>w</i>	recursive levels of Winograd's algorithm are used. No argument (or -1) does auto computation of w.

Warning

α must be invertible

11.1.3.295 fgemm() [21/23]

```
template INST_OR_DECL FFLAS_ELT * fgemm (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const FFLAS_ELT alpha,
    const FFLAS_ELT * A,
    const size_t lda,
    const FFLAS_ELT * B,
    const size_t ldb,
    const FFLAS_ELT beta,
    FFLAS_ELT * C,
    const size_t ldc,
    const ParSeqHelper::Sequential seq )
```

11.1.3.296 fgemm() [22/23]

```
template INST_OR_DECL FFLAS_ELT * fgemm (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const FFLAS_ELT alpha,
    const FFLAS_ELT * A,
    const size_t lda,
    const FFLAS_ELT * B,
    const size_t ldb,
    const FFLAS_ELT beta,
    FFLAS_ELT * C,
    const size_t ldc,
    const ParSeqHelper::Parallel< CuttingStrategy::Recursive, StrategyParameter::TwoDAdaptive
> par )
```

11.1.3.297 fgemm() [23/23]

```
template INST_OR_DECL FFLAS_ELT * fgemm (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const FFLAS_ELT alpha,
```

```

    const FFLAS_ELT * A,
    const size_t lda,
    const FFLAS_ELT * B,
    const size_t ldb,
    const FFLAS_ELT beta,
    FFLAS_ELT * C,
    const size_t ldc,
    const ParSeqHelper::Parallel< CuttingStrategy::Block, StrategyParameter::Threads
> par )

```

11.1.3.298 fsquare() [6/6]

```

template INST_OR_DECL FFLAS_ELT * fsquare (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS_TRANSPOSE ta,
    const size_t n,
    const FFLAS_ELT alpha,
    const FFLAS_ELT * A,
    const size_t lda,
    const FFLAS_ELT beta,
    FFLAS_ELT * C,
    const size_t ldc )

```

fsquare: Squares a matrix.

compute $C \leftarrow \alpha \text{op}(A) \text{op}(A) + \beta C$ over a FFLAS_FIELD <FFLAS_ELT> $\mathbb{F}$ Avoid the conversion of B

Parameters

<i>ta</i>	if $ta == \text{FflasTrans}$, $\text{op}(A) = A^T$.
<i>F</i>	field
<i>n</i>	size of A
<i>alpha</i>	scalar
<i>beta</i>	scalar
<i>A</i>	dense matrix of size $n \times n$
<i>lda</i>	leading dimension of A
<i>C</i>	dense matrix of size $n \times n$
<i>ldc</i>	leading dimension of C

11.1.3.299 BlockCuts() [1/2]

```

template<class Cut = CuttingStrategy::Block, class Strat = StrategyParameter::Threads>
void BlockCuts (
    size_t & RBLOCKSIZE,
    size_t & CBLOCKSIZE,
    const size_t m,
    const size_t n,
    const size_t numthreads ) [inline]

```

11.1.3.300 BlockCuts< CuttingStrategy::Single, StrategyParameter::Threads >()

```

template<>
void BlockCuts< CuttingStrategy::Single, StrategyParameter::Threads > (

```

```

    size_t & RBLOCKSIZE,
    size_t & CBLOCKSIZE,
    const size_t m,
    const size_t n,
    const size_t numthreads ) [inline]

```

11.1.3.301 **BlockCuts< CuttingStrategy::Row, StrategyParameter::Fixed >()**

```

template<>
void BlockCuts< CuttingStrategy::Row, StrategyParameter::Fixed > (
    size_t & RBLOCKSIZE,
    size_t & CBLOCKSIZE,
    const size_t m,
    const size_t n,
    const size_t numthreads ) [inline]

```

11.1.3.302 **BlockCuts< CuttingStrategy::Row, StrategyParameter::Grain >()**

```

template<>
void BlockCuts< CuttingStrategy::Row, StrategyParameter::Grain > (
    size_t & RBLOCKSIZE,
    size_t & CBLOCKSIZE,
    const size_t m,
    const size_t n,
    const size_t grainsize ) [inline]

```

11.1.3.303 **BlockCuts< CuttingStrategy::Block, StrategyParameter::Grain >()**

```

template<>
void BlockCuts< CuttingStrategy::Block, StrategyParameter::Grain > (
    size_t & RBLOCKSIZE,
    size_t & CBLOCKSIZE,
    const size_t m,
    const size_t n,
    const size_t grainsize ) [inline]

```

11.1.3.304 **BlockCuts< CuttingStrategy::Column, StrategyParameter::Fixed >()**

```

template<>
void BlockCuts< CuttingStrategy::Column, StrategyParameter::Fixed > (
    size_t & RBLOCKSIZE,
    size_t & CBLOCKSIZE,
    const size_t m,
    const size_t n,
    const size_t numthreads ) [inline]

```

11.1.3.305 BlockCuts< CuttingStrategy::Column, StrategyParameter::Grain >()

```
template<>
void BlockCuts< CuttingStrategy::Column, StrategyParameter::Grain > (
    size_t & RBLOCKSIZE,
    size_t & CBLOCKSIZE,
    const size_t m,
    const size_t n,
    const size_t grainsize ) [inline]
```

11.1.3.306 BlockCuts< CuttingStrategy::Block, StrategyParameter::Fixed >()

```
template<>
void BlockCuts< CuttingStrategy::Block, StrategyParameter::Fixed > (
    size_t & RBLOCKSIZE,
    size_t & CBLOCKSIZE,
    const size_t m,
    const size_t n,
    const size_t numthreads ) [inline]
```

11.1.3.307 BlockCuts< CuttingStrategy::Row, StrategyParameter::Threads >()

```
template<>
void BlockCuts< CuttingStrategy::Row, StrategyParameter::Threads > (
    size_t & RBLOCKSIZE,
    size_t & CBLOCKSIZE,
    const size_t m,
    const size_t n,
    const size_t numthreads ) [inline]
```

11.1.3.308 BlockCuts< CuttingStrategy::Column, StrategyParameter::Threads >()

```
template<>
void BlockCuts< CuttingStrategy::Column, StrategyParameter::Threads > (
    size_t & RBLOCKSIZE,
    size_t & CBLOCKSIZE,
    const size_t m,
    const size_t n,
    const size_t numthreads ) [inline]
```

11.1.3.309 BlockCuts< CuttingStrategy::Block, StrategyParameter::Threads >()

```
template<>
void BlockCuts< CuttingStrategy::Block, StrategyParameter::Threads > (
    size_t & RBLOCKSIZE,
    size_t & CBLOCKSIZE,
    const size_t m,
    const size_t n,
    const size_t numthreads ) [inline]
```

11.1.3.310 BlockCuts() [2/2]

```

template<class Cut = CuttingStrategy::Block, class Param = StrategyParameter::Threads>
void BlockCuts (
    size_t & rowBlockSize,
    size_t & colBlockSize,
    size_t & lastRBS,
    size_t & lastCBS,
    size_t & changeRBS,
    size_t & changeCBS,
    size_t & numRowsBlock,
    size_t & numColBlock,
    size_t m,
    size_t n,
    const size_t numthreads ) [inline]

```

11.1.3.311 pfzero()

```

template<class Field >
void pfzero (
    const Field & F,
    size_t m,
    size_t n,
    typename Field::Element_ptr C,
    size_t BS = 0 )

```

11.1.3.312 pfrand()

```

template<class Field , class RandIter >
void pfrand (
    const Field & F,
    RandIter & G,
    size_t m,
    size_t n,
    typename Field::Element_ptr C,
    size_t BS = 0 )

```

11.1.3.313 fdot() [11/11]

```

template<class Field , class Cut , class Param >
Field::Element & fdot (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr x,
    const size_t incx,
    typename Field::ConstElement_ptr y,
    const size_t incy,
    typename Field::Element & d,
    const ParSeqHelper::Parallel< Cut, Param > par ) [inline]

```


11.1.3.314 pfgemm() [2/7]

```

template<class Field , class AlgoT , class FieldTrait >
Field::Element * pfgemm (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element * C,
    const size_t ldc,
    MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Block,
StrategyParameter::Threads > > & H )

```

11.1.3.315 pfgemm() [3/7]

```

template<class Field , class AlgoT , class FieldTrait >
Field::Element * pfgemm (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr AA,
    const size_t lda,
    const typename Field::ConstElement_ptr BB,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element * C,
    const size_t ldc,
    MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive,
StrategyParameter::ThreeDAdaptive > > & H )

```

11.1.3.316 pfgemm() [4/7]

```

template<class Field , class AlgoT , class FieldTrait >
Field::Element * pfgemm (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr AA,

```

```

    const size_t lda,
    const typename Field::ConstElement_ptr BB,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element * C,
    const size_t ldc,
    MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive,
StrategyParameter::TwoDAdaptive > > & H )

```

11.1.3.317 pfgemm() [5/7]

```

template<class Field , class AlgoT , class FieldTrait >
Field::Element * pfgemm (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr AA,
    const size_t lda,
    const typename Field::ConstElement_ptr BB,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element * C,
    const size_t ldc,
    MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive,
StrategyParameter::TwoD > > & H )

```

11.1.3.318 pfgemm() [6/7]

```

template<class Field , class AlgoT , class FieldTrait >
Field::Element_ptr pfgemm (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive,
StrategyParameter::ThreeD > > & H )

```

11.1.3.319 pfgemm() [7/7]

```
template<class Field , class AlgoT , class FieldTrait >
Field::Element * pfgemm (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive,
StrategyParameter::ThreeDInPlace > > & H )
```

11.1.3.320 fgemv() [18/19]

```
template<class Field , class AlgoT , class FieldTrait >
Field::Element_ptr fgemv (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const size_t m,
    const size_t n,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::ConstElement_ptr X,
    const size_t incX,
    const typename Field::Element beta,
    typename Field::Element_ptr Y,
    const size_t incY,
    MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive,
StrategyParameter::Threads > > & H )
```

11.1.3.321 fgemv() [19/19]

```
template<class Field , class AlgoT , class FieldTrait , class Cut >
Field::Element_ptr fgemv (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const size_t m,
    const size_t n,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::ConstElement_ptr X,
    const size_t incX,
    const typename Field::Element beta,
```

```

        typename Field::Element_ptr Y,
        const size_t incY,
        MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Row,
Cut > > & H )

```

11.1.3.322 parseArguments()

```

void parseArguments (
    int argc,
    char ** argv,
    Argument * args,
    bool printDefaults = true )

```

11.1.3.323 getArgumentValue()

```

char * getArgumentValue (
    int argc,
    char ** argv,
    int i )

```

Get the value of an argument and avoid core dump when no value was given after an argument.

Parameters

<i>argv</i>	argument value list
<i>i</i>	argument index

Returns

char* argument value

11.1.3.324 writeCommandString()

```

std::ostream & writeCommandString (
    std::ostream & os,
    Argument * args,
    const char * programName = nullptr )

```

writes the values of all arguments, preceded by the programName

11.1.3.325 WriteMatrix() [1/2]

```

template<class Field >
std::ostream & WriteMatrix (
    std::ostream & c,
    const Field & F,
    size_t m,
    size_t n,
    typename Field::ConstElement_ptr A,

```

```
size_t lda,  
FFLAS_FORMAT format,  
bool column_major ) [inline]
```

WriteMatrix: write a matrix to an output stream.

Parameters

<i>c</i>	output stream
<i>F</i>	base field
<i>m</i>	row dimension
<i>n</i>	column dimension
<i>A</i>	matrix
<i>format</i>	input format (FflasAuto, FflasDense, FflasSMS, FflasBinary)
<i>column_major</i>	whether the matrix is stored in column or row major (row by default)

11.1.3.326 preamble()

```
void preamble (
    std::ifstream & ifs,
    FFLAS_FORMAT & format ) [inline]
```

11.1.3.327 ReadMatrix() [1/2]

```
template<class Field >
Field::Element_ptr ReadMatrix (
    std::ifstream & ifs,
    Field & F,
    size_t & m,
    size_t & n,
    typename Field::Element_ptr & A,
    FFLAS_FORMAT format = FflasAuto )
```

ReadMatrix: read a matrix from an input stream.

Parameters

	<i>ifs</i>	input stream
	<i>F</i>	base field
out	<i>m</i>	row dimension
out	<i>n</i>	column dimension
out	<i>A</i>	output matrix
	<i>format</i>	input format (FflasAuto, FflasDense, FflasSMS, FflasBinary)

11.1.3.328 ReadMatrix() [2/2]

```
template<class Field >
Field::Element_ptr ReadMatrix (
    const std::string & matrix_file,
    Field & F,
    size_t & m,
    size_t & n,
    typename Field::Element_ptr & A,
    FFLAS_FORMAT format = FflasAuto ) [inline]
```

ReadMatrix: read a matrix from a file.

Parameters

	<i>matrix_file</i>	filename
	<i>F</i>	base field
out	<i>m</i>	row dimension
out	<i>n</i>	column dimension
out	<i>A</i>	output matrix
	<i>format</i>	input format (FflasAuto, FflasDense, FflasSMS, FflasBinary)

11.1.3.329 WriteMatrix() [2/2]

```
template<class Field >
void WriteMatrix (
    std::string & matrix_file,
    const Field & F,
    int m,
    int n,
    typename Field::ConstElement_ptr A,
    size_t lda,
    FFLAS_FORMAT format = FflasDense,
    bool column_major = false )
```

WriteMatrix: write a matrix to a file.

Parameters

<i>matrix_file</i>	file name
<i>F</i>	base field
<i>m</i>	row dimension
<i>n</i>	column dimension
<i>A</i>	matrix
<i>format</i>	input format (FflasAuto, FflasDense, FflasSMS, FflasBinary)
<i>column_major</i>	whether the matrix is stored in column or row major (row by default)

11.1.3.330 WritePermutation()

```
std::ostream & WritePermutation (
    std::ostream & c,
    const size_t * P,
    size_t N ) [inline]
```

WritePermutation: write a permutation matrix to an output stream.

Parameters

<i>c</i>	output stream
<i>P</i>	permutation
<i>N</i>	size of the permutation

11.1.3.331 alignable()

```
template<class Element >
bool alignable ( ) [inline]
```

11.1.3.332 alignable< Givaro::Integer * >()

```
template<>
bool alignable< Givaro::Integer * > ( ) [inline]
```

11.1.3.333 fflas_new() [5/7]

```
template<class Field >
Field::Element_ptr fflas_new (
    const Field & F,
    const size_t m,
    const Alignment align = Alignment::DEFAULT ) [inline]
```

11.1.3.334 fflas_new() [6/7]

```
template<class Field >
Field::Element_ptr fflas_new (
    const Field & F,
    const size_t m,
    const size_t n,
    const Alignment align = Alignment::DEFAULT ) [inline]
```

11.1.3.335 fflas_new() [7/7]

```
template<class Element >
Element * fflas_new (
    const size_t m,
    const Alignment align = Alignment::DEFAULT ) [inline]
```

11.1.3.336 fflas_delete() [3/4]

```
template<class Element_ptr >
void fflas_delete (
    Element_ptr A ) [inline]
```

11.1.3.337 fflas_delete() [4/4]

```
template<class Ptr , class ... Args>
void fflas_delete (
    Ptr p,
    Args ... args ) [inline]
```


11.1.3.338 prefetch()

```
void prefetch (
    const int64_t * ) [inline]
```

11.1.3.339 getTLBSize()

```
void getTLBSize (
    int & tlb ) [inline]
```

11.1.3.340 queryCacheSizes()

```
void queryCacheSizes (
    int & l1,
    int & l2,
    int & l3 ) [inline]
```

Queries and returns the cache sizes in Bytes of the L1, L2, and L3 data caches respectively

11.1.3.341 queryL1CacheSize()

```
int queryL1CacheSize ( ) [inline]
```

Returns

the size in Bytes of the L1 data cache

11.1.3.342 queryTopLevelCacheSize()

```
int queryTopLevelCacheSize ( ) [inline]
```

Returns

the size in Bytes of the L2 or L3 cache if this later is present

11.1.3.343 getSeed()

```
uint64_t getSeed ( )
```

11.2 FFLAS::_ftranspose_impl Namespace Reference

Functions

- `template<size_t bs, typename Field , typename BTSimd >`
`void not_inplace (const Field &F, const BTSimd &BTS, const size_t m, const size_t n, typename Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr B, const size_t ldb)`
- `template<size_t bs, typename Field , typename BTSimd >`
`void square_inplace (const Field &F, const BTSimd &BTS, const size_t m, typename Field::Element_ptr A, const size_t lda)`
- `template<size_t bs, typename Field , typename BTSimd >`
`void nonsquare_inplace_v1 (const Field &F, const BTSimd &BTS, const size_t m, const size_t n, typename Field::Element_ptr A)`
- `template<size_t bs, typename Field , typename BTSimd >`
`void nonsquare_inplace_v2 (const Field &F, const BTSimd &BTS, const size_t m, const size_t n, typename Field::Element_ptr A)`

11.2.1 Function Documentation

11.2.1.1 not_inplace()

```
template<size_t bs, typename Field , typename BTSimd >
void not_inplace (
    const Field & F,
    const BTSimd & BTS,
    const size_t m,
    const size_t n,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb )
```

11.2.1.2 square_inplace()

```
template<size_t bs, typename Field , typename BTSimd >
void square_inplace (
    const Field & F,
    const BTSimd & BTS,
    const size_t m,
    typename Field::Element_ptr A,
    const size_t lda )
```

11.2.1.3 nonsquare_inplace_v1()

```
template<size_t bs, typename Field , typename BTSimd >
void nonsquare_inplace_v1 (
    const Field & F,
    const BTSimd & BTS,
    const size_t m,
    const size_t n,
    typename Field::Element_ptr A )
```

11.2.1.4 nonsquare_inplace_v2()

```
template<size_t bs, typename Field , typename BTSimd >
void nonsquare_inplace_v2 (
    const Field & F,
    const BTSimd & BTS,
    const size_t m,
    const size_t n,
    typename Field::Element_ptr A )
```

11.3 FFLAS::BLAS3 Namespace Reference

Functions

- template<class Field >
void [Bini](#) (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, const typename Field::Element_ptr A, const size_t lda, const typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const size_t kmax, const size_t w, const FFLAS_BASE base, const size_t rec_level)
- template<class Field , class FieldTrait , class Strat , class Param >
[Field::Element_ptr WinoPar](#) (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::WinogradPar, FieldTrait, ParSeqHelper::Parallel< Strat, Param > > &WH)
- template<class Field , class FieldTrait >
void [Winograd](#) (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > &WH)
- template<class Field , class FieldTrait >
void [WinogradAcc_3_23](#) (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > &WH)
- template<class Field , class FieldTrait >
void [WinogradAcc_3_21](#) (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > &WH)
- template<class Field , class FieldTrait >
void [WinogradAcc_2_24](#) (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, const type-name Field::Element_ptr A, const size_t lda, const typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > &WH)
- template<class Field , class FieldTrait >
void [WinogradAcc_2_27](#) (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, const type-name Field::Element_ptr A, const size_t lda, const typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > &WH)

- `template<class Field , class FieldTrait >`
`void WinogradAcc_LR (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const MMHelper< Field, MMHelperAlgo::Winograd, Field↵ Trait > &WH)`
- `template<class Field , class FieldTrait >`
`void WinogradAcc_R_S (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, const type-
name Field::Element_ptr A, const size_t lda, typename Field::Element_ptr B, const size_t ldb, const type-
name Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const MMHelper< Field,
MMHelperAlgo::Winograd, FieldTrait > &WH)`
- `template<class Field , class FieldTrait >`
`void WinogradAcc_L_S (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::Element_ptr A, const size_t lda, const typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > &WH)`
- `template<class Field , class FieldTrait >`
`void Winograd_LR_S (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const MMHelper< Field, MMHelperAlgo::Winograd, Field↵ Trait > &WH)`
- `template<class Field , class FieldTrait >`
`void Winograd_L_S (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::Element_ptr A, const size_t lda, const typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > &WH)`
- `template<class Field , class FieldTrait >`
`void Winograd_R_S (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, const typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr B, const size_t ldb, const type-
name Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const MMHelper< Field,
MMHelperAlgo::Winograd, FieldTrait > &WH)`

11.3.1 Function Documentation

11.3.1.1 Bini()

```
template<class Field >
void Bini (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    const typename Field::Element_ptr A,
    const size_t lda,
    const typename Field::Element_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
```

```

typename Field::Element_ptr C,
const size_t ldc,
const size_t kmax,
const size_t w,
const FFLAS_BASE base,
const size_t rec_level ) [inline]

```

11.3.1.2 WinoPar()

```

template<class Field , class FieldTrait , class Strat , class Param >
Field::Element_ptr WinoPar (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::WinogradPar, FieldTrait, ParSeqHelper::Parallel<
Strat, Param > > & WH ) [inline]

```

11.3.1.3 Winograd()

```

template<class Field , class FieldTrait >
void Winograd (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & WH ) [inline]

```

11.3.1.4 WinogradAcc_3_23()

```

template<class Field , class FieldTrait >
void WinogradAcc_3_23 (
    const Field & F,

```

```

const FFLAS_TRANSPOSE ta,
const FFLAS_TRANSPOSE tb,
const size_t mr,
const size_t nr,
const size_t kr,
const typename Field::Element alpha,
typename Field::ConstElement_ptr A,
const size_t lda,
typename Field::ConstElement_ptr B,
const size_t ldb,
const typename Field::Element beta,
typename Field::Element_ptr C,
const size_t ldc,
MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & WH ) [inline]

```

11.3.1.5 WinogradAcc_3_21()

```

template<class Field , class FieldTrait >
void WinogradAcc_3_21 (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & WH ) [inline]

```

11.3.1.6 WinogradAcc_2_24()

```

template<class Field , class FieldTrait >
void WinogradAcc_2_24 (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    const typename Field::Element_ptr A,
    const size_t lda,
    const typename Field::Element_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & WH ) [inline]

```

11.3.1.7 WinogradAcc_2_27()

```
template<class Field , class FieldTrait >
void WinogradAcc_2_27 (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    const typename Field::Element_ptr A,
    const size_t lda,
    const typename Field::Element_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & WH ) [inline]
```

11.3.1.8 WinogradAcc_LR()

```
template<class Field , class FieldTrait >
void WinogradAcc_LR (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    const MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & WH ) [inline]
```

11.3.1.9 WinogradAcc_R_S()

```
template<class Field , class FieldTrait >
void WinogradAcc_R_S (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    const typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
```

```

const size_t ldb,
const typename Field::Element beta,
typename Field::Element_ptr C,
const size_t ldc,
const MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & WH ) [inline]

```

11.3.1.10 WinogradAcc_L_S()

```

template<class Field , class FieldTrait >
void WinogradAcc_L_S (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    const typename Field::Element_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    const MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & WH ) [inline]

```

11.3.1.11 Winograd_LR_S()

```

template<class Field , class FieldTrait >
void Winograd_LR_S (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    const MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & WH ) [inline]

```

11.3.1.12 Winograd_L_S()

```

template<class Field , class FieldTrait >
void Winograd_L_S (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,

```



```

const size_t mr,
const size_t nr,
const size_t kr,
const typename Field::Element alpha,
typename Field::Element_ptr A,
const size_t lda,
const typename Field::Element_ptr B,
const size_t ldb,
const typename Field::Element beta,
typename Field::Element_ptr C,
const size_t ldc,
const MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & WH ) [inline]

```

11.3.1.13 Winograd_R_S()

```

template<class Field , class FieldTrait >
void Winograd_R_S (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    const typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    const MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > & WH ) [inline]

```

11.4 FFLAS::csr_hyb_details Namespace Reference

Data Structures

- struct [Coo](#)
- struct [Info](#)

11.5 FFLAS::CuttingStrategy Namespace Reference

Data Structures

- struct [Block](#)
- struct [Column](#)
- struct [Recursive](#)
- struct [Row](#)
- struct [Single](#)

Typedefs

- typedef [Row](#) [RNSModulus](#)

11.5.1 Typedef Documentation

11.5.1.1 RNSModulus

typedef [Row](#) [RNSModulus](#)

11.6 FFLAS::details Namespace Reference

Functions

- template<class [Field](#) , bool ADD>
std::enable_if< [FFLAS::support_simd_add](#)< typename [Field::Element](#) >::value, void >::type [fadd](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t inca, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc, [FieldCategories::ModularTag](#))
- template<class [Field](#) , bool ADD>
std::enable_if<![FFLAS::support_simd_add](#)< typename [Field::Element](#) >::value, void >::type [fadd](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t inca, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc, [FieldCategories::ModularTag](#))
- template<class [Field](#) , bool ADD>
void [fadd](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t inca, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc, [FieldCategories::GenericTag](#))
- template<class [Field](#) , bool ADD>
std::enable_if<![FFLAS::support_simd_add](#)< typename [Field::Element](#) >::value, void >::type [fadd](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t inca, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc, [FieldCategories::UnparametricTag](#))
- template<class [Field](#) , bool ADD>
std::enable_if< [FFLAS::support_simd_add](#)< typename [Field::Element](#) >::value, void >::type [fadd](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t inca, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc, [FieldCategories::UnparametricTag](#))
- template<class [Field](#) >
std::enable_if< [FFLAS::support_fast_mod](#)< typename [Field::Element](#) >::value, void >::type [faxpy](#) (const [Field](#) &F, const size_t N, const typename [Field::Element](#) a, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::Element_ptr](#) Y, const size_t incY, [FieldCategories::ModularTag](#))
- template<class [Field](#) , class FC >
void [faxpy](#) (const [Field](#) &F, const size_t N, const typename [Field::Element](#) a, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::Element_ptr](#) Y, const size_t incY, FC)
- template<class [Field](#) >
std::enable_if< [FFLAS::support_fast_mod](#)< typename [Field::Element](#) >::value, void >::type [freduce](#) (const [Field](#) &F, const size_t m, typename [Field::Element_ptr](#) A, const size_t incX, [FieldCategories::ModularTag](#))
- template<class [Field](#) >
std::enable_if< [FFLAS::support_fast_mod](#)< typename [Field::Element](#) >::value, void >::type [freduce](#) (const [Field](#) &F, const size_t m, typename [Field::ConstElement_ptr](#) B, const size_t incY, typename [Field::Element_ptr](#) A, const size_t incX, [FieldCategories::ModularTag](#))

- template<class [Field](#) , class FC >
void [freduce](#) (const [Field](#) &F, const size_t m, typename [Field::Element_ptr](#) A, const size_t incX, FC)
- template<class [Field](#) , class FC >
void [freduce](#) (const [Field](#) &F, const size_t m, typename [Field::ConstElement_ptr](#) B, const size_t incY, typename [Field::Element_ptr](#) A, const size_t incX, FC)
- template<class [Field](#) >
std::enable_if< [FFLAS::support_fast_mod](#)< typename [Field::Element](#) >::value, void >::type [fscalin](#) (const [Field](#) &F, const size_t N, const typename [Field::Element](#) a, typename [Field::Element_ptr](#) X, const size_t incX, [FieldCategories::ModularTag](#))
- template<class [Field](#) >
std::enable_if< [FFLAS::support_fast_mod](#)< typename [Field::Element](#) >::value, void >::type [fscal](#) (const [Field](#) &F, const size_t N, const typename [Field::Element](#) a, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::Element_ptr](#) Y, const size_t incY, [FieldCategories::ModularTag](#))
- template<class [Field](#) , class FC >
void [fscalin](#) (const [Field](#) &F, const size_t n, const typename [Field::Element](#) a, typename [Field::Element_ptr](#) X, const size_t incX, FC)
- template<class [Field](#) , class FC >
void [fscal](#) (const [Field](#) &F, const size_t N, const typename [Field::Element](#) a, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::Element_ptr](#) Y, const size_t incY, FC)
- template<enum [number_kind](#) K>
void [igebb44](#) (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)
- template<enum [number_kind](#) K>
void [igebb24](#) (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)
- template<enum [number_kind](#) K>
void [igebb14](#) (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)
- template<enum [number_kind](#) K>
void [igebb41](#) (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)
- template<enum [number_kind](#) K>
void [igebb21](#) (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)
- template<enum [number_kind](#) K>
void [igebb11](#) (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)
- template<enum [number_kind](#) K>
void [igebp](#) (size_t rows, size_t cols, size_t depth, const int64_t alpha, const int64_t *blockA, size_t lda, const int64_t *blockB, size_t ldb, int64_t *C, size_t ldc)
- template<size_t k, bool transpose>
void [pack_lhs](#) (int64_t *XX, const int64_t *X, size_t ldx, size_t rows, size_t cols)
- template<size_t k, bool transpose>
void [pack_rhs](#) (int64_t *XX, const int64_t *X, size_t ldx, size_t rows, size_t cols)
- void [gebp](#) (size_t rows, size_t cols, size_t depth, int64_t *C, size_t ldc, const int64_t *blockA, size_t lda, const int64_t *BlockB, size_t ldb, int64_t *BlockW)
- void [BlockingFactor](#) (size_t &m, size_t &n, size_t &k)

11.6.1 Function Documentation

11.6.1.1 fadd() [1/5]

```
template<class Field , bool ADD>
std::enable_if< FFLAS::support\_simd\_add< typename Field::Element >::value, void >::type fadd (
    const Field & F,
```

```

    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t inca,
    typename Field::ConstElement_ptr B,
    const size_t incb,
    typename Field::Element_ptr C,
    const size_t incc,
    FieldCategories::ModularTag )

```

11.6.1.2 fadd() [2/5]

```

template<class Field , bool ADD>
std::enable_if<!FFLAS::support_simd_add< typenameField::Element >::value, void >::type fadd (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t inca,
    typename Field::ConstElement_ptr B,
    const size_t incb,
    typename Field::Element_ptr C,
    const size_t incc,
    FieldCategories::ModularTag )

```

11.6.1.3 fadd() [3/5]

```

template<class Field , bool ADD>
void fadd (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t inca,
    typename Field::ConstElement_ptr B,
    const size_t incb,
    typename Field::Element_ptr C,
    const size_t incc,
    FieldCategories::GenericTag )

```

11.6.1.4 fadd() [4/5]

```

template<class Field , bool ADD>
std::enable_if<!FFLAS::support_simd_add< typenameField::Element >::value, void >::type fadd (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t inca,
    typename Field::ConstElement_ptr B,
    const size_t incb,
    typename Field::Element_ptr C,
    const size_t incc,
    FieldCategories::UnparametricTag ) [inline]

```

11.6.1.5 fadd() [5/5]

```
template<class Field , bool ADD>
std::enable_if< FFLAS::support_simd_add< typenameField::Element >::value, void >::type fadd (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t inca,
    typename Field::ConstElement_ptr B,
    const size_t incb,
    typename Field::Element_ptr C,
    const size_t incc,
    FieldCategories::UnparametricTag ) [inline]
```

11.6.1.6 faxpy() [1/2]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type faxpy
(
    const Field & F,
    const size_t N,
    const typename Field::Element a,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    typename Field::Element_ptr Y,
    const size_t incY,
    FieldCategories::ModularTag ) [inline]
```

11.6.1.7 faxpy() [2/2]

```
template<class Field , class FC >
void faxpy (
    const Field & F,
    const size_t N,
    const typename Field::Element a,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    typename Field::Element_ptr Y,
    const size_t incY,
    FC ) [inline]
```

11.6.1.8 freduce() [1/4]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type freduce
(
    const Field & F,
    const size_t m,
    typename Field::Element_ptr A,
    const size_t incX,
    FieldCategories::ModularTag ) [inline]
```

11.6.1.9 freduce() [2/4]

```

template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type freduce
(
    const Field & F,
    const size_t m,
    typename Field::ConstElement_ptr B,
    const size_t incY,
    typename Field::Element_ptr A,
    const size_t incX,
    FieldCategories::ModularTag ) [inline]

```

11.6.1.10 freduce() [3/4]

```

template<class Field , class FC >
void freduce (
    const Field & F,
    const size_t m,
    typename Field::Element_ptr A,
    const size_t incX,
    FC ) [inline]

```

11.6.1.11 freduce() [4/4]

```

template<class Field , class FC >
void freduce (
    const Field & F,
    const size_t m,
    typename Field::ConstElement_ptr B,
    const size_t incY,
    typename Field::Element_ptr A,
    const size_t incX,
    FC ) [inline]

```

11.6.1.12 fscaln() [1/2]

```

template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type fscaln
(
    const Field & F,
    const size_t N,
    const typename Field::Element a,
    typename Field::Element_ptr X,
    const size_t incX,
    FieldCategories::ModularTag ) [inline]

```

11.6.1.13 fscal() [1/2]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type fscal
(
    const Field & F,
    const size_t N,
    const typename Field::Element a,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    typename Field::Element_ptr Y,
    const size_t incY,
    FieldCategories::ModularTag ) [inline]
```

11.6.1.14 fscaln() [2/2]

```
template<class Field , class FC >
void fscaln (
    const Field & F,
    const size_t n,
    const typename Field::Element a,
    typename Field::Element_ptr X,
    const size_t incX,
    FC ) [inline]
```

11.6.1.15 fscal() [2/2]

```
template<class Field , class FC >
void fscal (
    const Field & F,
    const size_t N,
    const typename Field::Element a,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    typename Field::Element_ptr Y,
    const size_t incY,
    FC ) [inline]
```

11.6.1.16 igebb44()

```
template<enum number_kind K>
void igebb44 (
    size_t i,
    size_t j,
    size_t depth,
    size_t pdeth,
    const int64_t alpha,
    const int64_t * blA,
    const int64_t * blB,
    int64_t * C,
    size_t ldc ) [inline]
```

11.6.1.17 igebb24()

```
template<enum number_kind K>
void igebb24 (
    size_t i,
    size_t j,
    size_t depth,
    size_t pdeth,
    const int64_t alpha,
    const int64_t * blA,
    const int64_t * blB,
    int64_t * C,
    size_t ldc ) [inline]
```

11.6.1.18 igebb14()

```
template<enum number_kind K>
void igebb14 (
    size_t i,
    size_t j,
    size_t depth,
    size_t pdeth,
    const int64_t alpha,
    const int64_t * blA,
    const int64_t * blB,
    int64_t * C,
    size_t ldc ) [inline]
```

11.6.1.19 igebb41()

```
template<enum number_kind K>
void igebb41 (
    size_t i,
    size_t j,
    size_t depth,
    size_t pdeth,
    const int64_t alpha,
    const int64_t * blA,
    const int64_t * blB,
    int64_t * C,
    size_t ldc ) [inline]
```

bug ,B_0 dans VEC_MADD_32 ?

bug ,B_0 dans VEC_MADD_32 ?

11.6.1.20 igebb21()

```
template<enum number_kind K>
void igebb21 (
    size_t i,
    size_t j,
    size_t depth,
```



```

    size_t pdeth,
    const int64_t alpha,
    const int64_t * blA,
    const int64_t * blB,
    int64_t * C,
    size_t ldc ) [inline]

```

11.6.1.21 igebb11()

```

template<enum number_kind K>
void igebb11 (
    size_t i,
    size_t j,
    size_t depth,
    size_t pdeth,
    const int64_t alpha,
    const int64_t * blA,
    const int64_t * blB,
    int64_t * C,
    size_t ldc ) [inline]

```

11.6.1.22 igebp()

```

template<enum number_kind K>
void igebp (
    size_t rows,
    size_t cols,
    size_t depth,
    const int64_t alpha,
    const int64_t * blockA,
    size_t lda,
    const int64_t * blockB,
    size_t ldb,
    int64_t * C,
    size_t ldc )

```

11.6.1.23 pack_lhs()

```

template<size_t k, bool transpose>
void pack_lhs (
    int64_t * XX,
    const int64_t * X,
    size_t ldx,
    size_t rows,
    size_t cols )

```

Bug this is fassign

Bug this is fassign

Bug this is fassign

Bug this is fassign

11.6.1.24 pack_rhs()

```
template<size_t k, bool transpose>
void pack_rhs (
    int64_t * XX,
    const int64_t * X,
    size_t ldx,
    size_t rows,
    size_t cols )
```

Bug this is fassign

Bug this is fassign

Bug this is fassign

Bug this is fassign

11.6.1.25 gebp()

```
void gebp (
    size_t rows,
    size_t cols,
    size_t depth,
    int64_t * C,
    size_t ldc,
    const int64_t * blockA,
    size_t lda,
    const int64_t * BlockB,
    size_t ldb,
    int64_t * BlockW )
```

11.6.1.26 BlockingFactor()

```
void BlockingFactor (
    size_t & m,
    size_t & n,
    size_t & k ) [inline]
```

11.7 FFLAS::details_spmv Namespace Reference

Data Structures

- struct [Coo](#)

11.8 FFLAS::ElementCategories Namespace Reference

Data Structures

- struct [ArbitraryPrecIntTag](#)
Arbitrary precision integers: GMP.
- struct [FixedPrecIntTag](#)
Fixed precision integers above machine precision: Givaro::reclnt.
- struct [GenericTag](#)
default is generic
- struct [MachineFloatTag](#)
float or double
- struct [MachineIntTag](#)
short, int, long, long long, and unsigned variants
- struct [RNSElementTag](#)
Representation in a Residue Number System.

11.9 FFLAS::FieldCategories Namespace Reference

Traits and categories will need to be placed in a proper file later.

Data Structures

- struct [GenericTag](#)
generic ring.
- struct [ModularTag](#)
This is a modular field like e.g. `Modular<T>` or `ModularBalanced<T>`
- struct [UnparametricTag](#)
If the field uses a representation with infix operators.

11.9.1 Detailed Description

Traits and categories will need to be placed in a proper file later.

11.10 FFLAS::MMHelperAlgo Namespace Reference

Data Structures

- struct [Auto](#)
- struct [Bini](#)
- struct [Classic](#)
- struct [DivideAndConquer](#)
- struct [Winograd](#)
- struct [WinogradPar](#)

11.11 FFLAS::ModeCategories Namespace Reference

Specifies the mode of action for an algorithm w.r.t.

Data Structures

- struct [ConvertTo](#)
Force conversion to appropriate element type of ElementCategory T.
- struct [DefaultBoundedTag](#)
Use standard field operations, but keeps track of bounds on input and output.
- struct [DefaultTag](#)
No specific mode of action: use standard field operations.
- struct [DelayedTag](#)
Performs field operations with delayed mod reductions. Ensures result is reduced.
- struct [LazyTag](#)
Performs field operations with delayed mod only when necessary. Result may not be reduced.

11.11.1 Detailed Description

Specifies the mode of action for an algorithm w.r.t.

its field

11.12 FFLAS::ParSeqHelper Namespace Reference

[ParSeqHelper](#) for both fgemm and ftrsm.

Data Structures

- struct [Compose](#)
- struct [Parallel](#)
- struct [Sequential](#)

11.12.1 Detailed Description

[ParSeqHelper](#) for both fgemm and ftrsm.

[ParSeqHelper](#) for both fgemm and ftrsm

11.13 FFLAS::Protected Namespace Reference

Data Structures

- class [AreEqual](#)
- class [AreEqual< X, X >](#)
- class [ftrmmLeftLowerNoTransNonUnit](#)
- class [ftrmmLeftLowerNoTransUnit](#)
- class [ftrmmLeftLowerTransNonUnit](#)
- class [ftrmmLeftLowerTransUnit](#)
- class [ftrmmLeftUpperNoTransNonUnit](#)
- class [ftrmmLeftUpperNoTransUnit](#)
- class [ftrmmLeftUpperTransNonUnit](#)
- class [ftrmmLeftUpperTransUnit](#)
- class [ftrmmRightLowerNoTransNonUnit](#)
- class [ftrmmRightLowerNoTransUnit](#)
- class [ftrmmRightLowerTransNonUnit](#)
- class [ftrmmRightLowerTransUnit](#)
- class [ftrmmRightUpperNoTransNonUnit](#)
- class [ftrmmRightUpperNoTransUnit](#)
- class [ftrmmRightUpperTransNonUnit](#)
- class [ftrmmRightUpperTransUnit](#)
- class [ftrsmLeftLowerNoTransNonUnit](#)
- class [ftrsmLeftLowerNoTransUnit](#)
- class [ftrsmLeftLowerTransNonUnit](#)
- class [ftrsmLeftLowerTransUnit](#)
- class [ftrsmLeftUpperNoTransNonUnit](#)

Computes the maximal size for delaying the modular reduction in a triangular system resolution.

- class [ftrsmLeftUpperNoTransUnit](#)
- class [ftrsmLeftUpperTransNonUnit](#)
- class [ftrsmLeftUpperTransUnit](#)
- class [ftrsmRightLowerNoTransNonUnit](#)
- class [ftrsmRightLowerNoTransUnit](#)
- class [ftrsmRightLowerTransNonUnit](#)
- class [ftrsmRightLowerTransUnit](#)
- class [ftrsmRightUpperNoTransNonUnit](#)
- class [ftrsmRightUpperNoTransUnit](#)
- class [ftrsmRightUpperTransNonUnit](#)
- class [ftrsmRightUpperTransUnit](#)

Functions

- template<class [Field](#) >
double [computeFactorClassic](#) (const [Field](#) &F)
- template<> double [computeFactorClassic](#) (const [Givaro::ModularBalanced](#)< double > &F)
- template<> double [computeFactorClassic](#) (const [Givaro::ModularBalanced](#)< float > &F)
- template<class [Field](#) >
size_t [DotProdBoundClassic](#) (const [Field](#) &F, const typename [Field::Element](#) &beta)
- template<class [Field](#) >
size_t [TRSMBound](#) (const [Field](#) &)

TRSMBound.
- template<class [Element](#) >
size_t [TRSMBound](#) (const [Givaro::Modular](#)< [Element](#) > &F)

Specialization for positive modular representation over float.

- `template<class Element >`
`size_t TRSMBound (const Givaro::ModularBalanced< Element > &F)`

Specialization for balanced modular representation over double.

- `template<class NewField , class Field , class FieldMode >`
`Field::Element_ptr fgemm_convert (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, FieldMode > &H)`
- `template<class Field , class Element , class AlgoT , class ParSeqTrait >`
`bool NeedPreAddReduction (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > &WH)`
- `template<class Field , class Element , class AlgoT , class ModeT , class ParSeqTrait >`
`bool NeedPreAddReduction (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, MMHelper< Field, AlgoT, ModeT, ParSeqTrait > &WH)`
- `template<class Field , class Element , class AlgoT , class ParSeqTrait >`
`bool NeedPreSubReduction (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > &WH)`
- `template<class Field , class Element , class AlgoT , class ModeT , class ParSeqTrait >`
`bool NeedPreSubReduction (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, MMHelper< Field, AlgoT, ModeT, ParSeqTrait > &WH)`
- `template<class Field , class Element , class AlgoT , class ParSeqTrait >`
`bool NeedDoublePreAddReduction (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, Element beta, MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > &WH)`
- `template<class Field , class Element , class AlgoT , class ModeT , class ParSeqTrait >`
`bool NeedDoublePreAddReduction (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, Element beta, MMHelper< Field, AlgoT, ModeT, ParSeqTrait > &WH)`
- `template<class Field , class AlgoT , class ParSeqTrait >`
`void ScalAndReduce (const Field &F, const size_t N, const typename Field::Element alpha, typename Field::Element_ptr X, const size_t incX, const MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > &H)`
- `template<class Field , class AlgoT , class ParSeqTrait >`
`void ScalAndReduce (const Field &F, const size_t M, const size_t N, const typename Field::Element alpha, typename Field::Element_ptr A, const size_t lda, const MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > &H)`
- `template<class Field >`
`Field::Element_ptr fsquareCommon (const Field &F, const FFLAS_TRANSPOSE ta, const size_t n, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc)`
- `template<class Field >`
`int WinogradThreshold (const Field &F)`
Computes the number of recursive levels to perform.
- `template<> int WinogradThreshold (const Givaro::Modular< float > &F)`
- `template<> int WinogradThreshold (const Givaro::ModularBalanced< double > &F)`
- `template<> int WinogradThreshold (const Givaro::ModularBalanced< float > &F)`
- `template<class Field >`
`int WinogradSteps (const Field &F, const size_t &m)`
Computes the number of recursive levels to perform.
- `template<class Field , class FieldMode >`
`void DynamicPeeling (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda,`

- typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldMode](#) > &H, const typename [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldMode](#) >::DelayedField::Element Cmin, const typename [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldMode](#) >::DelayedField::Element Cmax)
- `template<class Field , class FieldMode >`
`void DynamicPeeling2 (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, FieldMode > &H, const typename MMHelper< Field, MMHelperAlgo::Winograd, FieldMode >::DelayedField::Element Cmin, const typename MMHelper< Field, MMHelperAlgo::Winograd, FieldMode >::DelayedField::Element Cmax)`
 - `template<class Field , class FieldMode >`
`void WinogradCalc (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, FieldMode > &H)`
 - `template<typename FloatElement , class Field >`
`Field::Element_ptr fgemv_convert (const Field &F, const FFLAS_TRANSPOSE ta, const size_t M, const size_t N, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr X, const size_t incX, const typename Field::Element beta, typename Field::Element_ptr Y, const size_t incY)`
 - `template<class FloatElement , class Field >`
`void fger\_convert (const Field &F, const size_t M, const size_t N, const typename Field::Element alpha, typename Field::ConstElement\_ptr x, const size_t incx, typename Field::ConstElement\_ptr y, const size_t incy, typename Field::Element\_ptr A, const size_t lda)`
 - `template<class NewField , class Field , class FieldMode >`
`Field::Element_ptr fsyrk_convert (const Field &F, const FFLAS_UPLO UpLo, const FFLAS_TRANSPOSE trans, const size_t N, const size_t K, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Classic, FieldMode > &H)`
 - `template<class Field , class AlgoT , class ParSeqTrait >`
`void ScaLAndReduce (const Field &F, const FFLAS\_UPLO UpLo, const size_t N, const typename Field::Element alpha, typename Field::Element\_ptr A, const size_t lda, const MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > &H)`
 - `template<class Field , class Element , class AlgoT , class ParSeqTrait >`
`bool NeedPreScaLReduction (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, const Element &x, MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > &WH)`
 - `template<class Field , class Element , class AlgoT , class ModeT , class ParSeqTrait >`
`bool NeedPreScaLReduction (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, const Element &x, MMHelper< Field, AlgoT, ModeT, ParSeqTrait > &WH)`
 - `template<class Field , class Element , class AlgoT , class ModeT , class ParSeqTrait >`
`bool NeedPreAxyReduction (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, const Element &x, MMHelper< Field, AlgoT, ModeT, ParSeqTrait > &WH)`
 - `template<class Field , class Element , class AlgoT , class ModeT , class ParSeqTrait >`
`bool NeedPreAxyReduction (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, const Element &x, MMHelper< Field, AlgoT, ModeT, ParSeqTrait > &WH)`
 - `template<class DFE >`
`size_t min\_types (const DFE &k)`
 - `template<> size_t min\_types (const Reclnt::rint< 6 > &k)`
 - `template<> size_t min\_types (const Reclnt::rint< 7 > &k)`
 - `template<> size_t min\_types (const Reclnt::rint< 8 > &k)`
 - `template<> size_t min\_types (const Reclnt::rint< 9 > &k)`
 - `template<> size_t min\_types (const Reclnt::rint< 10 > &k)`

- `template<> size_t min_types` (const Givaro::Integer &k)
- `template<class T >`
`bool unfit` (T x)
- `template<> bool unfit` (int64_t x)
- `template<size_t K>`
`bool unfit` (Reclnt::rint< K > x)
- `template<> bool unfit` (Reclnt::rint< 6 > x)
- `template<enum FFLAS_TRANSPOSE tA, enum FFLAS_TRANSPOSE tB>`
`void igemm_colmajor` (size_t rows, size_t cols, size_t depth, const int64_t alpha, const int64_t *A, size_t lda, const int64_t *B, size_t ldb, int64_t *C, size_t ldc)
- `template<enum FFLAS_TRANSPOSE tA, enum FFLAS_TRANSPOSE tB, enum number_kind alpha_kind>`
`void igemm_colmajor` (size_t rows, size_t cols, size_t depth, const int64_t alpha, const int64_t *A, size_t lda, const int64_t *B, size_t ldb, int64_t *C, size_t ldc)
- `void igemm` (const enum FFLAS_TRANSPOSE TransA, const enum FFLAS_TRANSPOSE TransB, size_t rows, size_t cols, size_t depth, const int64_t alpha, const int64_t *A, size_t lda, const int64_t *B, size_t ldb, const int64_t beta, int64_t *C, size_t ldc)
- `template<class Field >`
`void MatF2MatD_Triangular` (const Field &F, Givaro::DoubleDomain::Element_ptr S, const size_t lds, typename Field::ConstElement_ptr const E, const size_t lde, const size_t m, const size_t n)
- `template<class Field >`
`void MatF2MatFI_Triangular` (const Field &F, Givaro::FloatDomain::Element_ptr S, const size_t lds, typename Field::ConstElement_ptr const E, const size_t lde, const size_t m, const size_t n)

11.13.1 Function Documentation

11.13.1.1 computeFactorClassic() [1/3]

```
template<class Field >
double computeFactorClassic (
    const Field & F ) [inline]
```

11.13.1.2 computeFactorClassic() [2/3]

```
template<>
double computeFactorClassic (
    const Givaro::ModularBalanced< double > & F ) [inline]
```

11.13.1.3 computeFactorClassic() [3/3]

```
template<>
double computeFactorClassic (
    const Givaro::ModularBalanced< float > & F ) [inline]
```

11.13.1.4 DotProdBoundClassic()

```
template<class Field >
size_t DotProdBoundClassic (
    const Field & F,
    const typename Field::Element & beta ) [inline]
```


11.13.1.5 TRSMBound() [1/3]

```
template<class Field >
size_t TRSMBound (
    const Field & ) [inline]
```

TRSMBound.

computes the maximal size for delaying the modular reduction in a triangular system resolution

This is the default version over an arbitrary field. It is currently never used (the recursive algorithm is run until $n=1$ in this case)

Parameters

F	Finite Field/Ring of the computation

11.13.1.6 TRSMBound() [2/3]

```
template<class Element >
size_t TRSMBound (
    const Givaro::Modular< Element > & F ) [inline]
```

Specialization for positive modular representation over float.

Computes $n_{\max}$ s.t. $(p-1)/2 * (p^{\{n_{\max}-1\}} + (p-2)^{\{n_{\max}-1\}}) < 2^{24}$ @pbi See [Dumas Giorgi Pernet 06, arXiv:cs/0601133]

11.13.1.7 TRSMBound() [3/3]

```
template<class Element >
size_t TRSMBound (
    const Givaro::ModularBalanced< Element > & F ) [inline]
```

Specialization for balanced modular representation over double.

Computes $n_{\max}$ s.t. $(p-1)/2 * (((p+1)/2)^{\{n_{\max}-1\}}) < 2^{53}$

Bibliography • Dumas Giorgi Pernet 06, arXiv:cs/0601133

11.13.1.8 fgemm_convert()

```
template<class NewField , class Field , class FieldMode >
Field::Element_ptr fgemm_convert (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, FieldMode > & H ) [inline]
```

11.13.1.9 NeedPreAddReduction() [1/2]

```
template<class Field , class Element , class AlgoT , class ParSeqTrait >
bool NeedPreAddReduction (
    Element & Outmin,
    Element & Outmax,
    Element & Op1min,
    Element & Op1max,
    Element & Op2min,
    Element & Op2max,
    MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > & WH ) [inline]
```

11.13.1.10 NeedPreAddReduction() [2/2]

```
template<class Field , class Element , class AlgoT , class ModeT , class ParSeqTrait >
bool NeedPreAddReduction (
    Element & Outmin,
    Element & Outmax,
    Element & Op1min,
    Element & Op1max,
    Element & Op2min,
    Element & Op2max,
    MMHelper< Field, AlgoT, ModeT, ParSeqTrait > & WH ) [inline]
```

11.13.1.11 NeedPreSubReduction() [1/2]

```
template<class Field , class Element , class AlgoT , class ParSeqTrait >
bool NeedPreSubReduction (
    Element & Outmin,
    Element & Outmax,
    Element & Op1min,
    Element & Op1max,
    Element & Op2min,
    Element & Op2max,
    MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > & WH ) [inline]
```

11.13.1.12 NeedPreSubReduction() [2/2]

```
template<class Field , class Element , class AlgoT , class ModeT , class ParSeqTrait >
bool NeedPreSubReduction (
    Element & Outmin,
    Element & Outmax,
    Element & Op1min,
    Element & Op1max,
    Element & Op2min,
    Element & Op2max,
    MMHelper< Field, AlgoT, ModeT, ParSeqTrait > & WH ) [inline]
```

11.13.1.13 NeedDoublePreAddReduction() [1/2]

```
template<class Field , class Element , class AlgoT , class ParSeqTrait >
bool NeedDoublePreAddReduction (
    Element & Outmin,
    Element & Outmax,
    Element & Op1min,
    Element & Op1max,
    Element & Op2min,
    Element & Op2max,
    Element beta,
    MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > & WH ) [inline]
```

11.13.1.14 NeedDoublePreAddReduction() [2/2]

```
template<class Field , class Element , class AlgoT , class ModeT , class ParSeqTrait >
bool NeedDoublePreAddReduction (
    Element & Outmin,
    Element & Outmax,
    Element & Op1min,
    Element & Op1max,
    Element & Op2min,
    Element & Op2max,
    Element beta,
    MMHelper< Field, AlgoT, ModeT, ParSeqTrait > & WH ) [inline]
```

11.13.1.15 ScalAndReduce() [1/3]

```
template<class Field , class AlgoT , class ParSeqTrait >
void ScalAndReduce (
    const Field & F,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::Element_ptr X,
    const size_t incX,
    const MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > & H ) [inline]
```

11.13.1.16 ScalAndReduce() [2/3]

```
template<class Field , class AlgoT , class ParSeqTrait >
void ScalAndReduce (
    const Field & F,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    const MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > & H ) [inline]
```

11.13.1.17 fsquareCommon()

```
template<class Field >
Field::Element_ptr fsquareCommon (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const size_t n,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc ) [inline]
```

11.13.1.18 WinogradThreshold() [1/4]

```
template<class Field >
int WinogradThreshold (
    const Field & F ) [inline]
```

Computes the number of recursive levels to perform.

Parameters

<i>m</i>	the common dimension in the product AxB

11.13.1.19 WinogradThreshold() [2/4]

```
template<>
int WinogradThreshold (
    const Givaro::Modular< float > & F ) [inline]
```

11.13.1.20 WinogradThreshold() [3/4]

```
template<>
int WinogradThreshold (
    const Givaro::ModularBalanced< double > & F ) [inline]
```

11.13.1.21 WinogradThreshold() [4/4]

```
template<>
int WinogradThreshold (
    const Givaro::ModularBalanced< float > & F ) [inline]
```

11.13.1.22 WinogradSteps()

```
template<class Field >
int WinogradSteps (
    const Field & F,
    const size_t & m ) [inline]
```

Computes the number of recursive levels to perform.

Parameters

<i>m</i>	the common dimension in the product AxB

11.13.1.23 DynamicPeeling()

```
template<class Field , class FieldMode >
void DynamicPeeling (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, FieldMode > & H,
    const typename MMHelper< Field, MMHelperAlgo::Winograd, FieldMode >::Delayed←
Field::Element Cmin,
    const typename MMHelper< Field, MMHelperAlgo::Winograd, FieldMode >::Delayed←
Field::Element Cmax ) [inline]
```

11.13.1.24 DynamicPeeling2()

```
template<class Field , class FieldMode >
void DynamicPeeling2 (
    const Field & F,
```

```

    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t m,
    const size_t n,
    const size_t k,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, FieldMode > & H,
    const typename MMHelper< Field, MMHelperAlgo::Winograd, FieldMode >::Delayed←
Field::Element Cmin,
    const typename MMHelper< Field, MMHelperAlgo::Winograd, FieldMode >::Delayed←
Field::Element Cmax ) [inline]

```

11.13.1.25 WinogradCalc()

```

template<class Field , class FieldMode >
void WinogradCalc (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const FFLAS_TRANSPOSE tb,
    const size_t mr,
    const size_t nr,
    const size_t kr,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Winograd, FieldMode > & H ) [inline]

```

11.13.1.26 fgemv_convert()

```

template<typename FloatElement , class Field >
Field::Element_ptr fgemv_convert (
    const Field & F,
    const FFLAS_TRANSPOSE ta,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr X,
    const size_t incX,

```

```

    const typename Field::Element beta,
    typename Field::Element_ptr Y,
    const size_t incY ) [inline]

```

11.13.1.27 fger_convert()

```

template<class FloatElement , class Field >
void fger_convert (
    const Field & F,
    const size_t M,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr x,
    const size_t incx,
    typename Field::ConstElement_ptr y,
    const size_t incy,
    typename Field::Element_ptr A,
    const size_t lda ) [inline]

```

11.13.1.28 fsyrk_convert()

```

template<class NewField , class Field , class FieldMode >
Field::Element_ptr fsyrk_convert (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const FFLAS_TRANSPOSE trans,
    const size_t N,
    const size_t K,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc,
    MMHelper< Field, MMHelperAlgo::Classic, FieldMode > & H ) [inline]

```

11.13.1.29 ScalAndReduce() [3/3]

```

template<class Field , class AlgoT , class ParSeqTrait >
void ScalAndReduce (
    const Field & F,
    const FFLAS_UPLO UpLo,
    const size_t N,
    const typename Field::Element alpha,
    typename Field::Element_ptr A,
    const size_t lda,
    const MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > & H ) [inline]

```

11.13.1.30 NeedPreScalReduction() [1/2]

```
template<class Field , class Element , class AlgoT , class ParSeqTrait >
bool NeedPreScalReduction (
    Element & Outmin,
    Element & Outmax,
    Element & Op1min,
    Element & Op1max,
    const Element & x,
    MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > & WH ) [inline]
```

11.13.1.31 NeedPreScalReduction() [2/2]

```
template<class Field , class Element , class AlgoT , class ModeT , class ParSeqTrait >
bool NeedPreScalReduction (
    Element & Outmin,
    Element & Outmax,
    Element & Op1min,
    Element & Op1max,
    const Element & x,
    MMHelper< Field, AlgoT, ModeT, ParSeqTrait > & WH ) [inline]
```

11.13.1.32 NeedPreAxyReduction() [1/2]

```
template<class Field , class Element , class AlgoT , class ParSeqTrait >
bool NeedPreAxyReduction (
    Element & Outmin,
    Element & Outmax,
    Element & Op1min,
    Element & Op1max,
    Element & Op2min,
    Element & Op2max,
    const Element & x,
    MMHelper< Field, AlgoT, ModeCategories::LazyTag, ParSeqTrait > & WH ) [inline]
```

11.13.1.33 NeedPreAxyReduction() [2/2]

```
template<class Field , class Element , class AlgoT , class ModeT , class ParSeqTrait >
bool NeedPreAxyReduction (
    Element & Outmin,
    Element & Outmax,
    Element & Op1min,
    Element & Op1max,
    Element & Op2min,
    Element & Op2max,
    const Element & x,
    MMHelper< Field, AlgoT, ModeT, ParSeqTrait > & WH ) [inline]
```

11.13.1.34 min_types() [1/7]

```
template<class DFE >
size_t min_types (
    const DFE & k ) [inline]
```


11.13.1.35 min_types() [2/7]

```
template<>
size_t min_types (
    const RecInt::rint< 6 > & k ) [inline]
```

11.13.1.36 min_types() [3/7]

```
template<>
size_t min_types (
    const RecInt::rint< 7 > & k ) [inline]
```

11.13.1.37 min_types() [4/7]

```
template<>
size_t min_types (
    const RecInt::rint< 8 > & k ) [inline]
```

11.13.1.38 min_types() [5/7]

```
template<>
size_t min_types (
    const RecInt::rint< 9 > & k ) [inline]
```

11.13.1.39 min_types() [6/7]

```
template<>
size_t min_types (
    const RecInt::rint< 10 > & k ) [inline]
```

11.13.1.40 min_types() [7/7]

```
template<>
size_t min_types (
    const Givaro::Integer & k ) [inline]
```

11.13.1.41 unfit() [1/4]

```
template<class T >
bool unfit (
    T x ) [inline]
```

11.13.1.42 unfit() [2/4]

```
template<>
bool unfit (
    int64_t x ) [inline]
```

11.13.1.43 unfit() [3/4]

```
template<size_t K>
bool unfit (
    RecInt::rint< K > x ) [inline]
```

11.13.1.44 unfit() [4/4]

```
template<>
bool unfit (
    RecInt::rint< 6 > x ) [inline]
```

11.13.1.45 igemm_colmajor() [1/2]

```
template<enum FFLAS_TRANSPOSE tA, enum FFLAS_TRANSPOSE tB>
void igemm_colmajor (
    size_t rows,
    size_t cols,
    size_t depth,
    const int64_t alpha,
    const int64_t * A,
    size_t lda,
    const int64_t * B,
    size_t ldb,
    int64_t * C,
    size_t ldc )
```

11.13.1.46 igemm_colmajor() [2/2]

```
template<enum FFLAS_TRANSPOSE tA, enum FFLAS_TRANSPOSE tB, enum number_kind alpha_kind>
void igemm_colmajor (
    size_t rows,
    size_t cols,
    size_t depth,
    const int64_t alpha,
    const int64_t * A,
    size_t lda,
    const int64_t * B,
    size_t ldb,
    int64_t * C,
    size_t ldc )
```

11.13.1.47 igemm()

```
void igemm (
    const enum FFLAS_TRANSPOSE TransA,
    const enum FFLAS_TRANSPOSE TransB,
    size_t rows,
    size_t cols,
    size_t depth,
    const int64_t alpha,
```

```

    const int64_t * A,
    size_t lda,
    const int64_t * B,
    size_t ldb,
    const int64_t beta,
    int64_t * C,
    size_t ldc ) [inline]

```

Todo use primitive (no [Field\(\)](#)) and specialise for int64.

Todo use primitive (no [Field\(\)](#)) and specialise for int64.

11.13.148 MatF2MatD_Triangular()

```

template<class Field >
void MatF2MatD_Triangular (
    const Field & F,
    Givaro::DoubleDomain::Element_ptr S,
    const size_t lds,
    typename Field::ConstElement_ptr const E,
    const size_t lde,
    const size_t m,
    const size_t n )

```

11.13.149 MatF2MatFI_Triangular()

```

template<class Field >
void MatF2MatFI_Triangular (
    const Field & F,
    Givaro::FloatDomain::Element_ptr S,
    const size_t lds,
    typename Field::ConstElement_ptr const E,
    const size_t lde,
    const size_t m,
    const size_t n )

```

Todo do finit(...,FFLAS_TRANS,FFLAS_DIAG)
do fconvert(...,FFLAS_TRANS,FFLAS_DIAG)

11.14 FFLAS::sell_details Namespace Reference

Data Structures

- struct [Coo](#)
- struct [Info](#)

11.15 FFLAS::sparse_details Namespace Reference

Functions

- `template<class Field >`
`void init_y (const Field &F, const size_t m, const typename Field::Element b, typename Field::Element_ptr y)`
- `template<class Field >`
`void init_y (const Field &F, const size_t m, const size_t n, const typename Field::Element b, typename Field::Element_ptr y, const int ldy)`
- `template<class Field , class SM , class FC , class MZO >`
`std::enable_if<!(std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat >::value)||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag >::value)>::type fspmv_dispatch (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FC fc, MZO mzo)`
- `template<class Field , class SM , class FC , class MZO >`
`std::enable_if< std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat >::value)||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag >::value >::type fspmv_dispatch (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FC fc, MZO mzo)`
- `template<class Field , class SM >`
`void fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::GenericTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if<lisSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if<lisSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::ModularTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::ModularTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`void fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::GenericTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if<lisSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`void fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::ModularTag, std::true_type)`
- `template<class Field , class SM , class FCat , class MZO >`
`std::enable_if<!(std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat >::value)||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag >::value)>::type fspmm_dispatch (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FCat, MZO)`

- `template<class Field , class SM , class FCat , class MZO >`
`std::enable_if< std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat >::value || std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag >::value >::type fspmm_dispatch (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FCat, MZO)`
- `template<class Field , class SM >`
`void fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::UnparametricTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< !support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::UnparametricTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::ModularTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< !support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::ModularTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`void fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::UnparametricTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< !support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::UnparametricTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`void fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::ModularTag, ZOSparseMatrix)`
- `template<class Field , class SM , class FCat , class MZO >`
`std::enable_if< !(std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat >::value || std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag >::value) >::type pfspmm_dispatch (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FCat, MZO)`
- `template<class Field , class SM , class FCat , class MZO >`
`std::enable_if< std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat >::value || std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag >::value >::type pfspmm_dispatch (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FCat, MZO)`
- `template<class Field , class SM >`
`void pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< support_simd< typenameField::Element >::value >::type pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::UnparametricTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< !support_simd< typenameField::Element >::value >::type pfspmm (const Field &F, const SM`

- &A, size_t blockSize, typename [Field::ConstElement_ptr](#) x, int ldx, typename [Field::Element_ptr](#) y, int ldy, [FieldCategories::UnparametricTag](#), [NotZOSparseMatrix](#))
- `template<class Field , class SM >`
`std::enable_if<support\_simd< typenameField::Element >::value >::type pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::ModularTag, NotZOSparseMatrix)`
 - `template<class Field , class SM >`
`std::enable_if<!support\_simd< typenameField::Element >::value >::type pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::ModularTag, NotZOSparseMatrix)`
 - `template<class Field , class SM >`
`void pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::GenericTag, ZOSparseMatrix)`
 - `template<class Field , class SM >`
`std::enable_if<support\_simd< typenameField::Element >::value >::type pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::UnparametricTag, ZOSparseMatrix)`
 - `template<class Field , class SM >`
`std::enable_if<!support\_simd< typenameField::Element >::value >::type pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::UnparametricTag, ZOSparseMatrix)`
 - `template<class Field , class SM >`
`void pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::ModularTag, ZOSparseMatrix)`
 - `template<class Field , class SM >`
`void pfspmv (const Field &F, const SM &A, typename Field::ConstElement\_ptr x, typename Field::Element\_ptr y, FieldCategories::GenericTag, std::false_type)`
 - `template<class Field , class SM >`
`void pfspmv (const Field &F, const SM &A, typename Field::ConstElement\_ptr x, typename Field::Element\_ptr y, FieldCategories::UnparametricTag, std::false_type)`
 - `template<class Field , class SM >`
`void pfspmv (const Field &F, const SM &A, typename Field::ConstElement\_ptr x, typename Field::Element\_ptr y, FieldCategories::ModularTag, std::false_type)`
 - `template<class Field , class SM >`
`void pfspmv (const Field &F, const SM &A, typename Field::ConstElement\_ptr x, typename Field::Element\_ptr y, FieldCategories::GenericTag, std::true_type)`
 - `template<class Field , class SM >`
`void pfspmv (const Field &F, const SM &A, typename Field::ConstElement\_ptr x, typename Field::Element\_ptr y, FieldCategories::UnparametricTag, std::true_type)`
 - `template<class Field , class SM >`
`void pfspmv (const Field &F, const SM &A, typename Field::ConstElement\_ptr x, typename Field::Element\_ptr y, FieldCategories::ModularTag, std::true_type)`
 - `template<class Field , class SM >`
`std::enable_if<isSparseMatrixSimdFormat< Field, SM >::value &&support\_simd< typenameField::Element >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement\_ptr x, typename Field::Element\_ptr y, FieldCategories::UnparametricTag, NotZOSparseMatrix)`
 - `template<class Field , class SM >`
`std::enable_if<isSparseMatrixSimdFormat< Field, SM >::value &&support\_simd< typenameField::Element >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement\_ptr x, typename Field::Element\_ptr y, FieldCategories::ModularTag, NotZOSparseMatrix)`
 - `template<class Field , class SM >`
`std::enable_if<isSparseMatrixSimdFormat< Field, SM >::value &&support\_simd< typenameField::Element >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement\_ptr x, typename Field::Element\_ptr y, FieldCategories::UnparametricTag, ZOSparseMatrix)`

11.15.1 Function Documentation

11.15.1.1 init_y() [1/2]

```
template<class Field >
void init_y (
    const Field & F,
    const size_t m,
    const typename Field::Element b,
    typename Field::Element_ptr y ) [inline]
```

11.15.1.2 init_y() [2/2]

```
template<class Field >
void init_y (
    const Field & F,
    const size_t m,
    const size_t n,
    const typename Field::Element b,
    typename Field::Element_ptr y,
    const int ldy ) [inline]
```

11.15.1.3 fspmv_dispatch() [1/2]

```
template<class Field , class SM , class FC , class MZO >
std::enable_if<!(std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::Mac
>::value||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineInt
>::value)>::type fspmv_dispatch (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FC fC,
    MZO mzo ) [inline]
```

11.15.1.4 fspmv_dispatch() [2/2]

```
template<class Field , class SM , class FC , class MZO >
std::enable_if< std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::Mac
>::value||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineInt
>::value >::type fspmv_dispatch (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FC fC,
    MZO mzo ) [inline]
```

11.15.1.5 fspmv() [1/12]

```
template<class Field , class SM >
void fspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::GenericTag ,
    NotZOSparseMatrix ) [inline]
```

11.15.1.6 fspmv() [2/12]

```
template<class Field , class SM >
std::enable_if<!isSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::UnparametricTag ,
    NotZOSparseMatrix ) [inline]
```

11.15.1.7 fspmv() [3/12]

```
template<class Field , class SM >
std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::UnparametricTag ,
    NotZOSparseMatrix ) [inline]
```

11.15.1.8 fspmv() [4/12]

```
template<class Field , class SM >
std::enable_if<!isSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::ModularTag ,
    NotZOSparseMatrix ) [inline]
```

11.15.1.9 fspmv() [5/12]

```
template<class Field , class SM >
std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::ModularTag ,
    NotZOSparseMatrix ) [inline]
```


11.15.1.10 fspmv() [6/12]

```
template<class Field , class SM >
void fspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::GenericTag ,
    ZOSparseMatrix ) [inline]
```

11.15.1.11 fspmv() [7/12]

```
template<class Field , class SM >
std::enable_if<!isSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::UnparametricTag ,
    ZOSparseMatrix ) [inline]
```

11.15.1.12 fspmv() [8/12]

```
template<class Field , class SM >
std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::UnparametricTag ,
    ZOSparseMatrix ) [inline]
```

11.15.1.13 fspmv() [9/12]

```
template<class Field , class SM >
void fspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::ModularTag ,
    std::true_type ) [inline]
```

11.15.1.14 fspmm_dispatch() [1/2]

```
template<class Field , class SM , class FCat , class MZO >
std::enable_if<!(std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::Ma
>::value||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineInt
>::value)>::type fspmm_dispatch (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FCat ,
    MZO ) [inline]
```

11.15.1.15 fspmm_dispatch() [2/2]

```
template<class Field , class SM , class FCat , class MZO >
std::enable_if< std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::Mac
>::value||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineInt
>::value >::type fspmm_dispatch (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FCat ,
    MZO ) [inline]
```

11.15.1.16 fspmm() [1/9]

```
template<class Field , class SM >
void fspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::GenericTag ,
    NotZOSparseMatrix ) [inline]
```

11.15.1.17 fspmm() [2/9]

```
template<class Field , class SM >
std::enable_if< support_simd< typenameField::Element >::value >::type fspmm (
    const Field & F,
    const SM & A,
```

```

    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::UnparametricTag ,
    NotZOSparseMatrix ) [inline]

```

11.15.1.18 fspmm() [3/9]

```

template<class Field , class SM >
std::enable_if<!support\_simd< typenameField::Element >::value >::type fspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::UnparametricTag ,
    NotZOSparseMatrix ) [inline]

```

11.15.1.19 fspmm() [4/9]

```

template<class Field , class SM >
std::enable_if< support\_simd< typenameField::Element >::value >::type fspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::ModularTag ,
    NotZOSparseMatrix ) [inline]

```

11.15.1.20 fspmm() [5/9]

```

template<class Field , class SM >
std::enable_if<!support\_simd< typenameField::Element >::value >::type fspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::ModularTag ,
    NotZOSparseMatrix ) [inline]

```

11.15.1.21 fspmm() [6/9]

```
template<class Field , class SM >
void fspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::GenericTag ,
    ZOSparseMatrix ) [inline]
```

11.15.1.22 fspmm() [7/9]

```
template<class Field , class SM >
std::enable_if< support_simd< typenameField::Element >::value >::type fspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::UnparametricTag ,
    ZOSparseMatrix ) [inline]
```

11.15.1.23 fspmm() [8/9]

```
template<class Field , class SM >
std::enable_if< !support_simd< typenameField::Element >::value >::type fspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::UnparametricTag ,
    ZOSparseMatrix ) [inline]
```

11.15.1.24 fspmm() [9/9]

```
template<class Field , class SM >
void fspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::ModularTag ,
    ZOSparseMatrix ) [inline]
```

11.15.1.25 pfspmm_dispatch() [1/2]

```
template<class Field , class SM , class FCat , class MZO >
std::enable_if<!(std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::Ma
>::value||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineInt
>::value)>::type pfspmm_dispatch (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FCat ,
    MZO ) [inline]
```

11.15.1.26 pfspmm_dispatch() [2/2]

```
template<class Field , class SM , class FCat , class MZO >
std::enable_if< std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::Mac
>::value||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineInt
>::value >::type pfspmm_dispatch (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FCat ,
    MZO ) [inline]
```

11.15.1.27 pfspmm() [1/9]

```
template<class Field , class SM >
void pfspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::GenericTag ,
    NotZOSparseMatrix ) [inline]
```

11.15.1.28 pfspmm() [2/9]

```
template<class Field , class SM >
std::enable_if< support_simd< typenameField::Element >::value >::type pfspmm (
    const Field & F,
    const SM & A,
```

```

    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::UnparametricTag ,
    NotZOSparseMatrix ) [inline]

```

11.15.1.29 pfspmm() [3/9]

```

template<class Field , class SM >
std::enable_if<!support\_simd< typenameField::Element >::value >::type pfspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::UnparametricTag ,
    NotZOSparseMatrix ) [inline]

```

11.15.1.30 pfspmm() [4/9]

```

template<class Field , class SM >
std::enable_if< support\_simd< typenameField::Element >::value >::type pfspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::ModularTag ,
    NotZOSparseMatrix ) [inline]

```

11.15.1.31 pfspmm() [5/9]

```

template<class Field , class SM >
std::enable_if<!support\_simd< typenameField::Element >::value >::type pfspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::ModularTag ,
    NotZOSparseMatrix ) [inline]

```

11.15.1.32 pfspmm() [6/9]

```
template<class Field , class SM >
void pfspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::GenericTag ,
    ZOSparseMatrix ) [inline]
```

11.15.1.33 pfspmm() [7/9]

```
template<class Field , class SM >
std::enable_if< support_simd< typenameField::Element >::value >::type pfspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::UnparametricTag ,
    ZOSparseMatrix ) [inline]
```

11.15.1.34 pfspmm() [8/9]

```
template<class Field , class SM >
std::enable_if< !support_simd< typenameField::Element >::value >::type pfspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::UnparametricTag ,
    ZOSparseMatrix ) [inline]
```

11.15.1.35 pfspmm() [9/9]

```
template<class Field , class SM >
void pfspmm (
    const Field & F,
    const SM & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::ModularTag ,
    ZOSparseMatrix ) [inline]
```

11.15.1.36 pfspmv() [1/6]

```
template<class Field , class SM >
void pfspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::GenericTag ,
    std::false_type ) [inline]
```

11.15.1.37 pfspmv() [2/6]

```
template<class Field , class SM >
void pfspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::UnparametricTag ,
    std::false_type ) [inline]
```

11.15.1.38 pfspmv() [3/6]

```
template<class Field , class SM >
void pfspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::ModularTag ,
    std::false_type ) [inline]
```

11.15.1.39 pfspmv() [4/6]

```
template<class Field , class SM >
void pfspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::GenericTag ,
    std::true_type ) [inline]
```

11.15.1.40 pfspmv() [5/6]

```
template<class Field , class SM >
void pfspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::UnparametricTag ,
    std::true_type ) [inline]
```


11.15.1.41 pfspmv() [6/6]

```
template<class Field , class SM >
void pfspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::ModularTag ,
    std::true_type ) [inline]
```

11.15.1.42 fspmv() [10/12]

```
template<class Field , class SM >
std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value &&support_simd< typenameField↵
::Element >::value >::type fspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::UnparametricTag ,
    NotZOSparseMatrix ) [inline]
```

11.15.1.43 fspmv() [11/12]

```
template<class Field , class SM >
std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value &&support_simd< typenameField↵
::Element >::value >::type fspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::ModularTag ,
    NotZOSparseMatrix ) [inline]
```

11.15.1.44 fspmv() [12/12]

```
template<class Field , class SM >
std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value &&support_simd< typenameField↵
::Element >::value >::type fspmv (
    const Field & F,
    const SM & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::UnparametricTag ,
    ZOSparseMatrix ) [inline]
```

11.16 FFLAS::sparse_details_impl Namespace Reference

Functions

- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::COO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::COO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::COO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, const int64_t kmax)`
- `template<class Field >`
`void fspmm_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::COO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, const int64_t kmax)`
- `template<class Field >`
`void fspmm_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::COO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, const int64_t kmax)`
- `template<class Field >`
`void fspmm_one (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmm_mone (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmm_one_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm_one_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm_mone_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm_mone_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::COO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::COO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::COO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const uint64_t kmax)`
- `template<class Field >`
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`

- `template<class Field >`
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, const int64_t kmax)`
- `template<class Field >`
`void pfspmm_one (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmm_mone (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmm_one (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmm_mone (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmv_task (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const index_t iStart, const index_t iStop, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const int64_t kmax)`
- `template<class Field >`
`void pfspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`

- `template<class Field >`
`void pfspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, index_t blockSize, typename Field::ConstElement_ptr x_, index_t ldx, typename Field::Element_ptr y_, index_t ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, const int64_t kmax)`
- `template<class Field >`
`void fspmm_one (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmm_mone (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmm_one_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm_one_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm_mone_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm_mone_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const int64_t kmax)`
- `template<class Field >`
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`

- `template<class Field >`
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, const int64_t kmax)`
- `template<class Field >`
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, const int64_t kmax)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const int64_t kmax)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, const int64_t kmax)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const uint64_t kmax)`
- `template<class Field >`
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::GenericTag)`

- `template<class Field >`
`void pfsppmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfsppmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfsppmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfsppmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, const int64_t kmax)`
- `template<class Field >`
`void pfsppmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, const int64_t kmax)`
- `template<class Field, class Func >`
`void pfsppmm_zo (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, Func &&func)`
- `template<class Field, class Func >`
`void pfsppmm_zo (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, Func &&func)`
- `template<class Field >`
`void pfsppmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfsppmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfsppmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const int64_t kmax)`
- `template<class Field >`
`void pfsppmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfsppmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfsppmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfsppmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, const int64_t kmax)`
- `template<class Field >`
`void fspmm_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`

- `template<class Field >`
`void fspmm_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmm_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm_one_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm_one_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm_mone_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm_mone_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const uint64_t kmax)`
- `template<class Field >`
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const uint64_t kmax)`

- `template<class Field >`
`void pfspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv_simd (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv_simd (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const uint64_t kmax)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const uint64_t kmax)`
- `template<class Field >`
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv_one_simd (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv_mone_simd (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, uint64_t kmax)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::GenericTag)`

- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, uint64_t kmax)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, uint64_t kmax)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, uint64_t kmax)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::SELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::SELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::SELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const int64_t kmax)`
- `template<class Field >`
`void pfspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::SELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::SELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void pfspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::SELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void pfspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::SELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::SELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv_simd (const Field &F, const Sparse< Field, SparseMatrix_t::SELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::SELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv_simd (const Field &F, const Sparse< Field, SparseMatrix_t::SELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const uint64_t kmax)`

- `template<class Field >`
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::SELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const uint64_t kmax)`
- `template<class Field >`
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::SELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::SELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`
`void fspmv_one_simd (const Field &F, const Sparse< Field, SparseMatrix_t::SELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv_mone_simd (const Field &F, const Sparse< Field, SparseMatrix_t::SELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::SELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::SELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`

11.16.1 Function Documentation

11.16.1.1 fspmm() [1/15]

```
template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.2 fspmm() [2/15]

```
template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.3 fspmm() [3/15]

```
template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    const int64_t kmax ) [inline]
```

11.16.1.4 fspmm_simd_aligned() [1/2]

```
template<class Field >
void fspmm_simd_aligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    const int64_t kmax ) [inline]
```

11.16.1.5 fspmm_simd_unaligned() [1/2]

```
template<class Field >
void fspmm_simd_unaligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    const int64_t kmax ) [inline]
```

11.16.1.6 fspmm_one() [1/4]

```
template<class Field >
void fspmm_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.7 fspmm_mone() [1/4]

```
template<class Field >
void fspmm_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.8 fspmm_one_simd_aligned() [1/3]

```
template<class Field >
void fspmm_one_simd_aligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.9 fspmm_one_simd_unaligned() [1/3]

```
template<class Field >
void fspmm_one_simd_unaligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.10 fspmm_mone_simd_aligned() [1/3]

```
template<class Field >
void fspmm_mone_simd_aligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.11 fspmm_mone_simd_unaligned() [1/3]

```
template<class Field >
void fspmm_mone_simd_unaligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.12 fspmv() [1/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.13 fspmv() [2/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.14 fspmv() [3/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const uint64_t kmax ) [inline]
```

11.16.1.15 fspmv_one() [1/10]

```
template<class Field >
void fspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.16 fspmv_mone() [1/10]

```
template<class Field >
void fspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.17 fspmv_one() [2/10]

```
template<class Field >
void fspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.18 fspmv_mone() [2/10]

```
template<class Field >
void fspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::COO_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.19 pfspmm() [1/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.20 pfspmm() [2/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.21 pfspmm() [3/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    const int64_t kmax ) [inline]
```

11.16.1.22 pfspmm_one() [1/2]

```
template<class Field >
void pfspmm_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.23 pfspmm_mone() [1/2]

```
template<class Field >
void pfspmm_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.24 pfspmm_one() [2/2]

```
template<class Field >
void pfspmm_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.25 pfspmm_mone() [2/2]

```
template<class Field >
void pfspmm_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.26 pfspmv() [1/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.27 pfspmv_task()

```
template<class Field >
void pfspmv_task (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const index_t iStart,
    const index_t iStop,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.28 pfspmv() [2/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.29 pfspmv() [3/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const int64_t kmax ) [inline]
```


11.16.1.30 pfspmv_one() [1/8]

```
template<class Field >
void pfspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.31 pfspmv_mone() [1/8]

```
template<class Field >
void pfspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.32 pfspmv_one() [2/8]

```
template<class Field >
void pfspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.33 pfspmv_mone() [2/8]

```
template<class Field >
void pfspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.34 fspmm() [4/15]

```
template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.35 fspmm() [5/15]

```

template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    index_t blockSize,
    typename Field::ConstElement_ptr x_,
    index_t ldx,
    typename Field::Element_ptr y_,
    index_t ldy,
    FieldCategories::UnparametricTag ) [inline]

```

11.16.1.36 fspmm_simd_aligned() [2/2]

```

template<class Field >
void fspmm_simd_aligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]

```

11.16.1.37 fspmm_simd_unaligned() [2/2]

```

template<class Field >
void fspmm_simd_unaligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]

```

11.16.1.38 fspmm() [6/15]

```

template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    const int64_t kmax ) [inline]

```

11.16.139 fspmm_one() [2/4]

```
template<class Field >
void fspmm_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.140 fspmm_mone() [2/4]

```
template<class Field >
void fspmm_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.141 fspmm_one_simd_aligned() [2/3]

```
template<class Field >
void fspmm_one_simd_aligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.142 fspmm_one_simd_unaligned() [2/3]

```
template<class Field >
void fspmm_one_simd_unaligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.43 fspmm_mone_simd_aligned() [2/3]

```
template<class Field >
void fspmm_mone_simd_aligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.44 fspmm_mone_simd_unaligned() [2/3]

```
template<class Field >
void fspmm_mone_simd_unaligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.45 fspmv() [4/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.46 fspmv() [5/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.47 fspmv() [6/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const int64_t kmax ) [inline]
```

11.16.148 fspmv_one() [3/10]

```
template<class Field >
void fspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.149 fspmv_mone() [3/10]

```
template<class Field >
void fspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.150 fspmv_one() [4/10]

```
template<class Field >
void fspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.151 fspmv_mone() [4/10]

```
template<class Field >
void fspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.152 pfspmm() [4/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.53 pfspmm() [5/18]

```

template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::GenericTag ) [inline]

```

11.16.1.54 pfspmm() [6/18]

```

template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::UnparametricTag ) [inline]

```

11.16.1.55 pfspmm() [7/18]

```

template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]

```

11.16.1.56 pfspmm() [8/18]

```

template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    const int64_t kmax ) [inline]

```

11.16.157 pfspmm() [9/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    const int64_t kmax ) [inline]
```

11.16.158 pfspmv() [4/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.159 pfspmv() [5/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.160 pfspmv() [6/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const int64_t kmax ) [inline]
```

11.16.161 fspmm() [7/15]

```
template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.62 fspmm() [8/15]

```
template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.63 fspmm() [9/15]

```
template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    const int64_t kmax ) [inline]
```

11.16.1.64 fspmv() [7/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.65 fspmv() [8/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.66 fspmv() [9/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::CSR_HYB > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const uint64_t kmax ) [inline]
```


11.16.1.67 pfspmm() [10/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.68 pfspmm() [11/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.69 pfspmm() [12/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.70 pfspmm() [13/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.71 pfspmm() [14/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    const int64_t kmax ) [inline]
```

11.16.1.72 pfspmm() [15/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    const int64_t kmax ) [inline]
```

11.16.1.73 pfspmm_zo() [1/2]

```
template<class Field , class Func >
void pfspmm_zo (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    Func && func ) [inline]
```

11.16.1.74 pfspmm_zo() [2/2]

```
template<class Field , class Func >
void pfspmm_zo (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    Func && func ) [inline]
```

11.16.1.75 pfspmv() [7/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.76 pfspmv() [8/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.77 pfspmv() [9/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const int64_t kmax ) [inline]
```

11.16.1.78 pfspmv_one() [3/8]

```
template<class Field >
void pfspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.79 pfspmv_mone() [3/8]

```
template<class Field >
void pfspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.80 pfspmv_one() [4/8]

```
template<class Field >
void pfspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.81 pfspmv_mone() [4/8]

```
template<class Field >
void pfspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.82 fspmm() [10/15]

```
template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.83 fspmm() [11/15]

```
template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.84 fspmm() [12/15]

```
template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    const int64_t kmax ) [inline]
```

11.16.1.85 fspmm_mone() [3/4]

```
template<class Field >
void fspmm_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.86 fspmm_one() [3/4]

```
template<class Field >
void fspmm_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.87 fspmm_mone() [4/4]

```
template<class Field >
void fspmm_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.88 fspmm_one() [4/4]

```

template<class Field >
void fspmm_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]

```

11.16.1.89 fspmm_one_simd_aligned() [3/3]

```

template<class Field >
void fspmm_one_simd_aligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]

```

11.16.1.90 fspmm_one_simd_unaligned() [3/3]

```

template<class Field >
void fspmm_one_simd_unaligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]

```

11.16.1.91 fspmm_mone_simd_aligned() [3/3]

```

template<class Field >
void fspmm_mone_simd_aligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]

```

11.16.1.92 fspmm_mone_simd_unaligned() [3/3]

```
template<class Field >
void fspmm_mone_simd_unaligned (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x_,
    int ldx,
    typename Field::Element_ptr y_,
    int ldz,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.93 fspmv() [10/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.94 fspmv() [11/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.95 fspmv() [12/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const uint64_t kmax ) [inline]
```

11.16.1.96 fspmv_one() [5/10]

```
template<class Field >
void fspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.97 fspmv_mone() [5/10]

```
template<class Field >
void fspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.98 fspmv_one() [6/10]

```
template<class Field >
void fspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.99 fspmv_mone() [6/10]

```
template<class Field >
void fspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.100 pfspmv() [10/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.101 pfspmv() [11/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```


11.16.1.102 pfspmv() [12/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const uint64_t kmax ) [inline]
```

11.16.1.103 pfspmv_one() [5/8]

```
template<class Field >
void pfspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.104 pfspmv_mone() [5/8]

```
template<class Field >
void pfspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.105 pfspmv_one() [6/8]

```
template<class Field >
void pfspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.106 pfspmv_mone() [6/8]

```
template<class Field >
void pfspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.107 fspmv() [13/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.108 fspmv_simd() [1/4]

```
template<class Field >
void fspmv_simd (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.109 fspmv() [14/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.110 fspmv_simd() [2/4]

```
template<class Field >
void fspmv_simd (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const uint64_t kmax ) [inline]
```

11.16.1.111 fspmv() [15/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const uint64_t kmax ) [inline]
```

11.16.1.112 fspmv_one() [7/10]

```
template<class Field >
void fspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.113 fspmv_mone() [7/10]

```
template<class Field >
void fspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.114 fspmv_one() [8/10]

```
template<class Field >
void fspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.115 fspmv_mone() [8/10]

```
template<class Field >
void fspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.116 fspmv_one_simd() [1/2]

```
template<class Field >
void fspmv_one_simd (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.117 fspmv_mone_simd() [1/2]

```
template<class Field >
void fspmv_mone_simd (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.118 pfspmm() [16/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::HYB_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.119 pfspmm() [17/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::HYB_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.120 pfspmm() [18/18]

```
template<class Field >
void pfspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::HYB_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    uint64_t kmax ) [inline]
```

11.16.1.121 pfspmv() [13/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::HYB_ZO > & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.122 pfspmv() [14/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::HYB_ZO > & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.123 pfspmv() [15/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::HYB_ZO > & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    uint64_t kmax ) [inline]
```

11.16.1.124 fspmm() [13/15]

```
template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::HYB_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.125 fspmm() [14/15]

```
template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::HYB_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.126 fspmm() [15/15]

```
template<class Field >
void fspmm (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::HYB_ZO > & A,
    size_t blockSize,
    typename Field::ConstElement_ptr x,
    int ldx,
    typename Field::Element_ptr y,
    int ldy,
    uint64_t kmax ) [inline]
```

11.16.1.127 fspmv() [16/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::HYB_ZO > & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.128 fspmv() [17/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::HYB_ZO > & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.129 fspmv() [18/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::HYB_ZO > & A,
    typename Field::ConstElement_ptr x,
    typename Field::Element_ptr y,
    uint64_t kmax ) [inline]
```

11.16.1.130 pfspmv() [16/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.131 pfspmv() [17/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.132 pfspmv() [18/18]

```
template<class Field >
void pfspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const int64_t kmax ) [inline]
```

11.16.1.133 pfspmv_one() [7/8]

```
template<class Field >
void pfspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.134 pfspmv_mone() [7/8]

```
template<class Field >
void pfspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.135 pfspmv_one() [8/8]

```
template<class Field >
void pfspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.136 pfspmv_mone() [8/8]

```
template<class Field >
void pfspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.137 fspmv() [19/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.138 fspmv_simd() [3/4]

```
template<class Field >
void fspmv_simd (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.139 fspmv() [20/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.140 fspmv_simd() [4/4]

```
template<class Field >
void fspmv_simd (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const uint64_t kmax ) [inline]
```


11.16.1.141 fspmv() [21/21]

```
template<class Field >
void fspmv (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    const uint64_t kmax ) [inline]
```

11.16.1.142 fspmv_one() [9/10]

```
template<class Field >
void fspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.143 fspmv_mone() [9/10]

```
template<class Field >
void fspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::GenericTag ) [inline]
```

11.16.1.144 fspmv_one_simd() [2/2]

```
template<class Field >
void fspmv_one_simd (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.145 fspmv_mone_simd() [2/2]

```
template<class Field >
void fspmv_mone_simd (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.146 fspmv_one() [10/10]

```
template<class Field >
void fspmv_one (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.16.1.147 fspmv_mone() [10/10]

```
template<class Field >
void fspmv_mone (
    const Field & F,
    const Sparse< Field, SparseMatrix_t::SELL_ZO > & A,
    typename Field::ConstElement_ptr x_,
    typename Field::Element_ptr y_,
    FieldCategories::UnparametricTag ) [inline]
```

11.17 FFLAS::StrategyParameter Namespace Reference**Data Structures**

- struct [Fixed](#)
- struct [Grain](#)
- struct [Threads](#)
- struct [ThreeD](#)
- struct [ThreeDAdaptive](#)
- struct [ThreeDInPlace](#)
- struct [TwoD](#)
- struct [TwoDAdaptive](#)

11.18 FFLAS::StructureHelper Namespace Reference

[StructureHelper](#) for ftrsm.

Data Structures

- struct [Hybrid](#)
- struct [Iterative](#)
- struct [Recursive](#)

11.18.1 Detailed Description

[StructureHelper](#) for ftrsm.

11.19 FFLAS::vectorised Namespace Reference

Namespaces

- namespace [unswitch](#)

Data Structures

- struct [HelperMod](#)
- struct [HelperMod](#)< [Field](#), [ElementCategories::MachineIntTag](#) >
- struct [HelperMod](#)< [Field](#), [FFLAS::ElementCategories::ArbitraryPrecIntTag](#) >
- struct [HelperMod](#)< [Field](#), [FFLAS::ElementCategories::FixedPrecIntTag](#) >
- struct [HelperMod](#)< [Field](#), [FFLAS::ElementCategories::MachineFloatTag](#) >

Functions

- `template<class SimdT , class Element , bool positive>`
`std::enable_if< is\_simd< SimdT >::value, void >::type VEC\_ADD (SimdT &C, SimdT &A, SimdT &B, SimdT &Q, SimdT &T, SimdT &P, SimdT &NEGP, SimdT &MIN, SimdT &MAX)`
- `template<bool positive, class Element , class T1 , class T2 >`
`std::enable_if< FFLAS::support\_simd\_add< Element >::value, void >::type addp (Element *T, const Element *TA, const Element *TB, size_t n, Element p, T1 min_, T2 max_)`
- `template<class SimdT , class Element , bool positive>`
`std::enable_if< is\_simd< SimdT >::value, void >::type VEC\_SUB (SimdT &C, SimdT &A, SimdT &B, SimdT &Q, SimdT &T, SimdT &P, SimdT &NEGP, SimdT &MIN, SimdT &MAX)`
- `template<bool positive, class Element , class T1 , class T2 >`
`std::enable_if< FFLAS::support\_simd\_add< Element >::value, void >::type subp (Element *T, const Element *TA, const Element *TB, const size_t n, const Element p, const T1 min_, const T2 max_)`
- `template<class Element >`
`std::enable_if< FFLAS::support\_simd\_add< Element >::value, void >::type add (Element *T, const Element *TA, const Element *TB, size_t n)`
- `template<class Element >`
`std::enable_if< FFLAS::support\_simd\_add< Element >::value, void >::type sub (Element *T, const Element *TA, const Element *TB, size_t n)`
- `template<class Field >`
`std::enable_if< FFLAS::support\_fast\_mod< typename Field::Element >::value, void >::type axpyp (const Field &F, const typename Field::Element a, typename Field::ConstElement_ptr X, typename Field::Element_ptr Y, const size_t n)`
- `template<class Field >`
`std::enable_if< FFLAS::support\_fast\_mod< typename Field::Element >::value, void >::type axpyp (const Field &F, const typename Field::Element a, typename Field::ConstElement_ptr X, typename Field::Element_ptr Y, const size_t n, const size_t incX, const size_t incY)`
- `template<class T >`
`std::enable_if< !std::is_integral< T >::value, T >::type reduce (T A, T B)`
- `template<class T >`
`std::enable_if< std::is_integral< T >::value, T >::type reduce (T A, T B)`
- `template<> Givaro::Integer reduce (Givaro::Integer A, Givaro::Integer B)`
- `float reduce (float A, float B, float invB, float min, float max)`
- `double reduce (double A, double B, double invB, double min, double max)`
- `int64_t reduce (int64_t A, int64_t p, double invp, double min, double max, int64_t pow50rem)`
- `template<class Field >`
`Field::Element reduce (typename Field::Element A, HelperMod< Field, ElementCategories::MachineIntTag > &H)`

- `template<class Field >`
`Field::Element reduce (typename Field::Element A, HelperMod< Field, ElementCategories::MachineFloatTag > &H)`
- `template<class Field >`
`Field::Element reduce (typename Field::Element A, HelperMod< Field, ElementCategories::ArbitraryPrecIntTag > &H)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type modp (const Field &F, typename Field::ConstElement_ptr U, const size_t &n, typename Field::Element_ptr T)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type modp (const Field &F, typename Field::ConstElement_ptr U, const size_t &n, const size_t &incX, typename Field::Element_ptr T)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp (const Field &F, typename Field::Element_ptr T, const typename Field::Element alpha, typename Field::ConstElement_ptr U, const size_t n)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp (const Field &F, typename Field::Element_ptr T, const typename Field::Element alpha, typename Field::ConstElement_ptr U, const size_t n, const size_t &incX)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp (const Field &F, typename Field::Element_ptr T, const typename Field::Element alpha, typename Field::ConstElement_ptr U, const size_t n, const size_t &incX, const size_t &incY)`

11.19.1 Function Documentation

11.19.1.1 VEC_ADD()

```
template<class SimdT , class Element , bool positive>
std::enable_if< is_simd< SimdT >::value, void >::type VEC_ADD (
    SimdT & C,
    SimdT & A,
    SimdT & B,
    SimdT & Q,
    SimdT & T,
    SimdT & P,
    SimdT & NEGP,
    SimdT & MIN,
    SimdT & MAX ) [inline]
```

11.19.1.2 addp()

```
template<bool positive, class Element , class T1 , class T2 >
std::enable_if< FFLAS::support_simd_add< Element >::value, void >::type addp (
    Element * T,
    const Element * TA,
    const Element * TB,
    size_t n,
    Element p,
    T1 min_,
    T2 max_ ) [inline]
```

11.19.1.3 VEC_SUB()

```
template<class SimdT , class Element , bool positive>
std::enable_if< is_simd< SimdT >::value, void >::type VEC_SUB (
    SimdT & C,
    SimdT & A,
    SimdT & B,
    SimdT & Q,
    SimdT & T,
    SimdT & P,
    SimdT & NEGP,
    SimdT & MIN,
    SimdT & MAX ) [inline]
```

11.19.1.4 subp()

```
template<bool positive, class Element , class T1 , class T2 >
std::enable_if< FFLAS::support_simd_add< Element >::value, void >::type subp (
    Element * T,
    const Element * TA,
    const Element * TB,
    const size_t n,
    const Element p,
    const T1 min_,
    const T2 max_ ) [inline]
```

11.19.1.5 add()

```
template<class Element >
std::enable_if< FFLAS::support_simd_add< Element >::value, void >::type add (
    Element * T,
    const Element * TA,
    const Element * TB,
    size_t n ) [inline]
```

11.19.1.6 sub()

```
template<class Element >
std::enable_if< FFLAS::support_simd_add< Element >::value, void >::type sub (
    Element * T,
    const Element * TA,
    const Element * TB,
    size_t n ) [inline]
```

11.19.1.7 axpyp() [1/2]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type axpyp
(
    const Field & F,
    const typename Field::Element a,
    typename Field::ConstElement_ptr X,
    typename Field::Element_ptr Y,
    const size_t n ) [inline]
```

11.19.1.8 axpyp() [2/2]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type axpyp
(
    const Field & F,
    const typename Field::Element a,
    typename Field::ConstElement_ptr X,
    typename Field::Element_ptr Y,
    const size_t n,
    const size_t incX,
    const size_t incY ) [inline]
```

11.19.1.9 reduce() [1/9]

```
template<class T >
std::enable_if< !std::is_integral< T >::value, T >::type reduce (
    T A,
    T B ) [inline]
```

11.19.1.10 reduce() [2/9]

```
template<class T >
std::enable_if< std::is_integral< T >::value, T >::type reduce (
    T A,
    T B ) [inline]
```

11.19.1.11 reduce() [3/9]

```
template<>
Givaro::Integer reduce (
    Givaro::Integer A,
    Givaro::Integer B ) [inline]
```

11.19.1.12 reduce() [4/9]

```
float reduce (
    float A,
    float B,
    float invB,
    float min,
    float max ) [inline]
```

11.19.1.13 reduce() [5/9]

```
double reduce (
    double A,
    double B,
    double invB,
    double min,
    double max ) [inline]
```

11.19.1.14 reduce() [6/9]

```
int64_t reduce (
    int64_t A,
    int64_t p,
    double invp,
    double min,
    double max,
    int64_t pow50rem ) [inline]
```

11.19.1.15 reduce() [7/9]

```
template<class Field >
Field::Element reduce (
    typename Field::Element A,
    HelperMod< Field, ElementCategories::MachineIntTag > & H ) [inline]
```

11.19.1.16 reduce() [8/9]

```
template<class Field >
Field::Element reduce (
    typename Field::Element A,
    HelperMod< Field, ElementCategories::MachineFloatTag > & H ) [inline]
```

11.19.1.17 reduce() [9/9]

```
template<class Field >
Field::Element reduce (
    typename Field::Element A,
    HelperMod< Field, ElementCategories::ArbitraryPrecIntTag > & H ) [inline]
```

11.19.1.18 modp() [1/2]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type modp (
    const Field & F,
    typename Field::ConstElement_ptr U,
    const size_t & n,
    typename Field::Element_ptr T ) [inline]
```

11.19.1.19 modp() [2/2]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type modp (
    const Field & F,
    typename Field::ConstElement_ptr U,
    const size_t & n,
    const size_t & incX,
    typename Field::Element_ptr T ) [inline]
```

11.19.1.20 scalp() [1/3]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp
(
    const Field & F,
    typename Field::Element_ptr T,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr U,
    const size_t n ) [inline]
```

11.19.1.21 scalp() [2/3]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp
(
    const Field & F,
    typename Field::Element_ptr T,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr U,
    const size_t n,
    const size_t & incX ) [inline]
```

11.19.1.22 scalp() [3/3]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp
(
    const Field & F,
    typename Field::Element_ptr T,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr U,
    const size_t n,
    const size_t & incX,
    const size_t & incY ) [inline]
```

11.20 FFLAS::vectorised::unswitch Namespace Reference**Functions**

- template<class Field >
std::enable_if< !FFLAS::support_simd_mod< typenameField::Element >::value &&FFLAS::support_fast_mod< typenameField::Element >::value, void >::type axpyp (const Field &F, const typename Field::Element a, typename Field::ConstElement_ptr X, typename Field::Element_ptr Y, const size_t n, HelperMod< Field > &H)
- template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type axpyp (const Field &F, const typename Field::Element a, typename Field::ConstElement_ptr X, typename Field::Element_ptr Y, const size_t n, const size_t incX, const size_t incY, HelperMod< Field > &H)

- `template<class Field >`
`std::enable_if<!FFLAS::support_simd_mod< typenameField::Element >::value &&FFLAS::support_fast_mod<`
`typenameField::Element >::value, void >::type modp (const Field &F, typename Field::ConstElement_ptr U,`
`const size_t &n, typename Field::Element_ptr T, HelperMod< Field > &H)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type modp`
`(const Field &F, typename Field::ConstElement_ptr U, const size_t &n, const size_t &incX, typename`
`Field::Element_ptr T, HelperMod< Field > &H)`
- `template<class Field >`
`std::enable_if<!FFLAS::support_simd_mod< typenameField::Element >::value &&FFLAS::support_fast_mod<`
`typenameField::Element >::value, void >::type scalp (const Field &F, typename Field::Element_ptr T, const`
`typename Field::Element alpha, typename Field::ConstElement_ptr U, const size_t n, HelperMod< Field >`
`&H)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp`
`(const Field &F, typename Field::Element_ptr T, const typename Field::Element alpha, typename`
`Field::ConstElement_ptr U, const size_t n, const size_t &incX, HelperMod< Field > &H)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp`
`(const Field &F, typename Field::Element_ptr T, const typename Field::Element alpha, typename`
`Field::ConstElement_ptr U, const size_t n, const size_t &incX, const size_t &incY, HelperMod< Field >`
`&H)`

11.20.1 Function Documentation

11.20.1.1 axpyp() [1/2]

```
template<class Field >
std::enable_if<!FFLAS::support_simd_mod< typenameField::Element >::value &&FFLAS::support_fast_mod<
typenameField::Element >::value, void >::type axpyp (
    const Field & F,
    const typename Field::Element a,
    typename Field::ConstElement_ptr X,
    typename Field::Element_ptr Y,
    const size_t n,
    HelperMod< Field > & H ) [inline]
```

11.20.1.2 axpyp() [2/2]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type axpyp
(
    const Field & F,
    const typename Field::Element a,
    typename Field::ConstElement_ptr X,
    typename Field::Element_ptr Y,
    const size_t n,
    const size_t incX,
    const size_t incY,
    HelperMod< Field > & H ) [inline]
```

11.20.1.3 modp() [1/2]

```
template<class Field >
std::enable_if<!FFLAS::support_simd_mod< typenameField::Element >::value &&FFLAS::support_fast_mod<
typenameField::Element >::value, void >::type modp (
    const Field & F,
    typename Field::ConstElement_ptr U,
    const size_t & n,
    typename Field::Element_ptr T,
    HelperMod< Field > & H ) [inline]
```

11.20.1.4 modp() [2/2]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type modp (
    const Field & F,
    typename Field::ConstElement_ptr U,
    const size_t & n,
    const size_t & incX,
    typename Field::Element_ptr T,
    HelperMod< Field > & H ) [inline]
```

11.20.1.5 scalp() [1/3]

```
template<class Field >
std::enable_if<!FFLAS::support_simd_mod< typenameField::Element >::value &&FFLAS::support_fast_mod<
typenameField::Element >::value, void >::type scalp (
    const Field & F,
    typename Field::Element_ptr T,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr U,
    const size_t n,
    HelperMod< Field > & H ) [inline]
```

11.20.1.6 scalp() [2/3]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp
(
    const Field & F,
    typename Field::Element_ptr T,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr U,
    const size_t n,
    const size_t & incX,
    HelperMod< Field > & H ) [inline]
```

11.20.1.7 `scalp()` [3/3]

```
template<class Field >
std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp
(
    const Field & F,
    typename Field::Element_ptr T,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr U,
    const size_t n,
    const size_t & incX,
    const size_t & incY,
    HelperMod< Field > & H ) [inline]
```

11.21 FFPACK Namespace Reference

Finite **Field** **PACK** Set of elimination based routines for dense linear algebra.

Namespaces

- namespace [Protected](#)

Data Structures

- class [callLUdivine_small](#)
- class [callLUdivine_small< double >](#)
- class [callLUdivine_small< float >](#)
- class [CharpolyFailed](#)
- class [CheckerImplem_charpoly](#)
- class [CheckerImplem_charpoly< Givaro::ZRing< Givaro::Integer >, Polynomial >](#)
- class [CheckerImplem_Det](#)
- class [CheckerImplem_invert](#)
- class [CheckerImplem_PLUQ](#)
- class [Failure](#)
 - A precondition failed.*
- struct [rns_double](#)
- struct [rns_double_elt](#)
- struct [rns_double_elt_cstptr](#)
- struct [rns_double_elt_ptr](#)
- struct [rns_double_extended](#)
- class [RNSInteger](#)
- class [RNSIntegerMod](#)
- class [rnsRandIter](#)

Typedefs

- template<class [Field](#) >
using [Checker_PLUQ](#) = [FFLAS::Checker_Empty](#)< [Field](#) >
- template<class [Field](#) >
using [Checker_Det](#) = [FFLAS::Checker_Empty](#)< [Field](#) >
- template<class [Field](#) >
using [Checker_invert](#) = [FFLAS::Checker_Empty](#)< [Field](#) >
- template<class [Field](#) , class Polynomial >
using [Checker_charpoly](#) = [FFLAS::Checker_Empty](#)< [Field](#) >
- template<class [Field](#) >
using [ForceCheck_PLUQ](#) = [CheckerImplem_PLUQ](#)< [Field](#) >
- template<class [Field](#) >
using [ForceCheck_Det](#) = [CheckerImplem_Det](#)< [Field](#) >
- template<class [Field](#) >
using [ForceCheck_invert](#) = [CheckerImplem_invert](#)< [Field](#) >
- template<class [Field](#) , class Polynomial >
using [ForceCheck_charpoly](#) = [CheckerImplem_charpoly](#)< [Field](#) , Polynomial >

Functions

- void [LAPACKPerm2MathPerm](#) (size_t *MathP, const size_t *LapackP, const size_t N)
Conversion of a permutation from LAPACK format to Math format.
- void [MathPerm2LAPACKPerm](#) (size_t *LapackP, const size_t *MathP, const size_t N)
Conversion of a permutation from Maths format to LAPACK format.
- template<class [Field](#) >
void [applyP](#) (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) Side, const [FFLAS::FFLAS_TRANSPOSE](#) Trans, const size_t M, const size_t ibeg, const size_t iend, typename [Field::Element_ptr](#) A, const size_t lda, const size_t *P)
Computes $P1 \times \text{Diag}(I_R, P2)$ where $P1$ is a LAPACK and $P2$ a LAPACK permutation and store the result in $P1$ as a LAPACK permutation.
- template<class [Field](#) >
void [applyP](#) (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) Side, const [FFLAS::FFLAS_TRANSPOSE](#) Trans, const size_t m, const size_t ibeg, const size_t iend, typename [Field::Element_ptr](#) A, const size_t lda, const size_t *P, const [FFLAS::ParSeqHelper::Sequential](#) seq)
- template<class [Field](#) , class Cut , class Param >
void [applyP](#) (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) Side, const [FFLAS::FFLAS_TRANSPOSE](#) Trans, const size_t m, const size_t ibeg, const size_t iend, typename [Field::Element_ptr](#) A, const size_t lda, const size_t *P, const [FFLAS::ParSeqHelper::Parallel](#)< Cut, Param > par)
- template<class [Field](#) >
void [MonotonicApplyP](#) (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) Side, const [FFLAS::FFLAS_TRANSPOSE](#) Trans, const size_t M, const size_t ibeg, const size_t iend, typename [Field::Element_ptr](#) A, const size_t lda, const size_t *P, const size_t R)
Apply a R-monotonically increasing permutation P, to the matrix A.
- template<class [Field](#) >
void [fgetrs](#) (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) Side, const size_t M, const size_t N, const size_t R, typename [Field::Element_ptr](#) A, const size_t lda, const size_t *P, const size_t *Q, typename [Field::Element_ptr](#) B, const size_t ldb, int *info)
Solve the system $AX = B$ or $XA = B$.
- template<class [Field](#) >
[Field::Element_ptr](#) [fgetrs](#) (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) Side, const size_t M, const size_t N, const size_t NRHS, const size_t R, typename [Field::Element_ptr](#) A, const size_t lda, const size_t *P, const size_t *Q, typename [Field::Element_ptr](#) X, const size_t ldx, typename [Field::ConstElement_ptr](#) B, const size_t ldb, int *info)
Solve the system $AX = B$ or $XA = B$.

- template<class [Field](#) >
size_t [fgesv](#) (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) Side, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb, int *info)
Square system solver.
- template<class [Field](#) >
size_t [fgesv](#) (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) Side, const size_t M, const size_t N, const size_t NRHS, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) X, const size_t ldx, typename [Field::ConstElement_ptr](#) B, const size_t ldb, int *info)
Rectangular system solver.
- template<class [Field](#) >
void [ftrtri](#) (const [Field](#) &F, const [FFLAS::FFLAS_UPLO](#) Uplo, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, const size_t threshold=__FFLASFFPACK_FTRTRI_THRESHOLD)
Compute the inverse of a triangular matrix.
- template<class [Field](#) >
void [trinv_left](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) L, const size_t ldl, typename [Field::Element_ptr](#) X, const size_t ldx)
- template<class [Field](#) >
void [ftrtrm](#) (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) side, const [FFLAS::FFLAS_DIAG](#) diag, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda)
Compute the product of two triangular matrices of opposite shape.
- template<class [Field](#) >
void [ftrstr](#) (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) side, const [FFLAS::FFLAS_UPLO](#) Uplo, const [FFLAS::FFLAS_DIAG](#) diagA, const [FFLAS::FFLAS_DIAG](#) diagB, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb, const size_t threshold=__FFLASFFPACK_FTRSTR_THRESHOLD)
Solve a triangular system with a triangular right hand side of the same shape.
- template<class [Field](#) >
void [ftrssyr2k](#) (const [Field](#) &F, const [FFLAS::FFLAS_UPLO](#) Uplo, const [FFLAS::FFLAS_DIAG](#) diagA, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldx, const size_t ldb, const size_t threshold=__FFLASFFPACK_FTRSSYR2K_THRESHOLD)
Solve a triangular system in a symmetric sum: find B upper/lower triangular such that $A^T B + B^T A = C$ where C is symmetric.
- template<class [Field](#) >
bool [fsytrf](#) (const [Field](#) &F, const [FFLAS::FFLAS_UPLO](#) UpLo, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, const size_t threshold=__FFLASFFPACK_FSYTRF_THRESHOLD)
Triangular factorization of symmetric matrices.
- template<class [Field](#) >
bool [fsytrf](#) (const [Field](#) &F, const [FFLAS::FFLAS_UPLO](#) UpLo, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, const [FFLAS::ParSeqHelper::Sequential](#) seq, const size_t threshold=__FFLASFFPACK_FSYTRF_THRESHOLD)
- template<class [Field](#) , class [Cut](#) , class [Param](#) >
bool [fsytrf](#) (const [Field](#) &F, const [FFLAS::FFLAS_UPLO](#) UpLo, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, const [FFLAS::ParSeqHelper::Parallel](#)< [Cut](#) , [Param](#) > par, const size_t threshold=__FFLASFFPACK_FSYTRF_THRESHOLD)
- template<class [Field](#) >
bool [fsytrf_nonunit](#) (const [Field](#) &F, const [FFLAS::FFLAS_UPLO](#) UpLo, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) D, const size_t incD, const size_t threshold=__FFLASFFPACK_FSYTRF_THRESHOLD)
Triangular factorization of symmetric matrices.
- template<class [Field](#) >
size_t [PLUQ](#) (const [Field](#) &F, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, size_t *P, size_t *Q)
Compute a PLUQ factorization of the given matrix.
- template<class [Field](#) >
size_t [pPLUQ](#) (const [Field](#) &F, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, size_t *P, size_t *Q)

- `template<class Field >`
`size_t PLUQ (const Field &F, const FFLAS::FFLAS_DIAG Diag, const size_t M, const size_t N, type-`
`name Field::Element_ptr A, const size_t lda, size_t *P, size_t *Q, const FFLAS::ParSeqHelper::Sequential`
`&PSHelper, size_t BCThreshold=__FFLASFFPACK_PLUQ_THRESHOLD)`
- `template<class Field , class Cut , class Param >`
`size_t PLUQ (const Field &F, const FFLAS::FFLAS_DIAG Diag, const size_t M, const size_t N, typename`
`Field::Element_ptr A, const size_t lda, size_t *P, size_t *Q, const FFLAS::ParSeqHelper::Parallel< Cut,`
`Param > &PSHelper)`
- `template<class Field >`
`size_t LUdivine (const Field &F, const FFLAS::FFLAS_DIAG Diag, const FFLAS::FFLAS_TRANSPOSE trans,`
`const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt,`
`const FFPACK_LU_TAG LuTag=FfpackSlabRecursive, const size_t cutoff=__FFLASFFPACK_LUDIVINE↵`
`_THRESHOLD)`

Compute the CUP or PLE factorization of the given matrix.
- `template<class Field >`
`size_t ColumnEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr`
`A, const size_t lda, size_t *P, size_t *Qt, bool transform=false, const FFPACK_LU_TAG Lu↵`
`Tag=FfpackSlabRecursive)`

Compute the Column Echelon form of the input matrix in-place.
- `template<class Field >`
`size_t pColumnEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A,`
`const size_t lda, size_t *P, size_t *Qt, bool transform=false, size_t numthreads=0, const FFPACK_LU_TAG`
`LuTag=FfpackTileRecursive)`
- `template<class Field , class PSHelper >`
`size_t ColumnEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A,`
`const size_t lda, size_t *P, size_t *Qt, const bool transform, const FFPACK_LU_TAG LuTag, const PSHelper`
`&psH)`
- `template<class Field >`
`size_t RowEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr`
`A, const size_t lda, size_t *P, size_t *Qt, const bool transform=false, const FFPACK_LU_TAG Lu↵`
`Tag=FfpackSlabRecursive)`

Compute the Row Echelon form of the input matrix in-place.
- `template<class Field >`
`size_t pRowEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A,`
`const size_t lda, size_t *P, size_t *Qt, const bool transform=false, size_t numthreads=0, const FFPACK_↵`
`LU_TAG LuTag=FfpackTileRecursive)`
- `template<class Field , class PSHelper >`
`size_t RowEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A,`
`const size_t lda, size_t *P, size_t *Qt, const bool transform, const FFPACK_LU_TAG LuTag, const PSHelper`
`&psH)`
- `template<class Field >`
`size_t ReducedColumnEchelonForm (const Field &F, const size_t M, const size_t N, typename`
`Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const bool transform=false, const FFPACK_↵`
`LU_TAG LuTag=FfpackSlabRecursive)`

Compute the Reduced Column Echelon form of the input matrix in-place.
- `template<class Field >`
`size_t pReducedColumnEchelonForm (const Field &F, const size_t M, const size_t N, typename`
`Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const bool transform=false, size_t numthreads=0,`
`const FFPACK_LU_TAG LuTag=FfpackTileRecursive)`
- `template<class Field , class PSHelper >`
`size_t ReducedColumnEchelonForm (const Field &F, const size_t M, const size_t N, typename`
`Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const bool transform, const FFPACK_LU↵`
`_TAG LuTag, const PSHelper &psH)`
- `template<class Field >`
`size_t ReducedRowEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr`
`A, const size_t lda, size_t *P, size_t *Qt, const bool transform=false, const FFPACK_LU_TAG Lu↵`
`Tag=FfpackSlabRecursive)`

Compute the Reduced Row Echelon form of the input matrix in-place.

- template<class [Field](#) >
size_t [pReducedRowEchelonForm](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, size_t *P, size_t *Qt, const bool transform=false, size_t numthreads=0, const FFPACK_LU_TAG LuTag=[FfpackTileRecursive](#))

- template<class [Field](#) , class PSHelper >
size_t [ReducedRowEchelonForm](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, size_t *P, size_t *Qt, const bool transform, const FFPACK_LU_TAG LuTag, const PSHelper &psH)

- template<class [Field](#) >
[Field::Element_ptr](#) [Invert](#) (const [Field](#) &F, const size_t M, typename [Field::Element_ptr](#) A, const size_t lda, int &>nullity)

Invert the given matrix in place or computes its nullity if it is singular.

- template<class [Field](#) >
[Field::Element_ptr](#) [Invert](#) (const [Field](#) &F, const size_t M, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) X, const size_t idx, int &>nullity)

Invert the given matrix or computes its nullity if it is singular.

- template<class [Field](#) >
[Field::Element_ptr](#) [Invert2](#) (const [Field](#) &F, const size_t M, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) X, const size_t idx, int &>nullity)

Invert the given matrix or computes its nullity if it is singular.

- template<class [PolRing](#) >
std::list< typename [PolRing::Element](#) > & [CharPoly](#) (const [PolRing](#) &R, std::list< typename [PolRing::Element](#) > &charp, const size_t N, typename [PolRing::Domain_t::Element_ptr](#) A, const size_t lda, typename [PolRing::Domain_t::RandIter](#) &G, const FFPACK_CHARPOLY_TAG CharpTag=[FfpackAuto](#), const size_t degree=[__FFLASFFPACK_ARITHPROG_THRESHOLD](#))

Compute the characteristic polynomial of the matrix A.

- template<class [PolRing](#) >
[PolRing::Element](#) & [CharPoly](#) (const [PolRing](#) &R, typename [PolRing::Element](#) &charp, const size_t N, typename [PolRing::Domain_t::Element_ptr](#) A, const size_t lda, typename [PolRing::Domain_t::RandIter](#) &G, const FFPACK_CHARPOLY_TAG CharpTag=[FfpackAuto](#), const size_t degree=[__FFLASFFPACK_ARITHPROG_THRESHOLD](#))

Compute the characteristic polynomial of the matrix A.

- template<class [PolRing](#) >
[PolRing::Element](#) & [CharPoly](#) (const [PolRing](#) &R, typename [PolRing::Element](#) &charp, const size_t N, typename [PolRing::Domain_t::Element_ptr](#) A, const size_t lda, const FFPACK_CHARPOLY_TAG CharpTag=[FfpackAuto](#), const size_t degree=[__FFLASFFPACK_ARITHPROG_THRESHOLD](#))

Compute the characteristic polynomial of the matrix A.

- template<class [Field](#) , class [Polynomial](#) >
[Polynomial](#) & [MinPoly](#) (const [Field](#) &F, [Polynomial](#) &minP, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda)

Compute the minimal polynomial of the matrix A.

- template<class [Field](#) , class [Polynomial](#) , class [RandIter](#) >
[Polynomial](#) & [MinPoly](#) (const [Field](#) &F, [Polynomial](#) &minP, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, [RandIter](#) &G)

Compute the minimal polynomial of the matrix A.

- template<class [Field](#) , class [Polynomial](#) >
[Polynomial](#) & [MatVecMinPoly](#) (const [Field](#) &F, [Polynomial](#) &minP, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) v, const size_t incv)

Compute the minimal polynomial of the matrix A and a vector v, namely the first linear dependency relation in the Krylov basis $(v, Av, \dots, A^N v)$.

- template<class [Field](#) >
size_t [Rank](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda)

Computes the rank of the given matrix using a PLUQ factorization.

- template<class [Field](#) >
size_t [pRank](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, size_t numthreads=0)

- `template<class Field, class PSHelper >`
`size_t Rank (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, const PSHelper &psH)`
- `template<class Field >`
`bool IsSingular (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda)`
Returns true if the given matrix is singular.
- `template<class Field >`
`Field::Element & Det (const Field &F, typename Field::Element &det, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P=NULL, size_t *Q=NULL)`
Returns the determinant of the given square matrix.
- `template<class Field >`
`Field::Element & pDet (const Field &F, typename Field::Element &det, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t numthreads=0, size_t *P=NULL, size_t *Q=NULL)`
- `template<class Field, class PSHelper >`
`Field::Element & Det (const Field &F, typename Field::Element &det, const size_t N, typename Field::Element_ptr A, const size_t lda, const PSHelper &psH, size_t *P=NULL, size_t *Q=NULL)`
- `template<class Field >`
`Field::Element_ptr Solve (const Field &F, const size_t M, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr x, const int incx, typename Field::ConstElement_ptr b, const int incb)`
Solves a linear system $AX = b$ using PLUQ factorization.
- `template<class Field, class PSHelper >`
`Field::Element_ptr Solve (const Field &F, const size_t M, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr x, const int incx, typename Field::ConstElement_ptr b, const int incb, PSHelper &psH)`
- `template<class Field >`
`Field::Element_ptr pSolve (const Field &F, const size_t M, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr x, const int incx, typename Field::ConstElement_ptr b, const int incb, size_t numthreads=0)`
- `template<class Field >`
`*void RandomNullSpaceVector (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr X, const size_t incX)`
Solve $LX = B$ or $XL = B$ in place.
- `template<class Field >`
`size_t NullSpaceBasis (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr &NS, size_t &ldn, size_t &NSdim)`
Computes a basis of the Left/Right nullspace of the matrix A.
- `template<class Field >`
`size_t RowRankProfile (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *&rkprofile, const FFPACK_LU_TAG LuTag=FpackSlabRecursive)`
Computes the row rank profile of A.
- `template<class Field >`
`size_t pRowRankProfile (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *&rkprofile, size_t numthreads=0, const FFPACK_LU_TAG LuTag=FpackTileRecursive)`
- `template<class Field, class PSHelper >`
`size_t RowRankProfile (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *&rkprofile, const FFPACK_LU_TAG LuTag, PSHelper &psH)`
- `template<class Field >`
`size_t ColumnRankProfile (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *&rkprofile, const FFPACK_LU_TAG LuTag=FpackSlabRecursive)`
Computes the column rank profile of A.
- `template<class Field >`
`size_t pColumnRankProfile (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *&rkprofile, size_t numthreads=0, const FFPACK_LU_TAG LuTag=FpackTileRecursive)`

- template<class [Field](#) , class PSHelper >
size_t [ColumnRankProfile](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, size_t *rkprofile, const FFPACK_LU_TAG LuTag, PSHelper &psH)
- void [RankProfileFromLU](#) (const size_t *P, const size_t N, const size_t R, size_t *rkprofile, const FFPACK_LU_TAG LuTag)
Recovers the column/row rank profile from the permutation of an LU decomposition.
- size_t [LeadingSubmatrixRankProfiles](#) (const size_t M, const size_t N, const size_t R, const size_t LSm, const size_t LSn, const size_t *P, const size_t *Q, size_t *RRP, size_t *CRP)
Recovers the row and column rank profiles of any leading submatrix from the PLUQ decomposition.
- template<class [Field](#) >
size_t [RowRankProfileSubmatrixIndices](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, size_t *rowindices, size_t *colindices, size_t &R)
RowRankProfileSubmatrixIndices.
- template<class [Field](#) >
size_t [ColRankProfileSubmatrixIndices](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, size_t *rowindices, size_t *colindices, size_t &R)
Computes the indices of the submatrix $r \times r$ X of A whose columns correspond to the column rank profile of A.
- template<class [Field](#) >
size_t [RowRankProfileSubmatrix](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) &X, size_t &R)
Computes the $r \times r$ submatrix X of A, by picking the row rank profile rows of A.
- template<class [Field](#) >
size_t [ColRankProfileSubmatrix](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) &X, size_t &R)
Compute the $r \times r$ submatrix X of A, by picking the row rank profile rows of A.
- template<class [Field](#) >
void [getTriangular](#) (const [Field](#) &F, const FFLAS::FFLAS_UPLO Uplo, const FFLAS::FFLAS_DIAG diag, const size_t M, const size_t N, const size_t R, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) T, const size_t ldt, const bool OnlyNonZeroVectors=false)
Extracts a triangular matrix from a compact storage $A=L\backslash U$ of rank R.
- template<class [Field](#) >
void [getTriangular](#) (const [Field](#) &F, const FFLAS::FFLAS_UPLO Uplo, const FFLAS::FFLAS_DIAG diag, const size_t M, const size_t N, const size_t R, typename [Field::Element_ptr](#) A, const size_t lda)
Cleans up a compact storage $A=L\backslash U$ to reveal a triangular matrix of rank R.
- template<class [Field](#) >
void [getEchelonForm](#) (const [Field](#) &F, const FFLAS::FFLAS_UPLO Uplo, const FFLAS::FFLAS_DIAG diag, const size_t M, const size_t N, const size_t R, const size_t *P, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) T, const size_t ldt, const bool OnlyNonZeroVectors=false, const FFPACK_LU_TAG LuTag=[FfpackSlabRecursive](#))
Extracts a matrix in echelon form from a compact storage $A=L\backslash U$ of rank R obtained by RowEchelonForm or ColumnEchelonForm.
- template<class [Field](#) >
void [getEchelonForm](#) (const [Field](#) &F, const FFLAS::FFLAS_UPLO Uplo, const FFLAS::FFLAS_DIAG diag, const size_t M, const size_t N, const size_t R, const size_t *P, typename [Field::Element_ptr](#) A, const size_t lda, const FFPACK_LU_TAG LuTag=[FfpackSlabRecursive](#))
Cleans up a compact storage $A=L\backslash U$ obtained by RowEchelonForm or ColumnEchelonForm to reveal an echelon form of rank R.
- template<class [Field](#) >
void [getEchelonTransform](#) (const [Field](#) &F, const FFLAS::FFLAS_UPLO Uplo, const FFLAS::FFLAS_DIAG diag, const size_t M, const size_t N, const size_t R, const size_t *P, const size_t *Q, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) T, const size_t ldt, const FFPACK_LU_TAG LuTag=[FfpackSlabRecursive](#))
Extracts a transformation matrix to echelon form from a compact storage $A=L\backslash U$ of rank R obtained by RowEchelonForm or ColumnEchelonForm.

- `template<class Field >`
`void getReducedEchelonForm (const Field &F, const FFLAS::FFLAS_UPLO Uplo, const size_t M, const size_t N, const size_t R, const size_t *P, typename Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr T, const size_t ldt, const bool OnlyNonZeroVectors=false, const FFPACK_LU_TAG LuTag=FFpackSlabRecursive)`
Extracts a matrix in echelon form from a compact storage $A=L\backslash U$ of rank R obtained by ReducedRowEchelonForm or ReducedColumnEchelonForm with transform = true.
- `template<class Field >`
`void getReducedEchelonForm (const Field &F, const FFLAS::FFLAS_UPLO Uplo, const size_t M, const size_t N, const size_t R, const size_t *P, typename Field::Element_ptr A, const size_t lda, const FFPACK_LU_TAG LuTag=FFpackSlabRecursive)`
Cleans up a compact storage $A=L\backslash U$ of rank R obtained by ReducedRowEchelonForm or ReducedColumnEchelonForm with transform = true.
- `template<class Field >`
`void getReducedEchelonTransform (const Field &F, const FFLAS::FFLAS_UPLO Uplo, const size_t M, const size_t N, const size_t R, const size_t *P, const size_t *Q, typename Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr T, const size_t ldt, const FFPACK_LU_TAG LuTag=FFpackSlabRecursive)`
Extracts a transformation matrix to echelon form from a compact storage $A=L\backslash U$ of rank R obtained by RowEchelonForm or ColumnEchelonForm.
- `void PLUQtoEchelonPermutation (const size_t N, const size_t R, const size_t *P, size_t *outPerm)`
Auxiliary routine: determines the permutation that changes a PLUQ decomposition into a echelon form revealing PLUQ decomposition.
- `template<class Field >`
`size_t LTBruhatGen (const Field &Fi, const FFLAS::FFLAS_DIAG diag, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Q)`
LTBruhatGen Suppose A is Left Triangular Matrix This procedure computes the Bruhat Representation of A and return the rank of A.
- `template<class Field >`
`void getLTBruhatGen (const Field &Fi, const size_t N, const size_t r, const size_t *P, const size_t *Q, typename Field::Element_ptr R, const size_t ldr)`
GetLTBruhatGen This procedure Computes the Rank Revealing Matrix based on the Bruhta representation of a Matrix.
- `template<class Field >`
`void getLTBruhatGen (const Field &Fi, const FFLAS::FFLAS_UPLO Uplo, const FFLAS::FFLAS_DIAG diag, const size_t N, const size_t r, const size_t *P, const size_t *Q, typename Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr T, const size_t ldt)`
GetLTBruhatGen This procedure computes the matrix L or U f the Bruhat Representation Suppose that A is the bruhat representation of a matrix.
- `size_t LTQSorder (const size_t N, const size_t r, const size_t *P, const size_t *Q)`
LTQSorder This procedure computes the order of quasiseparability of a matrix.
- `template<class Field >`
`size_t CompressToBlockBiDiagonal (const Field &Fi, const FFLAS::FFLAS_UPLO Uplo, size_t N, size_t s, size_t r, const size_t *P, const size_t *Q, typename Field::Element_ptr A, size_t lda, typename Field::Element_ptr X, size_t ldx, size_t *K, size_t *M, size_t *T)`
CompressToBlockBiDiagonal This procedure compress a compact representation of a row echelon form or column echelon form.
- `template<class Field >`
`void ExpandBlockBiDiagonalToBruhat (const Field &Fi, const FFLAS::FFLAS_UPLO Uplo, size_t N, size_t s, size_t r, typename Field::Element_ptr A, size_t lda, typename Field::Element_ptr X, size_t ldx, size_t NbBlocks, size_t *K, size_t *M, size_t *T)`
ExpandBlockBiDiagonal This procedure expand a compact representation of a row echelon form or column echelon form.
- `void Bruhat2EchelonPermutation (size_t N, size_t R, const size_t *P, const size_t *Q, size_t *M)`
Bruhat2EchelonPermutation (N,R,P,Q) Compute M such that LM or MU is in echelon form where L or U are factors of the Bruhat Rpresentation.
- `size_t * Tinverter (size_t *T, size_t r)`

- `template<class Field >`
`void ComputeRPermutation (const Field &Fi, size_t N, size_t r, const size_t *P, const size_t *Q, size_t *R, size_t *MU, size_t *ML)`
- `template<class Field >`
`void productBruhatxTS (const Field &Fi, size_t N, size_t s, size_t r, const size_t *P, const size_t *Q, const typename Field::Element_ptr Xu, size_t ldu, size_t NbBlocksU, size_t *Ku, size_t *Tu, size_t *MU, const typename Field::Element_ptr XI, size_t ldl, size_t NbBlocksL, size_t *KI, size_t *TI, size_t *ML, typename Field::Element_ptr B, size_t t, size_t ldb, typename Field::Element_ptr C, size_t ldc)`
productBruhatxTS Compute the product between the CRE compact representation of a matrix A and B a tall matrix
- `template<class Field >`
`Field::Element_ptr LQUPTolInverseOfFullRankMinor (const Field &F, const size_t rank, typename Field::Element_ptr A_factors, const size_t lda, const size_t *QtPointer, typename Field::Element_ptr X, const size_t ldx)`
LQUPTolInverseOfFullRankMinor.
- `template<class Field >`
`void RandomNullSpaceVector (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr X, const size_t incX)`
Solve $LX = B$ or $XL = B$ in place.
- `template<class Field >`
`void solveLB (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, const size_t N, const size_t R, typename Field::Element_ptr L, const size_t ldl, const size_t *Q, typename Field::Element_ptr B, const size_t ldb)`
- `template<class Field >`
`void solveLB2 (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, const size_t N, const size_t R, typename Field::Element_ptr L, const size_t ldl, const size_t *Q, typename Field::Element_ptr B, const size_t ldb)`
- `size_t * Tinverter (const size_t *T, size_t r)`
- `template<class Field >`
`void ComputeRPermutation (const Field &Fi, size_t N, size_t r, const size_t *P, const size_t *Q, size_t *R, const size_t *MU, const size_t *ML)`
- `template<class Field >`
`Field::Element_ptr expandLCRE (const Field &Fi, size_t N, size_t s, size_t r, size_t *R, size_t i, typename Field::ConstElement_ptr Xu, size_t ldu, size_t NbBlocksU, const size_t *Ku, const size_t *Tuinv, typename Field::ConstElement_ptr XI, size_t ldl, size_t NbBlocksL, const size_t *KI, const size_t *Tlinv, typename Field::Element_ptr CRE, size_t ldcre)`
Expands an anti-diagonal block of a left triangular matrix from its compact Bruhat representation.
- `template<class Field >`
`void productBruhatxTS (const Field &Fi, size_t N, size_t s, size_t r, size_t t, const size_t *P, const size_t *Q, typename Field::ConstElement_ptr Xu, size_t ldu, size_t NbBlocksU, const size_t *Ku, const size_t *Tu, const size_t *MU, typename Field::ConstElement_ptr XI, size_t ldl, size_t NbBlocksL, const size_t *KI, const size_t *TI, const size_t *ML, typename Field::Element_ptr B, size_t ldb, const typename Field::Element_ptr beta, typename Field::Element_ptr D, size_t ldd)`
Compute the product of a left-triangular quasi-separable matrix A, represented by a compact Bruhat generator, with a dense rectangular matrix $B: C \leftarrow A \times B + \text{beta}C$.
- `template<class Field, class Polynomial >`
`std::list< Polynomial > & Danilevski (const Field &F, std::list< Polynomial > &charp, const size_t N, typename Field::Element_ptr A, const size_t lda)`
- `template<class Field >`
`Field::Element_ptr buildMatrix (const Field &F, typename Field::ConstElement_ptr E, typename Field::ConstElement_ptr C, const size_t lda, const size_t *B, const size_t *T, const size_t me, const size_t mc, const size_t lambda, const size_t mu)`
- `FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr CharPoly (const FFPACK::RNSInteger< FFPACK::rns_double > &F, typename FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr charp, const size_t N, typename FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr A, const size_t lda, Givaro::ZRing< Givaro::Integer >::RandIter &G, const FFPACK_CHARPOLY_TAG CharpTag, size_t degree)`

- `template<> Givaro::Poly1Dom< Givaro::ZRing< Givaro::Integer > >::Element & CharPoly` (const Givaro::Poly1Dom< Givaro::ZRing< Givaro::Integer > > &R, Givaro::Poly1Dom< Givaro::ZRing< Givaro::Integer > >::Element &charp, const size_t N, Givaro::Integer *A, const size_t Ida, Givaro::ZRing< Givaro::Integer >::RandIter &G, const FFPACK_CHARPOLY_TAG CharpTag, size_t degree)
- `template<class PSHelper >`
`FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr & Det` (const FFPACK::RNSInteger< FFPACK::rns_double > &F, typename FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr &det, const size_t N, typename FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr A, const size_t Ida, const PSHelper &psH)
- `template<class PSHelper >`
`Givaro::Integer & Det` (const Givaro::ZRing< Givaro::Integer > &F, Givaro::Integer &det, const size_t N, Givaro::Integer *A, const size_t Ida, const PSHelper &psH, size_t *P, size_t *Q)
- `template<class Field >`
`bool fsytrf_BC_Crout` (const Field &F, const FFLAS::FFLAS_UPLO UpLo, const size_t N, typename Field::Element_ptr A, const size_t Ida, typename Field::Element_ptr Dinv, const size_t incDinv)
- `template<class Field >`
`size_t fsytrf_BC_RL` (const Field &F, const FFLAS::FFLAS_UPLO UpLo, const size_t N, typename Field::Element_ptr A, const size_t Ida, typename Field::Element_ptr Dinv, const size_t incDinv)
- `template<class Field >`
`size_t fsytrf_UP_RPM_BC_RL` (const Field &F, const size_t N, typename Field::Element_ptr A, const size_t Ida, typename Field::Element_ptr Dinv, const size_t incDinv, size_t *P)
- `template<class Field >`
`size_t fsytrf_LOW_RPM_BC_Crout` (const Field &F, const size_t N, typename Field::Element_ptr A, const size_t Ida, typename Field::Element_ptr Dinv, const size_t incDinv, size_t *P)
- `template<class Field >`
`size_t fsytrf_UP_RPM_BC_Crout` (const Field &F, const size_t N, typename Field::Element_ptr A, const size_t Ida, typename Field::Element_ptr Dinv, const size_t incDinv, size_t *P)
- `template<class Field >`
`size_t fsytrf_UP_RPM` (const Field &Fi, const size_t N, typename Field::Element_ptr A, const size_t Ida, typename Field::Element_ptr Dinv, const size_t incDinv, size_t *P, size_t BCThreshold)
- `template<class Field >`
`bool fsytrf_nonunit` (const Field &F, const FFLAS::FFLAS_UPLO UpLo, const size_t N, typename Field::Element_ptr A, const size_t Ida, typename Field::Element_ptr Dinv, const size_t incDinv, FFLAS::ParSeqHelper::Sequential seq, size_t threshold)
- `template<class Field , class Cut , class Param >`
`bool fsytrf_nonunit` (const Field &F, const FFLAS::FFLAS_UPLO UpLo, const size_t N, typename Field::Element_ptr A, const size_t Ida, typename Field::Element_ptr Dinv, const size_t incDinv, FFLAS::ParSeqHelper::Parallel< Cut, Param > par, size_t threshold)
- `template<class Field >`
`size_t fsytrf_RPM` (const Field &F, const FFLAS::FFLAS_UPLO UpLo, const size_t N, typename Field::Element_ptr A, const size_t Ida, size_t *P, size_t threshold)
- `template<class Field >`
`void getTridiagonal` (const Field &F, const size_t N, const size_t R, typename Field::ConstElement_ptr A, const size_t Ida, size_t *P, typename Field::Element_ptr T, const size_t ldt)
- `template<class Field >`
`size_t LUdivine_gauss` (const Field &F, const FFLAS::FFLAS_DIAG Diag, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t Ida, size_t *P, size_t *Q, const FFPACK::FFPACK_LU_TAG LuTag)
- `template<class Field >`
`size_t LUdivine_small` (const Field &F, const FFLAS::FFLAS_DIAG Diag, const FFLAS::FFLAS_TRANSPOSE trans, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t Ida, size_t *P, size_t *Q, const FFPACK::FFPACK_LU_TAG LuTag)
- `template<class Field >`
`size_t LUdivine` (const Field &F, const FFLAS::FFLAS_DIAG Diag, const FFLAS::FFLAS_TRANSPOSE trans, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t Ida, size_t *P, size_t *Q, const FFPACK::FFPACK_LU_TAG LuTag, const size_t cutoff)

- `template<> size_t LUdivine` (const Givaro::Modular< Givaro::Integer > &F, const FFLAS::FFLAS_DIAG Diag, const FFLAS::FFLAS_TRANSPOSE trans, const size_t M, const size_t N, typename Givaro::Integer *A, const size_t lda, size_t *P, size_t *Q, const FFPACK::FFPACK_LU_TAG LuTag, const size_t cutoff)
- `template<class Field >`
void `MonotonicCompress` (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, typename Field::Element_ptr A, const size_t lda, const size_t incA, const size_t *MathP, const size_t R, const size_t maxpiv, const size_t rowstomove, const std::vector< bool > &ispiv)
- `template<class Field >`
void `MonotonicCompressMorePivots` (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, typename Field::Element_ptr A, const size_t lda, const size_t incA, const size_t *MathP, const size_t R, const size_t rowstomove, const size_t lenP)
- `template<class Field >`
void `MonotonicCompressCycles` (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, typename Field::Element_ptr A, const size_t lda, const size_t incA, const size_t *MathP, const size_t lenP)
- `template<class Field >`
void `MonotonicExpand` (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, typename Field::Element_ptr A, const size_t lda, const size_t incA, const size_t *MathP, const size_t R, const size_t maxpiv, const size_t rowstomove, const std::vector< bool > &ispiv)
- `template<class Field >`
void `applyP_block` (const Field &F, const FFLAS::FFLAS_SIDE Side, const FFLAS::FFLAS_TRANSPOSE Trans, const size_t M, const size_t ibeg, const size_t iend, typename Field::Element_ptr A, const size_t lda, const size_t *P)
- `template<class Field >`
void `doApplyS` (const Field &F, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr tmp, const size_t width, const size_t M2, const size_t R1, const size_t R2, const size_t R3, const size_t R4)
- `template<class Field >`
void `MatrixApplyS` (const Field &F, typename Field::Element_ptr A, const size_t lda, const size_t width, const size_t M2, const size_t R1, const size_t R2, const size_t R3, const size_t R4)
- `template<class Field >`
void `MatrixApplyS` (const Field &F, typename Field::Element_ptr A, const size_t lda, const size_t width, const size_t M2, const size_t R1, const size_t R2, const size_t R3, const size_t R4, const FFLAS::ParSeqHelper::Sequential seq)
- `template<class Field, class Cut, class Param >`
void `MatrixApplyS` (const Field &F, typename Field::Element_ptr A, const size_t lda, const size_t width, const size_t M2, const size_t R1, const size_t R2, const size_t R3, const size_t R4, const FFLAS::ParSeqHelper::Parallel< Cut, Param > par)
- `template<class T >`
void `PermApplyS` (T *A, const size_t lda, const size_t width, const size_t M2, const size_t R1, const size_t R2, const size_t R3, const size_t R4)
- `template<class Field >`
void `doApplyT` (const Field &F, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr tmp, const size_t width, const size_t N2, const size_t R1, const size_t R2, const size_t R3, const size_t R4)
- `template<class Field >`
void `MatrixApplyT` (const Field &F, typename Field::Element_ptr A, const size_t lda, const size_t width, const size_t N2, const size_t R1, const size_t R2, const size_t R3, const size_t R4)
- `template<class Field >`
void `MatrixApplyT` (const Field &F, typename Field::Element_ptr A, const size_t lda, const size_t width, const size_t N2, const size_t R1, const size_t R2, const size_t R3, const size_t R4, const FFLAS::ParSeqHelper::Sequential seq)
- `template<class Field, class Cut, class Param >`
void `MatrixApplyT` (const Field &F, typename Field::Element_ptr A, const size_t lda, const size_t width, const size_t N2, const size_t R1, const size_t R2, const size_t R3, const size_t R4, const FFLAS::ParSeqHelper::Parallel< Cut, Param > par)
- `template<class T >`
void `PermApplyT` (T *A, const size_t lda, const size_t width, const size_t N2, const size_t R1, const size_t R2, const size_t R3, const size_t R4)
- void `composePermutationsLLL` (size_t *P1, const size_t *P2, const size_t R, const size_t N)

Computes $P1 \times \text{Diag}(I\_R, P2)$ where $P1$ is a LAPACK and $P2$ a LAPACK permutation and store the result in $P1$ as a LAPACK permutation.

- void [composePermutationsLLM](#) (size_t *MathP, const size_t *P1, const size_t *P2, const size_t R, const size_t N)

Computes $P1 \times \text{Diag}(I\_R, P2)$ where $P1$ is a LAPACK and $P2$ a LAPACK permutation and store the result in $MathP$ as a MathPermutation format.

- void [composePermutationsMLM](#) (size_t *MathP1, const size_t *P2, const size_t R, const size_t N)

Computes $MathP1 \times \text{Diag}(I\_R, P2)$ where $MathP1$ is a MathPermutation and $P2$ a LAPACK permutation and store the result in $MathP1$ as a MathPermutation format.

- void [cyclic_shift_mathPerm](#) (size_t *P, const size_t s)
- template<class [Field](#) >
void [cyclic_shift_row_col](#) (const [Field](#) &F, typename [Field::Element_ptr](#) A, size_t m, size_t n, size_t lda)
- template<class [Field](#) >
void [cyclic_shift_row](#) (const [Field](#) &F, typename [Field::Element_ptr](#) A, size_t m, size_t n, size_t lda)
- template<typename T >
void [cyclic_shift_row](#) (const [RNSIntegerMod](#)< T > &F, typename T::Element_ptr A, size_t m, size_t n, size_t lda)
- template<class [Field](#) >
void [cyclic_shift_col](#) (const [Field](#) &F, typename [Field::Element_ptr](#) A, size_t m, size_t n, size_t lda)
- template<typename T >
void [cyclic_shift_col](#) (const [RNSIntegerMod](#)< T > &F, typename T::Element_ptr A, size_t m, size_t n, size_t lda)
- template<class [Field](#) >
size_t [PLUQ_basecaseV3](#) (const [Field](#) &Fi, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t M, const size_t N, typename [Field::Element](#) *A, const size_t lda, size_t *P, size_t *Q)
- template<class [Field](#) >
size_t [PLUQ_basecaseV2](#) (const [Field](#) &Fi, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t M, const size_t N, typename [Field::Element](#) *A, const size_t lda, size_t *P, size_t *Q)
- template<class [Field](#) >
size_t [PLUQ_basecaseCrout](#) (const [Field](#) &Fi, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, size_t *P, size_t *Q)
- template<class [Field](#) >
size_t [_PLUQ](#) (const [Field](#) &Fi, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, size_t *P, size_t *Q, size_t BCThreshold)
- template<class Cut, class Param >
size_t [PLUQ](#) (const [Givaro::Modular](#)< [Givaro::Integer](#) > &F, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t M, const size_t N, typename [Givaro::Integer](#) *A, const size_t lda, size_t *P, size_t *Q, size_t BCThreshold, [FFLAS::ParSeqHelper::Parallel](#)< Cut, Param > &PSHelper)
- template<class [Field](#) >
void [threads_fgemm](#) (const size_t m, const size_t n, const size_t r, int nbthreads, size_t *W1, size_t *W2, size_t *W3, size_t gamma)
- template<class [Field](#) >
void [threads_ftrsm](#) (const size_t m, const size_t n, int nbthreads, size_t *t1, size_t *t2)
- template<class [Field](#) >
size_t [PLUQ](#) (const [Field](#) &Fi, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, size_t *P, size_t *Q, const [FFLAS::ParSeqHelper::Parallel](#)< [FFLAS::CuttingStrategy::Recursive](#), [FFLAS::StrategyParameter::Threads](#) > &PSHelper)
- template<> [rns_double_elt_ptr_fflas_const_cast](#) ([rns_double_elt_cstptr](#) x)
- template<> [rns_double_elt_cstptr_fflas_const_cast](#) ([rns_double_elt_ptr](#) x)
- template<typename Base_t >
void [cyclic_shift_row_col](#) (Base_t *A, size_t m, size_t n, size_t lda)
- template [INST_OR_DECL](#) void [cyclic_shift_row](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, [FFLAS_ELT](#) *A, size_t m, size_t n, size_t lda)
- template [INST_OR_DECL](#) void [cyclic_shift_col](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, [FFLAS_ELT](#) *A, size_t m, size_t n, size_t lda)

- template [INST_OR_DECL](#) void [applyP](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_SIDE](#) Side, const [FFLAS::FFLAS_TRANSPOSE](#) Trans, const size_t M, const size_t ibeg, const size_t iend, [FFLAS_ELT](#) *A, const size_t lda, const size_t *P)
- template [INST_OR_DECL](#) void [fgetrs](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_SIDE](#) Side, const size_t M, const size_t N, const size_t R, [FFLAS_ELT](#) *A, const size_t lda, const size_t *P, const size_t *Q, [FFLAS_ELT](#) *B, const size_t ldb, int *info)
- template [INST_OR_DECL](#) [FFLAS_ELT](#) * [fgetrs](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_SIDE](#) Side, const size_t M, const size_t N, const size_t NRHS, const size_t R, [FFLAS_ELT](#) *A, const size_t lda, const size_t *P, const size_t *Q, [FFLAS_ELT](#) *X, const size_t idx, const [FFLAS_ELT](#) *B, const size_t ldb, int *info)
- template [INST_OR_DECL](#) size_t [fgesv](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_SIDE](#) Side, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, [FFLAS_ELT](#) *B, const size_t ldb, int *info)
- template [INST_OR_DECL](#) size_t [fgesv](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_SIDE](#) Side, const size_t M, const size_t N, const size_t NRHS, [FFLAS_ELT](#) *A, const size_t lda, [FFLAS_ELT](#) *X, const size_t idx, const [FFLAS_ELT](#) *B, const size_t ldb, int *info)
- template [INST_OR_DECL](#) void [ftrtri](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_UPLO](#) Uplo, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, const size_t threshold)
- template [INST_OR_DECL](#) void [trinv_left](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t N, const [FFLAS_ELT](#) *L, const size_t ldl, [FFLAS_ELT](#) *X, const size_t idx)
- template [INST_OR_DECL](#) void [ftrrm](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_SIDE](#) side, const [FFLAS::FFLAS_DIAG](#) diag, const size_t N, [FFLAS_ELT](#) *A, const size_t lda)
- template [INST_OR_DECL](#) size_t [PLUQ](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *P, size_t *Q)
- template [INST_OR_DECL](#) size_t [LUdivine](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_DIAG](#) Diag, const [FFLAS::FFLAS_TRANSPOSE](#) trans, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *P, size_t *Qt, const [FFPACK_LU_TAG](#) LuTag, const size_t cutoff)
- template [INST_OR_DECL](#) size_t [LUdivine_small](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_DIAG](#) Diag, const [FFLAS::FFLAS_TRANSPOSE](#) trans, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *P, size_t *Q, const [FFPACK_LU_TAG](#) LuTag)
- template [INST_OR_DECL](#) size_t [LUdivine_gauss](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *P, size_t *Q, const [FFPACK_LU_TAG](#) LuTag)
- template [INST_OR_DECL](#) size_t [RowEchelonForm](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *P, size_t *Qt, const bool transform, const [FFPACK_LU_TAG](#) LuTag)
- template [INST_OR_DECL](#) size_t [ReducedRowEchelonForm](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *P, size_t *Qt, const bool transform, const [FFPACK_LU_TAG](#) LuTag)
- template [INST_OR_DECL](#) size_t [ColumnEchelonForm](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *P, size_t *Qt, const bool transform, const [FFPACK_LU_TAG](#) LuTag)
- template [INST_OR_DECL](#) size_t [ReducedColumnEchelonForm](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *P, size_t *Qt, const bool transform, const [FFPACK_LU_TAG](#) LuTag)
- template [INST_OR_DECL](#) [FFLAS_ELT](#) * [Invert](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, [FFLAS_ELT](#) *A, const size_t lda, int &>nullity)
- template [INST_OR_DECL](#) [FFLAS_ELT](#) * [Invert](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const [FFLAS_ELT](#) *A, const size_t lda, [FFLAS_ELT](#) *X, const size_t idx, int &>nullity)
- template [INST_OR_DECL](#) [FFLAS_ELT](#) * [Invert2](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, [FFLAS_ELT](#) *A, const size_t lda, [FFLAS_ELT](#) *X, const size_t idx, int &>nullity)
- template [INST_OR_DECL](#) std::list< Givaro::Poly1Dom< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > >::Element > & [CharPoly](#) (const Givaro::Poly1Dom< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > > &R, std::list< Givaro::Poly1Dom< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > >::Element > &charp, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, [FFLAS_FIELD](#)< [FFLAS_ELT](#) >::RandIter &G, const [FFPACK_CHARPOLY_TAG](#) CharpTag, const size_t degree)

- template [INST_OR_DECL](#) Givaro::Poly1Dom< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > >::Element & [CharPoly](#) (const Givaro::Poly1Dom< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > > &R, Givaro::Poly1Dom< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > >::Element &charp, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, [FFLAS_FIELD](#)< [FFLAS_ELT](#) >::RandIter &G, const FFPACK_CHARPOLY_TAG CharpTag, const size_t degree)
- template [INST_OR_DECL](#) Givaro::Poly1Dom< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > >::Element & [CharPoly](#) (const Givaro::Poly1Dom< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > > &R, Givaro::Poly1Dom< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > >::Element &charp, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, const FFPACK_CHARPOLY_TAG CharpTag, const size_t degree)
- template [INST_OR_DECL](#) std::vector< [FFLAS_ELT](#) > & [MinPoly](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, std::vector< [FFLAS_ELT](#) > &minP, const size_t N, const [FFLAS_ELT](#) *A, const size_t lda, [FFLAS_FIELD](#)< [FFLAS_ELT](#) >::RandIter &G)
- template [INST_OR_DECL](#) std::vector< [FFLAS_ELT](#) > & [MinPoly](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, std::vector< [FFLAS_ELT](#) > &minP, const size_t N, const [FFLAS_ELT](#) *A, const size_t lda)
- template [INST_OR_DECL](#) std::vector< [FFLAS_ELT](#) > & [MatVecMinPoly](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, std::vector< [FFLAS_ELT](#) > &minP, const size_t N, const [FFLAS_ELT](#) *A, const size_t lda, const [FFLAS_ELT](#) *V, const size_t incv)
- template [INST_OR_DECL](#) size_t [KrylovElim](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *P, size_t *Q, const size_t deg, size_t *iterates, size_t *inviterates, const size_t maxit, size_t virt)
- template [INST_OR_DECL](#) size_t [SpecRankProfile](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, const size_t deg, size_t *rankProfile)
- template [INST_OR_DECL](#) size_t [Rank](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda)
- template [INST_OR_DECL](#) bool [IsSingular](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda)
- template [INST_OR_DECL](#) [FFLAS_ELT](#) & [Det](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, [FFLAS_ELT](#) &det, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *P, size_t *Q)
- template [INST_OR_DECL](#) [FFLAS_ELT](#) & [Det](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, [FFLAS_ELT](#) &det, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, const [FFLAS::ParSeqHelper::Parallel](#)< [FFLAS::CuttingStrategy::Recursive](#), [FFLAS::StrategyParameter::Threads](#) > &parH, size_t *P, size_t *Q)
- template [INST_OR_DECL](#) [FFLAS_ELT](#) * [Solve](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, [FFLAS_ELT](#) *A, const size_t lda, [FFLAS_ELT](#) *x, const int incx, const [FFLAS_ELT](#) *b, const int incb)
- template [INST_OR_DECL](#) void [solveLB](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_SIDE](#) Side, const size_t M, const size_t N, const size_t R, [FFLAS_ELT](#) *L, const size_t ldl, const size_t *Q, [FFLAS_ELT](#) *B, const size_t ldb)
- template [INST_OR_DECL](#) void [solveLB2](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_SIDE](#) Side, const size_t M, const size_t N, const size_t R, [FFLAS_ELT](#) *L, const size_t ldl, const size_t *Q, [FFLAS_ELT](#) *B, const size_t ldb)
- template [INST_OR_DECL](#) void [RandomNullSpaceVector](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_SIDE](#) Side, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, [FFLAS_ELT](#) *X, const size_t incX)
- template [INST_OR_DECL](#) size_t [NullSpaceBasis](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_SIDE](#) Side, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, [FFLAS_ELT](#) *NS, size_t &ldn, size_t &NSdim)
- template [INST_OR_DECL](#) size_t [RowRankProfile](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *rkprofile, const FFPACK_LU_TAG LuTag)
- template [INST_OR_DECL](#) size_t [ColumnRankProfile](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *rkprofile, const FFPACK_LU_TAG LuTag)
- template [INST_OR_DECL](#) size_t [RowRankProfileSubmatrixIndices](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *rowindices, size_t *colindices, size_t &R)
- template [INST_OR_DECL](#) size_t [ColRankProfileSubmatrixIndices](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, size_t *rowindices, size_t *colindices, size_t &R)
- template [INST_OR_DECL](#) size_t [RowRankProfileSubmatrix](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const size_t M, const size_t N, [FFLAS_ELT](#) *A, const size_t lda, [FFLAS_ELT](#) *X, size_t &R)

- template [INST_OR_DECL](#) [size_t](#) [ColRankProfileSubmatrix](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [size_t](#) M, const [size_t](#) N, [FFLAS_ELT](#) *A, const [size_t](#) lda, [FFLAS_ELT](#) *&X, [size_t](#) &R)
- template [INST_OR_DECL](#) void [getTriangular](#)< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > > (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_UPLO](#) Uplo, const [FFLAS::FFLAS_DIAG](#) diag, const [size_t](#) M, const [size_t](#) N, const [size_t](#) R, const [FFLAS_ELT](#) *A, const [size_t](#) lda, [FFLAS_ELT](#) *T, const [size_t](#) ldt, const bool OnlyNonZeroVectors)
- template [INST_OR_DECL](#) void [getTriangular](#)< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > > (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_UPLO](#) Uplo, const [FFLAS::FFLAS_DIAG](#) diag, const [size_t](#) M, const [size_t](#) N, const [size_t](#) R, [FFLAS_ELT](#) *A, const [size_t](#) lda)
- template [INST_OR_DECL](#) void [getEchelonForm](#)< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > > (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_UPLO](#) Uplo, const [FFLAS::FFLAS_DIAG](#) diag, const [size_t](#) M, const [size_t](#) N, const [size_t](#) R, const [size_t](#) *P, const [FFLAS_ELT](#) *A, const [size_t](#) lda, [FFLAS_ELT](#) *T, const [size_t](#) ldt, const bool OnlyNonZeroVectors, const [FFPACK_LU_TAG](#) LuTag)
- template [INST_OR_DECL](#) void [getEchelonForm](#)< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > > (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_UPLO](#) Uplo, const [FFLAS::FFLAS_DIAG](#) diag, const [size_t](#) M, const [size_t](#) N, const [size_t](#) R, const [size_t](#) *P, [FFLAS_ELT](#) *A, const [size_t](#) lda, const [FFPACK_LU_TAG](#) LuTag)
- template [INST_OR_DECL](#) void [getEchelonTransform](#)< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > > (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_UPLO](#) Uplo, const [FFLAS::FFLAS_DIAG](#) diag, const [size_t](#) M, const [size_t](#) N, const [size_t](#) R, const [size_t](#) *P, const [size_t](#) *Q, const [FFLAS_ELT](#) *A, const [size_t](#) lda, [FFLAS_ELT](#) *T, const [size_t](#) ldt, const [FFPACK_LU_TAG](#) LuTag)
- template [INST_OR_DECL](#) void [getReducedEchelonForm](#)< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > > (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_UPLO](#) Uplo, const [size_t](#) M, const [size_t](#) N, const [size_t](#) R, const [size_t](#) *P, const [FFLAS_ELT](#) *A, const [size_t](#) lda, [FFLAS_ELT](#) *T, const [size_t](#) ldt, const bool OnlyNonZeroVectors, const [FFPACK_LU_TAG](#) LuTag)
- template [INST_OR_DECL](#) void [getReducedEchelonForm](#)< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > > (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_UPLO](#) Uplo, const [size_t](#) M, const [size_t](#) N, const [size_t](#) R, const [size_t](#) *P, [FFLAS_ELT](#) *A, const [size_t](#) lda, const [FFPACK_LU_TAG](#) LuTag)
- template [INST_OR_DECL](#) void [getReducedEchelonTransform](#)< [FFLAS_FIELD](#)< [FFLAS_ELT](#) > > (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [FFLAS::FFLAS_UPLO](#) Uplo, const [size_t](#) M, const [size_t](#) N, const [size_t](#) R, const [size_t](#) *P, const [size_t](#) *Q, const [FFLAS_ELT](#) *A, const [size_t](#) lda, [FFLAS_ELT](#) *T, const [size_t](#) ldt, const [FFPACK_LU_TAG](#) LuTag)
- template [INST_OR_DECL](#) [FFLAS_ELT](#) * [LQUPtoInverseOfFullRankMinor](#) (const [FFLAS_FIELD](#)< [FFLAS_ELT](#) > &F, const [size_t](#) rank, [FFLAS_ELT](#) *A_factors, const [size_t](#) lda, const [size_t](#) *QtPointer, [FFLAS_ELT](#) *X, const [size_t](#) ldx)
- template<class T, class CT = const T>
T [fflas_const_cast](#) (CT x)
- [Failure](#) & [failure](#) ()
- template<class T >
bool [isOdd](#) (const T &a)
- bool [isOdd](#) (const float &a)
- bool [isOdd](#) (const double &a)
- template<class [Field](#), class [Randlter](#) >
[Field::Element_ptr](#) [NonZeroRandomMatrix](#) (const [Field](#) &F, [size_t](#) m, [size_t](#) n, typename [Field::Element_ptr](#) A, [size_t](#) lda, [Randlter](#) &G)
Random non-zero Matrix.
- template<class [Field](#), class [Randlter](#) >
[Field::Element_ptr](#) [NonZeroRandomMatrix](#) (const [Field](#) &F, [size_t](#) m, [size_t](#) n, typename [Field::Element_ptr](#) A, [size_t](#) lda)
Random non-zero Matrix.
- template<class [Field](#), class [Randlter](#) >
[Field::Element_ptr](#) [RandomMatrix](#) (const [Field](#) &F, [size_t](#) m, [size_t](#) n, typename [Field::Element_ptr](#) A, [size_t](#) lda, [Randlter](#) &G)
Random Matrix.
- template<class [Field](#) >
[Field::Element_ptr](#) [RandomMatrix](#) (const [Field](#) &F, [size_t](#) m, [size_t](#) n, typename [Field::Element_ptr](#) A, [size_t](#) lda)

Random Matrix.

- template<class [Field](#) , class RandIter >
[Field::Element_ptr](#) RandomTriangularMatrix (const [Field](#) &F, size_t m, size_t n, const [FFLAS::FFLAS_UPLO](#) UpLo, const [FFLAS::FFLAS_DIAG](#) Diag, bool nonsingular, typename [Field::Element_ptr](#) A, size_t lda, RandIter &G)

Random Triangular Matrix.

- template<class [Field](#) >
[Field::Element_ptr](#) RandomTriangularMatrix (const [Field](#) &F, size_t m, size_t n, const [FFLAS::FFLAS_UPLO](#) UpLo, const [FFLAS::FFLAS_DIAG](#) Diag, bool nonsingular, typename [Field::Element_ptr](#) A, size_t lda)

Random Triangular Matrix.

- size_t RandInt (size_t a, size_t b)
- template<class [Field](#) , class RandIter >
[Field::Element_ptr](#) RandomSymmetricMatrix (const [Field](#) &F, size_t n, bool nonsingular, typename [Field::Element_ptr](#) A, size_t lda, RandIter &G)

Random Symmetric Matrix.

- template<class [Field](#) , class RandIter >
[Field::Element_ptr](#) RandomMatrixWithRank (const [Field](#) &F, size_t m, size_t n, size_t r, typename [Field::Element_ptr](#) A, size_t lda, RandIter &G)

Random Matrix with prescribed rank.

- template<class [Field](#) >
[Field::Element_ptr](#) RandomMatrixWithRank (const [Field](#) &F, size_t m, size_t n, size_t r, typename [Field::Element_ptr](#) A, size_t lda)

Random Matrix with prescribed rank.

- size_t * RandomIndexSubset (size_t N, size_t R, size_t *P)
Pick uniformly at random a sequence of R distinct elements from the set $\{0, \dots, N - 1\}$ using Knuth's shuffle.
- size_t * RandomPermutation (size_t N, size_t *P)
Pick uniformly at random a permutation of size N stored in LAPACK format using Knuth's shuffle.
- void RandomRankProfileMatrix (size_t M, size_t N, size_t R, size_t *rows, size_t *cols)
Pick uniformly at random an R -subpermutation of dimension $M \times N$: a matrix with only R non-zeros equal to one, in a random rook placement.
- void swapval (size_t k, size_t N, size_t *P, size_t val)
- void RandomSymmetricRankProfileMatrix (size_t N, size_t R, size_t *rows, size_t *cols)
Pick uniformly at random a symmetric R -subpermutation of dimension $N \times N$: a symmetric matrix with only R non-zeros, all equal to one, in a random rook placement.
- void RandomLTQSRankProfileMatrix (size_t n, size_t r, size_t t, size_t *rows, size_t *cols)

- template<class [Field](#) , class RandIter >
[Field::Element_ptr](#) RandomMatrixWithRankandRPM (const [Field](#) &F, size_t M, size_t N, size_t R, typename [Field::Element_ptr](#) A, size_t lda, const size_t *RRP, const size_t *CRP, RandIter &G)

Random Matrix with prescribed rank and rank profile matrix Creates an $m \times n$ matrix with random entries and rank r .

- template<class [Field](#) >
[Field::Element_ptr](#) RandomMatrixWithRankandRPM (const [Field](#) &F, size_t M, size_t N, size_t R, typename [Field::Element_ptr](#) A, size_t lda, const size_t *RRP, const size_t *CRP)

Random Matrix with prescribed rank and rank profile matrix Creates an $m \times n$ matrix with random entries and rank r .

- template<class [Field](#) , class RandIter >
[Field::Element_ptr](#) RandomSymmetricMatrixWithRankandRPM (const [Field](#) &F, size_t N, size_t R, typename [Field::Element_ptr](#) A, size_t lda, const size_t *RRP, const size_t *CRP, RandIter &G)

Random Symmetric Matrix with prescribed rank and rank profile matrix Creates an $n \times n$ symmetric matrix with random entries and rank r .

- template<class [Field](#) >
[Field::Element_ptr](#) RandomSymmetricMatrixWithRankandRPM (const [Field](#) &F, size_t M, size_t N, size_t R, typename [Field::Element_ptr](#) A, size_t lda, const size_t *RRP, const size_t *CRP)

Random Symmetric Matrix with prescribed rank and rank profile matrix Creates an $n \times n$ symmetric matrix with random entries and rank r .

- `template<class Field , class Randlter >`
`Field::Element_ptr RandomMatrixWithRankandRandomRPM` (const `Field` &F, size_t M, size_t N, size_t R, typename `Field::Element_ptr` A, size_t lda, Randlter &G)
Random Matrix with prescribed rank, with random rank profile matrix Creates an $m \times n$ matrix with random entries, rank r and with a rank profile matrix chosen uniformly at random.
- `template<class Field >`
`Field::Element_ptr RandomMatrixWithRankandRandomRPM` (const `Field` &F, size_t M, size_t N, size_t R, typename `Field::Element_ptr` A, size_t lda)
Random Matrix with prescribed rank, with random rank profile matrix Creates an $m \times n$ matrix with random entries, rank r and with a rank profile matrix chosen uniformly at random.
- `template<class Field , class Randlter >`
`Field::Element_ptr RandomSymmetricMatrixWithRankandRandomRPM` (const `Field` &F, size_t N, size_t R, typename `Field::Element_ptr` A, size_t lda, Randlter &G)
Random Symmetric Matrix with prescribed rank, with random rank profile matrix Creates an $n \times n$ matrix with random entries, rank r and with a rank profile matrix chosen uniformly at random.
- `template<class Field >`
`Field::Element_ptr RandomSymmetricMatrixWithRankandRandomRPM` (const `Field` &F, size_t N, size_t R, typename `Field::Element_ptr` A, size_t lda)
Random Symmetric Matrix with prescribed rank, with random rank profile matrix Creates an $n \times n$ matrix with random entries, rank r and with a rank profile matrix chosen uniformly at random.
- `template<class Field >`
`Field::Element_ptr RandomMatrixWithDet` (const `Field` &F, size_t n, const typename `Field::Element` d, type-name `Field::Element_ptr` A, size_t lda)
Random Matrix with prescribed det.
- `template<class Field , class Randlter >`
`Field::Element_ptr RandomMatrixWithDet` (const `Field` &F, size_t n, const typename `Field::Element` d, type-name `Field::Element_ptr` A, size_t lda, Randlter &G)
Random Matrix with prescribed det.
- `template<class Field , class Randlter >`
`Field::Element_ptr RandomLTQSMMatrixWithRankandQSorder` (`Field` &F, size_t n, size_t r, size_t t, typename `Field::Element_ptr` A, size_t lda, Randlter &G)
- `template<typename Field >`
`Field * chooseField` (Givaro::Integer q, uint64_t b, uint64_t seed)
- `template<> Givaro::ZRing< int32_t > * chooseField< Givaro::ZRing< int32_t > >` (Givaro::Integer q, uint64_t b, uint64_t seed)
- `template<> Givaro::ZRing< int64_t > * chooseField< Givaro::ZRing< int64_t > >` (Givaro::Integer q, uint64_t b, uint64_t seed)
- `template<> Givaro::ZRing< float > * chooseField< Givaro::ZRing< float > >` (Givaro::Integer q, uint64_t b, uint64_t seed)
- `template<> Givaro::ZRing< double > * chooseField< Givaro::ZRing< double > >` (Givaro::Integer q, uint64_t b, uint64_t seed)

11.21.1 Detailed Description

Finite Field PACK Set of elimination based routines for dense linear algebra.

This namespace enlarges the set of BLAS routines of the class `FFLAS`, with higher level routines based on elimination.

11.21.2 Typedef Documentation

11.21.2.1 Checker_PLUQ

```
template<class Field >
using Checker_PLUQ = FFLAS::Checker_Empty<Field>
```

11.21.2.2 Checker_Det

```
template<class Field >
using Checker_Det = FFLAS::Checker_Empty<Field>
```

11.21.2.3 Checker_invert

```
template<class Field >
using Checker_invert = FFLAS::Checker_Empty<Field>
```

11.21.2.4 Checker_charpoly

```
template<class Field , class Polynomial >
using Checker_charpoly = FFLAS::Checker_Empty<Field>
```

11.21.2.5 ForceCheck_PLUQ

```
template<class Field >
using ForceCheck_PLUQ = CheckerImplem_PLUQ<Field>
```

11.21.2.6 ForceCheck_Det

```
template<class Field >
using ForceCheck_Det = CheckerImplem_Det<Field>
```

11.21.2.7 ForceCheck_invert

```
template<class Field >
using ForceCheck_invert = CheckerImplem_invert<Field>
```

11.21.2.8 ForceCheck_charpoly

```
template<class Field , class Polynomial >
using ForceCheck_charpoly = CheckerImplem_charpoly<Field,Polynomial>
```

11.21.3 Function Documentation

11.21.3.1 LAPACKPerm2MathPerm()

```
void LAPACKPerm2MathPerm (
    size_t * MathP,
    const size_t * LapackP,
    const size_t N ) [inline]
```

Conversion of a permutation from LAPACK format to Math format.

11.21.3.2 MathPerm2LAPACKPerm()

```
void MathPerm2LAPACKPerm (
    size_t * LapackP,
    const size_t * MathP,
    const size_t N ) [inline]
```

Conversion of a permutation from Maths format to LAPACK format.

11.21.3.3 applyP() [1/4]

```
template<class Field >
void applyP (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const FFLAS::FFLAS_TRANSPOSE Trans,
    const size_t M,
    const size_t ibeg,
    const size_t iend,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t * P ) [inline]
```

Computes $P1 \times \text{Diag}(I_R, P2)$ where $P1$ is a LAPACK and $P2$ a LAPACK permutation and store the result in $P1$ as a LAPACK permutation.

Parameters

in, out	$P1$	a LAPACK permutation of size N
	$P2$	a LAPACK permutation of size N-R

Applies a permutation P to the matrix A . Apply a permutation P , stored in the LAPACK format (a sequence of transpositions) between indices $ibeg$ and $iend$ of P to $(iend-ibeg)$ vectors of size M stored in A (as column for NoTrans and rows for Trans). $Side == \text{FFLAS::FflasLeft}$ for row permutation $Side == \text{FFLAS::FflasRight}$ for a column permutation $Trans == \text{FFLAS::FflasTrans}$ for the inverse permutation of P

Parameters

F	base field
$Side$	decides if rows (FflasLeft) or columns (FflasRight) are permuted
$Trans$	decides if the matrix is seen as columns (FflasTrans) or rows (FflasNoTrans)
M	size of the elements to permute
$ibeg$	first index to consider in P
$iend$	last index to consider in P
A	input matrix
lda	leading dimension of A
P	permutation in LAPACK format
psh	(optional): a sequential or parallel helper, to choose between sequential or parallel execution

Warning

not sure the submatrix is still a permutation and the one we expect in all cases... examples for iend=2, ibeg=1 and P=[2,2,2]

11.21.3.4 applyP() [2/4]

```
template<class Field >
void applyP (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const FFLAS::FFLAS_TRANSPOSE Trans,
    const size_t m,
    const size_t ibeg,
    const size_t iend,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t * P,
    const FFLAS::ParSeqHelper::Sequential seq ) [inline]
```

11.21.3.5 applyP() [3/4]

```
template<class Field , class Cut , class Param >
void applyP (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const FFLAS::FFLAS_TRANSPOSE Trans,
    const size_t m,
    const size_t ibeg,
    const size_t iend,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t * P,
    const FFLAS::ParSeqHelper::Parallel< Cut, Param > par ) [inline]
```

11.21.3.6 MonotonicApplyP()

```
template<class Field >
void MonotonicApplyP (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const FFLAS::FFLAS_TRANSPOSE Trans,
    const size_t M,
    const size_t ibeg,
    const size_t iend,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t * P,
    const size_t R ) [inline]
```

Apply a R-monotonically increasing permutation P, to the matrix A.

MonotonicApplyP Apply a permutation defined by the first R entries of the vector P (the pivots).

The permutation represented by P is defined as follows:

- the first R values of P is a LAPACK representation (a sequence of transpositions)
- the remaining $iend-ibeg-R$ values of the permutation are in a monotonically increasing progression $Side==FFLAS::FflasLeft$ for row permutation $Side==FFLAS::FflasRight$ for a column permutation $Trans==FFLAS::FflasTrans$ for the inverse permutation of P

Parameters

<i>F</i>	base field
<i>Side</i>	selects if it is a row (FflasLeft) or column (FflasRight) permutation
<i>Trans</i>	inverse permutation (FflasTrans/NoTrans)
<i>M</i>	
<i>ibeg</i>	
<i>iend</i>	
<i>A</i>	input matrix
<i>lda</i>	leading dimension of A
<i>P</i>	LAPACK permuation
<i>R</i>	first values of P

The non pivot elements, are located in montonically increasing order.

11.21.3.7 fgetrs() [1/4]

```
template<class Field >
void fgetrs (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    const size_t R,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t * P,
    const size_t * Q,
    typename Field::Element_ptr B,
    const size_t ldb,
    int * info )
```

Solve the system $AX = B$ or $XA = B$.

Solving using the PLUQ decomposition of A already computed inplace with PLUQ (FFLAS::FflasNonUnit). Version for A square. If A is rank deficient, a solution is returned if the system is consistent, Otherwise an info is 1

Parameters

<i>F</i>	base field
<i>Side</i>	Determine wheter the resolution is left (FflasLeft) or right (FflasRight) looking.
<i>M</i>	row dimension of B
<i>N</i>	col dimension of B
<i>R</i>	rank of A
<i>A</i>	input matrix
<i>lda</i>	leading dimension of A
<i>P</i>	row permutation of the PLUQ decomposition of A

Parameters

<i>Q</i>	column permutation of the PLUQ decomposition of A
<i>B</i>	Right/Left hand side matrix. Initially stores B, finally stores the solution X.
<i>ldb</i>	leading dimension of B
<i>info</i>	Success of the computation: 0 if successfull, >0 if system is inconsistent

11.21.3.8 fgetrs() [2/4]

```
template<class Field >
Field::Element_ptr fgetrs (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    const size_t NRHS,
    const size_t R,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t * P,
    const size_t * Q,
    typename Field::Element_ptr X,
    const size_t ldx,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    int * info )
```

Solve the system $A X = B$ or $X A = B$.

Solving using the PLUQ decomposition of A already computed inplace with PLUQ(FFLAS::FflasNonUnit). Version for A rectangular. If A is rank deficient, a solution is returned if the system is consistent, Otherwise an info is 1

Parameters

<i>F</i>	base field
<i>Side</i>	Determine wheter the resolution is left (FflasLeft) or right (FflasRight) looking.
<i>M</i>	row dimension of A
<i>N</i>	col dimension of A
<i>NRHS</i>	number of columns (if Side = FFLAS::FflasLeft) or row (if Side = FFLAS::FflasRight) of the matrices X and B
<i>R</i>	rank of A
<i>A</i>	input matrix
<i>lda</i>	leading dimension of A
<i>P</i>	row permutation of the PLUQ decomposition of A
<i>Q</i>	column permutation of the PLUQ decomposition of A
<i>X</i>	solution matrix
<i>ldx</i>	leading dimension of X
<i>B</i>	Right/Left hand side matrix.
<i>ldb</i>	leading dimension of B
<i>info</i>	Succes of the computation: 0 if successfull, >0 if system is inconsistent

11.21.3.9 fgesv() [1/4]

```
template<class Field >
size_t fgesv (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb,
    int * info )
```

Square system solver.

Parameters

<i>F</i>	The computation domain
<i>Side</i>	Determine wheter the resolution is left (FflasLeft) or right (FflasRight) looking
<i>M</i>	row dimension of B
<i>N</i>	col dimension of B
<i>A</i>	input matrix
<i>lda</i>	leading dimension of A
<i>B</i>	Right/Left hand side matrix. Initially contains B, finally contains the solution X.
<i>ldb</i>	leading dimension of B
<i>info</i>	Success of the computation: 0 if successfull, >0 if system is inconsistent

Returns

the rank of the system

Solve the system $A X = B$ or $X A = B$. Version for A square. If A is rank deficient, a solution is returned if the system is consistent, Otherwise an info is 1

11.21.3.10 fgesv() [2/4]

```
template<class Field >
size_t fgesv (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    const size_t NRHS,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr X,
    const size_t ldX,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    int * info )
```

Rectangular system solver.

Parameters

<i>F</i>	The computation domain
<i>Side</i>	Determine wheter the resolution is left (FflasLeft) or right (FflasRight) looking
<i>M</i>	row dimension of A
<i>N</i>	col dimension of A
<i>NRHS</i>	number of columns (if Side = FFLAS::FflasLeft) or row (if Side = FFLAS::FflasRight) of the matrices X and B
<i>A</i>	input matrix
<i>lda</i>	leading dimension of A
<i>B</i>	Right/Left hand side matrix. Initially contains B, finally contains the solution X.
<i>ldb</i>	leading dimension of B
<i>X</i>	
<i>ldx</i>	
<i>info</i>	Success of the computation: 0 if successfull, >0 if system is inconsistent

Returns

the rank of the system

Solve the system $A X = B$ or $X A = B$. Version for A square. If A is rank deficient, a solution is returned if the system is consistent, Otherwise an info is 1

11.21.3.11 `fttrtri()` [1/2]

```
template<class Field >
void fttrtri (
    const Field & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t threshold = __FFLASFFPACK_FTRTRI_THRESHOLD )
```

Compute the inverse of a triangular matrix.

Parameters

<i>F</i>	base field
<i>Uplo</i>	whether the matrix is upper or lower triangular
<i>Diag</i>	whether the matrix is unit diagonal (FflasUnit/NoUnit)
<i>N</i>	input matrix order
<i>A</i>	the input matrix
<i>lda</i>	leading dimension of A

11.21.3.12 `trinv_left()` [1/2]

```
template<class Field >
```

```

void trinv_left (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr L,
    const size_t ldl,
    typename Field::Element_ptr X,
    const size_t ldx )

```

11.21.3.13 ftrtrm() [1/2]

```

template<class Field >
void ftrtrm (
    const Field & F,
    const FFLAS::FFLAS_SIDE side,
    const FFLAS::FFLAS_DIAG diag,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda )

```

Compute the product of two triangular matrices of opposite shape.

Product UL or LU of the upper, resp lower triangular matrices U and L stored one above the other in the square matrix A.

Parameters

<i>F</i>	base field
<i>Side</i>	set to FflasLeft to compute the product UL, FflasRight to compute LU
<i>diag</i>	whether the matrix U is unit diagonal (FflasUnit/NoUnit)
<i>N</i>	input matrix order
<i>A</i>	the input matrix
<i>lda</i>	leading dimension of A

11.21.3.14 ftrstr()

```

template<class Field >
void ftrstr (
    const Field & F,
    const FFLAS::FFLAS_SIDE side,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG diagA,
    const FFLAS::FFLAS_DIAG diagB,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb,
    const size_t threshold = __FFLASFFPACK_FTRSTR_THRESHOLD ) [inline]

```

Solve a triangular system with a triangular right hand side of the same shape.

Parameters

<i>F</i>	base field
<i>Side</i>	set to FflasLeft to compute $U1^{-1} * U2$ or $L1^{-1} * L2$, FflasRight to compute $U1 * U2^{-1}$ or $L1 * L2^{-1}$
<i>Uplo</i>	whether the matrix A is upper or lower triangular
<i>diag1</i>	whether the matrix U1 or L2 is unit diagonal (FflasUnit/NoUnit)
<i>diag2</i>	whether the matrix U2 or L2 is unit diagonal (FflasUnit/NoUnit)
<i>N</i>	order of the input matrices
<i>A</i>	the input matrix to be inverted (U1 or L1)
<i>lda</i>	leading dimension of A
<i>B</i>	the input right hand side (U2 or L2)
<i>ldb</i>	leading dimension of B

11.21.3.15 ftrssyr2k()

```
template<class Field >
void ftrssyr2k (
    const Field & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG diagA,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr B,
    const size_t ldb,
    const size_t threshold = __FFLASFFPACK_FTRSSYR2K_THRESHOLD ) [inline]
```

Solve a triangular system in a symmetric sum: find B upper/lower triangular such that $A^T B + B^T A = C$ where C is symmetric.

C is overwritten by B.

Parameters

	<i>F</i>	base field
	<i>Side</i>	set to FflasLeft to compute $U1^{-1} * U2$ or $L1^{-1} * L2$, FflasRight to compute $U1 * U2^{-1}$ or $L1 * L2^{-1}$
	<i>Uplo</i>	whether the matrix A is upper or lower triangular
	<i>diagA</i>	whether the matrix A is unit diagonal (FflasUnit/NoUnit)
	<i>N</i>	order of the input matrices
	<i>A</i>	the input matrix
	<i>lda</i>	leading dimension of A
<i>in, out</i>	<i>B</i>	the input right hand side where the output is written
	<i>ldb</i>	leading dimension of B

11.21.3.16 fsytrf() [1/3]

```
template<class Field >
bool fsytrf (
```

```

const Field & F,
const FFLAS::FFLAS_UPLO UpLo,
const size_t N,
typename Field::Element_ptr A,
const size_t lda,
const size_t threshold = __FFLASFFPACK_FSYTRF_THRESHOLD )

```

Triangular factorization of symmetric matrices.

Parameters

	F	The computation domain
	$UpLo$	Determine wheter to store the upper (FflasUpper) or lower (FflasLower) triangular factor
	N	order of the matrix A
in, out	A	input matrix
	lda	leading dimension of A

Returns

false if the A does not have generic rank profile, making the computation fail.

Compute the a triangular factorization of the matrix A: $A = L \times D \times L^T$ if UpLo = FflasLower or $A = U^T \times D \times U$ otherwise. D is a diagonal matrix. The matrices L and U are unit diagonal lower (resp. upper) triangular and overwrite the input matrix A. The matrix D is stored on the diagonal of A, as the diagonal of L or U is known to be all ones. If A does not have generic rank profile, the LDLT or UTDU factorizations is not defined, and the algorithm returns false.

11.21.3.17 fsytrf() [2/3]

```

template<class Field >
bool fsytrf (
    const Field & F,
    const FFLAS::FFLAS_UPLO UpLo,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    const FFLAS::ParSeqHelper::Sequential seq,
    const size_t threshold = __FFLASFFPACK_FSYTRF_THRESHOLD ) [inline]

```

11.21.3.18 fsytrf() [3/3]

```

template<class Field , class Cut , class Param >
bool fsytrf (
    const Field & F,
    const FFLAS::FFLAS_UPLO UpLo,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    const FFLAS::ParSeqHelper::Parallel< Cut, Param > par,
    const size_t threshold = __FFLASFFPACK_FSYTRF_THRESHOLD ) [inline]

```

11.21.3.19 fsytrf_nonunit() [1/3]

```
template<class Field >
bool fsytrf_nonunit (
    const Field & F,
    const FFLAS::FFLAS_UPLO UpLo,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr D,
    const size_t incD,
    const size_t threshold = __FFLASFFPACK_FSYTRF_THRESHOLD )
```

Triangular factorization of symmetric matrices.

Parameters

	F	The computation domain
	$UpLo$	Determine wheter to store the upper (FflasUpper) or lower (FflasLower) triangular factor
	N	order of the matrix A
in, out	A	input matrix
in, out	D	
	lda	leading dimension of A

Returns

false if the A does not have generic rank profile, making the computation fail.

Compute the a triangular factorization of the matrix A: $A = L \times D_{inv} \times L^T$ if UpLo = FflasLower or $A = U^T \times D \times U$ otherwise. D is a diagonal matrix. The matrices L and U are lower (resp. upper) triangular and overwrite the input matrix A. The matrix D need to be stored separately, as the diagonal of L or U are not unit. If A does not have generic rank profile, the LDLT or UTDU factorizations is not defined, and the algorithm returns false.

11.21.3.20 PLUQ() [1/6]

```
template<class Field >
size_t PLUQ (
    const Field & F,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q ) [inline]
```

Compute a PLUQ factorization of the given matrix.

Return its rank. The permutations P and Q are represented using LAPACK's convention.

Parameters

F	base field

Parameters

<i>Diag</i>	whether U should have a unit diagonal (FflasUnit) or not (FflasNoUnit)
<i>M</i>	matrix row dimension
<i>N</i>	matrix column dimension
<i>A</i>	input matrix
<i>lda</i>	leading dimension of A
<i>P</i>	the row permutation
<i>Q</i>	the column permutation

Returns

the rank of A

Bibliography

- Dumas J-G., Pernet C., and Sultan Z. *Simultaneous computation of the row and column rank profiles*, ISSAC'13, 2013

11.21.3.21 pPLUQ()

```
template<class Field >
size_t pPLUQ (
    const Field & F,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q ) [inline]
```

11.21.3.22 PLUQ() [2/6]

```
template<class Field >
size_t PLUQ (
    const Field & F,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    const FFLAS::ParSeqHelper::Sequential & PSHelper,
    size_t BCThreshold = __FFLASFFPACK_PLUQ_THRESHOLD ) [inline]
```

11.21.3.23 PLUQ() [3/6]

```
template<class Field , class Cut , class Param >
size_t PLUQ (
    const Field & F,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    const FFLAS::ParSeqHelper::Parallel< Cut, Param > & PSHelper )
```

11.21.3.24 LUdivine() [1/4]

```
template<class Field >
size_t LUdivine (
    const Field & F,
    const FFLAS::FFLAS_DIAG Diag,
    const FFLAS::FFLAS_TRANSPOSE trans,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const FFPACK_LU_TAG LuTag = FfpackSlabRecursive,
    const size_t cutoff = __FFLASFFPACK_LUDIVINE_THRESHOLD )
```

Compute the CUP or PLE factorization of the given matrix.

Using a block algorithm and return its rank. The permutations P and Q are represented using LAPACK's convention.

Parameters

<i>F</i>	base field
<i>Diag</i>	whether the transformation matrix (U of the CUP, L of the PLE) should have a unit diagonal (FflasUnit) or not (FflasNoUnit)
<i>trans</i>	whether to compute the CUP decomposition (FflasNoTrans) or the PLE decomposition (FflasTrans)
<i>M</i>	matrix row dimension
<i>N</i>	matrix column dimension
<i>A</i>	input matrix
<i>lda</i>	leading dimension of A
<i>P</i>	the factor of CUP or PLE
<i>Q</i>	a permutation indicating the pivot position in the echelon form C or E in its first r positions
<i>LuTag</i>	flag for setting the earling termination if the matrix is singular
<i>cutoff</i>	threshold to basecase

Returns

the rank of A

Bibliography

- Jeannerod C-P, Pernet, C. and Storjohann, A. *Rank-profile revealing Gaussian elimination and the CUP matrix decomposition*, J. of Symbolic Comp., 2013
- Pernet C, Brassel M *LUdivine, une divine factorisation LU*, 2002

11.21.3.25 ColumnEchelonForm() [1/3]

```
template<class Field >
size_t ColumnEchelonForm (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    bool transform = false,
    const FFPACK_LU_TAG LuTag = FfpackSlabRecursive ) [inline]
```

Compute the Column Echelon form of the input matrix in-place.

If $LuTag == FfpackTileRecursive$, then after the computation $A = [M \setminus V]$ such that $AU = C$ is a column echelon decomposition of A , with $U = P^T [V]$ and $C = M + Q [I_r] [0 \text{ } I_{n-r}] [0]$ If $LuTag == FfpackTileRecursive$ then $A = [N \setminus V]$ such that the same holds with $M = Q N$

$Qt = Q^T$ If $transform=false$, the matrix V is not computed. See also test-colechelon for an example of use

Parameters

	F	base field
	M	number of rows
	N	number of columns
in	A	input matrix
	lda	leading dimension of A
	P	the column permutation
	Qt	the row position of the pivots in the echelon form
	$transform$	decides whether V is computed
	$LuTag$	chooses the elimination algorithm. SlabRecursive for LUdivine, TileRecursive for PLUQ

11.21.3.26 pColumnEchelonForm()

```
template<class Field >
size_t pColumnEchelonForm (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    bool transform = false,
    size_t numthreads = 0,
    const FFPACK_LU_TAG LuTag = FfpackTileRecursive ) [inline]
```

11.21.3.27 ColumnEchelonForm() [2/3]

```
template<class Field , class PSHelper >
size_t ColumnEchelonForm (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const bool transform,
    const FFPACK_LU_TAG LuTag,
    const PSHelper & psH ) [inline]
```

11.21.3.28 RowEchelonForm() [1/3]

```
template<class Field >
size_t RowEchelonForm (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const bool transform = false,
    const FFPACK_LU_TAG LuTag = FfpackSlabRecursive ) [inline]
```

Compute the Row Echelon form of the input matrix in-place.

If $\text{LuTag} == \text{FfpackTileRecursive}$, then after the computation $A = [L \setminus M]$ such that $XA = R$ is a row echelon decomposition of A , with $X = [L \ 0] P$ and $R = M + [I_r \ 0] Q^T [In-r]$ If $\text{LuTag} == \text{FfpackTileRecursive}$ then $A = [L \setminus N]$ such that the same holds with $M = N Q^T Qt = Q^T$ If $\text{transform} = \text{false}$, the matrix L is not computed. See also `test-rowechelon` for an example of use

Parameters

	F	base field
	M	number of rows
	N	number of columns
in	A	the input matrix
	lda	leading dimension of A
	P	the row permutation
	Qt	the column position of the pivots in the echelon form
	$transform$	decides whether L is computed
	$LuTag$	chooses the elimination algorithm. SlabRecursive for LUdivine, TileRecursive for PLUQ

11.21.3.29 pRowEchelonForm()

```
template<class Field >
size_t pRowEchelonForm (
```

```

const Field & F,
const size_t M,
const size_t N,
typename Field::Element_ptr A,
const size_t lda,
size_t * P,
size_t * Qt,
const bool transform = false,
size_t numthreads = 0,
const FFPACK_LU_TAG LuTag = FfpackTileRecursive ) [inline]

```

11.21.3.30 RowEchelonForm() [2/3]

```

template<class Field , class PSHelper >
size_t RowEchelonForm (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const bool transform,
    const FFPACK_LU_TAG LuTag,
    const PSHelper & psH ) [inline]

```

11.21.3.31 ReducedColumnEchelonForm() [1/3]

```

template<class Field >
size_t ReducedColumnEchelonForm (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const bool transform = false,
    const FFPACK_LU_TAG LuTag = FfpackSlabRecursive ) [inline]

```

Compute the Reduced Column Echelon form of the input matrix in-place.

After the computation $A = [V]$ such that $AX = R$ is a reduced col echelon $[M \ 0]$ decomposition of A , where $X = P^T [V]$ and $R = Q [I_r] [0 \ I_{n-r}] [M \ 0] Q^T = Q^T$ If transform=false, the matrix X is not computed and the matrix $A = R$

Parameters

	F	base field
	M	number of rows
	N	number of columns
in	A	input matrix
	lda	leading dimension of A
	P	the column permutation
	Qt	the row position of the pivots in the echelon form
	$transform$	decides whether X is computed
Generated on Wed Nov 29 2023 00:00:00 for FFPACK by Doxygen		
	$LuTag$	chooses the elimination algorithm. SlabRecursive for LUdivine, TileRecursive for PLUQ

11.21.3.32 pReducedColumnEchelonForm()

```
template<class Field >
size_t pReducedColumnEchelonForm (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const bool transform = false,
    size_t numthreads = 0,
    const FFPACK_LU_TAG LuTag = FfpackTileRecursive ) [inline]
```

11.21.3.33 ReducedColumnEchelonForm() [2/3]

```
template<class Field , class PSHelper >
size_t ReducedColumnEchelonForm (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const bool transform,
    const FFPACK_LU_TAG LuTag,
    const PSHelper & psH ) [inline]
```

11.21.3.34 ReducedRowEchelonForm() [1/3]

```
template<class Field >
size_t ReducedRowEchelonForm (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const bool transform = false,
    const FFPACK_LU_TAG LuTag = FfpackSlabRecursive ) [inline]
```

Compute the Reduced Row Echelon form of the input matrix in-place.

After the computation $A = [V1 \ M]$ such that $X \ A = R$ is a reduced row echelon $[V2 \ 0]$ decomposition of A , where $X = [V1 \ 0] \ P$ and $R = [I_r \ M] \ Q^T [V2 \ In-r] [0] \ Qt = Q^T$ If transform=false, the matrix X is not computed and the matrix $A = R$

Parameters

F	base field
M	number of rows

Parameters

	N	number of columns
in	A	input matrix
	lda	leading dimension of A
	P	the row permutation
	Qt	the column position of the pivots in the echelon form
	$transform$	decides whether X is computed
	$LuTag$	chooses the elimination algorithm. SlabRecursive for LUdivine, TileRecursive for PLUQ

11.21.3.35 pReducedRowEchelonForm()

```
template<class Field >
size_t pReducedRowEchelonForm (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const bool transform = false,
    size_t numthreads = 0,
    const FFPACK_LU_TAG LuTag = FfpackTileRecursive ) [inline]
```

11.21.3.36 ReducedRowEchelonForm() [2/3]

```
template<class Field , class PSHelper >
size_t ReducedRowEchelonForm (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const bool transform,
    const FFPACK_LU_TAG LuTag,
    const PSHelper & psH ) [inline]
```

11.21.3.37 Invert() [1/4]

```
template<class Field >
Field::Element_ptr Invert (
    const Field & F,
    const size_t M,
    typename Field::Element_ptr A,
    const size_t lda,
    int & nullity )
```

Invert the given matrix in place or computes its nullity if it is singular.

An inplace $2n^3$ algorithm is used.

Parameters

	F	The computation domain
	M	order of the matrix
in, out	A	input matrix ($M \times M$)
	lda	leading dimension of A
	$nullity$	dimension of the kernel of A

Returns

pointer to A and $A \leftarrow A^{-1}$

11.21.3.38 Invert() [2/4]

```
template<class Field >
Field::Element_ptr Invert (
    const Field & F,
    const size_t M,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr X,
    const size_t ldx,
    int & nullity )
```

Invert the given matrix or computes its nullity if it is singular.

Precondition

X is preallocated and should be large enough to store the $m \times m$ matrix A.

Parameters

	F	The computation domain
	M	order of the matrix
in	A	input matrix ($M \times M$)
	lda	leading dimension of A
out	X	this is the inverse of A if A is invertible (non NULL and <code>nullity = 0</code>). It is untouched otherwise.
	ldx	leading dimension of X
	$nullity$	dimension of the kernel of A

Returns

pointer to $X = A^{-1}$

11.21.3.39 Invert2() [1/2]

```
template<class Field >
Field::Element_ptr Invert2 (
```

```

const Field & F,
const size_t M,
typename Field::Element_ptr A,
const size_t lda,
typename Field::Element_ptr X,
const size_t ldx,
int & nullity )

```

Invert the given matrix or computes its nullity if it is singular.

An $2n^3f$ algorithm is used. This routine can be % faster than `FFPACK::Invert` but is not totally inplace.

Precondition

X is preallocated and should be large enough to store the $m \times m$ matrix A.

Warning

A is overwritten here !

Bug not tested.

Parameters

	<i>F</i>	the computation domain
	<i>M</i>	order of the matrix
in, out	<i>A</i>	input matrix ($M \times M$). On output, A is modified and represents a "psycological" factorisation LU.
	<i>lda</i>	leading dimension of A
out	<i>X</i>	this is the inverse of A if A is invertible (non NULL and <code>nullity = 0</code>). It is untouched otherwise.
	<i>ldx</i>	leading dimension of X
	<i>nullity</i>	dimension of the kernel of A

Returns

pointer to $X = A^{-1}$

Todo this init is not all necessary (done after `fttrtri`)

Todo this init is not all necessary (done after `fttrtri`)

11.21.3.40 CharPoly() [1/8]

```

template<class PolRing >
std::list< typename PolRing::Element > & CharPoly (
    const PolRing & R,
    std::list< typename PolRing::Element > & charp,
    const size_t N,

```

```

typename PolRing::Domain_t::Element_ptr A,
const size_t lda,
typename PolRing::Domain_t::RandIter & G,
const FFPACK_CHARPOLY_TAG CharpTag = FfpackAuto,
const size_t degree = __FFLASFFPACK_ARITHPROG_THRESHOLD ) [inline]

```

Compute the characteristic polynomial of the matrix A.

Parameters

	<i>R</i>	the polynomial ring of charp (contains the base field)
out	<i>charp</i>	the characteristic polynomial of as a list of factors
	<i>N</i>	order of the matrix A
in	<i>A</i>	the input matrix ($N \times N$) (could be overwritten in some algorithmic variants)
	<i>lda</i>	leading dimension of A
	<i>CharpTag</i>	the algorithmic variant
	<i>G</i>	a random iterator (required for the randomized variants LUKrylov and ArithProg)

11.21.3.41 CharPoly() [2/8]

```

template<class PolRing >
PolRing::Element & CharPoly (
    const PolRing & R,
    typename PolRing::Element & charp,
    const size_t N,
    typename PolRing::Domain_t::Element_ptr A,
    const size_t lda,
    typename PolRing::Domain_t::RandIter & G,
    const FFPACK_CHARPOLY_TAG CharpTag = FfpackAuto,
    const size_t degree = __FFLASFFPACK_ARITHPROG_THRESHOLD ) [inline]

```

Compute the characteristic polynomial of the matrix A.

Parameters

	<i>R</i>	the polynomial ring of charp (contains the base field)
out	<i>charp</i>	the characteristic polynomial of as a single polynomial
	<i>N</i>	order of the matrix A
in	<i>A</i>	the input matrix ($N \times N$) (could be overwritten in some algorithmic variants)
	<i>lda</i>	leading dimension of A
	<i>CharpTag</i>	the algorithmic variant
	<i>G</i>	a random iterator (required for the randomized variants LUKrylov and ArithProg)

11.21.3.42 CharPoly() [3/8]

```

template<class PolRing >
PolRing::Element & CharPoly (
    const PolRing & R,
    typename PolRing::Element & charp,

```



```

const size_t N,
typename PolRing::Domain_t::Element_ptr A,
const size_t lda,
const FFPACK_CHARPOLY_TAG CharpTag = FfpackAuto,
const size_t degree = __FFLASFFPACK_ARITHPROG_THRESHOLD ) [inline]

```

Compute the characteristic polynomial of the matrix A.

Parameters

	<i>R</i>	the polynomial ring of charp (contains the base field)
out	<i>charp</i>	the characteristic polynomial of as a single polynomial
	<i>N</i>	order of the matrix A
in	<i>A</i>	the input matrix ($N \times N$) (could be overwritten in some algorithmic variants)
	<i>lda</i>	leading dimension of A
	<i>CharpTag</i>	the algorithmic variant

11.21.3.43 MinPoly() [1/4]

```

template<class Field , class Polynomial >
Polynomial & MinPoly (
    const Field & F,
    Polynomial & minP,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda ) [inline]

```

Compute the minimal polynomial of the matrix A.

The algorithm is randomized probabilistic, and computes the minimal polynomial of the Krylov iterates of a random vector: (v, Av, ..., A^kv)

Parameters

	<i>F</i>	the base field
out	<i>minP</i>	the minimal polynomial of A
	<i>N</i>	order of the matrix A
in	<i>A</i>	the input matrix ($N \times N$)
	<i>lda</i>	leading dimension of A

11.21.3.44 MinPoly() [2/4]

```

template<class Field , class Polynomial , class RandIter >
Polynomial & MinPoly (
    const Field & F,
    Polynomial & minP,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    RandIter & G ) [inline]

```

Compute the minimal polynomial of the matrix A .

The algorithm is randomized probabilistic, and computes the minimal polynomial of the Krylov iterates of a random vector: $(v, Av, \dots, A^kv)$

Parameters

	F	the base field
out	$minP$	the minimal polynomial of A
	N	order of the matrix A
in	A	the input matrix ($N \times N$)
	lda	leading dimension of A
	G	a random iterator

11.21.3.45 MatVecMinPoly() [1/2]

```
template<class Field , class Polynomial >
Polynomial & MatVecMinPoly (
    const Field & F,
    Polynomial & minP,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr v,
    const size_t incv ) [inline]
```

Compute the minimal polynomial of the matrix A and a vector v , namely the first linear dependency relation in the Krylov basis $(v, Av, \dots, A^N v)$.

Parameters

	F	the base field
out	$minP$	the minimal polynomial of A and v
	N	order of the matrix A
in	A	the input matrix ($N \times N$)
	lda	leading dimension of A
	K	an $N \times (N + 1)$ matrix containing the vector v on its first row
	ldk	leading dimension of K
	P	[out] (optional) the permutation used in the elimination of the Krylov matrix K

11.21.3.46 Rank() [1/3]

```
template<class Field >
size_t Rank (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda )
```

Computes the rank of the given matrix using a PLUQ factorization.

The input matrix is modified.

Parameters

	F	base field
	M	row dimension of the matrix
	N	column dimension of the matrix
in	A	input matrix
	lda	leading dimension of A
	psH	(optional) a ParSeqHelper to choose between sequential and parallel execution

11.21.3.47 pRank()

```
template<class Field >
size_t pRank (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t numthreads = 0 )
```

11.21.3.48 Rank() [2/3]

```
template<class Field , class PSHelper >
size_t Rank (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    const PSHelper & psH )
```

11.21.3.49 IsSingular() [1/2]

```
template<class Field >
bool IsSingular (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda )
```

Returns true if the given matrix is singular.

The method is a block elimination with early termination

using LQUP factorization with early termination. If $M \neq N$, then the matrix is virtually padded with zeros to make it square and its determinant is zero.

Warning

The input matrix is modified.

Parameters

	F	base field
	M	row dimension of the matrix
	N	column dimension of the matrix.
in, out	A	input matrix
	lda	leading dimension of A

11.21.3.50 Det() [1/6]

```
template<class Field >
Field::Element & Det (
    const Field & F,
    typename Field::Element & det,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P = NULL,
    size_t * Q = NULL ) [inline]
```

Returns the determinant of the given square matrix.

The method is a block elimination using PLUQ factorization. The input matrix A is overwritten.

Warning

The input matrix is modified.

Parameters

	F	base field
out	det	the determinant of A
	N	the order of the square matrix A.
in, out	A	input matrix
	lda	leading dimension of A
	psH	(optional) a ParSeqHelper to choose between sequential and parallel execution
	P,Q	(optional) row and column permutations to be used by the PLUQ factorization. randomized checkers (see cherckes/checker_det.inl) need them for certification

11.21.3.51 pDet()

```
template<class Field >
Field::Element & pDet (
    const Field & F,
    typename Field::Element & det,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t numthreads = 0,
```

```
size_t * P = NULL,
size_t * Q = NULL ) [inline]
```

11.21.3.52 Det() [2/6]

```
template<class Field , class PSHelper >
Field::Element & Det (
    const Field & F,
    typename Field::Element & det,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    const PSHelper & psH,
    size_t * P = NULL,
    size_t * Q = NULL )
```

11.21.3.53 Solve() [1/3]

```
template<class Field >
Field::Element_ptr Solve (
    const Field & F,
    const size_t M,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr x,
    const int incx,
    typename Field::ConstElement_ptr b,
    const int incb ) [inline]
```

Solves a linear system $AX = b$ using PLUQ factorization.

@oaram F base field @oaram M matrix order

Parameters

in	<i>A</i>	input matrix
	<i>lda</i>	leading dimension of A
out	<i>x</i>	output solution vector
	<i>incx</i>	increment of x
	<i>b</i>	input right hand side of the system
	<i>incb</i>	increment of b

11.21.3.54 Solve() [2/3]

```
template<class Field , class PSHelper >
Field::Element_ptr Solve (
    const Field & F,
    const size_t M,
    typename Field::Element_ptr A,
    const size_t lda,
```

```

typename Field::Element_ptr x,
const int incx,
typename Field::ConstElement_ptr b,
const int incb,
PSHelper & psH )

```

11.21.3.55 pSolve()

```

template<class Field >
Field::Element_ptr pSolve (
    const Field & F,
    const size_t M,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr x,
    const int incx,
    typename Field::ConstElement_ptr b,
    const int incb,
    size_t numthreads = 0 ) [inline]

```

11.21.3.56 RandomNullSpaceVector() [1/3]

```

template<class Field >
*void RandomNullSpaceVector (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr X,
    const size_t incX )

```

Solve $LX = B$ or $XL = B$ in place.

L is $M \times M$ if Side == [FFLAS::FflasLeft](#) and $N \times N$ if Side == [FFLAS::FflasRight](#), B is $M \times N$. Only the R non trivial column of L are stored in the $M \times R$ matrix L Requirement : so that L could be expanded in-place Computes a vector of the Left/Right nullspace of the matrix A.

Parameters

	<i>F</i>	The computation domain
	<i>Side</i>	decides whether it computes the left (FflasLeft) or right (FflasRight) nullspace
	<i>M</i>	number of rows
	<i>N</i>	number of columns
in, out	<i>A</i>	input matrix of dimension $M \times N$, A is modified to its LU version
	<i>lda</i>	leading dimension of A
out	<i>X</i>	output vector
	<i>incX</i>	increment of X

11.21.3.57 NullSpaceBasis() [1/2]

```
template<class Field >
size_t NullSpaceBasis (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr & NS,
    size_t & ldn,
    size_t & NSdim )
```

Computes a basis of the Left/Right nullspace of the matrix A.

return the dimension of the nullspace.

Parameters

	<i>F</i>	The computation domain
	<i>Side</i>	decides whether it computes the left (FflasLeft) or right (FflasRight) nullspace
	<i>M</i>	number of rows
	<i>N</i>	number of columns
in, out	<i>A</i>	input matrix of dimension M x N, A is modified
	<i>lda</i>	leading dimension of A
out	<i>NS</i>	output matrix of dimension N x NSdim (allocated here)
out	<i>ldn</i>	leading dimension of NS
out	<i>NSdim</i>	the dimension of the Nullspace (N-rank(A))

11.21.3.58 RowRankProfile() [1/3]

```
template<class Field >
size_t RowRankProfile (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t *& rkprofile,
    const FFPACK_LU_TAG LuTag = FfpackSlabRecursive ) [inline]
```

Computes the row rank profile of A.

Parameters

	<i>F</i>	base field
	<i>M</i>	number of rows
	<i>N</i>	number of columns
in	<i>A</i>	input matrix of dimension M x N
	<i>lda</i>	leading dimension of A
out	<i>rkprofile</i>	return the rank profile as an array of row indexes, of dimension r=rank(A)
	<i>LuTag</i>	chooses the elimination algorithm. SlabRecursive for LUdivine, TileRecursive for PLUQ

A modified rkprofile is allocated during the computation.

Returns

R

11.21.3.59 pRowRankProfile()

```
template<class Field >
size_t pRowRankProfile (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t *rkprofile,
    size_t numthreads = 0,
    const FFPACK_LU_TAG LuTag = FfpackTileRecursive ) [inline]
```

11.21.3.60 RowRankProfile() [2/3]

```
template<class Field , class PSHelper >
size_t RowRankProfile (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t *rkprofile,
    const FFPACK_LU_TAG LuTag,
    PSHelper & psH ) [inline]
```

11.21.3.61 ColumnRankProfile() [1/3]

```
template<class Field >
size_t ColumnRankProfile (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t *rkprofile,
    const FFPACK_LU_TAG LuTag = FfpackSlabRecursive ) [inline]
```

Computes the column rank profile of A.

Parameters

	F	base field
	M	number of rows
	N	number of columns
in	A	input matrix of dimension
	lda	leading dimension of A
out	$rkprofile$	return the rank profile as an array of row indexes, of dimension $r=\text{rank}(A)$
	$LuTag$	chooses the elimination algorithm. SlabRecursive for LUdivine, TileRecursive for PLUQ

A is modified rkprofile is allocated during the computation.

Returns

R

11.21.3.62 pColumnRankProfile()

```
template<class Field >
size_t pColumnRankProfile (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * rkprofile,
    size_t numthreads = 0,
    const FFPACK_LU_TAG LuTag = FfpackTileRecursive ) [inline]
```

11.21.3.63 ColumnRankProfile() [2/3]

```
template<class Field , class PSHelper >
size_t ColumnRankProfile (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * rkprofile,
    const FFPACK_LU_TAG LuTag,
    PSHelper & psH ) [inline]
```

11.21.3.64 RankProfileFromLU()

```
void RankProfileFromLU (
    const size_t * P,
    const size_t N,
    const size_t R,
    size_t * rkprofile,
    const FFPACK_LU_TAG LuTag ) [inline]
```

Recovers the column/row rank profile from the permutation of an LU decomposition.

Works with both the CUP/PLE decompositions (obtained by LUdivine) or the PLUQ decomposition. Assumes that the output vector containing the rank profile is already allocated.

Parameters

	P	the permutation carrying the rank profile information
	N	the row/col dimension for a row/column rank profile
	R	the rank of the matrix
out	$rkprofile$	return the rank profile as an array of indices
	$LuTag$	chooses the elimination algorithm. StabRecursive for LUdivine, TileRecursive for PLUQ

11.21.3.65 LeadingSubmatrixRankProfiles()

```
size_t LeadingSubmatrixRankProfiles (
    const size_t M,
    const size_t N,
    const size_t R,
    const size_t LSm,
    const size_t LSn,
    const size_t * P,
    const size_t * Q,
    size_t * RRP,
    size_t * CRP ) [inline]
```

Recovers the row and column rank profiles of any leading submatrix from the PLUQ decomposition.

Only works with the PLUQ decomposition Assumes that the output vectors containing the rank profiles are already allocated.

Parameters

P	the permutation carrying the rank profile information
M	the row dimension of the initial matrix
N	the column dimension of the initial matrix
R	the rank of the initial matrix
LSm	the row dimension of the leading submatrix considered
LSn	the column dimension of the leading submatrix considered
P	the row permutation of the PLUQ decomposition
Q	the column permutation of the PLUQ decomposition
RRP	return the row rank profile of the leading submatrix

Returns

the rank of the $LSm \times LSn$ leading submatrix

A is modified

Bibliography • Dumas J-G., Pernet C., and Sultan Z. *Simultaneous computation of the row and column rank profiles*, ISSAC'13.

11.21.3.66 RowRankProfileSubmatrixIndices() [1/2]

```
template<class Field >
size_t RowRankProfileSubmatrixIndices (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * rowindices,
    size_t * colindices,
    size_t & R )
```

RowRankProfileSubmatrixIndices.

Computes the indices of the submatrix $r \times r$ X of A whose rows correspond to the row rank profile of A.

Parameters

	F	base field
	M	number of rows
	N	number of columns
in	A	input matrix of dimension
	<i>rowindices</i>	array of the row indices of X in A
	<i>colindices</i>	array of the col indices of X in A
	<i>lda</i>	leading dimension of A
out	R	list of indices

rowindices and colindices are allocated during the computation. A is modified

Returns

R

11.21.3.67 ColRankProfileSubmatrixIndices() [1/2]

```
template<class Field >
size_t ColRankProfileSubmatrixIndices (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t *& rowindices,
    size_t *& colindices,
    size_t & R )
```

Computes the indices of the submatrix $r \times r$ X of A whose columns correspond to the column rank profile of A.

Parameters

	F	base field
	M	number of rows
	N	number of columns
in	A	input matrix of dimension
	<i>rowindices</i>	array of the row indices of X in A
	<i>colindices</i>	array of the col indices of X in A
	<i>lda</i>	leading dimension of A
out	R	list of indices

rowindices and colindices are allocated during the computation.

Warning

A is modified

Returns

R

11.21.3.68 RowRankProfileSubmatrix() [1/2]

```
template<class Field >
size_t RowRankProfileSubmatrix (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr & X,
    size_t & R )
```

Computes the $r \times r$ submatrix X of A , by picking the row rank profile rows of A .

Parameters

	F	base field
	M	number of rows
	N	number of columns
in	A	input matrix of dimension $M \times N$
	lda	leading dimension of A
out	X	the output matrix
out	R	list of indices

A is not modified X is allocated during the computation.

Returns

R

11.21.3.69 ColRankProfileSubmatrix() [1/2]

```
template<class Field >
size_t ColRankProfileSubmatrix (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr & X,
    size_t & R )
```

Compute the $r \times r$ submatrix X of A , by picking the row rank profile rows of A .

Parameters

	F	base field
	M	number of rows

Parameters

	N	number of columns
in	A	input matrix of dimension $M \times N$
	lda	leading dimension of A
out	X	the output matrix
out	R	list of indices

A is not modified X is allocated during the computation.

Returns

R

11.21.3.70 getTriangular() [1/2]

```
template<class Field >
void getTriangular (
    const Field & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG diag,
    const size_t M,
    const size_t N,
    const size_t R,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr T,
    const size_t ldt,
    const bool OnlyNonZeroVectors = false ) [inline]
```

Extracts a triangular matrix from a compact storage $A=L/U$ of rank R .

if OnlyNonZeroVectors is false, then T and A have the same dimensions Otherwise, T is $R \times N$ if UpLo = FflasUpper, else T is $M \times R$

Parameters

	F	base field
	$UpLo$	selects if the upper (FflasUpper) or lower (FflasLower) triangular matrix is returned
	$diag$	selects if the triangular matrix unit-diagonal (FflasUnit/NoUnit)
	M	row dimension of T
	N	column dimension of T
	R	rank of the triangular matrix (how many rows/columns need to be copied)
in	A	input matrix
	lda	leading dimension of A
out	T	output matrix
	ldt	leading dimension of T
	$OnlyNonZeroVectors$	decides whether the last zero rows/columns should be ignored

Todo just one triangular fzero+fassign ?

Todo just one triangular fzero+fassign ?

11.21.3.71 getTriangular() [2/2]

```
template<class Field >
void getTriangular (
    const Field & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG diag,
    const size_t M,
    const size_t N,
    const size_t R,
    typename Field::Element_ptr A,
    const size_t lda ) [inline]
```

Cleans up a compact storage $A=LU$ to reveal a triangular matrix of rank R .

Parameters

	<i>F</i>	base field
	<i>UpLo</i>	selects if the upper (FflasUpper) or lower (FflasLower) triangular matrix is revealed
	<i>diag</i>	selects if the triangular matrix unit-diagonal (FflasUnit/NoUnit)
	<i>M</i>	row dimension of A
	<i>N</i>	column dimension of A
	<i>R</i>	rank of the triangular matrix
in, out	<i>A</i>	input/output matrix
	<i>lda</i>	leading dimension of A

Todo just one triangular fzero+fassign ?

Todo just one triangular fzero+fassign ?

11.21.3.72 getEchelonForm() [1/2]

```
template<class Field >
void getEchelonForm (
    const Field & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG diag,
    const size_t M,
    const size_t N,
    const size_t R,
    const size_t * P,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr T,
```

```

const size_t ldt,
const bool OnlyNonZeroVectors = false,
const FFPACK_LU_TAG LuTag = FfpackSlabRecursive ) [inline]

```

Extracts a matrix in echelon form from a compact storage $A=L\backslash U$ of rank R obtained by RowEchelonForm or ColumnEchelonForm.

Either L or U is in Echelon form (depending on Uplo) The echelon structure is defined by the first R values of the array P . row and column dimension of T are greater or equal to that of A

Parameters

	F	base field
	$UpLo$	selects if the upper (FflasUpper) or lower (FflasLower) triangular matrix is returned
	$diag$	selects if the echelon matrix has unit pivots (FflasUnit/NoUnit)
	M	row dimension of T
	N	column dimension of T
	R	rank of the triangular matrix (how many rows/columns need to be copied)
	P	positions of the R pivots
in	A	input matrix
	lda	leading dimension of A
out	T	output matrix
	ldt	leading dimension of T
	$OnlyNonZeroVectors$	decides whether the last zero rows/columns should be ignored
	$LuTag$	which factorized form (CUP/PLE if FfpackSlabRecursive, PLUQ if FfpackTileRecursive)

11.21.3.73 getEchelonForm() [2/2]

```

template<class Field >
void getEchelonForm (
    const Field & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG diag,
    const size_t M,
    const size_t N,
    const size_t R,
    const size_t * P,
    typename Field::Element_ptr A,
    const size_t lda,
    const FFPACK_LU_TAG LuTag = FfpackSlabRecursive ) [inline]

```

Cleans up a compact storage $A=L\backslash U$ obtained by RowEchelonForm or ColumnEchelonForm to reveal an echelon form of rank R .

Either L or U is in Echelon form (depending on Uplo) The echelon structure is defined by the first R values of the array P .

Parameters

	F	base field
	$UpLo$	selects if the upper (FflasUpper) or lower (FflasLower) triangular matrix is returned

Parameters

	<i>diag</i>	selects if the echelon matrix has unit pivots (FflasUnit/NoUnit)
	<i>M</i>	row dimension of A
	<i>N</i>	column dimension of A
	<i>R</i>	rank of the triangular matrix (how many rows/columns need to be copied)
	<i>P</i>	positions of the R pivots
<i>in, out</i>	<i>A</i>	input/output matrix
	<i>lda</i>	leading dimension of A
	<i>LuTag</i>	which factorized form (CUP/PLE if FfpackSlabRecursive, PLUQ if FfpackTileRecursive)

11.21.3.74 getEchelonTransform()

```
template<class Field >
void getEchelonTransform (
    const Field & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG diag,
    const size_t M,
    const size_t N,
    const size_t R,
    const size_t * P,
    const size_t * Q,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr T,
    const size_t ldt,
    const FFPACK_LU_TAG LuTag = FfpackSlabRecursive ) [inline]
```

Extracts a transformation matrix to echelon form from a compact storage $A=LU$ of rank R obtained by Row↔EchelonForm or ColumnEchelonForm.

If Uplo == FflasLower: T is $N \times N$ (already allocated) such that $A T = C$ is a transformation of A in Column echelon form Else T is $M \times M$ (already allocated) such that $T A = E$ is a transformation of A in Row Echelon form

Parameters

	<i>F</i>	base field
	<i>UpLo</i>	Lower (FflasLower) means Transformation to Column Echelon Form, Upper (FflasUpper), to Row Echelon Form
	<i>diag</i>	selects if the echelon matrix has unit pivots (FflasUnit/NoUnit)
	<i>M</i>	row dimension of A
	<i>N</i>	column dimension of A
	<i>R</i>	rank of the triangular matrix
	<i>P</i>	permutation matrix
<i>in</i>	<i>A</i>	input matrix
	<i>lda</i>	leading dimension of A
<i>out</i>	<i>T</i>	output matrix
	<i>ldt</i>	leading dimension of T
	<i>LuTag</i>	which factorized form (CUP/PLE if FfpackSlabRecursive, PLUQ if FfpackTileRecursive)

11.21.3.75 getReducedEchelonForm() [1/2]

```
template<class Field >
void getReducedEchelonForm (
    const Field & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const size_t M,
    const size_t N,
    const size_t R,
    const size_t * P,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr T,
    const size_t ldt,
    const bool OnlyNonZeroVectors = false,
    const FFPACK_LU_TAG LuTag = FfpackSlabRecursive ) [inline]
```

Extracts a matrix in echelon form from a compact storage $A=L\backslash U$ of rank R obtained by ReducedRowEchelonForm or ReducedColumnEchelonForm with transform = true.

Either L or U is in Echelon form (depending on Uplo) The echelon structure is defined by the first R values of the array P . row and column dimension of T are greater or equal to that of A

Parameters

	<i>F</i>	base field
	<i>UpLo</i>	selects if the upper (FflasUpper) or lower (FflasLower) triangular matrix is returned
	<i>diag</i>	selects if the echelon matrix has unit pivots (FflasUnit/NoUnit)
	<i>M</i>	row dimension of T
	<i>N</i>	column dimension of T
	<i>R</i>	rank of the triangular matrix (how many rows/columns need to be copied)
	<i>P</i>	positions of the R pivots
in	<i>A</i>	input matrix
	<i>lda</i>	leading dimension of A
	<i>ldt</i>	leading dimension of T
	<i>LuTag</i>	which factorized form (CUP/PLE if FfpackSlabRecursive, PLUQ if FfpackTileRecursive)
	<i>OnlyNonZeroVectors</i>	decides whether the last zero rows/columns should be ignored

11.21.3.76 getReducedEchelonForm() [2/2]

```
template<class Field >
void getReducedEchelonForm (
    const Field & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const size_t M,
    const size_t N,
    const size_t R,
    const size_t * P,
    typename Field::Element_ptr A,
    const size_t lda,
    const FFPACK_LU_TAG LuTag = FfpackSlabRecursive ) [inline]
```

Cleans up a compact storage $A=L\backslash U$ of rank R obtained by `ReducedRowEchelonForm` or `ReducedColumnEchelonForm` with `transform = true`.

Either L or U is in Echelon form (depending on `Uplo`) The echelon structure is defined by the first R values of the array P .

Parameters

	F	base field
	$UpLo$	selects if the upper (<code>FflasUpper</code>) or lower (<code>FflasLower</code>) triangular matrix is returned
	$diag$	selects if the echelon matrix has unit pivots (<code>FflasUnit/NoUnit</code>)
	M	row dimension of A
	N	column dimension of A
	R	rank of the triangular matrix (how many rows/columns need to be copied)
	P	positions of the R pivots
in, out	A	input/output matrix
	lda	leading dimension of A
	$LuTag$	which factorized form (CUP/PLE if <code>FfpackSlabRecursive</code> , PLUQ if <code>FfpackTileRecursive</code>)

11.21.3.77 `getReducedEchelonTransform()`

```
template<class Field >
void getReducedEchelonTransform (
    const Field & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const size_t M,
    const size_t N,
    const size_t R,
    const size_t * P,
    const size_t * Q,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr T,
    const size_t ldt,
    const FFPACK_LU_TAG LuTag = FfpackSlabRecursive ) [inline]
```

Extracts a transformation matrix to echelon form from a compact storage $A=L\backslash U$ of rank R obtained by `RowEchelonForm` or `ColumnEchelonForm`.

If `Uplo == FflasLower`: T is $N \times N$ (already allocated) such that $A T = C$ is a transformation of A in Column echelon form Else T is $M \times M$ (already allocated) such that $T A = E$ is a transformation of A in Row Echelon form

Parameters

	F	base field
	$UpLo$	selects Col (<code>FflasLower</code>) or Row (<code>FflasUpper</code>) Echelon Form
	$diag$	selects if the echelon matrix has unit pivots (<code>FflasUnit/NoUnit</code>)
	M	row dimension of A
	N	column dimension of A
	R	rank of the triangular matrix
	P	permutation matrix
in	A	input matrix

Parameters

	<i>lda</i>	leading dimension of A
out	<i>T</i>	output matrix
	<i>ldt</i>	leading dimension of T
	<i>LuTag</i>	which factorized form (CUP/PLE if FfpackSlabRecursive, PLUQ if FfpackTileRecursive)

11.21.3.78 PLUQtoEchelonPermutation()

```
void PLUQtoEchelonPermutation (
    const size_t N,
    const size_t R,
    const size_t * P,
    size_t * outPerm ) [inline]
```

Auxiliary routine: determines the permutation that changes a PLUQ decomposition into a echelon form revealing PLUQ decomposition.

11.21.3.79 LTBruhatGen()

```
template<class Field >
size_t LTBruhatGen (
    const Field & Fi,
    const FFLAS::FFLAS_DIAG diag,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q ) [inline]
```

LTBruhatGen Suppose A is Left Triangular Matrix This procedure computes the Bruhat Representation of A and return the rank of A.

Parameters

<i>Fi</i>	base Field
<i>diag</i>	
<i>N</i>	size of A
<i>A</i>	the matrix we search the Bruhat representation
<i>lda</i>	the leading dimension of A
<i>P</i>	a permutation matrix
<i>Q</i>	a permutation matrix

11.21.3.80 getLTBruhatGen() [1/2]

```
template<class Field >
void getLTBruhatGen (
    const Field & Fi,
```

```

    const size_t N,
    const size_t r,
    const size_t * P,
    const size_t * Q,
    typename Field::Element_ptr R,
    const size_t ldr ) [inline]

```

GetLTBruhatGen This procedure Computes the Rank Revealing Matrix based on the Bruhta representation of a Matrix.

Parameters

<i>Fi</i>	base Field
<i>N</i>	size of the matrix
<i>r</i>	the rank of the matrix
<i>P</i>	a permutation matrix
<i>Q</i>	a permutation matrix
<i>R</i>	the matrix that will contain the rank revealing matrix
<i>ldr</i>	the leading fimension of R

11.21.3.81 getLTBruhatGen() [2/2]

```

template<class Field >
void getLTBruhatGen (
    const Field & Fi,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG diag,
    const size_t N,
    const size_t r,
    const size_t * P,
    const size_t * Q,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr T,
    const size_t ldt ) [inline]

```

GetLTBruhatGen This procedure computes the matrix L or U f the Bruhat Representation Suppose that A is the bruhat representation of a matrix.

Parameters

<i>Fi</i>	base Field
<i>Uplo</i>	choose if the procedure return L or U
<i>diag</i>	
<i>N</i>	size of A
<i>r</i>	rank of A
<i>P</i>	permutaion matrix
<i>Q</i>	permutation matrix
<i>A</i>	a bruhat representation
<i>lda</i>	leading dimension of A
<i>T</i>	matrix that will contains L or U
<i>ldt</i>	leading dimension of T

11.21.3.82 LTQSorter()

```
size_t LTQSorter (
    const size_t N,
    const size_t r,
    const size_t * P,
    const size_t * Q ) [inline]
```

LTQSorter This procedure computes the order of quasiseparability of a matrix.

Parameters

N	size of the matrix
r	rank of the matrix
P	permutation matrix
Q	permutation matrix

11.21.3.83 CompressToBlockBiDiagonal()

```
template<class Field >
size_t CompressToBlockBiDiagonal (
    const Field & Fi,
    const FFLAS::FFLAS_UPLO Uplo,
    size_t N,
    size_t s,
    size_t r,
    const size_t * P,
    const size_t * Q,
    typename Field::Element_ptr A,
    size_t lda,
    typename Field::Element_ptr X,
    size_t ldx,
    size_t * K,
    size_t * M,
    size_t * T ) [inline]
```

CompressToBlockBiDiagonal This procedure compress a compact representation of a row echelon form or column echelon form.

Parameters

Fi	base Field
$Uplo$	chosse if the procedure is based on row or column
N	size of the matrix
s	order of quasiseparability
r	rank
P	permutation matrix
Q	permutation matrix
A	the matrix to compact
lda	leading dimension of A
X	matrix that will stock the representation
ldx	leading dimension of X

Parameters

<i>K</i>	stock the position of the blocks in A
<i>M</i>	permutation matrix
<i>T</i>	stock the operation done in the procedure

11.21.3.84 ExpandBlockBiDiagonalToBruhat()

```
template<class Field >
void ExpandBlockBiDiagonalToBruhat (
    const Field & Fi,
    const FFLAS::FFLAS_UPLO Uplo,
    size_t N,
    size_t s,
    size_t r,
    typename Field::Element_ptr A,
    size_t lda,
    typename Field::Element_ptr X,
    size_t ldx,
    size_t NbBlocks,
    size_t * K,
    size_t * M,
    size_t * T ) [inline]
```

ExpandBlockBiDiagonal This procedure expand a compact representation of a row echelon form or column echelon form.

Parameters

<i>Fi</i>	base Field
<i>Uplo</i>	chosse if the procedure is based on row or column
<i>N</i>	size of the matrix
<i>s</i>	order of qausiseparability
<i>r</i>	rank
<i>A</i>	the matrix that will sotck the expanded representation
<i>lda</i>	leading dimension of A
<i>X</i>	matrix to expand
<i>ldx</i>	leading dimension of X
<i>K</i>	stock the position of the blocks in A
<i>M</i>	permutation matrix
<i>T</i>	stock the operation done in the procedure

11.21.3.85 Bruhat2EchelonPermutation()

```
void Bruhat2EchelonPermutation (
    size_t N,
    size_t R,
    const size_t * P,
    const size_t * Q,
    size_t * M ) [inline]
```

Bruhat2EchelonPermutation (N,R,P,Q) Compute M such that LM or MU is in echelon form where L or U are factors of the Bruhat Rpresentation.

Parameters

in	N	size of the matrix
in	R	rank
in	P	permutation Matrix
in	Q	permutation Matrix
out	M	output permutation matrix

11.21.3.86 TInverter() [1/2]

```
size_t * TInverter (
    size_t * T,
    size_t r )
```

11.21.3.87 ComputeRPermutation() [1/2]

```
template<class Field >
void ComputeRPermutation (
    const Field & Fi,
    size_t N,
    size_t r,
    const size_t * P,
    const size_t * Q,
    size_t * R,
    size_t * MU,
    size_t * ML )
```

11.21.3.88 productBruhatxTS() [1/2]

```
template<class Field >
void productBruhatxTS (
    const Field & Fi,
    size_t N,
    size_t s,
    size_t r,
    const size_t * P,
    const size_t * Q,
    const typename Field::Element_ptr Xu,
    size_t ldu,
    size_t NbBlocksU,
    size_t * Ku,
    size_t * Tu,
    size_t * MU,
    const typename Field::Element_ptr Xl,
    size_t ldl,
    size_t NbBlocksL,
    size_t * Kl,
    size_t * Tl,
```

```

size_t * ML,
typename Field::Element_ptr B,
size_t t,
size_t ldb,
typename Field::Element_ptr C,
size_t ldc )

```

productBruhatxTS Compute the product between the CRE compact representation of a matrix A and B a tall matrix

11.21.3.89 LQUPtoInverseOfFullRankMinor() [1/2]

```

template<class Field >
Field::Element_ptr LQUPtoInverseOfFullRankMinor (
    const Field & F,
    const size_t rank,
    typename Field::Element_ptr A_factors,
    const size_t lda,
    const size_t * QtPointer,
    typename Field::Element_ptr X,
    const size_t ldc )

```

LQUPtoInverseOfFullRankMinor.

Suppose A has been factorized as L.Q.U.P, with rank r. Then Qt.A.Pt has an invertible leading principal r x r submatrix This procedure efficiently computes the inverse of this minor and puts it into X.

Note

It changes the lower entries of A_factors in the process (NB: unless A was nonsingular and square)

Parameters

<i>F</i>	base field
<i>rank</i>	rank of the matrix.
<i>A_factors</i>	matrix containing the L and U entries of the factorization
<i>lda</i>	leading dimension of A
<i>QtPointer</i>	theLQUP->getQ()->getPointer() (note: getQ returns Qt!)
<i>X</i>	desired location for output
<i>ldx</i>	leading dimension of X

11.21.3.90 RandomNullSpaceVector() [2/3]

```

template<class Field >
void RandomNullSpaceVector (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,

```



```
typename Field::Element_ptr X,
const size_t incX )
```

Solve $LX = B$ or $XL = B$ in place.

L is $M \times M$ if Side == FFLAS::FflasLeft and $N \times N$ if Side == FFLAS::FflasRight, B is $M \times N$. Only the R non trivial column of L are stored in the $M \times R$ matrix L Requirement : so that L could be expanded in-place Computes a vector of the Left/Right nullspace of the matrix A.

Parameters

	<i>F</i>	The computation domain
	<i>Side</i>	decides whether it computes the left (FflasLeft) or right (FflasRight) nullspace
	<i>M</i>	number of rows
	<i>N</i>	number of columns
in, out	<i>A</i>	input matrix of dimension $M \times N$, A is modified to its LU version
	<i>lda</i>	leading dimension of A
out	<i>X</i>	output vector
	<i>incX</i>	increment of X

11.21.3.91 solveLB() [1/2]

```
template<class Field >
void solveLB (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    const size_t R,
    typename Field::Element_ptr L,
    const size_t ldl,
    const size_t * Q,
    typename Field::Element_ptr B,
    const size_t ldb )
```

11.21.3.92 solveLB2() [1/2]

```
template<class Field >
void solveLB2 (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    const size_t R,
    typename Field::Element_ptr L,
    const size_t ldl,
    const size_t * Q,
    typename Field::Element_ptr B,
    const size_t ldb )
```

11.21.3.93 TInverter() [2/2]

```
size_t * TInverter (
    const size_t * T,
    size_t r ) [inline]
```

11.21.3.94 ComputeRPermutation() [2/2]

```
template<class Field >
void ComputeRPermutation (
    const Field & Fi,
    size_t N,
    size_t r,
    const size_t * P,
    const size_t * Q,
    size_t * R,
    const size_t * MU,
    const size_t * ML ) [inline]
```

11.21.3.95 expandLCRE()

```
template<class Field >
Field::Element_ptr expandLCRE (
    const Field & Fi,
    size_t N,
    size_t s,
    size_t r,
    size_t * R,
    size_t i,
    typename Field::ConstElement_ptr Xu,
    size_t ldu,
    size_t NbBlocksU,
    const size_t * Ku,
    const size_t * Tuinv,
    typename Field::ConstElement_ptr Xl,
    size_t ldl,
    size_t NbBlocksL,
    const size_t * Kl,
    const size_t * Tlinv,
    typename Field::Element_ptr CRE,
    size_t ldcre ) [inline]
```

Expands an anti-diagonal block of a left triangular matrix from its compact Bruhat representation.

11.21.3.96 productBruhatxTS() [2/2]

```
template<class Field >
void productBruhatxTS (
    const Field & Fi,
    size_t N,
    size_t s,
    size_t r,
```

```

size_t t,
const size_t * P,
const size_t * Q,
typename Field::ConstElement_ptr Xu,
size_t ldu,
size_t NbBlocksU,
const size_t * Ku,
const size_t * Tu,
const size_t * MU,
typename Field::ConstElement_ptr Xl,
size_t ldl,
size_t NbBlocksL,
const size_t * Kl,
const size_t * Tl,
const size_t * ML,
typename Field::Element_ptr B,
size_t ldb,
const typename Field::Element beta,
typename Field::Element_ptr D,
size_t ldd ) [inline]

```

Compute the product of a left-triangular quasi-separable matrix A, represented by a compact Bruhat generator, with a dense rectangular matrix B: $C \leftarrow A \times B + \text{beta}C$.

Parameters

	<i>F</i>	the base field
	<i>N</i>	the order of A
	<i>s</i>	the order of quasiseparability of A
	<i>r</i>	the number of pivots in the left-triangular par of the rank profile matrix of A
	<i>t</i>	the number of columns of B
	<i>P</i>	the row indices of the pivots of A
	<i>Q</i>	the column indices of the pivots of A
	<i>Xu</i>	the compact storage of U: Du blocks in the first s rows, Su blocks in the last s rows
	<i>ldxu</i>	the leading dimension of Xu
	<i>NbBlocksU</i>	the number of diagonal blocks in the compact storage of U
	<i>Ku</i>	the list of starting column positions for each block of the storage of U
	<i>Tu</i>	the folding matrix for the compact storage of U: $Du + TuSu$ is in row echelon form
	<i>Mu</i>	a permutation matrix such that $Mu(Du + TuSu)$ is the U factor of the Bruhat generator
	<i>Xl</i>	the compact storage of L: Dl blocks in the first s columns, Sl blocks in the last s columns
	<i>ldxl</i>	the leading dimension of Xl
	<i>NbBlocksL</i>	the number of diagonal blocks in the compact storage of L
	<i>Kl</i>	the list of starting row positions for each block of the storage of L
	<i>Tl</i>	the folding matrix for the compact storage of L: $Dl + SlTl$ is in column echelon form
	<i>Ml</i>	a permutation matrix such that $(Dl + SlTl)Ml$ is the L factor of the Bruhat generator
	<i>B</i>	an $N \times t$ dense matrix
	<i>ldb</i>	leading dimension of B
	<i>beta</i>	scaling constant
in, out	<i>C</i>	output matrix
	<i>ldc</i>	leading dimension of C

Bibliography Pernet C. and Storjohann A. *Time and space efficient generators for quasiseparable matrices*, JSC (85), 2018, doi:10.1016/j.jsc.2017.07.010

11.21.3.97 Danilevski()

```
template<class Field , class Polynomial >
std::list< Polynomial > & Danilevski (
    const Field & F,
    std::list< Polynomial > & charp,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda )
```

11.21.3.98 buildMatrix()

```
template<class Field >
Field::Element_ptr buildMatrix (
    const Field & F,
    typename Field::ConstElement_ptr E,
    typename Field::ConstElement_ptr C,
    const size_t lda,
    const size_t * B,
    const size_t * T,
    const size_t me,
    const size_t mc,
    const size_t lambda,
    const size_t mu )
```

Bug is this :

11.21.3.99 CharPoly() [4/8]

```
FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr CharPoly (
    const FFPACK::RNSInteger< FFPACK::rns_double > & F,
    typename FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr charp,
    const size_t N,
    typename FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr A,
    const size_t lda,
    Givaro::ZRing< Givaro::Integer >::RandIter & G,
    const FFPACK_CHARPOLY_TAG CharpTag,
    size_t degree ) [inline]
```

11.21.3.100 CharPoly() [5/8]

```
template<>
Givaro::Poly1Dom< Givaro::ZRing< Givaro::Integer > >::Element & CharPoly (
    const Givaro::Poly1Dom< Givaro::ZRing< Givaro::Integer > > & R,
    Givaro::Poly1Dom< Givaro::ZRing< Givaro::Integer > >::Element & charp,
    const size_t N,
    Givaro::Integer * A,
    const size_t lda,
    Givaro::ZRing< Givaro::Integer >::RandIter & G,
    const FFPACK_CHARPOLY_TAG CharpTag,
    size_t degree ) [inline]
```

11.21.3.101 Det() [3/6]

```
template<class PSHelper >
FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr & Det (
    const FFPACK::RNSInteger< FFPACK::rns_double > & F,
    typename FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr & det,
    const size_t N,
    typename FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr A,
    const size_t lda,
    const PSHelper & psH ) [inline]
```

11.21.3.102 Det() [4/6]

```
template<class PSHelper >
Givaro::Integer & Det (
    const Givaro::ZRing< Givaro::Integer > & F,
    Givaro::Integer & det,
    const size_t N,
    Givaro::Integer * A,
    const size_t lda,
    const PSHelper & psH,
    size_t * P,
    size_t * Q ) [inline]
```

11.21.3.103 fsytrf_BC_Crout()

```
template<class Field >
bool fsytrf_BC_Crout (
    const Field & F,
    const FFLAS::FFLAS_UPLO UpLo,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr Dinv,
    const size_t incDinv ) [inline]
```

11.21.3.104 fsytrf_BC_RL()

```
template<class Field >
size_t fsytrf_BC_RL (
    const Field & F,
    const FFLAS::FFLAS_UPLO UpLo,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr Dinv,
    const size_t incDinv ) [inline]
```

11.21.3.105 fsytrf_UP_RPM_BC_RL()

```
template<class Field >
size_t fsytrf_UP_RPM_BC_RL (
    const Field & F,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr Dinv,
    const size_t incDinv,
    size_t * P ) [inline]
```

11.21.3.106 fsytrf_LOW_RPM_BC_Crout()

```
template<class Field >
size_t fsytrf_LOW_RPM_BC_Crout (
    const Field & F,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr Dinv,
    const size_t incDinv,
    size_t * P ) [inline]
```

11.21.3.107 fsytrf_UP_RPM_BC_Crout()

```
template<class Field >
size_t fsytrf_UP_RPM_BC_Crout (
    const Field & F,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr Dinv,
    const size_t incDinv,
    size_t * P ) [inline]
```

11.21.3.108 fsytrf_UP_RPM()

```
template<class Field >
size_t fsytrf_UP_RPM (
    const Field & Fi,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr Dinv,
    const size_t incDinv,
    size_t * P,
    size_t BCThreshold ) [inline]
```

MathP <- [[I] x P1 | [[L (N1+R2)] [P2^T]]] x [P3^T] [----- | ----] [[Q2^T]

Changing [U1 V1 | E1 E21 E22] into [U1 E11 E12 V1 E* E*] [0 | L2 \ U2 V21 V22] [U4 V41 0 V42 V43] [0 | M2 0 0] [U3 0 0 V3] [----- | -----] [0 0 0] [0 | H1 H21 H22] [0 | U3 V3] [0 | 0] where U4 is the 2R2 x 2R2 matrix formed by interleaving U2, L2^T and H1

11.21.3.109 fsytrf_nonunit() [2/3]

```

template<class Field >
bool fsytrf_nonunit (
    const Field & F,
    const FFLAS::FFLAS_UPLO UpLo,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr Dinv,
    const size_t incDinv,
    FFLAS::ParSeqHelper::Sequential seq,
    size_t threshold ) [inline]

```

11.21.3.110 fsytrf_nonunit() [3/3]

```

template<class Field , class Cut , class Param >
bool fsytrf_nonunit (
    const Field & F,
    const FFLAS::FFLAS_UPLO UpLo,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr Dinv,
    const size_t incDinv,
    FFLAS::ParSeqHelper::Parallel< Cut, Param > par,
    size_t threshold ) [inline]

```

11.21.3.111 fsytrf_RPM()

```

template<class Field >
size_t fsytrf_RPM (
    const Field & F,
    const FFLAS::FFLAS_UPLO UpLo,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t threshold ) [inline]

```

11.21.3.112 getTridiagonal()

```

template<class Field >
void getTridiagonal (
    const Field & F,
    const size_t N,
    const size_t R,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    size_t * P,
    typename Field::Element_ptr T,
    const size_t ldt ) [inline]

```

11.21.3.113 LUdivine_gauss() [1/2]

```
template<class Field >
size_t LUdivine_gauss (
    const Field & F,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    const FFPACK::FFPACK_LU_TAG LuTag ) [inline]
```

11.21.3.114 LUdivine_small() [1/2]

```
template<class Field >
size_t LUdivine_small (
    const Field & F,
    const FFLAS::FFLAS_DIAG Diag,
    const FFLAS::FFLAS_TRANSPOSE trans,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    const FFPACK::FFPACK_LU_TAG LuTag ) [inline]
```

11.21.3.115 LUdivine() [2/4]

```
template<class Field >
size_t LUdivine (
    const Field & F,
    const FFLAS::FFLAS_DIAG Diag,
    const FFLAS::FFLAS_TRANSPOSE trans,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    const FFPACK::FFPACK_LU_TAG LuTag,
    const size_t cutoff ) [inline]
```

Todo std::swap ?

11.21.3.116 LUdivine() [3/4]

```
template<>
size_t LUdivine (
    const Givaro::Modular< Givaro::Integer > & F,
    const FFLAS::FFLAS_DIAG Diag,
    const FFLAS::FFLAS_TRANSPOSE trans,
    const size_t M,
    const size_t N,
    typename Givaro::Integer * A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    const FFPACK::FFPACK_LU_TAG LuTag,
    const size_t cutoff ) [inline]
```

11.21.3.117 MonotonicCompress()

```
template<class Field >
void MonotonicCompress (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t incA,
    const size_t * MathP,
    const size_t R,
    const size_t maxpiv,
    const size_t rowstomove,
    const std::vector< bool > & ispiv ) [inline]
```

11.21.3.118 MonotonicCompressMorePivots()

```
template<class Field >
void MonotonicCompressMorePivots (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t incA,
    const size_t * MathP,
    const size_t R,
    const size_t rowstomove,
    const size_t lenP ) [inline]
```

11.21.3.119 MonotonicCompressCycles()

```
template<class Field >
void MonotonicCompressCycles (
    const Field & F,
```

```

    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t incA,
    const size_t * MathP,
    const size_t lenP ) [inline]

```

11.21.3.120 MonotonicExpand()

```

template<class Field >
void MonotonicExpand (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t incA,
    const size_t * MathP,
    const size_t R,
    const size_t maxpiv,
    const size_t rowstomove,
    const std::vector< bool > & ispiv )

```

11.21.3.121 applyP_block()

```

template<class Field >
void applyP_block (
    const Field & F,
    const FFLAS::FFLAS_SIDE Side,
    const FFLAS::FFLAS_TRANSPOSE Trans,
    const size_t M,
    const size_t ibeg,
    const size_t iend,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t * P ) [inline]

```

11.21.3.122 doApplyS()

```

template<class Field >
void doApplyS (
    const Field & F,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr tmp,
    const size_t width,
    const size_t M2,
    const size_t R1,
    const size_t R2,
    const size_t R3,
    const size_t R4 ) [inline]

```

11.21.3.123 MatrixApplyS() [1/3]

```
template<class Field >
void MatrixApplyS (
    const Field & F,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t width,
    const size_t M2,
    const size_t R1,
    const size_t R2,
    const size_t R3,
    const size_t R4 ) [inline]
```

11.21.3.124 MatrixApplyS() [2/3]

```
template<class Field >
void MatrixApplyS (
    const Field & F,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t width,
    const size_t M2,
    const size_t R1,
    const size_t R2,
    const size_t R3,
    const size_t R4,
    const FFLAS::ParSeqHelper::Sequential seq ) [inline]
```

11.21.3.125 MatrixApplyS() [3/3]

```
template<class Field , class Cut , class Param >
void MatrixApplyS (
    const Field & F,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t width,
    const size_t M2,
    const size_t R1,
    const size_t R2,
    const size_t R3,
    const size_t R4,
    const FFLAS::ParSeqHelper::Parallel< Cut, Param > par ) [inline]
```

11.21.3.126 PermApplyS()

```
template<class T >
void PermApplyS (
    T * A,
    const size_t lda,
    const size_t width,
    const size_t M2,
    const size_t R1,
    const size_t R2,
    const size_t R3,
    const size_t R4 ) [inline]
```

11.21.3.127 doApplyT()

```

template<class Field >
void doApplyT (
    const Field & F,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr tmp,
    const size_t width,
    const size_t N2,
    const size_t R1,
    const size_t R2,
    const size_t R3,
    const size_t R4 ) [inline]

```

11.21.3.128 MatrixApplyT() [1/3]

```

template<class Field >
void MatrixApplyT (
    const Field & F,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t width,
    const size_t N2,
    const size_t R1,
    const size_t R2,
    const size_t R3,
    const size_t R4 ) [inline]

```

11.21.3.129 MatrixApplyT() [2/3]

```

template<class Field >
void MatrixApplyT (
    const Field & F,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t width,
    const size_t N2,
    const size_t R1,
    const size_t R2,
    const size_t R3,
    const size_t R4,
    const FFLAS::ParSeqHelper::Sequential seq ) [inline]

```

11.21.3.130 MatrixApplyT() [3/3]

```

template<class Field , class Cut , class Param >
void MatrixApplyT (
    const Field & F,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t width,

```

```

const size_t N2,
const size_t R1,
const size_t R2,
const size_t R3,
const size_t R4,
const FFLAS::ParSeqHelper::Parallel< Cut, Param > par ) [inline]

```

11.21.3.131 PermApplyT()

```

template<class T >
void PermApplyT (
    T * A,
    const size_t lda,
    const size_t width,
    const size_t N2,
    const size_t R1,
    const size_t R2,
    const size_t R3,
    const size_t R4 ) [inline]

```

11.21.3.132 composePermutationsLLL()

```

void composePermutationsLLL (
    size_t * P1,
    const size_t * P2,
    const size_t R,
    const size_t N ) [inline]

```

Computes $P1 \times \text{Diag}(I_R, P2)$ where $P1$ is a LAPACK and $P2$ a LAPACK permutation and store the result in $P1$ as a LAPACK permutation.

Parameters

in, out	$P1$	a LAPACK permutation of size N
	$P2$	a LAPACK permutation of size N-R

11.21.3.133 composePermutationsLLM()

```

void composePermutationsLLM (
    size_t * MathP,
    const size_t * P1,
    const size_t * P2,
    const size_t R,
    const size_t N ) [inline]

```

Computes $P1 \times \text{Diag}(I_R, P2)$ where $P1$ is a LAPACK and $P2$ a LAPACK permutation and store the result in $MathP$ as a MathPermutation format.

Parameters

out		

a MathPermutation of size N

Parameters

<i>P1</i>	a LAPACK permutation of size N
<i>P2</i>	a LAPACK permutation of size N-R

11.21.3.134 composePermutationsMLM()

```
void composePermutationsMLM (
    size_t * MathP1,
    const size_t * P2,
    const size_t R,
    const size_t N ) [inline]
```

Computes MathP1 x Diag (I_R, P2) where MathP1 is a MathPermutation and P2 a LAPACK permutation and store the result in MathP1 as a MathPermutation format.

Parameters

in, out	<i>MathP1</i>	a MathPermutation of size N
	<i>P2</i>	a LAPACK permutation of size N-R

11.21.3.135 cyclic_shift_mathPerm()

```
void cyclic_shift_mathPerm (
    size_t * P,
    const size_t s ) [inline]
```

11.21.3.136 cyclic_shift_row_col() [1/2]

```
template<class Field >
void cyclic_shift_row_col (
    const Field & F,
    typename Field::Element_ptr A,
    size_t m,
    size_t n,
    size_t lda ) [inline]
```

11.21.3.137 cyclic_shift_row() [1/3]

```
template<class Field >
void cyclic_shift_row (
    const Field & F,
    typename Field::Element_ptr A,
    size_t m,
    size_t n,
    size_t lda ) [inline]
```

11.21.3.138 cyclic_shift_row() [2/3]

```
template<typename T >
void cyclic_shift_row (
    const RNSIntegerMod< T > & F,
    typename T::Element_ptr A,
    size_t m,
    size_t n,
    size_t lda ) [inline]
```

11.21.3.139 cyclic_shift_col() [1/3]

```
template<class Field >
void cyclic_shift_col (
    const Field & F,
    typename Field::Element_ptr A,
    size_t m,
    size_t n,
    size_t lda ) [inline]
```

11.21.3.140 cyclic_shift_col() [2/3]

```
template<typename T >
void cyclic_shift_col (
    const RNSIntegerMod< T > & F,
    typename T::Element_ptr A,
    size_t m,
    size_t n,
    size_t lda ) [inline]
```

11.21.3.141 PLUQ_basecaseV3()

```
template<class Field >
size_t PLUQ_basecaseV3 (
    const Field & Fi,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    typename Field::Element * A,
    const size_t lda,
    size_t * P,
    size_t * Q ) [inline]
```

11.21.3.142 PLUQ_basecaseV2()

```
template<class Field >
size_t PLUQ_basecaseV2 (
    const Field & Fi,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    typename Field::Element * A,
    const size_t lda,
    size_t * P,
    size_t * Q ) [inline]
```

11.21.3.143 PLUQ_basecaseCrout()

```
template<class Field >
size_t PLUQ_basecaseCrout (
    const Field & Fi,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q ) [inline]
```

11.21.3.144 _PLUQ()

```
template<class Field >
size_t _PLUQ (
    const Field & Fi,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    size_t BCThreshold ) [inline]
```

11.21.3.145 PLUQ() [4/6]

```
template<class Cut , class Param >
size_t PLUQ (
    const Givaro::Modular< Givaro::Integer > & F,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    typename Givaro::Integer * A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    size_t BCThreshold,
    FFLAS::ParSeqHelper::Parallel< Cut, Param > & PSHelper ) [inline]
```

11.21.3.146 threads_fgemm()

```
template<class Field >
void threads_fgemm (
    const size_t m,
    const size_t n,
    const size_t r,
    int nbthreads,
    size_t * W1,
    size_t * W2,
    size_t * W3,
    size_t gamma )
```


11.21.3.147 threads_ftrsm()

```
template<class Field >
void threads_ftrsm (
    const size_t m,
    const size_t n,
    int nbthreads,
    size_t * t1,
    size_t * t2 )
```

11.21.3.148 PLUQ() [5/6]

```
template<class Field >
size_t PLUQ (
    const Field & Fi,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    const FFLAS::ParSeqHelper::Parallel< FFLAS::CuttingStrategy::Recursive, FFLAS::StrategyParameter
> & PSHelper ) [inline]
```

11.21.3.149 fflas_const_cast() [1/3]

```
template<>
rns_double_elt_ptr fflas_const_cast (
    rns_double_elt_cstptr x ) [inline]
```

11.21.3.150 fflas_const_cast() [2/3]

```
template<>
rns_double_elt_cstptr fflas_const_cast (
    rns_double_elt_ptr x ) [inline]
```

11.21.3.151 cyclic_shift_row_col() [2/2]

```
template<typename Base_t >
void cyclic_shift_row_col (
    Base_t * A,
    size_t m,
    size_t n,
    size_t lda )
```

11.21.3.152 cyclic_shift_row() [3/3]

```
template INST_OR_DECL void cyclic_shift_row (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    FFLAS_ELT * A,
    size_t m,
    size_t n,
    size_t lda )
```

11.21.3.153 cyclic_shift_col() [3/3]

```
template INST_OR_DECL void cyclic_shift_col (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    FFLAS_ELT * A,
    size_t m,
    size_t n,
    size_t lda )
```

11.21.3.154 applyP() [4/4]

```
template INST_OR_DECL void applyP (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_SIDE Side,
    const FFLAS::FFLAS_TRANSPOSE Trans,
    const size_t M,
    const size_t ibeg,
    const size_t iend,
    FFLAS_ELT * A,
    const size_t lda,
    const size_t * P )
```

11.21.3.155 fgetrs() [3/4]

```
template INST_OR_DECL void fgetrs (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    const size_t R,
    FFLAS_ELT * A,
    const size_t lda,
    const size_t * P,
    const size_t * Q,
    FFLAS_ELT * B,
    const size_t ldb,
    int * info )
```

11.21.3.156 fgetrs() [4/4]

```

template INST_OR_DECL FFLAS_ELT * fgetrs (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    const size_t NRHS,
    const size_t R,
    FFLAS_ELT * A,
    const size_t lda,
    const size_t * P,
    const size_t * Q,
    FFLAS_ELT * X,
    const size_t ldx,
    const FFLAS_ELT * B,
    const size_t ldb,
    int * info )

```

11.21.3.157 fgesv() [3/4]

```

template INST_OR_DECL size_t fgesv (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * B,
    const size_t ldb,
    int * info )

```

11.21.3.158 fgesv() [4/4]

```

template INST_OR_DECL size_t fgesv (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    const size_t NRHS,
    FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * X,
    const size_t ldx,
    const FFLAS_ELT * B,
    const size_t ldb,
    int * info )

```

11.21.3.159 ftrtri() [2/2]

```

template INST_OR_DECL void ftrtri (
    const FFLAS_FIELD< FFLAS_ELT > & F,

```

```

const FFLAS::FFLAS_UPLO Uplo,
const FFLAS::FFLAS_DIAG Diag,
const size_t N,
FFLAS_ELT * A,
const size_t lda,
const size_t threshold )

```

11.21.3.160 trinv_left() [2/2]

```

template INST_OR_DECL void trinv_left (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t N,
    const FFLAS_ELT * L,
    const size_t ldl,
    FFLAS_ELT * X,
    const size_t idx )

```

11.21.3.161 ftrtrm() [2/2]

```

template INST_OR_DECL void ftrtrm (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_SIDE side,
    const FFLAS::FFLAS_DIAG diag,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda )

```

11.21.3.162 PLUQ() [6/6]

```

template INST_OR_DECL size_t PLUQ (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t * P,
    size_t * Q )

```

11.21.3.163 LUdivine() [4/4]

```

template INST_OR_DECL size_t LUdivine (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_DIAG Diag,
    const FFLAS::FFLAS_TRANSPOSE trans,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const FFPACK_LU_TAG LuTag,
    const size_t cutoff )

```

11.21.3.164 LUdivine_small() [2/2]

```
template INST_OR_DECL size_t LUdivine_small (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_DIAG Diag,
    const FFLAS::FFLAS_TRANSPOSE trans,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    const FFPACK_LU_TAG LuTag )
```

11.21.3.165 LUdivine_gauss() [2/2]

```
template INST_OR_DECL size_t LUdivine_gauss (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    const FFPACK_LU_TAG LuTag )
```

11.21.3.166 RowEchelonForm() [3/3]

```
template INST_OR_DECL size_t RowEchelonForm (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const bool transform,
    const FFPACK_LU_TAG LuTag )
```

11.21.3.167 ReducedRowEchelonForm() [3/3]

```
template INST_OR_DECL size_t ReducedRowEchelonForm (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const bool transform,
    const FFPACK_LU_TAG LuTag )
```

11.21.3.168 ColumnEchelonForm() [3/3]

```
template INST_OR_DECL size_t ColumnEchelonForm (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const bool transform,
    const FFPACK_LU_TAG LuTag )
```

11.21.3.169 ReducedColumnEchelonForm() [3/3]

```
template INST_OR_DECL size_t ReducedColumnEchelonForm (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t * P,
    size_t * Qt,
    const bool transform,
    const FFPACK_LU_TAG LuTag )
```

11.21.3.170 Invert() [3/4]

```
template INST_OR_DECL FFLAS_ELT * Invert (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    FFLAS_ELT * A,
    const size_t lda,
    int & nullity )
```

11.21.3.171 Invert() [4/4]

```
template INST_OR_DECL FFLAS_ELT * Invert (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * X,
    const size_t ldx,
    int & nullity )
```

11.21.3.172 Invert2() [2/2]

```
template INST_OR_DECL FFLAS_ELT * Invert2 (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * X,
    const size_t ldx,
    int & nullity )
```

11.21.3.173 CharPoly() [6/8]

```
template INST_OR_DECL std::list< Givaro::Poly1Dom< FFLAS_FIELD< FFLAS_ELT > >::Element > &
CharPoly (
    const Givaro::Poly1Dom< FFLAS_FIELD< FFLAS_ELT > > & R,
    std::list< Givaro::Poly1Dom< FFLAS_FIELD< FFLAS_ELT > >::Element > & charp,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    FFLAS_FIELD< FFLAS_ELT >::RandIter & G,
    const FFPACK_CHARPOLY_TAG CharpTag,
    const size_t degree )
```

11.21.3.174 CharPoly() [7/8]

```
template INST_OR_DECL Givaro::Poly1Dom< FFLAS_FIELD< FFLAS_ELT > >::Element & CharPoly (
    const Givaro::Poly1Dom< FFLAS_FIELD< FFLAS_ELT > > & R,
    Givaro::Poly1Dom< FFLAS_FIELD< FFLAS_ELT > >::Element & charp,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    FFLAS_FIELD< FFLAS_ELT >::RandIter & G,
    const FFPACK_CHARPOLY_TAG CharpTag,
    const size_t degree )
```

11.21.3.175 CharPoly() [8/8]

```
template INST_OR_DECL Givaro::Poly1Dom< FFLAS_FIELD< FFLAS_ELT > >::Element & CharPoly (
    const Givaro::Poly1Dom< FFLAS_FIELD< FFLAS_ELT > > & R,
    Givaro::Poly1Dom< FFLAS_FIELD< FFLAS_ELT > >::Element & charp,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    const FFPACK_CHARPOLY_TAG CharpTag,
    const size_t degree )
```

11.21.3.176 MinPoly() [3/4]

```
template INST_OR_DECL std::vector< FFLAS_ELT > & MinPoly (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    std::vector< FFLAS_ELT > & minP,
    const size_t N,
    const FFLAS_ELT * A,
    const size_t lda,
    FFLAS_FIELD< FFLAS_ELT >::RandIter & G )
```

11.21.3.177 MinPoly() [4/4]

```
template INST_OR_DECL std::vector< FFLAS_ELT > & MinPoly (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    std::vector< FFLAS_ELT > & minP,
    const size_t N,
    const FFLAS_ELT * A,
    const size_t lda )
```

11.21.3.178 MatVecMinPoly() [2/2]

```
template INST_OR_DECL std::vector< FFLAS_ELT > & MatVecMinPoly (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    std::vector< FFLAS_ELT > & minP,
    const size_t N,
    const FFLAS_ELT * A,
    const size_t lda,
    const FFLAS_ELT * V,
    const size_t incv )
```

11.21.3.179 KrylovElim()

```
template INST_OR_DECL size_t KrylovElim (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    const size_t deg,
    size_t * iterates,
    size_t * inviterates,
    const size_t maxit,
    size_t virt )
```

11.21.3.180 SpecRankProfile()

```
template INST_OR_DECL size_t SpecRankProfile (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    const size_t deg,
    size_t * rankProfile )
```

11.21.3.181 Rank() [3/3]

```
template INST_OR_DECL size_t Rank (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda )
```

11.21.3.182 IsSingular() [2/2]

```
template INST_OR_DECL bool IsSingular (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda )
```


11.21.3.183 Det() [5/6]

```
template INST_OR_DECL FFLAS_ELT & Det (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    FFLAS_ELT & det,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t * P,
    size_t * Q )
```

11.21.3.184 Det() [6/6]

```
template INST_OR_DECL FFLAS_ELT & Det (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    FFLAS_ELT & det,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    const FFLAS::ParSeqHelper::Parallel< FFLAS::CuttingStrategy::Recursive, FFLAS::StrategyParameter
> & parH,
    size_t * P,
    size_t * Q )
```

11.21.3.185 Solve() [3/3]

```
template INST_OR_DECL FFLAS_ELT * Solve (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * x,
    const int incx,
    const FFLAS_ELT * b,
    const int incb )
```

11.21.3.186 solveLB() [2/2]

```
template INST_OR_DECL void solveLB (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    const size_t R,
    FFLAS_ELT * L,
    const size_t ldl,
    const size_t * Q,
    FFLAS_ELT * B,
    const size_t ldb )
```

11.21.3.187 solveLB2() [2/2]

```
template INST_OR_DECL void solveLB2 (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    const size_t R,
    FFLAS_ELT * L,
    const size_t ldl,
    const size_t * Q,
    FFLAS_ELT * B,
    const size_t ldb )
```

11.21.3.188 RandomNullSpaceVector() [3/3]

```
template INST_OR_DECL void RandomNullSpaceVector (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * X,
    const size_t incX )
```

11.21.3.189 NullSpaceBasis() [2/2]

```
template INST_OR_DECL size_t NullSpaceBasis (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_SIDE Side,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT *& NS,
    size_t & ldn,
    size_t & NSdim )
```

11.21.3.190 RowRankProfile() [3/3]

```
template INST_OR_DECL size_t RowRankProfile (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t *& rkprofile,
    const FFPACK_LU_TAG LuTag )
```

11.21.3.191 ColumnRankProfile() [3/3]

```
template INST_OR_DECL size_t ColumnRankProfile (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t * rkprofile,
    const FFPACK_LU_TAG LuTag )
```

11.21.3.192 RowRankProfileSubmatrixIndices() [2/2]

```
template INST_OR_DECL size_t RowRankProfileSubmatrixIndices (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t * rowindices,
    size_t * colindices,
    size_t & R )
```

11.21.3.193 ColRankProfileSubmatrixIndices() [2/2]

```
template INST_OR_DECL size_t ColRankProfileSubmatrixIndices (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    size_t * rowindices,
    size_t * colindices,
    size_t & R )
```

11.21.3.194 RowRankProfileSubmatrix() [2/2]

```
template INST_OR_DECL size_t RowRankProfileSubmatrix (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * X,
    size_t & R )
```

11.21.3.195 ColRankProfileSubmatrix() [2/2]

```
template INST_OR_DECL size_t ColRankProfileSubmatrix (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t M,
    const size_t N,
    FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * X,
    size_t & R )
```

11.21.3.196 getTriangular< FFLAS_FIELD< FFLAS_ELT > >() [1/2]

```
template INST_OR_DECL void getTriangular< FFLAS_FIELD< FFLAS_ELT > > > (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG diag,
    const size_t M,
    const size_t N,
    const size_t R,
    const FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * T,
    const size_t ldt,
    const bool OnlyNonZeroVectors )
```

11.21.3.197 getTriangular< FFLAS_FIELD< FFLAS_ELT > >() [2/2]

```
template INST_OR_DECL void getTriangular< FFLAS_FIELD< FFLAS_ELT > > > (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG diag,
    const size_t M,
    const size_t N,
    const size_t R,
    FFLAS_ELT * A,
    const size_t lda )
```

11.21.3.198 getEchelonForm< FFLAS_FIELD< FFLAS_ELT > >() [1/2]

```
template INST_OR_DECL void getEchelonForm< FFLAS_FIELD< FFLAS_ELT > > > (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG diag,
    const size_t M,
    const size_t N,
    const size_t R,
    const size_t * P,
    const FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * T,
    const size_t ldt,
    const bool OnlyNonZeroVectors,
    const FFPACK_LU_TAG LuTag )
```

11.21.3.199 getEchelonForm< FFLAS_FIELD< FFLAS_ELT > >() [2/2]

```
template INST_OR_DECL void getEchelonForm< FFLAS_FIELD< FFLAS_ELT > > > (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG diag,
    const size_t M,
    const size_t N,
    const size_t R,
    const size_t * P,
    FFLAS_ELT * A,
    const size_t lda,
    const FFPACK_LU_TAG LuTag )
```

11.21.3.200 getEchelonTransform< FFLAS_FIELD< FFLAS_ELT > >()

```
template INST_OR_DECL void getEchelonTransform< FFLAS_FIELD< FFLAS_ELT > > (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const FFLAS::FFLAS_DIAG diag,
    const size_t M,
    const size_t N,
    const size_t R,
    const size_t * P,
    const size_t * Q,
    const FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * T,
    const size_t ldt,
    const FFPACK_LU_TAG LuTag )
```

11.21.3.201 getReducedEchelonForm< FFLAS_FIELD< FFLAS_ELT > >() [1/2]

```
template INST_OR_DECL void getReducedEchelonForm< FFLAS_FIELD< FFLAS_ELT > > (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const size_t M,
    const size_t N,
    const size_t R,
    const size_t * P,
    const FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * T,
    const size_t ldt,
    const bool OnlyNonZeroVectors,
    const FFPACK_LU_TAG LuTag )
```

11.21.3.202 getReducedEchelonForm< FFLAS_FIELD< FFLAS_ELT > >() [2/2]

```
template INST_OR_DECL void getReducedEchelonForm< FFLAS_FIELD< FFLAS_ELT > > (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const size_t M,
    const size_t N,
    const size_t R,
    const size_t * P,
    FFLAS_ELT * A,
    const size_t lda,
    const FFPACK_LU_TAG LuTag )
```

11.21.3.203 getReducedEchelonTransform< FFLAS_FIELD< FFLAS_ELT > >()

```
template INST_OR_DECL void getReducedEchelonTransform< FFLAS_FIELD< FFLAS_ELT > > (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const FFLAS::FFLAS_UPLO Uplo,
    const size_t M,
```

```

    const size_t N,
    const size_t R,
    const size_t * P,
    const size_t * Q,
    const FFLAS_ELT * A,
    const size_t lda,
    FFLAS_ELT * T,
    const size_t ldt,
    const FFPACK_LU_TAG LuTag )

```

11.21.3.204 LQUPtoInverseOfFullRankMinor() [2/2]

```

template INST_OR_DECL FFLAS_ELT * LQUPtoInverseOfFullRankMinor (
    const FFLAS_FIELD< FFLAS_ELT > & F,
    const size_t rank,
    FFLAS_ELT * A_factors,
    const size_t lda,
    const size_t * QtPointer,
    FFLAS_ELT * X,
    const size_t ldx )

```

11.21.3.205 fflas_const_cast() [3/3]

```

template<class T , class CT = const T>
T fflas_const_cast (
    CT x )

```

11.21.3.206 failure()

```

Failure & failure ( ) [inline]

```

11.21.3.207 isOdd() [1/3]

```

template<class T >
bool isOdd (
    const T & a ) [inline]

```

11.21.3.208 isOdd() [2/3]

```

bool isOdd (
    const float & a ) [inline]

```

11.21.3.209 isOdd() [3/3]

```

bool isOdd (
    const double & a ) [inline]

```

11.21.3.210 NonZeroRandomMatrix() [1/2]

```
template<class Field , class RandIter >
Field::Element_ptr NonZeroRandomMatrix (
    const Field & F,
    size_t m,
    size_t n,
    typename Field::Element_ptr A,
    size_t lda,
    RandIter & G ) [inline]
```

Random non-zero Matrix.

Creates a $m \times n$ matrix with random entries, and at least one of them is non zero.

Parameters

	F	field
	m	number of rows in A
	n	number of cols in A
out	A	the matrix (preallocated to at least $m \times lda$ field elements)
	lda	leading dimension of A
	G	a random iterator

Returns

A .

11.21.3.211 NonZeroRandomMatrix() [2/2]

```
template<class Field , class RandIter >
Field::Element_ptr NonZeroRandomMatrix (
    const Field & F,
    size_t m,
    size_t n,
    typename Field::Element_ptr A,
    size_t lda ) [inline]
```

Random non-zero Matrix.

Creates a $m \times n$ matrix with random entries, and at least one of them is non zero.

Parameters

	F	field
	m	number of rows in A
	n	number of cols in A
out	A	the matrix (preallocated to at least $m \times lda$ field elements)
	lda	leading dimension of A

Returns

A.

11.21.3.212 RandomMatrix() [1/2]

```
template<class Field , class RandIter >
Field::Element_ptr RandomMatrix (
    const Field & F,
    size_t m,
    size_t n,
    typename Field::Element_ptr A,
    size_t lda,
    RandIter & G ) [inline]
```

Random Matrix.

Creates a $m \times n$ matrix with random entries.

Parameters

	<i>F</i>	field
	<i>m</i>	number of rows in A
	<i>n</i>	number of cols in A
out	<i>A</i>	the matrix (preallocated to at least $m \times lda$ field elements)
	<i>lda</i>	leading dimension of A
	<i>G</i>	a random iterator

Returns

A.

11.21.3.213 RandomMatrix() [2/2]

```
template<class Field >
Field::Element_ptr RandomMatrix (
    const Field & F,
    size_t m,
    size_t n,
    typename Field::Element_ptr A,
    size_t lda ) [inline]
```

Random Matrix.

Creates a $m \times n$ matrix with random entries.

Parameters

	<i>F</i>	field
	<i>m</i>	number of rows in A
	<i>n</i>	number of cols in A
out	<i>A</i>	the matrix (preallocated to at least $m \times lda$ field elements)
	<i>lda</i>	leading dimension of A

Returns

A.

11.21.3.214 RandomTriangularMatrix() [1/2]

```
template<class Field , class RandIter >
Field::Element_ptr RandomTriangularMatrix (
    const Field & F,
    size_t m,
    size_t n,
    const FFLAS::FFLAS_UPLO UpLo,
    const FFLAS::FFLAS_DIAG Diag,
    bool nonsingular,
    typename Field::Element_ptr A,
    size_t lda,
    RandIter & G ) [inline]
```

Random Triangular Matrix.

Creates a $m \times n$ triangular matrix with random entries. The UpLo parameter defines whether it is upper or lower triangular.

Parameters

	<i>F</i>	field
	<i>m</i>	number of rows in A
	<i>n</i>	number of cols in A
	<i>UpLo</i>	whether A is upper or lower triangular
out	<i>A</i>	the matrix (preallocated to at least $m \times lda$ field elements)
	<i>lda</i>	leading dimension of A
	<i>G</i>	a random iterator

Returns

A.

11.21.3.215 RandomTriangularMatrix() [2/2]

```
template<class Field >
Field::Element_ptr RandomTriangularMatrix (
    const Field & F,
    size_t m,
    size_t n,
    const FFLAS::FFLAS_UPLO UpLo,
    const FFLAS::FFLAS_DIAG Diag,
    bool nonsingular,
    typename Field::Element_ptr A,
    size_t lda ) [inline]
```

Random Triangular Matrix.

Creates a $m \times n$ triangular matrix with random entries. The UpLo parameter defines whether it is upper or lower triangular.

Parameters

	F	field
	m	number of rows in A
	n	number of cols in A
	$UpLo$	whether A is upper or lower triangular
out	A	the matrix (preallocated to at least $m \times lda$ field elements)
	lda	leading dimension of A

Returns

A .

11.21.3.216 RandInt()

```
size_t RandInt (
    size_t a,
    size_t b ) [inline]
```

11.21.3.217 RandomSymmetricMatrix()

```
template<class Field , class RandIter >
Field::Element_ptr RandomSymmetricMatrix (
    const Field & F,
    size_t n,
    bool nonsingular,
    typename Field::Element_ptr A,
    size_t lda,
    RandIter & G ) [inline]
```

Random Symmetric Matrix.

Creates a $m \times n$ triangular matrix with random entries. The $UpLo$ parameter defines whether it is upper or lower triangular.

Parameters

	F	field
	n	order of A
out	A	the matrix (preallocated to at least $n \times lda$ field elements)
	lda	leading dimension of A
	G	a random iterator

Returns

A .

11.21.3.218 RandomMatrixWithRank() [1/2]

```
template<class Field , class RandIter >
Field::Element_ptr RandomMatrixWithRank (
    const Field & F,
    size_t m,
    size_t n,
    size_t r,
    typename Field::Element_ptr A,
    size_t lda,
    RandIter & G ) [inline]
```

Random Matrix with prescribed rank.

Creates an $m \times n$ matrix with random entries and rank r .

Parameters

F	field
m	number of rows in A
n	number of cols in A
r	rank of the matrix to build
A	the matrix (preallocated to at least $m \times lda$ field elements)
lda	leading dimension of A
G	a random iterator

Returns

A .

11.21.3.219 RandomMatrixWithRank() [2/2]

```
template<class Field >
Field::Element_ptr RandomMatrixWithRank (
    const Field & F,
    size_t m,
    size_t n,
    size_t r,
    typename Field::Element_ptr A,
    size_t lda ) [inline]
```

Random Matrix with prescribed rank.

Creates an $m \times n$ matrix with random entries and rank r .

Parameters

	F	field
	m	number of rows in A
	n	number of cols in A
	r	rank of the matrix to build
out	A	the matrix (preallocated to at least $m \times lda$ field elements)
	lda	leading dimension of A

Returns

A.

11.21.3.220 RandomIndexSubset()

```
size_t * RandomIndexSubset (
    size_t N,
    size_t R,
    size_t * P ) [inline]
```

Pick uniformly at random a sequence of R distinct elements from the set $\{0, \dots, N - 1\}$ using Knuth's shuffle.

Parameters

	N	the cardinality of the sampling set
	R	the number of elements to sample
out	P	the output sequence (pre-allocated to at least R indices)

11.21.3.221 RandomPermutation()

```
size_t * RandomPermutation (
    size_t N,
    size_t * P ) [inline]
```

Pick uniformly at random a permutation of size N stored in LAPACK format using Knuth's shuffle.

Parameters

	N	the length of the permutation
out	P	the output permutation (pre-allocated to at least N indices)

11.21.3.222 RandomRankProfileMatrix()

```
void RandomRankProfileMatrix (
    size_t M,
    size_t N,
    size_t R,
    size_t * rows,
    size_t * cols ) [inline]
```

Pick uniformly at random an R -subpermutation of dimension $M \times N$: a matrix with only R non-zeros equal to one, in a random rook placement.

Parameters

	M	row dimension
	N	column dimension
out	$rows$	the row position of each non zero element (pre-allocated)
out	$cols$	the column position of each non zero element (pre-allocated)

11.21.3.223 swapval()

```
void swapval (
    size_t k,
    size_t N,
    size_t * P,
    size_t val ) [inline]
```

11.21.3.224 RandomSymmetricRankProfileMatrix()

```
void RandomSymmetricRankProfileMatrix (
    size_t N,
    size_t R,
    size_t * rows,
    size_t * cols ) [inline]
```

Pick uniformly at random a symmetric R-subpermutation of dimension $N \times N$: a symmetric matrix with only R non-zeros, all equal to one, in a random rook placement.

Parameters

	<i>N</i>	matrix order
out	<i>rows</i>	the row position of each non zero element (pre-allocated)
out	<i>cols</i>	the column position of each non zero element (pre-allocated)

11.21.3.225 RandomLTQSRankProfileMatrix()

```
void RandomLTQSRankProfileMatrix (
    size_t n,
    size_t r,
    size_t t,
    size_t * rows,
    size_t * cols ) [inline]
```

11.21.3.226 RandomMatrixWithRankandRPM() [1/2]

```
template<class Field , class RandIter >
Field::Element_ptr RandomMatrixWithRankandRPM (
    const Field & F,
    size_t M,
    size_t N,
    size_t R,
    typename Field::Element_ptr A,
    size_t lda,
    const size_t * RRP,
    const size_t * CRP,
    RandIter & G ) [inline]
```

Random Matrix with prescribed rank and rank profile matrix Creates an $m \times n$ matrix with random entries and rank r .

Parameters

<i>F</i>	field
<i>m</i>	number of rows in A
<i>n</i>	number of cols in A
<i>r</i>	rank of the matrix to build
<i>A</i>	the matrix (preallocated to at least $m \times lda$ field elements)
<i>lda</i>	leading dimension of A
<i>RRP</i>	the R dimensional array with row positions of the rank profile matrix' pivots
<i>CRP</i>	the R dimensional array with column positions of the rank profile matrix' pivots
<i>G</i>	a random iterator

Returns

A.

11.21.3.227 RandomMatrixWithRankandRPM() [2/2]

```
template<class Field >
Field::Element_ptr RandomMatrixWithRankandRPM (
    const Field & F,
    size_t M,
    size_t N,
    size_t R,
    typename Field::Element_ptr A,
    size_t lda,
    const size_t * RRP,
    const size_t * CRP ) [inline]
```

Random Matrix with prescribed rank and rank profile matrix Creates an $m \times n$ matrix with random entries and rank r .

Parameters

<i>F</i>	field
<i>m</i>	number of rows in A
<i>n</i>	number of cols in A
<i>r</i>	rank of the matrix to build
<i>A</i>	the matrix (preallocated to at least $m \times lda$ field elements)
<i>lda</i>	leading dimension of A
<i>RRP</i>	the R dimensional array with row positions of the rank profile matrix' pivots
<i>CRP</i>	the R dimensional array with column positions of the rank profile matrix' pivots

Returns

A.

11.21.3.228 RandomSymmetricMatrixWithRankandRPM() [1/2]

```
template<class Field , class RandIter >
Field::Element_ptr RandomSymmetricMatrixWithRankandRPM (
```

```

const Field & F,
size_t N,
size_t R,
typename Field::Element_ptr A,
size_t lda,
const size_t * RRP,
const size_t * CRP,
RandIter & G ) [inline]

```

Random Symmetric Matrix with prescribed rank and rank profile matrix Creates an $n \times n$ symmetric matrix with random entries and rank r .

Parameters

<i>F</i>	field
<i>n</i>	order of A
<i>r</i>	rank of A
<i>A</i>	the matrix (preallocated to at least $n \times lda$ field elements)
<i>lda</i>	leading dimension of A
<i>RRP</i>	the R dimensional array with row positions of the rank profile matrix' pivots
<i>CRP</i>	the R dimensional array with column positions of the rank profile matrix' pivots
<i>G</i>	a random iterator

Returns

A.

11.21.3.229 RandomSymmetricMatrixWithRankandRPM() [2/2]

```

template<class Field >
Field::Element_ptr RandomSymmetricMatrixWithRankandRPM (
    const Field & F,
    size_t M,
    size_t N,
    size_t R,
    typename Field::Element_ptr A,
    size_t lda,
    const size_t * RRP,
    const size_t * CRP ) [inline]

```

Random Symmetric Matrix with prescribed rank and rank profile matrix Creates an $n \times n$ symmetric matrix with random entries and rank r .

Parameters

<i>F</i>	field
<i>n</i>	order of A
<i>r</i>	rank of A
<i>A</i>	the matrix (preallocated to at least $n \times lda$ field elements)
<i>lda</i>	leading dimension of A
<i>RRP</i>	the R dimensional array with row positions of the rank profile matrix' pivots
<i>CRP</i>	the R dimensional array with column positions of the rank profile matrix' pivots

Returns

A.

11.21.3.230 RandomMatrixWithRankandRandomRPM() [1/2]

```
template<class Field , class RandIter >
Field::Element_ptr RandomMatrixWithRankandRandomRPM (
    const Field & F,
    size_t M,
    size_t N,
    size_t R,
    typename Field::Element_ptr A,
    size_t lda,
    RandIter & G ) [inline]
```

Random Matrix with prescribed rank, with random rank profile matrix Creates an $m \times n$ matrix with random entries, rank r and with a rank profile matrix chosen uniformly at random.

Parameters

F	field
m	number of rows in A
n	number of cols in A
r	rank of the matrix to build
A	the matrix (preallocated to at least $m \times lda$ field elements)
lda	leading dimension of A
G	a random iterator

Returns

A.

11.21.3.231 RandomMatrixWithRankandRandomRPM() [2/2]

```
template<class Field >
Field::Element_ptr RandomMatrixWithRankandRandomRPM (
    const Field & F,
    size_t M,
    size_t N,
    size_t R,
    typename Field::Element_ptr A,
    size_t lda ) [inline]
```

Random Matrix with prescribed rank, with random rank profile matrix Creates an $m \times n$ matrix with random entries, rank r and with a rank profile matrix chosen uniformly at random.

Parameters

F	field
m	number of rows in A
n	number of cols in A
r	rank of the matrix to build
A	the matrix (preallocated to at least $m \times lda$ field elements)
lda	leading dimension of A

Returns

A.

11.21.3.232 RandomSymmetricMatrixWithRankandRandomRPM() [1/2]

```
template<class Field , class RandIter >
Field::Element_ptr RandomSymmetricMatrixWithRankandRandomRPM (
    const Field & F,
    size_t N,
    size_t R,
    typename Field::Element_ptr A,
    size_t lda,
    RandIter & G ) [inline]
```

Random Symmetric Matrix with prescribed rank, with random rank profile matrix Creates an $n \times n$ matrix with random entries, rank r and with a rank profile matrix chosen uniformly at random.

Parameters

F	field
n	order of A
r	rank of A
A	the matrix (preallocated to at least $n \times lda$ field elements)
lda	leading dimension of A
G	a random iterator

Returns

A.

11.21.3.233 RandomSymmetricMatrixWithRankandRandomRPM() [2/2]

```
template<class Field >
Field::Element_ptr RandomSymmetricMatrixWithRankandRandomRPM (
    const Field & F,
    size_t N,
    size_t R,
    typename Field::Element_ptr A,
    size_t lda ) [inline]
```

Random Symmetric Matrix with prescribed rank, with random rank profile matrix Creates an $n \times n$ matrix with random entries, rank r and with a rank profile matrix chosen uniformly at random.

Parameters

F	field
n	order of A
r	rank of A
A	the matrix (preallocated to at least $n \times lda$ field elements)
lda	leading dimension of A

Returns

A.

11.21.3.234 RandomMatrixWithDet() [1/2]

```
template<class Field >
Field::Element_ptr RandomMatrixWithDet (
    const Field & F,
    size_t n,
    const typename Field::Element d,
    typename Field::Element_ptr A,
    size_t lda ) [inline]
```

Random Matrix with prescribed det.

Creates a $m \times n$ matrix with random entries and rank r .

Parameters

F	field
d	the prescribed value for the determinant of A
n	number of cols in A
A	the matrix to be generated (preallocated to at least $n \times lda$ field elements)
lda	leading dimension of A

Returns

A.

11.21.3.235 RandomMatrixWithDet() [2/2]

```
template<class Field , class RandIter >
Field::Element_ptr RandomMatrixWithDet (
    const Field & F,
    size_t n,
    const typename Field::Element d,
    typename Field::Element_ptr A,
    size_t lda,
    RandIter & G ) [inline]
```

Random Matrix with prescribed det.

Creates a $m \times n$ matrix with random entries and rank r .

Parameters

F	field
d	the prescribed value for the determinant of A
n	number of cols in A
A	the matrix to be generated (preallocated to at least $n \times lda$ field elements)
lda	leading dimension of A

Returns

A.

11.21.3.236 RandomLTQSMATRIXWithRankandQSOrder()

```
template<class Field , class RandIter >
Field::Element_ptr RandomLTQSMATRIXWithRankandQSOrder (
    Field & F,
    size_t n,
    size_t r,
    size_t t,
    typename Field::Element_ptr A,
    size_t lda,
    RandIter & G ) [inline]
```

11.21.3.237 chooseField()

```
template<typename Field >
Field * chooseField (
    Givaro::Integer q,
    uint64_t b,
    uint64_t seed )
```

11.21.3.238 chooseField< Givaro::ZRing< int32_t > >()

```
template<>
Givaro::ZRing< int32_t > * chooseField< Givaro::ZRing< int32_t > > (
    Givaro::Integer q,
    uint64_t b,
    uint64_t seed )
```

11.21.3.239 chooseField< Givaro::ZRing< int64_t > >()

```
template<>
Givaro::ZRing< int64_t > * chooseField< Givaro::ZRing< int64_t > > (
    Givaro::Integer q,
    uint64_t b,
    uint64_t seed )
```

11.21.3.240 chooseField< Givaro::ZRing< float > >()

```
template<>
Givaro::ZRing< float > * chooseField< Givaro::ZRing< float > > (
    Givaro::Integer q,
    uint64_t b,
    uint64_t seed )
```

11.21.3.241 chooseField< Givaro::ZRing< double > >()

```
template<>
Givaro::ZRing< double > * chooseField< Givaro::ZRing< double > > (
    Givaro::Integer q,
    uint64_t b,
    uint64_t seed )
```

11.22 FFPACK::Protected Namespace Reference

Functions

- template<class [Field](#) >
size_t [LUdivine_construct](#) (const [Field](#) &F, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) X, const size_t ldx, typename [Field::Element_ptr](#) u, const size_t incu, size_t *P, bool computeX, const FFPACK_MINPOLY_TAG MinTag=[FpackDense](#), const size_t kg_mc=0, const size_t kg_mb=0, const size_t kg_j=0)
- template<class [Field](#) >
size_t [GaussJordan](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, const size_t colbeg, const size_t rowbeg, const size_t colsize, size_t *P, size_t *Q, const FFPACK::FFPACK_LU_TAG LuTag)
Gauss-Jordan algorithm computing the Reduced Row echelon form and its transform matrix.
- template<class [Field](#) , class Polynomial >
std::list< Polynomial > & [KellerGehrig](#) (const [Field](#) &F, std::list< Polynomial > &charp, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda)
- template<class [Field](#) , class Polynomial >
int [KGFast](#) (const [Field](#) &F, std::list< Polynomial > &charp, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, size_t *kg_mc, size_t *kg_mb, size_t *kg_j)
- template<class [Field](#) , class Polynomial >
std::list< Polynomial > & [KGFast_generalized](#) (const [Field](#) &F, std::list< Polynomial > &charp, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda)
- template<class [Field](#) >
void [fgemv_kgf](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::Element_ptr](#) Y, const size_t incY, const size_t kg_mc, const size_t kg_mb, const size_t kg_j)
- template<class [Field](#) , class Polynomial , class RandIter >
std::list< Polynomial > & [LUKrylov](#) (const [Field](#) &F, std::list< Polynomial > &charp, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) U, const size_t ldu, RandIter &G)
- template<class [Field](#) , class Polynomial >
std::list< Polynomial > & [Danilevski](#) (const [Field](#) &F, std::list< Polynomial > &charp, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda)
- template<class PolRing >
void [RandomKrylovPrecond](#) (const PolRing &PR, std::list< typename PolRing::Element > &completedFactors, const size_t N, typename PolRing::Domain_t::Element_ptr A, const size_t lda, size_t &Nb, typename PolRing::Domain_t::Element_ptr &B, size_t &ldb, typename PolRing::Domain_t::RandIter &g, const size_t degree=__FFLASFFPACK_ARITHPROG_THRESHOLD)
- template<class PolRing >
std::list< typename PolRing::Element > & [ArithProg](#) (const PolRing &PR, std::list< typename PolRing::Element > &frobeniusForm, const size_t N, typename PolRing::Domain_t::Element_ptr A, const size_t lda, const size_t degree)
- template<class [Field](#) , class Polynomial >
std::list< Polynomial > & [LUKrylov_KGFast](#) (const [Field](#) &F, std::list< Polynomial > &charp, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) X, const size_t ldx)

- template<class [Field](#) , class Polynomial >
Polynomial & [MatVecMinPoly](#) (const [Field](#) &F, Polynomial &minP, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) v, const size_t incv, typename [Field::Element_ptr](#) K, const size_t ldk, size_t *P)
- template<class [Field](#) , class Polynomial >
Polynomial & [Hybrid_KGF_LUK_MinPoly](#) (const [Field](#) &F, Polynomial &minP, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) X, const size_t ldx, size_t *P, const FFPACK_MINPOLY_TAG MinTag=FFPACK::FfpackDense, const size_t kg_mc=0, const size_t kg_↵mb=0, const size_t kg_j=0)
- template<class [Field](#) >
size_t [updated](#) (const [Field](#) &F, size_t *d, size_t k, std::vector< std::vector< typename [Field::Element](#) > > &minpt)
- template<class [Field](#) >
size_t [newD](#) (const [Field](#) &F, size_t *d, bool &KeepOn, const size_t l, const size_t N, typename [Field::Element_ptr](#) X, const size_t *Q, std::vector< std::vector< typename [Field::Element](#) > > &minpt)
- template<class [Field](#) >
void [CompressRows](#) ([Field](#) &F, const size_t M, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) tmp, const size_t ldtmp, const size_t *d, const size_t nb_blocs)
- template<class [Field](#) >
void [CompressRowsQK](#) ([Field](#) &F, const size_t M, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) tmp, const size_t ldtmp, const size_t *d, const size_t deg, const size_t nb_blocs)
- template<class [Field](#) >
void [DeCompressRows](#) ([Field](#) &F, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t ↵_t lda, typename [Field::Element_ptr](#) tmp, const size_t ldtmp, const size_t *d, const size_t nb_blocs)
- template<class [Field](#) >
void [DeCompressRowsQK](#) ([Field](#) &F, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) tmp, const size_t ldtmp, const size_t *d, const size_t deg, const size_t nb_blocs)
- template<class [Field](#) >
void [CompressRowsQA](#) ([Field](#) &F, const size_t M, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) tmp, const size_t ldtmp, const size_t *d, const size_t nb_blocs)
- template<class [Field](#) >
void [DeCompressRowsQA](#) ([Field](#) &F, const size_t M, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) tmp, const size_t ldtmp, const size_t *d, const size_t nb_blocs)
- template<class [Field](#) >
size_t [LUdivine_construct](#) (const [Field](#) &F, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t M, const size_t ↵_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) X, const size_t ldx, typename [Field::Element_ptr](#) u, const size_t incu, size_t *P, bool computeX, const FFPACK::FFPACK ↵_MINPOLY_TAG MinTag, const size_t kg_mc, const size_t kg_mb, const size_t kg_j)

11.22.1 Function Documentation

11.22.1.1 LUdivine_construct() [1/2]

```
template<class Field >
size_t LUdivine_construct (
    const Field & F,
    const FFLAS::FFLAS\_DIAG Diag,
    const size_t M,
    const size_t N,
    typename Field::ConstElement\_ptr A,
    const size_t lda,
    typename Field::Element\_ptr X,
    const size_t ldx,
    typename Field::Element\_ptr u,
```

```

const size_t incu,
size_t * P,
bool computeX,
const FFPACK_MINPOLY_TAG MinTag = FfpackDense,
const size_t kg_mc = 0,
const size_t kg_mb = 0,
const size_t kg_j = 0 )

```

11.22.1.2 GaussJordan()

```

template<class Field >
size_t GaussJordan (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    const size_t colbeg,
    const size_t rowbeg,
    const size_t colsize,
    size_t * P,
    size_t * Q,
    const FFPACK::FFPACK_LU_TAG LuTag ) [inline]

```

Gauss-Jordan algorithm computing the Reduced Row echelon form and its transform matrix.

- Bibliography**
- Algorithm 2.8 of A. Storjohann Thesis 2000,
 - Algorithm 11 of Jeannerod C-P., Pernet, C. and Storjohann, A. *Rank-profile revealing Gaussian elimination and the CUP matrix decomposition*, J. of Symbolic Comp., 2013

Parameters

	<i>M</i>	row dimension of A
	<i>N</i>	column dimension of A
<i>in, out</i>	<i>A</i>	an m x n matrix
	<i>lda</i>	leading dimension of A
	<i>P</i>	row permutation
	<i>Q</i>	column permutation
	<i>LuTag</i>	set the base case to a Tile (FfpackGaussJordanTile) or Slab (FfpackGaussJordanSlab) recursive RedEchelon

where the transformation matrix is stored at the pivot column position

11.22.1.3 KellerGehrig()

```

template<class Field , class Polynomial >
std::list< Polynomial > & KellerGehrig (
    const Field & F,
    std::list< Polynomial > & charp,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda )

```

11.22.1.4 KGFast()

```
template<class Field , class Polynomial >
int KGFast (
    const Field & F,
    std::list< Polynomial > & charp,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * kg_mc,
    size_t * kg_mb,
    size_t * kg_j )
```

11.22.1.5 KGFast_generalized()

```
template<class Field , class Polynomial >
std::list< Polynomial > & KGFast_generalized (
    const Field & F,
    std::list< Polynomial > & charp,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda )
```

11.22.1.6 fgemv_kgf()

```
template<class Field >
void fgemv_kgf (
    const Field & F,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr X,
    const size_t incX,
    typename Field::Element_ptr Y,
    const size_t incY,
    const size_t kg_mc,
    const size_t kg_mb,
    const size_t kg_j )
```

11.22.1.7 LUKrylov()

```
template<class Field , class Polynomial , class RandIter >
std::list< Polynomial > & LUKrylov (
    const Field & F,
    std::list< Polynomial > & charp,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr U,
    const size_t ldu,
    RandIter & G )
```

11.22.1.8 Danilevski()

```
template<class Field , class Polynomial >
std::list< Polynomial > & Danilevski (
    const Field & F,
    std::list< Polynomial > & charp,
    const size_t N,
```

```

typename Field::Element_ptr A,
const size_t lda )

```

11.22.1.9 RandomKrylovPrecond()

```

template<class PolRing >
void RandomKrylovPrecond (
    const PolRing & PR,
    std::list< typename PolRing::Element > & completedFactors,
    const size_t N,
    typename PolRing::Domain_t::Element_ptr A,
    const size_t lda,
    size_t & Nb,
    typename PolRing::Domain_t::Element_ptr & B,
    size_t & ldb,
    typename PolRing::Domain_t::RandIter & g,
    const size_t degree = __FFLASFFPACK_ARITHPROG_THRESHOLD ) [inline]

```

Todo swap to save space ??

Todo

Todo don't assing K2 c*noc x N but only mas (c,noc) x N and store each one after the other

Todo swap to save space ??

Todo

Todo don't assing K2 c*noc x N but only mas (c,noc) x N and store each one after the other

11.22.1.10 ArithProg()

```

template<class PolRing >
std::list< typename PolRing::Element > & ArithProg (
    const PolRing & PR,
    std::list< typename PolRing::Element > & frobeniusForm,
    const size_t N,
    typename PolRing::Domain_t::Element_ptr A,
    const size_t lda,
    const size_t degree ) [inline]

```

11.22.1.11 LUKrylov_KGFast()

```

template<class Field , class Polynomial >
std::list< Polynomial > & LUKrylov_KGFast (
    const Field & F,
    std::list< Polynomial > & charp,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr X,
    const size_t ldx )

```

11.22.1.12 MatVecMinPoly()

```

template<class Field , class Polynomial >
Polynomial & MatVecMinPoly (
    const Field & F,

```



```

Polynomial & minP,
const size_t N,
typename Field::ConstElement_ptr A,
const size_t lda,
typename Field::Element_ptr v,
const size_t incv,
typename Field::Element_ptr K,
const size_t ldk,
size_t * P ) [inline]

```

11.22.1.13 Hybrid_KGF_LUK_MinPoly()

```

template<class Field , class Polynomial >
Polynomial & Hybrid_KGF_LUK_MinPoly (
    const Field & F,
    Polynomial & minP,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr X,
    const size_t ldx,
    size_t * P,
    const FFPACK_MINPOLY_TAG MinTag = FFPACK::FfpackDense,
    const size_t kg_mc = 0,
    const size_t kg_mb = 0,
    const size_t kg_j = 0 )

```

11.22.1.14 updateD()

```

template<class Field >
size_t updateD (
    const Field & F,
    size_t * d,
    size_t k,
    std::vector< std::vector< typename Field::Element > > & minpt )

```

11.22.1.15 newD()

```

template<class Field >
size_t newD (
    const Field & F,
    size_t * d,
    bool & KeepOn,
    const size_t l,
    const size_t N,
    typename Field::Element_ptr X,
    const size_t * Q,
    std::vector< std::vector< typename Field::Element > > & minpt )

```

11.22.1.16 CompressRows()

```

template<class Field >
void CompressRows (
    Field & F,
    const size_t M,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr tmp,
    const size_t ldtmp,

```

```

    const size_t * d,
    const size_t nb_blocs ) [inline]

```

11.22.1.17 CompressRowsQK()

```

template<class Field >
void CompressRowsQK (
    Field & F,
    const size_t M,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr tmp,
    const size_t ldtmp,
    const size_t * d,
    const size_t deg,
    const size_t nb_blocs ) [inline]

```

11.22.1.18 DeCompressRows()

```

template<class Field >
void DeCompressRows (
    Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr tmp,
    const size_t ldtmp,
    const size_t * d,
    const size_t nb_blocs ) [inline]

```

11.22.1.19 DeCompressRowsQK()

```

template<class Field >
void DeCompressRowsQK (
    Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr tmp,
    const size_t ldtmp,
    const size_t * d,
    const size_t deg,
    const size_t nb_blocs ) [inline]

```

11.22.1.20 CompressRowsQA()

```

template<class Field >
void CompressRowsQA (
    Field & F,
    const size_t M,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr tmp,
    const size_t ldtmp,
    const size_t * d,
    const size_t nb_blocs ) [inline]

```

11.22.1.21 DeCompressRowsQA()

```
template<class Field >
void DeCompressRowsQA (
    Field & F,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    typename Field::Element_ptr tmp,
    const size_t ldtmp,
    const size_t * d,
    const size_t nb_blocs ) [inline]
```

11.22.1.22 LUdivine_construct() [2/2]

```
template<class Field >
size_t LUdivine_construct (
    const Field & F,
    const FFLAS::FFLAS_DIAG Diag,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::Element_ptr X,
    const size_t ldx,
    typename Field::Element_ptr u,
    const size_t incu,
    size_t * P,
    bool computeX,
    const FFPACK::FFPACK_MINPOLY_TAG MinTag,
    const size_t kg_mc,
    const size_t kg_mb,
    const size_t kg_j )
```

11.23 Givaro Namespace Reference**Data Structures**

- class [ModularBalanced](#)
- class [Montgomery](#)

11.24 MKL_CONFIG Namespace Reference**11.25 Reclnt Namespace Reference****Data Structures**

- class [rint](#)
- class [ruint](#)

Chapter 12

Data Structure Documentation

12.1 AlgoChooser< ModeT, ParSeq > Struct Template Reference

Public Types

- typedef [MMHelperAlgo::Winograd value](#)

12.1.1 Member Typedef Documentation

12.1.1.1 value

```
template<class ModeT , class ParSeq >
typedef MMHelperAlgo::Winograd value
```

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.2 AlgoChooser< ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeq > Struct Template Reference

Public Types

- typedef [MMHelperAlgo::Classic value](#)

12.2.1 Member Typedef Documentation

12.2.1.1 value

```
template<class ParSeq >
typedef MMHelperAlgo::Classic value
```

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.3 ALL< v > Struct Template Reference

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.4 ALL< false, v... > Struct Template Reference

Static Public Attributes

- static constexpr bool [value](#) = false

12.4.1 Field Documentation

12.4.1.1 value

```
template<bool... v>
constexpr bool value = false [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.5 ALL< true, v... > Struct Template Reference

Static Public Attributes

- static constexpr bool [value](#) = [ALL<v...>::value](#)

12.5.1 Field Documentation

12.5.1.1 value

```
template<bool... v>
constexpr bool value = ALL<v...>::value [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.6 ALL<> Struct Reference

Static Public Attributes

- static constexpr bool [value](#) = true

12.6.1 Field Documentation

12.6.1.1 value

```
constexpr bool value = true [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.7 ArbitraryPrecIntTag Struct Reference

Arbitrary precision integers: GMP.

```
#include <field-traits.h>
```

12.7.1 Detailed Description

Arbitrary precision integers: GMP.

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.8 AreEqual< X, Y > Class Template Reference

```
#include <fflas_enum.h>
```

Static Public Attributes

- static const bool [value](#) = false

12.8.1 Field Documentation

12.8.1.1 value

```
template<class X , class Y >
const bool value = false [static]
```

The documentation for this class was generated from the following file:

- [fflas_enum.h](#)

12.9 AreEqual< X, X > Class Template Reference

```
#include <fflas_enum.h>
```

Static Public Attributes

- static const bool [value](#) = true

12.9.1 Field Documentation

12.9.1.1 value

```
template<class X >
const bool value = true [static]
```

The documentation for this class was generated from the following file:

- [fflas_enum.h](#)

12.10 Argument Struct Reference

```
#include <args-parser.h>
```

Data Fields

- char [c](#)
- const char * [example](#)
- const char * [helpString](#)
- [ArgumentType](#) type
- void * [data](#)

12.10.1 Field Documentation

12.10.1.1 c

```
char c
```

12.10.1.2 example

```
const char* example
```

12.10.1.3 helpString

```
const char* helpString
```

12.10.1.4 type

```
ArgumentType type
```

12.10.1.5 data

```
void* data
```

The documentation for this struct was generated from the following file:

- [args-parser.h](#)

12.11 associatedDelayedField< Field > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [Field](#) [field](#)
- typedef [Field](#) & [type](#)

12.11.1 Member Typedef Documentation

12.11.1.1 field

```
template<class Field >
typedef Field field
```

12.11.1.2 type

```
template<class Field >
typedef Field& type
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.12 associatedDelayedField< const FFPACK::RNSIntegerMod< RNS > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FFPACK::RNSInteger](#)< [RNS](#) > [field](#)
- typedef [FFPACK::RNSInteger](#)< [RNS](#) > [type](#)

12.12.1 Member Typedef Documentation

12.12.1.1 field

```
template<typename RNS >
typedef FFPACK::RNSInteger<RNS> field
```


12.12.1.2 type

```
template<typename RNS >
typedef FFPACK::RNSInteger<RNS> type
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.13 associatedDelayedField< const Givaro::Modular< T, X > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef Givaro::ZRing< T > [field](#)
- typedef Givaro::ZRing< T > [type](#)

12.13.1 Member Typedef Documentation

12.13.1.1 field

```
template<typename T , typename X >
typedef Givaro::ZRing<T> field
```

12.13.1.2 type

```
template<typename T , typename X >
typedef Givaro::ZRing<T> type
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.14 associatedDelayedField< const Givaro::ModularBalanced< T > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef Givaro::ZRing< T > [field](#)
- typedef Givaro::ZRing< T > [type](#)

12.14.1 Member Typedef Documentation

12.14.1.1 field

```
template<typename T >
typedef Givaro::ZRing<T> field
```

12.14.1.2 type

```
template<typename T >
typedef Givaro::ZRing<T> type
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.15 associatedDelayedField< const Givaro::ZRing< T > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef Givaro::ZRing< T > [field](#)
- typedef Givaro::ZRing< T > [type](#)

12.15.1 Member Typedef Documentation

12.15.1.1 field

```
template<typename T >
typedef Givaro::ZRing<T> field
```

12.15.1.2 type

```
template<typename T >
typedef Givaro::ZRing<T> type
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.16 Auto Struct Reference

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.17 Bench< Elt > Class Template Reference

Public Types

- using [Field](#) = Modular< Elt >
- using [Elt_ptr](#) = typename [Field::Element_ptr](#)
- using [Residu](#) = typename [Field::Residu_t](#)
- template<bool B, class T = void>
 using [enable_if_t](#) = typename std::enable_if< B, T >::type
- template<typename [Simd](#) >
 using [is_same_element](#) = typename [Simd::template is_same_element](#)< [Field](#) >
- template<typename E >
 using [enable_if_no_simd_t](#) = [enable_if_t](#)< [Simd](#)< E >::vect_size==1 >
- template<typename E >
 using [enable_if_simd128_t](#) = [enable_if_t](#)< sizeof(E) *[Simd](#)< E >::vect_size==16 >
- template<typename E >
 using [enable_if_simd256_t](#) = [enable_if_t](#)< sizeof(E) *[Simd](#)< E >::vect_size==32 >
- template<typename E >
 using [enable_if_simd512_t](#) = [enable_if_t](#)< sizeof(E) *[Simd](#)< E >::vect_size==64 >

Public Member Functions

- [Bench](#) (size_t m, size_t n, size_t iters, bool inplace)
- template<typename [Simd](#) = NoSimd<Elt>, [enable_if_t](#)< [is_same_element](#)< [Simd](#) >::value > * = nullptr>
 void [doBenchs](#) ()
- template<typename _E = Elt, [enable_if_t](#)< is_same< _E, Elt >::value > * = nullptr, [enable_if_no_simd_t](#)< _E > * = nullptr>
 void [run](#) (bool allsimd)

Static Public Member Functions

- `template<typename _E = Elt, enable\_if\_t<lis_same<_E, Givaro::Integer>::value> * = nullptr> static Residu cardinality ()`
- `template<typename _E = Elt, enable\_if\_t<is_same<_E, Givaro::Integer>::value> * = nullptr> static Residu cardinality ()`

Protected Attributes

- [Field F](#)
- `const size_t m`
- `const size_t n`
- `const size_t iters`
- `const bool inplace`

12.17.1 Member Typedef Documentation**12.17.1.1 Field**

```
template<typename Elt >
using Field = Modular<Elt>
```

12.17.1.2 Elt_ptr

```
template<typename Elt >
using Elt\_ptr = typename Field::Element\_ptr
```

12.17.1.3 Residu

```
template<typename Elt >
using Residu = typename Field::Residu\_t
```

12.17.1.4 enable_if_t

```
template<typename Elt >
template<bool B, class T = void>
using enable\_if\_t = typename std::enable_if<B, T>::type
```

12.17.1.5 is_same_element

```
template<typename Elt >
template<typename Simd >
using is\_same\_element = typename Simd::template is\_same\_element<Field>
```

12.17.1.6 enable_if_no_simd_t

```
template<typename Elt >
template<typename E >
using enable\_if\_no\_simd\_t = enable\_if\_t<Simd<E>::vect_size == 1>
```

12.17.1.7 enable_if_simd128_t

```
template<typename Elt >
template<typename E >
using enable\_if\_simd128\_t = enable\_if\_t<sizeof(E)*Simd<E>::vect_size == 16>
```

12.17.1.8 enable_if_simd256_t

```
template<typename Elt >
template<typename E >
using enable\_if\_simd256\_t = enable\_if\_t<sizeof(E)*Simd<E>::vect_size == 32>
```

12.17.1.9 enable_if_simd512_t

```
template<typename Elt >
template<typename E >
using enable_if_simd512_t = enable_if_t<sizeof(E)*Simd<E>::vect_size == 64>
```

12.17.2 Constructor & Destructor Documentation

12.17.2.1 Bench()

```
template<typename Elt >
Bench (
    size_t m,
    size_t n,
    size_t iters,
    bool inplace ) [inline]
```

12.17.3 Member Function Documentation

12.17.3.1 cardinality() [1/2]

```
template<typename Elt >
template<typename _E = Elt, enable_if_t<!is_same< _E, Givaro::Integer >::value > * = nullptr>
static Residu cardinality ( ) [inline], [static]
```

12.17.3.2 cardinality() [2/2]

```
template<typename Elt >
template<typename _E = Elt, enable_if_t< is_same< _E, Givaro::Integer >::value > * = nullptr>
static Residu cardinality ( ) [inline], [static]
```

12.17.3.3 doBenchs()

```
template<typename Elt >
template<typename Simd = NoSimd<Elt>, enable_if_t< is_same_element< Simd >::value > * =
nullptr>
void doBenchs ( ) [inline]
```

12.17.3.4 run()

```
template<typename Elt >
template<typename _E = Elt, enable_if_t< is_same< _E, Elt >::value > * = nullptr, enable_if_no_simd_t<
_E > * = nullptr>
void run (
    bool allsimd ) [inline]
```

12.17.4 Field Documentation

12.17.4.1 F

```
template<typename Elt >
Field F [protected]
```

12.17.4.2 m

```
template<typename Elt >
const size_t m [protected]
```

12.17.4.3 n

```
template<typename Elt >
const size_t n [protected]
```

12.17.4.4 iters

```
template<typename Elt >
const size_t iters [protected]
```

12.17.4.5 inplace

```
template<typename Elt >
const bool inplace [protected]
```

The documentation for this class was generated from the following file:

- [benchmark-storage-transpose.C](#)

12.18 Bini Struct Reference

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.19 Block Struct Reference

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.20 BlockTransposeSIMD< Field, Simd, > Struct Template Reference

```
#include <fflas_transpose.h>
```

Public Member Functions

- `template<size_t s = Simd::vect_size, lsSimdSize<_s, 1> * = nullptr>`
void [transpose](#) (const [Field](#) &F, ConstElement_ptr A, size_t lda, Element_ptr B, size_t ldb) const
- `template<size_t s = Simd::vect_size, lsSimdSize<_s, 2> * = nullptr>`
void [transpose](#) (const [Field](#) &F, ConstElement_ptr A, size_t lda, Element_ptr B, size_t ldb) const
- `template<size_t s = Simd::vect_size, lsSimdSize<_s, 4> * = nullptr>`
void [transpose](#) (const [Field](#) &F, ConstElement_ptr A, size_t lda, Element_ptr B, size_t ldb) const
- `template<size_t s = Simd::vect_size, lsSimdSize<_s, 8> * = nullptr>`
void [transpose](#) (const [Field](#) &F, ConstElement_ptr A, size_t lda, Element_ptr B, size_t ldb) const
- `template<size_t s = Simd::vect_size, lsSimdSize<_s, 16> * = nullptr>`
void [transpose](#) (const [Field](#) &F, ConstElement_ptr A, size_t lda, Element_ptr B, size_t ldb) const

Static Public Member Functions

- static constexpr size_t [size](#) ()
- static const std::string [info](#) ()

12.20.1 Member Function Documentation**12.20.1.1 size()**

```
template<typename Field , typename Simd , typename std::enable_if< Simd::template is_same_↔
element< Field >::value >::type * = nullptr>
static constexpr size_t size ( ) [inline], [static], [constexpr]
```

12.20.1.2 info()

```
template<typename Field , typename Simd , typename std::enable_if< Simd::template is_same_↵
element< Field >::value >::type * = nullptr>
static const std::string info ( ) [inline], [static]
```

12.20.1.3 transpose() [1/5]

```
template<typename Field , typename Simd , typename std::enable_if< Simd::template is_same_↵
element< Field >::value >::type * = nullptr>
template<size_t _s = Simd::vect_size, IsSimdSize< _s, 1 > * = nullptr>
void transpose (
    const Field & F,
    ConstElement_ptr A,
    size_t lda,
    Element_ptr B,
    size_t ldb ) const [inline]
```

12.20.1.4 transpose() [2/5]

```
template<typename Field , typename Simd , typename std::enable_if< Simd::template is_same_↵
element< Field >::value >::type * = nullptr>
template<size_t _s = Simd::vect_size, IsSimdSize< _s, 2 > * = nullptr>
void transpose (
    const Field & F,
    ConstElement_ptr A,
    size_t lda,
    Element_ptr B,
    size_t ldb ) const [inline]
```

12.20.1.5 transpose() [3/5]

```
template<typename Field , typename Simd , typename std::enable_if< Simd::template is_same_↵
element< Field >::value >::type * = nullptr>
template<size_t _s = Simd::vect_size, IsSimdSize< _s, 4 > * = nullptr>
void transpose (
    const Field & F,
    ConstElement_ptr A,
    size_t lda,
    Element_ptr B,
    size_t ldb ) const [inline]
```

12.20.1.6 transpose() [4/5]

```
template<typename Field , typename Simd , typename std::enable_if< Simd::template is_same_↵
element< Field >::value >::type * = nullptr>
template<size_t _s = Simd::vect_size, IsSimdSize< _s, 8 > * = nullptr>
void transpose (
    const Field & F,
    ConstElement_ptr A,
    size_t lda,
    Element_ptr B,
    size_t ldb ) const [inline]
```

12.20.1.7 transpose() [5/5]

```
template<typename Field , typename Simd , typename std::enable_if< Simd::template is_same_↵
element< Field >::value >::type * = nullptr>
template<size_t _s = Simd::vect_size, IsSimdSize< _s, 16 > * = nullptr>
```

```
void transpose (
    const Field & F,
    ConstElement_ptr A,
    size_t lda,
    Element_ptr B,
    size_t ldb ) const [inline]
```

The documentation for this struct was generated from the following file:

- [fflas_transpose.h](#)

12.21 callLUdivine_small< Element > Class Template Reference

Public Member Functions

- `template<class Field >`
`size_t operator() (const Field &F, const FFLAS::FFLAS_DIAG Diag, const FFLAS::FFLAS_TRANSPOSE trans, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Q, const FFPACK::FFPACK_LU_TAG LuTag)`

12.21.1 Member Function Documentation

12.21.1.1 operator>()

```
template<class Element >
template<class Field >
size_t operator() (
    const Field & F,
    const FFLAS::FFLAS_DIAG Diag,
    const FFLAS::FFLAS_TRANSPOSE trans,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    const FFPACK::FFPACK_LU_TAG LuTag ) [inline]
```

The documentation for this class was generated from the following file:

- [ffpack_ludivine.inl](#)

12.22 callLUdivine_small< double > Class Reference

Public Member Functions

- `template<class Field >`
`size_t operator() (const Field &F, const FFLAS::FFLAS_DIAG Diag, const FFLAS::FFLAS_TRANSPOSE trans, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Q, const FFPACK::FFPACK_LU_TAG LuTag)`

12.22.1 Member Function Documentation

12.22.1.1 operator>()

```
template<class Field >
size_t operator() (
    const Field & F,
    const FFLAS::FFLAS_DIAG Diag,
    const FFLAS::FFLAS_TRANSPOSE trans,
    const size_t M,
```

```

    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    const FFPACK::FFPACK_LU_TAG LuTag ) [inline]

```

The documentation for this class was generated from the following file:

- [ffpack_ludivine.inl](#)

12.23 callLUdivine_small< float > Class Reference

Public Member Functions

- `template<class Field >`
`size_t operator() (const Field &F, const FFLAS::FFLAS_DIAG Diag, const FFLAS::FFLAS_TRANSPOSE trans, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Q, const FFPACK::FFPACK_LU_TAG LuTag)`

12.23.1 Member Function Documentation

12.23.1.1 operator>()

```

template<class Field >
size_t operator() (
    const Field & F,
    const FFLAS::FFLAS_DIAG Diag,
    const FFLAS::FFLAS_TRANSPOSE trans,
    const size_t M,
    const size_t N,
    typename Field::Element_ptr A,
    const size_t lda,
    size_t * P,
    size_t * Q,
    const FFPACK::FFPACK_LU_TAG LuTag ) [inline]

```

The documentation for this class was generated from the following file:

- [ffpack_ludivine.inl](#)

12.24 CharpolyFailed Class Reference

```
#include <ffpack.h>
```

The documentation for this class was generated from the following file:

- [ffpack.h](#)

12.25 Checker_Empty< Field > Struct Template Reference

```
#include <checker_empty.h>
```

Public Member Functions

- `template<typename... Params>`
`Checker_Empty (Params... parameters)`
- `template<typename... Params>`
`bool check (Params... parameters)`

12.25.1 Constructor & Destructor Documentation

12.25.1.1 Checker_Empty()

```
template<class Field >
template<typename... Params>
Checker_Empty (
    Params... parameters ) [inline]
```

12.25.2 Member Function Documentation

12.25.2.1 check()

```
template<class Field >
template<typename... Params>
bool check (
    Params... parameters ) [inline]
```

The documentation for this struct was generated from the following file:

- [checker_empty.h](#)

12.26 CheckerImplem_charpoly< Field, Polynomial > Class Template Reference

Public Member Functions

- [CheckerImplem_charpoly](#) (const [Field](#) &F_, const size_t n_, typename [Field::ConstElement_ptr](#) A, size_t lda_)
- [CheckerImplem_charpoly](#) (typename [Field::RandIter](#) &G, const size_t n_, typename [Field::ConstElement_ptr](#) A, size_t lda_)
- [~CheckerImplem_charpoly](#) ()
- bool [check](#) (Polynomial &g)

12.26.1 Constructor & Destructor Documentation

12.26.1.1 CheckerImplem_charpoly() [1/2]

```
template<class Field , class Polynomial >
CheckerImplem_charpoly (
    const Field & F_,
    const size_t n_,
    typename Field::ConstElement_ptr A,
    size_t lda_ ) [inline]
```

12.26.1.2 CheckerImplem_charpoly() [2/2]

```
template<class Field , class Polynomial >
CheckerImplem_charpoly (
    typename Field::RandIter & G,
    const size_t n_,
    typename Field::ConstElement_ptr A,
    size_t lda_ ) [inline]
```

12.26.1.3 ~CheckerImplem_charpoly()

```
template<class Field , class Polynomial >
~CheckerImplem_charpoly ( ) [inline]
```

12.26.2 Member Function Documentation

12.26.2.1 check()

```
template<class Field , class Polynomial >
bool check (
    Polynomial & g ) [inline]
```

The documentation for this class was generated from the following file:

- [checker_charpoly.inl](#)

12.27 CheckerImplem_charpoly< Givaro::ZRing< Givaro::Integer >, Polynomial > Class Template Reference

Public Types

- typedef Givaro::ZRing< Givaro::Integer > [Ring](#)

Public Member Functions

- [CheckerImplem_charpoly](#) (const [Ring](#) &F_, const size_t n_, typename Ring::ConstElement_ptr A, size_t lda_)
- [CheckerImplem_charpoly](#) (typename Ring::RandIter &G, const size_t n_, typename Ring::ConstElement_ptr A, size_t lda_)
- [~CheckerImplem_charpoly](#) ()
- bool [check](#) (Polynomial &g)

12.27.1 Member Typedef Documentation

12.27.1.1 Ring

```
template<class Polynomial >
typedef Givaro::ZRing<Givaro::Integer> Ring
```

12.27.2 Constructor & Destructor Documentation

12.27.2.1 CheckerImplem_charpoly() [1/2]

```
template<class Polynomial >
CheckerImplem\_charpoly (
    const Ring & F_,
    const size_t n_,
    typename Ring::ConstElement_ptr A,
    size_t lda_ ) [inline]
```

12.27.2.2 CheckerImplem_charpoly() [2/2]

```
template<class Polynomial >
CheckerImplem\_charpoly (
    typename Ring::RandIter & G,
    const size_t n_,
    typename Ring::ConstElement_ptr A,
    size_t lda_ ) [inline]
```

12.27.2.3 ~CheckerImplem_charpoly()

```
template<class Polynomial >
~CheckerImplem\_charpoly ( ) [inline]
```

12.27.3 Member Function Documentation

12.27.3.1 check()

```
template<class Polynomial >
bool check (
    Polynomial & g ) [inline]
```

The documentation for this class was generated from the following file:

- [checker_charpoly.inl](#)

12.28 CheckerImplem_Det< Field > Class Template Reference

Public Member Functions

- [CheckerImplem_Det](#) (const [Field](#) &F_, size_t n_, typename [Field::ConstElement_ptr](#) A, size_t lda)
- [CheckerImplem_Det](#) (typename [Field::RandIter](#) &G, size_t n_, typename [Field::ConstElement_ptr](#) A, size_t lda)
- [~CheckerImplem_Det](#) ()
- bool [check](#) (const typename [Field::Element](#) &det, typename [Field::ConstElement_ptr](#) LU, size_t lda, size_t *P, size_t *Q) const
check if the Det factorization is correct.

12.28.1 Constructor & Destructor Documentation

12.28.1.1 CheckerImplem_Det() [1/2]

```
template<class Field >
CheckerImplem_Det (
    const Field & F_,
    size_t n_,
    typename Field::ConstElement_ptr A,
    size_t lda ) [inline]
```

12.28.1.2 CheckerImplem_Det() [2/2]

```
template<class Field >
CheckerImplem_Det (
    typename Field::RandIter & G,
    size_t n_,
    typename Field::ConstElement_ptr A,
    size_t lda ) [inline]
```

12.28.1.3 ~CheckerImplem_Det()

```
template<class Field >
~CheckerImplem_Det ( ) [inline]
```

12.28.2 Member Function Documentation

12.28.2.1 check()

```
template<class Field >
bool check (
    const typename Field::Element & det,
    typename Field::ConstElement_ptr LU,
    size_t lda,
    size_t * P,
    size_t * Q ) const [inline]
```

check if the Det factorization is correct.

Needs matrix in LU form

Parameters

<i>LU,storage</i>	for L and U
<i>det</i>	
<i>P</i>	
<i>Q</i>	

The documentation for this class was generated from the following file:

- [checker_det.inl](#)

12.29 CheckerImplem_fgemm< Field > Class Template Reference

Public Member Functions

- [CheckerImplem_fgemm](#) (const [Field](#) &F_, const size_t m_, const size_t n_, const size_t k_, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc_)
- [CheckerImplem_fgemm](#) (typename [Field::RandIter](#) &G, const size_t m_, const size_t n_, const size_t k_, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc_)
- [~CheckerImplem_fgemm](#) ()
- bool [check](#) (const [FFLAS::FFLAS_TRANSPOSE](#) ta, const [FFLAS::FFLAS_TRANSPOSE](#) tb, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::ConstElement_ptr](#) C)

12.29.1 Constructor & Destructor Documentation

12.29.1.1 CheckerImplem_fgemm() [1/2]

```
template<class Field >
CheckerImplem_fgemm (
    const Field & F_,
    const size_t m_,
    const size_t n_,
    const size_t k_,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc_ ) [inline]
```

12.29.1.2 CheckerImplem_fgemm() [2/2]

```
template<class Field >
CheckerImplem_fgemm (
    typename Field::RandIter & G,
    const size_t m_,
    const size_t n_,
    const size_t k_,
    const typename Field::Element beta,
    typename Field::Element_ptr C,
    const size_t ldc_ ) [inline]
```

12.29.1.3 ~CheckerImplem_fgemm()

```
template<class Field >
~CheckerImplem_fgemm ( ) [inline]
```

12.29.2 Member Function Documentation

12.29.2.1 check()

```
template<class Field >
bool check (
    const FFLAS::FFLAS_TRANSPOSE ta,
    const FFLAS::FFLAS_TRANSPOSE tb,
    const typename Field::Element alpha,
    typename Field::ConstElement_ptr A,
    const size_t lda,
    typename Field::ConstElement_ptr B,
    const size_t ldb,
    typename Field::ConstElement_ptr C ) [inline]
```

The documentation for this class was generated from the following file:

- [checker_fgemm.inl](#)

12.30 CheckerImplem_ftrsm< Field > Class Template Reference

Public Member Functions

- [CheckerImplem_ftrsm](#) (const [Field](#) &F_, const size_t m, const size_t n, const typename [Field::Element](#) alpha, const typename [Field::ConstElement_ptr](#) B, const size_t ldb)
- [CheckerImplem_ftrsm](#) (typename [Field::RandIter](#) &G, const size_t m, const size_t n, const typename [Field::Element](#) alpha, const typename [Field::ConstElement_ptr](#) B, const size_t ldb)
- [~CheckerImplem_ftrsm](#) ()
- bool [check](#) (const [FFLAS::FFLAS_SIDE](#) side, const [FFLAS::FFLAS_UPLO](#) uplo, const [FFLAS::FFLAS_TRANSPOSE](#) trans, const [FFLAS::FFLAS_DIAG](#) diag, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, size_t lda, const typename [Field::ConstElement_ptr](#) X, size_t ldx)

12.30.1 Constructor & Destructor Documentation

12.30.1.1 CheckerImplem_ftrsm() [1/2]

```
template<class Field >
CheckerImplem_ftrsm (
    const Field & F_,
    const size_t m,
    const size_t n,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr B,
    const size_t ldb ) [inline]
```

12.30.1.2 CheckerImplem_ftrsm() [2/2]

```
template<class Field >
CheckerImplem_ftrsm (
    typename Field::RandIter & G,
    const size_t m,
    const size_t n,
    const typename Field::Element alpha,
    const typename Field::ConstElement_ptr B,
    const size_t ldb ) [inline]
```

12.30.1.3 ~CheckerImplem_ftrsm()

```
template<class Field >
~CheckerImplem_ftrsm ( ) [inline]
```

12.30.2 Member Function Documentation

12.30.2.1 check()

```
template<class Field >
bool check (
    const FFLAS::FFLAS_SIDE side,
    const FFLAS::FFLAS_UPLO uplo,
    const FFLAS::FFLAS_TRANSPOSE trans,
    const FFLAS::FFLAS_DIAG diag,
    const size_t m,
    const size_t n,
    typename Field::Element_ptr A,
    size_t lda,
    const typename Field::ConstElement_ptr X,
    size_t ldx ) [inline]
```

The documentation for this class was generated from the following file:

- [checker_frsm.inl](#)

12.31 CheckerImplem_invert< Field > Class Template Reference

Public Member Functions

- [CheckerImplem_invert](#) (const [Field](#) &F_, const size_t m_, typename [Field::ConstElement_ptr](#) A, const size_t lda_)
- [CheckerImplem_invert](#) (typename [Field::RandIter](#) &G, const size_t m_, typename [Field::ConstElement_ptr](#) A, const size_t lda_)
- [~CheckerImplem_invert](#) ()
- bool [check](#) (typename [Field::ConstElement_ptr](#) A, int nullity)

12.31.1 Constructor & Destructor Documentation

12.31.1.1 CheckerImplem_invert() [1/2]

```
template<class Field >
CheckerImplem_invert (
    const Field & F_,
    const size_t m_,
    typename Field::ConstElement_ptr A,
    const size_t lda_ ) [inline]
```

12.31.1.2 CheckerImplem_invert() [2/2]

```
template<class Field >
CheckerImplem_invert (
    typename Field::RandIter & G,
    const size_t m_,
    typename Field::ConstElement_ptr A,
    const size_t lda_ ) [inline]
```

12.31.1.3 ~CheckerImplem_invert()

```
template<class Field >
~CheckerImplem_invert ( ) [inline]
```

12.31.2 Member Function Documentation

12.31.2.1 check()

```
template<class Field >
```

```
bool check (
    typename Field::ConstElement_ptr A,
    int nullity ) [inline]
```

The documentation for this class was generated from the following file:

- [checker_invert.inl](#)

12.32 CheckerImplem_PLUQ< Field > Class Template Reference

Public Member Functions

- [CheckerImplem_PLUQ](#) (const [Field](#) &F_, size_t m_, size_t n_, typename [Field::ConstElement_ptr](#) A, size_t lda)
- [CheckerImplem_PLUQ](#) (typename [Field::RandIter](#) &G, size_t m_, size_t n_, typename [Field::ConstElement_ptr](#) A, size_t lda)
- [~CheckerImplem_PLUQ](#) ()
- bool [check](#) (typename [Field::ConstElement_ptr](#) A, size_t lda, const [FFLAS::FFLAS_DIAG](#) Diag, size_t r, size_t *P, size_t *Q) const

check if the PLUQ factorization is correct.

12.32.1 Constructor & Destructor Documentation

12.32.1.1 CheckerImplem_PLUQ() [1/2]

```
template<class Field >
CheckerImplem_PLUQ (
    const Field & F_,
    size_t m_,
    size_t n_,
    typename Field::ConstElement_ptr A,
    size_t lda ) [inline]
```

12.32.1.2 CheckerImplem_PLUQ() [2/2]

```
template<class Field >
CheckerImplem_PLUQ (
    typename Field::RandIter & G,
    size_t m_,
    size_t n_,
    typename Field::ConstElement_ptr A,
    size_t lda ) [inline]
```

12.32.1.3 ~CheckerImplem_PLUQ()

```
template<class Field >
~CheckerImplem_PLUQ ( ) [inline]
```

12.32.2 Member Function Documentation

12.32.2.1 check()

```
template<class Field >
bool check (
    typename Field::ConstElement_ptr A,
    size_t lda,
    const FFLAS::FFLAS_DIAG Diag,
    size_t r,
    size_t * P,
    size_t * Q ) const [inline]
```


check if the PLUQ factorization is correct.
Returns true if $w - P(L(U(Q.v))) == 0$

Parameters

<i>A</i>	
<i>r</i>	
<i>P</i>	
<i>Q</i>	

The documentation for this class was generated from the following file:

- [checker_pluq.inl](#)

12.33 Classic Struct Reference

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.34 Column Struct Reference

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.35 CompactElement< Element > Struct Template Reference

Public Types

- typedef Element [type](#)

12.35.1 Member Typedef Documentation

12.35.1.1 type

```
template<class Element >
typedef Element type
```

The documentation for this struct was generated from the following file:

- [test-io.C](#)

12.36 CompactElement< double > Struct Reference

Public Types

- typedef int32_t [type](#)

12.36.1 Member Typedef Documentation

12.36.1.1 type

```
typedef int32_t type
```

The documentation for this struct was generated from the following file:

- [test-io.C](#)

12.37 CompactElement< float > Struct Reference

Public Types

- `typedef int16_t` [type](#)

12.37.1 Member Typedef Documentation

12.37.1.1 type

`typedef int16_t` [type](#)

The documentation for this struct was generated from the following file:

- [test-io.C](#)

12.38 CompactElement< int16_t > Struct Reference

Public Types

- `typedef int8_t` [type](#)

12.38.1 Member Typedef Documentation

12.38.1.1 type

`typedef int8_t` [type](#)

The documentation for this struct was generated from the following file:

- [test-io.C](#)

12.39 CompactElement< int32_t > Struct Reference

Public Types

- `typedef int16_t` [type](#)

12.39.1 Member Typedef Documentation

12.39.1.1 type

`typedef int16_t` [type](#)

The documentation for this struct was generated from the following file:

- [test-io.C](#)

12.40 CompactElement< int64_t > Struct Reference

Public Types

- `typedef int32_t` [type](#)

12.40.1 Member Typedef Documentation

12.40.1.1 type

`typedef int32_t` [type](#)

The documentation for this struct was generated from the following file:

- [test-io.C](#)

12.41 compatible_data_type< Field > Struct Template Reference

Static Public Attributes

- static constexpr bool [value](#) = true

12.41.1 Field Documentation

12.41.1.1 value

```
template<typename Field >
constexpr bool value = true [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [benchmark-fgemv.C](#)

12.42 compatible_data_type< Givaro::ZRing< double > > Struct Reference

Static Public Attributes

- static constexpr bool [value](#) = false

12.42.1 Field Documentation

12.42.1.1 value

```
constexpr bool value = false [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [benchmark-fgemv.C](#)

12.43 compatible_data_type< Givaro::ZRing< float > > Struct Reference

Static Public Attributes

- static constexpr bool [value](#) = false

12.43.1 Field Documentation

12.43.1.1 value

```
constexpr bool value = false [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [benchmark-fgemv.C](#)

12.44 Compose< H1, H2 > Struct Template Reference

Public Member Functions

- [Compose](#) ()
- [Compose](#) (const [Compose](#) &other)
- [Compose](#) (const [Sequential](#) &S)
- [Compose](#) (size_t th1, size_t th2)
- [Compose](#) (const H1 &o1, const H2 &o2)
- H1 [first_component](#) () const
- H2 [second_component](#) () const

Friends

- `std::ostream & operator<< (std::ostream &o, const Compose &c)`

12.44.1 Constructor & Destructor Documentation

12.44.1.1 [Compose\(\)](#) [1/5]

```
template<typename H1 = Sequential, typename H2 = Sequential>
Compose ( ) [inline]
```

12.44.1.2 [Compose\(\)](#) [2/5]

```
template<typename H1 = Sequential, typename H2 = Sequential>
Compose (
    const Compose< H1, H2 > & other ) [inline]
```

12.44.1.3 [Compose\(\)](#) [3/5]

```
template<typename H1 = Sequential, typename H2 = Sequential>
Compose (
    const Sequential & S ) [inline]
```

12.44.1.4 [Compose\(\)](#) [4/5]

```
template<typename H1 = Sequential, typename H2 = Sequential>
Compose (
    size_t th1,
    size_t th2 ) [inline]
```

12.44.1.5 [Compose\(\)](#) [5/5]

```
template<typename H1 = Sequential, typename H2 = Sequential>
Compose (
    const H1 & o1,
    const H2 & o2 ) [inline]
```

12.44.2 Member Function Documentation

12.44.2.1 [first_component\(\)](#)

```
template<typename H1 = Sequential, typename H2 = Sequential>
H1 first\_component ( ) const [inline]
```

12.44.2.2 [second_component\(\)](#)

```
template<typename H1 = Sequential, typename H2 = Sequential>
H2 second\_component ( ) const [inline]
```

12.44.3 Friends And Related Symbol Documentation

12.44.3.1 [operator<<](#)

```
template<typename H1 = Sequential, typename H2 = Sequential>
std::ostream & operator<< (
    std::ostream & o,
    const Compose< H1, H2 > & c ) [friend]
```

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.45 Simd128_impl< true, true, false, 2 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.45.1 Field Documentation

12.45.1.1 v

[vect_tv](#)

12.45.1.2 t

[scalar_tt](#) t [vect_size]

The documentation for this union was generated from the following file:

- [simd128_int16.inl](#)

12.46 Simd128_impl< true, true, false, 4 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.46.1 Field Documentation

12.46.1.1 v

[vect_tv](#)

12.46.1.2 t

[scalar_tt](#) t [vect_size]

The documentation for this union was generated from the following file:

- [simd128_int32.inl](#)

12.47 Simd128_impl< true, true, false, 8 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.47.1 Field Documentation

12.47.1.1 v

[vect_tv](#)

12.47.1.2 t

[scalar_tt](#) t [vect_size]

The documentation for this union was generated from the following file:

- [simd128_int64.inl](#)

12.48 Simd128_impl< true, true, true, 2 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.48.1 Field Documentation

12.48.1.1 v

[vect_tv](#) v

12.48.1.2 t

[scalar_tt](#) t [vect_size]

The documentation for this union was generated from the following file:

- [simd128_int16.inl](#)

12.49 Simd128_impl< true, true, true, 4 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.49.1 Field Documentation

12.49.1.1 v

[vect_tv](#) v

12.49.1.2 t

[scalar_tt](#) t [vect_size]

The documentation for this union was generated from the following file:

- [simd128_int32.inl](#)

12.50 Simd128_impl< true, true, true, 8 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.50.1 Field Documentation

12.50.1.1 v

[vect_tv](#) v

12.50.1.2 t

[scalar_tt](#) t [vect_size]

The documentation for this union was generated from the following file:

- [simd128_int64.inl](#)

12.51 Simd256_impl< true, false, true, 8 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.51.1 Field Documentation

12.51.1.1 v

[vect_tv](#)

12.51.1.2 t

[scalar_tt](#) t [vect_size]

The documentation for this union was generated from the following file:

- [simd256_double.inl](#)

12.52 Simd256_impl< true, true, false, 2 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.52.1 Field Documentation

12.52.1.1 v

[vect_tv](#)

12.52.1.2 t

[scalar_tt](#) t [vect_size]

The documentation for this union was generated from the following file:

- [simd256_int16.inl](#)

12.53 Simd256_impl< true, true, false, 4 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.53.1 Field Documentation

12.53.1.1 v

[vect_tv](#)

12.53.1.2 t

[scalar_tt](#) t

The documentation for this union was generated from the following files:

- [simd256_int32.inl](#)
- [simd512_int32.inl](#)

12.54 Simd256_impl< true, true, false, 8 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.54.1 Field Documentation

12.54.1.1 v

[vect_tv](#) v

12.54.1.2 t

[scalar_tt](#) t [vect_size]

The documentation for this union was generated from the following file:

- [simd256_int64.inl](#)

12.55 Simd256_impl< true, true, true, 2 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.55.1 Field Documentation

12.55.1.1 v

[vect_tv](#) v

12.55.1.2 t

[scalar_tt](#) t [vect_size]

The documentation for this union was generated from the following file:

- [simd256_int16.inl](#)

12.56 Simd256_impl< true, true, true, 4 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.56.1 Field Documentation

12.56.1.1 v

[vect_tv](#) v

12.56.1.2 t

[scalar_tt](#) t

The documentation for this union was generated from the following files:

- [simd256_int32.inl](#)
- [simd512_int32.inl](#)

12.57 Simd256_impl< true, true, true, 8 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.57.1 Field Documentation

12.57.1.1 v

[vect_tv](#) v

12.57.1.2 t

[scalar_tt](#) t [vect_size]

The documentation for this union was generated from the following file:

- [simd256_int64.inl](#)

12.58 Simd512_impl< true, true, false, 8 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.58.1 Field Documentation

12.58.1.1 v

[vect_tv](#) v

12.58.1.2 t

[scalar_tt](#) t [vect_size]

The documentation for this union was generated from the following file:

- [simd512_int64.inl](#)

12.59 Simd512_impl< true, true, true, 8 >::Converter Union Reference

Data Fields

- [vect_tv](#)
- [scalar_tt](#) [vect_size]

12.59.1 Field Documentation

12.59.1.1 v

[vect_tv](#) v

12.59.1.2 t

[scalar_tt](#) t [vect_size]

The documentation for this union was generated from the following file:

- [simd512_int64.inl](#)

12.60 ConvertTo< T > Struct Template Reference

Force conversion to appropriate element type of ElementCategory T.

```
#include <field-traits.h>
```

12.60.1 Detailed Description

```
template<class T>
```

```
struct FFLAS::ModeCategories::ConvertTo< T >
```

Force conversion to appropriate element type of ElementCategory T.

e.g.

- ConvertTo<ElementCategories::MachineFloatTag> tries conversion of Modular<int> to Modular<double>
- ConvertTo<ElementCategories::FixedPreIntTag> tries conversion of Modular<Integer> to Modular<RecInt<K>>
- ConvertTo<ElementCategories::ArbitraryPreIntTag> tries conversion of Modular<Integer> to RNSInteger

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.61 Coo< ValT, IdxT > Struct Template Reference

Public Types

- using [Self](#) = [Coo](#)< ValT, IdxT >

Public Member Functions

- [Coo](#) (ValT v, IdxT r, IdxT c)
- [Coo](#) ()=default
- [Coo](#) (const [Self](#) &)=default
- [Coo](#) ([Self](#) &&)=default
- [Self](#) & [operator](#)= (const [Self](#) &)=default
- [Self](#) & [operator](#)= ([Self](#) &&)=default

Data Fields

- ValT [val](#) = 0
- IdxT [row](#) = 0
- IdxT [col](#) = 0

12.61.1 Member Typedef Documentation

12.61.1.1 Self

```
template<class ValT , class IdxT >
using Self = Coo<ValT, IdxT>
```

12.61.2 Constructor & Destructor Documentation

12.61.2.1 Coo() [1/4]

```
template<class ValT , class IdxT >
Coo (
    ValT v,
    IdxT r,
    IdxT c ) [inline]
```

12.61.2.2 `Coo()` [2/4]

```
template<class ValT , class IdxT >
Coo ( ) [default]
```

12.61.2.3 `Coo()` [3/4]

```
template<class ValT , class IdxT >
Coo (
    const Self & ) [default]
```

12.61.2.4 `Coo()` [4/4]

```
template<class ValT , class IdxT >
Coo (
    Self && ) [default]
```

12.61.3 Member Function Documentation**12.61.3.1 `operator=()` [1/2]**

```
template<class ValT , class IdxT >
Self & operator= (
    const Self & ) [default]
```

12.61.3.2 `operator=()` [2/2]

```
template<class ValT , class IdxT >
Self & operator= (
    Self && ) [default]
```

12.61.4 Field Documentation**12.61.4.1 `val`**

```
template<class ValT , class IdxT >
ValT val = 0
```

12.61.4.2 `row`

```
template<class ValT , class IdxT >
IdxT row = 0
```

12.61.4.3 `col`

```
template<class ValT , class IdxT >
IdxT col = 0
```

The documentation for this struct was generated from the following file:

- [csr_hyb_utils.inl](#)

12.62 `Coo<Field>` Struct Template Reference

```
#include <read_sparse.h>
```

Public Member Functions

- `Coo()`=default
- `Coo` (typename `Field::Element` v, `index_t` r, `index_t` c)
- `Coo` (const `Self` &)=default

- `Coo (Self &&)=default`
- `Self & operator= (const Self &)=default`
- `Self & operator= (Self &&)=default`

Data Fields

- `Field::Element val = 0`
- `index_t col = 0`
- `index_t row = 0`
- `bool deleted = false`

12.62.1 Constructor & Destructor Documentation

12.62.1.1 Coo() [1/4]

```
template<class Field >
Coo ( ) [default]
```

12.62.1.2 Coo() [2/4]

```
template<class Field >
Coo (
    typename Field::Element v,
    index_t r,
    index_t c ) [inline]
```

12.62.1.3 Coo() [3/4]

```
template<class Field >
Coo (
    const Self & ) [default]
```

12.62.1.4 Coo() [4/4]

```
template<class Field >
Coo (
    Self && ) [default]
```

12.62.2 Member Function Documentation

12.62.2.1 operator=() [1/2]

```
template<class Field >
Self & operator= (
    const Self & ) [default]
```

12.62.2.2 operator=() [2/2]

```
template<class Field >
Self & operator= (
    Self && ) [default]
```

12.62.3 Field Documentation

12.62.3.1 val

```
template<class Field >
Field::Element val = 0
```

12.62.3.2 col

```
template<class Field >
index_t col = 0
```

12.62.3.3 row

```
template<class Field >
index_t row = 0
```

12.62.3.4 deleted

```
template<class Field >
bool deleted = false
```

The documentation for this struct was generated from the following file:

- [read_sparse.h](#)

12.63 `Coo< ValT, IdxT >` Struct Template Reference**Public Types**

- using `Self` = `Coo< ValT, IdxT >`

Public Member Functions

- `Coo` (`ValT` v, `IdxT` r, `IdxT` c)
- `Coo` ()=default
- `Coo` (const `Self` &)=default
- `Coo` (`Self` &&)=default
- `Self` & `operator`= (const `Self` &)=default
- `Self` & `operator`= (`Self` &&)=default

Data Fields

- `ValT` `val` = 0
- `IdxT` `row` = 0
- `IdxT` `col` = 0

12.63.1 Member Typedef Documentation**12.63.1.1 Self**

```
template<class ValT , class IdxT >
using Self = Coo<ValT, IdxT>
```

12.63.2 Constructor & Destructor Documentation**12.63.2.1 `Coo()` [1/4]**

```
template<class ValT , class IdxT >
Coo (
    ValT v,
    IdxT r,
    IdxT c ) [inline]
```

12.63.2.2 `Coo()` [2/4]

```
template<class ValT , class IdxT >
Coo ( ) [default]
```

12.63.2.3 **Coo()** [3/4]

```
template<class ValT , class IdxT >
Coo (
    const Self & ) [default]
```

12.63.2.4 **Coo()** [4/4]

```
template<class ValT , class IdxT >
Coo (
    Self && ) [default]
```

12.63.3 **Member Function Documentation****12.63.3.1** **operator=()** [1/2]

```
template<class ValT , class IdxT >
Self & operator= (
    const Self & ) [default]
```

12.63.3.2 **operator=()** [2/2]

```
template<class ValT , class IdxT >
Self & operator= (
    Self && ) [default]
```

12.63.4 **Field Documentation****12.63.4.1** **val**

```
template<class ValT , class IdxT >
ValT val = 0
```

12.63.4.2 **row**

```
template<class ValT , class IdxT >
IdxT row = 0
```

12.63.4.3 **col**

```
template<class ValT , class IdxT >
IdxT col = 0
```

The documentation for this struct was generated from the following file:

- [sell_utils.inl](#)

12.64 **CooMat< Field > Struct Template Reference**

```
#include <fflas_sparse.h>
```

Data Fields

- [FFLAS::Sparse< Field, SparseMatrix_t::COO, int16_t > * _coo16](#) = nullptr
- [FFLAS::Sparse< Field, SparseMatrix_t::COO, int32_t > * _coo32](#) = nullptr
- [FFLAS::Sparse< Field, SparseMatrix_t::COO, int64_t > * _coo64](#) = nullptr
- [FFLAS::Sparse< Field, SparseMatrix_t::COO_ZO, int16_t > * _coo16_zo](#) = nullptr
- [FFLAS::Sparse< Field, SparseMatrix_t::COO_ZO, int32_t > * _coo32_zo](#) = nullptr
- [FFLAS::Sparse< Field, SparseMatrix_t::COO_ZO, int64_t > * _coo64_zo](#) = nullptr

12.64.1 Field Documentation

12.64.1.1 _coo16

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::COO, int16_t>* _coo16 = nullptr
```

12.64.1.2 _coo32

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::COO, int32_t>* _coo32 = nullptr
```

12.64.1.3 _coo64

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::COO, int64_t>* _coo64 = nullptr
```

12.64.1.4 _coo16_zo

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::COO_ZO, int16_t>* _coo16_zo = nullptr
```

12.64.1.5 _coo32_zo

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::COO_ZO, int32_t>* _coo32_zo = nullptr
```

12.64.1.6 _coo64_zo

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::COO_ZO, int64_t>* _coo64_zo = nullptr
```

The documentation for this struct was generated from the following file:

- [fflas_sparse.h](#)

12.65 count_nonconst_lvalue_reference< T > Struct Template Reference

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.66 count_nonconst_lvalue_reference< const T &, O... > Struct Template Reference

Static Public Attributes

- static constexpr size_t n = count_nonconst_lvalue_reference<O...>::n

12.66.1 Field Documentation

12.66.1.1 n

```
template<typename T , typename... O>
constexpr size_t n = count_nonconst_lvalue_reference<O...>::n [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.67 `count_nonconst_lvalue_reference< T &, O... >` Struct Template Reference

Static Public Attributes

- static constexpr `size_t` `n`

12.67.1 Field Documentation

12.67.1.1 `n`

```
template<typename T , typename... O>
constexpr size_t n [static], [constexpr]
Initial value:
= std::integral_constant<size_t, 1>::value
+ count_nonconst_lvalue_reference<O...>::n
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.68 `count_nonconst_lvalue_reference< T, O... >` Struct Template Reference

Static Public Attributes

- static constexpr `size_t` `n` = `count_nonconst_lvalue_reference<O...>::n`

12.68.1 Field Documentation

12.68.1.1 `n`

```
template<typename T , typename... O>
constexpr size_t n = count_nonconst_lvalue_reference<O...>::n [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.69 `count_nonconst_lvalue_reference<>` Struct Reference

Static Public Attributes

- static constexpr `size_t` `n` = `std::integral_constant<size_t, 0>::value`

12.69.1 Field Documentation

12.69.1.1 `n`

```
constexpr size_t n = std::integral_constant<size_t, 0>::value [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.70 `CsrMat< Field >` Struct Template Reference

```
#include <fflas_sparse.h>
```


Data Fields

- [FFLAS::Sparse](#)< [Field](#), [SparseMatrix_t::CSR](#), [int16_t](#) > * [_csr16](#) = nullptr
- [FFLAS::Sparse](#)< [Field](#), [SparseMatrix_t::CSR](#), [int32_t](#) > * [_csr32](#) = nullptr
- [FFLAS::Sparse](#)< [Field](#), [SparseMatrix_t::CSR](#), [int64_t](#) > * [_csr64](#) = nullptr
- [FFLAS::Sparse](#)< [Field](#), [SparseMatrix_t::CSR_ZO](#), [int16_t](#) > * [_csr16_zo](#) = nullptr
- [FFLAS::Sparse](#)< [Field](#), [SparseMatrix_t::CSR_ZO](#), [int32_t](#) > * [_csr32_zo](#) = nullptr
- [FFLAS::Sparse](#)< [Field](#), [SparseMatrix_t::CSR_ZO](#), [int64_t](#) > * [_csr64_zo](#) = nullptr

12.70.1 Field Documentation**12.70.1.1 [_csr16](#)**

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::CSR, int16_t>* _csr16 = nullptr
```

12.70.1.2 [_csr32](#)

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::CSR, int32_t>* _csr32 = nullptr
```

12.70.1.3 [_csr64](#)

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::CSR, int64_t>* _csr64 = nullptr
```

12.70.1.4 [_csr16_zo](#)

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::CSR_ZO, int16_t>* _csr16_zo = nullptr
```

12.70.1.5 [_csr32_zo](#)

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::CSR_ZO, int32_t>* _csr32_zo = nullptr
```

12.70.1.6 [_csr64_zo](#)

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::CSR_ZO, int64_t>* _csr64_zo = nullptr
```

The documentation for this struct was generated from the following file:

- [fflas_sparse.h](#)

12.71 DefaultBoundedTag Struct Reference

Use standard field operations, but keeps track of bounds on input and output.

```
#include <field-traits.h>
```

12.71.1 Detailed Description

Use standard field operations, but keeps track of bounds on input and output.

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.72 DefaultTag Struct Reference

No specific mode of action: use standard field operations.

```
#include <field-traits.h>
```

12.72.1 Detailed Description

No specific mode of action: use standard field operations.

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.73 DelayedTag Struct Reference

Performs field operations with delayed mod reductions. Ensures result is reduced.

```
#include <field-traits.h>
```

12.73.1 Detailed Description

Performs field operations with delayed mod reductions. Ensures result is reduced.

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.74 DivideAndConquer Struct Reference

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.75 ElementTraits< Element > Struct Template Reference

[ElementTraits](#).

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::GenericTag](#) value

12.75.1 Detailed Description

```
template<class Element>
```

```
struct FFLAS::ElementTraits< Element >
```

[ElementTraits](#).

12.75.2 Member Typedef Documentation

12.75.2.1 value

```
template<class Element >
```

```
typedef ElementCategories::GenericTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.76 ElementTraits< double > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::MachineFloatTag](#) value

12.76.1 Member Typedef Documentation

12.76.1.1 value

typedef [ElementCategories::MachineFloatTag](#) value

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.77 ElementTraits< FFPACK::rns_double_elt > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::RNSElementTag](#) value

12.77.1 Member Typedef Documentation

12.77.1.1 value

typedef [ElementCategories::RNSElementTag](#) value

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.78 ElementTraits< float > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::MachineFloatTag](#) value

12.78.1 Member Typedef Documentation

12.78.1.1 value

typedef [ElementCategories::MachineFloatTag](#) value

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.79 ElementTraits< Givaro::Integer > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::ArbitraryPrecIntTag](#) value

12.79.1 Member Typedef Documentation

12.79.1.1 value

typedef [ElementCategories::ArbitraryPrecIntTag](#) value

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.80 ElementTraits< int16_t > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::MachineIntTag](#) value

12.80.1 Member Typedef Documentation

12.80.1.1 value

```
typedef ElementCategories::MachineIntTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.81 ElementTraits< int32_t > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::MachineIntTag](#) value

12.81.1 Member Typedef Documentation

12.81.1.1 value

```
typedef ElementCategories::MachineIntTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.82 ElementTraits< int64_t > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::MachineIntTag](#) value

12.82.1 Member Typedef Documentation

12.82.1.1 value

```
typedef ElementCategories::MachineIntTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.83 ElementTraits< int8_t > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::MachineIntTag](#) value

12.83.1 Member Typedef Documentation

12.83.1.1 value

typedef [ElementCategories::MachineIntTag](#) value

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.84 ElementTraits< RecInt::rint< K > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::FixedPrecIntTag](#) value

12.84.1 Member Typedef Documentation

12.84.1.1 value

```
template<size_t K>
```

typedef [ElementCategories::FixedPrecIntTag](#) value

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.85 ElementTraits< RecInt::rmint< K, MG > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::FixedPrecIntTag](#) value

12.85.1 Member Typedef Documentation

12.85.1.1 value

```
template<size_t K, int MG>
```

typedef [ElementCategories::FixedPrecIntTag](#) value

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.86 ElementTraits< RecInt::ruint< K > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::FixedPrecIntTag](#) value

12.86.1 Member Typedef Documentation

12.86.1.1 value

```
template<size_t K>
```

```
typedef ElementCategories::FixedPrecIntTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.87 ElementTraits< uint16_t > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::MachineIntTag](#) value

12.87.1 Member Typedef Documentation

12.87.1.1 value

```
typedef ElementCategories::MachineIntTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.88 ElementTraits< uint32_t > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::MachineIntTag](#) value

12.88.1 Member Typedef Documentation

12.88.1.1 value

```
typedef ElementCategories::MachineIntTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.89 ElementTraits< uint64_t > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::MachineIntTag](#) value

12.89.1 Member Typedef Documentation

12.89.1.1 value

```
typedef ElementCategories::MachineIntTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.90 ElementTraits< uint8_t > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ElementCategories::MachineIntTag](#) value

12.90.1 Member Typedef Documentation

12.90.1.1 value

```
typedef ElementCategories::MachineIntTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.91 EIMat< Field > Struct Template Reference

```
#include <fflas_sparse.h>
```

Data Fields

- [FFLAS::Sparse< Field, SparseMatrix_t::ELL, int16_t > * _ell16](#) = nullptr
- [FFLAS::Sparse< Field, SparseMatrix_t::ELL, int32_t > * _ell32](#) = nullptr
- [FFLAS::Sparse< Field, SparseMatrix_t::ELL, int64_t > * _ell64](#) = nullptr
- [FFLAS::Sparse< Field, SparseMatrix_t::ELL_ZO, int16_t > * _ell16_zo](#) = nullptr
- [FFLAS::Sparse< Field, SparseMatrix_t::ELL_ZO, int32_t > * _ell32_zo](#) = nullptr
- [FFLAS::Sparse< Field, SparseMatrix_t::ELL_ZO, int64_t > * _ell64_zo](#) = nullptr

12.91.1 Field Documentation

12.91.1.1 _ell16

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::ELL, int16_t>* _ell16 = nullptr
```

12.91.1.2 _ell32

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::ELL, int32_t>* _ell32 = nullptr
```

12.91.1.3 _ell64

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::ELL, int64_t>* _ell64 = nullptr
```

12.91.1.4 _ell16_zo

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::ELL_ZO, int16_t>* _ell16_zo = nullptr
```

12.91.1.5 _ell32_zo

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::ELL_ZO, int32_t>* _ell32_zo = nullptr
```

12.91.1.6 `_ell64_zo`

```
template<class Field >
FFLAS::Sparse<Field, SparseMatrix_t::ELL_ZO, int64_t>* _ell64_zo = nullptr
```

The documentation for this struct was generated from the following file:

- [fflas_sparse.h](#)

12.92 Failure Class Reference

A precondition failed.

```
#include <debug.h>
```

Public Member Functions

- [Failure](#) ()
- void [operator\(\)](#) (const char *function, int line, const char *check)
- void [operator\(\)](#) (const char *function, const char *file, int line, const char *check)
- void [setErrorStream](#) (std::ostream &stream)
- std::ostream & [print](#) (std::ostream &o) const

Protected Attributes

- std::ostream * [_errorStream](#)

12.92.1 Detailed Description

A precondition failed.

The `throw` mechanism is usually used here as in

```
if (!check)
failure() (__func__, __LINE__, "this check just failed");
```

The parameters of the constructor help debugging.

12.92.2 Constructor & Destructor Documentation

12.92.2.1 Failure()

```
Failure ( ) [inline]
```

12.92.3 Member Function Documentation

12.92.3.1 `operator()()` [1/2]

```
void operator() (
    const char * function,
    int line,
    const char * check ) [inline]
```

A precondition failed.

Parameters

<i>function</i>	usually <code>__func__</code> , the function that threw the error
<i>line</i>	usually <code>__LINE__</code> , the line where it happened
<i>check</i>	a string telling what failed.

12.92.3.2 `operator()()` [2/2]

```
void operator() (
```



```

    const char * function,
    const char * file,
    int line,
    const char * check ) [inline]

```

A precondition failed. The parameter help debugging. This is not much different from the previous except we can dig faster in the file where the exception was triggered.

Parameters

<i>function</i>	usually <code>__func__</code> , the function that threw the error
<i>file</i>	usually <code>__FILE__</code> , the file where this function is
<i>line</i>	usually <code>__LINE__</code> , the line where it happened
<i>check</i>	a string telling what failed.

12.92.3.3 setErrorStream()

```

void setErrorStream (
    std::ostream & stream )

```

12.92.3.4 print()

```

std::ostream & print (
    std::ostream & o ) const [inline]

```

overload the virtual print of LinboxError.

Parameters

<i>o</i>	output stream

12.92.4 Field Documentation

12.92.4.1 _errorStream

```
std::ostream* _errorStream [protected]
```

The documentation for this class was generated from the following file:

- [debug.h](#)

12.93 FailureCharpolyCheck Class Reference

```
#include <checkers_ffpack.h>
```

The documentation for this class was generated from the following file:

- [checkers_ffpack.h](#)

12.94 FailureDetCheck Class Reference

```
#include <checkers_ffpack.h>
```

The documentation for this class was generated from the following file:

- [checkers_ffpack.h](#)

12.95 FailureFgemmCheck Class Reference

```
#include <checkers_fflas.h>
```

The documentation for this class was generated from the following file:

- [checkers_fflas.h](#)

12.96 FailureInvertCheck Class Reference

#include <checkers_ffpack.h>

The documentation for this class was generated from the following file:

- [checkers_ffpack.h](#)

12.97 FailurePLUQCheck Class Reference

#include <checkers_ffpack.h>

The documentation for this class was generated from the following file:

- [checkers_ffpack.h](#)

12.98 FailureTrsmCheck Class Reference

#include <checkers_fflas.h>

The documentation for this class was generated from the following file:

- [checkers_fflas.h](#)

12.99 FieldSimd< _Field > Class Template Reference

Public Types

- using [Field](#) = [_Field](#)
- using [Element](#) = typename [Field::Element](#)
- using [simd](#) = [Simd](#)< typename [_Field::Element](#) >
- using [vect_t](#) = typename [simd::vect_t](#)
- using [scalar_t](#) = typename [simd::scalar_t](#)

Public Member Functions

- [FieldSimd](#) (const [Field](#) &f)
- [FieldSimd](#) (const [Self](#) &)=default
- [FieldSimd](#) ([Self](#) &&)=default
- [Self](#) & operator= (const [Self](#) &)=default
- [Self](#) & operator= ([Self](#) &&)=default
- [INLINE vect_t init](#) ([vect_t](#) &x, const [vect_t](#) a) const
- [INLINE vect_t init](#) (const [vect_t](#) a) const
- [INLINE vect_t add](#) ([vect_t](#) &c, const [vect_t](#) a, const [vect_t](#) b)
- [INLINE vect_t add](#) (const [vect_t](#) a, const [vect_t](#) b)
- [INLINE vect_t addin](#) ([vect_t](#) &a, const [vect_t](#) b) const
- [INLINE vect_t add_r](#) ([vect_t](#) &c, const [vect_t](#) a, const [vect_t](#) b) const
- [INLINE vect_t add_r](#) (const [vect_t](#) a, const [vect_t](#) b) const
- [INLINE vect_t addin_r](#) ([vect_t](#) &a, const [vect_t](#) b) const
- [INLINE vect_t sub](#) ([vect_t](#) &c, const [vect_t](#) a, const [vect_t](#) b)
- [INLINE vect_t sub](#) (const [vect_t](#) a, const [vect_t](#) b)
- [INLINE vect_t subin](#) ([vect_t](#) &a, const [vect_t](#) b) const
- [INLINE vect_t sub_r](#) ([vect_t](#) &c, const [vect_t](#) a, const [vect_t](#) b) const
- [INLINE vect_t sub_r](#) (const [vect_t](#) a, const [vect_t](#) b) const
- [INLINE vect_t subin_r](#) ([vect_t](#) &a, const [vect_t](#) b) const
- [INLINE vect_t zero](#) ([vect_t](#) &x) const

- `INLINE vect_t zero () const`
- `INLINE vect_t mod (vect_t &c) const`
- `INLINE vect_t mul (vect_t &c, const vect_t a, const vect_t b) const`
- `INLINE vect_t mul (const vect_t a, const vect_t b) const`
- `INLINE vect_t mulin (vect_t &a, const vect_t b) const`
- `INLINE vect_t mul_r (vect_t &c, const vect_t a, const vect_t b) const`
- `INLINE vect_t mul_r (const vect_t a, const vect_t b) const`
- `INLINE vect_t axpy (vect_t &r, const vect_t a, const vect_t b, const vect_t c) const`
- `INLINE vect_t axpy (const vect_t c, const vect_t a, const vect_t b) const`
- `INLINE vect_t axpyin (vect_t &c, const vect_t a, const vect_t b) const`
- `INLINE vect_t axpy_r (vect_t &r, const vect_t a, const vect_t b, const vect_t c) const`
- `INLINE vect_t axpy_r (const vect_t c, const vect_t a, const vect_t b) const`
- `INLINE vect_t axpyin_r (vect_t &c, const vect_t a, const vect_t b) const`
- `INLINE vect_t maxpy (vect_t &r, const vect_t a, const vect_t b, const vect_t c) const`
- `INLINE vect_t maxpy (const vect_t c, const vect_t a, const vect_t b) const`
- `INLINE vect_t maxpyin (vect_t &c, const vect_t a, const vect_t b) const`

Static Public Attributes

- static const constexpr size_t `vect_size` = `simd::vect_size`
- static const constexpr size_t `alignment` = `simd::alignment`

12.99.1 Member Typedef Documentation

12.99.1.1 Field

```
template<class _Field >
using Field = _Field
```

12.99.1.2 Element

```
template<class _Field >
using Element = typename Field::Element
```

12.99.1.3 simd

```
template<class _Field >
using simd = Simd<typename _Field::Element>
```

12.99.1.4 vect_t

```
template<class _Field >
using vect_t = typename simd::vect_t
```

12.99.1.5 scalar_t

```
template<class _Field >
using scalar_t = typename simd::scalar_t
```

12.99.2 Constructor & Destructor Documentation

12.99.2.1 FieldSimd() [1/3]

```
template<class _Field >
FieldSimd (
    const Field & f ) [inline]
```

12.99.2.2 FieldSimd() [2/3]

```
template<class _Field >
FieldSimd (
    const Self & ) [default]
```

12.99.2.3 FieldSimd() [3/3]

```
template<class _Field >
FieldSimd (
    Self && ) [default]
```

12.99.3 Member Function Documentation**12.99.3.1 operator=() [1/2]**

```
template<class _Field >
Self & operator= (
    const Self & ) [default]
```

12.99.3.2 operator=() [2/2]

```
template<class _Field >
Self & operator= (
    Self && ) [default]
```

12.99.3.3 init() [1/2]

```
template<class _Field >
INLINE vect_t init (
    vect_t & x,
    const vect_t a ) const [inline]
```

12.99.3.4 init() [2/2]

```
template<class _Field >
INLINE vect_t init (
    const vect_t a ) const [inline]
```

12.99.3.5 add() [1/2]

```
template<class _Field >
INLINE vect_t add (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline]
```

12.99.3.6 add() [2/2]

```
template<class _Field >
INLINE vect_t add (
    const vect_t a,
    const vect_t b ) [inline]
```

12.99.3.7 addin()

```
template<class _Field >
INLINE vect_t addin (
    vect_t & a,
    const vect_t b ) const [inline]
```

12.99.3.8 add_r() [1/2]

```
template<class _Field >
INLINE vect_t add_r (
    vect_t & c,
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.3.9 add_r() [2/2]

```
template<class _Field >
INLINE vect_t add_r (
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.3.10 addin_r()

```
template<class _Field >
INLINE vect_t addin_r (
    vect_t & a,
    const vect_t b ) const [inline]
```

12.99.3.11 sub() [1/2]

```
template<class _Field >
INLINE vect_t sub (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline]
```

12.99.3.12 sub() [2/2]

```
template<class _Field >
INLINE vect_t sub (
    const vect_t a,
    const vect_t b ) [inline]
```

12.99.3.13 subin()

```
template<class _Field >
INLINE vect_t subin (
    vect_t & a,
    const vect_t b ) const [inline]
```

12.99.3.14 sub_r() [1/2]

```
template<class _Field >
INLINE vect_t sub_r (
    vect_t & c,
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.3.15 sub_r() [2/2]

```
template<class _Field >
INLINE vect_t sub_r (
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.3.16 subin_r()

```
template<class _Field >
INLINE vect_t subin_r (
    vect_t & a,
    const vect_t b ) const [inline]
```

12.99.3.17 zero() [1/2]

```
template<class _Field >
INLINE vect_t zero (
    vect_t & x ) const [inline]
```

12.99.3.18 zero() [2/2]

```
template<class _Field >
INLINE vect_t zero ( ) const [inline]
```

12.99.3.19 mod()

```
template<class _Field >
INLINE vect_t mod (
    vect_t & c ) const [inline]
```

12.99.3.20 mul() [1/2]

```
template<class _Field >
INLINE vect_t mul (
    vect_t & c,
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.3.21 mul() [2/2]

```
template<class _Field >
INLINE vect_t mul (
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.3.22 mulin()

```
template<class _Field >
INLINE vect_t mulin (
    vect_t & a,
    const vect_t b ) const [inline]
```

12.99.3.23 mul_r() [1/2]

```
template<class _Field >
INLINE vect_t mul_r (
    vect_t & c,
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.3.24 mul_r() [2/2]

```
template<class _Field >
INLINE vect_t mul_r (
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.3.25 axpy() [1/2]

```
template<class _Field >
INLINE vect_t axpy (
    vect_t & r,
    const vect_t a,
    const vect_t b,
    const vect_t c ) const [inline]
```

12.99.3.26 axpy() [2/2]

```
template<class _Field >
INLINE vect_t axpy (
    const vect_t c,
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.3.27 axpyin()

```
template<class _Field >
INLINE vect_t axpyin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.3.28 axpy_r() [1/2]

```
template<class _Field >
INLINE vect_t axpy_r (
    vect_t & r,
    const vect_t a,
    const vect_t b,
    const vect_t c ) const [inline]
```

12.99.3.29 axpy_r() [2/2]

```
template<class _Field >
INLINE vect_t axpy_r (
    const vect_t c,
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.3.30 axpyin_r()

```
template<class _Field >
INLINE vect_t axpyin_r (
    vect_t & c,
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.3.31 maxpy() [1/2]

```
template<class _Field >
INLINE vect_t maxpy (
    vect_t & r,
    const vect_t a,
    const vect_t b,
    const vect_t c ) const [inline]
```

12.99.3.32 maxpy() [2/2]

```
template<class _Field >
INLINE vect_t maxpy (
    const vect_t c,
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.3.33 maxpyin()

```
template<class _Field >
INLINE vect_t maxpyin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) const [inline]
```

12.99.4 Field Documentation**12.99.4.1 vect_size**

```
template<class _Field >
const constexpr size_t vect_size = simd::vect_size [static], [constexpr]
```

12.99.4.2 alignment

```
template<class _Field >
const constexpr size_t alignment = simd::alignment [static], [constexpr]
```

The documentation for this class was generated from the following file:

- [simd_modular.inl](#)

12.100 FieldTraits< Field > Struct Template Reference

FieldTrait.

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::GenericTag](#) category

Static Public Attributes

- static const bool [balanced](#) = false

12.100.1 Detailed Description

```
template<class Field>
struct FFLAS::FieldTraits< Field >
```

FieldTrait.

12.100.2 Member Typedef Documentation**12.100.2.1 category**

```
template<class Field >
typedef FieldCategories::GenericTag category
```


12.100.3 Field Documentation

12.100.3.1 balanced

```
template<class Field >
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.101 FieldTraits< FFPACK::RNSInteger< T > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::UnparametricTag](#) category

Static Public Attributes

- static const bool [balanced](#) = false

12.101.1 Member Typedef Documentation

12.101.1.1 category

```
template<typename T >
typedef FieldCategories::UnparametricTag category
```

12.101.2 Field Documentation

12.101.2.1 balanced

```
template<typename T >
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.102 FieldTraits< FFPACK::RNSIntegerMod< T > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::ModularTag](#) category

Static Public Attributes

- static const bool [balanced](#) = false

12.102.1 Member Typedef Documentation

12.102.1.1 category

```
template<typename T >
typedef FieldCategories::ModularTag category
```

12.102.2 Field Documentation

12.102.2.1 balanced

```
template<typename T >
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.103 FieldTraits< Givaro::Modular< Element > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::ModularTag](#) category

Static Public Attributes

- static const bool [balanced](#) = false

12.103.1 Member Typedef Documentation

12.103.1.1 category

```
template<class Element >
typedef FieldCategories::ModularTag category
```

12.103.2 Field Documentation

12.103.2.1 balanced

```
template<class Element >
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.104 FieldTraits< Givaro::ModularBalanced< Element > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::ModularTag](#) category

Static Public Attributes

- static const bool [balanced](#) = true

12.104.1 Member Typedef Documentation

12.104.1.1 category

```
template<class Element >
typedef FieldCategories::ModularTag category
```

12.104.2 Field Documentation

12.104.2.1 balanced

```
template<class Element >
```

```
const bool balanced = true [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.105 FieldTraits< Givaro::ZRing< double > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::UnparametricTag](#) category

Static Public Attributes

- static const bool [balanced](#) = false

12.105.1 Member Typedef Documentation

12.105.1.1 category

```
typedef FieldCategories::UnparametricTag category
```

12.105.2 Field Documentation

12.105.2.1 balanced

```
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.106 FieldTraits< Givaro::ZRing< float > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::UnparametricTag](#) category

Static Public Attributes

- static const bool [balanced](#) = false

12.106.1 Member Typedef Documentation

12.106.1.1 category

```
typedef FieldCategories::UnparametricTag category
```

12.106.2 Field Documentation

12.106.2.1 `balanced`

```
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.107 `FieldTraits< Givaro::ZRing< Givaro::Integer > >` Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::UnparametricTag](#) `category`

Static Public Attributes

- static const bool [balanced](#) = false

12.107.1 Member Typedef Documentation

12.107.1.1 `category`

```
typedef FieldCategories::UnparametricTag category
```

12.107.2 Field Documentation

12.107.2.1 `balanced`

```
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.108 `FieldTraits< Givaro::ZRing< int16_t > >` Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::UnparametricTag](#) `category`

Static Public Attributes

- static const bool [balanced](#) = false

12.108.1 Member Typedef Documentation

12.108.1.1 `category`

```
typedef FieldCategories::UnparametricTag category
```

12.108.2 Field Documentation

12.108.2.1 balanced

```
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.109 FieldTraits< Givaro::ZRing< int32_t > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::UnparametricTag](#) category

Static Public Attributes

- static const bool [balanced](#) = false

12.109.1 Member Typedef Documentation

12.109.1.1 category

```
typedef FieldCategories::UnparametricTag category
```

12.109.2 Field Documentation

12.109.2.1 balanced

```
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.110 FieldTraits< Givaro::ZRing< int64_t > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::UnparametricTag](#) category

Static Public Attributes

- static const bool [balanced](#) = false

12.110.1 Member Typedef Documentation

12.110.1.1 category

```
typedef FieldCategories::UnparametricTag category
```

12.110.2 Field Documentation

12.110.2.1 balanced

```
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.111 FieldTraits< Givaro::ZRing< RecInt::ruint< K > > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::UnparametricTag](#) category

Static Public Attributes

- static const bool [balanced](#) = false

12.111.1 Member Typedef Documentation

12.111.1.1 category

```
template<size_t K>
typedef FieldCategories::UnparametricTag category
```

12.111.2 Field Documentation

12.111.2.1 balanced

```
template<size_t K>
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.112 FieldTraits< Givaro::ZRing< uint16_t > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::UnparametricTag](#) category

Static Public Attributes

- static const bool [balanced](#) = false

12.112.1 Member Typedef Documentation

12.112.1.1 category

```
typedef FieldCategories::UnparametricTag category
```

12.112.2 Field Documentation

12.112.2.1 balanced

```
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.113 FieldTraits< Givaro::ZRing< uint32_t > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::UnparametricTag](#) category

Static Public Attributes

- static const bool [balanced](#) = false

12.113.1 Member Typedef Documentation**12.113.1.1 category**

```
typedef FieldCategories::UnparametricTag category
```

12.113.2 Field Documentation**12.113.2.1 balanced**

```
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.114 FieldTraits< Givaro::ZRing< uint64_t > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [FieldCategories::UnparametricTag](#) category

Static Public Attributes

- static const bool [balanced](#) = false

12.114.1 Member Typedef Documentation**12.114.1.1 category**

```
typedef FieldCategories::UnparametricTag category
```

12.114.2 Field Documentation**12.114.2.1 balanced**

```
const bool balanced = false [static]
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.115 Fixed Struct Reference

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.116 FixedPrecIntTag Struct Reference

Fixed precision integers above machine precision: Givaro::reclnt.

```
#include <field-traits.h>
```

12.116.1 Detailed Description

Fixed precision integers above machine precision: Givaro::reclnt.

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.117 ScalFunctionsBase< Element, typename enable_if< is_floating_point< Element >::value >::type >::FloatingPointTestDistribution Class Reference

Public Types

- using [IntType](#) = typename make_unsigned_int< Element >::type

Public Member Functions

- [FloatingPointTestDistribution](#) ()
- template<class Generator >
Element [operator\(\)](#) (Generator &g)

12.117.1 Member Typedef Documentation

12.117.1.1 IntType

```
template<typename Element >
using IntType = typename make_unsigned_int<Element>::type
```

12.117.2 Constructor & Destructor Documentation

12.117.2.1 FloatingPointTestDistribution()

```
template<typename Element >
FloatingPointTestDistribution ( ) [inline]
```

12.117.3 Member Function Documentation

12.117.3.1 operator()()

```
template<typename Element >
template<class Generator >
Element operator() (
    Generator & g ) [inline]
```

The documentation for this class was generated from the following file:

- [test-simd.C](#)

12.118 ForStrategy1D< blocksize_t, Cut, Param > Struct Template Reference

Public Member Functions

- [ForStrategy1D](#) (const blocksize_t n, const [ParSeqHelper::Parallel](#)< Cut, Param > H)
- [ForStrategy1D](#) (const blocksize_t b, const blocksize_t e, const [ParSeqHelper::Parallel](#)< Cut, Param > H)
- void [build](#) (const blocksize_t n, const [ParSeqHelper::Parallel](#)< Cut, Param > H)
- blocksize_t [initialize](#) ()
- bool [isTerminated](#) () const
- blocksize_t [begin](#) () const

- blocksize_t [end](#) () const
- blocksize_t [numblocks](#) () const
- blocksize_t [blockindex](#) () const
- blocksize_t [operator++](#) ()

Protected Attributes

- blocksize_t [ibeg](#)
- blocksize_t [iend](#)
- blocksize_t [current](#)
- blocksize_t [firstBlockSize](#)
- blocksize_t [lastBlockSize](#)
- blocksize_t [changeBS](#)
- blocksize_t [numBlock](#)

12.118.1 Constructor & Destructor Documentation

12.118.1.1 ForStrategy1D() [1/2]

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
ForStrategy1D (
    const blocksize_t n,
    const ParSeqHelper::Parallel< Cut, Param > H ) [inline]
```

12.118.1.2 ForStrategy1D() [2/2]

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
ForStrategy1D (
    const blocksize_t b,
    const blocksize_t e,
    const ParSeqHelper::Parallel< Cut, Param > H ) [inline]
```

12.118.2 Member Function Documentation

12.118.2.1 build()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
void build (
    const blocksize_t n,
    const ParSeqHelper::Parallel< Cut, Param > H ) [inline]
```

12.118.2.2 initialize()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t initialize ( ) [inline]
```

12.118.2.3 isTerminated()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
bool isTerminated ( ) const [inline]
```

12.118.2.4 begin()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t begin ( ) const [inline]
```

12.118.2.5 end()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t end ( ) const [inline]
```

12.118.2.6 numblocks()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t numblocks ( ) const [inline]
```

12.118.2.7 blockindex()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t blockindex ( ) const [inline]
```

12.118.2.8 operator++()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t operator++ ( ) [inline]
```

12.118.3 Field Documentation**12.118.3.1 ibeg**

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t ibeg [protected]
```

12.118.3.2 iend

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t iend [protected]
```

12.118.3.3 current

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t current [protected]
```

12.118.3.4 firstBlockSize

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t firstBlockSize [protected]
```

12.118.3.5 lastBlockSize

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t lastBlockSize [protected]
```

12.118.3.6 changeBS

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t changeBS [protected]
```

12.118.3.7 numBlock

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t numBlock [protected]
```

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.119 ForStrategy2D< blocksize_t, Cut, Param > Struct Template Reference

Public Member Functions

- [ForStrategy2D](#) (const blocksize_t m, const blocksize_t n, const [ParSeqHelper::Parallel](#)< Cut, Param > H)
- blocksize_t [initialize](#) ()
- bool [isTerminated](#) () const
- blocksize_t [ibegin](#) () const
- blocksize_t [jbegin](#) () const
- blocksize_t [iend](#) () const
- blocksize_t [jend](#) () const
- blocksize_t [operator++](#) ()
- blocksize_t [rownumblocks](#) () const
- blocksize_t [colnumblocks](#) () const
- blocksize_t [blockindex](#) () const
- blocksize_t [rowblockindex](#) () const
- blocksize_t [colblockindex](#) () const

Protected Attributes

- blocksize_t [_ibeg](#)
- blocksize_t [_iend](#)
- blocksize_t [_jbeg](#)
- blocksize_t [_jend](#)
- blocksize_t [rowBlockSize](#)
- blocksize_t [colBlockSize](#)
- blocksize_t [current](#)
- blocksize_t [lastRBS](#)
- blocksize_t [lastCBS](#)
- blocksize_t [changeRBS](#)
- blocksize_t [changeCBS](#)
- blocksize_t [numRowBlock](#)
- blocksize_t [numColBlock](#)
- blocksize_t [BLOCKS](#)

Friends

- std::ostream & [operator<<](#) (std::ostream &out, const [ForStrategy2D](#) &FS2D)

12.119.1 Constructor & Destructor Documentation

12.119.1.1 ForStrategy2D()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
ForStrategy2D (
    const blocksize_t m,
    const blocksize_t n,
    const ParSeqHelper::Parallel< Cut, Param > H ) [inline]
```

12.119.2 Member Function Documentation

12.119.2.1 initialize()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t initialize ( ) [inline]
```

12.119.2.2 isTerminated()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
bool isTerminated ( ) const [inline]
```

12.119.2.3 ibegin()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t ibegin ( ) const [inline]
```

12.119.2.4 jbegin()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t jbegin ( ) const [inline]
```

12.119.2.5 iend()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t iend ( ) const [inline]
```

12.119.2.6 jend()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t jend ( ) const [inline]
```

12.119.2.7 operator++()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t operator++ ( ) [inline]
```

12.119.2.8 rownumblocks()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t rownumblocks ( ) const [inline]
```

12.119.2.9 colnumblocks()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t colnumblocks ( ) const [inline]
```

12.119.2.10 blockindex()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t blockindex ( ) const [inline]
```

12.119.2.11 rowblockindex()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t rowblockindex ( ) const [inline]
```

12.119.2.12 colblockindex()

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t colblockindex ( ) const [inline]
```

12.119.3 Friends And Related Symbol Documentation**12.119.3.1 operator<<**

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
std::ostream & operator<< (
    std::ostream & out,
    const ForStrategy2D< blocksize_t, Cut, Param > & FS2D ) [friend]
```

12.119.4 Field Documentation**12.119.4.1 _ibeg**

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t _ibeg [protected]
```

12.119.4.2 _iend

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t _iend [protected]
```

12.119.4.3 _jbeg

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t _jbeg [protected]
```

12.119.4.4 _jend

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t _jend [protected]
```

12.119.4.5 rowBlockSize

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t rowBlockSize [protected]
```

12.119.4.6 colBlockSize

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t colBlockSize [protected]
```

12.119.4.7 current

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t current [protected]
```

12.119.4.8 lastRBS

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t lastRBS [protected]
```

12.119.4.9 lastCBS

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t lastCBS [protected]
```

12.119.4.10 changeRBS

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t changeRBS [protected]
```

12.119.4.11 changeCBS

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t changeCBS [protected]
```

12.119.4.12 numRowsBlock

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t numRowsBlock [protected]
```

12.119.4.13 numColBlock

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t numColBlock [protected]
```

12.119.4.14 BLOCKS

```
template<typename blocksize_t = size_t, typename Cut = CuttingStrategy::Block, typename Param
= StrategyParameter::Threads>
blocksize_t BLOCKS [protected]
```

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.120 `ftrmmLeftLowerNoTransNonUnit< Element >` Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.121 `ftrmmLeftLowerNoTransUnit< Element >` Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.122 `ftrmmLeftLowerTransNonUnit< Element >` Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.123 `ftrmmLeftLowerTransUnit< Element >` Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.124 `ftrmmLeftUpperNoTransNonUnit< Element >` Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.125 `ftrmmLeftUpperNoTransUnit< Element >` Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.126 `ftrmmLeftUpperTransNonUnit< Element >` Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.127 `ftrmmLeftUpperTransUnit`< `Element` > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.128 `ftrmmRightLowerNoTransNonUnit`< `Element` > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.129 `ftrmmRightLowerNoTransUnit`< `Element` > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.130 `ftrmmRightLowerTransNonUnit`< `Element` > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.131 `ftrmmRightLowerTransUnit`< `Element` > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.132 `ftrmmRightUpperNoTransNonUnit`< `Element` > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.133 `ftrmmRightUpperNoTransUnit`< `Element` > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.134 `ftrmmRightUpperTransNonUnit`< `Element` > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.135 ftrmmRightUpperTransUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.136 ftrsmLeftLowerNoTransNonUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.137 ftrsmLeftLowerNoTransUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.138 ftrsmLeftLowerTransNonUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.139 ftrsmLeftLowerTransUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.140 ftrsmLeftUpperNoTransNonUnit< Element > Class Template Reference

Computes the maximal size for delaying the modular reduction in a triangular system resolution.

12.140.1 Detailed Description

template<class Element>

class FFLAS::Protected::ftrsmLeftUpperNoTransNonUnit< Element >

Computes the maximal size for delaying the modular reduction in a triangular system resolution.

Compute the maximal dimension k , such that a unit diagonal triangular system of dimension k can be solved over Z without overflow of the underlying floating point representation.

Bibliography • Dumas, Giorgi, Pernet 06, arXiv:cs/0601133.

Parameters

F	Finite Field/Ring of the computation

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.141 ftrsmLeftUpperNoTransUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.142 ftrsmLeftUpperTransNonUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.143 ftrsmLeftUpperTransUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.144 ftrsmRightLowerNoTransNonUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.145 ftrsmRightLowerNoTransUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.146 ftrsmRightLowerTransNonUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.147 ftrsmRightLowerTransUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.148 ftrsmRightUpperNoTransNonUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.149 ftrsmRightUpperNoTransUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.150 ftrsmRightUpperTransNonUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.151 ftrsmRightUpperTransUnit< Element > Class Template Reference

The documentation for this class was generated from the following file:

- [fflas_level3.inl](#)

12.152 GenericTag Struct Reference

default is generic

```
#include <field-traits.h>
```

12.152.1 Detailed Description

default is generic

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.153 GenericTag Struct Reference

generic ring.

```
#include <field-traits.h>
```

12.153.1 Detailed Description

generic ring.

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.154 Grain Struct Reference

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.155 `has_minus_eq_impl< C >` Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Static Public Attributes

- static constexpr bool [value](#) = type::value

12.155.1 Field Documentation

12.155.1.1 `value`

```
template<typename C >
constexpr bool value = type::value [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.156 `has_minus_impl< C >` Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Static Public Attributes

- static constexpr bool [value](#) = type::value

12.156.1 Field Documentation

12.156.1.1 `value`

```
template<typename C >
constexpr bool value = type::value [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.157 `has_mul_eq_impl< C >` Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Static Public Attributes

- static constexpr bool [value](#) = type::value

12.157.1 Field Documentation

12.157.1.1 `value`

```
template<typename C >
constexpr bool value = type::value [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.158 `has_mul_impl< C >` Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Static Public Attributes

- static constexpr bool [value](#) = type::value

12.158.1 Field Documentation**12.158.1.1 value**

```
template<typename C >
constexpr bool value = type::value [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.159 has_operation< T > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Static Public Attributes

- static constexpr bool [value](#)

12.159.1 Field Documentation**12.159.1.1 value**

```
template<class T >
constexpr bool value [static], [constexpr]
```

Initial value:

```
= (has_plus<T>::value && has_minus<T>::value && has_equal<T>::value &&
    has_plus_eq<T>::value && has_minus_eq<T>::value && has_mul<T>::value
    && has_mul_eq<T>::value)
```

The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.160 has_plus_eq_impl< C > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Static Public Attributes

- static constexpr bool [value](#) = type::value

12.160.1 Field Documentation**12.160.1.1 value**

```
template<typename C >
constexpr bool value = type::value [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.161 has_plus_impl< C > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Static Public Attributes

- static constexpr bool [value](#) = type::value

12.161.1 Field Documentation

12.161.1.1 value

```
template<typename C >
```

```
constexpr bool value = type::value [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.162 HelperFlag Struct Reference

```
#include <fflas_sparse.h>
```

Static Public Attributes

- static constexpr uint64_t [none](#) = 0_ui64
- static constexpr uint64_t [coo](#) = 1_ui64
- static constexpr uint64_t [csr](#) = 1_ui64 << 1
- static constexpr uint64_t [ell](#) = 1_ui64 << 2
- static constexpr uint64_t [aut](#) = 1_ui64 << 32
- static constexpr uint64_t [pm1](#) = 1_ui64 << 33

12.162.1 Field Documentation

12.162.1.1 none

```
constexpr uint64_t none = 0_ui64 [static], [constexpr]
```

12.162.1.2 coo

```
constexpr uint64_t coo = 1_ui64 [static], [constexpr]
```

12.162.1.3 csr

```
constexpr uint64_t csr = 1_ui64 << 1 [static], [constexpr]
```

12.162.1.4 ell

```
constexpr uint64_t ell = 1_ui64 << 2 [static], [constexpr]
```

12.162.1.5 aut

```
constexpr uint64_t aut = 1_ui64 << 32 [static], [constexpr]
```

12.162.1.6 pm1

```
constexpr uint64_t pm1 = 1_ui64 << 33 [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [fflas_sparse.h](#)

12.163 HelperMod< Field, ElementTraits > Struct Template Reference

The documentation for this struct was generated from the following file:

- [fflas_freduce.inl](#)

12.164 HelperMod< Field, ElementCategories::MachineIntTag > Struct Template Reference

Public Member Functions

- [HelperMod](#) ()
- [HelperMod](#) (const [Field](#) &F)

Data Fields

- [Field::Element](#) p
- double [invp](#)
- double [min](#)
- double [max](#)
- int64_t [pow50rem](#)

12.164.1 Constructor & Destructor Documentation

12.164.1.1 HelperMod() [1/2]

```
template<class Field >
HelperMod ( ) [inline]
```

12.164.1.2 HelperMod() [2/2]

```
template<class Field >
HelperMod (
    const Field & F ) [inline]
```

12.164.2 Field Documentation

12.164.2.1 p

```
template<class Field >
Field::Element p
```

12.164.2.2 invp

```
template<class Field >
double invp
```

12.164.2.3 min

```
template<class Field >
double min
```

12.164.2.4 max

```
template<class Field >
double max
```

12.164.2.5 pow50rem

```
template<class Field >
int64_t pow50rem
```

The documentation for this struct was generated from the following file:

- [fflas_freduce.inl](#)

12.165 HelperMod< Field, FFLAS::ElementCategories::ArbitraryPrecIntTag > Struct Template Reference

Public Member Functions

- [HelperMod\(\)](#)
- [HelperMod\(const Field &F\)](#)

Data Fields

- [Field::Element p](#)

12.165.1 Constructor & Destructor Documentation

12.165.1.1 HelperMod() [1/2]

```
template<class Field >
HelperMod ( ) [inline]
```

12.165.1.2 HelperMod() [2/2]

```
template<class Field >
HelperMod (
    const Field & F ) [inline]
```

12.165.2 Field Documentation

12.165.2.1 p

```
template<class Field >
Field::Element p
```

The documentation for this struct was generated from the following file:

- [fflas_freduce.inl](#)

12.166 HelperMod< Field, FFLAS::ElementCategories::FixedPrecIntTag > Struct Template Reference

Public Member Functions

- [HelperMod\(\)](#)
- [HelperMod\(const Field &F\)](#)

Data Fields

- [Field::Element p](#)

12.166.1 Constructor & Destructor Documentation

12.166.1.1 HelperMod() [1/2]

```
template<class Field >
HelperMod ( ) [inline]
```

12.166.1.2 HelperMod() [2/2]

```
template<class Field >
HelperMod (
    const Field & F ) [inline]
```


12.166.2 Field Documentation

12.166.2.1 p

```
template<class Field >
Field::Element p
```

The documentation for this struct was generated from the following file:

- [fflas_freduce.inl](#)

12.167 HelperMod< Field, FFLAS::ElementCategories::MachineFloatTag > Struct Template Reference

Public Member Functions

- [HelperMod](#) ()
- [HelperMod](#) (const [Field](#) &F)

Data Fields

- [Field::Element](#) p
- [Field::Element](#) invp
- [Field::Element](#) min
- [Field::Element](#) max

12.167.1 Constructor & Destructor Documentation

12.167.1.1 HelperMod() [1/2]

```
template<class Field >
HelperMod ( ) [inline]
```

12.167.1.2 HelperMod() [2/2]

```
template<class Field >
HelperMod (
    const Field & F ) [inline]
```

12.167.2 Field Documentation

12.167.2.1 p

```
template<class Field >
Field::Element p
```

12.167.2.2 invp

```
template<class Field >
Field::Element invp
```

12.167.2.3 min

```
template<class Field >
Field::Element min
```

12.167.2.4 max

```
template<class Field >
Field::Element max
```

The documentation for this struct was generated from the following file:

- [fflas_freduce.inl](#)

12.168 Hybrid Struct Reference

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.169 Info Struct Reference

Public Member Functions

- [Info](#) (uint64_t it, uint64_t s, uint64_t p)
- [Info](#) ()=default
- [Info](#) (const [Info](#) &)=default
- [Info](#) ([Info](#) &&)=default
- [Info](#) & [operator=](#) (const [Info](#) &)=default
- [Info](#) & [operator=](#) ([Info](#) &&)=default

Data Fields

- uint64_t [size](#) = 0
- uint64_t [perm](#) = 0
- uint64_t [begin](#) = 0

12.169.1 Constructor & Destructor Documentation

12.169.1.1 Info() [1/4]

```
Info (
    uint64_t it,
    uint64_t s,
    uint64_t p ) [inline]
```

12.169.1.2 Info() [2/4]

```
Info ( ) [default]
```

12.169.1.3 Info() [3/4]

```
Info (
    const Info & ) [default]
```

12.169.1.4 Info() [4/4]

```
Info (
    Info && ) [default]
```

12.169.2 Member Function Documentation

12.169.2.1 operator=() [1/2]

```
Info & operator= (
    const Info & ) [default]
```

12.169.2.2 operator=() [2/2]

```
Info & operator= (
    Info && ) [default]
```

12.169.3 Field Documentation

12.169.3.1 size

`uint64_t size = 0`

12.169.3.2 perm

`uint64_t perm = 0`

12.169.3.3 begin

`uint64_t begin = 0`

The documentation for this struct was generated from the following file:

- [csr_hyb_utils.inl](#)

12.170 Info Struct Reference

Public Member Functions

- [Info](#) (`uint64_t it`, `uint64_t s`, `uint64_t p`)
- [Info](#) ()=default
- [Info](#) (const [Info](#) &)=default
- [Info](#) ([Info](#) &&)=default
- [Info](#) & [operator=](#) (const [Info](#) &)=default
- [Info](#) & [operator=](#) ([Info](#) &&)=default

Data Fields

- `uint64_t` [size](#) = 0
- `uint64_t` [perm](#) = 0
- `uint64_t` [begin](#) = 0

12.170.1 Constructor & Destructor Documentation

12.170.1.1 Info() [1/4]

```
Info (
    uint64_t it,
    uint64_t s,
    uint64_t p ) [inline]
```

12.170.1.2 Info() [2/4]

```
Info ( ) [default]
```

12.170.1.3 Info() [3/4]

```
Info (
    const Info & ) [default]
```

12.170.1.4 Info() [4/4]

```
Info (
    Info && ) [default]
```

12.170.2 Member Function Documentation

12.170.2.1 operator=() [1/2]

`Info` & operator= (
 const `Info` &) [default]

12.170.2.2 operator=() [2/2]

`Info` & operator= (
 `Info` &&) [default]

12.170.3 Field Documentation

12.170.3.1 size

`uint64_t` size = 0

12.170.3.2 perm

`uint64_t` perm = 0

12.170.3.3 begin

`uint64_t` begin = 0

The documentation for this struct was generated from the following file:

- [sell_utils.inl](#)

12.171 is_all_same< Args > Struct Template Reference

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.172 is_all_same< T, Args... > Struct Template Reference

Static Public Attributes

- static constexpr bool `value` = `ALL`<std::is_same<typename decay<T>::type, typename decay<Args>↵
::type>::value...>::value

12.172.1 Field Documentation

12.172.1.1 value

```
template<typename T , typename... Args>
constexpr bool value = ALL<std::is_same<typename decay<T>::type, typename decay<Args>↵
::type>::value...>::value [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.173 is_all_same<> Struct Reference

Static Public Attributes

- static constexpr bool `value` = true

12.173.1 Field Documentation

12.173.1.1 value

```
constexpr bool value = true [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.174 `is_simd< T >` Struct Template Reference

```
#include <fflas_simd.h>
```

Public Types

- using `type` = `std::integral_constant< bool, false >`

Static Public Attributes

- static const constexpr bool `value` = false

12.174.1 Member Typedef Documentation

12.174.1.1 type

```
template<class T >
using type = std::integral_constant<bool, false>
```

12.174.2 Field Documentation

12.174.2.1 value

```
template<class T >
const constexpr bool value = false [static], [constexpr]
```


The documentation for this struct was generated from the following file:

- [fflas_simd.h](#)

12.175 `isSparseMatrix< Field, M >` Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for `isSparseMatrix< Field, M >`:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.176 `isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO > >` Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for `isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO > >`:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.177 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO_ZO > > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for `isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO_ZO > >`:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.178 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR > > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for `isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR > >`:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.179 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_HYB > > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for `isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_HYB > >`:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.180 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_ZO > > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_ZO > >:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.181 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL > > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL > >:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.182 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd > > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd > >:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.183 `isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > >` Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for `isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > >`:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.184 `isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_ZO > >` Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for `isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_ZO > >`:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.185 `isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::HYB_ZO > >` Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for `isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::HYB_ZO > >`:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.186 `isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL > >` Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for `isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL > >`:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.187 isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL_ZO > > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for isSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL_ZO > >:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.188 isSparseMatrixMKLFormat< F, M > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for isSparseMatrixMKLFormat< F, M >:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.189 isSparseMatrixSimdFormat< F, M > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for isSparseMatrixSimdFormat< F, M >:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.190 isZOSparseMatrix< F, M > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for isZOSparseMatrix< F, M >:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.191 isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO_ZO > > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::COO_ZO > >:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.192 isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_ZO > > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::CSR_ZO > >:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.193 isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > >:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.194 isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_ZO > > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_ZO > >:




The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.195 isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL_ZO > > Struct Template Reference

```
#include <sparse_matrix_traits.h>
```

Inheritance diagram for isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL_ZO > >:



The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.196 Iterative Struct Reference

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.197 LazyTag Struct Reference

Performs field operations with delayed mod only when necessary. Result may not be reduced.

```
#include <field-traits.h>
```

12.197.1 Detailed Description

Performs field operations with delayed mod only when necessary. Result may not be reduced.
The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.198 `limits< T >` Struct Template Reference

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.199 `limits< char >` Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef char [T](#)

Static Public Member Functions

- static constexpr char [max](#) () noexcept
- static constexpr char [min](#) () noexcept
- static constexpr int32_t [digits](#) () noexcept

12.199.1 Member Typedef Documentation

12.199.1.1 `T`

```
typedef char T
```

12.199.2 Member Function Documentation

12.199.2.1 `max()`

```
static constexpr char max ( ) [inline], [static], [constexpr], [noexcept]
```

12.199.2.2 `min()`

```
static constexpr char min ( ) [inline], [static], [constexpr], [noexcept]
```

12.199.2.3 `digits()`

```
static constexpr int32_t digits ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.200 `limits< double >` Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef double [T](#)

Static Public Member Functions

- static constexpr int64_t [max](#) () noexcept
- static constexpr int64_t [min](#) () noexcept
- static constexpr int32_t [digits](#) () noexcept

12.200.1 Member Typedef Documentation

12.200.1.1 T

```
typedef double T
```

12.200.2 Member Function Documentation

12.200.2.1 max()

```
static constexpr int64_t max ( ) [inline], [static], [constexpr], [noexcept]
```

12.200.2.2 min()

```
static constexpr int64_t min ( ) [inline], [static], [constexpr], [noexcept]
```

12.200.2.3 digits()

```
static constexpr int32_t digits ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.201 limits< float > Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef float [T](#)

Static Public Member Functions

- static constexpr int32_t [max](#) () noexcept
- static constexpr int32_t [min](#) () noexcept
- static constexpr int32_t [digits](#) () noexcept

12.201.1 Member Typedef Documentation

12.201.1.1 T

```
typedef float T
```

12.201.2 Member Function Documentation

12.201.2.1 max()

```
static constexpr int32_t max ( ) [inline], [static], [constexpr], [noexcept]
```

12.201.2.2 min()

```
static constexpr int32_t min ( ) [inline], [static], [constexpr], [noexcept]
```

12.201.2.3 digits()

```
static constexpr int32_t digits ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.202 limits< Givaro::Integer > Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef Givaro::Integer [T](#)

Static Public Member Functions

- static constexpr int [max](#) () noexcept
- static constexpr int [min](#) () noexcept

12.202.1 Member Typedef Documentation

12.202.1.1 T

```
typedef Givaro::Integer T
```

12.202.2 Member Function Documentation

12.202.2.1 max()

```
static constexpr int max ( ) [inline], [static], [constexpr], [noexcept]
```

12.202.2.2 min()

```
static constexpr int min ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.203 limits< int > Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef int [T](#)

Static Public Member Functions

- static constexpr int [max](#) () noexcept
- static constexpr int [min](#) () noexcept
- static constexpr int32_t [digits](#) () noexcept

12.203.1 Member Typedef Documentation

12.203.1.1 T

```
typedef int T
```

12.203.2 Member Function Documentation

12.203.2.1 max()

```
static constexpr int max ( ) [inline], [static], [constexpr], [noexcept]
```

12.203.2.2 min()

```
static constexpr int min ( ) [inline], [static], [constexpr], [noexcept]
```

12.203.2.3 digits()

```
static constexpr int32_t digits ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.204 limits< long > Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef long [T](#)

Static Public Member Functions

- static constexpr long [max](#) () noexcept
- static constexpr long [min](#) () noexcept
- static constexpr int32_t [digits](#) () noexcept

12.204.1 Member Typedef Documentation

12.204.1.1 T

```
typedef long T
```

12.204.2 Member Function Documentation

12.204.2.1 max()

```
static constexpr long max ( ) [inline], [static], [constexpr], [noexcept]
```

12.204.2.2 min()

```
static constexpr long min ( ) [inline], [static], [constexpr], [noexcept]
```

12.204.2.3 digits()

```
static constexpr int32_t digits ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.205 limits< long long > Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef long long [T](#)

Static Public Member Functions

- static constexpr long long [max](#) () noexcept
- static constexpr long long [min](#) () noexcept
- static constexpr int32_t [digits](#) () noexcept

12.205.1 Member Typedef Documentation

12.205.1.1 T

```
typedef long long T
```

12.205.2 Member Function Documentation

12.205.2.1 max()

```
static constexpr long long max ( ) [inline], [static], [constexpr], [noexcept]
```

12.205.2.2 min()

```
static constexpr long long min ( ) [inline], [static], [constexpr], [noexcept]
```

12.205.2.3 digits()

```
static constexpr int32_t digits ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.206 limits< RecInt::rint< K > > Struct Template Reference

```
#include <flimits.h>
```

Public Types

- typedef [RecInt::ruint](#)< K > T

Static Public Member Functions

- static constexpr [RecInt::rint](#)< K > [max](#) () noexcept
- static constexpr [RecInt::rint](#)< K > [min](#) () noexcept

12.206.1 Member Typedef Documentation

12.206.1.1 T

```
template<size_t K>
typedef RecInt::ruint<K> T
```

12.206.2 Member Function Documentation

12.206.2.1 max()

```
template<size_t K>
static constexpr RecInt::rint< K > max ( ) [inline], [static], [constexpr], [noexcept]
```


12.206.2.2 min()

```
template<size_t K>
```

```
static constexpr RecInt::rint< K > min ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.207 limits< RecInt::ruint< K > > Struct Template Reference

```
#include <flimits.h>
```

Public Types

- typedef [RecInt::ruint< K > T](#)

Static Public Member Functions

- static constexpr [RecInt::ruint< K > max](#) () noexcept
- static constexpr [RecInt::ruint< K > min](#) () noexcept

12.207.1 Member Typedef Documentation**12.207.1.1 T**

```
template<size_t K>
```

```
typedef RecInt::ruint<K> T
```

12.207.2 Member Function Documentation**12.207.2.1 max()**

```
template<size_t K>
```

```
static constexpr RecInt::ruint< K > max ( ) [inline], [static], [constexpr], [noexcept]
```

12.207.2.2 min()

```
template<size_t K>
```

```
static constexpr RecInt::ruint< K > min ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.208 limits< short int > Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef short int [T](#)

Static Public Member Functions

- static constexpr short int [max](#) () noexcept
- static constexpr short int [min](#) () noexcept
- static constexpr int32_t [digits](#) () noexcept

12.208.1 Member Typedef Documentation

12.208.1.1 T

```
typedef short int T
```

12.208.2 Member Function Documentation

12.208.2.1 max()

```
static constexpr short int max ( ) [inline], [static], [constexpr], [noexcept]
```

12.208.2.2 min()

```
static constexpr short int min ( ) [inline], [static], [constexpr], [noexcept]
```

12.208.2.3 digits()

```
static constexpr int32_t digits ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.209 limits< signed char > Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef signed char [T](#)

Static Public Member Functions

- static constexpr signed char [max](#) () noexcept
- static constexpr signed char [min](#) () noexcept
- static constexpr int32_t [digits](#) () noexcept

12.209.1 Member Typedef Documentation

12.209.1.1 T

```
typedef signed char T
```

12.209.2 Member Function Documentation

12.209.2.1 max()

```
static constexpr signed char max ( ) [inline], [static], [constexpr], [noexcept]
```

12.209.2.2 min()

```
static constexpr signed char min ( ) [inline], [static], [constexpr], [noexcept]
```

12.209.2.3 digits()

```
static constexpr int32_t digits ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.210 limits< unsigned char > Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef unsigned char [T](#)

Static Public Member Functions

- static constexpr unsigned char [max](#) () noexcept
- static constexpr unsigned char [min](#) () noexcept
- static constexpr int32_t [digits](#) () noexcept

12.210.1 Member Typedef Documentation

12.210.1.1 T

```
typedef unsigned char T
```

12.210.2 Member Function Documentation

12.210.2.1 max()

```
static constexpr unsigned char max ( ) [inline], [static], [constexpr], [noexcept]
```

12.210.2.2 min()

```
static constexpr unsigned char min ( ) [inline], [static], [constexpr], [noexcept]
```

12.210.2.3 digits()

```
static constexpr int32_t digits ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.211 limits< unsigned int > Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef unsigned int [T](#)

Static Public Member Functions

- static constexpr unsigned int [max](#) () noexcept
- static constexpr unsigned int [min](#) () noexcept
- static constexpr int32_t [digits](#) () noexcept

12.211.1 Member Typedef Documentation

12.211.1.1 T

```
typedef unsigned int T
```

12.211.2 Member Function Documentation

12.211.2.1 max()

```
static constexpr unsigned int max ( ) [inline], [static], [constexpr], [noexcept]
```

12.211.2.2 min()

```
static constexpr unsigned int min ( ) [inline], [static], [constexpr], [noexcept]
```

12.211.2.3 digits()

```
static constexpr int32_t digits ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.212 limits< unsigned long > Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef unsigned long [T](#)

Static Public Member Functions

- static constexpr unsigned long [max](#) () noexcept
- static constexpr unsigned long [min](#) () noexcept
- static constexpr int32_t [digits](#) () noexcept

12.212.1 Member Typedef Documentation

12.212.1.1 T

```
typedef unsigned long T
```

12.212.2 Member Function Documentation

12.212.2.1 max()

```
static constexpr unsigned long max ( ) [inline], [static], [constexpr], [noexcept]
```

12.212.2.2 min()

```
static constexpr unsigned long min ( ) [inline], [static], [constexpr], [noexcept]
```

12.212.2.3 digits()

```
static constexpr int32_t digits ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.213 limits< unsigned long long > Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef unsigned long long [T](#)

Static Public Member Functions

- static constexpr unsigned long long [max](#) () noexcept
- static constexpr unsigned long long [min](#) () noexcept
- static constexpr int32_t [digits](#) () noexcept

12.213.1 Member Typedef Documentation

12.213.1.1 T

```
typedef unsigned long long T
```

12.213.2 Member Function Documentation

12.213.2.1 max()

```
static constexpr unsigned long long max ( ) [inline], [static], [constexpr], [noexcept]
```

12.213.2.2 min()

```
static constexpr unsigned long long min ( ) [inline], [static], [constexpr], [noexcept]
```

12.213.2.3 digits()

```
static constexpr int32_t digits ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.214 limits< unsigned short int > Struct Reference

```
#include <flimits.h>
```

Public Types

- typedef unsigned short int [T](#)

Static Public Member Functions

- static constexpr unsigned short int [max](#) () noexcept
- static constexpr unsigned short int [min](#) () noexcept
- static constexpr int32_t [digits](#) () noexcept

12.214.1 Member Typedef Documentation

12.214.1.1 T

```
typedef unsigned short int T
```

12.214.2 Member Function Documentation

12.214.2.1 max()

```
static constexpr unsigned short int max ( ) [inline], [static], [constexpr], [noexcept]
```

12.214.2.2 min()

```
static constexpr unsigned short int min ( ) [inline], [static], [constexpr], [noexcept]
```

12.214.2.3 digits()

```
static constexpr int32_t digits ( ) [inline], [static], [constexpr], [noexcept]
```

The documentation for this struct was generated from the following file:

- [flimits.h](#)

12.215 MachineFloatTag Struct Reference

float or double

```
#include <field-traits.h>
```

12.215.1 Detailed Description

float or double

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.216 MachineIntTag Struct Reference

short, int, long, long long, and unsigned variants

```
#include <field-traits.h>
```

12.216.1 Detailed Description

short, int, long, long long, and unsigned variants

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.217 MMHelper< Field, AlgoTrait, ModeTrait, ParSeqTrait > Struct Template Reference

Public Types

- typedef [MMHelper](#)< [Field](#), [AlgoTrait](#), [ModeTrait](#), [ParSeqTrait](#) > [Self_t](#)
- typedef [associatedDelayedField](#)< constField >::type [DelayedField_t](#)
- typedef [associatedDelayedField](#)< constField >::field [DelayedField](#)
- typedef [DelayedField](#)::Element [DFelt](#)

Public Member Functions

- void [initC](#) ()
- void [initA](#) ()
- void [initB](#) ()
- void [initOut](#) ()
- size_t [MaxDelayedDim](#) ([DFelt](#) beta)
- bool [Aunfit](#) ()
- bool [Bunfit](#) ()
- void [setOutBounds](#) (const size_t k, const [DFelt](#) alpha, const [DFelt](#) beta)
- bool [checkA](#) (const [Field](#) &F, const [FFLAS::FFLAS_TRANSPOSE](#) ta, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda)
- bool [checkB](#) (const [Field](#) &F, const [FFLAS::FFLAS_TRANSPOSE](#) tb, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t ldb)
- bool [checkOut](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda)

- bool `checkOut` (const `Field` &F, `FFLAS_UPLO` uplo, const `size_t` M, const `size_t` N, typename `Field::ConstElement_ptr` A, const `size_t` lda)
- `MMHelper` ()
- `MMHelper` (const `Field` &F, `size_t` m, `size_t` k, `size_t` n, `ParSeqTrait_PS`)
- `MMHelper` (const `Field` &F, int w, `ParSeqTrait_PS`=`ParSeqTrait`())
- template<class F2 , typename AlgoT2 , typename FT2 , typename PS2 >
`MMHelper` (`MMHelper`< F2, AlgoT2, FT2, PS2 > &WH)
- `MMHelper` (const `Field` &F, int w, `DFElt_Amin`, `DFElt_Amax`, `DFElt_Bmin`, `DFElt_Bmax`, `DFElt_Cmin`, `DFElt_Cmax`, `ParSeqTrait_PS`=`ParSeqTrait`())

Data Fields

- int `recLevel`
- `DFElt` `FieldMin`
- `DFElt` `FieldMax`
- `DFElt` `Amin`
- `DFElt` `Amax`
- `DFElt` `Bmin`
- `DFElt` `Bmax`
- `DFElt` `Cmin`
- `DFElt` `Cmax`
- `DFElt` `Outmin`
- `DFElt` `Outmax`
- `DFElt` `MaxStorableValue`
- const `DelayedField_t` `delayedField`
- `ParSeqTrait` `parseq`

Friends

- std::ostream & `operator<<` (std::ostream &out, const `Self_t` &M)

12.217.1 Member Typedef Documentation

12.217.1.1 Self_t

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
typedef MMHelper<Field,AlgoTrait,ModeTrait,ParSeqTrait> Self_t
```

12.217.1.2 DelayedField_t

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
typedef associatedDelayedField<constField>::type DelayedField_t
```

12.217.1.3 DelayedField

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
typedef associatedDelayedField<constField>::field DelayedField
```

12.217.1.4 DFElt

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
typedef DelayedField::Element DFElt
```

12.217.2 Constructor & Destructor Documentation

12.217.2.1 MMHelper() [1/5]

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
MMHelper ( ) [inline]
```

12.217.2.2 MMHelper() [2/5]

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
MMHelper (
    const Field & F,
    size_t m,
    size_t k,
    size_t n,
    ParSeqTrait _PS ) [inline]
```

12.217.2.3 MMHelper() [3/5]

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
MMHelper (
    const Field & F,
    int w,
    ParSeqTrait _PS = ParSeqTrait() ) [inline]
```

12.217.2.4 MMHelper() [4/5]

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
template<class F2 , typename AlgoT2 , typename FT2 , typename PS2 >
MMHelper (
    MMHelper< F2, AlgoT2, FT2, PS2 > & WH ) [inline]
```

12.217.2.5 MMHelper() [5/5]

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
MMHelper (
    const Field & F,
    int w,
    DFelt _Amin,
    DFelt _Amax,
    DFelt _Bmin,
    DFelt _Bmax,
    DFelt _Cmin,
    DFelt _Cmax,
    ParSeqTrait _PS = ParSeqTrait() ) [inline]
```

12.217.3 Member Function Documentation**12.217.3.1 initC()**

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
void initC ( ) [inline]
```

12.217.3.2 initA()

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
void initA ( ) [inline]
```

12.217.3.3 initB()

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
void initB ( ) [inline]
```

12.217.3.4 initOut()

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
void initOut ( ) [inline]
```


12.217.3.5 MaxDelayedDim()

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
size_t MaxDelayedDim (
    DFelt beta ) [inline]
```

12.217.3.6 Aunfit()

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
bool Aunfit ( ) [inline]
```

12.217.3.7 Bunfit()

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
bool Bunfit ( ) [inline]
```

12.217.3.8 setOutBounds()

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
void setOutBounds (
    const size_t k,
    const DFelt alpha,
    const DFelt beta ) [inline]
```

12.217.3.9 checkA()

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
bool checkA (
    const Field & F,
    const FFLAS::FFLAS_TRANSPOSE ta,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda ) [inline]
```

12.217.3.10 checkB()

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
bool checkB (
    const Field & F,
    const FFLAS::FFLAS_TRANSPOSE tb,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr B,
    const size_t ldb ) [inline]
```

12.217.3.11 checkOut() [1/2]

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
bool checkOut (
    const Field & F,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda ) [inline]
```

12.217.3.12 checkOut() [2/2]

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
bool checkOut (
```

```

    const Field & F,
    FFLAS_UPLO uplo,
    const size_t M,
    const size_t N,
    typename Field::ConstElement_ptr A,
    const size_t lda ) [inline]

```

12.217.4 Friends And Related Symbol Documentation

12.217.4.1 operator<<

```

template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
std::ostream & operator<< (
    std::ostream & out,
    const Self_t & M ) [friend]

```

12.217.5 Field Documentation

12.217.5.1 recLevel

```

template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
int recLevel

```

12.217.5.2 FieldMin

```

template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
DFElt FieldMin

```

12.217.5.3 FieldMax

```

template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
DFElt FieldMax

```

12.217.5.4 Amin

```

template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
DFElt Amin

```

12.217.5.5 Amax

```

template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
DFElt Amax

```

12.217.5.6 Bmin

```

template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
DFElt Bmin

```

12.217.5.7 Bmax

```

template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
DFElt Bmax

```

12.217.5.8 Cmin

```

template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >
DFElt Cmin

```

12.217.5.9 Cmax

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >  
DFelt Cmax
```

12.217.5.10 Outmin

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >  
DFelt Outmin
```

12.217.5.11 Outmax

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >  
DFelt Outmax
```

12.217.5.12 MaxStorableValue

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >  
DFelt MaxStorableValue
```

12.217.5.13 delayedField

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >  
const DelayedField_t delayedField
```

12.217.5.14 parseq

```
template<class Field , typename AlgoTrait , typename ModeTrait , typename ParSeqTrait >  
ParSeqTrait parseq
```

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.218 MMHelper< FFPACK::RNSInteger< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait > Struct Template Reference

Public Types

- typedef [MMHelper](#)< [FFPACK::RNSInteger](#)< E >, [AlgoTrait](#), [ModeCategories::DefaultTag](#), [ParSeqTrait](#) > [Self_t](#)

Public Member Functions

- [MMHelper](#) ()
- [MMHelper](#) (Givaro::Integer Amax, Givaro::Integer Bmax)
- [MMHelper](#) (const [FFPACK::RNSInteger](#)< E > &F, size_t m, size_t n, size_t k, [ParSeqTrait](#) PS=[ParSeqTrait](#)())
- [MMHelper](#) (const [FFPACK::RNSInteger](#)< E > &F, int wino, [ParSeqTrait](#) PS=[ParSeqTrait](#)())
- template<class F2 , class A2 , class M2 , class PS2 >
 [MMHelper](#) ([MMHelper](#)< F2, A2, M2, PS2 > H2)
- void [setNorm](#) (Givaro::Integer p)

Data Fields

- Givaro::Integer [normA](#)
- Givaro::Integer [normB](#)
- int [recLevel](#)
- [ParSeqTrait](#) [parseq](#)

Friends

- `std::ostream & operator<< (std::ostream &out, const Self_t &M)`

12.218.1 Member Typedef Documentation

12.218.1.1 Self_t

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
typedef MMHelper<FFPACK::RNSInteger<E>, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait>
Self_t
```

12.218.2 Constructor & Destructor Documentation

12.218.2.1 MMHelper() [1/5]

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
MMHelper ( ) [inline]
```

12.218.2.2 MMHelper() [2/5]

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
MMHelper (
    Givaro::Integer Amax,
    Givaro::Integer Bmax ) [inline]
```

12.218.2.3 MMHelper() [3/5]

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
MMHelper (
    const FFPACK::RNSInteger< E > & F,
    size_t m,
    size_t n,
    size_t k,
    ParSeqTrait PS = ParSeqTrait() ) [inline]
```

12.218.2.4 MMHelper() [4/5]

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
MMHelper (
    const FFPACK::RNSInteger< E > & F,
    int wino,
    ParSeqTrait PS = ParSeqTrait() ) [inline]
```

12.218.2.5 MMHelper() [5/5]

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
template<class F2 , class A2 , class M2 , class PS2 >
MMHelper (
    MMHelper< F2, A2, M2, PS2 > H2 ) [inline]
```

12.218.3 Member Function Documentation

12.218.3.1 setNorm()

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
void setNorm (
    Givaro::Integer p ) [inline]
```

12.218.4 Friends And Related Symbol Documentation

12.218.4.1 operator<<

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
std::ostream & operator<< (
    std::ostream & out,
    const Self_t & M ) [friend]
```

12.218.5 Field Documentation

12.218.5.1 normA

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
Givaro::Integer normA
```

12.218.5.2 normB

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
Givaro::Integer normB
```

12.218.5.3 recLevel

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
int recLevel
```

12.218.5.4 parseq

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
ParSeqTrait parseq
```

The documentation for this struct was generated from the following file:

- [fgemm_classical_mp.inl](#)

12.219 MMHelper< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait > Struct Template Reference

Public Types

- typedef [MMHelper< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait > Self_t](#)

Public Member Functions

- [MMHelper](#) ()
- [MMHelper](#) (Givaro::Integer Amax, Givaro::Integer Bmax)
- [MMHelper](#) (const [FFPACK::RNSIntegerMod< E >](#) &F, size_t m, size_t n, size_t k, ParSeqTrait PS=ParSeqTrait())
- [MMHelper](#) (const [FFPACK::RNSIntegerMod< E >](#) &F, int wino, ParSeqTrait PS=ParSeqTrait())
- template<class F2 , typename AlgoT2 , typename FT2 , typename PS2 > [MMHelper](#) ([MMHelper](#)< F2, AlgoT2, FT2, PS2 > &WH)
- void [setNorm](#) (Givaro::Integer p)

Data Fields

- Givaro::Integer [normA](#)
- Givaro::Integer [normB](#)
- int [recLevel](#)
- ParSeqTrait [parseq](#)

Friends

- `std::ostream & operator<< (std::ostream &out, const Self_t &M)`

12.219.1 Member Typedef Documentation

12.219.1.1 Self_t

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
typedef MMHelper<FFPACK::RNSIntegerMod<E>, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait>
Self_t
```

12.219.2 Constructor & Destructor Documentation

12.219.2.1 MMHelper() [1/5]

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
MMHelper ( ) [inline]
```

12.219.2.2 MMHelper() [2/5]

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
MMHelper (
    Givaro::Integer Amax,
    Givaro::Integer Bmax ) [inline]
```

12.219.2.3 MMHelper() [3/5]

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
MMHelper (
    const FFPACK::RNSIntegerMod< E > & F,
    size_t m,
    size_t n,
    size_t k,
    ParSeqTrait PS = ParSeqTrait() ) [inline]
```

12.219.2.4 MMHelper() [4/5]

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
MMHelper (
    const FFPACK::RNSIntegerMod< E > & F,
    int wino,
    ParSeqTrait PS = ParSeqTrait() ) [inline]
```

12.219.2.5 MMHelper() [5/5]

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
template<class F2 , typename AlgoT2 , typename FT2 , typename PS2 >
MMHelper (
    MMHelper< F2, AlgoT2, FT2, PS2 > & WH ) [inline]
```

12.219.3 Member Function Documentation

12.219.3.1 setNorm()

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
void setNorm (
    Givaro::Integer p ) [inline]
```

12.219.4 Friends And Related Symbol Documentation

12.219.4.1 operator<<

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
std::ostream & operator<< (
    std::ostream & out,
    const Self_t & M ) [friend]
```

12.219.5 Field Documentation

12.219.5.1 normA

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
Givaro::Integer normA
```

12.219.5.2 normB

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
Givaro::Integer normB
```

12.219.5.3 recLevel

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
int recLevel
```

12.219.5.4 parseq

```
template<typename E , typename AlgoTrait , typename ParSeqTrait >
ParSeqTrait parseq
```

The documentation for this struct was generated from the following file:

- [fgemm_classical_mp.inl](#)

12.220 MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< Dest >, ParSeqTrait > Struct Template Reference

Public Types

- typedef MMHelper< [Field](#), AlgoTrait, [ModeCategories::ConvertTo< Dest >](#), ParSeqTrait > [Self_t](#)

Public Member Functions

- [MMHelper](#) ()
- [MMHelper](#) (const [Field](#) &F, size_t m, size_t k, size_t n, ParSeqTrait _PS)
- [MMHelper](#) (const [Field](#) &F, int w, ParSeqTrait _PS=ParSeqTrait())
- template<class F2 , typename AlgoT2 , typename FT2 , typename PS2 > [MMHelper](#) ([MMHelper](#)< F2, AlgoT2, FT2, PS2 > &WH)

Data Fields

- int [recLevel](#)
- ParSeqTrait [parseq](#)

Friends

- std::ostream & [operator<<](#) (std::ostream &out, const [Self_t](#) &M)

12.220.1 Member Typedef Documentation

12.220.1.1 Self_t

```
template<class Field , typename AlgoTrait , typename Dest , typename ParSeqTrait >
typedef MMHelper<Field,AlgoTrait, ModeCategories::ConvertTo<Dest>,ParSeqTrait> Self_t
```

12.220.2 Constructor & Destructor Documentation

12.220.2.1 MMHelper() [1/4]

```
template<class Field , typename AlgoTrait , typename Dest , typename ParSeqTrait >
MMHelper ( ) [inline]
```

12.220.2.2 MMHelper() [2/4]

```
template<class Field , typename AlgoTrait , typename Dest , typename ParSeqTrait >
MMHelper (
    const Field & F,
    size_t m,
    size_t k,
    size_t n,
    ParSeqTrait _PS ) [inline]
```

12.220.2.3 MMHelper() [3/4]

```
template<class Field , typename AlgoTrait , typename Dest , typename ParSeqTrait >
MMHelper (
    const Field & F,
    int w,
    ParSeqTrait _PS = ParSeqTrait() ) [inline]
```

12.220.2.4 MMHelper() [4/4]

```
template<class Field , typename AlgoTrait , typename Dest , typename ParSeqTrait >
template<class F2 , typename AlgoT2 , typename FT2 , typename PS2 >
MMHelper (
    MMHelper< F2, AlgoT2, FT2, PS2 > & WH ) [inline]
```

12.220.3 Friends And Related Symbol Documentation

12.220.3.1 operator<<

```
template<class Field , typename AlgoTrait , typename Dest , typename ParSeqTrait >
std::ostream & operator<< (
    std::ostream & out,
    const Self_t & M ) [friend]
```

12.220.4 Field Documentation

12.220.4.1 recLevel

```
template<class Field , typename AlgoTrait , typename Dest , typename ParSeqTrait >
int recLevel
```

12.220.4.2 parseq

```
template<class Field , typename AlgoTrait , typename Dest , typename ParSeqTrait >
ParSeqTrait parseq
```

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.221 MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeqTrait > Struct Template Reference

Public Types

- typedef [MMHelper](#)< [Field](#), [AlgoTrait](#), [ModeCategories::ConvertTo](#)< [ElementCategories::RNSElementTag](#) >, [ParSeqTrait](#) > [Self_t](#)

Public Member Functions

- [MMHelper](#) ()
- template<class F2 , class A2 , class M2 , class PS2 >
[MMHelper](#) ([MMHelper](#)< F2, A2, M2, PS2 > H2)
- [MMHelper](#) (Givaro::Integer Amax, Givaro::Integer Bmax)
- [MMHelper](#) (const [Field](#) &F, size_t m, size_t n, size_t k, ParSeqTrait PS=ParSeqTrait())
- [MMHelper](#) (const [Field](#) &F, int wino, ParSeqTrait PS=ParSeqTrait())
- void [setNorm](#) (Givaro::Integer p)

Data Fields

- Givaro::Integer [normA](#)
- Givaro::Integer [normB](#)
- int [recLevel](#)
- ParSeqTrait [parseq](#)

Friends

- std::ostream & [operator<<](#) (std::ostream &out, const [Self_t](#) &M)

12.221.1 Member Typedef Documentation

12.221.1.1 Self_t

```
template<typename Field , typename AlgoTrait , typename ParSeqTrait >
typedef MMHelper<Field, AlgoTrait,ModeCategories::ConvertTo<ElementCategories::RNSElementTag>,
ParSeqTrait> Self\_t
```

12.221.2 Constructor & Destructor Documentation

12.221.2.1 MMHelper() [1/5]

```
template<typename Field , typename AlgoTrait , typename ParSeqTrait >
MMHelper ( ) [inline]
```

12.221.2.2 MMHelper() [2/5]

```
template<typename Field , typename AlgoTrait , typename ParSeqTrait >
template<class F2 , class A2 , class M2 , class PS2 >
MMHelper (
    MMHelper< F2, A2, M2, PS2 > H2 ) [inline]
```

12.221.2.3 MMHelper() [3/5]

```
template<typename Field , typename AlgoTrait , typename ParSeqTrait >
MMHelper (
    Givaro::Integer Amax,
    Givaro::Integer Bmax ) [inline]
```

12.221.2.4 MMHelper() [4/5]

```
template<typename Field , typename AlgoTrait , typename ParSeqTrait >
MMHelper (
    const Field & F,
    size_t m,
    size_t n,
    size_t k,
    ParSeqTrait PS = ParSeqTrait() ) [inline]
```

12.221.2.5 MMHelper() [5/5]

```
template<typename Field , typename AlgoTrait , typename ParSeqTrait >
MMHelper (
    const Field & F,
    int wino,
    ParSeqTrait PS = ParSeqTrait() ) [inline]
```

12.221.3 Member Function Documentation**12.221.3.1 setNorm()**

```
template<typename Field , typename AlgoTrait , typename ParSeqTrait >
void setNorm (
    Givaro::Integer p ) [inline]
```

12.221.4 Friends And Related Symbol Documentation**12.221.4.1 operator<<**

```
template<typename Field , typename AlgoTrait , typename ParSeqTrait >
std::ostream & operator<< (
    std::ostream & out,
    const Self_t & M ) [friend]
```

12.221.5 Field Documentation**12.221.5.1 normA**

```
template<typename Field , typename AlgoTrait , typename ParSeqTrait >
Givaro::Integer normA
```

12.221.5.2 normB

```
template<typename Field , typename AlgoTrait , typename ParSeqTrait >
Givaro::Integer normB
```

12.221.5.3 recLevel

```
template<typename Field , typename AlgoTrait , typename ParSeqTrait >
int recLevel
```

12.221.5.4 parseq

```
template<typename Field , typename AlgoTrait , typename ParSeqTrait >
ParSeqTrait parseq
```

The documentation for this struct was generated from the following file:

- [fgemm_classical_mp.inl](#)

12.222 MMHelper< Field, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait > Struct Template Reference

FGEMM Helper for Default and ConvertTo modes of operation.

Public Types

- typedef [MMHelper](#)< [Field](#), [AlgoTrait](#), [ModeCategories::DefaultTag](#), [ParSeqTrait](#) > [Self_t](#)

Public Member Functions

- [MMHelper](#) ()
- [MMHelper](#) (const [Field](#) &F, size_t m, size_t k, size_t n, [ParSeqTrait](#) _PS)
- [MMHelper](#) (const [Field](#) &F, int w, [ParSeqTrait](#) _PS=[ParSeqTrait](#)())
- template<class F2 , typename AlgoT2 , typename FT2 , typename PS2 >
[MMHelper](#) ([MMHelper](#)< F2, AlgoT2, FT2, PS2 > &WH)

Data Fields

- int [recLevel](#)
- [ParSeqTrait](#) [parseq](#)

Friends

- std::ostream & [operator](#)<< (std::ostream &out, const [Self_t](#) &M)

12.222.1 Detailed Description

```
template<class Field, typename AlgoTrait, typename ParSeqTrait>
struct FFLAS::MMHelper< Field, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >
```

FGEMM Helper for Default and ConvertTo modes of operation.

12.222.2 Member Typedef Documentation

12.222.2.1 Self_t

```
template<class Field , typename AlgoTrait , typename ParSeqTrait >
typedef MMHelper<Field,AlgoTrait, ModeCategories::DefaultTag,ParSeqTrait> Self\_t
```

12.222.3 Constructor & Destructor Documentation

12.222.3.1 MMHelper() [1/4]

```
template<class Field , typename AlgoTrait , typename ParSeqTrait >
MMHelper ( ) [inline]
```

12.222.3.2 MMHelper() [2/4]

```
template<class Field , typename AlgoTrait , typename ParSeqTrait >
MMHelper (
    const Field & F,
    size_t m,
    size_t k,
    size_t n,
    ParSeqTrait _PS ) [inline]
```

12.222.3.3 MMHelper() [3/4]

```
template<class Field , typename AlgoTrait , typename ParSeqTrait >
MMHelper (
    const Field & F,
    int w,
    ParSeqTrait _PS = ParSeqTrait() ) [inline]
```

12.222.3.4 MMHelper() [4/4]

```
template<class Field , typename AlgoTrait , typename ParSeqTrait >
template<class F2 , typename AlgoT2 , typename FT2 , typename PS2 >
MMHelper (
    MMHelper< F2, AlgoT2, FT2, PS2 > & WH ) [inline]
```

12.222.4 Friends And Related Symbol Documentation**12.222.4.1 operator<<**

```
template<class Field , typename AlgoTrait , typename ParSeqTrait >
std::ostream & operator<< (
    std::ostream & out,
    const Self_t & M ) [friend]
```

12.222.5 Field Documentation**12.222.5.1 recLevel**

```
template<class Field , typename AlgoTrait , typename ParSeqTrait >
int recLevel
```

12.222.5.2 parseq

```
template<class Field , typename AlgoTrait , typename ParSeqTrait >
ParSeqTrait parseq
```

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.223 ModeTraits< Field > Struct Template Reference

[ModeTraits.](#)

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::DefaultTag](#) value

12.223.1 Detailed Description

```
template<class Field>
struct FFLAS::ModeTraits< Field >
```

[ModeTraits.](#)

12.223.2 Member Typedef Documentation**12.223.2.1 value**

```
template<class Field >
typedef ModeCategories::DefaultTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.224 ModeTraits< Givaro::Modular< Element, Compute > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::DelayedTag](#) value

12.224.1 Member Typedef Documentation

12.224.1.1 value

```
template<typename Element , typename Compute >
typedef ModeCategories::DelayedTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.225 ModeTraits< Givaro::Modular< Givaro::Integer, Compute > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::ConvertTo< ElementCategories::RNSElementTag >](#) value

12.225.1 Member Typedef Documentation

12.225.1.1 value

```
template<typename Compute >
typedef ModeCategories::ConvertTo<ElementCategories::RNSElementTag> value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.226 ModeTraits< Givaro::Modular< int16_t, Compute > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::ConvertTo< ElementCategories::MachineFloatTag >](#) value

12.226.1 Member Typedef Documentation

12.226.1.1 value

```
template<typename Compute >
typedef ModeCategories::ConvertTo<ElementCategories::MachineFloatTag> value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.227 ModeTraits< Givaro::Modular< int32_t, Compute > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::ConvertTo< ElementCategories::MachineFloatTag > value](#)

12.227.1 Member Typedef Documentation

12.227.1.1 value

```
template<typename Compute >
```

```
typedef ModeCategories::ConvertTo<ElementCategories::MachineFloatTag> value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.228 ModeTraits< Givaro::Modular< int64_t, uint64_t > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::DefaultTag value](#)

12.228.1 Member Typedef Documentation

12.228.1.1 value

```
typedef ModeCategories::DefaultTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.229 ModeTraits< Givaro::Modular< int8_t, Compute > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::ConvertTo< ElementCategories::MachineFloatTag > value](#)

12.229.1 Member Typedef Documentation

12.229.1.1 value

```
template<typename Compute >
```

```
typedef ModeCategories::ConvertTo<ElementCategories::MachineFloatTag> value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.230 ModeTraits< Givaro::Modular< RecInt::ruint< K >, Compute > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::ConvertTo< ElementCategories::RNSElementTag > value](#)

12.230.1 Member Typedef Documentation

12.230.1.1 value

```
template<typename Compute , size_t K>
```

```
typedef ModeCategories::ConvertTo<ElementCategories::RNSElementTag> value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.231 ModeTraits< Givaro::Modular< uint16_t, Compute > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::ConvertTo< ElementCategories::MachineFloatTag > value](#)

12.231.1 Member Typedef Documentation

12.231.1.1 value

```
template<typename Compute >
```

```
typedef ModeCategories::ConvertTo<ElementCategories::MachineFloatTag> value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.232 ModeTraits< Givaro::Modular< uint32_t, Compute > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::ConvertTo< ElementCategories::MachineFloatTag > value](#)

12.232.1 Member Typedef Documentation

12.232.1.1 value

```
template<typename Compute >
```

```
typedef ModeCategories::ConvertTo<ElementCategories::MachineFloatTag> value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.233 ModeTraits< Givaro::Modular< uint8_t, Compute > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::ConvertTo< ElementCategories::MachineFloatTag > value](#)

12.233.1 Member Typedef Documentation

12.233.1.1 value

```
template<typename Compute >
```

```
typedef ModeCategories::ConvertTo<ElementCategories::MachineFloatTag> value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.234 ModeTraits< Givaro::ModularBalanced< Element > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::DelayedTag value](#)

12.234.1 Member Typedef Documentation

12.234.1.1 value

```
template<typename Element >
```

```
typedef ModeCategories::DelayedTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.235 ModeTraits< Givaro::ModularBalanced< Givaro::Integer > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::ConvertTo< ElementCategories::RNSElementTag > value](#)

12.235.1 Member Typedef Documentation

12.235.1.1 value

```
typedef ModeCategories::ConvertTo<ElementCategories::RNSElementTag> value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.236 ModeTraits< Givaro::ModularBalanced< int16_t > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::ConvertTo< ElementCategories::MachineFloatTag > value](#)

12.236.1 Member Typedef Documentation

12.236.1.1 value

```
typedef ModeCategories::ConvertTo<ElementCategories::MachineFloatTag> value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.237 ModeTraits< Givaro::ModularBalanced< int32_t > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::ConvertTo< ElementCategories::MachineFloatTag > value](#)

12.237.1 Member Typedef Documentation

12.237.1.1 value

```
typedef ModeCategories::ConvertTo<ElementCategories::MachineFloatTag> value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.238 ModeTraits< Givaro::ModularBalanced< int8_t > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::ConvertTo< ElementCategories::MachineFloatTag > value](#)

12.238.1 Member Typedef Documentation

12.238.1.1 value

```
typedef ModeCategories::ConvertTo<ElementCategories::MachineFloatTag> value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.239 ModeTraits< Givaro::Montgomery< T > > Struct Template Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::DefaultBoundedTag](#) value

12.239.1 Member Typedef Documentation**12.239.1.1 value**

```
template<class T >
```

```
typedef ModeCategories::DefaultBoundedTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.240 ModeTraits< Givaro::ZRing< double > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::DefaultBoundedTag](#) value

12.240.1 Member Typedef Documentation**12.240.1.1 value**

```
typedef ModeCategories::DefaultBoundedTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.241 ModeTraits< Givaro::ZRing< float > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::DefaultBoundedTag](#) value

12.241.1 Member Typedef Documentation**12.241.1.1 value**

```
typedef ModeCategories::DefaultBoundedTag value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.242 ModeTraits< Givaro::ZRing< Givaro::Integer > > Struct Reference

```
#include <field-traits.h>
```

Public Types

- typedef [ModeCategories::ConvertTo< ElementCategories::RNSElementTag >](#) value

12.242.1 Member Typedef Documentation

12.242.1.1 value

```
typedef ModeCategories::ConvertTo<ElementCategories::RNSElementTag> value
```

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.243 ModularBalanced< T > Class Template Reference

The documentation for this class was generated from the following file:

- [field-traits.h](#)

12.244 ModularTag Struct Reference

This is a modular field like e.g. Modular<T> or ModularBalanced<T>
`#include <field-traits.h>`

12.244.1 Detailed Description

This is a modular field like e.g. Modular<T> or ModularBalanced<T>
 The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.245 Montgomery< T > Class Template Reference

The documentation for this class was generated from the following file:

- [field-traits.h](#)

12.246 need_field_characteristic< Field > Struct Template Reference

Static Public Attributes

- static constexpr bool [value](#) = false

12.246.1 Field Documentation

12.246.1.1 value

```
template<typename Field >
constexpr bool value = false [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [benchmark-fgemv.C](#)

12.247 need_field_characteristic< Givaro::Modular< Field > > Struct Template Reference

Static Public Attributes

- static constexpr bool [value](#) = true

12.247.1 Field Documentation

12.247.1.1 value

```
template<typename Field >
constexpr bool value = true [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [benchmark-fgemv.C](#)

12.248 need_field_characteristic< Givaro::ModularBalanced< Field > > Struct Template Reference

Static Public Attributes

- static constexpr bool [value](#) = true

12.248.1 Field Documentation

12.248.1.1 value

```
template<typename Field >
constexpr bool value = true [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [benchmark-fgemv.C](#)

12.249 NoSimd< T > Struct Template Reference

```
#include <fflas_simd.h>
```

Public Types

- using [vect_t](#) = T *
- using [scalar_t](#) = T
- using [aligned_allocator](#) = AlignedAllocator< [scalar_t](#), Alignment([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >
- template<class [Field](#) >
using [is_same_element](#) = std::is_same< typename [Field::Element](#), T >

Static Public Member Functions

- static const std::string [type_string](#) ()
- template<class TT >
static constexpr bool [valid](#) (TT p)
- template<class TT >
static constexpr bool [compliant](#) (TT n)

Static Public Attributes

- static const constexpr size_t [vect_size](#) = 1
- static const constexpr size_t [alignment](#) = static_cast<size_t>(Alignment::Normal)

12.249.1 Member Typedef Documentation

12.249.1.1 vect_t

```
template<typename T >
using vect\_t = T*
```

12.249.1.2 scalar_t

```
template<typename T >
using scalar_t = T
```

12.249.1.3 aligned_allocator

```
template<typename T >
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.249.1.4 aligned_vector

```
template<typename T >
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.249.1.5 is_same_element

```
template<typename T >
template<class Field >
using is_same_element = std::is_same<typename Field::Element, T>
```

12.249.2 Member Function Documentation**12.249.2.1 type_string()**

```
template<typename T >
static const std::string type_string ( ) [inline], [static]
```

12.249.2.2 valid()

```
template<typename T >
template<class TT >
static constexpr bool valid (
    TT p ) [inline], [static], [constexpr]
```

12.249.2.3 compliant()

```
template<typename T >
template<class TT >
static constexpr bool compliant (
    TT n ) [inline], [static], [constexpr]
```

12.249.3 Field Documentation**12.249.3.1 vect_size**

```
template<typename T >
const constexpr size_t vect_size = 1 [static], [constexpr]
```

12.249.3.2 alignment

```
template<typename T >
const constexpr size_t alignment = static_cast<size_t>(Alignment::Normal) [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [fflas_simd.h](#)

12.250 Parallel< C, P > Struct Template Reference

Public Types

- typedef C [Cut](#)
- typedef P [Param](#)

Public Member Functions

- [Parallel](#) (size_t n=NUM_THREADS)
- size_t [numthreads](#) () const
- size_t & [set_numthreads](#) (size_t n)

Friends

- std::ostream & [operator<<](#) (std::ostream &out, const [Parallel](#) &p)

12.250.1 Member Typedef Documentation

12.250.1.1 Cut

```
template<typename C = CuttingStrategy::Block, typename P = StrategyParameter::Threads>
typedef C Cut
```

12.250.1.2 Param

```
template<typename C = CuttingStrategy::Block, typename P = StrategyParameter::Threads>
typedef P Param
```

12.250.2 Constructor & Destructor Documentation

12.250.2.1 Parallel()

```
template<typename C = CuttingStrategy::Block, typename P = StrategyParameter::Threads>
Parallel (
    size_t n = NUM\_THREADS ) [inline]
```

12.250.3 Member Function Documentation

12.250.3.1 numthreads()

```
template<typename C = CuttingStrategy::Block, typename P = StrategyParameter::Threads>
size_t numthreads ( ) const [inline]
```

12.250.3.2 set_numthreads()

```
template<typename C = CuttingStrategy::Block, typename P = StrategyParameter::Threads>
size_t & set_numthreads (
    size_t n ) [inline]
```

12.250.4 Friends And Related Symbol Documentation

12.250.4.1 operator<<

```
template<typename C = CuttingStrategy::Block, typename P = StrategyParameter::Threads>
std::ostream & operator<< (
    std::ostream & out,
    const Parallel< C, P > & p ) [friend]
```


The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.251 RNSInteger< RNS >::RandIter Class Reference

#include <rns-integer.h>

Inheritance diagram for RNSInteger< RNS >::RandIter:



Public Member Functions

- [RandIter](#) (const [RNSInteger< RNS >](#) &F, uint64_t seed=0)
- [RNS::Element](#) & [random](#) (typename [RNS::Element](#) &elt) const
RNS ring Element random assignment.
- [RNS::Element](#) [random](#) () const
- [RNS::Element](#) & [operator\(\)](#) (typename [RNS::Element](#) &elt) const
- [RNS::Element](#) [operator\(\)](#) () const
- const [RNS](#) & [ring](#) () const

12.251.1 Constructor & Destructor Documentation

12.251.1.1 RandIter()

```

template<typename RNS >
RandIter (
    const RNSInteger< RNS > & F,
    uint64_t seed = 0 ) [inline]
  
```

12.251.2 Member Function Documentation

12.251.2.1 random() [1/2]

```

template<typename RNS >
RNS::Element & random (
    typename RNS::Element & elt ) const [inline], [inherited]
  
```

RNS ring Element random assignment.

Element is supposed to be initialized

Returns

random ring Element

12.251.2.2 random() [2/2]

```

template<typename RNS >
RNS::Element random ( ) const [inline], [inherited]
  
```

12.251.2.3 operator>() [1/2]

```

template<typename RNS >
RNS::Element & operator() (
    typename RNS::Element & elt ) const [inline], [inherited]
  
```

12.251.2.4 operator>() [2/2]

```

template<typename RNS >
RNS::Element operator() ( ) const [inline], [inherited]
  
```

12.251.2.5 ring()


```
template<typename RNS >
const RNS & ring ( ) const [inline], [inherited]
```

The documentation for this class was generated from the following file:

- [rns-integer.h](#)

12.252 RNSIntegerMod< RNS >::RandIter Class Reference

```
#include <rns-integer-mod.h>
Inheritance diagram for RNSIntegerMod< RNS >::RandIter:
```



Public Member Functions

- [RandIter](#) (const [RNSIntegerMod< RNS >](#) &F, uint64_t seed=0)
- [RNS::Element](#) & [random](#) (typename [RNS::Element](#) &elt) const
- [RNS::Element](#) [random](#) () const
- [RNS::Element](#) & [operator\(\)](#) (typename [RNS::Element](#) &elt) const
- [RNS::Element](#) [operator\(\)](#) () const
- const [RNS](#) & [ring](#) () const

12.252.1 Constructor & Destructor Documentation

12.252.1.1 RandIter()

```
template<typename RNS >
RandIter (
    const RNSIntegerMod< RNS > & F,
    uint64_t seed = 0 ) [inline]
```

12.252.2 Member Function Documentation

12.252.2.1 random() [1/2]

```
template<typename RNS >
RNS::Element & random (
    typename RNS::Element & elt ) const [inline]
```

12.252.2.2 random() [2/2]

```
template<typename RNS >
RNS::Element random ( ) const [inline], [inherited]
```

12.252.2.3 operator>() [1/2]

```
template<typename RNS >
RNS::Element & operator() (
    typename RNS::Element & elt ) const [inline], [inherited]
```

12.252.2.4 operator>() [2/2]

```
template<typename RNS >
RNS::Element operator() ( ) const [inline], [inherited]
```


12.252.2.5 ring()

```
template<typename RNS >
const RNS & ring ( ) const [inline], [inherited]
```

The documentation for this class was generated from the following file:

- [rns-integer-mod.h](#)

12.253 readMyMachineType< Field, T > Struct Template Reference

```
#include <read_sparse.h>
```

Public Types

- typedef [Field::Element](#) [Element](#)
- typedef [Field::Element_ptr](#) [Element_ptr](#)

Public Member Functions

- void [operator\(\)](#) (const [Field](#) &F, [Element](#) &modulo, [Element_ptr](#) val, std::ifstream &file, const uint64_t dims, const [mask_t](#) data_type, const [mask_t](#) field_desc)

12.253.1 Member Typedef Documentation

12.253.1.1 Element

```
template<class Field , class T >
typedef Field::Element Element
```

12.253.1.2 Element_ptr

```
template<class Field , class T >
typedef Field::Element_ptr Element_ptr
```

12.253.2 Member Function Documentation

12.253.2.1 operator>()

```
template<class Field , typename T >
void operator() (
    const Field & F,
    Element & modulo,
    Element_ptr val,
    std::ifstream & file,
    const uint64_t dims,
    const mask_t data_type,
    const mask_t field_desc )
```

The documentation for this struct was generated from the following file:

- [read_sparse.h](#)

12.254 readMyMachineType< Field, mpz_t > Struct Template Reference

```
#include <read_sparse.h>
```

Public Types

- typedef [Field::Element](#) [Element](#)
- typedef [Field::Element_ptr](#) [Element_ptr](#)

Public Member Functions

- void [operator\(\)](#) (const [Field](#) &F, [Element](#) &modulo, [Element_ptr](#) val, std::ifstream &file, const uint64_t dims, const [mask_t](#) data_type, const [mask_t](#) field_desc)

12.254.1 Member Typedef Documentation

12.254.1.1 Element

```
template<class Field >
typedef Field::Element Element
```

12.254.1.2 Element_ptr

```
template<class Field >
typedef Field::Element\_ptr Element\_ptr
```

12.254.2 Member Function Documentation

12.254.2.1 operator>()

```
template<class Field >
void operator() (
    const Field & F,
    typename Field::Element & modulo,
    typename Field::Element\_ptr val,
    std::ifstream & file,
    const uint64_t dims,
    const mask\_t data_type,
    const mask\_t field_desc )
```

The documentation for this struct was generated from the following file:

- [read_sparse.h](#)

12.255 Recursive Struct Reference

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.256 Recursive Struct Reference

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.257 rint< K > Class Template Reference

The documentation for this class was generated from the following file:

- [field-traits.h](#)

12.258 rns_double Struct Reference

```
#include <rns-double.h>
```

Public Types

- typedef Givaro::Integer [integer](#)
- typedef Givaro::Modular< double > [ModField](#)
- typedef double [BasisElement](#)
- typedef [rns_double_elt](#) [Element](#)
- typedef [rns_double_elt_ptr](#) [Element_ptr](#)
- typedef [rns_double_elt_cstptr](#) [ConstElement_ptr](#)

Public Member Functions

- [rns_double](#) (const [integer](#) &bound, size_t pbits, bool rnsmod=false, long seed=time(NULL))
- [rns_double](#) (size_t pbits, size_t size, long seed=time(NULL))
- template<typename Vect >
 [rns_double](#) (const Vect &basis, bool rnsmod=false, long seed=time(NULL))
- [rns_double](#) (const [RNSIntegerMod](#)< [rns_double](#) > &basis, bool rnsmod=false, long seed=time(NULL))
- void [precompute_cst](#) (size_t K=0)
- template<typename T >
 void [init](#) (size_t m, size_t n, double *Arns, size_t rda, const T *A, size_t lda, const [integer](#) &maxA, bool RNS_MAJOR=false) const
- void [init](#) (size_t m, size_t n, double *Arns, size_t rda, const [integer](#) *A, size_t lda, size_t k, bool RNS_MAJOR=false) const
- void [init_transpose](#) (size_t m, size_t n, double *Arns, size_t rda, const [integer](#) *A, size_t lda, size_t k, bool RNS_MAJOR=false) const
- void [convert](#) (size_t m, size_t n, [integer](#) gamma, [integer](#) *A, size_t lda, const double *Arns, size_t rda, bool RNS_MAJOR=false) const
- void [convert_transpose](#) (size_t m, size_t n, [integer](#) gamma, [integer](#) *A, size_t lda, const double *Arns, size_t rda, bool RNS_MAJOR=false) const
- void [reduce](#) (size_t n, double *Arns, size_t rda, bool RNS_MAJOR=false) const
- template<size_t K>
 void [init](#) (size_t m, size_t n, double *Arns, size_t rda, const [Reclnt::ruint](#)< K > *A, size_t lda, size_t k, bool RNS_MAJOR=false) const
- template<size_t K>
 void [convert](#) (size_t m, size_t n, [integer](#) gamma, [Reclnt::ruint](#)< K > *A, size_t lda, const double *Arns, size_t rda, [integer](#) p=0, bool RNS_MAJOR=false) const

Data Fields

- std::vector< double, AlignedAllocator< double, Alignment::CACHE_LINE > > [_basis](#)
- std::vector< double, AlignedAllocator< double, Alignment::CACHE_LINE > > [_basisMax](#)
- std::vector< double, AlignedAllocator< double, Alignment::CACHE_LINE > > [_negbasis](#)
- std::vector< double, AlignedAllocator< double, Alignment::CACHE_LINE > > [_invbasis](#)
- std::vector< [ModField](#) > [_field_rns](#)
- [integer](#) [_M](#)
- std::vector< [integer](#) > [_Mi](#)
- std::vector< double > [_MMi](#)
- std::vector< double > [_crt_in](#)
- std::vector< double > [_crt_out](#)
- size_t [_size](#)
- size_t [_pbits](#)
- size_t [_ldm](#)
- [integer](#) [_mi_sum](#)

12.258.1 Member Typedef Documentation

12.258.1.1 integer

```
typedef Givaro::Integer integer
```

12.258.1.2 ModField

```
typedef Givaro::Modular<double> ModField
```

12.258.1.3 BasisElement

```
typedef double BasisElement
```

12.258.1.4 Element

```
typedef rns_double_elt Element
```

12.258.1.5 Element_ptr

```
typedef rns_double_elt_ptr Element_ptr
```

12.258.1.6 ConstElement_ptr

```
typedef rns_double_elt_cstptr ConstElement_ptr
```

12.258.2 Constructor & Destructor Documentation**12.258.2.1 rns_double() [1/4]**

```
rns_double (
    const integer & bound,
    size_t pbits,
    bool rnsmod = false,
    long seed = time(NULL) ) [inline]
```

12.258.2.2 rns_double() [2/4]

```
rns_double (
    size_t pbits,
    size_t size,
    long seed = time(NULL) ) [inline]
```

12.258.2.3 rns_double() [3/4]

```
template<typename Vect >
rns_double (
    const Vect & basis,
    bool rnsmod = false,
    long seed = time(NULL) ) [inline]
```

12.258.2.4 rns_double() [4/4]

```
rns_double (
    const RNSIntegerMod< rns_double > & basis,
    bool rnsmod = false,
    long seed = time(NULL) ) [inline]
```

12.258.3 Member Function Documentation**12.258.3.1 precompute_cst()**

```
void precompute_cst (
    size_t K = 0 ) [inline]
```

12.258.3.2 init() [1/3]

```
template<typename T >
void init (
    size_t m,
    size_t n,
    double * Arns,
    size_t rda,
    const T * A,
    size_t lda,
    const integer & maxA,
    bool RNS_MAJOR = false ) const [inline]
```

12.258.3.3 init() [2/3]

```
void init (
    size_t m,
    size_t n,
    double * Arns,
    size_t rda,
    const integer * A,
    size_t lda,
    size_t k,
    bool RNS_MAJOR = false ) const [inline]
```

12.258.3.4 init_transpose()

```
void init_transpose (
    size_t m,
    size_t n,
    double * Arns,
    size_t rda,
    const integer * A,
    size_t lda,
    size_t k,
    bool RNS_MAJOR = false ) const [inline]
```

12.258.3.5 convert() [1/2]

```
void convert (
    size_t m,
    size_t n,
    integer gamma,
    integer * A,
    size_t lda,
    const double * Arns,
    size_t rda,
    bool RNS_MAJOR = false ) const [inline]
```

12.258.3.6 convert_transpose()

```
void convert_transpose (
    size_t m,
    size_t n,
    integer gamma,
    integer * A,
    size_t lda,
    const double * Arns,
    size_t rda,
    bool RNS_MAJOR = false ) const [inline]
```

12.258.3.7 reduce()

```
void reduce (
    size_t n,
    double * Arns,
    size_t rda,
    bool RNS_MAJOR = false ) const [inline]
```

12.258.3.8 init() [3/3]

```
template<size_t K>
void init (
    size_t m,
    size_t n,
    double * Arns,
    size_t rda,
    const RecInt::ruint< K > * A,
    size_t lda,
    size_t k,
    bool RNS_MAJOR = false ) const [inline]
```

12.258.3.9 convert() [2/2]

```
template<size_t K>
void convert (
    size_t m,
    size_t n,
    integer gamma,
    RecInt::ruint< K > * A,
    size_t lda,
    const double * Arns,
    size_t rda,
    integer p = 0,
    bool RNS_MAJOR = false ) const [inline]
```

12.258.4 Field Documentation**12.258.4.1 _basis**

```
std::vector<double, AlignedAllocator<double, Alignment::CACHE_LINE> > _basis
```

12.258.4.2 _basisMax

```
std::vector<double, AlignedAllocator<double, Alignment::CACHE_LINE> > _basisMax
```

12.258.4.3 _negbasis

```
std::vector<double, AlignedAllocator<double, Alignment::CACHE_LINE> > _negbasis
```

12.258.4.4 _invbasis

```
std::vector<double, AlignedAllocator<double, Alignment::CACHE_LINE> > _invbasis
```

12.258.4.5 _field_rns

```
std::vector<ModField> _field_rns
```

12.258.4.6 _M

```
integer _M
```

12.258.4.7 _Mi

```
std::vector<integer> _Mi
```

12.258.4.8 _MMi

```
std::vector<double> _MMi
```

12.258.4.9 _crt_in

```
std::vector<double> _crt_in
```

12.258.4.10 _crt_out

```
std::vector<double> _crt_out
```

12.258.4.11 _size

```
size_t _size
```

12.258.4.12 _pbits

```
size_t _pbits
```

12.258.4.13 _ldm

```
size_t _ldm
```

12.258.4.14 _mi_sum

```
integer _mi_sum
```


The documentation for this struct was generated from the following files:

- [rns-double.h](#)
- [rns-double-recint.inl](#)
- [rns-double.inl](#)

12.259 rns_double_elt Struct Reference

```
#include <rns-double-elt.h>
```

Inheritance diagram for rns_double_elt:

**Public Member Functions**

- [rns_double_elt](#) ()
- [~rns_double_elt](#) ()
- [rns_double_elt](#) (double *p, size_t r, size_t a=false)
- [rns_double_elt_ptr](#) operator& ()
- [rns_double_elt_cstptr](#) operator& () const
- [rns_double_elt](#) (const [rns_double_elt](#) &x)

Data Fields

- [double * _ptr](#)
- [size_t _stride](#)
- [bool _alloc](#)

12.259.1 Constructor & Destructor Documentation**12.259.1.1 `rns_double_elt()` [1/3]**

```
rns_double_elt ( ) [inline]
```

12.259.1.2 `~rns_double_elt()`

```
~rns_double_elt ( ) [inline]
```

12.259.1.3 `rns_double_elt()` [2/3]

```
rns_double_elt (
    double * p,
    size_t r,
    size_t a = false ) [inline]
```

12.259.1.4 `rns_double_elt()` [3/3]

```
rns_double_elt (
    const rns_double_elt & x ) [inline]
```

12.259.2 Member Function Documentation**12.259.2.1 `operator&()` [1/2]**

```
rns_double_elt_ptr operator& ( ) [inline]
```

12.259.2.2 `operator&()` [2/2]

```
rns_double_elt_cstptr operator& ( ) const [inline]
```

12.259.3 Field Documentation**12.259.3.1 `_ptr`**

```
double* _ptr
```

12.259.3.2 `_stride`

```
size_t _stride
```

12.259.3.3 `_alloc`

```
bool _alloc
```


The documentation for this struct was generated from the following file:

- [rns-double-elt.h](#)

12.260 rns_double_elt_cstptr Struct Reference

```
#include <rns-double-elt.h>
```

Inheritance diagram for rns_double_elt_cstptr:



Public Member Functions

- [rns_double_elt_cstptr](#) ()
- [rns_double_elt_cstptr](#) (double *p, size_t r)
- [rns_double_elt_cstptr](#) (const [rns_double_elt_ptr](#) &x)
- [rns_double_elt_cstptr](#) (const [rns_double_elt_cstptr](#) &x)
- [rns_double_elt_cstptr](#) ([rns_double_elt_cstptr](#) &&)=default
- [rns_double_elt_cstptr * operator&](#) ()
- [rns_double_elt & operator*](#) () const
- [rns_double_elt operator\[\]](#) (size_t i) const
- [rns_double_elt & operator\[\]](#) (size_t i)
- [rns_double_elt_cstptr operator++](#) ()
- [rns_double_elt_cstptr operator--](#) ()
- [rns_double_elt_cstptr operator+](#) (size_t inc) const
- [rns_double_elt_cstptr operator-](#) (size_t inc) const
- [rns_double_elt_cstptr & operator+=](#) (size_t inc)
- [rns_double_elt_cstptr & operator-=](#) (size_t inc)
- [rns_double_elt_cstptr & operator=](#) (const [rns_double_elt_cstptr](#) &x)
- [bool operator<](#) (const [rns_double_elt_cstptr](#) &x)
- [bool operator!=](#) (const [rns_double_elt_cstptr](#) &x)
- [rns_double_elt_cstptr operator&](#) () const

Data Fields

- [rns_double_elt other](#)
- [double * _ptr](#)
- [size_t _stride](#)
- [bool _alloc](#)

12.260.1 Constructor & Destructor Documentation

12.260.1.1 rns_double_elt_cstptr() [1/5]

```
rns\_double\_elt\_cstptr ( ) [inline]
```

12.260.1.2 rns_double_elt_cstptr() [2/5]

```
rns\_double\_elt\_cstptr (
    double * p,
    size_t r ) [inline]
```

12.260.1.3 rns_double_elt_cstptr() [3/5]

```
rns\_double\_elt\_cstptr (
    const rns\_double\_elt\_ptr & x ) [inline]
```

12.260.1.4 rns_double_elt_cstptr() [4/5]

```
rns_double_elt_cstptr (
    const rns_double_elt_cstptr & x ) [inline]
```

12.260.1.5 rns_double_elt_cstptr() [5/5]

```
rns_double_elt_cstptr (
    rns_double_elt_cstptr && ) [default]
```

12.260.2 Member Function Documentation**12.260.2.1 operator&()** [1/2]

```
rns_double_elt_cstptr * operator& ( ) [inline]
```

12.260.2.2 operator*()

```
rns_double_elt & operator* ( ) const [inline]
```

12.260.2.3 operator[]() [1/2]

```
rns_double_elt operator[] (
    size_t i ) const [inline]
```

12.260.2.4 operator[]() [2/2]

```
rns_double_elt & operator[] (
    size_t i ) [inline]
```

12.260.2.5 operator++()

```
rns_double_elt_cstptr operator++ ( ) [inline]
```

12.260.2.6 operator--()

```
rns_double_elt_cstptr operator-- ( ) [inline]
```

12.260.2.7 operator+()

```
rns_double_elt_cstptr operator+ (
    size_t inc ) const [inline]
```

12.260.2.8 operator-()

```
rns_double_elt_cstptr operator- (
    size_t inc ) const [inline]
```

12.260.2.9 operator+=()

```
rns_double_elt_cstptr & operator+= (
    size_t inc ) [inline]
```

12.260.2.10 operator-=()

```
rns_double_elt_cstptr & operator-= (
    size_t inc ) [inline]
```

12.260.2.11 operator=()

```
rns_double_elt_cstptr & operator= (
    const rns_double_elt_cstptr & x ) [inline]
```

12.260.2.12 operator<()

```
bool operator< (
    const rns_double_elt_cstptr & x ) [inline]
```

12.260.2.13 operator"!=()

```
bool operator!= (
    const rns_double_elt_cstptr & x ) [inline]
```

12.260.2.14 operator&() [2/2]

```
rns_double_elt_cstptr operator& ( ) const [inline], [inherited]
```

12.260.3 Field Documentation**12.260.3.1 other**

```
rns_double_elt other
```

12.260.3.2 _ptr

```
double* _ptr [inherited]
```

12.260.3.3 _stride

```
size_t _stride [inherited]
```

12.260.3.4 _alloc

```
bool _alloc [inherited]
```


The documentation for this struct was generated from the following file:

- [rns-double-elt.h](#)

12.261 rns_double_elt_ptr Struct Reference

```
#include <rns-double-elt.h>
```

Inheritance diagram for rns_double_elt_ptr:

**Public Member Functions**

- [rns_double_elt_ptr](#) ()
- [rns_double_elt_ptr](#) (double *p, size_t r)
- [rns_double_elt_ptr](#) (const [rns_double_elt_ptr](#) &x)
- [rns_double_elt_ptr](#) (const [rns_double_elt_cstptr](#) &x)
- [rns_double_elt_ptr](#) ([rns_double_elt_ptr](#) &&)=default
- [rns_double_elt_ptr](#) * [operator&](#) ()

- `rns_double_elt & operator* ( )`
- `rns_double_elt operator[] (size_t i) const`
- `rns_double_elt & operator[] (size_t i)`
- `rns_double_elt_ptr operator++ ( )`
- `rns_double_elt_ptr operator-- ( )`
- `rns_double_elt_ptr operator+ (size_t inc)`
- `rns_double_elt_ptr operator- (size_t inc)`
- `rns_double_elt_ptr & operator+= (size_t inc)`
- `rns_double_elt_ptr & operator-= (size_t inc)`
- `rns_double_elt_ptr & operator= (const rns_double_elt_ptr &x)`
- `bool operator< (const rns_double_elt_ptr &x)`
- `bool operator!= (const rns_double_elt_ptr &x)`
- `rns_double_elt_cstptr operator& ( ) const`

Data Fields

- `rns_double_elt other`
- `double * _ptr`
- `size_t _stride`
- `bool _alloc`

12.261.1 Constructor & Destructor Documentation

12.261.1.1 `rns_double_elt_ptr()` [1/5]

```
rns_double_elt_ptr ( ) [inline]
```

12.261.1.2 `rns_double_elt_ptr()` [2/5]

```
rns_double_elt_ptr (
    double * p,
    size_t r ) [inline]
```

12.261.1.3 `rns_double_elt_ptr()` [3/5]

```
rns_double_elt_ptr (
    const rns_double_elt_ptr & x ) [inline]
```

12.261.1.4 `rns_double_elt_ptr()` [4/5]

```
rns_double_elt_ptr (
    const rns_double_elt_cstptr & x ) [inline]
```

12.261.1.5 `rns_double_elt_ptr()` [5/5]

```
rns_double_elt_ptr (
    rns_double_elt_ptr && ) [default]
```

12.261.2 Member Function Documentation

12.261.2.1 `operator&()` [1/2]

```
rns_double_elt_ptr * operator& ( ) [inline]
```

12.261.2.2 `operator*()`

```
rns_double_elt & operator* ( ) [inline]
```

12.261.2.3 operator[]() [1/2]

```
rns_double_elt operator[] (
    size_t i ) const [inline]
```

12.261.2.4 operator[]() [2/2]

```
rns_double_elt & operator[] (
    size_t i ) [inline]
```

12.261.2.5 operator++()

```
rns_double_elt_ptr operator++ ( ) [inline]
```

12.261.2.6 operator--()

```
rns_double_elt_ptr operator-- ( ) [inline]
```

12.261.2.7 operator+()

```
rns_double_elt_ptr operator+ (
    size_t inc ) [inline]
```

12.261.2.8 operator-()

```
rns_double_elt_ptr operator- (
    size_t inc ) [inline]
```

12.261.2.9 operator+=()

```
rns_double_elt_ptr & operator+= (
    size_t inc ) [inline]
```

12.261.2.10 operator-=()

```
rns_double_elt_ptr & operator-= (
    size_t inc ) [inline]
```

12.261.2.11 operator=()

```
rns_double_elt_ptr & operator= (
    const rns_double_elt_ptr & x ) [inline]
```

12.261.2.12 operator<()

```
bool operator< (
    const rns_double_elt_ptr & x ) [inline]
```

12.261.2.13 operator"!=()

```
bool operator!= (
    const rns_double_elt_ptr & x ) [inline]
```

12.261.2.14 operator&() [2/2]

```
rns_double_elt_cstptr operator& ( ) const [inline], [inherited]
```

12.261.3 Field Documentation

12.261.3.1 other

`rns_double_elt` other

12.261.3.2 _ptr

`double* _ptr` [inherited]

12.261.3.3 _stride

`size_t _stride` [inherited]

12.261.3.4 _alloc

`bool _alloc` [inherited]

The documentation for this struct was generated from the following file:

- [rns-double-elt.h](#)

12.262 `rns_double_extended` Struct Reference

```
#include <rns-double.h>
```

Public Types

- typedef Givaro::Integer [integer](#)
- typedef Givaro::ModularExtended< double > [ModField](#)
- typedef double [BasisElement](#)
- typedef [rns_double_elt](#) [Element](#)
- typedef [rns_double_elt_ptr](#) [Element_ptr](#)
- typedef [rns_double_elt_cstptr](#) [ConstElement_ptr](#)

Public Member Functions

- [rns_double_extended](#) (const [integer](#) &bound, size_t pbits, bool rnsmod=false, long seed=time(NULL))
- [rns_double_extended](#) (size_t pbits, size_t size, long seed=time(NULL))
- template<typename Vect >
 [rns_double_extended](#) (const Vect &basis, bool rnsmod=false, long seed=time(NULL))
- void [precompute_cst](#) ()
- void [init](#) (size_t m, size_t n, double *Arns, size_t rda, const [integer](#) *A, size_t lda, const [integer](#) &maxA, bool RNS_MAJOR=false) const
- void [init](#) (size_t m, size_t n, double *Arns, size_t rda, const [integer](#) *A, size_t lda, size_t k, bool RNS_MAJOR=false)
- void [convert](#) (size_t m, size_t n, [integer](#) gamma, [integer](#) *A, size_t lda, const double *Arns, size_t rda, bool RNS_MAJOR=false)
- void [init](#) (size_t m, double *Arns, const [integer](#) *A, size_t lda) const
- void [convert](#) (size_t m, [integer](#) *A, const double *Arns) const
- void [reduce](#) (size_t n, double *Arns, size_t rda, bool RNS_MAJOR=false) const

Data Fields

- std::vector< double, AlignedAllocator< double, Alignment::CACHE_LINE > > [_basis](#)
- std::vector< double, AlignedAllocator< double, Alignment::CACHE_LINE > > [_basisMax](#)
- std::vector< double, AlignedAllocator< double, Alignment::CACHE_LINE > > [_negbasis](#)
- std::vector< double, AlignedAllocator< double, Alignment::CACHE_LINE > > [_invbasis](#)
- std::vector< [ModField](#) > [_field_rns](#)

- [integer_M](#)
- `std::vector< integer > _Mi`
- `std::vector< double > _MMi`
- `std::vector< double > _crt_in`
- `std::vector< double > _crt_out`
- `size_t _size`
- `size_t _pbits`
- `size_t _ldm`

12.262.1 Member Typedef Documentation

12.262.1.1 integer

```
typedef Givaro::Integer integer
```

12.262.1.2 ModField

```
typedef Givaro::ModularExtended<double> ModField
```

12.262.1.3 BasisElement

```
typedef double BasisElement
```

12.262.1.4 Element

```
typedef rns\_double\_elt Element
```

12.262.1.5 Element_ptr

```
typedef rns\_double\_elt\_ptr Element\_ptr
```

12.262.1.6 ConstElement_ptr

```
typedef rns\_double\_elt\_cstptr ConstElement\_ptr
```

12.262.2 Constructor & Destructor Documentation

12.262.2.1 rns_double_extended() [1/3]

```
rns\_double\_extended (
    const integer & bound,
    size_t pbits,
    bool rnsmod = false,
    long seed = time(NULL) ) [inline]
```

12.262.2.2 rns_double_extended() [2/3]

```
rns\_double\_extended (
    size_t pbits,
    size_t size,
    long seed = time(NULL) ) [inline]
```

12.262.2.3 rns_double_extended() [3/3]

```
template<typename Vect >
rns\_double\_extended (
    const Vect & basis,
    bool rnsmod = false,
    long seed = time(NULL) ) [inline]
```

12.262.3 Member Function Documentation

12.262.3.1 precompute_cst()

```
void precompute_cst ( ) [inline]
```

12.262.3.2 init() [1/3]

```
void init (
    size_t m,
    size_t n,
    double * Arns,
    size_t rda,
    const integer * A,
    size_t lda,
    const integer & maxA,
    bool RNS_MAJOR = false ) const [inline]
```

12.262.3.3 init() [2/3]

```
void init (
    size_t m,
    size_t n,
    double * Arns,
    size_t rda,
    const integer * A,
    size_t lda,
    size_t k,
    bool RNS_MAJOR = false ) [inline]
```

12.262.3.4 convert() [1/2]

```
void convert (
    size_t m,
    size_t n,
    integer gamma,
    integer * A,
    size_t lda,
    const double * Arns,
    size_t rda,
    bool RNS_MAJOR = false ) [inline]
```

12.262.3.5 init() [3/3]

```
void init (
    size_t m,
    double * Arns,
    const integer * A,
    size_t lda ) const [inline]
```

12.262.3.6 convert() [2/2]

```
void convert (
    size_t m,
    integer * A,
    const double * Arns ) const [inline]
```

12.262.3.7 reduce()

```
void reduce (
```



```
    size_t n,  
    double * Arns,  
    size_t rda,  
    bool RNS_MAJOR = false ) const [inline]
```

12.262.4 Field Documentation

12.262.4.1 `_basis`

```
std::vector<double, AlignedAllocator<double, Alignment::CACHE_LINE> > _basis
```

12.262.4.2 `_basisMax`

```
std::vector<double, AlignedAllocator<double, Alignment::CACHE_LINE> > _basisMax
```

12.262.4.3 `_negbasis`

```
std::vector<double, AlignedAllocator<double, Alignment::CACHE_LINE> > _negbasis
```

12.262.4.4 `_invbasis`

```
std::vector<double, AlignedAllocator<double, Alignment::CACHE_LINE> > _invbasis
```

12.262.4.5 `_field_rns`

```
std::vector<ModField> _field_rns
```

12.262.4.6 `_M`

```
integer _M
```

12.262.4.7 `_Mi`

```
std::vector<integer> _Mi
```

12.262.4.8 `_MMi`

```
std::vector<double> _MMi
```

12.262.4.9 `_crt_in`

```
std::vector<double> _crt_in
```

12.262.4.10 `_crt_out`

```
std::vector<double> _crt_out
```

12.262.4.11 `_size`

```
size_t _size
```

12.262.4.12 `_pbits`

```
size_t _pbits
```

12.262.4.13 `_ldm`

```
size_t _ldm
```

The documentation for this struct was generated from the following files:

- [rns-double.h](#)
- [rns-double.inl](#)

12.263 RNSElementTag Struct Reference

Representation in a Residue Number System.

```
#include <field-traits.h>
```

12.263.1 Detailed Description

Representation in a Residue Number System.

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.264 RNSInteger< RNS > Class Template Reference

```
#include <rns-integer.h>
```

Data Structures

- class [RandIter](#)

Public Types

- typedef [RNS::Element](#) [Element](#)
- typedef [RNS::Element_ptr](#) [Element_ptr](#)
- typedef [RNS::ConstElement_ptr](#) [ConstElement_ptr](#)

Public Member Functions

- [RNSInteger](#) (const [RNS](#) &myrns)
- template<typename T >
 [RNSInteger](#) (const T &F)
- const [RNS](#) & [rns](#) () const
- size_t [size](#) () const
- bool [isOne](#) (const [Element](#) &x) const
- bool [isMOne](#) (const [Element](#) &x) const
- bool [isZero](#) (const [Element](#) &x) const
- [integer characteristic](#) ([integer](#) &p) const
- [integer cardinality](#) ([integer](#) &p) const
- [Element](#) & [init](#) ([Element](#) &x) const
- [Element](#) & [init](#) ([Element](#) &x, const Givaro::Integer &y) const
- [Element](#) & [reduce](#) ([Element](#) &x, const [Element](#) &y) const
- [Element](#) & [reduce](#) ([Element](#) &x) const
- Givaro::Integer [convert](#) (Givaro::Integer &x, const [Element](#) &y) const
- [Element](#) & [assign](#) ([Element](#) &x, const [Element](#) &y) const
- std::ostream & [write](#) (std::ostream &os, const [Element](#) &y) const
- std::ostream & [write](#) (std::ostream &os) const

Data Fields

- [Element one](#)
- [Element mOne](#)
- [Element zero](#)

Protected Types

- typedef [RNS::BasisElement](#) [BasisElement](#)
- typedef Givaro::Integer [integer](#)

Protected Attributes

- const [RNS](#) * [_rns](#)

12.264.1 Member Typedef Documentation**12.264.1.1 BasisElement**

```
template<typename RNS >
typedef RNS::BasisElement BasisElement [protected]
```

12.264.1.2 integer

```
template<typename RNS >
typedef Givaro::Integer integer [protected]
```

12.264.1.3 Element

```
template<typename RNS >
typedef RNS::Element Element
```

12.264.1.4 Element_ptr

```
template<typename RNS >
typedef RNS::Element\_ptr Element\_ptr
```

12.264.1.5 ConstElement_ptr

```
template<typename RNS >
typedef RNS::ConstElement\_ptr ConstElement\_ptr
```

12.264.2 Constructor & Destructor Documentation**12.264.2.1 RNSInteger() [1/2]**

```
template<typename RNS >
RNSInteger (
    const RNS & myrns ) [inline]
```

12.264.2.2 RNSInteger() [2/2]

```
template<typename RNS >
template<typename T >
RNSInteger (
    const T & F ) [inline]
```

12.264.3 Member Function Documentation**12.264.3.1 rns()**

```
template<typename RNS >
const RNS & rns ( ) const [inline]
```

12.264.3.2 size()

```
template<typename RNS >
size_t size ( ) const [inline]
```

12.264.3.3 isOne()

```
template<typename RNS >
bool isOne (
    const Element & x ) const [inline]
```

12.264.3.4 isMOne()

```
template<typename RNS >
bool isMOne (
    const Element & x ) const [inline]
```

12.264.3.5 isZero()

```
template<typename RNS >
bool isZero (
    const Element & x ) const [inline]
```

12.264.3.6 characteristic()

```
template<typename RNS >
integer characteristic (
    integer & p ) const [inline]
```

12.264.3.7 cardinality()

```
template<typename RNS >
integer cardinality (
    integer & p ) const [inline]
```

12.264.3.8 init() [1/2]

```
template<typename RNS >
Element & init (
    Element & x ) const [inline]
```

12.264.3.9 init() [2/2]

```
template<typename RNS >
Element & init (
    Element & x,
    const Givaro::Integer & y ) const [inline]
```

12.264.3.10 reduce() [1/2]

```
template<typename RNS >
Element & reduce (
    Element & x,
    const Element & y ) const [inline]
```

12.264.3.11 reduce() [2/2]

```
template<typename RNS >
Element & reduce (
    Element & x ) const [inline]
```

12.264.3.12 convert()

```
template<typename RNS >
Givaro::Integer convert (
    Givaro::Integer & x,
    const Element & y ) const [inline]
```

12.264.3.13 assign()

```
template<typename RNS >
Element & assign (
    Element & x,
    const Element & y ) const [inline]
```

12.264.3.14 write() [1/2]

```
template<typename RNS >
std::ostream & write (
    std::ostream & os,
    const Element & y ) const [inline]
```

12.264.3.15 write() [2/2]

```
template<typename RNS >
std::ostream & write (
    std::ostream & os ) const [inline]
```

12.264.4 Field Documentation**12.264.4.1 _rns**

```
template<typename RNS >
const RNS* _rns [protected]
```

12.264.4.2 one

```
template<typename RNS >
Element one
```

12.264.4.3 mOne

```
template<typename RNS >
Element mOne
```

12.264.4.4 zero

```
template<typename RNS >
Element zero
```

The documentation for this class was generated from the following files:

- [field-traits.h](#)
- [rns-integer.h](#)

12.265 RNSIntegerMod< RNS > Class Template Reference

```
#include <rns-integer-mod.h>
```

Data Structures

- class [RandIter](#)

Public Types

- typedef [RNS::Element](#) [Element](#)
- typedef [RNS::Element_ptr](#) [Element_ptr](#)
- typedef [RNS::ConstElement_ptr](#) [ConstElement_ptr](#)

Public Member Functions

- [RNSIntegerMod](#) (const [integer](#) &p, const [RNS](#) &myrns)
- const [rns_double](#) & [rns](#) () const
- const [RNSInteger](#)< [RNS](#) > & [delayed](#) () const
- [size_t](#) [size](#) () const
- bool [isOne](#) (const [Element](#) &x) const
- bool [isMOne](#) (const [Element](#) &x) const
- bool [isZero](#) (const [Element](#) &x) const
- [integer](#) & [characteristic](#) ([integer](#) &p) const
- [integer](#) [characteristic](#) () const
- [integer](#) & [cardinality](#) ([integer](#) &p) const
- [integer](#) [cardinality](#) () const
- [integer](#) [minElement](#) () const
- [integer](#) [maxElement](#) () const
- [Element](#) & [init](#) ([Element](#) &x) const
- [Element](#) & [init](#) ([Element](#) &x, const Givaro::Integer &y) const
- [Element](#) & [reduce](#) ([Element](#) &x, const [Element](#) &y) const
- [Element](#) & [reduce](#) ([Element](#) &x) const
- [Element](#) & [init](#) ([Element](#) &x, const [Element](#) &y) const
- Givaro::Integer [convert](#) (Givaro::Integer &x, const [Element](#) &y) const
- [Element](#) & [assign](#) ([Element](#) &x, const [Element](#) &y) const
- [Element](#) & [add](#) ([Element](#) &x, const [Element](#) &y, const [Element](#) &z) const
- [Element](#) & [sub](#) ([Element](#) &x, const [Element](#) &y, const [Element](#) &z) const
- [Element](#) & [neg](#) ([Element](#) &x, const [Element](#) &y) const
- [Element](#) & [mul](#) ([Element](#) &x, const [Element](#) &y, const [Element](#) &z) const
- [Element](#) & [axpyin](#) ([Element](#) &x, const [Element](#) &y, const [Element](#) &z) const
- [Element](#) & [inv](#) ([Element](#) &x, const [Element](#) &y) const
- bool [areEqual](#) (const [Element](#) &x, const [Element](#) &y) const
- std::ostream & [write](#) (std::ostream &os, const [Element](#) &y) const
- std::ostream & [write](#) (std::ostream &os) const
- void [reduce_modp](#) (size_t n, [Element_ptr](#) B) const
- std::ostream & [write_matrix](#) (std::ostream &c, const double *E, int n, int m, int lda) const
- std::ostream & [write_matrix_long](#) (std::ostream &c, const double *E, int n, int m, int lda) const
- void [reduce_modp](#) (size_t m, size_t n, [Element_ptr](#) B, size_t lda) const
- void [reduce_modp_rnsmajor](#) (size_t n, [Element_ptr](#) B) const

Data Fields

- [Element](#) [one](#)
- [Element](#) [mOne](#)
- [Element](#) [zero](#)

Protected Types

- typedef [RNS::BasisElement](#) [BasisElement](#)
- typedef Givaro::Modular< [BasisElement](#) > [ModField](#)
- typedef Givaro::Integer [integer](#)

Protected Attributes

- [integer_p](#)
- `std::vector< BasisElement, AlignedAllocator< BasisElement, Alignment::CACHE_LINE > > \_Mi\_modp\_rns`
- `std::vector< BasisElement, AlignedAllocator< BasisElement, Alignment::CACHE_LINE > > \_iM\_modp\_rns`
- `const RNS * \_rns`
- `Givaro::Modular< Givaro::Integer > \_F`
- `RNSInteger< RNS > \_RNSdelayed`

12.265.1 Member Typedef Documentation**12.265.1.1 Element**

```
template<typename RNS >
typedef RNS::Element Element
```

12.265.1.2 Element_ptr

```
template<typename RNS >
typedef RNS::Element\_ptr Element\_ptr
```

12.265.1.3 ConstElement_ptr

```
template<typename RNS >
typedef RNS::ConstElement\_ptr ConstElement\_ptr
```

12.265.1.4 BasisElement

```
template<typename RNS >
typedef RNS::BasisElement BasisElement [protected]
```

12.265.1.5 ModField

```
template<typename RNS >
typedef Givaro::Modular<BasisElement> ModField [protected]
```

12.265.1.6 integer

```
template<typename RNS >
typedef Givaro::Integer integer [protected]
```

12.265.2 Constructor & Destructor Documentation**12.265.2.1 RNSIntegerMod()**

```
template<typename RNS >
RNSIntegerMod (
    const integer & p,
    const RNS & myrns ) [inline]
```

12.265.3 Member Function Documentation**12.265.3.1 rns()**

```
template<typename RNS >
const rns\_double & rns ( ) const [inline]
```

12.265.3.2 delayed()

```
template<typename RNS >
const RNSInteger< RNS > & delayed ( ) const [inline]
```

12.265.3.3 size()

```
template<typename RNS >
size_t size ( ) const [inline]
```

12.265.3.4 isOne()

```
template<typename RNS >
bool isOne (
    const Element & x ) const [inline]
```

12.265.3.5 isMOne()

```
template<typename RNS >
bool isMOne (
    const Element & x ) const [inline]
```

12.265.3.6 isZero()

```
template<typename RNS >
bool isZero (
    const Element & x ) const [inline]
```

12.265.3.7 characteristic() [1/2]

```
template<typename RNS >
integer & characteristic (
    integer & p ) const [inline]
```

12.265.3.8 characteristic() [2/2]

```
template<typename RNS >
integer characteristic ( ) const [inline]
```

12.265.3.9 cardinality() [1/2]

```
template<typename RNS >
integer & cardinality (
    integer & p ) const [inline]
```

12.265.3.10 cardinality() [2/2]

```
template<typename RNS >
integer cardinality ( ) const [inline]
```

12.265.3.11 minElement()

```
template<typename RNS >
integer minElement ( ) const [inline]
```

12.265.3.12 maxElement()

```
template<typename RNS >
integer maxElement ( ) const [inline]
```

12.265.3.13 init() [1/3]

```
template<typename RNS >
Element & init (
    Element & x ) const [inline]
```


12.265.3.14 init() [2/3]

```
template<typename RNS >
Element & init (
    Element & x,
    const Givaro::Integer & y ) const [inline]
```

12.265.3.15 reduce() [1/2]

```
template<typename RNS >
Element & reduce (
    Element & x,
    const Element & y ) const [inline]
```

12.265.3.16 reduce() [2/2]

```
template<typename RNS >
Element & reduce (
    Element & x ) const [inline]
```

12.265.3.17 init() [3/3]

```
template<typename RNS >
Element & init (
    Element & x,
    const Element & y ) const [inline]
```

12.265.3.18 convert()

```
template<typename RNS >
Givaro::Integer convert (
    Givaro::Integer & x,
    const Element & y ) const [inline]
```

12.265.3.19 assign()

```
template<typename RNS >
Element & assign (
    Element & x,
    const Element & y ) const [inline]
```

12.265.3.20 add()

```
template<typename RNS >
Element & add (
    Element & x,
    const Element & y,
    const Element & z ) const [inline]
```

12.265.3.21 sub()

```
template<typename RNS >
Element & sub (
    Element & x,
    const Element & y,
    const Element & z ) const [inline]
```

12.265.3.22 neg()

```
template<typename RNS >
Element & neg (
    Element & x,
    const Element & y ) const [inline]
```

12.265.3.23 mul()

```
template<typename RNS >
Element & mul (
    Element & x,
    const Element & y,
    const Element & z ) const [inline]
```

12.265.3.24 axpyin()

```
template<typename RNS >
Element & axpyin (
    Element & x,
    const Element & y,
    const Element & z ) const [inline]
```

12.265.3.25 inv()

```
template<typename RNS >
Element & inv (
    Element & x,
    const Element & y ) const [inline]
```

12.265.3.26 areEqual()

```
template<typename RNS >
bool areEqual (
    const Element & x,
    const Element & y ) const [inline]
```

12.265.3.27 write() [1/2]

```
template<typename RNS >
std::ostream & write (
    std::ostream & os,
    const Element & y ) const [inline]
```

12.265.3.28 write() [2/2]

```
template<typename RNS >
std::ostream & write (
    std::ostream & os ) const [inline]
```

12.265.3.29 reduce_modp() [1/2]

```
template<typename RNS >
void reduce_modp (
    size_t n,
    Element_ptr B ) const [inline]
```

12.265.3.30 write_matrix()

```
template<typename RNS >
std::ostream & write_matrix (
    std::ostream & c,
    const double * E,
    int n,
    int m,
    int lda ) const [inline]
```

12.265.3.31 write_matrix_long()

```
template<typename RNS >
std::ostream & write_matrix_long (
    std::ostream & c,
    const double * E,
    int n,
    int m,
    int lda ) const [inline]
```

12.265.3.32 reduce_modp() [2/2]

```
template<typename RNS >
void reduce_modp (
    size_t m,
    size_t n,
    Element_ptr B,
    size_t lda ) const [inline]
```

12.265.3.33 reduce_modp_rnsmajor()

```
template<typename RNS >
void reduce_modp_rnsmajor (
    size_t n,
    Element_ptr B ) const [inline]
```

12.265.4 Field Documentation**12.265.4.1 _p**

```
template<typename RNS >
integer _p [protected]
```

12.265.4.2 _Mi_modp_rns

```
template<typename RNS >
std::vector<BasisElement, AlignedAllocator<BasisElement, Alignment::CACHE_LINE> > _Mi_modp_↵
rns [protected]
```

12.265.4.3 _iM_modp_rns

```
template<typename RNS >
std::vector<BasisElement, AlignedAllocator<BasisElement, Alignment::CACHE_LINE> > _iM_modp_↵
rns [protected]
```

12.265.4.4 _rns

```
template<typename RNS >
const RNS* _rns [protected]
```

12.265.4.5 `_F`

```
template<typename RNS >
Givaro::Modular<Givaro::Integer> _F [protected]
```

12.265.4.6 `_RNSdelayed`

```
template<typename RNS >
RNSInteger<RNS> _RNSdelayed [protected]
```

12.265.4.7 `one`

```
template<typename RNS >
Element one
```

12.265.4.8 `mOne`

```
template<typename RNS >
Element mOne
```

12.265.4.9 `zero`

```
template<typename RNS >
Element zero
```


The documentation for this class was generated from the following files:

- [field-traits.h](#)
- [rns-integer-mod.h](#)

12.266 `rnsRandIter< RNS >` Class Template Reference

```
#include <rns-double.h>
```

Inheritance diagram for `rnsRandIter< RNS >`:



Public Member Functions

- `rnsRandIter` (const `RNS` &`R`, uint64_t seed=0)
- `RNS::Element & random` (typename `RNS::Element` &elt) const
RNS ring Element random assignement.
- `RNS::Element & operator()` (typename `RNS::Element` &elt) const
- `RNS::Element operator()` () const
- `RNS::Element random` () const
- const `RNS` & `ring` () const

12.266.1 Constructor & Destructor Documentation

12.266.1.1 `rnsRandIter()`

```
template<typename RNS >
rnsRandIter (
    const RNS & R,
    uint64_t seed = 0 ) [inline]
```

12.266.2 Member Function Documentation

12.266.2.1 random() [1/2]

```
template<typename RNS >
RNS::Element & random (
    typename RNS::Element & elt ) const [inline]
```

RNS ring Element random assignment.

Element is supposed to be initialized

Returns

random ring Element

12.266.2.2 operator>() [1/2]

```
template<typename RNS >
RNS::Element & operator() (
    typename RNS::Element & elt ) const [inline]
```

12.266.2.3 operator>() [2/2]

```
template<typename RNS >
RNS::Element operator() ( ) const [inline]
```

12.266.2.4 random() [2/2]

```
template<typename RNS >
RNS::Element random ( ) const [inline]
```

12.266.2.5 ring()

```
template<typename RNS >
const RNS & ring ( ) const [inline]
```

The documentation for this class was generated from the following file:

- [rns-double.h](#)

12.267 Row Struct Reference

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)


12.268 ruint< K > Class Template Reference

The documentation for this class was generated from the following file:

- [field-traits.h](#)

12.269 ScalFunctions< Element > Struct Template Reference

Inheritance diagram for ScalFunctions< Element >:



Public Types

- using `vectElt` = vector< Element >

Static Public Member Functions

- static void `genInputs` (vector< `vectElt` > &inputs)
- static void `genInputsWithZero` (vector< `vectElt` > &inputs)
- static Element `zero` ()
- static Element `vand` (Element x1, Element x2)
- static Element `vor` (Element x1, Element x2)
- static Element `vxor` (Element x1, Element x2)
- static Element `vandnot` (Element x1, Element x2)
- static Element `add` (Element x1, Element x2)
- static Element `addin` (Element &x1, Element x2)
- static Element `sub` (Element x1, Element x2)
- static Element `subin` (Element &x1, Element x2)
- static Element `mul` (Element x1, Element x2)
- static Element `mulin` (Element &x1, Element x2)
- static Element `div` (Element x1, Element x2)
- static Element `fmadd` (Element x1, Element x2, Element x3)
- static Element `fmaddin` (Element &x1, Element x2, Element x3)
- static Element `fmsub` (Element x1, Element x2, Element x3)
- static Element `fmsubin` (Element &x1, Element x2, Element x3)
- static Element `fnmadd` (Element x1, Element x2, Element x3)
- static Element `fnmaddin` (Element &x1, Element x2, Element x3)
- static Element `lesser` (Element x1, Element x2)
- static Element `lesser_eq` (Element x1, Element x2)
- static Element `greater` (Element x1, Element x2)
- static Element `greater_eq` (Element x1, Element x2)
- static Element `eq` (Element x1, Element x2)
- static `vectElt` `unpacklo` (`vectElt` a, `vectElt` b)
- static `vectElt` `unpackhi` (`vectElt` a, `vectElt` b)
- static void `unpacklohi` (`vectElt` &lo, `vectElt` &hi, `vectElt` a, `vectElt` b)
- static `vectElt` `pack_even` (`vectElt` a, `vectElt` b)
- static `vectElt` `pack_odd` (`vectElt` a, `vectElt` b)
- static void `pack` (`vectElt` &even, `vectElt` &odd, `vectElt` a, `vectElt` b)
- template<uint16_t s>
static `vectElt` `blend` (`vectElt` a, `vectElt` b)

12.269.1 Member Typedef Documentation

12.269.1.1 vectElt

```
template<typename Element >
using vectElt = vector<Element>
```

12.269.2 Member Function Documentation

12.269.2.1 genInputs()

```
template<typename Element >
static void genInputs (
    vector< vectElt > & inputs ) [inline], [static]
```

12.269.2.2 genInputsWithZero()

```
template<typename Element >
static void genInputsWithZero (
    vector< vectElt > & inputs ) [inline], [static]
```

12.269.2.3 zero()

```
template<typename Element >
static Element zero ( ) [inline], [static]
```

12.269.2.4 vand()

```
template<typename Element >
static Element vand (
    Element x1,
    Element x2 ) [inline], [static]
```

12.269.2.5 vor()

```
template<typename Element >
static Element vor (
    Element x1,
    Element x2 ) [inline], [static]
```

12.269.2.6 vxor()

```
template<typename Element >
static Element vxor (
    Element x1,
    Element x2 ) [inline], [static]
```

12.269.2.7 vandnot()

```
template<typename Element >
static Element vandnot (
    Element x1,
    Element x2 ) [inline], [static]
```

12.269.2.8 add()

```
template<typename Element >
static Element add (
    Element x1,
    Element x2 ) [inline], [static]
```

12.269.2.9 addin()

```
template<typename Element >
static Element addin (
    Element & x1,
    Element x2 ) [inline], [static]
```

12.269.2.10 sub()

```
template<typename Element >
static Element sub (
    Element x1,
    Element x2 ) [inline], [static]
```

12.269.2.11 subin()

```
template<typename Element >
static Element subin (
    Element & x1,
    Element x2 ) [inline], [static]
```

12.269.2.12 mul()

```
template<typename Element >
static Element mul (
    Element x1,
    Element x2 ) [inline], [static]
```

12.269.2.13 mulin()

```
template<typename Element >
static Element mulin (
    Element & x1,
    Element x2 ) [inline], [static]
```

12.269.2.14 div()

```
template<typename Element >
static Element div (
    Element x1,
    Element x2 ) [inline], [static]
```

12.269.2.15 fmadd()

```
template<typename Element >
static Element fmadd (
    Element x1,
    Element x2,
    Element x3 ) [inline], [static]
```

12.269.2.16 fmaddin()

```
template<typename Element >
static Element fmaddin (
    Element & x1,
    Element x2,
    Element x3 ) [inline], [static]
```

12.269.2.17 fmsub()

```
template<typename Element >
static Element fmsub (
    Element x1,
    Element x2,
    Element x3 ) [inline], [static]
```

12.269.2.18 fmsubin()

```
template<typename Element >
static Element fmsubin (
    Element & x1,
    Element x2,
    Element x3 ) [inline], [static]
```


12.269.2.19 fnmadd()

```
template<typename Element >
static Element fnmadd (
    Element x1,
    Element x2,
    Element x3 ) [inline], [static]
```

12.269.2.20 fnmaddin()

```
template<typename Element >
static Element fnmaddin (
    Element & x1,
    Element x2,
    Element x3 ) [inline], [static]
```

12.269.2.21 lesser()

```
template<typename Element >
static Element lesser (
    Element x1,
    Element x2 ) [inline], [static]
```

12.269.2.22 lesser_eq()

```
template<typename Element >
static Element lesser_eq (
    Element x1,
    Element x2 ) [inline], [static]
```

12.269.2.23 greater()

```
template<typename Element >
static Element greater (
    Element x1,
    Element x2 ) [inline], [static]
```

12.269.2.24 greater_eq()

```
template<typename Element >
static Element greater_eq (
    Element x1,
    Element x2 ) [inline], [static]
```

12.269.2.25 eq()

```
template<typename Element >
static Element eq (
    Element x1,
    Element x2 ) [inline], [static]
```

12.269.2.26 unpacklo()

```
template<typename Element >
static vectElt unpacklo (
    vectElt a,
    vectElt b ) [inline], [static]
```

12.269.2.27 unpackhi()

```
template<typename Element >
static vectElt unpackhi (
    vectElt a,
    vectElt b ) [inline], [static]
```

12.269.2.28 unpacklohi()

```
template<typename Element >
static void unpacklohi (
    vectElt & lo,
    vectElt & hi,
    vectElt a,
    vectElt b ) [inline], [static]
```

12.269.2.29 pack_even()

```
template<typename Element >
static vectElt pack_even (
    vectElt a,
    vectElt b ) [inline], [static]
```

12.269.2.30 pack_odd()

```
template<typename Element >
static vectElt pack_odd (
    vectElt a,
    vectElt b ) [inline], [static]
```

12.269.2.31 pack()

```
template<typename Element >
static void pack (
    vectElt & even,
    vectElt & odd,
    vectElt a,
    vectElt b ) [inline], [static]
```

12.269.2.32 blend()


```
template<typename Element >
template<uint16_t s>
static vectElt blend (
    vectElt a,
    vectElt b ) [inline], [static]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.270 ScalFunctionsBase< Element, Enable > Struct Template Reference

Inheritance diagram for ScalFunctionsBase< Element, Enable >:



The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.271 **ScalFunctionsBase< Element, typename enable_if< is_floating_point< Element >::value >::type > Struct Template Reference**

Data Structures

- class [FloatingPointTestDistribution](#)

Static Public Member Functions

- static [FloatingPointTestDistribution](#) [get_default_random_generator](#) ()
- static [Element](#) [ceil](#) ([Element](#) x)
- static [Element](#) [floor](#) ([Element](#) x)
- static [Element](#) [round](#) ([Element](#) x)
- static [Element](#) [blendv](#) ([Element](#) a, [Element](#) b, [Element](#) mask)
- static [Element](#) [fma](#) ([Element](#) x, [Element](#) y, [Element](#) z)

Static Public Attributes

- static constexpr [Element](#) [_zero](#) = 0.0
- static constexpr [Element](#) [cmp_true](#) = NAN
- static constexpr [Element](#) [cmp_false](#) = [_zero](#)

12.271.1 Member Function Documentation

12.271.1.1 [get_default_random_generator\(\)](#)

```
template<typename Element >
static FloatingPointTestDistribution get_default_random_generator ( ) [inline], [static]
```

12.271.1.2 [ceil\(\)](#)

```
template<typename Element >
static Element ceil (
    Element x ) [inline], [static]
```

12.271.1.3 [floor\(\)](#)

```
template<typename Element >
static Element floor (
    Element x ) [inline], [static]
```

12.271.1.4 [round\(\)](#)

```
template<typename Element >
static Element round (
    Element x ) [inline], [static]
```

12.271.1.5 blendv()

```
template<typename Element >
static Element blendv (
    Element a,
    Element b,
    Element mask ) [inline], [static]
```

12.271.1.6 fma()

```
template<typename Element >
static Element fma (
    Element x,
    Element y,
    Element z ) [inline], [static]
```

12.271.2 Field Documentation

12.271.2.1 _zero

```
template<typename Element >
constexpr Element _zero = 0.0 [static], [constexpr]
```

12.271.2.2 cmp_true

```
template<typename Element >
constexpr Element cmp_true = NAN [static], [constexpr]
```

12.271.2.3 cmp_false

```
template<typename Element >
constexpr Element cmp_false = \_zero [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.272 ScalFunctionsBase< Element, typename enable_if< is_integral< Element >::value >::type > Struct Template Reference

Static Public Member Functions

- static uniform_int_distribution< Element > [get_default_random_generator](#) ()
- static Element [round](#) (Element x)
- static Element [fma](#) (Element x, Element y, Element z)
- static Element [mullo](#) (Element x1, Element x2)
- static Element [mulhi](#) (Element x1, Element x2)
- static Element [mulx](#) (Element x1, Element x2)
- static Element [fmaddx](#) (Element x1, Element x2, Element x3)
- static Element [fmaddxin](#) (Element &x1, Element x2, Element x3)
- static Element [fmsubx](#) (Element x1, Element x2, Element x3)
- static Element [fmsubxin](#) (Element &x1, Element x2, Element x3)
- static Element [fnmaddx](#) (Element x1, Element x2, Element x3)
- static Element [fnmaddxin](#) (Element &x1, Element x2, Element x3)
- template<int s>
 static Element [sra](#) (Element x1)
- template<int s>
 static Element [srl](#) (Element x1)
- template<int s>
 static Element [sll](#) (Element x1)

Static Public Attributes

- static constexpr Element [_zero](#) = 0
- static constexpr Element [cmp_true](#) = -1
- static constexpr Element [cmp_false](#) = [_zero](#)

12.272.1 Member Function Documentation

12.272.1.1 [get_default_random_generator\(\)](#)

```
template<typename Element >  
static uniform_int_distribution< Element > get_default_random_generator ( ) [inline], [static]
```

12.272.1.2 [round\(\)](#)

```
template<typename Element >  
static Element round (  
    Element x ) [inline], [static]
```

12.272.1.3 [fma\(\)](#)

```
template<typename Element >  
static Element fma (  
    Element x,  
    Element y,  
    Element z ) [inline], [static]
```

12.272.1.4 [mullo\(\)](#)

```
template<typename Element >  
static Element mullo (  
    Element x1,  
    Element x2 ) [inline], [static]
```

12.272.1.5 [mulhi\(\)](#)

```
template<typename Element >  
static Element mulhi (  
    Element x1,  
    Element x2 ) [inline], [static]
```

12.272.1.6 [mulx\(\)](#)

```
template<typename Element >  
static Element mulx (  
    Element x1,  
    Element x2 ) [inline], [static]
```

12.272.1.7 [fmaddx\(\)](#)

```
template<typename Element >  
static Element fmaddx (  
    Element x1,  
    Element x2,  
    Element x3 ) [inline], [static]
```

12.272.1.8 fmaddxin()

```
template<typename Element >
static Element fmaddxin (
    Element & x1,
    Element x2,
    Element x3 ) [inline], [static]
```

12.272.1.9 fmsubx()

```
template<typename Element >
static Element fmsubx (
    Element x1,
    Element x2,
    Element x3 ) [inline], [static]
```

12.272.1.10 fmsubxin()

```
template<typename Element >
static Element fmsubxin (
    Element & x1,
    Element x2,
    Element x3 ) [inline], [static]
```

12.272.1.11 fnmaddx()

```
template<typename Element >
static Element fnmaddx (
    Element x1,
    Element x2,
    Element x3 ) [inline], [static]
```

12.272.1.12 fnmaddxin()

```
template<typename Element >
static Element fnmaddxin (
    Element & x1,
    Element x2,
    Element x3 ) [inline], [static]
```

12.272.1.13 sra()

```
template<typename Element >
template<int s>
static Element sra (
    Element x1 ) [inline], [static]
```

12.272.1.14 srl()

```
template<typename Element >
template<int s>
static Element srl (
    Element x1 ) [inline], [static]
```

12.272.1.15 sll()

```
template<typename Element >
template<int s>
static Element sll (
    Element x1 ) [inline], [static]
```

12.272.2 Field Documentation

12.272.2.1 `_zero`

```
template<typename Element >
constexpr Element _zero = 0 [static], [constexpr]
```

12.272.2.2 `cmp_true`

```
template<typename Element >
constexpr Element cmp_true = -1 [static], [constexpr]
```

12.272.2.3 `cmp_false`

```
template<typename Element >
constexpr Element cmp_false = \_zero [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.273 Sequential Struct Reference

Public Member Functions

- [Sequential](#) ()
- [Sequential](#) (size_t nth)
- template<class Cut , class Param >
[Sequential](#) ([Parallel](#)< Cut, Param > &)
- size_t [numthreads](#) () const

Friends

- std::ostream & [operator<<](#) (std::ostream &out, const [Sequential](#) &)

12.273.1 Constructor & Destructor Documentation

12.273.1.1 `Sequential()` [1/3]

```
Sequential ( ) [inline]
```

12.273.1.2 `Sequential()` [2/3]

```
Sequential (
    size_t nth ) [inline]
```

12.273.1.3 `Sequential()` [3/3]

```
template<class Cut , class Param >
Sequential (
    Parallel< Cut, Param > & ) [inline]
```

12.273.2 Member Function Documentation

12.273.2.1 `numthreads()`

```
size_t numthreads ( ) const [inline]
```

12.273.3 Friends And Related Symbol Documentation

12.273.3.1 operator<<

```
std::ostream & operator<< (
    std::ostream & out,
    const Sequential & ) [friend]
```

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.274 Simd128_impl< ArithType, Int, Signed, Size > Struct Template Reference

The documentation for this struct was generated from the following file:

- [simd128.inl](#)

12.275 Simd128_impl< true, false, true, 4 > Struct Reference

The documentation for this struct was generated from the following file:

- [simd128_float.inl](#)


12.276 Simd128_impl< true, false, true, 8 > Struct Reference

The documentation for this struct was generated from the following file:

- [simd128_double.inl](#)

12.277 Simd128_impl< true, true, false, 2 > Struct Reference

Inheritance diagram for Simd128_impl< true, true, false, 2 >:



Data Structures

- union [Converter](#)

Public Types

- using [scalar_t](#) = uint16_t
- using [aligned_allocator](#) = AlignedAllocator< [scalar_t](#), Alignment([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >
- template<class [Field](#) >
using [is_same_element](#) = std::is_same< typename [Field::Element](#), [scalar_t](#) >
- using [vect_t](#) = __m128i

Static Public Member Functions

- static const std::string [type_string](#) ()
- static [INLINE CONST vect_t set1](#) (const [scalar_t](#) x)
- static [INLINE CONST vect_t set](#) (const [scalar_t](#) x0, const [scalar_t](#) x1, const [scalar_t](#) x2, const [scalar_t](#) x3, const [scalar_t](#) x4, const [scalar_t](#) x5, const [scalar_t](#) x6, const [scalar_t](#) x7)
- template<class T >
static [INLINE PURE vect_t gather](#) (const [scalar_t](#) *const p, const T *const idx)
- static [INLINE PURE vect_t load](#) (const [scalar_t](#) *const p)
- static [INLINE PURE vect_t loadu](#) (const [scalar_t](#) *const p)
- static [INLINE void store](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void storeu](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void stream](#) ([scalar_t](#) *p, const [vect_t](#) v)
- template<int s>
static [INLINE CONST vect_t sra](#) (const [vect_t](#) a)
- static [INLINE CONST vect_t greater](#) ([vect_t](#) a, [vect_t](#) b)
- static [INLINE CONST vect_t lesser](#) ([vect_t](#) a, [vect_t](#) b)
- static [INLINE CONST vect_t greater_eq](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t lesser_eq](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t mulhi](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t mulx](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t fmadddx](#) (const [vect_t](#) c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE vect_t fmadddxin](#) ([vect_t](#) &c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t fnmadddx](#) (const [vect_t](#) c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE vect_t fnmadddxin](#) ([vect_t](#) &c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t fmsubx](#) (const [vect_t](#) c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE vect_t fmsubxin](#) ([vect_t](#) &c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST scalar_t hadd_to_scal](#) (const [vect_t](#) a)
- template<class T >
static constexpr bool [valid](#) (T *p)
- template<class T >
static constexpr bool [compliant](#) (T n)
- static [INLINE CONST vect_t set1](#) (const [scalar_t](#) x)
- static [INLINE CONST vect_t set](#) (const [scalar_t](#) x0, const [scalar_t](#) x1, const [scalar_t](#) x2, const [scalar_t](#) x3, const [scalar_t](#) x4, const [scalar_t](#) x5, const [scalar_t](#) x6, const [scalar_t](#) x7)
- template<class T >
static [INLINE PURE vect_t gather](#) (const [scalar_t](#) *const p, const T *const idx)
- static [INLINE PURE vect_t load](#) (const [scalar_t](#) *const p)
- static [INLINE PURE vect_t loadu](#) (const [scalar_t](#) *const p)
- static [INLINE void store](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void storeu](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void stream](#) ([scalar_t](#) *p, const [vect_t](#) v)
- template<int s>
static [INLINE CONST vect_t sll](#) (const [vect_t](#) a)
- template<int s>
static [INLINE CONST vect_t srl](#) (const [vect_t](#) a)
- template<uint32_t s>
static [INLINE CONST vect_t shuffle](#) (const [vect_t](#) a)
- static [INLINE CONST vect_t unpacklo_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpacklo](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE void unpacklohi](#) ([vect_t](#) &lo, [vect_t](#) &hi, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_even](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_odd](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE void pack](#) ([vect_t](#) &even, [vect_t](#) &odd, const [vect_t](#) a, const [vect_t](#) b)

- static `INLINE` void `transpose` (`vect_t` &r0, `vect_t` &r1, `vect_t` &r2, `vect_t` &r3, `vect_t` &r4, `vect_t` &r5, `vect_t` &r6, `vect_t` &r7)
- template<uint8_t s>
static `INLINE` `CONST` `vect_t` `blend` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `add` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `addin` (`vect_t` &a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `sub` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `subin` (`vect_t` &a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `mullo` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fnmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `round` (const `vect_t` a)
- static `INLINE` `vect_t` `mod` (`vect_t` &C, const `vect_t` &P, const `__m64` &INVP, const `vect_t` &NEGP, const `vect_t` &MIN, const `vect_t` &MAX, `vect_t` &Q, `vect_t` &T)
- static `INLINE` `CONST` `vect_t` `zero` ()
- template<uint8_t s>
static `INLINE` `CONST` `vect_t` `sll128` (const `vect_t` a)
- template<uint8_t s>
static `INLINE` `CONST` `vect_t` `srl128` (const `vect_t` a)
- static `INLINE` `CONST` `vect_t` `vand` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `vor` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `vxor` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `vandnot` (const `vect_t` a, const `vect_t` b)

Static Public Attributes

- static const constexpr size_t `vect_size` = 8
- static const constexpr size_t `alignment` = 16

12.277.1 Member Typedef Documentation

12.277.1.1 scalar_t

```
using scalar_t = uint16_t
```

12.277.1.2 aligned_allocator

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.277.1.3 aligned_vector

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.277.1.4 is_same_element

```
template<class Field >  
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.277.1.5 vect_t

```
using vect_t = __m128i [inherited]
```

12.277.2 Member Function Documentation

12.277.2.1 type_string()

```
static const std::string type_string ( ) [inline], [static]
```

12.277.2.2 set1() [1/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.277.2.3 set() [1/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7 ) [inline], [static]
```

12.277.2.4 gather() [1/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.277.2.5 load() [1/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.277.2.6 loadu() [1/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.277.2.7 store() [1/2]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.277.2.8 storeu() [1/2]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.277.2.9 stream() [1/2]

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static]
```

12.277.2.10 sra()

```
template<int s>
static INLINE CONST vect_t sra (
    const vect_t a ) [inline], [static]
```

12.277.2.11 greater()

```
static INLINE CONST vect_t greater (
    vect_t a,
    vect_t b ) [inline], [static]
```

12.277.2.12 lesser()

```
static INLINE CONST vect_t lesser (
    vect_t a,
    vect_t b ) [inline], [static]
```

12.277.2.13 greater_eq()

```
static INLINE CONST vect_t greater_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.277.2.14 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.277.2.15 mulhi()

```
static INLINE CONST vect_t mulhi (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.277.2.16 mulx()

```
static INLINE CONST vect_t mulx (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.277.2.17 fmaddx()

```
static INLINE CONST vect_t fmaddx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.277.2.18 fmaddxin()

```
static INLINE vect_t fmaddxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.277.2.19 fnmaddx()

```
static INLINE CONST vect_t fnmaddx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.277.2.20 fnmaddxin()

```
static INLINE vect_t fnmaddxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.277.2.21 fmsubx()

```
static INLINE CONST vect_t fmsubx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.277.2.22 fmsubxin()

```
static INLINE vect_t fmsubxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.277.2.23 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.277.2.24 valid()

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr], [inherited]
```

12.277.2.25 compliant()

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr], [inherited]
```

12.277.2.26 set1() [2/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static], [inherited]
```

12.277.2.27 set() [2/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
```

```
const scalar_t x6,
const scalar_t x7 ) [inline], [static], [inherited]
```

12.277.2.28 gather() [2/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static], [inherited]
```

12.277.2.29 load() [2/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static], [inherited]
```

12.277.2.30 loadu() [2/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static], [inherited]
```

12.277.2.31 store() [2/2]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]
```

12.277.2.32 storeu() [2/2]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]
```

12.277.2.33 stream() [2/2]

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static], [inherited]
```

12.277.2.34 sll()

```
template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static], [inherited]
```

12.277.2.35 srl()

```
template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static], [inherited]
```

12.277.2.36 shuffle()

```
template<uint32_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static], [inherited]
```

12.277.2.37 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.38 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.39 unpacklo()

```
static INLINE CONST vect_t unpacklo (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.40 unpackhi()

```
static INLINE CONST vect_t unpackhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.41 unpacklohi()

```
static INLINE void unpacklohi (  
    vect_t & lo,  
    vect_t & hi,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.42 pack_even()

```
static INLINE CONST vect_t pack_even (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.43 pack_odd()

```
static INLINE CONST vect_t pack_odd (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.44 pack()

```
static INLINE void pack (  
    vect_t & even,  
    vect_t & odd,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.45 transpose()

```
static INLINE void transpose (  
    vect_t & r0,  
    vect_t & r1,  
    vect_t & r2,  
    vect_t & r3,  
    vect_t & r4,
```

```
    vect_t & r5,  
    vect_t & r6,  
    vect_t & r7 ) [inline], [static], [inherited]
```

12.277.2.46 blend()

```
template<uint8_t s>  
static INLINE CONST vect_t blend (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.47 add()

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.48 addin()

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.49 sub()

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.50 subin()

```
static INLINE vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.51 mullo()

```
static INLINE CONST vect_t mullo (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.52 mul()

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.53 fmadd()

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.54 fmaddin()

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```


12.277.2.55 fnmadd()

```
static INLINE CONST vect_t fnmadd (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.56 fnmaddin()

```
static INLINE vect_t fnmaddin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.57 fmsub()

```
static INLINE CONST vect_t fmsub (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.58 fmsubin()

```
static INLINE vect_t fmsubin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.59 eq()

```
static INLINE CONST vect_t eq (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.60 round()

```
static INLINE CONST vect_t round (
    const vect_t a ) [inline], [static], [inherited]
```

12.277.2.61 mod()

```
static INLINE vect_t mod (
    vect_t & C,
    const vect_t & P,
    const __m64 & INVP,
    const vect_t & NEGP,
    const vect_t & MIN,
    const vect_t & MAX,
    vect_t & Q,
    vect_t & T ) [inline], [static], [inherited]
```

12.277.2.62 zero()

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.277.2.63 sll128()

```
template<uint8_t s>
static INLINE CONST vect_t sll128 (
    const vect_t a ) [inline], [static], [inherited]
```

12.277.2.64 srl128()

```
template<uint8_t s>
static INLINE CONST vect_t srl128 (
    const vect_t a ) [inline], [static], [inherited]
```

12.277.2.65 vand()

```
static INLINE CONST vect_t vand (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.66 vor()

```
static INLINE CONST vect_t vor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.67 vxor()

```
static INLINE CONST vect_t vxor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.277.2.68 vandnot()

```
static INLINE CONST vect_t vandnot (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.277.3 Field Documentation**12.277.3.1 vect_size**

```
const constexpr size_t vect_size = 8 [static], [constexpr], [inherited]
```

12.277.3.2 alignment


```
const constexpr size_t alignment = 16 [static], [constexpr], [inherited]
```

The documentation for this struct was generated from the following file:

- [simd128_int16.inl](#)

12.278 Simd128_impl< true, true, false, 4 > Struct Reference

Inheritance diagram for Simd128_impl< true, true, false, 4 >:

**Data Structures**

- union [Converter](#)

Public Types

- using `scalar_t` = `uint32_t`
- using `aligned_allocator` = `AlignedAllocator< scalar_t, Alignment(alignment)>`
- using `aligned_vector` = `std::vector< scalar_t, aligned_allocator >`
- template<class `Field` >
using `is_same_element` = `std::is_same< typename Field::Element, scalar_t >`
- using `vect_t` = `__m128i`

Static Public Member Functions

- static const std::string `type_string` ()
- static `INLINE CONST vect_t set1` (const `scalar_t` x)
- static `INLINE CONST vect_t set` (const `scalar_t` x0, const `scalar_t` x1, const `scalar_t` x2, const `scalar_t` x3)
- template<class `T` >
static `INLINE PURE vect_t gather` (const `scalar_t` *const p, const `T` *const idx)
- static `INLINE PURE vect_t load` (const `scalar_t` *const p)
- static `INLINE PURE vect_t loadu` (const `scalar_t` *const p)
- static `INLINE void store` (`scalar_t` *p, `vect_t` v)
- static `INLINE void storeu` (`scalar_t` *p, `vect_t` v)
- static `INLINE void stream` (`scalar_t` *p, const `vect_t` v)
- template<int `s`>
static `INLINE CONST vect_t sra` (const `vect_t` a)
- static `INLINE CONST vect_t greater` (`vect_t` a, `vect_t` b)
- static `INLINE CONST vect_t lesser` (`vect_t` a, `vect_t` b)
- static `INLINE CONST vect_t greater_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mulhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mulx` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fnmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsubx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmsubxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST scalar_t hadd_to_scal` (const `vect_t` a)
- template<class `T` >
static constexpr bool `valid` (`T` *p)
- template<class `T` >
static constexpr bool `compliant` (`T` n)
- static `INLINE CONST vect_t set1` (const `scalar_t` x)
- static `INLINE CONST vect_t set` (const `scalar_t` x0, const `scalar_t` x1, const `scalar_t` x2, const `scalar_t` x3)
- template<class `T` >
static `INLINE PURE vect_t gather` (const `scalar_t` *const p, const `T` *const idx)
- static `INLINE PURE vect_t load` (const `scalar_t` *const p)
- static `INLINE PURE vect_t loadu` (const `scalar_t` *const p)
- static `INLINE void store` (`scalar_t` *p, `vect_t` v)
- static `INLINE void storeu` (`scalar_t` *p, `vect_t` v)
- static `INLINE void stream` (`scalar_t` *p, const `vect_t` v)
- template<int `s`>
static `INLINE CONST vect_t sll` (const `vect_t` a)
- template<int `s`>
static `INLINE CONST vect_t srl` (const `vect_t` a)
- template<uint8_t `s`>
static `INLINE CONST vect_t shuffle` (const `vect_t` a)
- static `INLINE CONST vect_t unpacklo_intrinsic` (const `vect_t` a, const `vect_t` b)

- static `INLINE CONST vect_t unpackhi_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpacklo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE void unpacklohi` (`vect_t` &lo, `vect_t` &hi, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_even` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_odd` (const `vect_t` a, const `vect_t` b)
- static `INLINE void pack` (`vect_t` &even, `vect_t` &odd, const `vect_t` a, const `vect_t` b)
- static `INLINE void transpose` (`vect_t` &r0, `vect_t` &r1, `vect_t` &r2, `vect_t` &r3)
- `template<uint8_t s>`
static `INLINE CONST vect_t blend` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t add` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t addin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t sub` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t subin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t mullo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fnmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t round` (const `vect_t` a)
- static `INLINE vect_t mod` (`vect_t` &C, const `vect_t` &P, const `vect_t` &INVP, const `vect_t` &NEGP, const `vect_t` &MIN, const `vect_t` &MAX, `vect_t` &Q, `vect_t` &T)
- static `INLINE CONST vect_t zero` ()
- `template<uint8_t s>`
static `INLINE CONST vect_t sll128` (const `vect_t` a)
- `template<uint8_t s>`
static `INLINE CONST vect_t srl128` (const `vect_t` a)
- static `INLINE CONST vect_t vand` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vxor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vandnot` (const `vect_t` a, const `vect_t` b)

Static Public Attributes

- static const constexpr size_t `vect_size` = 4
- static const constexpr size_t `alignment` = 16

12.278.1 Member Typedef Documentation

12.278.1.1 scalar_t

```
using scalar_t = uint32_t
```

12.278.1.2 aligned_allocator

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.278.1.3 aligned_vector

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.278.1.4 is_same_element

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.278.1.5 vect_t

```
using vect_t = __m128i [inherited]
```

12.278.2 Member Function Documentation

12.278.2.1 type_string()

```
static const std::string type_string ( ) [inline], [static]
```

12.278.2.2 set1() [1/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.278.2.3 set() [1/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3 ) [inline], [static]
```

12.278.2.4 gather() [1/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.278.2.5 load() [1/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.278.2.6 loadu() [1/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.278.2.7 store() [1/2]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.278.2.8 storeu() [1/2]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.278.2.9 stream() [1/2]

```
static INLINE void stream (  
    scalar_t * p,  
    const vect_t v ) [inline], [static]
```

12.278.2.10 sra()

```
template<int s>  
static INLINE CONST vect_t sra (  
    const vect_t a ) [inline], [static]
```

12.278.2.11 greater()

```
static INLINE CONST vect_t greater (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.278.2.12 lesser()

```
static INLINE CONST vect_t lesser (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.278.2.13 greater_eq()

```
static INLINE CONST vect_t greater_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.278.2.14 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.278.2.15 mulhi()

```
static INLINE CONST vect_t mulhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.278.2.16 mulx()

```
static INLINE CONST vect_t mulx (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.278.2.17 fmaddx()

```
static INLINE CONST vect_t fmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.278.2.18 fmaddxin()

```
static INLINE vect_t fmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.278.2.19 fnmaddx()

```
static INLINE CONST vect_t fnmaddx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.278.2.20 fnmaddxin()

```
static INLINE vect_t fnmaddxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.278.2.21 fmsubx()

```
static INLINE CONST vect_t fmsubx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.278.2.22 fmsubxin()

```
static INLINE vect_t fmsubxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.278.2.23 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.278.2.24 valid()

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr], [inherited]
```

12.278.2.25 compliant()

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr], [inherited]
```

12.278.2.26 set1() [2/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static], [inherited]
```

12.278.2.27 set() [2/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3 ) [inline], [static], [inherited]
```

12.278.2.28 gather() [2/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static], [inherited]
```

12.278.2.29 load() [2/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static], [inherited]
```

12.278.2.30 loadu() [2/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static], [inherited]
```

12.278.2.31 store() [2/2]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]
```

12.278.2.32 storeu() [2/2]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]
```

12.278.2.33 stream() [2/2]

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static], [inherited]
```

12.278.2.34 sll()

```
template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static], [inherited]
```

12.278.2.35 srl()

```
template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static], [inherited]
```

12.278.2.36 shuffle()

```
template<uint8_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static], [inherited]
```

12.278.2.37 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```


12.278.2.38 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.39 unpacklo()

```
static INLINE CONST vect_t unpacklo (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.40 unpackhi()

```
static INLINE CONST vect_t unpackhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.41 unpacklohi()

```
static INLINE void unpacklohi (  
    vect_t & lo,  
    vect_t & hi,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.42 pack_even()

```
static INLINE CONST vect_t pack_even (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.43 pack_odd()

```
static INLINE CONST vect_t pack_odd (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.44 pack()

```
static INLINE void pack (  
    vect_t & even,  
    vect_t & odd,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.45 transpose()

```
static INLINE void transpose (  
    vect_t & r0,  
    vect_t & r1,  
    vect_t & r2,  
    vect_t & r3 ) [inline], [static], [inherited]
```

12.278.2.46 blend()

```
template<uint8_t s>  
static INLINE CONST vect_t blend (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.47 add()

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.48 addin()

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.49 sub()

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.50 subin()

```
static INLINE vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.51 mullo()

```
static INLINE CONST vect_t mullo (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.52 mul()

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.53 fmadd()

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.54 fmaddin()

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.55 fnmadd()

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.56 fnmaddin()

```
static INLINE vect_t fnmaddin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.57 fmsub()

```
static INLINE CONST vect_t fmsub (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.58 fmsubin()

```
static INLINE vect_t fmsubin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.59 eq()

```
static INLINE CONST vect_t eq (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.60 round()

```
static INLINE CONST vect_t round (
    const vect_t a ) [inline], [static], [inherited]
```

12.278.2.61 mod()

```
static INLINE vect_t mod (
    vect_t & C,
    const vect_t & P,
    const vect_t & INVP,
    const vect_t & NEGP,
    const vect_t & MIN,
    const vect_t & MAX,
    vect_t & Q,
    vect_t & T ) [inline], [static], [inherited]
```

12.278.2.62 zero()

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.278.2.63 sll128()

```
template<uint8_t s>
static INLINE CONST vect_t sll128 (
    const vect_t a ) [inline], [static], [inherited]
```

12.278.2.64 srl128()

```
template<uint8_t s>
static INLINE CONST vect_t srl128 (
    const vect_t a ) [inline], [static], [inherited]
```

12.278.2.65 vand()

```
static INLINE CONST vect_t vand (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.66 vor()

```
static INLINE CONST vect_t vor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.67 vxor()

```
static INLINE CONST vect_t vxor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.278.2.68 vandnot()

```
static INLINE CONST vect_t vandnot (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.278.3 Field Documentation**12.278.3.1 vect_size**

```
const constexpr size_t vect_size = 4 [static], [constexpr], [inherited]
```

12.278.3.2 alignment


```
const constexpr size_t alignment = 16 [static], [constexpr], [inherited]
```

The documentation for this struct was generated from the following file:

- [simd128_int32.inl](#)

12.279 Simd128_impl< true, true, false, 8 > Struct Reference

Inheritance diagram for Simd128_impl< true, true, false, 8 >:

**Data Structures**

- union [Converter](#)

Public Types

- using [scalar_t](#) = uint64_t
- using [aligned_allocator](#) = AlignedAllocator< [scalar_t](#), Alignment([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >

- template<class Field >
using is_same_element = std::is_same< typename Field::Element, scalar_t >
- using vect_t = __m128i

Static Public Member Functions

- static const std::string type_string ()
- static INLINE CONST vect_t set1 (const scalar_t x)
- static INLINE CONST vect_t set (const scalar_t x0, const scalar_t x1)
- template<class T >
static INLINE PURE vect_t gather (const scalar_t *const p, const T *const idx)
- static INLINE PURE vect_t load (const scalar_t *const p)
- static INLINE PURE vect_t loadu (const scalar_t *const p)
- static INLINE void store (scalar_t *p, vect_t v)
- static INLINE void storeu (scalar_t *p, vect_t v)
- static INLINE void stream (scalar_t *p, const vect_t v)
- template<int s>
static INLINE CONST vect_t sra (const vect_t a)
- static INLINE CONST vect_t greater (vect_t a, vect_t b)
- static INLINE CONST vect_t lesser (vect_t a, vect_t b)
- static INLINE CONST vect_t greater_eq (const vect_t a, const vect_t b)
- static INLINE CONST vect_t lesser_eq (const vect_t a, const vect_t b)
- static INLINE CONST vect_t mullo (const vect_t x0, const vect_t x1)
- static INLINE CONST vect_t mulhi (const vect_t a, const vect_t b)
- static INLINE CONST vect_t mulx (const vect_t a, const vect_t b)
- static INLINE CONST vect_t fmaddx (const vect_t c, const vect_t a, const vect_t b)
- static INLINE vect_t fmaddxin (vect_t &c, const vect_t a, const vect_t b)
- static INLINE CONST vect_t fnmaddx (const vect_t c, const vect_t a, const vect_t b)
- static INLINE vect_t fnmaddxin (vect_t &c, const vect_t a, const vect_t b)
- static INLINE CONST vect_t fmsubx (const vect_t c, const vect_t a, const vect_t b)
- static INLINE vect_t fmsubxin (vect_t &c, const vect_t a, const vect_t b)
- static INLINE CONST scalar_t hadd_to_scal (const vect_t a)
- template<class T >
static constexpr bool valid (T *p)
- template<class T >
static constexpr bool compliant (T n)
- static INLINE CONST vect_t set1 (const scalar_t x)
- static INLINE CONST vect_t set (const scalar_t x0, const scalar_t x1)
- template<class T >
static INLINE PURE vect_t gather (const scalar_t *const p, const T *const idx)
- template<int idx>
static INLINE CONST scalar_t get (vect_t v)
- static INLINE PURE vect_t load (const scalar_t *const p)
- static INLINE PURE vect_t loadu (const scalar_t *const p)
- static INLINE void store (scalar_t *p, vect_t v)
- static INLINE void storeu (scalar_t *p, vect_t v)
- static INLINE void stream (scalar_t *p, const vect_t v)
- template<int s>
static INLINE CONST vect_t sll (const vect_t a)
- template<int s>
static INLINE CONST vect_t srl (const vect_t a)
- template<uint8_t s>
static INLINE CONST vect_t shuffle (const vect_t a)
- static INLINE CONST vect_t unpacklo_intrinsic (const vect_t a, const vect_t b)
- static INLINE CONST vect_t unpackhi_intrinsic (const vect_t a, const vect_t b)
- static INLINE CONST vect_t unpacklo (const vect_t a, const vect_t b)

- static `INLINE CONST vect_t unpackhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE void unpacklohi` (`vect_t` &lo, `vect_t` &hi, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_even` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_odd` (const `vect_t` a, const `vect_t` b)
- static `INLINE void pack` (`vect_t` &even, `vect_t` &odd, const `vect_t` a, const `vect_t` b)
- static `INLINE void transpose` (`vect_t` &r0, `vect_t` &r1)
- template<uint8_t s>
 - static `INLINE CONST vect_t blend` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t add` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t addin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t sub` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t subin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fnmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t round` (const `vect_t` a)
- static `INLINE CONST vect_t mask_high` ()
- static `INLINE CONST vect_t mulhi_fast` (`vect_t` x, `vect_t` y)
- static `INLINE vect_t mod` (`vect_t` &C, const __m128d &P, const __m128d &INVP, const __m128d &NEGP, const `vect_t` &POW50REM, const __m128d &MIN, const __m128d &MAX, __m128d &Q, __m128d &T)
- static `INLINE CONST vect_t zero` ()
- template<uint8_t s>
 - static `INLINE CONST vect_t sll128` (const `vect_t` a)
- template<uint8_t s>
 - static `INLINE CONST vect_t srl128` (const `vect_t` a)
- static `INLINE CONST vect_t vand` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vxor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vandnot` (const `vect_t` a, const `vect_t` b)

Static Public Attributes

- static const constexpr size_t `vect_size` = 2
- static const constexpr size_t `alignment` = 16

Static Protected Member Functions

- static `INLINE CONST vect_t signbits` (const `vect_t` x)

12.279.1 Member Typedef Documentation

12.279.1.1 scalar_t

```
using scalar_t = uint64_t
```

12.279.1.2 aligned_allocator

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.279.1.3 aligned_vector

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.279.1.4 is_same_element

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.279.1.5 vect_t

```
using vect_t = __m128i [inherited]
```

12.279.2 Member Function Documentation

12.279.2.1 type_string()

```
static const std::string type_string ( ) [inline], [static]
```

12.279.2.2 set1() [1/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.279.2.3 set() [1/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1 ) [inline], [static]
```

12.279.2.4 gather() [1/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.279.2.5 load() [1/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.279.2.6 loadu() [1/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.279.2.7 store() [1/2]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.279.2.8 storeu() [1/2]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.279.2.9 stream() [1/2]

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static]
```

12.279.2.10 sra()

```
template<int s>
static INLINE CONST vect_t sra (
    const vect_t a ) [inline], [static]
```

12.279.2.11 greater()

```
static INLINE CONST vect_t greater (
    vect_t a,
    vect_t b ) [inline], [static]
```

12.279.2.12 lesser()

```
static INLINE CONST vect_t lesser (
    vect_t a,
    vect_t b ) [inline], [static]
```

12.279.2.13 greater_eq()

```
static INLINE CONST vect_t greater_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.279.2.14 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.279.2.15 mullo()

```
static INLINE CONST vect_t mullo (
    const vect_t x0,
    const vect_t x1 ) [inline], [static]
```

12.279.2.16 mulhi()

```
static INLINE CONST vect_t mulhi (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.279.2.17 mulx()

```
static INLINE CONST vect_t mulx (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.279.2.18 fmaddx()

```
static INLINE CONST vect_t fmaddx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.279.2.19 fmaddxin()

```
static INLINE vect_t fmaddxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```


12.279.2.20 fnmaddx()

```
static INLINE CONST vect_t fnmaddx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.279.2.21 fnmaddxin()

```
static INLINE vect_t fnmaddxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.279.2.22 fmsubx()

```
static INLINE CONST vect_t fmsubx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.279.2.23 fmsubxin()

```
static INLINE vect_t fmsubxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.279.2.24 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.279.2.25 valid()

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr], [inherited]
```

12.279.2.26 compliant()

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr], [inherited]
```

12.279.2.27 set1() [2/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static], [inherited]
```

12.279.2.28 set() [2/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1 ) [inline], [static], [inherited]
```

12.279.2.29 gather() [2/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static], [inherited]
```

12.279.2.30 get()

```
template<int idx>
static INLINE CONST scalar_t get (
    vect_t v ) [inline], [static], [inherited]
```

12.279.2.31 load() [2/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static], [inherited]
```

12.279.2.32 loadu() [2/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static], [inherited]
```

12.279.2.33 store() [2/2]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]
```

12.279.2.34 storeu() [2/2]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]
```

12.279.2.35 stream() [2/2]

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static], [inherited]
```

12.279.2.36 sll()

```
template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static], [inherited]
```

12.279.2.37 srl()

```
template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static], [inherited]
```

12.279.2.38 shuffle()

```
template<uint8_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static], [inherited]
```

12.279.2.39 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.40 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.41 unpacklo()

```
static INLINE CONST vect_t unpacklo (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.42 unpackhi()

```
static INLINE CONST vect_t unpackhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.43 unpacklohi()

```
static INLINE void unpacklohi (  
    vect_t & lo,  
    vect_t & hi,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.44 pack_even()

```
static INLINE CONST vect_t pack_even (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.45 pack_odd()

```
static INLINE CONST vect_t pack_odd (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.46 pack()

```
static INLINE void pack (  
    vect_t & even,  
    vect_t & odd,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.47 transpose()

```
static INLINE void transpose (  
    vect_t & r0,  
    vect_t & r1 ) [inline], [static], [inherited]
```

12.279.2.48 blend()

```
template<uint8_t s>
static INLINE CONST vect_t blend (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.49 add()

```
static INLINE CONST vect_t add (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.50 addin()

```
static INLINE vect_t addin (
    vect_t & a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.51 sub()

```
static INLINE CONST vect_t sub (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.52 subin()

```
static INLINE vect_t subin (
    vect_t & a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.53 mul()

```
static INLINE CONST vect_t mul (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.54 fmadd()

```
static INLINE CONST vect_t fmadd (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.55 fmaddin()

```
static INLINE vect_t fmaddin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.56 fnmadd()

```
static INLINE CONST vect_t fnmadd (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.57 fnmaddin()

```
static INLINE vect_t fnmaddin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.58 fmsub()

```
static INLINE CONST vect_t fmsub (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.59 fmsubin()

```
static INLINE vect_t fmsubin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.60 eq()

```
static INLINE CONST vect_t eq (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.61 round()

```
static INLINE CONST vect_t round (
    const vect_t a ) [inline], [static], [inherited]
```

12.279.2.62 mask_high()

```
static INLINE CONST vect_t mask_high ( ) [inline], [static], [inherited]
```

12.279.2.63 mulhi_fast()

```
INLINE CONST vect_t mulhi_fast (
    vect_t x,
    vect_t y ) [static], [inherited]
```

12.279.2.64 mod()

```
INLINE vect_t mod (
    vect_t & C,
    const __m128d & P,
    const __m128d & INVP,
    const __m128d & NEGP,
    const vect_t & POW50REM,
    const __m128d & MIN,
    const __m128d & MAX,
    __m128d & Q,
    __m128d & T ) [static], [inherited]
```

12.279.2.65 signbits()

```
static INLINE CONST vect_t signbits (
    const vect_t x ) [inline], [static], [protected], [inherited]
```

12.279.2.66 zero()

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.279.2.67 sll128()

```
template<uint8_t s>
static INLINE CONST vect_t sll128 (
    const vect_t a ) [inline], [static], [inherited]
```

12.279.2.68 srl128()

```
template<uint8_t s>
static INLINE CONST vect_t srl128 (
    const vect_t a ) [inline], [static], [inherited]
```

12.279.2.69 vand()

```
static INLINE CONST vect_t vand (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.70 vor()

```
static INLINE CONST vect_t vor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.71 vxor()

```
static INLINE CONST vect_t vxor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.2.72 vandnot()

```
static INLINE CONST vect_t vandnot (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.279.3 Field Documentation**12.279.3.1 vect_size**

```
const constexpr size_t vect_size = 2 [static], [constexpr], [inherited]
```

12.279.3.2 alignment


```
const constexpr size_t alignment = 16 [static], [constexpr], [inherited]
```

The documentation for this struct was generated from the following file:

- [simd128_int64.inl](#)

12.280 Simd128_impl< true, true, true, 2 > Struct Reference

Inheritance diagram for Simd128_impl< true, true, true, 2 >:



Data Structures

- union [Converter](#)

Public Types

- using [vect_t](#) = __m128i
- using [scalar_t](#) = int16_t
- using [aligned_allocator](#) = AlignedAllocator< [scalar_t](#), Alignment([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >
- template<class [Field](#) >
using [is_same_element](#) = std::is_same< typename [Field::Element](#), [scalar_t](#) >

Static Public Member Functions

- static const std::string [type_string](#) ()
- template<class T >
static constexpr bool [valid](#) (T *p)
- template<class T >
static constexpr bool [compliant](#) (T n)
- static [INLINE CONST vect_t set1](#) (const [scalar_t](#) x)
- static [INLINE CONST vect_t set](#) (const [scalar_t](#) x0, const [scalar_t](#) x1, const [scalar_t](#) x2, const [scalar_t](#) x3, const [scalar_t](#) x4, const [scalar_t](#) x5, const [scalar_t](#) x6, const [scalar_t](#) x7)
- template<class T >
static [INLINE PURE vect_t gather](#) (const [scalar_t](#) *const p, const T *const idx)
- static [INLINE PURE vect_t load](#) (const [scalar_t](#) *const p)
- static [INLINE PURE vect_t loadu](#) (const [scalar_t](#) *const p)
- static [INLINE](#) void [store](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE](#) void [storeu](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE](#) void [stream](#) ([scalar_t](#) *p, const [vect_t](#) v)
- template<int s>
static [INLINE CONST vect_t sll](#) (const [vect_t](#) a)
- template<int s>
static [INLINE CONST vect_t srl](#) (const [vect_t](#) a)
- template<int s>
static [INLINE CONST vect_t sra](#) (const [vect_t](#) a)
- template<uint32_t s>
static [INLINE CONST vect_t shuffle](#) (const [vect_t](#) a)
- static [INLINE CONST vect_t unpacklo_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpacklo](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) void [unpacklohi](#) ([vect_t](#) &lo, [vect_t](#) &hi, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_even](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_odd](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) void [pack](#) ([vect_t](#) &even, [vect_t](#) &odd, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) void [transpose](#) ([vect_t](#) &r0, [vect_t](#) &r1, [vect_t](#) &r2, [vect_t](#) &r3, [vect_t](#) &r4, [vect_t](#) &r5, [vect_t](#) &r6, [vect_t](#) &r7)

- `template<uint8_t s>`
`static INLINE CONST vect_t blend (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t add (const vect_t a, const vect_t b)`
- `static INLINE vect_t addin (vect_t &a, const vect_t b)`
- `static INLINE CONST vect_t sub (const vect_t a, const vect_t b)`
- `static INLINE vect_t subin (vect_t &a, const vect_t b)`
- `static INLINE CONST vect_t mullo (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t mul (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t mulhi (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t mulx (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fmaddd (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fmadddin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fmadddx (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fmadddxin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fnmadd (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fnmaddin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fnmaddx (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fnmaddxin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fmsub (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fmsubin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fmsubx (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fmsubxin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t eq (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t greater (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t lesser (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t greater_eq (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t lesser_eq (const vect_t a, const vect_t b)`
- `static INLINE CONST scalar_t hadd_to_scal (const vect_t a)`
- `static INLINE CONST vect_t round (const vect_t a)`
- `static INLINE vect_t mod (vect_t &C, const vect_t &P, const __m64 &INVP, const vect_t &NEGP, const vect_t &MIN, const vect_t &MAX, vect_t &Q, vect_t &T)`
- `static INLINE CONST vect_t zero ()`
- `template<uint8_t s>`
`static INLINE CONST vect_t sll128 (const vect_t a)`
- `template<uint8_t s>`
`static INLINE CONST vect_t srl128 (const vect_t a)`
- `static INLINE CONST vect_t vand (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t vor (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t vxor (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t vandnot (const vect_t a, const vect_t b)`

Static Public Attributes

- `static const constexpr size_t vect_size = 8`
- `static const constexpr size_t alignment = 16`

12.280.1 Member Typedef Documentation

12.280.1.1 vect_t

using `vect_t` = `__m128i`

12.280.1.2 scalar_t

using `scalar_t` = `int16_t`

12.280.1.3 aligned_allocator

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.280.1.4 aligned_vector

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.280.1.5 is_same_element

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.280.2 Member Function Documentation**12.280.2.1 type_string()**

```
static const std::string type_string ( ) [inline], [static]
```

12.280.2.2 valid()

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr]
```

12.280.2.3 compliant()

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr]
```

12.280.2.4 set1()

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.280.2.5 set()

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7 ) [inline], [static]
```

12.280.2.6 gather()

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.280.2.7 load()

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.280.2.8 loadu()

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.280.2.9 store()

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.280.2.10 storeu()

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.280.2.11 stream()

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static]
```

12.280.2.12 sll()

```
template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static]
```

12.280.2.13 srl()

```
template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static]
```

12.280.2.14 sra()

```
template<int s>
static INLINE CONST vect_t sra (
    const vect_t a ) [inline], [static]
```

12.280.2.15 shuffle()

```
template<uint32_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static]
```

12.280.2.16 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.17 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.18 unpacklo()

```
static INLINE CONST vect_t unpacklo (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.19 unpackhi()

```
static INLINE CONST vect_t unpackhi (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.20 unpacklohi()

```
static INLINE void unpacklohi (
    vect_t & lo,
    vect_t & hi,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.21 pack_even()

```
static INLINE CONST vect_t pack_even (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.22 pack_odd()

```
static INLINE CONST vect_t pack_odd (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.23 pack()

```
static INLINE void pack (
    vect_t & even,
    vect_t & odd,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.24 transpose()

```
static INLINE void transpose (
    vect_t & r0,
    vect_t & r1,
    vect_t & r2,
    vect_t & r3,
    vect_t & r4,
    vect_t & r5,
    vect_t & r6,
    vect_t & r7 ) [inline], [static]
```

12.280.2.25 blend()

```
template<uint8_t s>
static INLINE CONST vect_t blend (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.26 add()

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.27 addin()

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.280.2.28 sub()

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.29 subin()

```
static INLINE vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.280.2.30 mullo()

```
static INLINE CONST vect_t mullo (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.31 mul()

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.32 mulhi()

```
static INLINE CONST vect_t mulhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.33 mulx()

```
static INLINE CONST vect_t mulx (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.34 fmadd()

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.35 fmaddin()

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.36 fmaddx()

```
static INLINE CONST vect_t fmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.37 fmaddxin()

```
static INLINE vect_t fmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.38 fnmadd()

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.39 fnmaddin()

```
static INLINE vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.40 fnmaddx()

```
static INLINE CONST vect_t fnmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.41 fnmaddxin()

```
static INLINE vect_t fnmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.42 fmsub()

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.43 fmsubin()

```
static INLINE vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.280.2.44 fmsubx()

```
static INLINE CONST vect_t fmsubx (  
    const vect_t c,
```

```
const vect_t a,
const vect_t b ) [inline], [static]
```

12.280.2.45 fmsubxin()

```
static INLINE vect_t fmsubxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.46 eq()

```
static INLINE CONST vect_t eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.47 greater()

```
static INLINE CONST vect_t greater (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.48 lesser()

```
static INLINE CONST vect_t lesser (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.49 greater_eq()

```
static INLINE CONST vect_t greater_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.50 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.280.2.51 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.280.2.52 round()

```
static INLINE CONST vect_t round (
    const vect_t a ) [inline], [static]
```

12.280.2.53 mod()

```
static INLINE vect_t mod (
    vect_t & C,
    const vect_t & P,
    const __m64 & INVP,
    const vect_t & NEGP,
    const vect_t & MIN,
    const vect_t & MAX,
```

```

    vect_t & Q,
    vect_t & T ) [inline], [static]

```

12.280.2.54 zero()

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.280.2.55 sll128()

```

template<uint8_t s>
static INLINE CONST vect_t sll128 (
    const vect_t a ) [inline], [static], [inherited]

```

12.280.2.56 srl128()

```

template<uint8_t s>
static INLINE CONST vect_t srl128 (
    const vect_t a ) [inline], [static], [inherited]

```

12.280.2.57 vand()

```

static INLINE CONST vect_t vand (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]

```

12.280.2.58 vor()

```

static INLINE CONST vect_t vor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]

```

12.280.2.59 vxor()

```

static INLINE CONST vect_t vxor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]

```

12.280.2.60 vandnot()

```

static INLINE CONST vect_t vandnot (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]

```

12.280.3 Field Documentation

12.280.3.1 vect_size

```
const constexpr size_t vect_size = 8 [static], [constexpr]
```

12.280.3.2 alignment


```
const constexpr size_t alignment = 16 [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [simd128_int16.inl](#)

12.281 Simd128_impl< true, true, true, 4 > Struct Reference

Inheritance diagram for Simd128_impl< true, true, true, 4 >:



Data Structures

- union [Converter](#)

Public Types

- using [vect_t](#) = __m128i
- using [scalar_t](#) = int32_t
- using [aligned_allocator](#) = AlignedAllocator< [scalar_t](#), Alignment([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >
- template<class [Field](#) >
using [is_same_element](#) = std::is_same< typename [Field::Element](#), [scalar_t](#) >

Static Public Member Functions

- static const std::string [type_string](#) ()
- template<class T >
static constexpr bool [valid](#) (T *p)
- template<class T >
static constexpr bool [compliant](#) (T n)
- static [INLINE CONST vect_t set1](#) (const [scalar_t](#) x)
- static [INLINE CONST vect_t set](#) (const [scalar_t](#) x0, const [scalar_t](#) x1, const [scalar_t](#) x2, const [scalar_t](#) x3)
- template<class T >
static [INLINE PURE vect_t gather](#) (const [scalar_t](#) *const p, const T *const idx)
- static [INLINE PURE vect_t load](#) (const [scalar_t](#) *const p)
- static [INLINE PURE vect_t loadu](#) (const [scalar_t](#) *const p)
- static [INLINE void store](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void storeu](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void stream](#) ([scalar_t](#) *p, const [vect_t](#) v)
- template<int s>
static [INLINE CONST vect_t sll](#) (const [vect_t](#) a)
- template<int s>
static [INLINE CONST vect_t srl](#) (const [vect_t](#) a)
- template<int s>
static [INLINE CONST vect_t sra](#) (const [vect_t](#) a)
- template<uint8_t s>
static [INLINE CONST vect_t shuffle](#) (const [vect_t](#) a)
- static [INLINE CONST vect_t unpacklo_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpacklo](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE void unpacklohi](#) ([vect_t](#) &lo, [vect_t](#) &hi, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_even](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_odd](#) (const [vect_t](#) a, const [vect_t](#) b)

- static `INLINE` void `pack` (`vect_t` &even, `vect_t` &odd, const `vect_t` a, const `vect_t` b)
- static `INLINE` void `transpose` (`vect_t` &r0, `vect_t` &r1, `vect_t` &r2, `vect_t` &r3)
- template<uint8_t s>
 - static `INLINE` `CONST` `vect_t` `blend` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `add` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `addin` (`vect_t` &a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `sub` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `subin` (`vect_t` &a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `mullo` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `mulhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `mulx` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `fmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fnmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `fnmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fnmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `fmsubx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fmsubxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `greater` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `lesser` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `greater_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `lesser_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `scalar_t` `hadd_to_scal` (const `vect_t` a)
- static `INLINE` `CONST` `vect_t` `round` (const `vect_t` a)
- static `INLINE` `vect_t` `mod` (`vect_t` &C, const `vect_t` &P, const `vect_t` &INVP, const `vect_t` &NEGP, const `vect_t` &MIN, const `vect_t` &MAX, `vect_t` &Q, `vect_t` &T)
- static `INLINE` `CONST` `vect_t` `zero` ()
- template<uint8_t s>
 - static `INLINE` `CONST` `vect_t` `sll128` (const `vect_t` a)
- template<uint8_t s>
 - static `INLINE` `CONST` `vect_t` `srl128` (const `vect_t` a)
- static `INLINE` `CONST` `vect_t` `vand` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `vor` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `vxor` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `vandnot` (const `vect_t` a, const `vect_t` b)

Static Public Attributes

- static const constexpr size_t `vect_size` = 4
- static const constexpr size_t `alignment` = 16

12.281.1 Member Typedef Documentation

12.281.1.1 `vect_t`

```
using vect_t = __m128i
```

12.281.1.2 `scalar_t`

```
using scalar_t = int32_t
```

12.281.1.3 aligned_allocator

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.281.1.4 aligned_vector

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.281.1.5 is_same_element

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.281.2 Member Function Documentation**12.281.2.1 type_string()**

```
static const std::string type_string ( ) [inline], [static]
```

12.281.2.2 valid()

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr]
```

12.281.2.3 compliant()

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr]
```

12.281.2.4 set1()

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.281.2.5 set()

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3 ) [inline], [static]
```

12.281.2.6 gather()

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.281.2.7 load()

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.281.2.8 loadu()

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.281.2.9 store()

```
static INLINE void store (  
    scalar_t * p,  
    vect_t v ) [inline], [static]
```

12.281.2.10 storeu()

```
static INLINE void storeu (  
    scalar_t * p,  
    vect_t v ) [inline], [static]
```

12.281.2.11 stream()

```
static INLINE void stream (  
    scalar_t * p,  
    const vect_t v ) [inline], [static]
```

12.281.2.12 sll()

```
template<int s>  
static INLINE CONST vect_t sll (  
    const vect_t a ) [inline], [static]
```

12.281.2.13 srl()

```
template<int s>  
static INLINE CONST vect_t srl (  
    const vect_t a ) [inline], [static]
```

12.281.2.14 sra()

```
template<int s>  
static INLINE CONST vect_t sra (  
    const vect_t a ) [inline], [static]
```

12.281.2.15 shuffle()

```
template<uint8_t s>  
static INLINE CONST vect_t shuffle (  
    const vect_t a ) [inline], [static]
```

12.281.2.16 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.17 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.18 unpacklo()

```
static INLINE CONST vect_t unpacklo (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.19 unpackhi()

```
static INLINE CONST vect_t unpackhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.20 unpacklohi()

```
static INLINE void unpacklohi (  
    vect_t & lo,  
    vect_t & hi,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.21 pack_even()

```
static INLINE CONST vect_t pack_even (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.22 pack_odd()

```
static INLINE CONST vect_t pack_odd (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.23 pack()

```
static INLINE void pack (  
    vect_t & even,  
    vect_t & odd,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.24 transpose()

```
static INLINE void transpose (  
    vect_t & r0,  
    vect_t & r1,  
    vect_t & r2,  
    vect_t & r3 ) [inline], [static]
```

12.281.2.25 blend()

```
template<uint8_t s>  
static INLINE CONST vect_t blend (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.26 add()

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.27 addin()

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.281.2.28 sub()

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.29 subin()

```
static INLINE vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.281.2.30 mullo()

```
static INLINE CONST vect_t mullo (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.31 mul()

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.32 mulhi()

```
static INLINE CONST vect_t mulhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.33 mulx()

```
static INLINE CONST vect_t mulx (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.34 fmadd()

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.35 fmaddin()

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.36 fmaddx()

```
static INLINE CONST vect_t fmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.37 fmaddxin()

```
static INLINE vect_t fmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.38 fnmadd()

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.39 fnmaddin()

```
static INLINE vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.40 fnmaddx()

```
static INLINE CONST vect_t fnmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.41 fnmaddxin()

```
static INLINE vect_t fnmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.42 fmsub()

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.43 fmsubin()

```
static INLINE vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.44 fmsubx()

```
static INLINE CONST vect_t fmsubx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.281.2.45 fmsubxin()

```
static INLINE vect_t fmsubxin (  
    vect_t & c,
```

```
const vect_t a,
const vect_t b ) [inline], [static]
```

12.281.2.46 eq()

```
static INLINE CONST vect_t eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.281.2.47 greater()

```
static INLINE CONST vect_t greater (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.281.2.48 lesser()

```
static INLINE CONST vect_t lesser (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.281.2.49 greater_eq()

```
static INLINE CONST vect_t greater_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.281.2.50 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.281.2.51 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.281.2.52 round()

```
static INLINE CONST vect_t round (
    const vect_t a ) [inline], [static]
```

12.281.2.53 mod()

```
static INLINE vect_t mod (
    vect_t & C,
    const vect_t & P,
    const vect_t & INVP,
    const vect_t & NEGP,
    const vect_t & MIN,
    const vect_t & MAX,
    vect_t & Q,
    vect_t & T ) [inline], [static]
```

12.281.2.54 zero()

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.281.2.55 sll128()

```
template<uint8_t s>
static INLINE CONST vect_t sll128 (
    const vect_t a ) [inline], [static], [inherited]
```

12.281.2.56 srl128()

```
template<uint8_t s>
static INLINE CONST vect_t srl128 (
    const vect_t a ) [inline], [static], [inherited]
```

12.281.2.57 vand()

```
static INLINE CONST vect_t vand (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.281.2.58 vor()

```
static INLINE CONST vect_t vor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.281.2.59 vxor()

```
static INLINE CONST vect_t vxor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.281.2.60 vandnot()

```
static INLINE CONST vect_t vandnot (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.281.3 Field Documentation**12.281.3.1 vect_size**

```
const constexpr size_t vect_size = 4 [static], [constexpr]
```

12.281.3.2 alignment


```
const constexpr size_t alignment = 16 [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [simd128_int32.inl](#)

12.282 Simd128_impl< true, true, true, 8 > Struct Reference

Inheritance diagram for Simd128_impl< true, true, true, 8 >:



Data Structures

- union [Converter](#)

Public Types

- using [vect_t](#) = __m128i
- using [scalar_t](#) = int64_t
- using [aligned_allocator](#) = AlignedAllocator< [scalar_t](#), Alignment([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >
- template<class [Field](#) >
using [is_same_element](#) = std::is_same< typename [Field::Element](#), [scalar_t](#) >

Static Public Member Functions

- static const std::string [type_string](#) ()
- template<class T >
static constexpr bool [valid](#) (T *p)
- template<class T >
static constexpr bool [compliant](#) (T n)
- static [INLINE CONST vect_t set1](#) (const [scalar_t](#) x)
- static [INLINE CONST vect_t set](#) (const [scalar_t](#) x0, const [scalar_t](#) x1)
- template<class T >
static [INLINE PURE vect_t gather](#) (const [scalar_t](#) *const p, const T *const idx)
- template<int idx>
static [INLINE CONST scalar_t get](#) ([vect_t](#) v)
- static [INLINE PURE vect_t load](#) (const [scalar_t](#) *const p)
- static [INLINE PURE vect_t loadu](#) (const [scalar_t](#) *const p)
- static [INLINE void store](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void storeu](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void stream](#) ([scalar_t](#) *p, const [vect_t](#) v)
- template<int s>
static [INLINE CONST vect_t sll](#) (const [vect_t](#) a)
- template<int s>
static [INLINE CONST vect_t srl](#) (const [vect_t](#) a)
- template<int s>
static [INLINE CONST vect_t sra](#) (const [vect_t](#) a)
- template<uint8_t s>
static [INLINE CONST vect_t shuffle](#) (const [vect_t](#) a)
- static [INLINE CONST vect_t unpacklo_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpacklo](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE void unpacklohi](#) ([vect_t](#) &lo, [vect_t](#) &hi, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_even](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_odd](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE void pack](#) ([vect_t](#) &even, [vect_t](#) &odd, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE void transpose](#) ([vect_t](#) &r0, [vect_t](#) &r1)

- `template<uint8_t s>`
`static INLINE CONST vect_t blend (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t add (const vect_t a, const vect_t b)`
- `static INLINE vect_t addin (vect_t &a, const vect_t b)`
- `static INLINE CONST vect_t sub (const vect_t a, const vect_t b)`
- `static INLINE vect_t subin (vect_t &a, const vect_t b)`
- `static INLINE CONST vect_t mullo (const vect_t x0, const vect_t x1)`
- `static INLINE CONST vect_t mul (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t mulhi (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t mulx (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fmadd (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fmaddin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fmaddx (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fmaddxin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fnmadd (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fnmaddin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fnmaddx (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fnmaddxin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fmsub (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fmsubin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fmsubx (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fmsubxin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t eq (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t greater (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t lesser (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t greater_eq (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t lesser_eq (const vect_t a, const vect_t b)`
- `static INLINE CONST scalar_t hadd_to_scal (const vect_t a)`
- `static INLINE CONST vect_t round (const vect_t a)`
- `static INLINE CONST vect_t mask_high ()`
- `static INLINE CONST vect_t mulhi_fast (vect_t x, vect_t y)`
- `static INLINE vect_t mod (vect_t &C, const __m128d &P, const __m128d &INVP, const __m128d &NEGP, const vect_t &POW50REM, const __m128d &MIN, const __m128d &MAX, __m128d &Q, __m128d &T)`
- `static INLINE CONST vect_t zero ()`
- `template<uint8_t s>`
`static INLINE CONST vect_t sll128 (const vect_t a)`
- `template<uint8_t s>`
`static INLINE CONST vect_t srl128 (const vect_t a)`
- `static INLINE CONST vect_t vand (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t vor (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t vxor (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t vandnot (const vect_t a, const vect_t b)`

Static Public Attributes

- `static const constexpr size_t vect_size = 2`
- `static const constexpr size_t alignment = 16`

Static Protected Member Functions

- `static INLINE CONST vect_t signbits (const vect_t x)`

12.282.1 Member Typedef Documentation

12.282.1.1 vect_t

```
using vect_t = __m128i
```

12.282.1.2 scalar_t

```
using scalar_t = int64_t
```

12.282.1.3 aligned_allocator

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.282.1.4 aligned_vector

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.282.1.5 is_same_element

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.282.2 Member Function Documentation

12.282.2.1 type_string()

```
static const std::string type_string ( ) [inline], [static]
```

12.282.2.2 valid()

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr]
```

12.282.2.3 compliant()

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr]
```

12.282.2.4 set1()

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.282.2.5 set()

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1 ) [inline], [static]
```

12.282.2.6 gather()

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.282.2.7 get()

```
template<int idx>
static INLINE CONST scalar_t get (
    vect_t v ) [inline], [static]
```

12.282.2.8 load()

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.282.2.9 loadu()

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.282.2.10 store()

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.282.2.11 storeu()

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.282.2.12 stream()

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static]
```

12.282.2.13 sll()

```
template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static]
```

12.282.2.14 srl()

```
template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static]
```

12.282.2.15 sra()

```
template<int s>
static INLINE CONST vect_t sra (
    const vect_t a ) [inline], [static]
```

12.282.2.16 shuffle()

```
template<uint8_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static]
```

12.282.2.17 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.282.2.18 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.19 unpacklo()

```
static INLINE CONST vect_t unpacklo (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.20 unpackhi()

```
static INLINE CONST vect_t unpackhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.21 unpacklohi()

```
static INLINE void unpacklohi (  
    vect_t & lo,  
    vect_t & hi,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.22 pack_even()

```
static INLINE CONST vect_t pack_even (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.23 pack_odd()

```
static INLINE CONST vect_t pack_odd (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.24 pack()

```
static INLINE void pack (  
    vect_t & even,  
    vect_t & odd,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.25 transpose()

```
static INLINE void transpose (  
    vect_t & r0,  
    vect_t & r1 ) [inline], [static]
```

12.282.2.26 blend()

```
template<uint8_t s>  
static INLINE CONST vect_t blend (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.27 add()

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.28 addin()

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.282.2.29 sub()

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.30 subin()

```
static INLINE vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.282.2.31 mullo()

```
static INLINE CONST vect_t mullo (  
    const vect_t x0,  
    const vect_t x1 ) [inline], [static]
```

12.282.2.32 mul()

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.33 mulhi()

```
static INLINE CONST vect_t mulhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.34 mulx()

```
static INLINE CONST vect_t mulx (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.35 fmadd()

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.36 fmaddin()

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.37 fmaddx()

```
static INLINE CONST vect_t fmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.38 fmaddxin()

```
static INLINE vect_t fmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.39 fnmadd()

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.40 fnmaddin()

```
static INLINE vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.41 fnmaddx()

```
static INLINE CONST vect_t fnmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.42 fnmaddxin()

```
static INLINE vect_t fnmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.43 fmsub()

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.44 fmsubin()

```
static INLINE vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.45 fmsubx()

```
static INLINE CONST vect_t fmsubx (  
    const vect_t c,
```

```
const vect_t a,  
const vect_t b ) [inline], [static]
```

12.282.2.46 fmsubxin()

```
static INLINE vect_t fmsubxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.47 eq()

```
static INLINE CONST vect_t eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.48 greater()

```
static INLINE CONST vect_t greater (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.49 lesser()

```
static INLINE CONST vect_t lesser (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.50 greater_eq()

```
static INLINE CONST vect_t greater_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.51 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.282.2.52 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (  
    const vect_t a ) [inline], [static]
```

12.282.2.53 round()

```
static INLINE CONST vect_t round (  
    const vect_t a ) [inline], [static]
```

12.282.2.54 mask_high()

```
static INLINE CONST vect_t mask_high ( ) [inline], [static]
```

12.282.2.55 mulhi_fast()

```
INLINE CONST vect_t mulhi_fast (  
    vect_t x,  
    vect_t y ) [static]
```


12.282.2.56 mod()

```

INLINE vect_t mod (
    vect_t & C,
    const __m128d & P,
    const __m128d & INVP,
    const __m128d & NEGP,
    const vect_t & POW50REM,
    const __m128d & MIN,
    const __m128d & MAX,
    __m128d & Q,
    __m128d & T ) [static]

```

12.282.2.57 signbits()

```

static INLINE CONST vect_t signbits (
    const vect_t x ) [inline], [static], [protected]

```

12.282.2.58 zero()

```

static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]

```

12.282.2.59 sll128()

```

template<uint8_t s>
static INLINE CONST vect_t sll128 (
    const vect_t a ) [inline], [static], [inherited]

```

12.282.2.60 srl128()

```

template<uint8_t s>
static INLINE CONST vect_t srl128 (
    const vect_t a ) [inline], [static], [inherited]

```

12.282.2.61 vand()

```

static INLINE CONST vect_t vand (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]

```

12.282.2.62 vor()

```

static INLINE CONST vect_t vor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]

```

12.282.2.63 vxor()

```

static INLINE CONST vect_t vxor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]

```

12.282.2.64 vandnot()

```

static INLINE CONST vect_t vandnot (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]

```

12.282.3 Field Documentation

12.282.3.1 vect_size

```
const constexpr size_t vect_size = 2 [static], [constexpr]
```

12.282.3.2 alignment


```
const constexpr size_t alignment = 16 [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [simd128_int64.inl](#)

12.283 Simd128i_base Struct Reference

Inheritance diagram for Simd128i_base:



Public Types

- using [vect_t](#) = __m128i

Static Public Member Functions

- static [INLINE CONST vect_t zero](#) ()
- template<uint8_t s>
static [INLINE CONST vect_t sll128](#) (const [vect_t](#) a)
- template<uint8_t s>
static [INLINE CONST vect_t srl128](#) (const [vect_t](#) a)
- static [INLINE CONST vect_t vand](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t vor](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t vxor](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t vandnot](#) (const [vect_t](#) a, const [vect_t](#) b)

12.283.1 Member Typedef Documentation

12.283.1.1 vect_t

```
using vect\_t = __m128i
```

12.283.2 Member Function Documentation

12.283.2.1 zero()

```
static INLINE CONST vect\_t zero ( ) [inline], [static]
```

12.283.2.2 sll128()

```
template<uint8_t s>
static INLINE CONST vect\_t sll128 (
    const vect\_t a ) [inline], [static]
```

12.283.2.3 srl128()

```
template<uint8_t s>
static INLINE CONST vect_t srl128 (
    const vect_t a ) [inline], [static]
```

12.283.2.4 vand()

```
static INLINE CONST vect_t vand (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.283.2.5 vor()

```
static INLINE CONST vect_t vor (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.283.2.6 vxor()

```
static INLINE CONST vect_t vxor (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.283.2.7 vandnot()

```
static INLINE CONST vect_t vandnot (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

The documentation for this struct was generated from the following file:

- [simd128.inl](#)


12.284 Simd256_impl< ArithType, Int, Signed, Size > Struct Template Reference

The documentation for this struct was generated from the following file:

- [simd256.inl](#)

12.285 Simd256_impl< true, false, true, 4 > Struct Reference

Inheritance diagram for Simd256_impl< true, false, true, 4 >:




The documentation for this struct was generated from the following file:

- [simd256_float.inl](#)

12.286 Simd256_impl< true, false, true, 8 > Struct Reference

Inheritance diagram for Simd256_impl< true, false, true, 8 >:



Data Structures

- union [Converter](#)

Public Types

- using [vect_t](#) = __m256d
- using [scalar_t](#) = double
- using [aligned_allocator](#) = AlignedAllocator< [scalar_t](#), Alignment([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >
- template<class [Field](#) >
using [is_same_element](#) = std::is_same< typename [Field::Element](#), [scalar_t](#) >

Static Public Member Functions

- static const std::string [type_string](#) ()
- template<class T >
static constexpr bool [valid](#) (T *p)
- template<class T >
static constexpr bool [compliant](#) (T n)
- static [INLINE CONST vect_t zero](#) ()
- static [INLINE CONST vect_t set1](#) (const [scalar_t](#) x)
- static [INLINE CONST vect_t set](#) (const [scalar_t](#) x1, const [scalar_t](#) x2, const [scalar_t](#) x3, const [scalar_t](#) x4)
- template<class T >
static [INLINE PURE vect_t gather](#) (const [scalar_t](#) *const p, const T *const idx)
- static [INLINE PURE vect_t load](#) (const [scalar_t](#) *const p)
- static [INLINE PURE vect_t loadu](#) (const [scalar_t](#) *const p)
- static [INLINE void store](#) (const [scalar_t](#) *p, const [vect_t](#) v)
- static [INLINE void storeu](#) (const [scalar_t](#) *p, const [vect_t](#) v)
- static [INLINE void stream](#) (const [scalar_t](#) *p, const [vect_t](#) v)
- static [INLINE CONST vect_t unpacklo_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpacklo](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE void unpacklohi](#) ([vect_t](#) &lo, [vect_t](#) &hi, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_even](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_odd](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE void pack](#) ([vect_t](#) &even, [vect_t](#) &odd, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE void transpose](#) ([vect_t](#) &r0, [vect_t](#) &r1, [vect_t](#) &r2, [vect_t](#) &r3)
- template<uint8_t s>
static [INLINE CONST vect_t blend](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t blendv](#) (const [vect_t](#) a, const [vect_t](#) b, const [vect_t](#) mask)
- static [INLINE CONST vect_t add](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE vect_t addin](#) ([vect_t](#) &a, const [vect_t](#) b)
- static [INLINE CONST vect_t sub](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t subin](#) ([vect_t](#) &a, const [vect_t](#) b)

- static `INLINE CONST vect_t mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mulin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t div` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t greater` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t greater_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vand` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vxor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vandnot` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t floor` (const `vect_t` a)
- static `INLINE CONST vect_t ceil` (const `vect_t` a)
- static `INLINE CONST vect_t round` (const `vect_t` a)
- static `INLINE CONST vect_t hadd` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST scalar_t hadd_to_scal` (const `vect_t` a)
- static `INLINE vect_t mod` (`vect_t` &C, const `vect_t` &P, const `vect_t` &INVP, const `vect_t` &NEGP, const `vect_t` &MIN, const `vect_t` &MAX, `vect_t` &Q, `vect_t` &T)

Static Public Attributes

- static const constexpr size_t `vect_size` = 4
- static const constexpr size_t `alignment` = 32

12.286.1 Member Typedef Documentation

12.286.1.1 vect_t

```
using vect_t = __m256d
```

12.286.1.2 scalar_t

```
using scalar_t = double
```

12.286.1.3 aligned_allocator

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.286.1.4 aligned_vector

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.286.1.5 is_same_element

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.286.2 Member Function Documentation

12.286.2.1 type_string()

```
static const std::string type_string ( ) [inline], [static]
```

12.286.2.2 valid()

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr]
```

12.286.2.3 compliant()

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr]
```

12.286.2.4 zero()

```
static INLINE CONST vect_t zero ( ) [inline], [static]
```

12.286.2.5 set1()

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.286.2.6 set()

```
static INLINE CONST vect_t set (
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4 ) [inline], [static]
```

12.286.2.7 gather()

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.286.2.8 load()

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.286.2.9 loadu()

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.286.2.10 store()

```
static INLINE void store (
    const scalar_t * p,
    const vect_t v ) [inline], [static]
```

12.286.2.11 storeu()

```
static INLINE void storeu (
    const scalar_t * p,
    const vect_t v ) [inline], [static]
```

12.286.2.12 stream()

```
static INLINE void stream (  
    const scalar_t * p,  
    const vect_t v ) [inline], [static]
```

12.286.2.13 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.14 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.15 unpacklo()

```
static INLINE CONST vect_t unpacklo (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.16 unpackhi()

```
static INLINE CONST vect_t unpackhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.17 unpacklohi()

```
static INLINE void unpacklohi (  
    vect_t & lo,  
    vect_t & hi,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.18 pack_even()

```
static INLINE CONST vect_t pack_even (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.19 pack_odd()

```
static INLINE CONST vect_t pack_odd (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.20 pack()

```
static INLINE void pack (  
    vect_t & even,  
    vect_t & odd,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.21 transpose()

```
static INLINE void transpose (  
    vect_t & r0,  
    vect_t & r1,  
    vect_t & r2,  
    vect_t & r3 ) [inline], [static]
```

12.286.2.22 blend()

```
template<uint8_t s>  
static INLINE CONST vect_t blend (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.23 blendv()

```
static INLINE CONST vect_t blendv (  
    const vect_t a,  
    const vect_t b,  
    const vect_t mask ) [inline], [static]
```

12.286.2.24 add()

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.25 addin()

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.286.2.26 sub()

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.27 subin()

```
static INLINE CONST vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.286.2.28 mul()

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.29 mulin()

```
static INLINE CONST vect_t mulin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```


12.286.2.30 div()

```
static INLINE CONST vect_t div (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.31 fmadd()

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.32 fmaddin()

```
static INLINE CONST vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.33 fnmadd()

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.34 fnmaddin()

```
static INLINE CONST vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.35 fmsub()

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.36 fmsubin()

```
static INLINE CONST vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.37 eq()

```
static INLINE CONST vect_t eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.38 lesser()

```
static INLINE CONST vect_t lesser (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.39 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.40 greater()

```
static INLINE CONST vect_t greater (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.41 greater_eq()

```
static INLINE CONST vect_t greater_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.42 vand()

```
static INLINE CONST vect_t vand (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.43 vor()

```
static INLINE CONST vect_t vor (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.44 vxor()

```
static INLINE CONST vect_t vxor (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.45 vandnot()

```
static INLINE CONST vect_t vandnot (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.286.2.46 floor()

```
static INLINE CONST vect_t floor (  
    const vect_t a ) [inline], [static]
```

12.286.2.47 ceil()

```
static INLINE CONST vect_t ceil (  
    const vect_t a ) [inline], [static]
```

12.286.2.48 round()

```
static INLINE CONST vect_t round (  
    const vect_t a ) [inline], [static]
```

12.286.2.49 hadd()

```
static INLINE CONST vect_t hadd (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.286.2.50 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.286.2.51 mod()

```
static INLINE vect_t mod (
    vect_t & C,
    const vect_t & P,
    const vect_t & INV_P,
    const vect_t & NEG_P,
    const vect_t & MIN,
    const vect_t & MAX,
    vect_t & Q,
    vect_t & T ) [inline], [static]
```

12.286.3 Field Documentation**12.286.3.1 vect_size**

```
const constexpr size_t vect_size = 4 [static], [constexpr]
```

12.286.3.2 alignment


```
const constexpr size_t alignment = 32 [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [simd256_double.inl](#)

12.287 Simd256_impl< true, true, false, 2 > Struct Reference

Inheritance diagram for Simd256_impl< true, true, false, 2 >:

**Data Structures**

- union [Converter](#)

Public Types

- using [scalar_t](#) = uint16_t
- using [aligned_allocator](#) = AlignedAllocator< [scalar_t](#), Alignment([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >

- `template<class Field >`
`using is_same_element = std::is_same< typename Field::Element, scalar_t >`
- `using simdHalf = Simd128< scalar_t >`
- `using vect_t = __m256i`
- `using half_t = __m128i`

Static Public Member Functions

- `static const std::string type_string ()`
- `static INLINE CONST vect_t set1 (const scalar_t x)`
- `static INLINE CONST vect_t set (const scalar_t x0, const scalar_t x1, const scalar_t x2, const scalar_t x3, const scalar_t x4, const scalar_t x5, const scalar_t x6, const scalar_t x7, const scalar_t x8, const scalar_t x9, const scalar_t x10, const scalar_t x11, const scalar_t x12, const scalar_t x13, const scalar_t x14, const scalar_t x15)`
- `template<class T >`
`static INLINE PURE vect_t gather (const scalar_t *const p, const T *const idx)`
- `static INLINE PURE vect_t load (const scalar_t *const p)`
- `static INLINE PURE vect_t loadu (const scalar_t *const p)`
- `static INLINE void store (scalar_t *p, vect_t v)`
- `static INLINE void storeu (scalar_t *p, vect_t v)`
- `static INLINE void stream (scalar_t *p, const vect_t v)`
- `template<int s>`
`static INLINE CONST vect_t sra (const vect_t a)`
- `static INLINE CONST vect_t greater (vect_t a, vect_t b)`
- `static INLINE CONST vect_t lesser (vect_t a, vect_t b)`
- `static INLINE CONST vect_t greater_eq (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t lesser_eq (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t mulhi (const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t mulx (vect_t a, vect_t b)`
- `static INLINE CONST vect_t fmaddx (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fmaddxin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fnmaddx (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fnmaddxin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST vect_t fmsubx (const vect_t c, const vect_t a, const vect_t b)`
- `static INLINE vect_t fmsubxin (vect_t &c, const vect_t a, const vect_t b)`
- `static INLINE CONST scalar_t hadd_to_scal (const vect_t a)`
- `template<class T >`
`static constexpr bool valid (T *p)`
- `template<class T >`
`static constexpr bool compliant (T n)`
- `static INLINE CONST vect_t set1 (const scalar_t x)`
- `static INLINE CONST vect_t set (const scalar_t x0, const scalar_t x1, const scalar_t x2, const scalar_t x3, const scalar_t x4, const scalar_t x5, const scalar_t x6, const scalar_t x7, const scalar_t x8, const scalar_t x9, const scalar_t x10, const scalar_t x11, const scalar_t x12, const scalar_t x13, const scalar_t x14, const scalar_t x15)`
- `template<class T >`
`static INLINE PURE vect_t gather (const scalar_t *const p, const T *const idx)`
- `static INLINE PURE vect_t load (const scalar_t *const p)`
- `static INLINE PURE vect_t loadu (const scalar_t *const p)`
- `static INLINE void store (scalar_t *p, vect_t v)`
- `static INLINE void storeu (scalar_t *p, vect_t v)`
- `static INLINE void stream (scalar_t *p, const vect_t v)`
- `template<int s>`
`static INLINE CONST vect_t sll (const vect_t a)`
- `template<int s>`
`static INLINE CONST vect_t srl (const vect_t a)`

- `template<uint64_t s>`
static `INLINE CONST vect_t shuffle` (const `vect_t` a)
- static `INLINE CONST vect_t unpacklo_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpacklo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE void unpacklohi` (`vect_t` &lo, `vect_t` &hi, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_even` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_odd` (const `vect_t` a, const `vect_t` b)
- static `INLINE void pack` (`vect_t` &even, `vect_t` &odd, const `vect_t` a, const `vect_t` b)
- static `INLINE void transpose` (`vect_t` &r0, `vect_t` &r1, `vect_t` &r2, `vect_t` &r3, `vect_t` &r4, `vect_t` &r5, `vect_t` &r6, `vect_t` &r7, `vect_t` &r8, `vect_t` &r9, `vect_t` &r10, `vect_t` &r11, `vect_t` &r12, `vect_t` &r13, `vect_t` &r14, `vect_t` &r15)
- `template<uint16_t s, typename std::enable_if<(s & 0x00ff) == (s > > 8)>::type * = nullptr>`
static `INLINE vect_t blend` (const `vect_t` a, const `vect_t` b)
- `template<uint16_t s, typename std::enable_if<(s & 0x00ff) != (s > > 8)>::type * = nullptr>`
static `INLINE vect_t blend` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t add` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t addin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t sub` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t subin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t mullo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmadin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fnmadin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t round` (const `vect_t` a)
- static `INLINE vect_t mod` (`vect_t` &C, const `vect_t` &P, const `vect_t` &INVP, const `vect_t` &NEGP, const `vect_t` &MIN, const `vect_t` &MAX, `vect_t` &Q, `vect_t` &T)
- static `INLINE CONST vect_t zero` ()

Static Public Attributes

- static const constexpr size_t `vect_size` = 16
- static const constexpr size_t `alignment` = 32

12.287.1 Member Typedef Documentation

12.287.1.1 scalar_t

```
using scalar_t = uint16_t
```

12.287.1.2 aligned_allocator

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.287.1.3 aligned_vector

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.287.1.4 is_same_element

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.287.1.5 simdHalf

```
using simdHalf = Simd128<scalar_t>
```

12.287.1.6 vect_t

```
using vect_t = __m256i [inherited]
```

12.287.1.7 half_t

```
using half_t = __m128i [inherited]
```

12.287.2 Member Function Documentation**12.287.2.1 type_string()**

```
static const std::string type_string ( ) [inline], [static]
```

12.287.2.2 set1() [1/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.287.2.3 set() [1/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7,
    const scalar_t x8,
    const scalar_t x9,
    const scalar_t x10,
    const scalar_t x11,
    const scalar_t x12,
    const scalar_t x13,
    const scalar_t x14,
    const scalar_t x15 ) [inline], [static]
```

12.287.2.4 gather() [1/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.287.2.5 load() [1/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.287.2.6 loadu() [1/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.287.2.7 store() [1/2]

```
static INLINE void store (  
    scalar_t * p,  
    vect_t v ) [inline], [static]
```

12.287.2.8 storeu() [1/2]

```
static INLINE void storeu (  
    scalar_t * p,  
    vect_t v ) [inline], [static]
```

12.287.2.9 stream() [1/2]

```
static INLINE void stream (  
    scalar_t * p,  
    const vect_t v ) [inline], [static]
```

12.287.2.10 sra()

```
template<int s>  
static INLINE CONST vect_t sra (  
    const vect_t a ) [inline], [static]
```

12.287.2.11 greater()

```
static INLINE CONST vect_t greater (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.287.2.12 lesser()

```
static INLINE CONST vect_t lesser (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.287.2.13 greater_eq()

```
static INLINE CONST vect_t greater_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.287.2.14 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.287.2.15 mulhi()

```
static INLINE CONST vect_t mulhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.287.2.16 mulx()

```
static INLINE CONST vect_t mulx (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.287.2.17 fmaddx()

```
static INLINE CONST vect_t fmaddx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.287.2.18 fmaddxin()

```
static INLINE vect_t fmaddxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.287.2.19 fnmaddx()

```
static INLINE CONST vect_t fnmaddx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.287.2.20 fnmaddxin()

```
static INLINE vect_t fnmaddxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.287.2.21 fmsubx()

```
static INLINE CONST vect_t fmsubx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.287.2.22 fmsubxin()

```
static INLINE vect_t fmsubxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.287.2.23 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.287.2.24 valid()

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr], [inherited]
```

12.287.2.25 compliant()

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr], [inherited]
```


12.287.2.26 set1() [2/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static], [inherited]
```

12.287.2.27 set() [2/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7,
    const scalar_t x8,
    const scalar_t x9,
    const scalar_t x10,
    const scalar_t x11,
    const scalar_t x12,
    const scalar_t x13,
    const scalar_t x14,
    const scalar_t x15 ) [inline], [static], [inherited]
```

12.287.2.28 gather() [2/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static], [inherited]
```

12.287.2.29 load() [2/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static], [inherited]
```

12.287.2.30 loadu() [2/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static], [inherited]
```

12.287.2.31 store() [2/2]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]
```

12.287.2.32 storeu() [2/2]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]
```

12.287.2.33 stream() [2/2]

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static], [inherited]
```

12.287.2.34 sll()

```
template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static], [inherited]
```

12.287.2.35 srl()

```
template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static], [inherited]
```

12.287.2.36 shuffle()

```
template<uint64_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static], [inherited]
```

12.287.2.37 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.38 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.39 unpacklo()

```
static INLINE CONST vect_t unpacklo (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.40 unpackhi()

```
static INLINE CONST vect_t unpackhi (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.41 unpacklohi()

```
static INLINE void unpacklohi (
    vect_t & lo,
    vect_t & hi,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.42 pack_even()

```
static INLINE CONST vect_t pack_even (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.43 pack_odd()

```
static INLINE CONST vect_t pack_odd (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.44 pack()

```
static INLINE void pack (
    vect_t & even,
    vect_t & odd,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.45 transpose()

```
static INLINE void transpose (
    vect_t & r0,
    vect_t & r1,
    vect_t & r2,
    vect_t & r3,
    vect_t & r4,
    vect_t & r5,
    vect_t & r6,
    vect_t & r7,
    vect_t & r8,
    vect_t & r9,
    vect_t & r10,
    vect_t & r11,
    vect_t & r12,
    vect_t & r13,
    vect_t & r14,
    vect_t & r15 ) [inline], [static], [inherited]
```

12.287.2.46 blend() [1/2]

```
template<uint16_t s, typename std::enable_if<(s &0x00ff)==(s > > 8)>::type * = nullptr>
static INLINE vect_t blend (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.47 blend() [2/2]

```
template<uint16_t s, typename std::enable_if<(s &0x00ff) !=(s > > 8)>::type * = nullptr>
static INLINE vect_t blend (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.48 add()

```
static INLINE CONST vect_t add (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.49 addin()

```
static INLINE vect_t addin (
    vect_t & a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.50 sub()

```
static INLINE CONST vect_t sub (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.51 subin()

```
static INLINE vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.52 mullo()

```
static INLINE CONST vect_t mullo (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.53 mul()

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.54 fmadd()

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.55 fmaddin()

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.56 fnmadd()

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.57 fnmaddin()

```
static INLINE vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.58 fmsub()

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.59 fmsubin()

```
static INLINE vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.60 eq()

```
static INLINE CONST vect_t eq (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.287.2.61 round()

```
static INLINE CONST vect_t round (
    const vect_t a ) [inline], [static], [inherited]
```

12.287.2.62 mod()

```
static INLINE vect_t mod (
    vect_t & C,
    const vect_t & P,
    const vect_t & INVP,
    const vect_t & NEGP,
    const vect_t & MIN,
    const vect_t & MAX,
    vect_t & Q,
    vect_t & T ) [inline], [static], [inherited]
```

12.287.2.63 zero()

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.287.3 Field Documentation**12.287.3.1 vect_size**

```
const constexpr size_t vect_size = 16 [static], [constexpr], [inherited]
```

12.287.3.2 alignment


```
const constexpr size_t alignment = 32 [static], [constexpr], [inherited]
```

The documentation for this struct was generated from the following file:

- [simd256_int16.inl](#)

12.288 Simd256_impl< true, true, false, 4 > Struct Reference

Inheritance diagram for Simd256_impl< true, true, false, 4 >:

**Data Structures**

- union [Converter](#)

Public Types

- using `scalar_t` = `uint32_t`
- using `aligned_allocator` = `AlignedAllocator< scalar_t, Alignment(alignment)>`
- using `aligned_vector` = `std::vector< scalar_t, aligned_allocator >`
- template<class `Field` >
using `is_same_element` = `std::is_same< typename Field::Element, scalar_t >`
- using `simdHalf` = `Simd128< scalar_t >`
- using `scalar_t` = `uint32_t`
- using `aligned_allocator` = `AlignedAllocator< scalar_t, Alignment(alignment)>`
- using `aligned_vector` = `std::vector< scalar_t, aligned_allocator >`
- template<class `Field` >
using `is_same_element` = `std::is_same< typename Field::Element, scalar_t >`
- using `simdHalf` = `Simd128< scalar_t >`
- using `vect_t` = `__m256i`
- using `vect_t` = `__m512i`
- using `half_t` = `__m128i`
- using `half_t` = `__m256i`

Static Public Member Functions

- static const `std::string type_string` ()
- static `INLINE CONST vect_t set1` (const `scalar_t` x)
- static `INLINE CONST vect_t set` (const `scalar_t` x0, const `scalar_t` x1, const `scalar_t` x2, const `scalar_t` x3, const `scalar_t` x4, const `scalar_t` x5, const `scalar_t` x6, const `scalar_t` x7)
- template<class `T` >
static `INLINE PURE vect_t gather` (const `scalar_t` *const p, const `T` *const idx)
- static `INLINE PURE vect_t load` (const `scalar_t` *const p)
- static `INLINE PURE vect_t loadu` (const `scalar_t` *const p)
- static `INLINE void store` (`scalar_t` *p, `vect_t` v)
- static `INLINE void storeu` (`scalar_t` *p, `vect_t` v)
- static `INLINE void stream` (`scalar_t` *p, const `vect_t` v)
- template<int `s`>
static `INLINE CONST vect_t sra` (const `vect_t` a)
- static `INLINE CONST vect_t greater` (`vect_t` a, `vect_t` b)
- static `INLINE CONST vect_t lesser` (`vect_t` a, `vect_t` b)
- static `INLINE CONST vect_t greater_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mulhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mulx` (`vect_t` a, `vect_t` b)
- static `INLINE CONST vect_t fmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fnmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsubx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmsubxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST scalar_t hadd_to_scal` (const `vect_t` a)
- static const `std::string type_string` ()
- static `INLINE CONST vect_t set1` (const `scalar_t` x)
- static `INLINE CONST vect_t set` (const `scalar_t` x0, const `scalar_t` x1, const `scalar_t` x2, const `scalar_t` x3, const `scalar_t` x4, const `scalar_t` x5, const `scalar_t` x6, const `scalar_t` x7)
- template<class `T` >
static `INLINE PURE vect_t gather` (const `scalar_t` *const p, const `T` *const idx)
- static `INLINE PURE vect_t load` (const `scalar_t` *const p)
- static `INLINE PURE vect_t loadu` (const `scalar_t` *const p)
- static `INLINE void store` (`scalar_t` *p, `vect_t` v)

- static `INLINE` void `storeu` (`scalar_t` *p, `vect_t` v)
- static `INLINE` void `stream` (`scalar_t` *p, const `vect_t` v)
- template<int s>
 - static `INLINE` `CONST` `vect_t` `sra` (const `vect_t` a)
- static `INLINE` `CONST` `vect_t` `greater` (`vect_t` a, `vect_t` b)
- static `INLINE` `CONST` `vect_t` `lesser` (`vect_t` a, `vect_t` b)
- static `INLINE` `CONST` `vect_t` `greater_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `lesser_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `mulhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `mulx` (`vect_t` a, `vect_t` b)
- static `INLINE` `CONST` `vect_t` `fmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `fnmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fnmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `vect_t` `fmsubx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fmsubxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `CONST` `scalar_t` `hadd_to_scal` (const `vect_t` a)
- template<class T >
 - static constexpr bool `valid` (T *p)
- template<class T >
 - static constexpr bool `valid` (T *p)
- template<class T >
 - static constexpr bool `compliant` (T n)
- template<class T >
 - static constexpr bool `compliant` (T n)
- static `INLINE` `CONST` `vect_t` `set1` (const `scalar_t` x)
- static `INLINE` `CONST` `vect_t` `set` (const `scalar_t` x0, const `scalar_t` x1, const `scalar_t` x2, const `scalar_t` x3, const `scalar_t` x4, const `scalar_t` x5, const `scalar_t` x6, const `scalar_t` x7)
- static `INLINE` `CONST` `vect_t` `set` (const `scalar_t` x0, const `scalar_t` x1, const `scalar_t` x2, const `scalar_t` x3, const `scalar_t` x4, const `scalar_t` x5, const `scalar_t` x6, const `scalar_t` x7, const `scalar_t` x8, const `scalar_t` x9, const `scalar_t` x10, const `scalar_t` x11, const `scalar_t` x12, const `scalar_t` x13, const `scalar_t` x14, const `scalar_t` x15)
- template<class T >
 - static `INLINE` `PURE` `vect_t` `gather` (const `scalar_t` *const p, const T *const idx)
- static `INLINE` `PURE` `vect_t` `load` (const `scalar_t` *const p)
- static `INLINE` `PURE` `vect_t` `loadu` (const `scalar_t` *const p)
- static `INLINE` void `store` (`scalar_t` *p, `vect_t` v)
- static `INLINE` void `storeu` (`scalar_t` *p, `vect_t` v)
- static `INLINE` void `stream` (`scalar_t` *p, const `vect_t` v)
- template<int s>
 - static `INLINE` `CONST` `vect_t` `sll` (const `vect_t` a)
- template<int s>
 - static `INLINE` `CONST` `vect_t` `sll` (const `vect_t` a)
- template<int s>
 - static `INLINE` `CONST` `vect_t` `srl` (const `vect_t` a)
- template<int s>
 - static `INLINE` `CONST` `vect_t` `srl` (const `vect_t` a)
- template<uint8_t s>
 - static `INLINE` `CONST` `vect_t` `shuffle_twice` (const `vect_t` a)
- template<uint8_t s>
 - static `INLINE` `CONST` `vect_t` `shuffle_twice` (const `vect_t` a)
- template<uint32_t s>
 - static `INLINE` `CONST` `vect_t` `shuffle` (const `vect_t` a)
- template<uint64_t s>
 - static `INLINE` `CONST` `vect_t` `shuffle` (const `vect_t` a)
- static `INLINE` `CONST` `vect_t` `unpacklo_intrinsic` (const `vect_t` a, const `vect_t` b)

- static `INLINE CONST vect_t unpacklo_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpacklo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpacklo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE` void `unpacklohi` (`vect_t` &lo, `vect_t` &hi, const `vect_t` a, const `vect_t` b)
- static `INLINE` void `unpacklohi` (`vect_t` &lo, `vect_t` &hi, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_even` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_even` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_odd` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_odd` (const `vect_t` a, const `vect_t` b)
- static `INLINE` void `pack` (`vect_t` &even, `vect_t` &odd, const `vect_t` a, const `vect_t` b)
- static `INLINE` void `pack` (`vect_t` &even, `vect_t` &odd, const `vect_t` a, const `vect_t` b)
- static `INLINE` void `transpose` (`vect_t` &r0, `vect_t` &r1, `vect_t` &r2, `vect_t` &r3, `vect_t` &r4, `vect_t` &r5, `vect_t` &r6, `vect_t` &r7)
- static `INLINE` void `transpose` (`vect_t` &r0, `vect_t` &r1, `vect_t` &r2, `vect_t` &r3, `vect_t` &r4, `vect_t` &r5, `vect_t` &r6, `vect_t` &r7, `vect_t` &r8, `vect_t` &r9, `vect_t` &r10, `vect_t` &r11, `vect_t` &r12, `vect_t` &r13, `vect_t` &r14, `vect_t` &r15)
- `template<uint8_t s>`
static `INLINE CONST vect_t blend` (const `vect_t` a, const `vect_t` b)
- `template<uint16_t s>`
static `INLINE CONST vect_t blend` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t add` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t add` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t addin` (`vect_t` &a, const `vect_t` b)
- static `INLINE` `vect_t addin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t sub` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t sub` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t subin` (`vect_t` &a, const `vect_t` b)
- static `INLINE` `vect_t subin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t mullo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mullo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t fmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t fmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t fnmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t fnmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t round` (const `vect_t` a)
- static `INLINE CONST vect_t round` (const `vect_t` a)
- static `INLINE` `vect_t mod` (`vect_t` &C, const `vect_t` &P, const `vect_t` &INVP, const `vect_t` &NEGP, const `vect_t` &MIN, const `vect_t` &MAX, `vect_t` &Q, `vect_t` &T)
- static `INLINE` `vect_t mod` (`vect_t` &C, const `vect_t` &P, const `vect_t` &INVP, const `vect_t` &NEGP, const `vect_t` &MIN, const `vect_t` &MAX, `vect_t` &Q, `vect_t` &T)

- static `INLINE CONST vect_t zero ()`
- static `INLINE CONST vect_t zero ()`
- static `INLINE CONST vect_t vor (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t vxor (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t vand (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t vandnot (const vect_t a, const vect_t b)`

Static Public Attributes

- static const constexpr size_t `vect_size` = 8
- static const constexpr size_t `alignment` = 32

12.288.1 Member Typedef Documentation

12.288.1.1 scalar_t [1/2]

```
using scalar_t = uint32_t
```

12.288.1.2 aligned_allocator [1/2]

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.288.1.3 aligned_vector [1/2]

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.288.1.4 is_same_element [1/2]

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.288.1.5 simdHalf [1/2]

```
using simdHalf = Simd128<scalar_t>
```

12.288.1.6 scalar_t [2/2]

```
using scalar_t = uint32_t
```

12.288.1.7 aligned_allocator [2/2]

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.288.1.8 aligned_vector [2/2]

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.288.1.9 is_same_element [2/2]

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.288.1.10 simdHalf [2/2]

```
using simdHalf = Simd128<scalar_t>
```

12.288.1.11 vect_t [1/2]

```
using vect_t = __m256i [inherited]
```

12.288.1.12 vect_t [2/2]

```
using vect_t = __m512i [inherited]
```

12.288.1.13 half_t [1/2]

```
using half_t = __m128i [inherited]
```

12.288.1.14 half_t [2/2]

```
using half_t = __m256i [inherited]
```

12.288.2 Member Function Documentation**12.288.2.1 type_string() [1/2]**

```
static const std::string type_string ( ) [inline], [static]
```

12.288.2.2 set1() [1/3]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.288.2.3 set() [1/4]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7 ) [inline], [static]
```

12.288.2.4 gather() [1/3]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.288.2.5 load() [1/3]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.288.2.6 loadu() [1/3]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.288.2.7 store() [1/3]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.288.2.8 storeu() [1/3]

```
static INLINE void storeu (  
    scalar_t * p,  
    vect_t v ) [inline], [static]
```

12.288.2.9 stream() [1/3]

```
static INLINE void stream (  
    scalar_t * p,  
    const vect_t v ) [inline], [static]
```

12.288.2.10 sra() [1/2]

```
template<int s>  
static INLINE CONST vect_t sra (  
    const vect_t a ) [inline], [static]
```

12.288.2.11 greater() [1/2]

```
static INLINE CONST vect_t greater (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.288.2.12 lesser() [1/2]

```
static INLINE CONST vect_t lesser (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.288.2.13 greater_eq() [1/2]

```
static INLINE CONST vect_t greater_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.288.2.14 lesser_eq() [1/2]

```
static INLINE CONST vect_t lesser_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.288.2.15 mulhi() [1/2]

```
static INLINE CONST vect_t mulhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.288.2.16 mulx() [1/2]

```
static INLINE CONST vect_t mulx (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.288.2.17 fmaddx() [1/2]

```
static INLINE CONST vect_t fmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.288.2.18 fmaddxin() [1/2]

```
static INLINE vect_t fmaddxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.288.2.19 fnmaddx() [1/2]

```
static INLINE CONST vect_t fnmaddx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.288.2.20 fnmaddxin() [1/2]

```
static INLINE vect_t fnmaddxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.288.2.21 fmsubx() [1/2]

```
static INLINE CONST vect_t fmsubx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.288.2.22 fmsubxin() [1/2]

```
static INLINE vect_t fmsubxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.288.2.23 hadd_to_scal() [1/2]

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.288.2.24 type_string() [2/2]

```
static const std::string type_string ( ) [inline], [static]
```

12.288.2.25 set1() [2/3]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.288.2.26 set() [2/4]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7 ) [inline], [static]
```

12.288.2.27 gather() [2/3]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.288.2.28 load() [2/3]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.288.2.29 loadu() [2/3]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.288.2.30 store() [2/3]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.288.2.31 storeu() [2/3]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.288.2.32 stream() [2/3]

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static]
```

12.288.2.33 sra() [2/2]

```
template<int s>
static INLINE CONST vect_t sra (
    const vect_t a ) [inline], [static]
```

12.288.2.34 greater() [2/2]

```
static INLINE CONST vect_t greater (
    vect_t a,
    vect_t b ) [inline], [static]
```

12.288.2.35 lesser() [2/2]

```
static INLINE CONST vect_t lesser (
    vect_t a,
    vect_t b ) [inline], [static]
```

12.288.2.36 greater_eq() [2/2]

```
static INLINE CONST vect_t greater_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.288.2.37 lesser_eq() [2/2]

```
static INLINE CONST vect_t lesser_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.288.2.38 mulhi() [2/2]

```
static INLINE CONST vect_t mulhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.288.2.39 mulx() [2/2]

```
static INLINE CONST vect_t mulx (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.288.2.40 fmaddx() [2/2]

```
static INLINE CONST vect_t fmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.288.2.41 fmaddxin() [2/2]

```
static INLINE vect_t fmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.288.2.42 fnmaddx() [2/2]

```
static INLINE CONST vect_t fnmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.288.2.43 fnmaddxin() [2/2]

```
static INLINE vect_t fnmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.288.2.44 fmsubx() [2/2]

```
static INLINE CONST vect_t fmsubx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.288.2.45 fmsubxin() [2/2]

```
static INLINE vect_t fmsubxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.288.2.46 hadd_to_scal() [2/2]

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.288.2.47 valid() [1/2]

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr], [inherited]
```

12.288.2.48 valid() [2/2]

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr], [inherited]
```

12.288.2.49 compliant() [1/2]

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr], [inherited]
```

12.288.2.50 compliant() [2/2]

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr], [inherited]
```

12.288.2.51 set1() [3/3]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static], [inherited]
```

12.288.2.52 set() [3/4]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7 ) [inline], [static], [inherited]
```

12.288.2.53 set() [4/4]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7,
    const scalar_t x8,
    const scalar_t x9,
    const scalar_t x10,
```

```

const scalar_t x11,
const scalar_t x12,
const scalar_t x13,
const scalar_t x14,
const scalar_t x15 ) [inline], [static], [inherited]

```

12.288.2.54 gather() [3/3]

```

template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static], [inherited]

```

12.288.2.55 load() [3/3]

```

static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static], [inherited]

```

12.288.2.56 loadu() [3/3]

```

static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static], [inherited]

```

12.288.2.57 store() [3/3]

```

static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]

```

12.288.2.58 storeu() [3/3]

```

static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]

```

12.288.2.59 stream() [3/3]

```

static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static], [inherited]

```

12.288.2.60 sll() [1/2]

```

template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static], [inherited]

```

12.288.2.61 srl() [2/2]

```

template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static], [inherited]

```

12.288.2.62 srl() [1/2]

```

template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static], [inherited]

```


12.288.2.63 srl() [2/2]

```
template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static], [inherited]
```

12.288.2.64 shuffle_twice() [1/2]

```
template<uint8_t s>
static INLINE CONST vect_t shuffle_twice (
    const vect_t a ) [inline], [static], [inherited]
```

12.288.2.65 shuffle_twice() [2/2]

```
template<uint8_t s>
static INLINE CONST vect_t shuffle_twice (
    const vect_t a ) [inline], [static], [inherited]
```

12.288.2.66 shuffle() [1/2]

```
template<uint32_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static], [inherited]
```

12.288.2.67 shuffle() [2/2]

```
template<uint64_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static], [inherited]
```

12.288.2.68 unpacklo_intrinsic() [1/2]

```
static INLINE CONST vect_t unpacklo_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.69 unpacklo_intrinsic() [2/2]

```
static INLINE CONST vect_t unpacklo_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.70 unpackhi_intrinsic() [1/2]

```
static INLINE CONST vect_t unpackhi_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.71 unpackhi_intrinsic() [2/2]

```
static INLINE CONST vect_t unpackhi_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.72 unpacklo() [1/2]

```
static INLINE CONST vect_t unpacklo (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.73 unpacklo() [2/2]

```
static INLINE CONST vect_t unpacklo (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.74 unpackhi() [1/2]

```
static INLINE CONST vect_t unpackhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.75 unpackhi() [2/2]

```
static INLINE CONST vect_t unpackhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.76 unpacklohi() [1/2]

```
static INLINE void unpacklohi (  
    vect_t & lo,  
    vect_t & hi,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.77 unpacklohi() [2/2]

```
static INLINE void unpacklohi (  
    vect_t & lo,  
    vect_t & hi,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.78 pack_even() [1/2]

```
static INLINE CONST vect_t pack_even (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.79 pack_even() [2/2]

```
static INLINE CONST vect_t pack_even (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.80 pack_odd() [1/2]

```
static INLINE CONST vect_t pack_odd (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.81 pack_odd() [2/2]

```
static INLINE CONST vect_t pack_odd (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.82 pack() [1/2]

```
static INLINE void pack (
    vect_t & even,
    vect_t & odd,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.83 pack() [2/2]

```
static INLINE void pack (
    vect_t & even,
    vect_t & odd,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.84 transpose() [1/2]

```
static INLINE void transpose (
    vect_t & r0,
    vect_t & r1,
    vect_t & r2,
    vect_t & r3,
    vect_t & r4,
    vect_t & r5,
    vect_t & r6,
    vect_t & r7 ) [inline], [static], [inherited]
```

12.288.2.85 transpose() [2/2]

```
static INLINE void transpose (
    vect_t & r0,
    vect_t & r1,
    vect_t & r2,
    vect_t & r3,
    vect_t & r4,
    vect_t & r5,
    vect_t & r6,
    vect_t & r7,
    vect_t & r8,
    vect_t & r9,
    vect_t & r10,
    vect_t & r11,
    vect_t & r12,
    vect_t & r13,
    vect_t & r14,
    vect_t & r15 ) [inline], [static], [inherited]
```

12.288.2.86 blend() [1/2]

```
template<uint8_t s>
static INLINE CONST vect_t blend (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.87 blend() [2/2]

```
template<uint16_t s>
static INLINE CONST vect_t blend (
```

```
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.88 add() [1/2]

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.89 add() [2/2]

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.90 addin() [1/2]

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.91 addin() [2/2]

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.92 sub() [1/2]

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.93 sub() [2/2]

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.94 subin() [1/2]

```
static INLINE vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.95 subin() [2/2]

```
static INLINE vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.96 mullo() [1/2]

```
static INLINE CONST vect_t mullo (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.97 mullo() [2/2]

```
static INLINE CONST vect_t mullo (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.98 mul() [1/2]

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.99 mul() [2/2]

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.100 fmadd() [1/2]

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.101 fmadd() [2/2]

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.102 fmaddin() [1/2]

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.103 fmaddin() [2/2]

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.104 fnmadd() [1/2]

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.105 fnmadd() [2/2]

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.106 fnmaddin() [1/2]

```
static INLINE vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.107 fnmaddin() [2/2]

```
static INLINE vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.108 fmsub() [1/2]

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.109 fmsub() [2/2]

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.110 fmsubin() [1/2]

```
static INLINE vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.111 fmsubin() [2/2]

```
static INLINE vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.112 eq() [1/2]

```
static INLINE CONST vect_t eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.113 eq() [2/2]

```
static INLINE CONST vect_t eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.114 round() [1/2]

```
static INLINE CONST vect_t round (  
    const vect_t a ) [inline], [static], [inherited]
```

12.288.2.115 round() [2/2]

```
static INLINE CONST vect_t round (
    const vect_t a ) [inline], [static], [inherited]
```

12.288.2.116 mod() [1/2]

```
static INLINE vect_t mod (
    vect_t & C,
    const vect_t & P,
    const vect_t & INVP,
    const vect_t & NEGP,
    const vect_t & MIN,
    const vect_t & MAX,
    vect_t & Q,
    vect_t & T ) [inline], [static], [inherited]
```

12.288.2.117 mod() [2/2]

```
static INLINE vect_t mod (
    vect_t & C,
    const vect_t & P,
    const vect_t & INVP,
    const vect_t & NEGP,
    const vect_t & MIN,
    const vect_t & MAX,
    vect_t & Q,
    vect_t & T ) [inline], [static], [inherited]
```

12.288.2.118 zero() [1/2]

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.288.2.119 zero() [2/2]

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.288.2.120 vor()

```
static INLINE CONST vect_t vor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.121 vxor()

```
static INLINE CONST vect_t vxor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.122 vand()

```
static INLINE CONST vect_t vand (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.288.2.123 vandnot()

```
static INLINE CONST vect_t vandnot (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.288.3 Field Documentation

12.288.3.1 vect_size

```
static const constexpr size_t vect_size = 8 [static], [constexpr], [inherited]
```

12.288.3.2 alignment


```
static const constexpr size_t alignment = 32 [static], [constexpr], [inherited]
```

The documentation for this struct was generated from the following files:

- [simd256_int32.inl](#)
- [simd512_int32.inl](#)

12.289 Simd256_impl< true, true, false, 8 > Struct Reference

Inheritance diagram for Simd256_impl< true, true, false, 8 >:



Data Structures

- union [Converter](#)

Public Types

- using [scalar_t](#) = uint64_t
- using [aligned_allocator](#) = AlignedAllocator< [scalar_t](#), Alignment([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >
- template<class [Field](#) >
using [is_same_element](#) = std::is_same< typename [Field::Element](#), [scalar_t](#) >
- using [simdHalf](#) = Simd128< [scalar_t](#) >
- using [vect_t](#) = __m256i
- using [half_t](#) = __m128i

Static Public Member Functions

- static const std::string [type_string](#) ()
- static [INLINE CONST vect_t set1](#) (const [scalar_t](#) x)
- static [INLINE CONST vect_t set](#) (const [scalar_t](#) x0, const [scalar_t](#) x1, const [scalar_t](#) x2, const [scalar_t](#) x3)
- template<class T >
static [INLINE PURE vect_t gather](#) (const [scalar_t](#) *const p, const T *const idx)
- static [INLINE PURE vect_t load](#) (const [scalar_t](#) *const p)
- static [INLINE PURE vect_t loadu](#) (const [scalar_t](#) *const p)
- static [INLINE void store](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void storeu](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void stream](#) ([scalar_t](#) *p, const [vect_t](#) v)
- template<int s>
static [INLINE CONST vect_t sra](#) (const [vect_t](#) a)
- static [INLINE CONST vect_t greater](#) ([vect_t](#) a, [vect_t](#) b)
- static [INLINE CONST vect_t lesser](#) ([vect_t](#) a, [vect_t](#) b)

- static `INLINE CONST vect_t greater_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mullo` (`vect_t` a, `vect_t` b)
- static `INLINE CONST vect_t mulhi` (`vect_t` a, `vect_t` b)
- static `INLINE CONST vect_t mulx` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fnmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsubx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmsubxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST scalar_t hadd_to_scal` (const `vect_t` a)
- template<class T >
static constexpr bool `valid` (T *p)
- template<class T >
static constexpr bool `compliant` (T n)
- static `INLINE CONST vect_t set1` (const `scalar_t` x)
- static `INLINE CONST vect_t set` (const `scalar_t` x0, const `scalar_t` x1, const `scalar_t` x2, const `scalar_t` x3)
- template<class T >
static `INLINE PURE vect_t gather` (const `scalar_t` *const p, const T *const idx)
- template<int idx>
static `INLINE CONST scalar_t get` (`vect_t` v)
- static `INLINE PURE vect_t load` (const `scalar_t` *const p)
- static `INLINE PURE vect_t loadu` (const `scalar_t` *const p)
- static `INLINE void store` (`scalar_t` *p, `vect_t` v)
- static `INLINE void storeu` (`scalar_t` *p, `vect_t` v)
- static `INLINE void stream` (`scalar_t` *p, const `vect_t` v)
- template<int s>
static `INLINE CONST vect_t sll` (const `vect_t` a)
- template<int s>
static `INLINE CONST vect_t srl` (const `vect_t` a)
- template<uint8_t s>
static `INLINE CONST vect_t shuffle` (const `vect_t` a)
- static `INLINE CONST vect_t unpacklo_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpacklo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE void unpacklohi` (`vect_t` &lo, `vect_t` &hi, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_even` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_odd` (const `vect_t` a, const `vect_t` b)
- static `INLINE void pack` (`vect_t` &even, `vect_t` &odd, const `vect_t` a, const `vect_t` b)
- static `INLINE void transpose` (`vect_t` &r0, `vect_t` &r1, `vect_t` &r2, `vect_t` &r3)
- template<uint8_t s>
static `INLINE CONST vect_t blend` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t add` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t addin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t sub` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t subin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fnmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)

- static `INLINE CONST vect_t eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t round` (const `vect_t` a)
- static `INLINE CONST vect_t mask_high` ()
- static `INLINE CONST vect_t mulhi_fast` (`vect_t` x, `vect_t` y)
- static `INLINE vect_t mod` (`vect_t` &C, const `__m256d` &P, const `__m256d` &INVP, const `__m256d` &NEGP, const `vect_t` &POW50REM, const `__m256d` &MIN, const `__m256d` &MAX, `__m256d` &Q, `__m256d` &T)
- static `INLINE CONST vect_t zero` ()

Static Public Attributes

- static const constexpr size_t `vect_size` = 4
- static const constexpr size_t `alignment` = 32

Static Protected Member Functions

- static `INLINE CONST vect_t signbits` (const `vect_t` x)

12.289.1 Member Typedef Documentation

12.289.1.1 scalar_t

```
using scalar_t = uint64_t
```

12.289.1.2 aligned_allocator

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.289.1.3 aligned_vector

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.289.1.4 is_same_element

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.289.1.5 simdHalf

```
using simdHalf = Simd128<scalar_t>
```

12.289.1.6 vect_t

```
using vect_t = __m256i [inherited]
```

12.289.1.7 half_t

```
using half_t = __m128i [inherited]
```

12.289.2 Member Function Documentation

12.289.2.1 type_string()

```
static const std::string type_string ( ) [inline], [static]
```

12.289.2.2 set1() [1/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.289.2.3 set() [1/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3 ) [inline], [static]
```

12.289.2.4 gather() [1/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.289.2.5 load() [1/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.289.2.6 loadu() [1/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.289.2.7 store() [1/2]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.289.2.8 storeu() [1/2]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.289.2.9 stream() [1/2]

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static]
```

12.289.2.10 sra()

```
template<int s>
static INLINE CONST vect_t sra (
    const vect_t a ) [inline], [static]
```

12.289.2.11 greater()

```
static INLINE CONST vect_t greater (
    vect_t a,
    vect_t b ) [inline], [static]
```

12.289.2.12 lesser()

```
static INLINE CONST vect_t lesser (
    vect_t a,
    vect_t b ) [inline], [static]
```

12.289.2.13 greater_eq()

```
static INLINE CONST vect_t greater_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.289.2.14 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.289.2.15 mullo()

```
static INLINE CONST vect_t mullo (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.289.2.16 mulhi()

```
static INLINE CONST vect_t mulhi (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.289.2.17 mulx()

```
static INLINE CONST vect_t mulx (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.289.2.18 fmaddx()

```
static INLINE CONST vect_t fmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.289.2.19 fmaddxin()

```
static INLINE vect_t fmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.289.2.20 fnmaddx()

```
static INLINE CONST vect_t fnmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.289.2.21 fnmaddxin()

```
static INLINE vect_t fnmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.289.2.22 fmsubx()

```
static INLINE CONST vect_t fmsubx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.289.2.23 fmsubxin()

```
static INLINE vect_t fmsubxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.289.2.24 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.289.2.25 valid()

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr], [inherited]
```

12.289.2.26 compliant()

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr], [inherited]
```

12.289.2.27 set1() [2/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static], [inherited]
```

12.289.2.28 set() [2/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3 ) [inline], [static], [inherited]
```

12.289.2.29 gather() [2/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static], [inherited]
```

12.289.2.30 get()

```
template<int idx>
static INLINE CONST scalar_t get (
    vect_t v ) [inline], [static], [inherited]
```

12.289.2.31 load() [2/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static], [inherited]
```

12.289.2.32 loadu() [2/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static], [inherited]
```

12.289.2.33 store() [2/2]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]
```

12.289.2.34 storeu() [2/2]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]
```

12.289.2.35 stream() [2/2]

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static], [inherited]
```

12.289.2.36 sll()

```
template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static], [inherited]
```

12.289.2.37 srl()

```
template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static], [inherited]
```

12.289.2.38 shuffle()

```
template<uint8_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static], [inherited]
```

12.289.2.39 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.40 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.41 unpacklo()

```
static INLINE CONST vect_t unpacklo (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.42 unpackhi()

```
static INLINE CONST vect_t unpackhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.43 unpacklohi()

```
static INLINE void unpacklohi (  
    vect_t & lo,  
    vect_t & hi,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.44 pack_even()

```
static INLINE CONST vect_t pack_even (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.45 pack_odd()

```
static INLINE CONST vect_t pack_odd (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.46 pack()

```
static INLINE void pack (  
    vect_t & even,  
    vect_t & odd,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.47 transpose()

```
static INLINE void transpose (  
    vect_t & r0,  
    vect_t & r1,  
    vect_t & r2,  
    vect_t & r3 ) [inline], [static], [inherited]
```

12.289.2.48 blend()

```
template<uint8_t s>  
static INLINE CONST vect_t blend (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.49 add()

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.50 addin()

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.51 sub()

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.52 subin()

```
static INLINE vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.53 mul()

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.54 fmadd()

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.55 fmaddin()

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.56 fnmadd()

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.57 fnmaddin()

```
static INLINE vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.58 fmsub()

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.59 fmsubin()

```
static INLINE vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```


12.289.2.60 eq()

```
static INLINE CONST vect_t eq (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.289.2.61 round()

```
static INLINE CONST vect_t round (
    const vect_t a ) [inline], [static], [inherited]
```

12.289.2.62 mask_high()

```
static INLINE CONST vect_t mask_high ( ) [inline], [static], [inherited]
```

12.289.2.63 mulhi_fast()

```
INLINE CONST vect_t mulhi_fast (
    vect_t x,
    vect_t y ) [static], [inherited]
```

12.289.2.64 mod()

```
INLINE vect_t mod (
    vect_t & C,
    const __m256d & P,
    const __m256d & INV_P,
    const __m256d & NEG_P,
    const vect_t & POW50REM,
    const __m256d & MIN,
    const __m256d & MAX,
    __m256d & Q,
    __m256d & T ) [static], [inherited]
```

12.289.2.65 signbits()

```
static INLINE CONST vect_t signbits (
    const vect_t x ) [inline], [static], [protected], [inherited]
```

12.289.2.66 zero()

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.289.3 Field Documentation**12.289.3.1 vect_size**

```
const constexpr size_t vect_size = 4 [static], [constexpr], [inherited]
```

12.289.3.2 alignment


```
const constexpr size_t alignment = 32 [static], [constexpr], [inherited]
```

The documentation for this struct was generated from the following file:

- [simd256_int64.inl](#)

12.290 Simd256_impl< true, true, true, 2 > Struct Reference

Inheritance diagram for Simd256_impl< true, true, true, 2 >:



Data Structures

- union [Converter](#)

Public Types

- using [vect_t](#) = __m256i
- using [half_t](#) = __m128i
- using [scalar_t](#) = int16_t
- using [simdHalf](#) = [Simd128](#)< [scalar_t](#) >
- using [aligned_allocator](#) = [AlignedAllocator](#)< [scalar_t](#), [Alignment](#)([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >
- template<class [Field](#) >
using [is_same_element](#) = std::is_same< typename [Field::Element](#), [scalar_t](#) >

Static Public Member Functions

- static const std::string [type_string](#) ()
- template<class T >
static constexpr bool [valid](#) (T *p)
- template<class T >
static constexpr bool [compliant](#) (T n)
- static [INLINE CONST vect_t set1](#) (const [scalar_t](#) x)
- static [INLINE CONST vect_t set](#) (const [scalar_t](#) x0, const [scalar_t](#) x1, const [scalar_t](#) x2, const [scalar_t](#) x3, const [scalar_t](#) x4, const [scalar_t](#) x5, const [scalar_t](#) x6, const [scalar_t](#) x7, const [scalar_t](#) x8, const [scalar_t](#) x9, const [scalar_t](#) x10, const [scalar_t](#) x11, const [scalar_t](#) x12, const [scalar_t](#) x13, const [scalar_t](#) x14, const [scalar_t](#) x15)
- template<class T >
static [INLINE PURE vect_t gather](#) (const [scalar_t](#) *const p, const T *const idx)
- static [INLINE PURE vect_t load](#) (const [scalar_t](#) *const p)
- static [INLINE PURE vect_t loadu](#) (const [scalar_t](#) *const p)
- static [INLINE void store](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void storeu](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void stream](#) ([scalar_t](#) *p, const [vect_t](#) v)
- template<int s>
static [INLINE CONST vect_t sll](#) (const [vect_t](#) a)
- template<int s>
static [INLINE CONST vect_t srl](#) (const [vect_t](#) a)
- template<int s>
static [INLINE CONST vect_t sra](#) (const [vect_t](#) a)
- template<uint64_t s>
static [INLINE CONST vect_t shuffle](#) (const [vect_t](#) a)
- static [INLINE CONST vect_t unpacklo_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)

- static `INLINE CONST vect_t unpacklo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE void unpacklohi` (`vect_t` &lo, `vect_t` &hi, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_even` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_odd` (const `vect_t` a, const `vect_t` b)
- static `INLINE void pack` (`vect_t` &even, `vect_t` &odd, const `vect_t` a, const `vect_t` b)
- static `INLINE void transpose` (`vect_t` &r0, `vect_t` &r1, `vect_t` &r2, `vect_t` &r3, `vect_t` &r4, `vect_t` &r5, `vect_t` &r6, `vect_t` &r7, `vect_t` &r8, `vect_t` &r9, `vect_t` &r10, `vect_t` &r11, `vect_t` &r12, `vect_t` &r13, `vect_t` &r14, `vect_t` &r15)
- template<uint16_t s, typename std::enable_if<(s & 0x00ff) == (s > 8)>::type * = nullptr>
static `INLINE vect_t blend` (const `vect_t` a, const `vect_t` b)
- template<uint16_t s, typename std::enable_if<(s & 0x00ff) != (s > 8)>::type * = nullptr>
static `INLINE vect_t blend` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t add` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t addin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t sub` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t subin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t mullo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mulhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mulx` (`vect_t` a, `vect_t` b)
- static `INLINE CONST vect_t fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fnmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fnmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsubx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmsubxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t greater` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t greater_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST scalar_t hadd_to_scal` (const `vect_t` a)
- static `INLINE CONST vect_t round` (const `vect_t` a)
- static `INLINE vect_t mod` (`vect_t` &C, const `vect_t` &P, const `vect_t` &INVP, const `vect_t` &NEGP, const `vect_t` &MIN, const `vect_t` &MAX, `vect_t` &Q, `vect_t` &T)
- static `INLINE CONST vect_t zero` ()

Static Public Attributes

- static const constexpr size_t `vect_size` = 16
- static const constexpr size_t `alignment` = 32

12.290.1 Member Typedef Documentation

12.290.1.1 vect_t

```
using vect_t = __m256i
```

12.290.1.2 half_t

```
using half_t = __m128i
```

12.290.1.3 scalar_t

```
using scalar_t = int16_t
```

12.290.1.4 simdHalf

```
using simdHalf = Simd128<scalar_t>
```

12.290.1.5 aligned_allocator

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.290.1.6 aligned_vector

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.290.1.7 is_same_element

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.290.2 Member Function Documentation**12.290.2.1 type_string()**

```
static const std::string type_string ( ) [inline], [static]
```

12.290.2.2 valid()

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr]
```

12.290.2.3 compliant()

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr]
```

12.290.2.4 set1()

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.290.2.5 set()

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7,
    const scalar_t x8,
    const scalar_t x9,
    const scalar_t x10,
    const scalar_t x11,
    const scalar_t x12,
```

```

const scalar_t x13,
const scalar_t x14,
const scalar_t x15 ) [inline], [static]

```

12.290.2.6 gather()

```

template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]

```

12.290.2.7 load()

```

static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]

```

12.290.2.8 loadu()

```

static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]

```

12.290.2.9 store()

```

static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]

```

12.290.2.10 storeu()

```

static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static]

```

12.290.2.11 stream()

```

static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static]

```

12.290.2.12 sll()

```

template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static]

```

12.290.2.13 srl()

```

template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static]

```

12.290.2.14 sra()

```

template<int s>
static INLINE CONST vect_t sra (
    const vect_t a ) [inline], [static]

```

12.290.2.15 shuffle()

```
template<uint64_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static]
```

12.290.2.16 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.17 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.18 unpacklo()

```
static INLINE CONST vect_t unpacklo (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.19 unpackhi()

```
static INLINE CONST vect_t unpackhi (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.20 unpacklohi()

```
static INLINE void unpacklohi (
    vect_t & lo,
    vect_t & hi,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.21 pack_even()

```
static INLINE CONST vect_t pack_even (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.22 pack_odd()

```
static INLINE CONST vect_t pack_odd (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.23 pack()

```
static INLINE void pack (
    vect_t & even,
    vect_t & odd,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.24 transpose()

```
static INLINE void transpose (
    vect_t & r0,
    vect_t & r1,
    vect_t & r2,
    vect_t & r3,
    vect_t & r4,
    vect_t & r5,
    vect_t & r6,
    vect_t & r7,
    vect_t & r8,
    vect_t & r9,
    vect_t & r10,
    vect_t & r11,
    vect_t & r12,
    vect_t & r13,
    vect_t & r14,
    vect_t & r15 ) [inline], [static]
```

12.290.2.25 blend() [1/2]

```
template<uint16_t s, typename std::enable_if<(s &0x00ff)==(s > > 8)>::type * = nullptr>
static INLINE vect_t blend (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.26 blend() [2/2]

```
template<uint16_t s, typename std::enable_if<(s &0x00ff) !=(s > > 8)>::type * = nullptr>
static INLINE vect_t blend (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.27 add()

```
static INLINE CONST vect_t add (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.28 addin()

```
static INLINE vect_t addin (
    vect_t & a,
    const vect_t b ) [inline], [static]
```

12.290.2.29 sub()

```
static INLINE CONST vect_t sub (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.30 subin()

```
static INLINE vect_t subin (
    vect_t & a,
    const vect_t b ) [inline], [static]
```

12.290.2.31 mullo()

```
static INLINE CONST vect_t mullo (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.32 mul()

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.33 mulhi()

```
static INLINE CONST vect_t mulhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.34 mulx()

```
static INLINE CONST vect_t mulx (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.290.2.35 fmadd()

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.36 fmaddin()

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.37 fmaddx()

```
static INLINE CONST vect_t fmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.38 fmaddxin()

```
static INLINE vect_t fmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.39 fnmadd()

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```


12.290.2.40 fnmaddin()

```
static INLINE vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.41 fnmaddx()

```
static INLINE CONST vect_t fnmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.42 fnmaddxin()

```
static INLINE vect_t fnmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.43 fmsub()

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.44 fmsubin()

```
static INLINE vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.45 fmsubx()

```
static INLINE CONST vect_t fmsubx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.46 fmsubxin()

```
static INLINE vect_t fmsubxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.47 eq()

```
static INLINE CONST vect_t eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.48 greater()

```
static INLINE CONST vect_t greater (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.290.2.49 lesser()

```
static INLINE CONST vect_t lesser (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.50 greater_eq()

```
static INLINE CONST vect_t greater_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.51 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.290.2.52 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.290.2.53 round()

```
static INLINE CONST vect_t round (
    const vect_t a ) [inline], [static]
```

12.290.2.54 mod()

```
static INLINE vect_t mod (
    vect_t & C,
    const vect_t & P,
    const vect_t & INVP,
    const vect_t & NEGP,
    const vect_t & MIN,
    const vect_t & MAX,
    vect_t & Q,
    vect_t & T ) [inline], [static]
```

12.290.2.55 zero()

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.290.3 Field Documentation**12.290.3.1 vect_size**

```
const constexpr size_t vect_size = 16 [static], [constexpr]
```

12.290.3.2 alignment


```
const constexpr size_t alignment = 32 [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [simd256_int16.inl](#)

12.291 Simd256_impl< true, true, true, 4 > Struct Reference

Inheritance diagram for Simd256_impl< true, true, true, 4 >:



Data Structures

- union [Converter](#)

Public Types

- using `vect_t` = `__m256i`
- using `half_t` = `__m128i`
- using `scalar_t` = `int32_t`
- using `simdHalf` = `Simd128< scalar_t >`
- using `aligned_allocator` = `AlignedAllocator< scalar_t, Alignment(alignment)>`
- using `aligned_vector` = `std::vector< scalar_t, aligned_allocator >`
- template<class `Field` >
using `is_same_element` = `std::is_same< typename Field::Element, scalar_t >`
- using `vect_t` = `__m512i`
- using `half_t` = `__m256i`
- using `scalar_t` = `int32_t`
- using `simdHalf` = `Simd256< scalar_t >`
- using `aligned_allocator` = `AlignedAllocator< scalar_t, Alignment(alignment)>`
- using `aligned_vector` = `std::vector< scalar_t, aligned_allocator >`
- template<class `Field` >
using `is_same_element` = `std::is_same< typename Field::Element, scalar_t >`

Static Public Member Functions

- static const std::string `type_string` ()
- template<class `T` >
static constexpr bool `valid` (`T *p`)
- template<class `T` >
static constexpr bool `compliant` (`T n`)
- static `INLINE CONST vect_t set1` (`const scalar_t x`)
- static `INLINE CONST vect_t set` (`const scalar_t x0, const scalar_t x1, const scalar_t x2, const scalar_t x3, const scalar_t x4, const scalar_t x5, const scalar_t x6, const scalar_t x7`)
- template<class `T` >
static `INLINE PURE vect_t gather` (`const scalar_t *const p, const T *const idx`)
- static `INLINE PURE vect_t load` (`const scalar_t *const p`)
- static `INLINE PURE vect_t loadu` (`const scalar_t *const p`)
- static `INLINE void store` (`scalar_t *p, vect_t v`)
- static `INLINE void storeu` (`scalar_t *p, vect_t v`)
- static `INLINE void stream` (`scalar_t *p, const vect_t v`)
- template<int `s` >
static `INLINE CONST vect_t sll` (`const vect_t a`)
- template<int `s` >
static `INLINE CONST vect_t srl` (`const vect_t a`)

- `template<int s>`
static `INLINE CONST vect_t sra` (const `vect_t` a)
- `template<uint8_t s>`
static `INLINE CONST vect_t shuffle_twice` (const `vect_t` a)
- `template<uint32_t s>`
static `INLINE CONST vect_t shuffle` (const `vect_t` a)
- static `INLINE CONST vect_t unpacklo_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpacklo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE` void `unpacklohi` (`vect_t` &lo, `vect_t` &hi, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_even` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_odd` (const `vect_t` a, const `vect_t` b)
- static `INLINE` void `pack` (`vect_t` &even, `vect_t` &odd, const `vect_t` a, const `vect_t` b)
- static `INLINE` void `transpose` (`vect_t` &r0, `vect_t` &r1, `vect_t` &r2, `vect_t` &r3, `vect_t` &r4, `vect_t` &r5, `vect_t` &r6, `vect_t` &r7)
- `template<uint8_t s>`
static `INLINE CONST vect_t blend` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t add` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `addin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t sub` (const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `subin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t mullo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mulhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mulx` (`vect_t` a, `vect_t` b)
- static `INLINE CONST vect_t fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmadddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fnmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fnmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsubx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE` `vect_t` `fmsubxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t greater` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t greater_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST scalar_t hadd_to_scal` (const `vect_t` a)
- static `INLINE CONST vect_t round` (const `vect_t` a)
- static `INLINE` `vect_t` `mod` (`vect_t` &C, const `vect_t` &P, const `vect_t` &INVP, const `vect_t` &NEGP, const `vect_t` &MIN, const `vect_t` &MAX, `vect_t` &Q, `vect_t` &T)
- static const std::string `type_string` ()
- `template<class T >`
static constexpr bool `valid` (T *p)
- `template<class T >`
static constexpr bool `compliant` (T n)
- static `INLINE CONST vect_t set1` (const `scalar_t` x)

- static `INLINE CONST vect_t set` (const `scalar_t` x0, const `scalar_t` x1, const `scalar_t` x2, const `scalar_t` x3, const `scalar_t` x4, const `scalar_t` x5, const `scalar_t` x6, const `scalar_t` x7, const `scalar_t` x8, const `scalar_t` x9, const `scalar_t` x10, const `scalar_t` x11, const `scalar_t` x12, const `scalar_t` x13, const `scalar_t` x14, const `scalar_t` x15)
- `template<class T >`
static `INLINE PURE vect_t gather` (const `scalar_t` *const p, const T *const idx)
- static `INLINE PURE vect_t load` (const `scalar_t` *const p)
- static `INLINE PURE vect_t loadu` (const `scalar_t` *const p)
- static `INLINE void store` (`scalar_t` *p, `vect_t` v)
- static `INLINE void storeu` (`scalar_t` *p, `vect_t` v)
- static `INLINE void stream` (`scalar_t` *p, const `vect_t` v)
- `template<int s>`
static `INLINE CONST vect_t sll` (const `vect_t` a)
- `template<int s>`
static `INLINE CONST vect_t srl` (const `vect_t` a)
- `template<int s>`
static `INLINE CONST vect_t sra` (const `vect_t` a)
- `template<uint8_t s>`
static `INLINE CONST vect_t shuffle_twice` (const `vect_t` a)
- `template<uint64_t s>`
static `INLINE CONST vect_t shuffle` (const `vect_t` a)
- static `INLINE CONST vect_t unpacklo_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpacklo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE void unpacklohi` (`vect_t` &lo, `vect_t` &hi, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_even` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_odd` (const `vect_t` a, const `vect_t` b)
- static `INLINE void pack` (`vect_t` &even, `vect_t` &odd, const `vect_t` a, const `vect_t` b)
- static `INLINE void transpose` (`vect_t` &r0, `vect_t` &r1, `vect_t` &r2, `vect_t` &r3, `vect_t` &r4, `vect_t` &r5, `vect_t` &r6, `vect_t` &r7, `vect_t` &r8, `vect_t` &r9, `vect_t` &r10, `vect_t` &r11, `vect_t` &r12, `vect_t` &r13, `vect_t` &r14, `vect_t` &r15)
- `template<uint16_t s>`
static `INLINE CONST vect_t blend` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t add` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t addin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t sub` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t subin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t mullo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mulhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mulx` (`vect_t` a, `vect_t` b)
- static `INLINE CONST vect_t fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fnmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fnmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsubx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmsubxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t greater` (const `vect_t` a, const `vect_t` b)

- static `INLINE CONST vect_t lesser` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t greater_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST scalar_t hadd_to_scal` (const `vect_t` a)
- static `INLINE CONST vect_t round` (const `vect_t` a)
- static `INLINE vect_t mod` (`vect_t` &C, const `vect_t` &P, const `vect_t` &INVP, const `vect_t` &NEGP, const `vect_t` &MIN, const `vect_t` &MAX, `vect_t` &Q, `vect_t` &T)
- static `INLINE CONST vect_t zero` ()
- static `INLINE CONST vect_t zero` ()
- static `INLINE CONST vect_t vor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vxor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vand` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vandnot` (const `vect_t` a, const `vect_t` b)

Static Public Attributes

- static const constexpr size_t `vect_size` = 8
- static const constexpr size_t `alignment` = 32

12.291.1 Member Typedef Documentation

12.291.1.1 `vect_t` [1/2]

```
using vect_t = __m256i
```

12.291.1.2 `half_t` [1/2]

```
using half_t = __m128i
```

12.291.1.3 `scalar_t` [1/2]

```
using scalar_t = int32_t
```

12.291.1.4 `simdHalf` [1/2]

```
using simdHalf = Simd128<scalar_t>
```

12.291.1.5 `aligned_allocator` [1/2]

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.291.1.6 `aligned_vector` [1/2]

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.291.1.7 `is_same_element` [1/2]

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.291.1.8 `vect_t` [2/2]

```
using vect_t = __m512i
```

12.291.1.9 `half_t` [2/2]

```
using half_t = __m256i
```

12.291.1.10 scalar_t [2/2]

```
using scalar_t = int32_t
```

12.291.1.11 simdHalf [2/2]

```
using simdHalf = Simd256<scalar_t>
```

12.291.1.12 aligned_allocator [2/2]

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.291.1.13 aligned_vector [2/2]

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.291.1.14 is_same_element [2/2]

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.291.2 Member Function Documentation**12.291.2.1 type_string() [1/2]**

```
static const std::string type_string ( ) [inline], [static]
```

12.291.2.2 valid() [1/2]

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr]
```

12.291.2.3 compliant() [1/2]

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr]
```

12.291.2.4 set1() [1/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.291.2.5 set() [1/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7 ) [inline], [static]
```

12.291.2.6 gather() [1/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.291.2.7 load() [1/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.291.2.8 loadu() [1/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.291.2.9 store() [1/2]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.291.2.10 storeu() [1/2]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.291.2.11 stream() [1/2]

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static]
```

12.291.2.12 sll() [1/2]

```
template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static]
```

12.291.2.13 srl() [1/2]

```
template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static]
```

12.291.2.14 sra() [1/2]

```
template<int s>
static INLINE CONST vect_t sra (
    const vect_t a ) [inline], [static]
```

12.291.2.15 shuffle_twice() [1/2]

```
template<uint8_t s>
static INLINE CONST vect_t shuffle_twice (
    const vect_t a ) [inline], [static]
```


12.291.2.16 shuffle() [1/2]

```
template<uint32_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static]
```

12.291.2.17 unpacklo_intrinsic() [1/2]

```
static INLINE CONST vect_t unpacklo_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.18 unpackhi_intrinsic() [1/2]

```
static INLINE CONST vect_t unpackhi_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.19 unpacklo() [1/2]

```
static INLINE CONST vect_t unpacklo (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.20 unpackhi() [1/2]

```
static INLINE CONST vect_t unpackhi (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.21 unpacklohi() [1/2]

```
static INLINE void unpacklohi (
    vect_t & lo,
    vect_t & hi,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.22 pack_even() [1/2]

```
static INLINE CONST vect_t pack_even (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.23 pack_odd() [1/2]

```
static INLINE CONST vect_t pack_odd (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.24 pack() [1/2]

```
static INLINE void pack (
    vect_t & even,
    vect_t & odd,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.25 transpose() [1/2]

```
static INLINE void transpose (  
    vect_t & r0,  
    vect_t & r1,  
    vect_t & r2,  
    vect_t & r3,  
    vect_t & r4,  
    vect_t & r5,  
    vect_t & r6,  
    vect_t & r7 ) [inline], [static]
```

12.291.2.26 blend() [1/2]

```
template<uint8_t s>  
static INLINE CONST vect_t blend (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.27 add() [1/2]

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.28 addin() [1/2]

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.291.2.29 sub() [1/2]

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.30 subin() [1/2]

```
static INLINE vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.291.2.31 mullo() [1/2]

```
static INLINE CONST vect_t mullo (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.32 mul() [1/2]

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.33 mulhi() [1/2]

```
static INLINE CONST vect_t mulhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.34 mulx() [1/2]

```
static INLINE CONST vect_t mulx (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.291.2.35 fmadd() [1/2]

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.36 fmaddin() [1/2]

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.37 fmaddx() [1/2]

```
static INLINE CONST vect_t fmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.38 fmaddxin() [1/2]

```
static INLINE vect_t fmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.39 fnmadd() [1/2]

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.40 fnmaddin() [1/2]

```
static INLINE vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.41 fnmaddx() [1/2]

```
static INLINE CONST vect_t fnmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.42 fnmaddxin() [1/2]

```
static INLINE vect_t fnmaddxin (  
    vect_t & c,
```

```
const vect_t a,  
const vect_t b ) [inline], [static]
```

12.291.2.43 fmsub() [1/2]

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.44 fmsubin() [1/2]

```
static INLINE vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.45 fmsubx() [1/2]

```
static INLINE CONST vect_t fmsubx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.46 fmsubxin() [1/2]

```
static INLINE vect_t fmsubxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.47 eq() [1/2]

```
static INLINE CONST vect_t eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.48 greater() [1/2]

```
static INLINE CONST vect_t greater (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.49 lesser() [1/2]

```
static INLINE CONST vect_t lesser (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.50 greater_eq() [1/2]

```
static INLINE CONST vect_t greater_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.51 lesser_eq() [1/2]

```
static INLINE CONST vect_t lesser_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.52 hadd_to_scal() [1/2]

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.291.2.53 round() [1/2]

```
static INLINE CONST vect_t round (
    const vect_t a ) [inline], [static]
```

12.291.2.54 mod() [1/2]

```
static INLINE vect_t mod (
    vect_t & C,
    const vect_t & P,
    const vect_t & INVP,
    const vect_t & NEGP,
    const vect_t & MIN,
    const vect_t & MAX,
    vect_t & Q,
    vect_t & T ) [inline], [static]
```

12.291.2.55 type_string() [2/2]

```
static const std::string type_string ( ) [inline], [static]
```

12.291.2.56 valid() [2/2]

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr]
```

12.291.2.57 compliant() [2/2]

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr]
```

12.291.2.58 set1() [2/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.291.2.59 set() [2/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7,
    const scalar_t x8,
    const scalar_t x9,
    const scalar_t x10,
    const scalar_t x11,
    const scalar_t x12,
    const scalar_t x13,
```

```
const scalar_t x14,
const scalar_t x15 ) [inline], [static]
```

12.291.2.60 gather() [2/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.291.2.61 load() [2/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.291.2.62 loadu() [2/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.291.2.63 store() [2/2]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.291.2.64 storeu() [2/2]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.291.2.65 stream() [2/2]

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static]
```

12.291.2.66 sll() [2/2]

```
template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static]
```

12.291.2.67 srl() [2/2]

```
template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static]
```

12.291.2.68 sra() [2/2]

```
template<int s>
static INLINE CONST vect_t sra (
    const vect_t a ) [inline], [static]
```

12.291.2.69 shuffle_twice() [2/2]

```
template<uint8_t s>
static INLINE CONST vect_t shuffle_twice (
    const vect_t a ) [inline], [static]
```

12.291.2.70 shuffle() [2/2]

```
template<uint64_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static]
```

12.291.2.71 unpacklo_intrinsic() [2/2]

```
static INLINE CONST vect_t unpacklo_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.72 unpackhi_intrinsic() [2/2]

```
static INLINE CONST vect_t unpackhi_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.73 unpacklo() [2/2]

```
static INLINE CONST vect_t unpacklo (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.74 unpackhi() [2/2]

```
static INLINE CONST vect_t unpackhi (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.75 unpacklohi() [2/2]

```
static INLINE void unpacklohi (
    vect_t & lo,
    vect_t & hi,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.76 pack_even() [2/2]

```
static INLINE CONST vect_t pack_even (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.77 pack_odd() [2/2]

```
static INLINE CONST vect_t pack_odd (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.78 pack() [2/2]

```
static INLINE void pack (  
    vect_t & even,  
    vect_t & odd,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.79 transpose() [2/2]

```
static INLINE void transpose (  
    vect_t & r0,  
    vect_t & r1,  
    vect_t & r2,  
    vect_t & r3,  
    vect_t & r4,  
    vect_t & r5,  
    vect_t & r6,  
    vect_t & r7,  
    vect_t & r8,  
    vect_t & r9,  
    vect_t & r10,  
    vect_t & r11,  
    vect_t & r12,  
    vect_t & r13,  
    vect_t & r14,  
    vect_t & r15 ) [inline], [static]
```

12.291.2.80 blend() [2/2]

```
template<uint16_t s>  
static INLINE CONST vect_t blend (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.81 add() [2/2]

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.82 addin() [2/2]

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.291.2.83 sub() [2/2]

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.84 subin() [2/2]

```
static INLINE vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```


12.291.2.85 mullo() [2/2]

```
static INLINE CONST vect_t mullo (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.86 mul() [2/2]

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.87 mulhi() [2/2]

```
static INLINE CONST vect_t mulhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.88 mulx() [2/2]

```
static INLINE CONST vect_t mulx (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.291.2.89 fmadd() [2/2]

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.90 fmaddin() [2/2]

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.91 fmaddx() [2/2]

```
static INLINE CONST vect_t fmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.92 fmaddxin() [2/2]

```
static INLINE vect_t fmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.93 fnmadd() [2/2]

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.94 fnmaddin() [2/2]

```
static INLINE vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.95 fnmaddx() [2/2]

```
static INLINE CONST vect_t fnmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.96 fnmaddxin() [2/2]

```
static INLINE vect_t fnmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.97 fmsub() [2/2]

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.98 fmsubin() [2/2]

```
static INLINE vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.99 fmsubx() [2/2]

```
static INLINE CONST vect_t fmsubx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.100 fmsubxin() [2/2]

```
static INLINE vect_t fmsubxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.101 eq() [2/2]

```
static INLINE CONST vect_t eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.102 greater() [2/2]

```
static INLINE CONST vect_t greater (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.291.2.103 lesser() [2/2]

```
static INLINE CONST vect_t lesser (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.104 greater_eq() [2/2]

```
static INLINE CONST vect_t greater_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.105 lesser_eq() [2/2]

```
static INLINE CONST vect_t lesser_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.291.2.106 hadd_to_scal() [2/2]

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.291.2.107 round() [2/2]

```
static INLINE CONST vect_t round (
    const vect_t a ) [inline], [static]
```

12.291.2.108 mod() [2/2]

```
static INLINE vect_t mod (
    vect_t & C,
    const vect_t & P,
    const vect_t & INVP,
    const vect_t & NEGP,
    const vect_t & MIN,
    const vect_t & MAX,
    vect_t & Q,
    vect_t & T ) [inline], [static]
```

12.291.2.109 zero() [1/2]

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.291.2.110 zero() [2/2]

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.291.2.111 vor()

```
static INLINE CONST vect_t vor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.291.2.112 vxor()

```
static INLINE CONST vect_t vxor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.291.2.113 vand()

```
static INLINE CONST vect_t vand (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.291.2.114 vandnot()

```
static INLINE CONST vect_t vandnot (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.291.3 Field Documentation**12.291.3.1 vect_size**

```
static const constexpr size_t vect_size = 8 [static], [constexpr]
```

12.291.3.2 alignment


```
static const constexpr size_t alignment = 32 [static], [constexpr]
```

The documentation for this struct was generated from the following files:

- [simd256_int32.inl](#)
- [simd512_int32.inl](#)

12.292 Simd256_impl< true, true, true, 8 > Struct Reference

Inheritance diagram for Simd256_impl< true, true, true, 8 >:

**Data Structures**

- union [Converter](#)

Public Types

- using [vect_t](#) = __m256i
- using [half_t](#) = __m128i
- using [scalar_t](#) = int64_t
- using [simdHalf](#) = [Simd128](#)< [scalar_t](#) >
- using [aligned_allocator](#) = [AlignedAllocator](#)< [scalar_t](#), [Alignment](#)([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >
- template<class [Field](#) >
using [is_same_element](#) = std::is_same< typename [Field::Element](#), [scalar_t](#) >

Static Public Member Functions

- static const std::string [type_string](#) ()
- template<class T >
static constexpr bool [valid](#) (T *p)
- template<class T >
static constexpr bool [compliant](#) (T n)
- static [INLINE CONST vect_t set1](#) (const [scalar_t](#) x)
- static [INLINE CONST vect_t set](#) (const [scalar_t](#) x0, const [scalar_t](#) x1, const [scalar_t](#) x2, const [scalar_t](#) x3)
- template<class T >
static [INLINE PURE vect_t gather](#) (const [scalar_t](#) *const p, const T *const idx)
- template<int idx>
static [INLINE CONST scalar_t get](#) ([vect_t](#) v)
- static [INLINE PURE vect_t load](#) (const [scalar_t](#) *const p)
- static [INLINE PURE vect_t loadu](#) (const [scalar_t](#) *const p)
- static [INLINE](#) void [store](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE](#) void [storeu](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE](#) void [stream](#) ([scalar_t](#) *p, const [vect_t](#) v)
- template<int s>
static [INLINE CONST vect_t sll](#) (const [vect_t](#) a)
- template<int s>
static [INLINE CONST vect_t srl](#) (const [vect_t](#) a)
- template<int s>
static [INLINE CONST vect_t sra](#) (const [vect_t](#) a)
- template<uint8_t s>
static [INLINE CONST vect_t shuffle](#) (const [vect_t](#) a)
- static [INLINE CONST vect_t unpacklo_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpacklo](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) void [unpacklohi](#) ([vect_t](#) &lo, [vect_t](#) &hi, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_even](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_odd](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) void [pack](#) ([vect_t](#) &even, [vect_t](#) &odd, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) void [transpose](#) ([vect_t](#) &r0, [vect_t](#) &r1, [vect_t](#) &r2, [vect_t](#) &r3)
- template<uint8_t s>
static [INLINE CONST vect_t blend](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t add](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) [vect_t](#) [addin](#) ([vect_t](#) &a, const [vect_t](#) b)
- static [INLINE CONST vect_t sub](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) [vect_t](#) [subin](#) ([vect_t](#) &a, const [vect_t](#) b)
- static [INLINE CONST vect_t mullo](#) ([vect_t](#) a, [vect_t](#) b)
- static [INLINE CONST vect_t mul](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t mulhi](#) ([vect_t](#) a, [vect_t](#) b)
- static [INLINE CONST vect_t mulx](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t fmaddd](#) (const [vect_t](#) c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) [vect_t](#) [fmadddin](#) ([vect_t](#) &c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t fmadddx](#) (const [vect_t](#) c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) [vect_t](#) [fmadddxin](#) ([vect_t](#) &c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t fnmadd](#) (const [vect_t](#) c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) [vect_t](#) [fnmaddin](#) ([vect_t](#) &c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t fnmaddx](#) (const [vect_t](#) c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) [vect_t](#) [fnmaddxin](#) ([vect_t](#) &c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t fmsub](#) (const [vect_t](#) c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) [vect_t](#) [fmsubin](#) ([vect_t](#) &c, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t fmsubx](#) (const [vect_t](#) c, const [vect_t](#) a, const [vect_t](#) b)

- static `INLINE vect_t fmsubxin (vect_t &c, const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t eq (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t greater (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t lesser (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t greater_eq (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t lesser_eq (const vect_t a, const vect_t b)`
- static `INLINE CONST scalar_t hadd_to_scal (const vect_t a)`
- static `INLINE CONST vect_t round (const vect_t a)`
- static `INLINE CONST vect_t mask_high ()`
- static `INLINE CONST vect_t mulhi_fast (vect_t x, vect_t y)`
- static `INLINE vect_t mod (vect_t &C, const __m256d &P, const __m256d &INVP, const __m256d &NEGP, const vect_t &POW50REM, const __m256d &MIN, const __m256d &MAX, __m256d &Q, __m256d &T)`
- static `INLINE CONST vect_t zero ()`

Static Public Attributes

- static const constexpr size_t `vect_size` = 4
- static const constexpr size_t `alignment` = 32

Static Protected Member Functions

- static `INLINE CONST vect_t signbits (const vect_t x)`

12.292.1 Member Typedef Documentation

12.292.1.1 vect_t

```
using vect_t = __m256i
```

12.292.1.2 half_t

```
using half_t = __m128i
```

12.292.1.3 scalar_t

```
using scalar_t = int64_t
```

12.292.1.4 simdHalf

```
using simdHalf = Simd128<scalar_t>
```

12.292.1.5 aligned_allocator

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.292.1.6 aligned_vector

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.292.1.7 is_same_element

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.292.2 Member Function Documentation

12.292.2.1 type_string()

```
static const std::string type_string ( ) [inline], [static]
```

12.292.2.2 valid()

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr]
```

12.292.2.3 compliant()

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr]
```

12.292.2.4 set1()

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.292.2.5 set()

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3 ) [inline], [static]
```

12.292.2.6 gather()

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.292.2.7 get()

```
template<int idx>
static INLINE CONST scalar_t get (
    vect_t v ) [inline], [static]
```

12.292.2.8 load()

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.292.2.9 loadu()

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.292.2.10 store()

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.292.2.11 storeu()

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.292.2.12 stream()

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static]
```

12.292.2.13 sll()

```
template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static]
```

12.292.2.14 srl()

```
template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static]
```

12.292.2.15 sra()

```
template<int s>
static INLINE CONST vect_t sra (
    const vect_t a ) [inline], [static]
```

12.292.2.16 shuffle()

```
template<uint8_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static]
```

12.292.2.17 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.292.2.18 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.292.2.19 unpacklo()

```
static INLINE CONST vect_t unpacklo (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.292.2.20 unpackhi()

```
static INLINE CONST vect_t unpackhi (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.292.2.21 unpacklohi()

```
static INLINE void unpacklohi (
    vect_t & lo,
    vect_t & hi,
    const vect_t a,
    const vect_t b ) [inline], [static]
```


12.292.2.22 pack_even()

```
static INLINE CONST vect_t pack_even (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.23 pack_odd()

```
static INLINE CONST vect_t pack_odd (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.24 pack()

```
static INLINE void pack (  
    vect_t & even,  
    vect_t & odd,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.25 transpose()

```
static INLINE void transpose (  
    vect_t & r0,  
    vect_t & r1,  
    vect_t & r2,  
    vect_t & r3 ) [inline], [static]
```

12.292.2.26 blend()

```
template<uint8_t s>  
static INLINE CONST vect_t blend (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.27 add()

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.28 addin()

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.292.2.29 sub()

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.30 subin()

```
static INLINE vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.292.2.31 mullo()

```
static INLINE CONST vect_t mullo (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.292.2.32 mul()

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.33 mulhi()

```
static INLINE CONST vect_t mulhi (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.292.2.34 mulx()

```
static INLINE CONST vect_t mulx (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.35 fmadd()

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.36 fmaddin()

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.37 fmaddx()

```
static INLINE CONST vect_t fmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.38 fmaddxin()

```
static INLINE vect_t fmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.39 fnmadd()

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.40 fnmaddin()

```
static INLINE vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.41 fnmaddx()

```
static INLINE CONST vect_t fnmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.42 fnmaddxin()

```
static INLINE vect_t fnmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.43 fmsub()

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.44 fmsubin()

```
static INLINE vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.45 fmsubx()

```
static INLINE CONST vect_t fmsubx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.46 fmsubxin()

```
static INLINE vect_t fmsubxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.47 eq()

```
static INLINE CONST vect_t eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.48 greater()

```
static INLINE CONST vect_t greater (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.292.2.49 lesser()

```
static INLINE CONST vect_t lesser (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.292.2.50 greater_eq()

```
static INLINE CONST vect_t greater_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.292.2.51 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.292.2.52 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.292.2.53 round()

```
static INLINE CONST vect_t round (
    const vect_t a ) [inline], [static]
```

12.292.2.54 mask_high()

```
static INLINE CONST vect_t mask_high ( ) [inline], [static]
```

12.292.2.55 mulhi_fast()

```
INLINE CONST vect_t mulhi_fast (
    vect_t x,
    vect_t y ) [static]
```

12.292.2.56 mod()

```
INLINE vect_t mod (
    vect_t & C,
    const __m256d & P,
    const __m256d & INV_P,
    const __m256d & NEG_P,
    const vect_t & POW50REM,
    const __m256d & MIN,
    const __m256d & MAX,
    __m256d & Q,
    __m256d & T ) [static]
```

12.292.2.57 signbits()

```
static INLINE CONST vect_t signbits (
    const vect_t x ) [inline], [static], [protected]
```

12.292.2.58 zero()

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.292.3 Field Documentation

12.292.3.1 vect_size

```
const constexpr size_t vect_size = 4 [static], [constexpr]
```

12.292.3.2 alignment


```
const constexpr size_t alignment = 32 [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [simd256_int64.inl](#)

12.293 Simd256fp_base Struct Reference

Inheritance diagram for Simd256fp_base:




The documentation for this struct was generated from the following file:

- [simd256.inl](#)

12.294 Simd256i_base Struct Reference

Inheritance diagram for Simd256i_base:



Public Types

- using [vect_t](#) = __m256i

Static Public Member Functions

- static [INLINE CONST vect_t zero](#) ()

12.294.1 Member Typedef Documentation

12.294.1.1 vect_t

```
using vect\_t = __m256i
```

12.294.2 Member Function Documentation

12.294.2.1 zero()

```
static INLINE CONST vect\_t zero ( ) [inline], [static]
```

The documentation for this struct was generated from the following file:

- [simd256.inl](#)

12.295 Simd512_impl< ArithType, Int, Signed, Size > Struct Template Reference

The documentation for this struct was generated from the following file:

- [simd512.inl](#)

12.296 Simd512_impl< true, false, true, 4 > Struct Reference

The documentation for this struct was generated from the following file:

- [simd512_float.inl](#)

12.297 Simd512_impl< true, false, true, 8 > Struct Reference

Public Types

- using [vect_t](#) = __m512d
- using [scalar_t](#) = double
- using [aligned_allocator](#) = AlignedAllocator< [scalar_t](#), Alignment([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >
- template<class [Field](#) >
using [is_same_element](#) = std::is_same< typename [Field::Element](#), [scalar_t](#) >

Static Public Member Functions

- static const std::string [type_string](#) ()
- template<class T >
static constexpr bool [valid](#) (T *p)
- template<class T >
static constexpr bool [compliant](#) (T n)
- static [INLINE CONST vect_t zero](#) ()
- static [INLINE CONST vect_t set1](#) (const [scalar_t](#) x)
- static [INLINE CONST vect_t set](#) (const [scalar_t](#) x1, const [scalar_t](#) x2, const [scalar_t](#) x3, const [scalar_t](#) x4, const [scalar_t](#) x5, const [scalar_t](#) x6, const [scalar_t](#) x7, const [scalar_t](#) x8)
- template<class T >
static [INLINE PURE vect_t gather](#) (const [scalar_t](#) *const p, const T *const idx)
- static [INLINE PURE vect_t load](#) (const [scalar_t](#) *const p)
- static [INLINE PURE vect_t loadu](#) (const [scalar_t](#) *const p)
- static [INLINE](#) void [store](#) (const [scalar_t](#) *p, const [vect_t](#) v)
- static [INLINE](#) void [storeu](#) (const [scalar_t](#) *p, const [vect_t](#) v)
- static [INLINE](#) void [stream](#) (const [scalar_t](#) *p, const [vect_t](#) v)
- template<uint8_t s>
static [INLINE CONST vect_t shuffle](#) (const [vect_t](#) a)
- static [INLINE CONST vect_t unpacklo_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi_intrinsic](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpacklo](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t unpackhi](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) void [unpacklohi](#) ([vect_t](#) &lo, [vect_t](#) &hi, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_even](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t pack_odd](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) void [pack](#) ([vect_t](#) &even, [vect_t](#) &odd, const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE](#) void [transpose](#) ([vect_t](#) &r0, [vect_t](#) &r1, [vect_t](#) &r2, [vect_t](#) &r3, [vect_t](#) &r4, [vect_t](#) &r5, [vect_t](#) &r6, [vect_t](#) &r7)
- template<uint8_t s>
static [INLINE CONST vect_t blend](#) (const [vect_t](#) a, const [vect_t](#) b)

- static `INLINE CONST vect_t blendv` (const `vect_t` a, const `vect_t` b, const `vect_t` mask)
- static `INLINE CONST vect_t add` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t addin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t sub` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t subin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mulin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t div` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t greater` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t greater_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t floor` (const `vect_t` a)
- static `INLINE CONST vect_t ceil` (const `vect_t` a)
- static `INLINE CONST vect_t round` (const `vect_t` a)
- static `INLINE CONST vect_t hadd` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST scalar_t hadd_to_scal` (const `vect_t` a)

Static Public Attributes

- static const constexpr size_t `vect_size` = 8
- static const constexpr size_t `alignment` = 64

12.297.1 Member Typedef Documentation

12.297.1.1 vect_t

```
using vect_t = __m512d
```

12.297.1.2 scalar_t

```
using scalar_t = double
```

12.297.1.3 aligned_allocator

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.297.1.4 aligned_vector

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.297.1.5 is_same_element

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.297.2 Member Function Documentation

12.297.2.1 type_string()

```
static const std::string type_string ( ) [inline], [static]
```

12.297.2.2 valid()

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr]
```

12.297.2.3 compliant()

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr]
```

12.297.2.4 zero()

```
static INLINE CONST vect_t zero ( ) [inline], [static]
```

12.297.2.5 set1()

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.297.2.6 set()

```
static INLINE CONST vect_t set (
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7,
    const scalar_t x8 ) [inline], [static]
```

12.297.2.7 gather()

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.297.2.8 load()

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.297.2.9 loadu()

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.297.2.10 store()

```
static INLINE void store (
    const scalar_t * p,
    const vect_t v ) [inline], [static]
```

12.297.2.11 storeu()

```
static INLINE void storeu (
    const scalar_t * p,
    const vect_t v ) [inline], [static]
```


12.297.2.12 stream()

```
static INLINE void stream (  
    const scalar_t * p,  
    const vect_t v ) [inline], [static]
```

12.297.2.13 shuffle()

```
template<uint8_t s>  
static INLINE CONST vect_t shuffle (  
    const vect_t a ) [inline], [static]
```

12.297.2.14 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.15 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.16 unpacklo()

```
static INLINE CONST vect_t unpacklo (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.17 unpackhi()

```
static INLINE CONST vect_t unpackhi (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.18 unpacklohi()

```
static INLINE void unpacklohi (  
    vect_t & lo,  
    vect_t & hi,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.19 pack_even()

```
static INLINE CONST vect_t pack_even (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.20 pack_odd()

```
static INLINE CONST vect_t pack_odd (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.21 pack()

```
static INLINE void pack (  
    vect_t & even,  
    vect_t & odd,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.22 transpose()

```
static INLINE void transpose (  
    vect_t & r0,  
    vect_t & r1,  
    vect_t & r2,  
    vect_t & r3,  
    vect_t & r4,  
    vect_t & r5,  
    vect_t & r6,  
    vect_t & r7 ) [inline], [static]
```

12.297.2.23 blend()

```
template<uint8_t s>  
static INLINE CONST vect_t blend (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.24 blendv()

```
static INLINE CONST vect_t blendv (  
    const vect_t a,  
    const vect_t b,  
    const vect_t mask ) [inline], [static]
```

12.297.2.25 add()

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.26 addin()

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.297.2.27 sub()

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.28 subin()

```
static INLINE CONST vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.297.2.29 mul()

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.30 mulin()

```
static INLINE CONST vect_t mulin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.297.2.31 div()

```
static INLINE CONST vect_t div (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.32 fmadd()

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.33 fmaddin()

```
static INLINE CONST vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.34 fnmadd()

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.35 fnmaddin()

```
static INLINE CONST vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.36 fmsub()

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.37 fmsubin()

```
static INLINE CONST vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.38 eq()

```
static INLINE CONST vect_t eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.39 lesser()

```
static INLINE CONST vect_t lesser (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.40 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.41 greater()

```
static INLINE CONST vect_t greater (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.42 greater_eq()

```
static INLINE CONST vect_t greater_eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.43 floor()

```
static INLINE CONST vect_t floor (  
    const vect_t a ) [inline], [static]
```

12.297.2.44 ceil()

```
static INLINE CONST vect_t ceil (  
    const vect_t a ) [inline], [static]
```

12.297.2.45 round()

```
static INLINE CONST vect_t round (  
    const vect_t a ) [inline], [static]
```

12.297.2.46 hadd()

```
static INLINE CONST vect_t hadd (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.297.2.47 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (  
    const vect_t a ) [inline], [static]
```

12.297.3 Field Documentation

12.297.3.1 vect_size

```
const constexpr size_t vect_size = 8 [static], [constexpr]
```

12.297.3.2 alignment


```
const constexpr size_t alignment = 64 [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [simd512_double.inl](#)

12.298 Simd512_impl< true, true, false, 8 > Struct Reference

Inheritance diagram for Simd512_impl< true, true, false, 8 >:



Data Structures

- union [Converter](#)

Public Types

- using [scalar_t](#) = uint64_t
- using [aligned_allocator](#) = AlignedAllocator< [scalar_t](#), Alignment([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >
- template<class [Field](#) >
using [is_same_element](#) = std::is_same< typename [Field::Element](#), [scalar_t](#) >
- using [simdHalf](#) = [Simd256](#)< [scalar_t](#) >
- using [vect_t](#) = __m512i
- using [half_t](#) = __m256i

Static Public Member Functions

- static const std::string [type_string](#) ()
- static [INLINE CONST vect_t set1](#) (const [scalar_t](#) x)
- static [INLINE CONST vect_t set](#) (const [scalar_t](#) x0, const [scalar_t](#) x1, const [scalar_t](#) x2, const [scalar_t](#) x3, const [scalar_t](#) x4, const [scalar_t](#) x5, const [scalar_t](#) x6, const [scalar_t](#) x7)
- template<class T >
static [INLINE PURE vect_t gather](#) (const [scalar_t](#) *const p, const T *const idx)
- static [INLINE PURE vect_t load](#) (const [scalar_t](#) *const p)
- static [INLINE PURE vect_t loadu](#) (const [scalar_t](#) *const p)
- static [INLINE void store](#) ([scalar_t](#) *p, [vect_t](#) v)
- template<uint8_t k>
static [INLINE void maskstore](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void storeu](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void stream](#) ([scalar_t](#) *p, const [vect_t](#) v)
- template<int s>
static [INLINE CONST vect_t sra](#) (const [vect_t](#) a)
- static [INLINE CONST vect_t greater](#) ([vect_t](#) a, [vect_t](#) b)
- static [INLINE CONST vect_t lesser](#) ([vect_t](#) a, [vect_t](#) b)
- static [INLINE CONST vect_t greater_eq](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t lesser_eq](#) (const [vect_t](#) a, const [vect_t](#) b)
- static [INLINE CONST vect_t mullo](#) ([vect_t](#) a, [vect_t](#) b)

- static `INLINE CONST vect_t mulhi (vect_t a, vect_t b)`
- static `INLINE CONST vect_t mulx (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t fmaddx (const vect_t c, const vect_t a, const vect_t b)`
- static `INLINE vect_t fmaddxin (vect_t &c, const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t fnmaddx (const vect_t c, const vect_t a, const vect_t b)`
- static `INLINE vect_t fnmaddxin (vect_t &c, const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t fmsubx (const vect_t c, const vect_t a, const vect_t b)`
- static `INLINE vect_t fmsubxin (vect_t &c, const vect_t a, const vect_t b)`
- static `INLINE CONST scalar_t hadd_to_scal (const vect_t a)`
- `template<class T >`
static constexpr bool `valid (T *p)`
- `template<class T >`
static constexpr bool `compliant (T n)`
- static `INLINE CONST vect_t set1 (const scalar_t x)`
- static `INLINE CONST vect_t set (const scalar_t x0, const scalar_t x1, const scalar_t x2, const scalar_t x3, const scalar_t x4, const scalar_t x5, const scalar_t x6, const scalar_t x7)`
- static `INLINE CONST vect_t set (const scalar_t x0, const scalar_t x1, const scalar_t x2, const scalar_t x3)`
- `template<class T >`
static `INLINE PURE vect_t gather (const scalar_t *const p, const T *const idx)`
- static `INLINE PURE vect_t load (const scalar_t *const p)`
- static `INLINE PURE vect_t loadu (const scalar_t *const p)`
- static `INLINE void store (scalar_t *p, vect_t v)`
- `template<uint8_t k>`
static `INLINE void maskstore (scalar_t *p, vect_t v)`
- static `INLINE void storeu (scalar_t *p, vect_t v)`
- static `INLINE void stream (scalar_t *p, const vect_t v)`
- `template<int s>`
static `INLINE CONST vect_t sll (const vect_t a)`
- `template<int s>`
static `INLINE CONST vect_t srl (const vect_t a)`
- `template<uint8_t s>`
static `INLINE CONST vect_t shuffle (const vect_t a)`
- static `INLINE CONST vect_t unpacklo_intrinsic (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t unpackhi_intrinsic (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t unpacklo (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t unpackhi (const vect_t a, const vect_t b)`
- static `INLINE void unpacklohi (vect_t &lo, vect_t &hi, const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t pack_even (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t pack_odd (const vect_t a, const vect_t b)`
- static `INLINE void pack (vect_t &even, vect_t &odd, const vect_t a, const vect_t b)`
- static `INLINE void transpose (vect_t &r0, vect_t &r1, vect_t &r2, vect_t &r3, vect_t &r4, vect_t &r5, vect_t &r6, vect_t &r7)`
- `template<uint8_t s>`
static `INLINE CONST vect_t blend (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t add (const vect_t a, const vect_t b)`
- static `INLINE vect_t addin (vect_t &a, const vect_t b)`
- static `INLINE CONST vect_t sub (const vect_t a, const vect_t b)`
- static `INLINE vect_t subin (vect_t &a, const vect_t b)`
- static `INLINE CONST vect_t mul (const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t fmadd (const vect_t c, const vect_t a, const vect_t b)`
- static `INLINE vect_t fmadin (vect_t &c, const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t fnmadd (const vect_t c, const vect_t a, const vect_t b)`
- static `INLINE vect_t fnmadin (vect_t &c, const vect_t a, const vect_t b)`
- static `INLINE CONST vect_t fmsub (const vect_t c, const vect_t a, const vect_t b)`
- static `INLINE vect_t fmsubin (vect_t &c, const vect_t a, const vect_t b)`

- static `INLINE CONST vect_t eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t round` (const `vect_t` a)
- static `INLINE CONST vect_t mask_high` ()
- static `INLINE CONST vect_t mulhi_fast` (`vect_t` x, `vect_t` y)
- static `INLINE vect_t mod` (`vect_t` &C, const `__m512d` &P, const `__m512d` &INVP, const `__m512d` &NEGP, const `vect_t` &POW50REM, const `__m512d` &MIN, const `__m512d` &MAX, `__m512d` &Q, `__m512d` &T)
- static `INLINE CONST vect_t zero` ()
- static `INLINE CONST vect_t vor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vxor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vand` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vandnot` (const `vect_t` a, const `vect_t` b)

Static Public Attributes

- static const constexpr size_t `vect_size` = 8
- static const constexpr size_t `alignment` = 64

Static Protected Member Functions

- static `INLINE CONST vect_t signbits` (const `vect_t` x)

12.298.1 Member Typedef Documentation

12.298.1.1 scalar_t

```
using scalar_t = uint64_t
```

12.298.1.2 aligned_allocator

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.298.1.3 aligned_vector

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.298.1.4 is_same_element

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.298.1.5 simdHalf

```
using simdHalf = Simd256<scalar_t>
```

12.298.1.6 vect_t

```
using vect_t = __m512i [inherited]
```

12.298.1.7 half_t

```
using half_t = __m256i [inherited]
```

12.298.2 Member Function Documentation

12.298.2.1 type_string()

```
static const std::string type_string ( ) [inline], [static]
```

12.298.2.2 set1() [1/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.298.2.3 set() [1/3]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7 ) [inline], [static]
```

12.298.2.4 gather() [1/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.298.2.5 load() [1/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.298.2.6 loadu() [1/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.298.2.7 store() [1/2]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.298.2.8 maskstore() [1/2]

```
template<uint8_t k>
static INLINE void maskstore (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.298.2.9 storeu() [1/2]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.298.2.10 stream() [1/2]

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static]
```


12.298.2.11 sra()

```
template<int s>
static INLINE CONST vect_t sra (
    const vect_t a ) [inline], [static]
```

12.298.2.12 greater()

```
static INLINE CONST vect_t greater (
    vect_t a,
    vect_t b ) [inline], [static]
```

12.298.2.13 lesser()

```
static INLINE CONST vect_t lesser (
    vect_t a,
    vect_t b ) [inline], [static]
```

12.298.2.14 greater_eq()

```
static INLINE CONST vect_t greater_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.298.2.15 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.298.2.16 mullo()

```
static INLINE CONST vect_t mullo (
    vect_t a,
    vect_t b ) [inline], [static]
```

12.298.2.17 mulhi()

```
static INLINE CONST vect_t mulhi (
    vect_t a,
    vect_t b ) [inline], [static]
```

12.298.2.18 mulx()

```
static INLINE CONST vect_t mulx (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.298.2.19 fmaddx()

```
static INLINE CONST vect_t fmaddx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.298.2.20 fmaddxin()

```
static INLINE vect_t fmaddxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.298.2.21 fnmaddx()

```
static INLINE CONST vect_t fnmaddx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.298.2.22 fnmaddxin()

```
static INLINE vect_t fnmaddxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.298.2.23 fmsubx()

```
static INLINE CONST vect_t fmsubx (
    const vect_t c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.298.2.24 fmsubxin()

```
static INLINE vect_t fmsubxin (
    vect_t & c,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.298.2.25 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.298.2.26 valid()

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr], [inherited]
```

12.298.2.27 compliant()

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr], [inherited]
```

12.298.2.28 set1() [2/2]

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static], [inherited]
```

12.298.2.29 set() [2/3]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
```

```
const scalar_t x6,
const scalar_t x7 ) [inline], [static], [inherited]
```

12.298.2.30 set() [3/3]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3 ) [inline], [static], [inherited]
```

12.298.2.31 gather() [2/2]

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static], [inherited]
```

12.298.2.32 load() [2/2]

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static], [inherited]
```

12.298.2.33 loadu() [2/2]

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static], [inherited]
```

12.298.2.34 store() [2/2]

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]
```

12.298.2.35 maskstore() [2/2]

```
template<uint8_t k>
static INLINE void maskstore (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]
```

12.298.2.36 storeu() [2/2]

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static], [inherited]
```

12.298.2.37 stream() [2/2]

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static], [inherited]
```

12.298.2.38 sll()

```
template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static], [inherited]
```

12.298.2.39 srl()

```
template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static], [inherited]
```

12.298.2.40 shuffle()

```
template<uint8_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static], [inherited]
```

12.298.2.41 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.42 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.43 unpacklo()

```
static INLINE CONST vect_t unpacklo (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.44 unpackhi()

```
static INLINE CONST vect_t unpackhi (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.45 unpacklohi()

```
static INLINE void unpacklohi (
    vect_t & lo,
    vect_t & hi,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.46 pack_even()

```
static INLINE CONST vect_t pack_even (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.47 pack_odd()

```
static INLINE CONST vect_t pack_odd (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.48 pack()

```
static INLINE void pack (
    vect_t & even,
    vect_t & odd,
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.49 transpose()

```
static INLINE void transpose (
    vect_t & r0,
    vect_t & r1,
    vect_t & r2,
    vect_t & r3,
    vect_t & r4,
    vect_t & r5,
    vect_t & r6,
    vect_t & r7 ) [inline], [static], [inherited]
```

12.298.2.50 blend()

```
template<uint8_t s>
static INLINE CONST vect_t blend (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.51 add()

```
static INLINE CONST vect_t add (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.52 addin()

```
static INLINE vect_t addin (
    vect_t & a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.53 sub()

```
static INLINE CONST vect_t sub (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.54 subin()

```
static INLINE vect_t subin (
    vect_t & a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.55 mul()

```
static INLINE CONST vect_t mul (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.56 fmadd()

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.57 fmaddin()

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.58 fnmadd()

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.59 fnmaddin()

```
static INLINE vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.60 fmsub()

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.61 fmsubin()

```
static INLINE vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.62 eq()

```
static INLINE CONST vect_t eq (  
    const vect_t a,  
    const vect_t b ) [inline], [static], [inherited]
```

12.298.2.63 round()

```
static INLINE CONST vect_t round (  
    const vect_t a ) [inline], [static], [inherited]
```

12.298.2.64 mask_high()

```
static INLINE CONST vect_t mask_high ( ) [inline], [static], [inherited]
```

12.298.2.65 mulhi_fast()

```

INLINE CONST vect_t mulhi_fast (
    vect_t x,
    vect_t y ) [static], [inherited]

```

12.298.2.66 mod()

```

INLINE vect_t mod (
    vect_t & C,
    const __m512d & P,
    const __m512d & INV_P,
    const __m512d & NEG_P,
    const vect_t & POW50REM,
    const __m512d & MIN,
    const __m512d & MAX,
    __m512d & Q,
    __m512d & T ) [static], [inherited]

```

12.298.2.67 signbits()

```

static INLINE CONST vect_t signbits (
    const vect_t x ) [inline], [static], [protected], [inherited]

```

12.298.2.68 zero()

```

static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]

```

12.298.2.69 vor()

```

static INLINE CONST vect_t vor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]

```

12.298.2.70 vxor()

```

static INLINE CONST vect_t vxor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]

```

12.298.2.71 vand()

```

static INLINE CONST vect_t vand (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]

```

12.298.2.72 vandnot()

```

static INLINE CONST vect_t vandnot (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]

```

12.298.3 Field Documentation**12.298.3.1 vect_size**

```

const constexpr size_t vect_size = 8 [static], [constexpr], [inherited]

```

12.298.3.2 alignment


```
const constexpr size_t alignment = 64 [static], [constexpr], [inherited]
```

The documentation for this struct was generated from the following file:

- [simd512_int64.inl](#)

12.299 Simd512_impl< true, true, true, 8 > Struct Reference

Inheritance diagram for Simd512_impl< true, true, true, 8 >:



Data Structures

- union [Converter](#)

Public Types

- using [vect_t](#) = __m512i
- using [half_t](#) = __m256i
- using [scalar_t](#) = int64_t
- using [simdHalf](#) = [Simd256](#)< [scalar_t](#) >
- using [aligned_allocator](#) = [AlignedAllocator](#)< [scalar_t](#), [Alignment](#)([alignment](#))>
- using [aligned_vector](#) = std::vector< [scalar_t](#), [aligned_allocator](#) >
- template<class [Field](#) >
using [is_same_element](#) = std::is_same< typename [Field::Element](#), [scalar_t](#) >

Static Public Member Functions

- static const std::string [type_string](#) ()
- template<class T >
static constexpr bool [valid](#) (T *p)
- template<class T >
static constexpr bool [compliant](#) (T n)
- static [INLINE CONST vect_t set1](#) (const [scalar_t](#) x)
- static [INLINE CONST vect_t set](#) (const [scalar_t](#) x0, const [scalar_t](#) x1, const [scalar_t](#) x2, const [scalar_t](#) x3, const [scalar_t](#) x4, const [scalar_t](#) x5, const [scalar_t](#) x6, const [scalar_t](#) x7)
- static [INLINE CONST vect_t set](#) (const [scalar_t](#) x0, const [scalar_t](#) x1, const [scalar_t](#) x2, const [scalar_t](#) x3)
- template<class T >
static [INLINE PURE vect_t gather](#) (const [scalar_t](#) *const p, const T *const idx)
- static [INLINE PURE vect_t load](#) (const [scalar_t](#) *const p)
- static [INLINE PURE vect_t loadu](#) (const [scalar_t](#) *const p)
- static [INLINE void store](#) ([scalar_t](#) *p, [vect_t](#) v)
- template<uint8_t k>
static [INLINE void maskstore](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void storeu](#) ([scalar_t](#) *p, [vect_t](#) v)
- static [INLINE void stream](#) ([scalar_t](#) *p, const [vect_t](#) v)
- template<int s>
static [INLINE CONST vect_t sll](#) (const [vect_t](#) a)

- `template<int s>`
static `INLINE CONST vect_t srl` (const `vect_t` a)
- `template<int s>`
static `INLINE CONST vect_t sra` (const `vect_t` a)
- `template<uint8_t s>`
static `INLINE CONST vect_t shuffle` (const `vect_t` a)
- static `INLINE CONST vect_t unpacklo_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi_intrinsic` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpacklo` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t unpackhi` (const `vect_t` a, const `vect_t` b)
- static `INLINE void unpacklohi` (`vect_t` &lo, `vect_t` &hi, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_even` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t pack_odd` (const `vect_t` a, const `vect_t` b)
- static `INLINE void pack` (`vect_t` &even, `vect_t` &odd, const `vect_t` a, const `vect_t` b)
- static `INLINE void transpose` (`vect_t` &r0, `vect_t` &r1, `vect_t` &r2, `vect_t` &r3, `vect_t` &r4, `vect_t` &r5, `vect_t` &r6, `vect_t` &r7)
- `template<uint8_t s>`
static `INLINE CONST vect_t blend` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t add` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t addin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t sub` (const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t subin` (`vect_t` &a, const `vect_t` b)
- static `INLINE CONST vect_t mullo` (`vect_t` a, `vect_t` b)
- static `INLINE CONST vect_t mul` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t mulhi` (`vect_t` a, `vect_t` b)
- static `INLINE CONST vect_t mulx` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmadddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmadddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmadd` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fnmaddin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fnmaddx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fnmaddxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsub` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmsubin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t fmsubx` (const `vect_t` c, const `vect_t` a, const `vect_t` b)
- static `INLINE vect_t fmsubxin` (`vect_t` &c, const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t greater` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t greater_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t lesser_eq` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST scalar_t hadd_to_scal` (const `vect_t` a)
- static `INLINE CONST vect_t round` (const `vect_t` a)
- static `INLINE CONST vect_t mask_high` ()
- static `INLINE CONST vect_t mulhi_fast` (`vect_t` x, `vect_t` y)
- static `INLINE vect_t mod` (`vect_t` &C, const `__m512d` &P, const `__m512d` &INVP, const `__m512d` &NEGP, const `vect_t` &POW50REM, const `__m512d` &MIN, const `__m512d` &MAX, `__m512d` &Q, `__m512d` &T)
- static `INLINE CONST vect_t zero` ()
- static `INLINE CONST vect_t vor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vxor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vand` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vandnot` (const `vect_t` a, const `vect_t` b)

Static Public Attributes

- static const constexpr size_t `vect_size` = 8
- static const constexpr size_t `alignment` = 64

Static Protected Member Functions

- static `INLINE CONST vect_t signbits` (const `vect_t` x)

12.299.1 Member Typedef Documentation

12.299.1.1 `vect_t`

```
using vect_t = __m512i
```

12.299.1.2 `half_t`

```
using half_t = __m256i
```

12.299.1.3 `scalar_t`

```
using scalar_t = int64_t
```

12.299.1.4 `simdHalf`

```
using simdHalf = Simd256<scalar_t>
```

12.299.1.5 `aligned_allocator`

```
using aligned_allocator = AlignedAllocator<scalar_t, Alignment(alignment)>
```

12.299.1.6 `aligned_vector`

```
using aligned_vector = std::vector<scalar_t, aligned_allocator>
```

12.299.1.7 `is_same_element`

```
template<class Field >
using is_same_element = std::is_same<typename Field::Element, scalar_t>
```

12.299.2 Member Function Documentation

12.299.2.1 `type_string()`

```
static const std::string type_string ( ) [inline], [static]
```

12.299.2.2 `valid()`

```
template<class T >
static constexpr bool valid (
    T * p ) [inline], [static], [constexpr]
```

12.299.2.3 `compliant()`

```
template<class T >
static constexpr bool compliant (
    T n ) [inline], [static], [constexpr]
```

12.299.2.4 set1()

```
static INLINE CONST vect_t set1 (
    const scalar_t x ) [inline], [static]
```

12.299.2.5 set() [1/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3,
    const scalar_t x4,
    const scalar_t x5,
    const scalar_t x6,
    const scalar_t x7 ) [inline], [static]
```

12.299.2.6 set() [2/2]

```
static INLINE CONST vect_t set (
    const scalar_t x0,
    const scalar_t x1,
    const scalar_t x2,
    const scalar_t x3 ) [inline], [static]
```

12.299.2.7 gather()

```
template<class T >
static INLINE PURE vect_t gather (
    const scalar_t *const p,
    const T *const idx ) [inline], [static]
```

12.299.2.8 load()

```
static INLINE PURE vect_t load (
    const scalar_t *const p ) [inline], [static]
```

12.299.2.9 loadu()

```
static INLINE PURE vect_t loadu (
    const scalar_t *const p ) [inline], [static]
```

12.299.2.10 store()

```
static INLINE void store (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.299.2.11 maskstore()

```
template<uint8_t k>
static INLINE void maskstore (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.299.2.12 storeu()

```
static INLINE void storeu (
    scalar_t * p,
    vect_t v ) [inline], [static]
```

12.299.2.13 stream()

```
static INLINE void stream (
    scalar_t * p,
    const vect_t v ) [inline], [static]
```

12.299.2.14 sll()

```
template<int s>
static INLINE CONST vect_t sll (
    const vect_t a ) [inline], [static]
```

12.299.2.15 srl()

```
template<int s>
static INLINE CONST vect_t srl (
    const vect_t a ) [inline], [static]
```

12.299.2.16 sra()

```
template<int s>
static INLINE CONST vect_t sra (
    const vect_t a ) [inline], [static]
```

12.299.2.17 shuffle()

```
template<uint8_t s>
static INLINE CONST vect_t shuffle (
    const vect_t a ) [inline], [static]
```

12.299.2.18 unpacklo_intrinsic()

```
static INLINE CONST vect_t unpacklo_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.299.2.19 unpackhi_intrinsic()

```
static INLINE CONST vect_t unpackhi_intrinsic (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.299.2.20 unpacklo()

```
static INLINE CONST vect_t unpacklo (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.299.2.21 unpackhi()

```
static INLINE CONST vect_t unpackhi (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.299.2.22 unpacklohi()

```
static INLINE void unpacklohi (
    vect_t & lo,
    vect_t & hi,
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.299.2.23 pack_even()

```
static INLINE CONST vect_t pack_even (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.24 pack_odd()

```
static INLINE CONST vect_t pack_odd (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.25 pack()

```
static INLINE void pack (  
    vect_t & even,  
    vect_t & odd,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.26 transpose()

```
static INLINE void transpose (  
    vect_t & r0,  
    vect_t & r1,  
    vect_t & r2,  
    vect_t & r3,  
    vect_t & r4,  
    vect_t & r5,  
    vect_t & r6,  
    vect_t & r7 ) [inline], [static]
```

12.299.2.27 blend()

```
template<uint8_t s>  
static INLINE CONST vect_t blend (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.28 add()

```
static INLINE CONST vect_t add (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.29 addin()

```
static INLINE vect_t addin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.299.2.30 sub()

```
static INLINE CONST vect_t sub (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.31 subin()

```
static INLINE vect_t subin (  
    vect_t & a,  
    const vect_t b ) [inline], [static]
```

12.299.2.32 mullo()

```
static INLINE CONST vect_t mullo (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.299.2.33 mul()

```
static INLINE CONST vect_t mul (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.34 mulhi()

```
static INLINE CONST vect_t mulhi (  
    vect_t a,  
    vect_t b ) [inline], [static]
```

12.299.2.35 mulx()

```
static INLINE CONST vect_t mulx (  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.36 fmadd()

```
static INLINE CONST vect_t fmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.37 fmaddin()

```
static INLINE vect_t fmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.38 fmaddx()

```
static INLINE CONST vect_t fmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.39 fmaddxin()

```
static INLINE vect_t fmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.40 fnmadd()

```
static INLINE CONST vect_t fnmadd (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.41 fnmaddin()

```
static INLINE vect_t fnmaddin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.42 fnmaddx()

```
static INLINE CONST vect_t fnmaddx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.43 fnmaddxin()

```
static INLINE vect_t fnmaddxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.44 fmsub()

```
static INLINE CONST vect_t fmsub (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.45 fmsubin()

```
static INLINE vect_t fmsubin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.46 fmsubx()

```
static INLINE CONST vect_t fmsubx (  
    const vect_t c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.47 fmsubxin()

```
static INLINE vect_t fmsubxin (  
    vect_t & c,  
    const vect_t a,  
    const vect_t b ) [inline], [static]
```

12.299.2.48 eq()

```
static INLINE CONST vect_t eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.299.2.49 greater()

```
static INLINE CONST vect_t greater (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.299.2.50 lesser()

```
static INLINE CONST vect_t lesser (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.299.2.51 greater_eq()

```
static INLINE CONST vect_t greater_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.299.2.52 lesser_eq()

```
static INLINE CONST vect_t lesser_eq (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.299.2.53 hadd_to_scal()

```
static INLINE CONST scalar_t hadd_to_scal (
    const vect_t a ) [inline], [static]
```

12.299.2.54 round()

```
static INLINE CONST vect_t round (
    const vect_t a ) [inline], [static]
```

12.299.2.55 mask_high()

```
static INLINE CONST vect_t mask_high ( ) [inline], [static]
```

12.299.2.56 mulhi_fast()

```
INLINE CONST vect_t mulhi_fast (
    vect_t x,
    vect_t y ) [static]
```

12.299.2.57 mod()

```
INLINE vect_t mod (
    vect_t & C,
    const __m512d & P,
    const __m512d & INV_P,
    const __m512d & NEG_P,
    const vect_t & POW50REM,
    const __m512d & MIN,
    const __m512d & MAX,
```



```
__m512d & Q,
__m512d & T ) [static]
```

12.299.2.58 signbits()

```
static INLINE CONST vect_t signbits (
    const vect_t x ) [inline], [static], [protected]
```

12.299.2.59 zero()

```
static INLINE CONST vect_t zero ( ) [inline], [static], [inherited]
```

12.299.2.60 vor()

```
static INLINE CONST vect_t vor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.299.2.61 vxor()

```
static INLINE CONST vect_t vxor (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.299.2.62 vand()

```
static INLINE CONST vect_t vand (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.299.2.63 vandnot()

```
static INLINE CONST vect_t vandnot (
    const vect_t a,
    const vect_t b ) [inline], [static], [inherited]
```

12.299.3 Field Documentation

12.299.3.1 vect_size

```
const constexpr size_t vect_size = 8 [static], [constexpr]
```

12.299.3.2 alignment


```
const constexpr size_t alignment = 64 [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [simd512_int64.inl](#)

12.300 Simd512i_base Struct Reference

Inheritance diagram for Simd512i_base:



Public Types

- using `vect_t` = `__m512i`

Static Public Member Functions

- static `INLINE CONST vect_t zero` ()
- static `INLINE CONST vect_t vor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vxor` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vand` (const `vect_t` a, const `vect_t` b)
- static `INLINE CONST vect_t vandnot` (const `vect_t` a, const `vect_t` b)

12.300.1 Member Typedef Documentation

12.300.1.1 vect_t

using `vect_t` = `__m512i`

12.300.2 Member Function Documentation

12.300.2.1 zero()

```
static INLINE CONST vect_t zero ( ) [inline], [static]
```

12.300.2.2 vor()

```
static INLINE CONST vect_t vor (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.300.2.3 vxor()

```
static INLINE CONST vect_t vxor (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.300.2.4 vand()

```
static INLINE CONST vect_t vand (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

12.300.2.5 vandnot()

```
static INLINE CONST vect_t vandnot (
    const vect_t a,
    const vect_t b ) [inline], [static]
```

The documentation for this struct was generated from the following file:

- `simd512.inl`

12.301 SimdChooser< T, bool, bool > Struct Template Reference

```
#include <fflas_simd.h>
```

The documentation for this struct was generated from the following file:

- [fflas_simd.h](#)

12.302 SimdChooser< T, false, b > Struct Template Reference

```
#include <fflas_simd.h>
```

Public Types

- using [value](#) = [NoSimd](#)< T >

12.302.1 Member Typedef Documentation

12.302.1.1 value

```
template<class T , bool b>
```

```
using value = NoSimd<T>
```

The documentation for this struct was generated from the following file:

- [fflas_simd.h](#)

12.303 SimdChooser< T, true, false > Struct Template Reference

```
#include <fflas_simd.h>
```

Public Types

- using [value](#) = [NoSimd](#)< T >

12.303.1 Member Typedef Documentation

12.303.1.1 value

```
template<class T >
```

```
using value = NoSimd<T>
```

The documentation for this struct was generated from the following file:

- [fflas_simd.h](#)

12.304 SimdChooser< T, true, true > Struct Template Reference

```
#include <fflas_simd.h>
```

Public Types

- using [value](#) = [NoSimd](#)< T >

12.304.1 Member Typedef Documentation

12.304.1.1 value

```
template<class T >
```

```
using value = NoSimd<T>
```

The documentation for this struct was generated from the following file:

- [fflas_simd.h](#)

12.305 `simdToType< T >` Struct Template Reference

The documentation for this struct was generated from the following file:

- [fflas_simd.h](#)

12.306 Single Struct Reference

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.307 `Sparse< Field, SparseMatrix_t, IdxT, PtrT >` Struct Template Reference


The documentation for this struct was generated from the following file:

- [fflas_sparse.h](#)

12.308 `Sparse< _Field, SparseMatrix_t::COO >` Struct Template Reference

```
#include <coo.h>
```

Inheritance diagram for `Sparse< _Field, SparseMatrix_t::COO >`:



Public Types

- using `Field` = `_Field`

Data Fields

- `index_t` * `col` = `nullptr`
- `index_t` * `row` = `nullptr`
- `_Field::Element_ptr` `dat`
- bool `delayed` = `false`
- `uint64_t` `kmax` = 0
- `index_t` `m` = 0
- `index_t` `n` = 0
- `uint64_t` `nnz` = 0
- `uint64_t` `nElements` = 0
- `uint64_t` `maxrow` = 0

12.308.1 Member Typedef Documentation

12.308.1.1 `Field`

```
template<class _Field >
using Field = _Field
```

12.308.2 Field Documentation

12.308.2.1 col

```
template<class _Field >
index_t* col = nullptr
```

12.308.2.2 row

```
template<class _Field >
index_t* row = nullptr
```

12.308.2.3 dat

```
template<class _Field >
_Field::Element_ptr dat
```

12.308.2.4 delayed

```
template<class _Field >
bool delayed = false
```

12.308.2.5 kmax

```
template<class _Field >
uint64_t kmax = 0
```

12.308.2.6 m

```
template<class _Field >
index_t m = 0
```

12.308.2.7 n

```
template<class _Field >
index_t n = 0
```

12.308.2.8 nnz

```
template<class _Field >
uint64_t nnz = 0
```

12.308.2.9 nElements

```
template<class _Field >
uint64_t nElements = 0
```

12.308.2.10 maxrow

```
template<class _Field >
uint64_t maxrow = 0
```


The documentation for this struct was generated from the following file:

- [coo.h](#)

12.309 Sparse< _Field, SparseMatrix_t::COO_ZO > Struct Template Reference

```
#include <coo.h>
```

Inheritance diagram for Sparse< _Field, SparseMatrix_t::COO_ZO >:



Public Types

- using `Field` = `_Field`

Data Fields

- `_Field::Element` `cst` = 1
- `index_t` * `col` = `nullptr`
- `index_t` * `row` = `nullptr`
- `_Field::Element_ptr` `dat`
- `bool` `delayed` = `false`
- `uint64_t` `kmax` = 0
- `index_t` `m` = 0
- `index_t` `n` = 0
- `uint64_t` `nnz` = 0
- `uint64_t` `nElements` = 0
- `uint64_t` `maxrow` = 0

12.309.1 Member Typedef Documentation

12.309.1.1 Field

```
template<class _Field >
using Field = _Field
```

12.309.2 Field Documentation

12.309.2.1 cst

```
template<class _Field >
_Field::Element cst = 1
```

12.309.2.2 col

```
template<class _Field >
index_t* col = nullptr [inherited]
```

12.309.2.3 row

```
template<class _Field >
index_t* row = nullptr [inherited]
```

12.309.2.4 dat

```
template<class _Field >
_Field::Element_ptr dat [inherited]
```

12.309.2.5 delayed

```
template<class _Field >
bool delayed = false [inherited]
```

12.309.2.6 kmax

```
template<class _Field >
uint64_t kmax = 0 [inherited]
```

12.309.2.7 m

```
template<class _Field >
index_t m = 0 [inherited]
```

12.309.2.8 n

```
template<class _Field >
index_t n = 0 [inherited]
```

12.309.2.9 nnz

```
template<class _Field >
uint64_t nnz = 0 [inherited]
```

12.309.2.10 nElements

```
template<class _Field >
uint64_t nElements = 0 [inherited]
```

12.309.2.11 maxrow

```
template<class _Field >
uint64_t maxrow = 0 [inherited]
```


The documentation for this struct was generated from the following file:

- [coo.h](#)

12.310 Sparse< _Field, SparseMatrix_t::CSR > Struct Template Reference

```
#include <csr.h>
```

Inheritance diagram for Sparse< _Field, SparseMatrix_t::CSR >:

**Public Types**

- using [Field](#) = _Field

Data Fields

- bool [delayed](#) = false
- uint64_t [kmax](#) = 0
- [index_t](#) [m](#) = 0
- [index_t](#) [n](#) = 0
- uint64_t [nnz](#) = 0
- uint64_t [nElements](#) = 0
- uint64_t [maxrow](#) = 0

- `index_t * col = nullptr`
- `index_t * st = nullptr`
- `index_t * stend = nullptr`
- `_Field::Element_ptr dat`

12.310.1 Member Typedef Documentation

12.310.1.1 Field

```
template<class _Field >
using Field = _Field
```

12.310.2 Field Documentation

12.310.2.1 delayed

```
template<class _Field >
bool delayed = false
```

12.310.2.2 kmax

```
template<class _Field >
uint64_t kmax = 0
```

12.310.2.3 m

```
template<class _Field >
index_t m = 0
```

12.310.2.4 n

```
template<class _Field >
index_t n = 0
```

12.310.2.5 nnz

```
template<class _Field >
uint64_t nnz = 0
```

12.310.2.6 nElements

```
template<class _Field >
uint64_t nElements = 0
```

12.310.2.7 maxrow

```
template<class _Field >
uint64_t maxrow = 0
```

12.310.2.8 col

```
template<class _Field >
index_t* col = nullptr
```

12.310.2.9 st

```
template<class _Field >
index_t* st = nullptr
```


12.310.2.10 stend

```
template<class _Field >
index_t* stend = nullptr
```

12.310.2.11 dat

```
template<class _Field >
_Field::Element_ptr dat
```

The documentation for this struct was generated from the following file:

- [csr.h](#)

12.311 Sparse< _Field, SparseMatrix_t::CSR_HYB > Struct Template Reference

```
#include <csr_hyb.h>
```

Public Types

- using [Field](#) = _Field

Data Fields

- bool [delayed](#) = false
- [index_t](#) * [col](#) = nullptr
- [index_t](#) * [st](#) = nullptr
- _Field::Element_ptr [dat](#)
- uint64_t [kmax](#) = 0
- [index_t](#) [m](#) = 0
- [index_t](#) [n](#) = 0
- uint64_t [nnz](#) = 0
- uint64_t [nElements](#) = 0
- uint64_t [maxrow](#) = 0
- uint64_t [nOnes](#) = 0
- uint64_t [nMOnes](#) = 0
- uint64_t [nOthers](#) = 0

12.311.1 Member Typedef Documentation**12.311.1.1 Field**

```
template<class _Field >
using Field = _Field
```

12.311.2 Field Documentation**12.311.2.1 delayed**

```
template<class _Field >
bool delayed = false
```

12.311.2.2 col

```
template<class _Field >
index_t* col = nullptr
```

12.311.2.3 st

```
template<class _Field >
index_t* st = nullptr
```

12.311.2.4 dat

```
template<class _Field >
_Field::Element_ptr dat
```

12.311.2.5 kmax

```
template<class _Field >
uint64_t kmax = 0
```

12.311.2.6 m

```
template<class _Field >
index_t m = 0
```

12.311.2.7 n

```
template<class _Field >
index_t n = 0
```

12.311.2.8 nnz

```
template<class _Field >
uint64_t nnz = 0
```

12.311.2.9 nElements

```
template<class _Field >
uint64_t nElements = 0
```

12.311.2.10 maxrow

```
template<class _Field >
uint64_t maxrow = 0
```

12.311.2.11 nOnes

```
template<class _Field >
uint64_t nOnes = 0
```

12.311.2.12 nMOnes

```
template<class _Field >
uint64_t nMOnes = 0
```

12.311.2.13 nOthers

```
template<class _Field >
uint64_t nOthers = 0
```


The documentation for this struct was generated from the following file:

- [csr_hyb.h](#)

12.312 Sparse< _Field, SparseMatrix_t::CSR_ZO > Struct Template Reference

```
#include <csr.h>
```

Inheritance diagram for Sparse< _Field, SparseMatrix_t::CSR_ZO >:



Public Types

- using [Field](#) = _Field

Data Fields

- int64_t [cst](#) = 1
- bool [delayed](#) = false
- uint64_t [kmax](#) = 0
- [index_t](#) [m](#) = 0
- [index_t](#) [n](#) = 0
- uint64_t [nnz](#) = 0
- uint64_t [nElements](#) = 0
- uint64_t [maxrow](#) = 0
- [index_t](#) * [col](#) = nullptr
- [index_t](#) * [st](#) = nullptr
- [index_t](#) * [stend](#) = nullptr
- _Field::Element_ptr [dat](#)

12.312.1 Member Typedef Documentation

12.312.1.1 Field

```
template<class _Field >
using Field = _Field
```

12.312.2 Field Documentation

12.312.2.1 cst

```
template<class _Field >
int64_t cst = 1
```

12.312.2.2 delayed

```
template<class _Field >
bool delayed = false
```

12.312.2.3 kmax

```
template<class _Field >
uint64_t kmax = 0 [inherited]
```

12.312.2.4 m

```
template<class _Field >
index\_t m = 0 [inherited]
```

12.312.2.5 n

```
template<class _Field >
index_t n = 0 [inherited]
```

12.312.2.6 nnz

```
template<class _Field >
uint64_t nnz = 0 [inherited]
```

12.312.2.7 nElements

```
template<class _Field >
uint64_t nElements = 0 [inherited]
```

12.312.2.8 maxrow

```
template<class _Field >
uint64_t maxrow = 0 [inherited]
```

12.312.2.9 col

```
template<class _Field >
index_t* col = nullptr [inherited]
```

12.312.2.10 st

```
template<class _Field >
index_t* st = nullptr [inherited]
```

12.312.2.11 stend

```
template<class _Field >
index_t* stend = nullptr [inherited]
```

12.312.2.12 dat

```
template<class _Field >
_Field::Element_ptr dat [inherited]
```


The documentation for this struct was generated from the following file:

- [csr.h](#)

12.313 Sparse< _Field, SparseMatrix_t::ELL > Struct Template Reference

```
#include <ell.h>
```

Inheritance diagram for Sparse< _Field, SparseMatrix_t::ELL >:

**Public Types**

- using [Field](#) = _Field

Data Fields

- bool `delayed` = false
- uint64_t `kmax` = 0
- index_t `m` = 0
- index_t `n` = 0
- index_t `ld` = 0
- uint64_t `nnz` = 0
- uint64_t `nElements` = 0
- uint64_t `maxrow` = 0
- index_t * `col` = nullptr
- _Field::Element_ptr `dat`

12.313.1 Member Typedef Documentation**12.313.1.1 Field**

```
template<class _Field >
using Field = _Field
```

12.313.2 Field Documentation**12.313.2.1 delayed**

```
template<class _Field >
bool delayed = false
```

12.313.2.2 kmax

```
template<class _Field >
uint64_t kmax = 0
```

12.313.2.3 m

```
template<class _Field >
index_t m = 0
```

12.313.2.4 n

```
template<class _Field >
index_t n = 0
```

12.313.2.5 ld

```
template<class _Field >
index_t ld = 0
```

12.313.2.6 nnz

```
template<class _Field >
uint64_t nnz = 0
```

12.313.2.7 nElements

```
template<class _Field >
uint64_t nElements = 0
```

12.313.2.8 maxrow

```
template<class _Field >
uint64_t maxrow = 0
```

12.313.2.9 col

```
template<class _Field >
index_t* col = nullptr
```

12.313.2.10 dat

```
template<class _Field >
_Field::Element_ptr dat
```


The documentation for this struct was generated from the following file:

- [ell.h](#)

12.314 Sparse< _Field, SparseMatrix_t::ELL_simd > Struct Template Reference

```
#include <ell_simd.h>
```

Inheritance diagram for Sparse< _Field, SparseMatrix_t::ELL_simd >:

**Data Fields**

- bool [delayed](#) = false
- int [chunk](#) = 0
- [index_t](#) [m](#) = 0
- [index_t](#) [n](#) = 0
- [index_t](#) [ld](#) = 0
- [uint64_t](#) [kmax](#) = 0
- [uint64_t](#) [nnz](#) = 0
- [uint64_t](#) [nElements](#) = 0
- [uint64_t](#) [maxrow](#) = 0
- [uint64_t](#) [nChunks](#) = 0
- [index_t](#)* [col](#) = nullptr
- [_Field::Element_ptr](#) [dat](#)

12.314.1 Field Documentation**12.314.1.1 delayed**

```
template<class _Field >
bool delayed = false
```

12.314.1.2 chunk

```
template<class _Field >
int chunk = 0
```

12.314.1.3 m

```
template<class _Field >
index_t m = 0
```

12.314.1.4 n

```
template<class _Field >
index_t n = 0
```

12.314.1.5 ld

```
template<class _Field >
index_t ld = 0
```

12.314.1.6 kmax

```
template<class _Field >
uint64_t kmax = 0
```

12.314.1.7 nnz

```
template<class _Field >
uint64_t nnz = 0
```

12.314.1.8 nElements

```
template<class _Field >
uint64_t nElements = 0
```

12.314.1.9 maxrow

```
template<class _Field >
uint64_t maxrow = 0
```

12.314.1.10 nChunks

```
template<class _Field >
uint64_t nChunks = 0
```

12.314.1.11 col

```
template<class _Field >
index_t* col = nullptr
```

12.314.1.12 dat

```
template<class _Field >
_Field::Element_ptr dat
```


The documentation for this struct was generated from the following file:

- [ell_simd.h](#)

12.315 Sparse< _Field, SparseMatrix_t::ELL_simd_ZO > Struct Template Reference

```
#include <ell_simd.h>
```

Inheritance diagram for Sparse< _Field, SparseMatrix_t::ELL_simd_ZO >:



Data Fields

- `_Field::Element` `cst` = 1
- `bool` `delayed` = false
- `int` `chunk` = 0
- `index_t` `m` = 0
- `index_t` `n` = 0
- `index_t` `ld` = 0
- `uint64_t` `kmax` = 0
- `uint64_t` `nnz` = 0
- `uint64_t` `nElements` = 0
- `uint64_t` `maxrow` = 0
- `uint64_t` `nChunks` = 0
- `index_t` * `col` = nullptr
- `_Field::Element_ptr` `dat`

12.315.1 Field Documentation

12.315.1.1 `cst`

```
template<class _Field >
_Field::Element cst = 1
```

12.315.1.2 `delayed`

```
template<class _Field >
bool delayed = false [inherited]
```

12.315.1.3 `chunk`

```
template<class _Field >
int chunk = 0 [inherited]
```

12.315.1.4 `m`

```
template<class _Field >
index_t m = 0 [inherited]
```

12.315.1.5 `n`

```
template<class _Field >
index_t n = 0 [inherited]
```

12.315.1.6 `ld`

```
template<class _Field >
index_t ld = 0 [inherited]
```

12.315.1.7 `kmax`

```
template<class _Field >
uint64_t kmax = 0 [inherited]
```

12.315.1.8 `nnz`

```
template<class _Field >
uint64_t nnz = 0 [inherited]
```


12.315.1.9 nElements

```
template<class _Field >
uint64_t nElements = 0 [inherited]
```

12.315.1.10 maxrow

```
template<class _Field >
uint64_t maxrow = 0 [inherited]
```

12.315.1.11 nChunks

```
template<class _Field >
uint64_t nChunks = 0 [inherited]
```

12.315.1.12 col

```
template<class _Field >
index_t* col = nullptr [inherited]
```

12.315.1.13 dat

```
template<class _Field >
_Field::Element_ptr dat [inherited]
```


The documentation for this struct was generated from the following file:

- [ell_simd.h](#)

12.316 Sparse< _Field, SparseMatrix_t::ELL_ZO > Struct Template Reference

```
#include <ell.h>
```

Inheritance diagram for Sparse< _Field, SparseMatrix_t::ELL_ZO >:

**Public Types**

- using [Field](#) = _Field

Data Fields

- _Field::Element [cst](#) = 1
- bool [delayed](#) = false
- uint64_t [kmax](#) = 0
- [index_t](#) [m](#) = 0
- [index_t](#) [n](#) = 0
- [index_t](#) [ld](#) = 0
- uint64_t [nnz](#) = 0
- uint64_t [nElements](#) = 0
- uint64_t [maxrow](#) = 0
- [index_t](#) * [col](#) = nullptr
- _Field::Element_ptr [dat](#)

12.316.1 Member Typedef Documentation

12.316.1.1 Field

```
template<class _Field >  
using Field = _Field
```

12.316.2 Field Documentation

12.316.2.1 cst

```
template<class _Field >  
_Field::Element cst = 1
```

12.316.2.2 delayed

```
template<class _Field >  
bool delayed = false [inherited]
```

12.316.2.3 kmax

```
template<class _Field >  
uint64_t kmax = 0 [inherited]
```

12.316.2.4 m

```
template<class _Field >  
index_t m = 0 [inherited]
```

12.316.2.5 n

```
template<class _Field >  
index_t n = 0 [inherited]
```

12.316.2.6 ld

```
template<class _Field >  
index_t ld = 0 [inherited]
```

12.316.2.7 nnz

```
template<class _Field >  
uint64_t nnz = 0 [inherited]
```

12.316.2.8 nElements

```
template<class _Field >  
uint64_t nElements = 0 [inherited]
```

12.316.2.9 maxrow

```
template<class _Field >  
uint64_t maxrow = 0 [inherited]
```

12.316.2.10 col

```
template<class _Field >  
index_t* col = nullptr [inherited]
```

12.316.2.11 dat

```
template<class _Field >
_Field::Element_ptr dat [inherited]
```

The documentation for this struct was generated from the following file:

- [ell.h](#)

12.317 Sparse< _Field, SparseMatrix_t::HYB_ZO > Struct Template Reference

```
#include <hyb_zo.h>
```

Public Types

- using [Field](#) = [_Field](#)
- typedef [Sparse< _Field, SparseMatrix_t::HYB_ZO > Self_t](#)

Data Fields

- bool [delayed](#) = false
- uint64_t [kmax](#) = 0
- [index_t](#) [m](#) = 0
- [index_t](#) [n](#) = 0
- uint64_t [nnz](#) = 0
- uint64_t [maxrow](#) = 0
- uint64_t [nElements](#) = 0
- [Sparse< _Field, SparseMatrix_t::CSR > * dat](#) = nullptr
- [Sparse< _Field, SparseMatrix_t::CSR_ZO > * one](#) = nullptr
- [Sparse< _Field, SparseMatrix_t::CSR_ZO > * mone](#) = nullptr

12.317.1 Member Typedef Documentation**12.317.1.1 Field**

```
template<class _Field >
using Field = \_Field
```

12.317.1.2 Self_t

```
template<class _Field >
typedef Sparse<\_Field, SparseMatrix\_t::HYB\_ZO> Self\_t
```

12.317.2 Field Documentation**12.317.2.1 delayed**

```
template<class _Field >
bool delayed = false
```

12.317.2.2 kmax

```
template<class _Field >
uint64_t kmax = 0
```

12.317.2.3 m

```
template<class _Field >
index\_t m = 0
```

12.317.2.4 n

```
template<class _Field >
index_t n = 0
```

12.317.2.5 nnz

```
template<class _Field >
uint64_t nnz = 0
```

12.317.2.6 maxrow

```
template<class _Field >
uint64_t maxrow = 0
```

12.317.2.7 nElements

```
template<class _Field >
uint64_t nElements = 0
```

12.317.2.8 dat

```
template<class _Field >
Sparse<_Field, SparseMatrix_t::CSR>* dat = nullptr
```

12.317.2.9 one

```
template<class _Field >
Sparse<_Field, SparseMatrix_t::CSR_ZO>* one = nullptr
```

12.317.2.10 mone

```
template<class _Field >
Sparse<_Field, SparseMatrix_t::CSR_ZO>* mone = nullptr
```


The documentation for this struct was generated from the following file:

- [hyb_zo.h](#)

12.318 Sparse< _Field, SparseMatrix_t::SELL > Struct Template Reference

```
#include <sell.h>
```

Inheritance diagram for Sparse< _Field, SparseMatrix_t::SELL >:

**Public Types**

- using [Field](#) = _Field

Data Fields

- bool `delayed` = false
- int `chunk` = 0
- `index_t` `kmax` = 0
- `index_t` `m` = 0
- `index_t` `n` = 0
- `index_t` `maxrow` = 0
- `index_t` `sigma` = 0
- `index_t` `nChunks` = 0
- `uint64_t` `nnz` = 0
- `uint64_t` `nElements` = 0
- `index_t` * `perm` = nullptr
- `uint64_t` * `st` = nullptr
- `index_t` * `chunkSize` = nullptr
- `index_t` * `col` = nullptr
- `_Field::Element_ptr` `dat`

12.318.1 Member Typedef Documentation**12.318.1.1 Field**

```
template<class _Field >
using Field = _Field
```

12.318.2 Field Documentation**12.318.2.1 delayed**

```
template<class _Field >
bool delayed = false
```

12.318.2.2 chunk

```
template<class _Field >
int chunk = 0
```

12.318.2.3 kmax

```
template<class _Field >
index_t kmax = 0
```

12.318.2.4 m

```
template<class _Field >
index_t m = 0
```

12.318.2.5 n

```
template<class _Field >
index_t n = 0
```

12.318.2.6 maxrow

```
template<class _Field >
index_t maxrow = 0
```

12.318.2.7 sigma

```
template<class _Field >
index_t sigma = 0
```

12.318.2.8 nChunks

```
template<class _Field >
index_t nChunks = 0
```

12.318.2.9 nnz

```
template<class _Field >
uint64_t nnz = 0
```

12.318.2.10 nElements

```
template<class _Field >
uint64_t nElements = 0
```

12.318.2.11 perm

```
template<class _Field >
index_t* perm = nullptr
```

12.318.2.12 st

```
template<class _Field >
uint64_t* st = nullptr
```

12.318.2.13 chunkSize

```
template<class _Field >
index_t* chunkSize = nullptr
```

12.318.2.14 col

```
template<class _Field >
index_t* col = nullptr
```

12.318.2.15 dat

```
template<class _Field >
_Field::Element_ptr dat
```


The documentation for this struct was generated from the following file:

- [sell.h](#)

12.319 Sparse<_Field, SparseMatrix_t::SELL_ZO > Struct Template Reference

```
#include <sell.h>
```

Inheritance diagram for Sparse<_Field, SparseMatrix_t::SELL_ZO >:



Public Types

- using [Field](#) = `_Field`

Data Fields

- `_Field::Element` [cst](#) = 1
- bool [delayed](#) = false
- int [chunk](#) = 0
- [index_t](#) [kmax](#) = 0
- [index_t](#) [m](#) = 0
- [index_t](#) [n](#) = 0
- [index_t](#) [maxrow](#) = 0
- [index_t](#) [sigma](#) = 0
- [index_t](#) [nChunks](#) = 0
- [uint64_t](#) [nnz](#) = 0
- [uint64_t](#) [nElements](#) = 0
- [index_t](#) * [perm](#) = nullptr
- [uint64_t](#) * [st](#) = nullptr
- [index_t](#) * [chunkSize](#) = nullptr
- [index_t](#) * [col](#) = nullptr
- `_Field::Element_ptr` [dat](#)

12.319.1 Member Typedef Documentation

12.319.1.1 Field

```
template<class _Field >
using Field = _Field
```

12.319.2 Field Documentation

12.319.2.1 cst

```
template<class _Field >
_Field::Element cst = 1
```

12.319.2.2 delayed

```
template<class _Field >
bool delayed = false [inherited]
```

12.319.2.3 chunk

```
template<class _Field >
int chunk = 0 [inherited]
```

12.319.2.4 kmax

```
template<class _Field >
index\_t kmax = 0 [inherited]
```

12.319.2.5 m

```
template<class _Field >
index\_t m = 0 [inherited]
```

12.319.2.6 n

```
template<class _Field >
index_t n = 0 [inherited]
```

12.319.2.7 maxrow

```
template<class _Field >
index_t maxrow = 0 [inherited]
```

12.319.2.8 sigma

```
template<class _Field >
index_t sigma = 0 [inherited]
```

12.319.2.9 nChunks

```
template<class _Field >
index_t nChunks = 0 [inherited]
```

12.319.2.10 nnz

```
template<class _Field >
uint64_t nnz = 0 [inherited]
```

12.319.2.11 nElements

```
template<class _Field >
uint64_t nElements = 0 [inherited]
```

12.319.2.12 perm

```
template<class _Field >
index_t* perm = nullptr [inherited]
```

12.319.2.13 st

```
template<class _Field >
uint64_t* st = nullptr [inherited]
```

12.319.2.14 chunkSize

```
template<class _Field >
index_t* chunkSize = nullptr [inherited]
```

12.319.2.15 col

```
template<class _Field >
index_t* col = nullptr [inherited]
```

12.319.2.16 dat

```
template<class _Field >
_Field::Element_ptr dat [inherited]
```

The documentation for this struct was generated from the following file:

- [sell.h](#)

12.320 SpMat< Field, flag > Struct Template Reference

```
#include <fflas_sparse.h>
```


Data Fields

- `FFLAS::CooMat<Field> * _coo = nullptr`
- `FFLAS::CsrMat<Field> * _csr = nullptr`
- `FFLAS::EllMat<Field> * _ell = nullptr`

12.320.1 Field Documentation**12.320.1.1 _coo**

```
template<class Field , int flag = HelperFlag::none>
FFLAS::CooMat<Field>* _coo = nullptr
```

12.320.1.2 _csr

```
template<class Field , int flag = HelperFlag::none>
FFLAS::CsrMat<Field>* _csr = nullptr
```

12.320.1.3 _ell

```
template<class Field , int flag = HelperFlag::none>
FFLAS::EllMat<Field>* _ell = nullptr
```

The documentation for this struct was generated from the following file:

- `fflas_sparse.h`

12.321 StatsMatrix Struct Reference

```
#include <utils.h>
```

Data Fields

- `uint64_t rowdim = 0`
- `uint64_t coldim = 0`
- `uint64_t nOnes = 0`
- `uint64_t nMOnes = 0`
- `uint64_t nOthers = 0`
- `uint64_t nnz = 0`
- `uint64_t maxRow = 0`
- `uint64_t minRow = 0`
- `uint64_t averageRow = 0`
- `uint64_t deviationRow = 0`
- `uint64_t maxCol = 0`
- `uint64_t minCol = 0`
- `uint64_t averageCol = 0`
- `uint64_t deviationCol = 0`
- `uint64_t minColDifference = 0`
- `uint64_t maxColDifference = 0`
- `uint64_t averageColDifference = 0`
- `uint64_t deviationColDifference = 0`
- `uint64_t minRowDifference = 0`
- `uint64_t maxRowDifference = 0`
- `uint64_t averageRowDifference = 0`
- `uint64_t deviationRowDifference = 0`
- `uint64_t nDenseRows = 0`
- `uint64_t nDenseCols = 0`
- `uint64_t nEmptyRows = 0`

- `uint64_t nEmptyCols = 0`
- `uint64_t nEmptyColsEnd = 0`
- `std::vector< uint64_t > denseRows`
- `std::vector< uint64_t > denseCols`

12.321.1 Field Documentation

12.321.1.1 rowdim

`uint64_t rowdim = 0`

12.321.1.2 coldim

`uint64_t coldim = 0`

12.321.1.3 nOnes

`uint64_t nOnes = 0`

12.321.1.4 nMOnes

`uint64_t nMOnes = 0`

12.321.1.5 nOthers

`uint64_t nOthers = 0`

12.321.1.6 nnz

`uint64_t nnz = 0`

12.321.1.7 maxRow

`uint64_t maxRow = 0`

12.321.1.8 minRow

`uint64_t minRow = 0`

12.321.1.9 averageRow

`uint64_t averageRow = 0`

12.321.1.10 deviationRow

`uint64_t deviationRow = 0`

12.321.1.11 maxCol

`uint64_t maxCol = 0`

12.321.1.12 minCol

`uint64_t minCol = 0`

12.321.1.13 averageCol

`uint64_t averageCol = 0`

12.321.1.14 deviationCol

```
uint64_t deviationCol = 0
```

12.321.1.15 minColDifference

```
uint64_t minColDifference = 0
```

12.321.1.16 maxColDifference

```
uint64_t maxColDifference = 0
```

12.321.1.17 averageColDifference

```
uint64_t averageColDifference = 0
```

12.321.1.18 deviationColDifference

```
uint64_t deviationColDifference = 0
```

12.321.1.19 minRowDifference

```
uint64_t minRowDifference = 0
```

12.321.1.20 maxRowDifference

```
uint64_t maxRowDifference = 0
```

12.321.1.21 averageRowDifference

```
uint64_t averageRowDifference = 0
```

12.321.1.22 deviationRowDifference

```
uint64_t deviationRowDifference = 0
```

12.321.1.23 nDenseRows

```
uint64_t nDenseRows = 0
```

12.321.1.24 nDenseCols

```
uint64_t nDenseCols = 0
```

12.321.1.25 nEmptyRows

```
uint64_t nEmptyRows = 0
```

12.321.1.26 nEmptyCols

```
uint64_t nEmptyCols = 0
```

12.321.1.27 nEmptyColsEnd

```
uint64_t nEmptyColsEnd = 0
```

12.321.1.28 denseRows

```
std::vector<uint64_t> denseRows
```

12.321.1.29 denseCols

```
std::vector<uint64_t> denseCols
```


The documentation for this struct was generated from the following file:

- [utils.h](#)

12.322 support_fast_mod< T > Struct Template Reference

```
#include <fflas_freduce.h>
```

Inheritance diagram for support_fast_mod< T >:




The documentation for this struct was generated from the following file:

- [fflas_freduce.h](#)

12.323 support_fast_mod< double > Struct Reference

```
#include <fflas_freduce.h>
```

Inheritance diagram for support_fast_mod< double >:




The documentation for this struct was generated from the following file:

- [fflas_freduce.h](#)

12.324 support_fast_mod< float > Struct Reference

```
#include <fflas_freduce.h>
```

Inheritance diagram for support_fast_mod< float >:




The documentation for this struct was generated from the following file:

- [fflas_freduce.h](#)

12.325 support_fast_mod< int64_t > Struct Reference

```
#include <fflas_freduce.h>
```

Inheritance diagram for support_fast_mod< int64_t >:




The documentation for this struct was generated from the following file:

- [fflas_freduce.h](#)

12.326 support_simd< T > Struct Template Reference

```
#include <fflas_simd.h>
```

Inheritance diagram for support_simd< T >:




The documentation for this struct was generated from the following file:

- [fflas_simd.h](#)

12.327 support_simd_add< T > Struct Template Reference

```
#include <fflas_fadd.h>
```

Inheritance diagram for support_simd_add< T >:




The documentation for this struct was generated from the following file:

- [fflas_fadd.h](#)

12.328 support_simd_mod< T > Struct Template Reference

```
#include <fflas_freduce.h>
```

Inheritance diagram for support_simd_mod< T >:



The documentation for this struct was generated from the following file:

- [fflas_freduce.h](#)

12.329 Test< Elt > Class Template Reference

Public Types

- using [Field](#) = Modular< Elt >
- using [Elt_ptr](#) = typename [Field::Element_ptr](#)
- using [Residu](#) = typename [Field::Residu_t](#)
- template<bool B, class T = void>
using [enable_if_t](#) = typename std::enable_if< B, T >::type
- template<typename [Simd](#) >
using [is_same_element](#) = typename [Simd::template is_same_element](#)< [Field](#) >
- template<typename E >
using [enable_if_no_simd_t](#) = [enable_if_t](#)< [Simd](#)< E >::vect_size==1 >
- template<typename E >
using [enable_if_simd128_t](#) = [enable_if_t](#)< sizeof(E) *[Simd](#)< E >::vect_size==16 >
- template<typename E >
using [enable_if_simd256_t](#) = [enable_if_t](#)< sizeof(E) *[Simd](#)< E >::vect_size==32 >
- template<typename E >
using [enable_if_simd512_t](#) = [enable_if_t](#)< sizeof(E) *[Simd](#)< E >::vect_size==64 >

Public Member Functions

- [Test](#) (size_t mm, size_t nn)
- template<typename [Simd](#) = NoSimd<Elt>, [enable_if_t](#)< [is_same_element](#)< [Simd](#) >::value > * = nullptr>
bool [test_ftranspose](#) (size_t m, size_t n, [Elt_ptr](#) A, size_t lda, [Elt_ptr](#) B, size_t ldb)
- template<typename [Simd](#) = NoSimd<Elt>, [enable_if_t](#)< [is_same_element](#)< [Simd](#) >::value > * = nullptr>
bool [doTests](#) ()
- template<typename _E = Elt, [enable_if_t](#)< [is_same](#)< _E, Elt >::value > * = nullptr, [enable_if_no_simd_t](#)< _E > * = nullptr>
bool [run](#) ()

Static Public Member Functions

- template<typename _E = Elt, [enable_if_t](#)< [is_same](#)< _E, Givaro::Integer >::value > * = nullptr>
static [Residu cardinality](#) ()
- template<typename _E = Elt, [enable_if_t](#)< [is_same](#)< _E, Givaro::Integer >::value > * = nullptr>
static [Residu cardinality](#) ()

Protected Attributes

- [Field F](#)
- size_t [_mm](#)
- size_t [_nn](#)

12.329.1 Member Typedef Documentation

12.329.1.1 Field

```
template<typename Elt >
using Field = Modular<Elt>
```

12.329.1.2 Elt_ptr

```
template<typename Elt >
using Elt\_ptr = typename Field::Element\_ptr
```

12.329.1.3 Residu

```
template<typename Elt >
using Residu = typename Field::Residu\_t
```

12.329.1.4 enable_if_t

```
template<typename Elt >
template<bool B, class T = void>
using enable_if_t = typename std::enable_if<B, T>::type
```

12.329.1.5 is_same_element

```
template<typename Elt >
template<typename Simd >
using is_same_element = typename Simd::template is_same_element<Field>
```

12.329.1.6 enable_if_no_simd_t

```
template<typename Elt >
template<typename E >
using enable_if_no_simd_t = enable_if_t<Simd<E>::vect_size == 1>
```

12.329.1.7 enable_if_simd128_t

```
template<typename Elt >
template<typename E >
using enable_if_simd128_t = enable_if_t<sizeof(E)*Simd<E>::vect_size == 16>
```

12.329.1.8 enable_if_simd256_t

```
template<typename Elt >
template<typename E >
using enable_if_simd256_t = enable_if_t<sizeof(E)*Simd<E>::vect_size == 32>
```

12.329.1.9 enable_if_simd512_t

```
template<typename Elt >
template<typename E >
using enable_if_simd512_t = enable_if_t<sizeof(E)*Simd<E>::vect_size == 64>
```

12.329.2 Constructor & Destructor Documentation**12.329.2.1 Test()**

```
template<typename Elt >
Test (
    size_t mm,
    size_t nn ) [inline]
```

12.329.3 Member Function Documentation**12.329.3.1 cardinality() [1/2]**

```
template<typename Elt >
template<typename _E = Elt, enable_if_t<!is_same< _E, Givaro::Integer >::value > * = nullptr>
static Residu cardinality ( ) [inline], [static]
```

12.329.3.2 cardinality() [2/2]

```
template<typename Elt >
template<typename _E = Elt, enable_if_t< is_same< _E, Givaro::Integer >::value > * = nullptr>
static Residu cardinality ( ) [inline], [static]
```

12.329.3.3 test_ftranspose()

```
template<typename Elt >
template<typename Simd = NoSimd<Elt>, enable_if_t< is_same_element< Simd >::value > * =
nullptr>
bool test_ftranspose (
    size_t m,
    size_t n,
    Elt_ptr A,
    size_t lda,
    Elt_ptr B,
    size_t ldb ) [inline]
```

12.329.3.4 doTests()

```
template<typename Elt >
template<typename Simd = NoSimd<Elt>, enable_if_t< is_same_element< Simd >::value > * =
nullptr>
bool doTests ( ) [inline]
```

12.329.3.5 run()

```
template<typename Elt >
template<typename _E = Elt, enable_if_t< is_same< _E, Elt >::value > * = nullptr, enable_if_no_simd_t<
_E > * = nullptr>
bool run ( ) [inline]
```

12.329.4 Field Documentation

12.329.4.1 F

```
template<typename Elt >
Field F [protected]
```

12.329.4.2 _mm

```
template<typename Elt >
size_t _mm [protected]
```

12.329.4.3 _nn

```
template<typename Elt >
size_t _nn [protected]
```

The documentation for this class was generated from the following file:

- [test-storage-transpose.C](#)

12.330 TestOneMethod< Simd > Class Template Reference

Public Types

- using [Element](#) = typename Simd::scalar_t
- using [vect_t](#) = typename Simd::vect_t
- using [vectElt](#) = vector< [Element](#) >
- template<bool B, typename T = void>
 using [enable_if_t](#) = typename enable_if< B, T >::type

Public Member Functions

- `template<typename... AScal, typename RScal, typename... ASimd, typename RSimd, enable_if_t< sizeof...(AScal)==sizeof...(ASimd)> * = nullptr, enable_if_t< count_nonconst_lvalue_reference< AScal... >::n==count_nonconst_lvalue_reference< ASimd... >::n > * = nullptr, enable_if_t< is_all_same< AScal... >::value > * = nullptr, enable_if_t< is_all_same< vect_t, ASimd... >::value > * = nullptr>`
`TestOneMethod` (function< RSimd(ASimd...)> fsimd, function< RScal(AScal...)> fscal, function< void(vector< [vectElt](#) > &)> genInputs, string fname)
- `template<typename Ret, typename... AScal>`
`enable\_if\_t< is\_all\_same< Element, AScal... >::value &&std::is_convertible< Ret, Element >::value, void >`
`evaluate\_scalar\_method` (function< Ret(AScal...)> fscal)
- `template<typename... AScal>`
`enable\_if\_t< is\_all\_same< vectElt, AScal... >::value, void >`
`evaluate\_scalar\_method` (function< [vectElt](#)(AScal...)> fscal)
- `template<typename... AScal>`
`enable\_if\_t< is\_all\_same< vectElt, AScal... >::value, void >`
`evaluate\_scalar\_method` (function< void(AScal...)> fscal)
- `template<typename Ret, typename... ASimd>`
`enable\_if\_t< is\_all\_same< vect\_t, ASimd... >::value &&std::is_convertible< Ret, vect\_t >::value, void >`
`evaluate\_simd\_method` (function< Ret(ASimd...)> fsimd, array< [vect_t](#), sizeof...(ASimd)> &simd_in)
- `template<typename... ASimd>`
`enable\_if\_t< is\_all\_same< vect\_t, ASimd... >::value, void >`
`evaluate\_simd\_method` (function< void(ASimd...)> fsimd, array< [vect_t](#), sizeof...(ASimd)> &simd_in)
- `bool getStatus () const`
- `string getTestName () const`
- `bool writeResultLine () const`
- `void writeDebugData () const`

Static Public Attributes

- `static constexpr size_t vect\_size = Simd::vect_size`

Protected Attributes

- `size_t nb\_lref`
- `string name`
- `vector< vectElt > inputs`
- `vector< vectElt > outputs\_simd`
- `vector< vectElt > outputs\_scalar`

12.330.1 Member Typedef Documentation

12.330.1.1 Element

```
template<typename Simd >
using Element = typename Simd::scalar_t
```

12.330.1.2 vect_t

```
template<typename Simd >
using vect\_t = typename Simd::vect_t
```

12.330.1.3 vectElt

```
template<typename Simd >
using vectElt = vector<Element>
```

12.330.1.4 enable_if_t

```
template<typename Simd >
template<bool B, typename T = void>
using enable_if_t = typename enable_if<B, T>::type
```

12.330.2 Constructor & Destructor Documentation

12.330.2.1 TestOneMethod()

```
template<typename Simd >
template<typename... AScal, typename RScal, typename... ASimd, typename RSimd, enable_if_t<
sizeof...(AScal)==sizeof...(ASimd)> * = nullptr, enable_if_t< count_nonconst_lvalue_reference<
AScal... >::n==count_nonconst_lvalue_reference< ASimd... >::n > * = nullptr, enable_if_t<
is_all_same< AScal... >::value > * = nullptr, enable_if_t< is_all_same< vect_t, ASimd...
>::value > * = nullptr>
TestOneMethod (
    function< RSimd(ASimd...)> fsimd,
    function< RScal(AScal...)> fscal,
    function< void(vector< vectElt > &)> genInputs,
    string fname ) [inline]
```

12.330.3 Member Function Documentation

12.330.3.1 evaluate_scalar_method() [1/3]

```
template<typename Simd >
template<typename Ret, typename... AScal>
enable_if_t< is_all_same< Element, AScal... >::value &&std::is_convertible< Ret, Element >↔
::value, void > evaluate_scalar_method (
    function< Ret(AScal...)> fscal ) [inline]
```

12.330.3.2 evaluate_scalar_method() [2/3]

```
template<typename Simd >
template<typename... AScal>
enable_if_t< is_all_same< vectElt, AScal... >::value, void > evaluate_scalar_method (
    function< vectElt(AScal...)> fscal ) [inline]
```

12.330.3.3 evaluate_scalar_method() [3/3]

```
template<typename Simd >
template<typename... AScal>
enable_if_t< is_all_same< vectElt, AScal... >::value, void > evaluate_scalar_method (
    function< void(AScal...)> fscal ) [inline]
```

12.330.3.4 evaluate_simd_method() [1/2]

```
template<typename Simd >
template<typename Ret, typename... ASimd>
enable_if_t< is_all_same< vect_t, ASimd... >::value &&std::is_convertible< Ret, vect_t >↔
::value, void > evaluate_simd_method (
    function< Ret(ASimd...)> fsimd,
    array< vect_t, sizeof...(ASimd)> & simd_in ) [inline]
```

12.330.3.5 evaluate_simd_method() [2/2]

```
template<typename Simd >
template<typename... ASimd>
enable_if_t< is_all_same< vect_t, ASimd... >::value, void > evaluate_simd_method (
```

```
function< void(ASimd...)> fsimd,
array< vect_t, sizeof...(ASimd)> & simd_in ) [inline]
```

12.330.3.6 getStatus()

```
template<typename Simd >
bool getStatus ( ) const [inline]
```

12.330.3.7 getTestName()

```
template<typename Simd >
string getTestName ( ) const [inline]
```

12.330.3.8 writeResultLine()

```
template<typename Simd >
bool writeResultLine ( ) const [inline]
```

12.330.3.9 writeDebugData()

```
template<typename Simd >
void writeDebugData ( ) const [inline]
```

12.330.4 Field Documentation

12.330.4.1 vect_size

```
template<typename Simd >
constexpr size_t vect_size = Simd::vect_size [static], [constexpr]
```

12.330.4.2 nb_lref

```
template<typename Simd >
size_t nb_lref [protected]
```

12.330.4.3 name

```
template<typename Simd >
string name [protected]
```

12.330.4.4 inputs

```
template<typename Simd >
vector<vectElt> inputs [protected]
```

12.330.4.5 outputs_simd

```
template<typename Simd >
vector<vectElt> outputs_simd [protected]
```

12.330.4.6 outputs_scalar

```
template<typename Simd >
vector<vectElt> outputs_scalar [protected]
```

The documentation for this class was generated from the following file:

- [test-simd.C](#)

12.331 tfn_minus Struct Reference

```
#include <sparse_matrix_traits.h>
```

Public Member Functions

- `template<typename... Args>`
`auto operator() (Args &&... args) const -> decltype(operator+(std::forward< Args >(args)...))`

12.331.1 Member Function Documentation

12.331.1.1 operator>()()

```
template<typename... Args>
auto operator() (
    Args &&... args ) const -> decltype(operator+(std::forward<Args>(args)...))

[inline]
```

The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.332 tfn_minus_eq Struct Reference

```
#include <sparse_matrix_traits.h>
```

Public Member Functions

- `template<typename... Args>`
`auto operator() (Args &&... args) const -> decltype(operator+(std::forward< Args >(args)...))`

12.332.1 Member Function Documentation

12.332.1.1 operator>()()

```
template<typename... Args>
auto operator() (
    Args &&... args ) const -> decltype(operator+(std::forward<Args>(args)...))

[inline]
```

The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.333 tfn_mul Struct Reference

```
#include <sparse_matrix_traits.h>
```

Public Member Functions

- `template<typename... Args>`
`auto operator() (Args &&... args) const -> decltype(operator+(std::forward< Args >(args)...))`

12.333.1 Member Function Documentation

12.333.1.1 operator>()()

```
template<typename... Args>
auto operator() (
    Args &&... args ) const -> decltype(operator+(std::forward<Args>(args)...))

[inline]
```

The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.334 tfn_mul_eq Struct Reference

```
#include <sparse_matrix_traits.h>
```

Public Member Functions

- `template<typename... Args>`
`auto operator() (Args &&... args) const -> decltype(operator+(std::forward< Args >(args)...))`

12.334.1 Member Function Documentation

12.334.1.1 operator>()()

```
template<typename... Args>
auto operator() (
    Args &&... args ) const -> decltype(operator+(std::forward<Args>(args)...))
[inline]
```

The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.335 tfn_plus Struct Reference

```
#include <sparse_matrix_traits.h>
```

Public Member Functions

- `template<typename... Args>`
`auto operator() (Args &&... args) const -> decltype(operator+(std::forward< Args >(args)...))`

12.335.1 Member Function Documentation

12.335.1.1 operator>()()

```
template<typename... Args>
auto operator() (
    Args &&... args ) const -> decltype(operator+(std::forward<Args>(args)...))
[inline]
```

The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.336 tfn_plus_eq Struct Reference

```
#include <sparse_matrix_traits.h>
```

Public Member Functions

- `template<typename... Args>`
`auto operator() (Args &&... args) const -> decltype(operator+(std::forward< Args >(args)...))`

12.336.1 Member Function Documentation

12.336.1.1 operator>()()

```
template<typename... Args>
auto operator() (
```

```
Args &&... args ) const -> decltype(operator+(std::forward<Args>(args)...))
[inline]
```

The documentation for this struct was generated from the following file:

- [sparse_matrix_traits.h](#)

12.337 Threads Struct Reference

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.338 ThreeD Struct Reference

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.339 ThreeDAdaptive Struct Reference

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.340 ThreeDInPlace Struct Reference

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.341 TRSMHelper< ReclterTrait, ParSeqTrait > Struct Template Reference

TRSM Helper.

Public Member Functions

- `template<class Cut , class Param >`
[TRSMHelper](#) ([ParSeqHelper::Parallel](#)< Cut, Param > _PS)
- `TRSMHelper` ([ParSeqHelper::Sequential](#) _PS)
- `template<typename RIT , typename PST >`
[TRSMHelper](#) ([TRSMHelper](#)< RIT, PST > &_TH)
- `template<class Dom , class Algo = FFLAS::MMHelperAlgo::Winograd, class ModeT = typename FFLAS::ModeTraits<Dom>::value>`
[FFLAS::MMHelper](#)< Dom, Algo, ModeT, ParSeqTrait > [pMMH](#) (Dom &D, size_t m, size_t k, size_t n, ParSeqTrait p) const
- `template<class Dom , class Algo = FFLAS::MMHelperAlgo::Winograd, class ModeT = typename FFLAS::ModeTraits<Dom>::value>`
[FFLAS::MMHelper](#)< Dom, Algo, ModeT, ParSeqTrait > [pMMH](#) (Dom &D, size_t m, size_t k, size_t n) const

Data Fields

- ParSeqTrait [parseq](#)

12.341.1 Detailed Description

```
template<typename RecIterTrait = StructureHelper::Recursive, typename ParSeqTrait = ParSeqHelper::Sequential>
```

```
struct FFLAS::TRSMHelper< RecIterTrait, ParSeqTrait >
```

TRSM Helper.

12.341.2 Constructor & Destructor Documentation

12.341.2.1 TRSMHelper() [1/3]

```
template<typename RecIterTrait = StructureHelper::Recursive, typename ParSeqTrait = ParSeqHelper::Sequential>
```

```
template<class Cut , class Param >
```

```
TRSMHelper (
    ParSeqHelper::Parallel< Cut, Param > _PS ) [inline]
```

12.341.2.2 TRSMHelper() [2/3]

```
template<typename RecIterTrait = StructureHelper::Recursive, typename ParSeqTrait = ParSeqHelper::Sequential>
```

```
TRSMHelper (
    ParSeqHelper::Sequential _PS ) [inline]
```

12.341.2.3 TRSMHelper() [3/3]

```
template<typename RecIterTrait = StructureHelper::Recursive, typename ParSeqTrait = ParSeqHelper::Sequential>
```

```
template<typename RIT , typename PST >
```

```
TRSMHelper (
    TRSMHelper< RIT, PST > & _TH ) [inline]
```

12.341.3 Member Function Documentation

12.341.3.1 pMMH() [1/2]

```
template<typename RecIterTrait = StructureHelper::Recursive, typename ParSeqTrait = ParSeqHelper::Sequential>
```

```
template<class Dom , class Algo = FFLAS::MMHelperAlgo::Winograd, class ModeT = typename FFLAS::ModeTraits<Dom>::value>
```

```
FFLAS::MMHelper< Dom, Algo, ModeT, ParSeqTrait > pMMH (
    Dom & D,
    size_t m,
    size_t k,
    size_t n,
    ParSeqTrait p ) const [inline]
```

12.341.3.2 pMMH() [2/2]

```
template<typename RecIterTrait = StructureHelper::Recursive, typename ParSeqTrait = ParSeqHelper::Sequential>
```

```
template<class Dom , class Algo = FFLAS::MMHelperAlgo::Winograd, class ModeT = typename FFLAS::ModeTraits<Dom>::value>
```

```
FFLAS::MMHelper< Dom, Algo, ModeT, ParSeqTrait > pMMH (
    Dom & D,
    size_t m,
    size_t k,
    size_t n ) const [inline]
```

12.341.4 Field Documentation

12.341.4.1 parseq

```
template<typename RecIterTrait = StructureHelper::Recursive, typename ParSeqTrait = ParSeqHelper::Sequential>
ParSeqTrait parseq
```

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.342 TwoD Struct Reference

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.343 TwoDAdaptive Struct Reference

The documentation for this struct was generated from the following file:

- [blockcuts.inl](#)

12.344 UnparametricTag Struct Reference

If the field uses a representation with infix operators.

```
#include <field-traits.h>
```

12.344.1 Detailed Description

If the field uses a representation with infix operators.

The documentation for this struct was generated from the following file:

- [field-traits.h](#)

12.345 width< T > Struct Template Reference

Static Public Attributes

- static constexpr size_t [value](#) = 2+2*sizeof(T)

12.345.1 Field Documentation

12.345.1.1 value

```
template<typename T >
constexpr size_t value = 2+2*sizeof(T) [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.346 width< double > Struct Reference

Static Public Attributes

- static constexpr size_t [value](#) = 24

12.346.1 Field Documentation

12.346.1.1 value

```
constexpr size_t value = 24 [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.347 width< float > Struct Reference

Static Public Attributes

- static constexpr size_t [value](#) = 16

12.347.1 Field Documentation

12.347.1.1 value

```
constexpr size_t value = 16 [static], [constexpr]
```

The documentation for this struct was generated from the following file:

- [test-simd.C](#)

12.348 Winograd Struct Reference

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

12.349 WinogradPar Struct Reference

The documentation for this struct was generated from the following file:

- [fflas_helpers.inl](#)

Chapter 13

File Documentation

13.1 arithprog.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include <iostream>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include <ctime>
```

Macros

- `#define CUBE(x) ((x)*(x)*(x))`
- `#define GFOPS(m, n, r, t) (2.7*CUBE(double(n)/1000.0))/t`

Typedefs

- `typedef Givaro::Timer TTimer`

Functions

- `int main (int argc, char **argv)`

13.1.1 Macro Definition Documentation

13.1.1.1 CUBE

```
#define CUBE(  
    x )  ((x)*(x)*(x))
```

13.1.1.2 GFOPS

```
#define GFOPS(  
    m,  
    n,  
    r,  
    t )  (2.7*CUBE(double(n)/1000.0))/t
```

13.1.2 Typedef Documentation

13.1.2.1 TTimer

```
typedef Givaro::Timer TTimer
```

13.1.3 Function Documentation

13.1.3.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.2 fsyrk.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include <ctime>
```

Macros

- `#define CUBE(x) ((x)*(x)*(x))`
- `#define GFOPS(n, t) (CUBE(double(n)/1000.0)/(3.0*t))`

Typedefs

- `typedef Givaro::Timer TTimer`

Functions

- `int main ()`

13.2.1 Macro Definition Documentation

13.2.1.1 CUBE

```
#define CUBE(
    x ) ((x)*(x)*(x))
```

13.2.1.2 GFOPS

```
#define GFOPS(
    n,
    t ) (CUBE(double(n)/1000.0)/(3.0*t))
```

13.2.2 Typedef Documentation

13.2.2.1 TTimer

```
typedef Givaro::Timer TTimer
```

13.2.3 Function Documentation

13.2.3.1 main()

```
int main (
    void )
```

13.3 fsytrf.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include <ctime>
```

Macros

- `#define CUBE(x) ((x)*(x)*(x))`
- `#define GFOPS(n, t) (CUBE(double(n)/1000.0)/(3.0*t))`

Typedefs

- `typedef Givaro::Timer TTimer`

Functions

- `int main ()`

13.3.1 Macro Definition Documentation

13.3.1.1 CUBE

```
#define CUBE(
    x ) ((x)*(x)*(x))
```

13.3.1.2 GFOPS

```
#define GFOPS(
    n,
    t ) (CUBE(double(n)/1000.0)/(3.0*t))
```

13.3.2 Typedef Documentation

13.3.2.1 TTimer

```
typedef Givaro::Timer TTimer
```

13.3.3 Function Documentation

13.3.3.1 main()

```
int main (
    void )
```

13.4 ftrtri.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include <iostream>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include <ctime>
```

Macros

- `#define CUBE(x) ((x)*(x)*(x))`
- `#define GFOPS(n, t) (CUBE(double(n)/1000.0)/(3.0*t))`

Typedefs

- `typedef Givaro::Timer TTimer`

Functions

- `int main ()`

13.4.1 Macro Definition Documentation**13.4.1.1 CUBE**

```
#define CUBE(
    x )  ((x)*(x)*(x))
```

13.4.1.2 GFOPS

```
#define GFOPS(
    n,
    t )  (CUBE(double(n)/1000.0)/(3.0*t))
```

13.4.2 Typedef Documentation**13.4.2.1 TTimer**

```
typedef Givaro::Timer TTimer
```

13.4.3 Function Documentation**13.4.3.1 main()**

```
int main (
    void )
```

13.5 winograd.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include <iostream>
#include <fstream>
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include <ctime>
```

Macros

- `#define DOUBLE_TO_FLOAT_CROSSOVER 0`
- `#define GFOPS(n, t) (2.0/t*(double)n/1000.0*(double)n/1000.0*(double)n/1000.0)`

Typedefs

- `typedef Givaro::Timer TTimer`

Functions

- template<class [Field](#) >
bool [balanced](#) (const [Field](#) &)
- template<class T >
bool [balanced](#) (const [Givaro::ModularBalanced](#)< T > &)
- int [main](#) ()

13.5.1 Macro Definition Documentation

13.5.1.1 DOUBLE_TO_FLOAT_CROSSOVER

```
#define DOUBLE_TO_FLOAT_CROSSOVER 0
```

13.5.1.2 GFOPS

```
#define GFOPS(  
    n,  
    t ) (2.0/t*(double)n/1000.0*(double)n/1000.0*(double)n/1000.0)
```

13.5.2 Typedef Documentation

13.5.2.1 TTimer

```
typedef Givaro::Timer TTimer
```

13.5.3 Function Documentation

13.5.3.1 [balanced\(\)](#) [1/2]

```
template<class Field >  
bool balanced (  
    const Field & )
```

13.5.3.2 [balanced\(\)](#) [2/2]

```
template<class T >  
bool balanced (  
    const Givaro::ModularBalanced< T > & )
```

13.5.3.3 [main\(\)](#)

```
int main (  
    void )
```

13.6 benchmark-charpoly-mp.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"  
#include <iostream>  
#include <givaro/modular.h>  
#include "fflas-ffpack/fflas-ffpack.h"  
#include "fflas-ffpack/utils/timer.h"  
#include "fflas-ffpack/utils/test-utils.h"  
#include "fflas-ffpack/utils/Matio.h"  
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- #define [__FFLASFFPACK_FORCE_SEQ](#)

Functions

- int [main](#) (int argc, char **argv)

13.6.1 Macro Definition Documentation

13.6.1.1 __FFLASFFPACK_FORCE_SEQ

```
#define __FFLASFFPACK_FORCE_SEQ
```

13.6.2 Function Documentation

13.6.2.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.7 benchmark-charpoly.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include <givaro/givpoly1.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- #define [__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET](#) 1

Functions

- template<class [Field](#) >
void [run_with_field](#) (int q, uint64_t bits, size_t n, size_t d, size_t iter, std::string file, int variant, uint64_t seed)
- int [main](#) (int argc, char **argv)

13.7.1 Macro Definition Documentation

13.7.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.7.2 Function Documentation

13.7.2.1 run_with_field()

```
template<class Field >
void run_with_field (
    int q,
    uint64_t bits,
    size_t n,
    size_t d,
    size_t iter,
    std::string file,
```



```
int variant,
uint64_t seed )
```

13.7.2.2 main()

```
int main (
    int argc,
    char ** argv )
```

13.8 benchmark-checkers.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <stdlib.h>
#include <time.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/checkers/checkers_fflas.h"
#include "fflas-ffpack/checkers/checkers_ffpack.h"
#include <fstream>
```

Macros

- `#define ENABLE_ALL_CHECKINGS 1`
- `#define _NR_TESTS 5`
- `#define _MAX_SIZE_MATRICES 1000`
- `#define CUBE(x) ((x)*(x)*(x))`

Functions

- `int main (int argc, char **argv)`

13.8.1 Macro Definition Documentation

13.8.1.1 ENABLE_ALL_CHECKINGS

```
#define ENABLE_ALL_CHECKINGS 1
```

13.8.1.2 _NR_TESTS

```
#define _NR_TESTS 5
```

13.8.1.3 _MAX_SIZE_MATRICES

```
#define _MAX_SIZE_MATRICES 1000
```

13.8.1.4 CUBE

```
#define CUBE(
    x ) ((x)*(x)*(x))
```

13.8.2 Function Documentation

13.8.2.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.9 benchmark-dgemm.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/config-blas.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- #define [CBLAS_GEMM](#) cblas_dgemm

Typedefs

- typedef [FFLAS::Timer](#) TTimer
- typedef double [Floats](#)

Functions

- int [main](#) (int argc, char **argv)

13.9.1 Macro Definition Documentation

13.9.1.1 CBLAS_GEMM

```
#define CBLAS_GEMM cblas_dgemm
```

13.9.2 Typedef Documentation

13.9.2.1 TTimer

```
typedef FFLAS::Timer TTimer
```

13.9.2.2 Floats

```
typedef double Floats
```

13.9.3 Function Documentation

13.9.3.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.10 benchmark-dgetrf.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <vector>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- `#define __FFLASFFPACK_HAVE_DGETRF 1`

Typedefs

- `typedef FFLAS::Timer TTimer`

Functions

- `int main (int argc, char **argv)`

13.10.1 Macro Definition Documentation

13.10.1.1 __FFLASFFPACK_HAVE_DGETRF

```
#define __FFLASFFPACK_HAVE_DGETRF 1
```

13.10.2 Typedef Documentation

13.10.2.1 TTimer

```
typedef FFLAS::Timer TTimer
```

13.10.3 Function Documentation

13.10.3.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.11 benchmark-dgetri.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <vector>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Typedefs

- `typedef FFLAS::Timer TTimer`

Functions

- int [main](#) (int argc, char **argv)

13.11.1 Typedef Documentation

13.11.1.1 TTimer

```
typedef FFLAS::Timer TTimer
```

13.11.2 Function Documentation

13.11.2.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.12 benchmark-dsytrf.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <vector>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- #define [EFFGFF](#)(n, t, i) ((double(n)/1000.*double(n)/1000.*double(n)/1000.0) / double(t) * double(i) / 3.)

Typedefs

- typedef [FFLAS::Timer](#) TTimer

Functions

- int [main](#) (int argc, char **argv)

13.12.1 Macro Definition Documentation

13.12.1.1 EFFGFF

```
#define EFFGFF(
    n,
    t,
    i ) ( (double(n)/1000.*double(n)/1000.*double(n)/1000.0) / double(t) * double(i)
/ 3.)
```

13.12.2 Typedef Documentation

13.12.2.1 TTimer

```
typedef FFLAS::Timer TTimer
```

13.12.3 Function Documentation

13.12.3.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.13 benchmark-dtrsm.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Typedefs

- typedef [FFLAS::Timer](#) [TTimer](#)

Functions

- int [main](#) (int argc, char **argv)

13.13.1 Typedef Documentation

13.13.1.1 TTimer

```
typedef FFLAS::Timer TTimer
```

13.13.2 Function Documentation

13.13.2.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.14 benchmark-dtrtri.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- #define [__FFLASFFPACK_HAVE_DTRTRI](#) 1

Typedefs

- typedef [FFLAS::Timer](#) [TTimer](#)

Functions

- int [main](#) (int argc, char **argv)

13.14.1 Macro Definition Documentation

13.14.1.1 __FFLASFFPACK_HAVE_DTRTRI

```
#define __FFLASFFPACK_HAVE_DTRTRI 1
```

13.14.2 Typedef Documentation

13.14.2.1 TTimer

```
typedef FFLAS::Timer TTimer
```

13.14.3 Function Documentation

13.14.3.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.15 benchmark-fadd-lvl2.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- #define [__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET](#) 1

Functions

- int [main](#) (int argc, char **argv)

13.15.1 Macro Definition Documentation

13.15.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.15.2 Function Documentation

13.15.2.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.16 benchmark-fdot.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include <givaro/givrational.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/paladin/parallel.h"
#include "fflas-ffpack/paladin/fflas_plevel1.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- `#define \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET 1`

Functions

- `template<class Field >`
`Field::Element run\_with\_field (int q, size_t iter, size_t N, const uint64_t BS, const size_t p, const size_t threads, uint64_t seed)`
- `int main (int argc, char **argv)`

13.16.1 Macro Definition Documentation

13.16.1.1 [__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET](#)

```
#define \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET 1
```

13.16.2 Function Documentation

13.16.2.1 [run_with_field\(\)](#)

```
template<class Field >
Field::Element run\_with\_field (
    int q,
    size_t iter,
    size_t N,
    const uint64_t BS,
    const size_t p,
    const size_t threads,
    uint64_t seed )
```

13.16.2.2 [main\(\)](#)

```
int main (
    int argc,
    char ** argv )
```

13.17 benchmark-fgemm-mp.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <typeinfo>
#include <vector>
#include <string>
```

```
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "givaro/modular-integer.h"
#include "givaro/givcaster.h"
#include "fflas-ffpack/paladin/parallel.h"
```

Macros

- `#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1`
- `#define MG_DEFAULT MG_ACTIVE`
- `#define STD_RECINT_SIZE 8`

Functions

- `template<typename Ints >`
`int tmain ()`
- `int main (int argc, char **argv)`

13.17.1 Macro Definition Documentation

13.17.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.17.1.2 MG_DEFAULT

```
#define MG_DEFAULT MG_ACTIVE
```

13.17.1.3 STD_RECINT_SIZE

```
#define STD_RECINT_SIZE 8
```

13.17.2 Function Documentation

13.17.2.1 tmain()

```
template<typename Ints >
int tmain ( )
```

13.17.2.2 main()

```
int main (
    int argc,
    char ** argv )
```

13.18 benchmark-fgemm-rns.C File Reference

```
#include "fflas-ffpack/fflas/fflas.h"
#include <iostream>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- `#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1`

Typedefs

- typedef `FFPACK::rns_double` `RNS`
- typedef `FFPACK::RNSInteger< RNS >` `Field`
- typedef `Field::Element_ptr` `Element_ptr`
- typedef `Field::ConstElement_ptr` `ConstElement_ptr`
- typedef `StrategyParameter::Threads` `THREADS`
- typedef `StrategyParameter::Grain` `GRAIN`
- typedef `StrategyParameter::TwoD` `TWOD`
- typedef `StrategyParameter::TwoDAdaptive` `TWODA`
- typedef `StrategyParameter::ThreeD` `THREED`
- typedef `StrategyParameter::ThreeDAdaptive` `THREEDA`
- typedef `StrategyParameter::ThreeDInPlace` `THREEDIP`
- typedef `ParSeqHelper::Sequential` `PSeq`

Functions

- int `main` (int argc, char *argv[])

13.18.1 Macro Definition Documentation

13.18.1.1 `__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET`

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.18.2 Typedef Documentation

13.18.2.1 `RNS`

```
typedef FFPACK::rns_double RNS
```

13.18.2.2 `Field`

```
typedef FFPACK::RNSInteger<RNS> Field
```

13.18.2.3 `Element_ptr`

```
typedef Field::Element_ptr Element_ptr
```

13.18.2.4 `ConstElement_ptr`

```
typedef Field::ConstElement_ptr ConstElement_ptr
```

13.18.2.5 `THREADS`

```
typedef StrategyParameter::Threads THREADS
```

13.18.2.6 `GRAIN`

```
typedef StrategyParameter::Grain GRAIN
```

13.18.2.7 `TWOD`

```
typedef StrategyParameter::TwoD TWOD
```

13.18.2.8 `TWODA`

```
typedef StrategyParameter::TwoDAdaptive TWODA
```

13.18.2.9 THREED

```
typedef StrategyParameter::ThreeD THREED
```

13.18.2.10 THREEDA

```
typedef StrategyParameter::ThreeDAdaptive THREEDA
```

13.18.2.11 THREEDIP

```
typedef StrategyParameter::ThreeDInPlace THREEDIP
```

13.18.2.12 PSeq

```
typedef ParSeqHelper::Sequential PSeq
```

13.18.3 Function Documentation**13.18.3.1 main()**

```
int main (
    int argc,
    char * argv[] )
```

13.19 benchmark-fgemm.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/config-blas.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- #define [CLASSIC_HYBRID](#)

Functions

- int [main](#) (int argc, char **argv)

13.19.1 Macro Definition Documentation**13.19.1.1 CLASSIC_HYBRID**

```
#define CLASSIC_HYBRID
```

13.19.2 Function Documentation**13.19.2.1 main()**

```
int main (
    int argc,
    char ** argv )
```

13.20 benchmark-fgemv-mp.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <typeinfo>
#include <vector>
#include <string>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "givaro/modular-integer.h"
#include "givaro/givcaster.h"
#include "fflas-ffpack/paladin/parallel.h"
```

Macros

- `#define \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET 1`
- `#define MG\_DEFAULT MG_ACTIVE`
- `#define STD\_RECINT\_SIZE 8`

Functions

- `template<typename T >`
`std::ostream & write\_matrix (std::ostream &out, Givaro::Integer p, size_t m, size_t n, T *C, size_t ldc)`
- `template<typename Ints >`
`int tmain ()`
- `int main (int argc, char **argv)`

13.20.1 Macro Definition Documentation

13.20.1.1 [__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET](#)

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.20.1.2 [MG_DEFAULT](#)

```
#define MG_DEFAULT MG_ACTIVE
```

13.20.1.3 [STD_RECINT_SIZE](#)

```
#define STD_RECINT_SIZE 8
```

13.20.2 Function Documentation

13.20.2.1 [write_matrix\(\)](#)

```
template<typename T >
std::ostream & write_matrix (
    std::ostream & out,
    Givaro::Integer p,
    size_t m,
    size_t n,
    T * C,
    size_t ldc )
```

13.20.2.2 [tmain\(\)](#)

```
template<typename Ints >
int tmain ( )
```

13.20.2.3 main()

```
int main (
    int argc,
    char ** argv )
```

13.21 benchmark-fgemv.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/config-blas.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "givaro/modular-integer.h"
#include "givaro/givcaster.h"
```

Data Structures

- struct [need_field_characteristic](#)< Field >
- struct [need_field_characteristic](#)< Givaro::Modular< Field > >
- struct [need_field_characteristic](#)< Givaro::ModularBalanced< Field > >
- struct [compatible_data_type](#)< Field >
- struct [compatible_data_type](#)< Givaro::ZRing< float > >
- struct [compatible_data_type](#)< Givaro::ZRing< double > >

Macros

- #define [__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET](#) 1

Functions

- template<class [Field](#) , class RandIter , class Matrix , class Vector >
void [fill_value](#) ([Field](#) &F, RandIter &Rand, Matrix &A, Vector &X, Vector &Y, size_t m, size_t k, size_t incX, size_t incY, size_t lda, int NBK)
- template<class [Field](#) , class Matrix , class Vector >
void [genData](#) ([Field](#) &F, Matrix &A, Vector &X, Vector &Y, size_t m, size_t k, size_t incX, size_t incY, size_t lda, int NBK, uint64_t bitsize, uint64_t seed)
- template<class [Field](#) , class Matrix , class Vector >
bool [check_result](#) ([Field](#) &F, size_t m, size_t lda, Matrix &A, Vector &X, size_t incX, Vector &Y, size_t incY)
- template<class [Field](#) , class Matrix , class Vector >
bool [benchmark_with_timer](#) ([Field](#) &F, int p, Matrix &A, Vector &X, Vector &Y, size_t m, size_t k, size_t incX, size_t incY, size_t lda, size_t iters, int t, double &time, size_t GrainSize)
- template<class [Field](#) , class arg >
void [benchmark_disp](#) ([Field](#) &F, bool pass, double &time, size_t iters, int p, size_t m, size_t k, arg &as)
- template<class [Field](#) , class arg >
void [benchmark_in_Field](#) ([Field](#) &F, int p, size_t m, size_t k, int NBK, uint64_t bitsize, uint64_t seed, size_t iters, int t, arg &as, size_t GrainSize)
- template<class [Field](#) , class arg >
void [benchmark_with_field](#) (int p, size_t m, size_t k, int NBK, uint64_t bitsize, uint64_t seed, size_t iters, int t, arg &as, size_t GrainSize)
- template<class [Field](#) , class arg >
void [benchmark_with_field](#) (const Givaro::Integer &q, int p, size_t m, size_t k, int NBK, uint64_t bitsize, uint64_t seed, size_t iters, int t, arg &as, size_t GrainSize)
- int [main](#) (int argc, char **argv)

13.21.1 Macro Definition Documentation

13.21.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.21.2 Function Documentation

13.21.2.1 fill_value()

```
template<class Field , class RandIter , class Matrix , class Vector >
void fill_value (
    Field & F,
    RandIter & Rand,
    Matrix & A,
    Vector & X,
    Vector & Y,
    size_t m,
    size_t k,
    size_t incX,
    size_t incY,
    size_t lda,
    int NBK )
```

13.21.2.2 genData()

```
template<class Field , class Matrix , class Vector >
void genData (
    Field & F,
    Matrix & A,
    Vector & X,
    Vector & Y,
    size_t m,
    size_t k,
    size_t incX,
    size_t incY,
    size_t lda,
    int NBK,
    uint64_t bitsize,
    uint64_t seed )
```

13.21.2.3 check_result()

```
template<class Field , class Matrix , class Vector >
bool check_result (
    Field & F,
    size_t m,
    size_t lda,
    Matrix & A,
    Vector & X,
    size_t incX,
    Vector & Y,
    size_t incY )
```

13.21.2.4 benchmark_with_timer()

```
template<class Field , class Matrix , class Vector >
bool benchmark_with_timer (
    Field & F,
    int p,
```

```

    Matrix & A,
    Vector & X,
    Vector & Y,
    size_t m,
    size_t k,
    size_t incX,
    size_t incY,
    size_t lda,
    size_t iters,
    int t,
    double & time,
    size_t GrainSize )

```

13.21.2.5 benchmark_disp()

```

template<class Field , class arg >
void benchmark_disp (
    Field & F,
    bool pass,
    double & time,
    size_t iters,
    int p,
    size_t m,
    size_t k,
    arg & as )

```

13.21.2.6 benchmark_in_Field()

```

template<class Field , class arg >
void benchmark_in_Field (
    Field & F,
    int p,
    size_t m,
    size_t k,
    int NBK,
    uint64_t bitsize,
    uint64_t seed,
    size_t iters,
    int t,
    arg & as,
    size_t GrainSize )

```

13.21.2.7 benchmark_with_field() [1/2]

```

template<class Field , class arg >
void benchmark_with_field (
    int p,
    size_t m,
    size_t k,
    int NBK,
    uint64_t bitsize,
    uint64_t seed,
    size_t iters,
    int t,
    arg & as,
    size_t GrainSize )

```

13.21.2.8 benchmark_with_field() [2/2]

```
template<class Field , class arg >
void benchmark_with_field (
    const Givaro::Integer & q,
    int p,
    size_t m,
    size_t k,
    int NBK,
    uint64_t bitsize,
    uint64_t seed,
    size_t iters,
    int t,
    arg & as,
    size_t GrainSize )
```

13.21.2.9 main()

```
int main (
    int argc,
    char ** argv )
```

13.22 benchmark-fgesv.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- #define `__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET` 1

Functions

- int `main` (int argc, char **argv)

13.22.1 Macro Definition Documentation**13.22.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET**

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.22.2 Function Documentation**13.22.2.1 main()**

```
int main (
    int argc,
    char ** argv )
```

13.23 benchmark-fsyr2k.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
```

```
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/config-blas.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Functions

- int [main](#) (int argc, char **argv)

13.23.1 Function Documentation

13.23.1.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.24 benchmark-fsyrrk.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- #define [__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET](#) 1

Functions

- int [main](#) (int argc, char **argv)

13.24.1 Macro Definition Documentation

13.24.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.24.2 Function Documentation

13.24.2.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.25 benchmark-fsytrf.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
```



```
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- `#define __FFPACK_FSYTRF_BC_CROUT`
- `#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1`
- `#define CUBE(x) ((x)*(x)*(x))`

Functions

- `int main (int argc, char **argv)`

13.25.1 Macro Definition Documentation

13.25.1.1 __FFPACK_FSYTRF_BC_CROUT

```
#define __FFPACK_FSYTRF_BC_CROUT
```

13.25.1.2 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.25.1.3 CUBE

```
#define CUBE(
    x ) ( (x)*(x)*(x) )
```

13.25.2 Function Documentation

13.25.2.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.26 benchmark-fftrsm-mp.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <vector>
#include <string>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "givaro/modular-integer.h"
```

Macros

- `#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1`

Functions

- `int main (int argc, char **argv)`

13.26.1 Macro Definition Documentation

13.26.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.26.2 Function Documentation

13.26.2.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.27 benchmark-ftsm.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- `#define \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET 1`

Functions

- `int main (int argc, char **argv)`

13.27.1 Macro Definition Documentation

13.27.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.27.2 Function Documentation

13.27.2.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.28 benchmark-ftsv.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- `#define \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET 1`

Functions

- int [main](#) (int argc, char **argv)

13.28.1 Macro Definition Documentation**13.28.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET**

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.28.2 Function Documentation**13.28.2.1 main()**

```
int main (
    int argc,
    char ** argv )
```

13.29 benchmark-fftrtri.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- #define [__FFLASFFPACK_OPENBLAS_NT_ALREADY_SET](#) 1
- #define [CUBE](#)(x) ((x)*(x)*(x))

Functions

- int [main](#) (int argc, char **argv)

13.29.1 Macro Definition Documentation**13.29.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET**

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.29.1.2 CUBE

```
#define CUBE(
    x ) ((x)*(x)*(x))
```

13.29.2 Function Documentation**13.29.2.1 main()**

```
int main (
    int argc,
    char ** argv )
```

13.30 benchmark-inverse.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- `#define CUBE(x) ((x)*(x)*(x))`

Functions

- `int main (int argc, char **argv)`

13.30.1 Macro Definition Documentation

13.30.1.1 CUBE

```
#define CUBE(  
    x )  ((x)*(x)*(x))
```

13.30.2 Function Documentation

13.30.2.1 main()

```
int main (  
    int argc,  
    char ** argv )
```

13.31 benchmark-lqmp.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <vector>
#include <string>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "givaro/modular-integer.h"
```

Functions

- `int main (int argc, char **argv)`

13.31.1 Function Documentation

13.31.1.1 main()

```
int main (  
    int argc,  
    char ** argv )
```

13.32 benchmark-lqup.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- #define [CUBE](#)(x) ((x)*(x)*(x))

Functions

- int [main](#) (int argc, char **argv)

13.32.1 Macro Definition Documentation

13.32.1.1 CUBE

```
#define CUBE(
    x )  ( (x)*(x)*(x) )
```

13.32.2 Function Documentation

13.32.2.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.33 benchmark-pluq.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <givaro/modular.h>
#include <givaro/givranditer.h>
#include <iostream>
#include "fflas-ffpack/config-blas.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/ffpack/ffpack.h"
```

Macros

- #define [_FFLASFFPACK_OPENBLAS_NT_ALREADY_SET](#) 1
- #define [CUBE](#)(x) ((x)*(x)*(x))

Typedefs

- typedef [Givaro::ModularBalanced](#)< double > [Field](#)

Functions

- void `verification_PLUQ` (const `Field` &`F`, typename `Field::Element` *`B`, typename `Field::Element` *`A`, `size_t` *`P`, `size_t` *`Q`, `size_t` `m`, `size_t` `n`, `size_t` `R`)
- void `Rec_Initialize` (`Field` &`F`, `Field::Element` *`C`, `size_t` `m`, `size_t` `n`, `size_t` `ldc`)
- int `main` (int `argc`, char **`argv`)

13.33.1 Macro Definition Documentation

13.33.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.33.1.2 CUBE

```
#define CUBE(  
    x ) ((x)*(x)*(x))
```

13.33.2 Typedef Documentation

13.33.2.1 Field

```
typedef Givaro::ModularBalanced<double> Field
```

13.33.3 Function Documentation

13.33.3.1 verification_PLUQ()

```
void verification_PLUQ (  
    const Field & F,  
    typename Field::Element * B,  
    typename Field::Element * A,  
    size_t * P,  
    size_t * Q,  
    size_t m,  
    size_t n,  
    size_t R )
```

13.33.3.2 Rec_Initialize()

```
void Rec_Initialize (  
    Field & F,  
    Field::Element * C,  
    size_t m,  
    size_t n,  
    size_t ldc )
```

13.33.3.3 main()

```
int main (  
    int argc,  
    char ** argv )
```

13.34 benchmark-quasisep.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"  
#include <iostream>  
#include <givaro/modular.h>  
#include <givaro/givpoly1.h>
```

```
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- `#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1`

Functions

- `template<class Field >`
`void run_with_field (int q, size_t n, size_t m, size_t t, size_t r, size_t iter, uint64_t seed)`
- `int main (int argc, char **argv)`

13.34.1 Macro Definition Documentation

13.34.1.1 __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET

```
#define __FFLASFFPACK_OPENBLAS_NT_ALREADY_SET 1
```

13.34.2 Function Documentation

13.34.2.1 run_with_field()

```
template<class Field >
void run_with_field (
    int q,
    size_t n,
    size_t m,
    size_t t,
    size_t r,
    size_t iter,
    uint64_t seed )
```

13.34.2.2 main()

```
int main (
    int argc,
    char ** argv )
```

13.35 benchmark-storage-transpose.C File Reference

```
#include <iomanip>
#include <iostream>
#include <random>
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/fflas_memory.h"
#include <givar/modular.h>
#include <recint/rint.h>
#include "fflas-ffpack/fflas/fflas_transpose.h"
```

Data Structures

- class [Bench<Elt>](#)

Functions

- int [main](#) (int argc, char **argv)

13.35.1 Function Documentation

13.35.1.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.36 benchmark-wino.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <fstream>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/utils/args-parser.h"
```

Macros

- #define [CUBE](#)(x) ((x)*(x)*(x))

Functions

- template<class [Field](#) >
void [launch_wino](#) (const [Field](#) &F, const size_t &n, const size_t &NB, const size_t &wino, const bool &asmax, const size_t &seed, const bool compare)
- int [main](#) (int argc, char **argv)

13.36.1 Macro Definition Documentation

13.36.1.1 CUBE

```
#define CUBE(
    x ) ((x)*(x)*(x))
```

13.36.2 Function Documentation

13.36.2.1 launch_wino()

```
template<class Field >
void launch_wino (
    const Field & F,
    const size_t & n,
    const size_t & NB,
    const size_t & wino,
    const bool & asmax,
    const size_t & seed,
    const bool compare )
```


13.36.2.2 main()

```
int main (
    int argc,
    char ** argv )
```

13.37 config.h File Reference

Macros

- #define [HAVE_BLAS](#) 1
- #define [HAVE_CBLAS](#) 1
- #define [HAVE_CXX11](#) 1
- #define [HAVE_DLFCN_H](#) 1
- #define [HAVE_FLOAT_H](#) 1
- #define [HAVE_INT128](#) 1
- #define [HAVE_INTPYPES_H](#) 1
- #define [HAVE_LAPACK](#) 1
- #define [HAVE_LIMITS_H](#) 1
- #define [HAVE_LITTLE_ENDIAN](#) 1
- #define [HAVE_PTHREAD_H](#) 1
- #define [HAVE_STDDEF_H](#) 1
- #define [HAVE_STDINT_H](#) 1
- #define [HAVE_STDIO_H](#) 1
- #define [HAVE_STDLIB_H](#) 1
- #define [HAVE_STRINGS_H](#) 1
- #define [HAVE_STRING_H](#) 1
- #define [HAVE_SYS_STAT_H](#) 1
- #define [HAVE_SYS_TIME_H](#) 1
- #define [HAVE_SYS_TYPES_H](#) 1
- #define [HAVE_UNISTD_H](#) 1
- #define [LT_OBJDIR](#) ".libs/"
- #define [OPENBLAS_NUM_THREADS](#) 1
- #define [PACKAGE](#) "fflas-ffpack"
- #define [PACKAGE_BUGREPORT](#) "ffpack-devel@googlegroups.com"
- #define [PACKAGE_NAME](#) "FFLAS-FFPACK"
- #define [PACKAGE_STRING](#) "FFLAS-FFPACK 2.5.0"
- #define [PACKAGE_TARNAME](#) "fflas-ffpack"
- #define [PACKAGE_URL](#) "https://github.com/linbox-team/fflas-ffpack"
- #define [PACKAGE_VERSION](#) "2.5.0"
- #define [SIZEOF_CHAR](#) 1
- #define [SIZEOF_INT](#) 4
- #define [SIZEOF_LONG](#) 8
- #define [SIZEOF_LONG_LONG](#) 8
- #define [SIZEOF_SHORT](#) 2
- #define [SIZEOF___INT64_T](#) 8
- #define [STDC_HEADERS](#) 1
- #define [USE_OPENMP](#) 1
- #define [VERSION](#) "2.5.0"

13.37.1 Macro Definition Documentation

13.37.1.1 HAVE_BLAS

```
#define HAVE_BLAS 1
```

13.37.1.2 HAVE_CBLAS

```
#define HAVE_CBLAS 1
```

13.37.1.3 HAVE_CXX11

```
#define HAVE_CXX11 1
```

13.37.1.4 HAVE_DLFCN_H

```
#define HAVE_DLFCN_H 1
```

13.37.1.5 HAVE_FLOAT_H

```
#define HAVE_FLOAT_H 1
```

13.37.1.6 HAVE_INT128

```
#define HAVE_INT128 1
```

13.37.1.7 HAVE_INTPYPES_H

```
#define HAVE_INTPYPES_H 1
```

13.37.1.8 HAVE_LAPACK

```
#define HAVE_LAPACK 1
```

13.37.1.9 HAVE_LIMITS_H

```
#define HAVE_LIMITS_H 1
```

13.37.1.10 HAVE_LITTLE_ENDIAN

```
#define HAVE_LITTLE_ENDIAN 1
```

13.37.1.11 HAVE_PTHREAD_H

```
#define HAVE_PTHREAD_H 1
```

13.37.1.12 HAVE_STDDEF_H

```
#define HAVE_STDDEF_H 1
```

13.37.1.13 HAVE_STDINT_H

```
#define HAVE_STDINT_H 1
```

13.37.1.14 HAVE_STDIO_H

```
#define HAVE_STDIO_H 1
```

13.37.1.15 HAVE_STDLIB_H

```
#define HAVE_STDLIB_H 1
```

13.37.1.16 HAVE_STRINGS_H

```
#define HAVE_STRINGS_H 1
```

13.37.1.17 HAVE_STRING_H

```
#define HAVE_STRING_H 1
```

13.37.1.18 HAVE_SYS_STAT_H

```
#define HAVE_SYS_STAT_H 1
```

13.37.1.19 HAVE_SYS_TIME_H

```
#define HAVE_SYS_TIME_H 1
```

13.37.1.20 HAVE_SYS_TYPES_H

```
#define HAVE_SYS_TYPES_H 1
```

13.37.1.21 HAVE_UNISTD_H

```
#define HAVE_UNISTD_H 1
```

13.37.1.22 LT_OBJDIR

```
#define LT_OBJDIR ".libs/"
```

13.37.1.23 OPENBLAS_NUM_THREADS

```
#define OPENBLAS_NUM_THREADS 1
```

13.37.1.24 PACKAGE

```
#define PACKAGE "fflas-ffpack"
```

13.37.1.25 PACKAGE_BUGREPORT

```
#define PACKAGE_BUGREPORT "ffpack-devel@googlegroups.com"
```

13.37.1.26 PACKAGE_NAME

```
#define PACKAGE_NAME "FFLAS-FFPACK"
```

13.37.1.27 PACKAGE_STRING

```
#define PACKAGE_STRING "FFLAS-FFPACK 2.5.0"
```

13.37.1.28 PACKAGE_TARNAME

```
#define PACKAGE_TARNAME "fflas-ffpack"
```

13.37.1.29 PACKAGE_URL

```
#define PACKAGE_URL "https://github.com/linbox-team/fflas-ffpack"
```

13.37.1.30 PACKAGE_VERSION

```
#define PACKAGE_VERSION "2.5.0"
```

13.37.1.31 SIZEOF_CHAR

```
#define SIZEOF_CHAR 1
```

13.37.1.32 `SIZEOF_INT`

```
#define SIZEOF_INT 4
```

13.37.1.33 `SIZEOF_LONG`

```
#define SIZEOF_LONG 8
```

13.37.1.34 `SIZEOF_LONG_LONG`

```
#define SIZEOF_LONG_LONG 8
```

13.37.1.35 `SIZEOF_SHORT`

```
#define SIZEOF_SHORT 2
```

13.37.1.36 `SIZEOF__INT64_T`

```
#define SIZEOF__INT64_T 8
```

13.37.1.37 `STDC_HEADERS`

```
#define STDC_HEADERS 1
```

13.37.1.38 `USE_OPENMP`

```
#define USE_OPENMP 1
```

13.37.1.39 `VERSION`

```
#define VERSION "2.5.0"
```

13.38 `config.h` File Reference**Macros**

- [#define `\_\_FFLASFFPACK\_HAVE\_BLAS` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_CBLAS` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_CXX11` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_DLFCN\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_FLOAT\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_INT128` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_INTPTR\_T` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_LAPACK` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_LIMITS\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_LITTLE\_ENDIAN` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_PTHREAD\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_STDDEF\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_STDINT\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_STDIO\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_STDLIB\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_STRINGS\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_STRING\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_SYS\_STAT\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_SYS\_TIME\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_SYS\_TYPES\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_HAVE\_UNISTD\_H` 1](#)
- [#define `\_\_FFLASFFPACK\_LT\_OBJDIR` `"./libs/"`](#)

- `#define __FFLASFFPACK_OPENBLAS_NUM_THREADS 1`
- `#define __FFLASFFPACK_PACKAGE "fflas-ffpack"`
- `#define __FFLASFFPACK_PACKAGE_BUGREPORT "ffpack-devel@googlegroups.com"`
- `#define __FFLASFFPACK_PACKAGE_NAME "FFLAS-FFPACK"`
- `#define __FFLASFFPACK_PACKAGE_STRING "FFLAS-FFPACK 2.5.0"`
- `#define __FFLASFFPACK_PACKAGE_TARNAME "fflas-ffpack"`
- `#define __FFLASFFPACK_PACKAGE_URL "https://github.com/linbox-team/fflas-ffpack"`
- `#define __FFLASFFPACK_PACKAGE_VERSION "2.5.0"`
- `#define __FFLASFFPACK_SIZEOF_CHAR 1`
- `#define __FFLASFFPACK_SIZEOF_INT 4`
- `#define __FFLASFFPACK_SIZEOF_LONG 8`
- `#define __FFLASFFPACK_SIZEOF_LONG_LONG 8`
- `#define __FFLASFFPACK_SIZEOF_SHORT 2`
- `#define __FFLASFFPACK_SIZEOF__INT64_T 8`
- `#define __FFLASFFPACK_STDC_HEADERS 1`
- `#define __FFLASFFPACK_USE_OPENMP 1`
- `#define __FFLASFFPACK_VERSION "2.5.0"`

13.38.1 Macro Definition Documentation

13.38.1.1 `__FFLASFFPACK_HAVE_BLAS`

```
#define __FFLASFFPACK_HAVE_BLAS 1
```

13.38.1.2 `__FFLASFFPACK_HAVE_CBLAS`

```
#define __FFLASFFPACK_HAVE_CBLAS 1
```

13.38.1.3 `__FFLASFFPACK_HAVE_CXX11`

```
#define __FFLASFFPACK_HAVE_CXX11 1
```

13.38.1.4 `__FFLASFFPACK_HAVE_DLFCN_H`

```
#define __FFLASFFPACK_HAVE_DLFCN_H 1
```

13.38.1.5 `__FFLASFFPACK_HAVE_FLOAT_H`

```
#define __FFLASFFPACK_HAVE_FLOAT_H 1
```

13.38.1.6 `__FFLASFFPACK_HAVE_INT128`

```
#define __FFLASFFPACK_HAVE_INT128 1
```

13.38.1.7 `__FFLASFFPACK_HAVE_INTTYPES_H`

```
#define __FFLASFFPACK_HAVE_INTTYPES_H 1
```

13.38.1.8 `__FFLASFFPACK_HAVE_LAPACK`

```
#define __FFLASFFPACK_HAVE_LAPACK 1
```

13.38.1.9 `__FFLASFFPACK_HAVE_LIMITS_H`

```
#define __FFLASFFPACK_HAVE_LIMITS_H 1
```

13.38.1.10 `__FFLASFFPACK_HAVE_LITTLE_ENDIAN`

```
#define __FFLASFFPACK_HAVE_LITTLE_ENDIAN 1
```

13.38.1.11 __FFLASFFPACK_HAVE_PTHREAD_H

```
#define __FFLASFFPACK_HAVE_PTHREAD_H 1
```

13.38.1.12 __FFLASFFPACK_HAVE_STDDEF_H

```
#define __FFLASFFPACK_HAVE_STDDEF_H 1
```

13.38.1.13 __FFLASFFPACK_HAVE_STDINT_H

```
#define __FFLASFFPACK_HAVE_STDINT_H 1
```

13.38.1.14 __FFLASFFPACK_HAVE_STDIO_H

```
#define __FFLASFFPACK_HAVE_STDIO_H 1
```

13.38.1.15 __FFLASFFPACK_HAVE_STDLIB_H

```
#define __FFLASFFPACK_HAVE_STDLIB_H 1
```

13.38.1.16 __FFLASFFPACK_HAVE_STRINGS_H

```
#define __FFLASFFPACK_HAVE_STRINGS_H 1
```

13.38.1.17 __FFLASFFPACK_HAVE_STRING_H

```
#define __FFLASFFPACK_HAVE_STRING_H 1
```

13.38.1.18 __FFLASFFPACK_HAVE_SYS_STAT_H

```
#define __FFLASFFPACK_HAVE_SYS_STAT_H 1
```

13.38.1.19 __FFLASFFPACK_HAVE_SYS_TIME_H

```
#define __FFLASFFPACK_HAVE_SYS_TIME_H 1
```

13.38.1.20 __FFLASFFPACK_HAVE_SYS_TYPES_H

```
#define __FFLASFFPACK_HAVE_SYS_TYPES_H 1
```

13.38.1.21 __FFLASFFPACK_HAVE_UNISTD_H

```
#define __FFLASFFPACK_HAVE_UNISTD_H 1
```

13.38.1.22 __FFLASFFPACK_LT_OBJDIR

```
#define __FFLASFFPACK_LT_OBJDIR ".libs/"
```

13.38.1.23 __FFLASFFPACK_OPENBLAS_NUM_THREADS

```
#define __FFLASFFPACK_OPENBLAS_NUM_THREADS 1
```

13.38.1.24 __FFLASFFPACK_PACKAGE

```
#define __FFLASFFPACK_PACKAGE "fflas-ffpack"
```

13.38.1.25 __FFLASFFPACK_PACKAGE_BUGREPORT

```
#define __FFLASFFPACK_PACKAGE_BUGREPORT "ffpack-devel@googlegroups.com"
```

13.38.1.26 __FFLASFFPACK_PACKAGE_NAME

```
#define __FFLASFFPACK_PACKAGE_NAME "FFLAS-FFPACK"
```

13.38.1.27 __FFLASFFPACK_PACKAGE_STRING

```
#define __FFLASFFPACK_PACKAGE_STRING "FFLAS-FFPACK 2.5.0"
```

13.38.1.28 __FFLASFFPACK_PACKAGE_TARNAME

```
#define __FFLASFFPACK_PACKAGE_TARNAME "fflas-ffpack"
```

13.38.1.29 __FFLASFFPACK_PACKAGE_URL

```
#define __FFLASFFPACK_PACKAGE_URL "https://github.com/linbox-team/fflas-ffpack"
```

13.38.1.30 __FFLASFFPACK_PACKAGE_VERSION

```
#define __FFLASFFPACK_PACKAGE_VERSION "2.5.0"
```

13.38.1.31 __FFLASFFPACK_SIZEOF_CHAR

```
#define __FFLASFFPACK_SIZEOF_CHAR 1
```

13.38.1.32 __FFLASFFPACK_SIZEOF_INT

```
#define __FFLASFFPACK_SIZEOF_INT 4
```

13.38.1.33 __FFLASFFPACK_SIZEOF_LONG

```
#define __FFLASFFPACK_SIZEOF_LONG 8
```

13.38.1.34 __FFLASFFPACK_SIZEOF_LONG_LONG

```
#define __FFLASFFPACK_SIZEOF_LONG_LONG 8
```

13.38.1.35 __FFLASFFPACK_SIZEOF_SHORT

```
#define __FFLASFFPACK_SIZEOF_SHORT 2
```

13.38.1.36 __FFLASFFPACK_SIZEOF__INT64_T

```
#define __FFLASFFPACK_SIZEOF__INT64_T 8
```

13.38.1.37 __FFLASFFPACK_STDC_HEADERS

```
#define __FFLASFFPACK_STDC_HEADERS 1
```

13.38.1.38 __FFLASFFPACK_USE_OPENMP

```
#define __FFLASFFPACK_USE_OPENMP 1
```

13.38.1.39 __FFLASFFPACK_VERSION

```
#define __FFLASFFPACK_VERSION "2.5.0"
```

13.39 mainpage.dox File Reference

13.40 charpoly.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include <iostream>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include <ctime>
```

Macros

- `#define CUBE(x) ((x)*(x)*(x))`
- `#define GFOPS(m, n, r, t) (2.7*CUBE(double(n)/1000.0))/t`

Typedefs

- `typedef Givaro::Timer TTimer`

Functions

- `int main ()`

13.40.1 Macro Definition Documentation

13.40.1.1 CUBE

```
#define CUBE(
    x )  ((x)*(x)*(x))
```

13.40.1.2 GFOPS

```
#define GFOPS(
    m,
    n,
    r,
    t )  (2.7*CUBE(double(n)/1000.0))/t
```

13.40.2 Typedef Documentation

13.40.2.1 TTimer

```
typedef Givaro::Timer TTimer
```

13.40.3 Function Documentation

13.40.3.1 main()

```
int main (
    void )
```

13.41 charpoly.C File Reference

```
#include <iostream>
#include "fflas-ffpack/fflas-ffpack.h"
```


Functions

- int `main` (int argc, char **argv)

This example computes the characteristic polynomial of a matrix over a defined finite field.

13.41.1 Function Documentation**13.41.1.1 main()**

```
int main (
    int argc,
    char ** argv )
```

This example computes the characteristic polynomial of a matrix over a defined finite field.
Outputs the characteristic polynomial.

13.42 det.C File Reference

```
#include <givaro/modular.h>
#include <iostream>
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/fflas_io.h"
```

Functions

- int `main` (int argc, char **argv)

This example computes the determinant of a matrix over a defined finite field.

13.42.1 Function Documentation**13.42.1.1 main()**

```
int main (
    int argc,
    char ** argv )
```

This example computes the determinant of a matrix over a defined finite field.
Outputs the determinant.

13.43 matmul.C File Reference

```
#include <iostream>
#include "fflas-ffpack/fflas-ffpack.h"
```

Functions

- int `main` (int argc, char **argv)

This example computes the matrix multiplication over a defined finite field.

13.43.1 Function Documentation**13.43.1.1 main()**

```
int main (
    int argc,
    char ** argv )
```

This example computes the matrix multiplication over a defined finite field.
Outputs the product of the matrix given as input.

13.44 pluq.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include <iostream>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include <ctime>
```

Macros

- `#define CUBE(x) ((x)*(x)*(x))`
- `#define GFOPS(m, n, r, t) (2.0/3.0*CUBE(double(n)/1000.0) +2*m/1000.0*n/1000.0*double(r)/1000.0 - double(r)/1000.0*double(r)/1000.0*(m+n)/1000)/t`

Typedefs

- `typedef Givaro::Timer TTimer`

Functions

- `int main ()`

13.44.1 Macro Definition Documentation

13.44.1.1 CUBE

```
#define CUBE(
    x )  ( (x)*(x)*(x) )
```

13.44.1.2 GFOPS

```
#define GFOPS(
    m,
    n,
    r,
    t ) (2.0/3.0*CUBE(double(n)/1000.0) +2*m/1000.0*n/1000.0*double(r)/1000.0 - double(r)/1000.0*double(r)/1000.0*(m+n)/1000)/t
```

13.44.2 Typedef Documentation

13.44.2.1 TTimer

```
typedef Givaro::Timer TTimer
```

13.44.3 Function Documentation

13.44.3.1 main()

```
int main (
    void )
```

13.45 pluq.C File Reference

```
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack-config.h"
```

```
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/fflas_io.h"
```

Functions

- int [main](#) (int argc, char **argv)

13.45.1 Function Documentation

13.45.1.1 main()

```
int main (
    int argc,
    char ** argv )
```

13.46 rank.C File Reference

```
#include <iostream>
#include "fflas-ffpack/fflas-ffpack.h"
```

Functions

- int [main](#) (int argc, char **argv)

This example computes the rank of a matrix over a defined finite field.

13.46.1 Function Documentation

13.46.1.1 main()

```
int main (
    int argc,
    char ** argv )
```

This example computes the rank of a matrix over a defined finite field.
Outputs the rank.

13.47 solve.C File Reference

```
#include <iostream>
#include "fflas-ffpack/fflas-ffpack.h"
```

Functions

- int [main](#) (int argc, char **argv)

This example solve the quare system defined by the input over a defined finite field.

13.47.1 Function Documentation

13.47.1.1 main()

```
int main (
    int argc,
    char ** argv )
```

This example solve the quare system defined by the input over a defined finite field.

13.48 checker_charpoly.inl File Reference

```
#include "fflas-ffpack/ffpack/ffpack.h"
```

Data Structures

- class [CheckerImplem_charpoly< Field, Polynomial >](#)
- class [CheckerImplem_charpoly< Givaro::ZRing< Givaro::Integer >, Polynomial >](#)

Namespaces

- namespace [FFPACK](#)
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

Macros

- #define [__FFLASFFPACK_checker_charpoly_INL](#)

13.48.1 Macro Definition Documentation

13.48.1.1 __FFLASFFPACK_checker_charpoly_INL

```
#define __FFLASFFPACK_checker_charpoly_INL
```

13.49 checker_det.inl File Reference

```
#include "fflas-ffpack/ffpack/ffpack.h"
```

Data Structures

- class [CheckerImplem_Det< Field >](#)

Namespaces

- namespace [FFPACK](#)
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

Macros

- #define [__FFLASFFPACK_checker_det_INL](#)

13.49.1 Macro Definition Documentation

13.49.1.1 __FFLASFFPACK_checker_det_INL

```
#define __FFLASFFPACK_checker_det_INL
```

13.50 checker_empty.h File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
```

Data Structures

- struct [Checker_Empty< Field >](#)

Namespaces

- namespace [FFLAS](#)

13.51 checker_fgemm.inl File Reference**Data Structures**

- class [CheckerImplem_fgemm< Field >](#)

Namespaces

- namespace [FFLAS](#)

Macros

- `#define __FFLASFFPACK_checker_fgemm_INL`

13.51.1 Macro Definition Documentation**13.51.1.1 __FFLASFFPACK_checker_fgemm_INL**

```
#define __FFLASFFPACK_checker_fgemm_INL
```

13.52 checker_ftrsm.inl File Reference**Data Structures**

- class [CheckerImplem_ftrsm< Field >](#)

Namespaces

- namespace [FFLAS](#)

Macros

- `#define __FFLASFFPACK_checker_ftrsm_INL`

13.52.1 Macro Definition Documentation**13.52.1.1 __FFLASFFPACK_checker_ftrsm_INL**

```
#define __FFLASFFPACK_checker_ftrsm_INL
```

13.53 checker_invert.inl File Reference**Data Structures**

- class [CheckerImplem_invert< Field >](#)

Namespaces

- namespace [FFPACK](#)
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

Macros

- `#define __FFLASFFPACK_checker_invert_INL`

13.53.1 Macro Definition Documentation

13.53.1.1 __FFLASFFPACK_checker_invert_INL

```
#define __FFLASFFPACK_checker_invert_INL
```

13.54 checker_pluq.inl File Reference

```
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/fflas_io.h"
```

Data Structures

- class [CheckerImplem_PLUQ< Field >](#)

Namespaces

- namespace [FFPACK](#)
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

Macros

- #define [__FFLASFFPACK_checker_pluq_INL](#)

13.54.1 Macro Definition Documentation

13.54.1.1 __FFLASFFPACK_checker_pluq_INL

```
#define __FFLASFFPACK_checker_pluq_INL
```

13.55 checkers.doxy File Reference

13.56 checkers_fflas.h File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "checker_empty.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/fflas/fflas_enum.h"
#include "fflas-ffpack/utils/fflas_memory.h"
```

Data Structures

- class [FailureFgemmCheck](#)
- class [FailureTrsmCheck](#)

Namespaces

- namespace [FFLAS](#)

Typedefs

- template<class [Field](#) >
using [Checker_fgemm](#) = [FFLAS::Checker_Empty< Field >](#)
- template<class [Field](#) >
using [Checker_ftsm](#) = [FFLAS::Checker_Empty< Field >](#)

13.57 checkers_fflas.inl File Reference

```
#include "checker_fgemm.inl"
#include "checker_ftrsm.inl"
```

Namespaces

- namespace [FFLAS](#)

Macros

- #define [FFLASFFPACK_checkers_fflas_inl_H](#)

Typedefs

- template<class [Field](#) >
using [ForceCheck_fgemm](#) = [CheckerImplem_fgemm](#)< [Field](#) >
- template<class [Field](#) >
using [ForceCheck_ftrsm](#) = [CheckerImplem_ftrsm](#)< [Field](#) >

13.57.1 Macro Definition Documentation

13.57.1.1 FFLASFFPACK_checkers_fflas_inl_H

```
#define FFLASFFPACK_checkers_fflas_inl_H
```

13.58 checkers_ffpack.h File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "checker_empty.h"
#include "fflas-ffpack/ffpack/ffpack.h"
```

Data Structures

- class [FailurePLUQCheck](#)
- class [FailureDetCheck](#)
- class [FailureInvertCheck](#)
- class [FailureCharpolyCheck](#)

Namespaces

- namespace [FFPACK](#)

*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

Typedefs

- template<class [Field](#) >
using [Checker_PLUQ](#) = [FFLAS::Checker_Empty](#)< [Field](#) >
- template<class [Field](#) >
using [Checker_Det](#) = [FFLAS::Checker_Empty](#)< [Field](#) >
- template<class [Field](#) >
using [Checker_invert](#) = [FFLAS::Checker_Empty](#)< [Field](#) >
- template<class [Field](#) , class Polynomial >
using [Checker_charpoly](#) = [FFLAS::Checker_Empty](#)< [Field](#) >

13.59 checkers_ffpack.inl File Reference

```
#include "checker_pluq.inl"
#include "checker_det.inl"
#include "checker_invert.inl"
#include "checker_charpoly.inl"
```

Namespaces

- namespace [FFPACK](#)
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

Macros

- #define [FFLASFFPACK_checkers_ffpack_inl_H](#)

Typedefs

- template<class [Field](#) >
using [ForceCheck_PLUQ](#) = [CheckerImplem_PLUQ](#)< [Field](#) >
- template<class [Field](#) >
using [ForceCheck_Det](#) = [CheckerImplem_Det](#)< [Field](#) >
- template<class [Field](#) >
using [ForceCheck_invert](#) = [CheckerImplem_invert](#)< [Field](#) >
- template<class [Field](#) , class Polynomial >
using [ForceCheck_charpoly](#) = [CheckerImplem_charpoly](#)< [Field](#), Polynomial >

13.59.1 Macro Definition Documentation

13.59.1.1 FFLASFFPACK_checkers_ffpack_inl_H

```
#define FFLASFFPACK_checkers_ffpack_inl_H
```

13.60 config-blas.h File Reference

Macros

- #define [CBLAS_INT](#) int
- #define [CBLAS_ENUM_DEFINED_H](#)
- #define [CBLAS_EXTERNALS](#)
- #define [blas_enum](#) enum

Enumerations

- enum [CBLAS_ORDER](#) { [CblasRowMajor](#) =101 , [CblasColMajor](#) =102 }
- enum [CBLAS_TRANSPOSE](#) { [CblasNoTrans](#) =111 , [CblasTrans](#) =112 , [CblasConjTrans](#) =113 , [AtlasConj](#) =114 }
- enum [CBLAS_UPLO](#) { [CblasUpper](#) =121 , [CblasLower](#) =122 }
- enum [CBLAS_DIAG](#) { [CblasNonUnit](#) =131 , [CblasUnit](#) =132 }
- enum [CBLAS_SIDE](#) { [CblasLeft](#) =141 , [CblasRight](#) =142 }

Functions

- void [daxpy_](#) (const int *, const double *, const double *, const int *, double *, const int *)
- void [saxpy_](#) (const int *, const float *, const float *, const int *, float *, const int *)
- double [ddot_](#) (const int *, const double *, const int *, const double *, const int *)
- float [sdot_](#) (const int *, const float *, const int *, const float *, const int *)

- double [dasum_](#) (const int *, const double *, const int *)
- int [idamax_](#) (const int *, const double *, const int *)
- double [dnrm2_](#) (const int *, const double *, const int *)
- void [dgemv_](#) (const char *, const int *, const int *, const double *, const double *, const int *, const double *, const int *, const double *, double *, const int *)
- void [sgemv_](#) (const char *, const int *, const int *, const float *, const float *, const int *, const float *, const int *, const float *, float *, const int *)
- void [dger_](#) (const int *, const int *, const double *, const double *, const int *, const double *, const int *, double *, const int *)
- void [sger_](#) (const int *, const int *, const float *, const float *, const int *, const float *, const int *, float *, const int *)
- void [dcopy_](#) (const int *, const double *, const int *, double *, const int *)
- void [scopy_](#) (const int *, const float *, const int *, float *, const int *)
- void [dscal_](#) (const int *, const double *, double *, const int *)
- void [sscal_](#) (const int *, const float *, float *, const int *)
- void [dtrsm_](#) (const char *, const char *, const char *, const char *, const int *, const int *, const double *, const double *, const int *, double *, const int *)
- void [strsm_](#) (const char *, const char *, const char *, const char *, const int *, const int *, const float *, const float *, const int *, float *, const int *)
- void [dtrmm_](#) (const char *, const char *, const char *, const char *, const int *, const int *, const double *, const double *, const int *, double *, const int *)
- void [strmm_](#) (const char *, const char *, const char *, const char *, const int *, const int *, const float *, const float *, const int *, float *, const int *)
- void [sgemm_](#) (const char *, const char *, const int *, const int *, const int *, const float *, const float *, const int *, const float *, const int *, const float *, float *, const int *)
- void [dgemm_](#) (const char *, const char *, const int *, const int *, const int *, const double *, const double *, const int *, const double *, const int *, const double *, double *, const int *)
- void [cblas_dsyrk](#) (const enum [CBLAS_ORDER](#) Order, const enum [CBLAS_UPLO](#) Uplo, const enum [CBLAS_TRANSPOSE](#) Trans, const int N, const int K, const double alpha, const double *A, const int lda, const double beta, double *C, const int ldc)

13.60.1 Macro Definition Documentation

13.60.1.1 CBLAS_INT

```
#define CBLAS_INT int
```

13.60.1.2 CBLAS_ENUM_DEFINED_H

```
#define CBLAS_ENUM_DEFINED_H
```

13.60.1.3 CBLAS_EXTERNALS

```
#define CBLAS_EXTERNALS
```

13.60.1.4 blas_enum

```
#define blas_enum enum
```

13.60.2 Enumeration Type Documentation

13.60.2.1 CBLAS_ORDER

```
enum CBLAS\_ORDER
```

Enumerator

CblasRowMajor	
CblasColMajor	

13.60.2.2 CBLAS_TRANSPOSE

enum [CBLAS_TRANSPOSE](#)

Enumerator

CblasNoTrans	
CblasTrans	
CblasConjTrans	
AtlasConj	

13.60.2.3 CBLAS_UPLO

enum [CBLAS_UPLO](#)

Enumerator

CblasUpper	
CblasLower	

13.60.2.4 CBLAS_DIAG

enum [CBLAS_DIAG](#)

Enumerator

CblasNonUnit	
CblasUnit	

13.60.2.5 CBLAS_SIDE

enum [CBLAS_SIDE](#)

Enumerator

CblasLeft	
CblasRight	

13.60.3 Function Documentation

13.60.3.1 daxpy_()

```
void daxpy_ (
    const int * ,
    const double * ,
    const double * ,
    const int * ,
    double * ,
    const int * )
```

13.60.3.2 saxpy_()

```
void saxpy_ (
    const int * ,
```

```
const float * ,  
const float * ,  
const int * ,  
float * ,  
const int * )
```

13.60.3.3 ddot_()

```
double ddot_ (  
    const int * ,  
    const double * ,  
    const int * ,  
    const double * ,  
    const int * )
```

13.60.3.4 sdot_()

```
float sdot_ (  
    const int * ,  
    const float * ,  
    const int * ,  
    const float * ,  
    const int * )
```

13.60.3.5 dasum_()

```
double dasum_ (  
    const int * ,  
    const double * ,  
    const int * )
```

13.60.3.6 idamax_()

```
int idamax_ (  
    const int * ,  
    const double * ,  
    const int * )
```

13.60.3.7 dnrm2_()

```
double dnrm2_ (  
    const int * ,  
    const double * ,  
    const int * )
```

13.60.3.8 dgemv_()

```
void dgemv_ (  
    const char * ,  
    const int * ,  
    const int * ,  
    const double * ,  
    const double * ,  
    const int * ,  
    const double * ,  
    const int * ,  
    const double * ,  
    double * ,  
    const int * )
```

13.60.3.9 sgemv_()

```
void sgemv_ (
    const char * ,
    const int * ,
    const int * ,
    const float * ,
    const float * ,
    const int * ,
    const float * ,
    const int * ,
    const float * ,
    float * ,
    const int * )
```

13.60.3.10 dger_()

```
void dger_ (
    const int * ,
    const int * ,
    const double * ,
    const double * ,
    const int * ,
    const double * ,
    const int * ,
    double * ,
    const int * )
```

13.60.3.11 sger_()

```
void sger_ (
    const int * ,
    const int * ,
    const float * ,
    const float * ,
    const int * ,
    const float * ,
    const int * ,
    float * ,
    const int * )
```

13.60.3.12 dcopy_()

```
void dcopy_ (
    const int * ,
    const double * ,
    const int * ,
    double * ,
    const int * )
```

13.60.3.13 scopy_()

```
void scopy_ (
    const int * ,
    const float * ,
    const int * ,
    float * ,
    const int * )
```

13.60.3.14 dscal_()

```
void dscal_ (
    const int * ,
    const double * ,
    double * ,
    const int * )
```

13.60.3.15 sscal_()

```
void sscal_ (
    const int * ,
    const float * ,
    float * ,
    const int * )
```

13.60.3.16 dtrsm_()

```
void dtrsm_ (
    const char * ,
    const char * ,
    const char * ,
    const char * ,
    const int * ,
    const int * ,
    const double * ,
    const double * ,
    const int * ,
    double * ,
    const int * )
```

13.60.3.17 strsm_()

```
void strsm_ (
    const char * ,
    const char * ,
    const char * ,
    const char * ,
    const int * ,
    const int * ,
    const float * ,
    const float * ,
    const int * ,
    float * ,
    const int * )
```

13.60.3.18 dtrmm_()

```
void dtrmm_ (
    const char * ,
    const char * ,
    const char * ,
    const char * ,
    const int * ,
    const int * ,
    const double * ,
    const double * ,
    const int * ,
    double * ,
    const int * )
```

13.60.3.19 strmm_()

```
void strmm_ (
    const char * ,
    const char * ,
    const char * ,
    const char * ,
    const int * ,
    const int * ,
    const float * ,
    const float * ,
    const int * ,
    float * ,
    const int * )
```

13.60.3.20 sgemm_()

```
void sgemm_ (
    const char * ,
    const char * ,
    const int * ,
    const int * ,
    const int * ,
    const float * ,
    const float * ,
    const int * ,
    const float * ,
    const int * ,
    const float * ,
    float * ,
    const int * )
```

13.60.3.21 dgemm_()

```
void dgemm_ (
    const char * ,
    const char * ,
    const int * ,
    const int * ,
    const int * ,
    const double * ,
    const double * ,
    const int * ,
    const double * ,
    const int * ,
    const double * ,
    double * ,
    const int * )
```

13.60.3.22 cblas_dsyrk()

```
void cblas_dsyrk (
    const enum CBLAS_ORDER Order,
    const enum CBLAS_UPLO Uplo,
    const enum CBLAS_TRANSPOSE Trans,
    const int N,
    const int K,
    const double alpha,
    const double * A,
```

```

const int lda,
const double beta,
double * C,
const int ldc )

```

13.61 fflas-ffpack-config.h File Reference

Defaults for optimised values.

```

#include "fflas-ffpack/config.h"
#include "fflas-ffpack/fflas-ffpack-thresholds.h"
#include "fflas-ffpack/fflas-ffpack-default-thresholds.h"
#include "givaro/givconfig.h"

```

Macros

- #define [GCC_VERSION](#) (`__GNUC__ * 10000 + __GNUC_MINOR__ * 100 + __GNUC_PATCHLEVEL__`)

13.61.1 Detailed Description

Defaults for optimised values.

While `fflas-ffpack-optimize.h` is created by `configure` script, (either left blank or filled by optimiser), this file produces the defaults for the optimised values. If `fflas-ffpack-optimize.h` is not empty, then its values preceeds the defaults here.

13.61.2 Macro Definition Documentation

13.61.2.1 GCC_VERSION

```
#define GCC_VERSION ( __GNUC__ * 10000 + __GNUC_MINOR__ * 100 + __GNUC_PATCHLEVEL__ )
```

13.62 fflas-ffpack-default-thresholds.h File Reference

Macros

- #define [__FFLASFFPACK_WINOTHRESHOLD](#) 1000
- #define [__FFLASFFPACK_WINOTHRESHOLD_FLT](#) 2000
- #define [__FFLASFFPACK_WINOTHRESHOLD_BAL](#) 1000
- #define [__FFLASFFPACK_WINOTHRESHOLD_BAL_FLT](#) 2000
- #define [__FFLASFFPACK_PLUQ_THRESHOLD](#) 256
- #define [__FFLASFFPACK_CHARPOLY_LUKrylov_ArithProg_THRESHOLD](#) 1000
- #define [__FFLASFFPACK_CHARPOLY_Danilevskii_LUKrylov_THRESHOLD](#) 16
- #define [__FFLASFFPACK_ARITHPROG_THRESHOLD](#) 30
- #define [__FFLASFFPACK_FTRTRI_THRESHOLD](#) 32
- #define [__FFLASFFPACK_FSYTRF_THRESHOLD](#) 64
- #define [__FFLASFFPACK_FSYRK_THRESHOLD](#) 3000

13.62.1 Macro Definition Documentation

13.62.1.1 __FFLASFFPACK_WINOTHRESHOLD

```
#define __FFLASFFPACK_WINOTHRESHOLD 1000
```

13.62.1.2 __FFLASFFPACK_WINOTHRESHOLD_FLT

```
#define __FFLASFFPACK_WINOTHRESHOLD_FLT 2000
```

13.62.1.3 __FflasFfpack_WinOThreshold_BAL

```
#define __FflasFfpack_WinOThreshold_BAL 1000
```

13.62.1.4 __FflasFfpack_WinOThreshold_BAL_Flt

```
#define __FflasFfpack_WinOThreshold_BAL_Flt 2000
```

13.62.1.5 __FflasFfpack_Pluq_Threshold

```
#define __FflasFfpack_Pluq_Threshold 256
```

13.62.1.6 __FflasFfpack_Charpoly_LUKrylov_ArithProg_Threshold

```
#define __FflasFfpack_Charpoly_LUKrylov_ArithProg_Threshold 1000
```

13.62.1.7 __FflasFfpack_Charpoly_Danilevskii_LUKrylov_Threshold

```
#define __FflasFfpack_Charpoly_Danilevskii_LUKrylov_Threshold 16
```

13.62.1.8 __FflasFfpack_ArithProg_Threshold

```
#define __FflasFfpack_ArithProg_Threshold 30
```

13.62.1.9 __FflasFfpack_FtrTri_Threshold

```
#define __FflasFfpack_FtrTri_Threshold 32
```

13.62.1.10 __FflasFfpack_FsyTrf_Threshold

```
#define __FflasFfpack_FsyTrf_Threshold 64
```

13.62.1.11 __FflasFfpack_FsyRk_Threshold

```
#define __FflasFfpack_FsyRk_Threshold 3000
```

13.63 fflas-ffpack-thresholds.h File Reference**13.64 fflas-ffpack.doxy File Reference****13.65 fflas-ffpack.h File Reference**

Includes [FFLAS](#) and [FFPACK](#).

```
#include "fflas-ffpack/fflas-ffpack-config.h"
```

```
#include "fflas/fflas.h"
```

13.65.1 Detailed Description

Includes [FFLAS](#) and [FFPACK](#).

13.66 fflas.doxy File Reference**13.67 fflas.h File Reference**

Finite Field Linear Algebra Subroutines


```

#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/config.h"
#include "fflas-ffpack/config-blas.h"
#include <cmath>
#include <cstring>
#include <float.h>
#include <algorithm>
#include "fflas_enum.h"
#include "fflas-ffpack/utils/fflas_memory.h"
#include "fflas-ffpack/paladin/parallel.h"
#include "fflas_level1.inl"
#include "fflas_level2.inl"
#include "fflas_level3.inl"
#include "fflas-ffpack/checkers/checkers_fflas.h"
#include "fflas_freduce.h"
#include "fflas_fadd.h"
#include "fflas_fscal.h"
#include "fflas_fassign.h"
#include "fflas_fgemm.inl"
#include "fflas_pfgemm.inl"
#include "fflas_fgemv.inl"
#include "fflas-ffpack/paladin/pfgemv.inl"
#include "fflas_freivalds.inl"
#include "fflas_fger.inl"
#include "fflas_fsyrk.inl"
#include "fflas_fsyrk_strassen.inl"
#include "fflas_fsyr2k.inl"
#include "fflas_ftrsm.inl"
#include "fflas_pftsm.inl"
#include "fflas_ftrmm.inl"
#include "fflas_ftrsv.inl"
#include "fflas_faxpy.inl"
#include "fflas_fdot.inl"
#include "fflas-ffpack/field/rns.h"
#include "fflas_fscal_mp.inl"
#include "fflas_freduce_mp.inl"
#include "fflas-ffpack/fflas/fflas_fger_mp.inl"
#include "fflas_fgemm/fgemm_classical_mp.inl"
#include "fflas_ftrsm_mp.inl"
#include "fflas_fgemv_mp.inl"
#include "fflas-ffpack/field/rns.inl"
#include "fflas-ffpack/paladin/fflas_plevel1.h"
#include "fflas_sparse.h"
#include "fflas-ffpack/checkers/checkers_fflas.inl"

```

Macros

- `#define WINOTHRESHOLD __FFLASFFPACK_WINOTHRESHOLD`
- `#define DOUBLE_TO_FLOAT_CROSSOVER 800`

Thresholds determining which floating point representation to use, depending on the cardinality of the finite field.

13.67.1 Detailed Description

Finite Field Linear Algebra Subroutines

Author

Clément Pernet.

13.67.2 Macro Definition Documentation

13.67.2.1 WINOTHRESHOLD

```
#define WINOTHRESHOLD __FflasFFPACK_WINOTHRESHOLD
```

13.67.2.2 DOUBLE_TO_FLOAT_CROSSOVER

```
#define DOUBLE_TO_FLOAT_CROSSOVER 800
```

Thresholds determining which floating point representation to use, depending on the cardinality of the finite field. This is only used when the element representation is not a floating point type.

Bug to be benchmarked.

13.68 fflas_bounds.inl File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/utils/flimits.h"
#include <givaro/udl.h>
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
```

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::Protected](#)

Macros

- `#define` [__FflasFFPACK_fflas_bounds_INL](#)
- `#define` [FFLAS_INT_TYPE](#) `uint64_t`

Functions

- `template<class Field >`
`double computeFactorClassic (const Field &F)`
- `template<> double computeFactorClassic (const Givaro::ModularBalanced< double > &F)`
- `template<> double computeFactorClassic (const Givaro::ModularBalanced< float > &F)`
- `template<class Field >`
`size_t DotProdBoundClassic (const Field &F, const typename Field::Element &beta)`
- `Givaro::Integer InfNorm (const size_t M, const size_t N, const Givaro::Integer *A, const size_t lda)`
- `template<class Field >`
`size_t TRSMBound (const Field &)`
TRSMBound.
- `template<class Element >`
`size_t TRSMBound (const Givaro::Modular< Element > &F)`
Specialization for positive modular representation over float.
- `template<class Element >`
`size_t TRSMBound (const Givaro::ModularBalanced< Element > &F)`
Specialization for balanced modular representation over double.

13.68.1 Macro Definition Documentation

13.68.1.1 __FFLASFFPACK_fflas_bounds_INL

```
#define __FFLASFFPACK_fflas_bounds_INL
```

13.68.1.2 FFLAS_INT_TYPE

```
#define FFLAS_INT_TYPE uint64_t
```

13.69 fflas_enum.h File Reference

```
#include <algorithm>
```

Data Structures

- class [AreEqual< X, Y >](#)
- class [AreEqual< X, X >](#)

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::Protected](#)

Enumerations

- enum [FFLAS_ORDER](#) { [FflasRowMajor](#) = 101 , [FflasColMajor](#) = 102 }
Storage by row or col ?
- enum [FFLAS_TRANSPOSE](#) { [FflasNoTrans](#) = 111 , [FflasTrans](#) = 112 }
Is matrix transposed ?
- enum [FFLAS_UPLO](#) { [FflasUpper](#) = 121 , [FflasLower](#) = 122 , [FflasLeftTri](#) = 123 , [FflasRightTri](#) = 124 }
Is triangular matrix's shape upper ?
- enum [FFLAS_DIAG](#) { [FflasNonUnit](#) = 131 , [FflasUnit](#) = 132 }
Is the triangular matrix implicitly unit diagonal ?
- enum [FFLAS_SIDE](#) { [FflasLeft](#) = 141 , [FflasRight](#) = 142 }
On what side ?
- enum [FFLAS_BASE](#) { [FflasDouble](#) = 151 , [FflasFloat](#) = 152 , [FflasGeneric](#) = 153 }
FFLAS_BASE determines the type of the element representation for Matrix Mult kernel.

Functions

- template<class T >
const T & [min3](#) (const T &m, const T &n, const T &k)
- template<class T >
const T & [max3](#) (const T &m, const T &n, const T &k)
- template<class T >
const T & [min4](#) (const T &m, const T &n, const T &k, const T &l)
- template<class T >
const T & [max4](#) (const T &m, const T &n, const T &k, const T &l)

13.70 fflas_fadd.h File Reference

```
#include "fflas-ffpack/fflas/fflas_simd.h"
#include "fflas_fadd.inl"
```

Data Structures

- struct [support_simd_add< T >](#)

Namespaces

- namespace [FFLAS](#)

Functions

- template<class [Field](#) >
void [fadd](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t inca, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc)
- template<class [Field](#) >
void [faddin](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc)
- template<class [Field](#) >
void [fsub](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t inca, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc)
- template<class [Field](#) >
void [fsubin](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc)
- template<class [Field](#) >
void [fadd](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t inca, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc)
- template<class [Field](#) >
void [pfadd](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc, const size_t numths)
- template<class [Field](#) >
void [pfsub](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc, const size_t numths)
- template<class [Field](#) >
void [pfaddin](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc, size_t numths)
- template<class [Field](#) >
void [pfsubin](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc, size_t numths)
- template<class [Field](#) >
void [fadd](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc)
fadd : matrix addition.
- template<class [Field](#) >
void [fsub](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc)
fsub : matrix subtraction.
- template<class [Field](#) >
void [faddin](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc)
faddin
- template<class [Field](#) >
void [faddin](#) (const [Field](#) &F, const [FFLAS_UPLO](#) uplo, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc)
fadding for symmetric matrices

- template<class [Field](#) >
void [fsubin](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc)
$$fsubin\ C = C - B$$
- template<class [Field](#) >
void [fadd](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc)
fadd : matrix addition with scaling.

13.71 fflas_fadd.inl File Reference

```
#include "fflas-ffpack/fflas/fflas_simd.h"
```

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::vectorised](#)
- namespace [FFLAS::details](#)

Macros

- #define [__FFLASFFPACK_fadd_INL](#)

Functions

- template<class SimdT , class Element , bool positive>
std::enable_if< [is_simd](#)< SimdT >::value, void >::type [VEC_ADD](#) (SimdT &C, SimdT &A, SimdT &B, SimdT &Q, SimdT &T, SimdT &P, SimdT &NEGP, SimdT &MIN, SimdT &MAX)
- template<bool positive, class Element , class T1 , class T2 >
std::enable_if< [FFLAS::support_simd_add](#)< Element >::value, void >::type [addp](#) (Element *T, const Element *TA, const Element *TB, size_t n, Element p, T1 min_, T2 max_)
- template<class SimdT , class Element , bool positive>
std::enable_if< [is_simd](#)< SimdT >::value, void >::type [VEC_SUB](#) (SimdT &C, SimdT &A, SimdT &B, SimdT &Q, SimdT &T, SimdT &P, SimdT &NEGP, SimdT &MIN, SimdT &MAX)
- template<bool positive, class Element , class T1 , class T2 >
std::enable_if< [FFLAS::support_simd_add](#)< Element >::value, void >::type [subp](#) (Element *T, const Element *TA, const Element *TB, const size_t n, const Element p, const T1 min_, const T2 max_)
- template<class Element >
std::enable_if< [FFLAS::support_simd_add](#)< Element >::value, void >::type [add](#) (Element *T, const Element *TA, const Element *TB, size_t n)
- template<class Element >
std::enable_if< [FFLAS::support_simd_add](#)< Element >::value, void >::type [sub](#) (Element *T, const Element *TA, const Element *TB, size_t n)
- template<class [Field](#) , bool ADD>
std::enable_if< [FFLAS::support_simd_add](#)< typename [Field::Element](#) >::value, void >::type [fadd](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t inca, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc, [FieldCategories::ModularTag](#))
- template<class [Field](#) , bool ADD>
std::enable_if<![FFLAS::support_simd_add](#)< typename [Field::Element](#) >::value, void >::type [fadd](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t inca, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc, [FieldCategories::ModularTag](#))

- `template<class Field, bool ADD>`
`void fadd (const Field &F, const size_t N, typename Field::ConstElement_ptr A, const size_t inca, type-`
`name Field::ConstElement_ptr B, const size_t incb, typename Field::Element_ptr C, const size_t incc,`
`FieldCategories::GenericTag)`
- `template<class Field, bool ADD>`
`std::enable_if<!FFLAS::support_simd_add< typenameField::Element >::value, void >::type fadd`
`(const Field &F, const size_t N, typename Field::ConstElement_ptr A, const size_t inca, typename`
`Field::ConstElement_ptr B, const size_t incb, typename Field::Element_ptr C, const size_t incc,`
`FieldCategories::UnparametricTag)`
- `template<class Field, bool ADD>`
`std::enable_if< FFLAS::support_simd_add< typenameField::Element >::value, void >::type fadd`
`(const Field &F, const size_t N, typename Field::ConstElement_ptr A, const size_t inca, typename`
`Field::ConstElement_ptr B, const size_t incb, typename Field::Element_ptr C, const size_t incc,`
`FieldCategories::UnparametricTag)`

13.71.1 Macro Definition Documentation

13.71.1.1 __FFLASFFPACK_fadd_INL

```
#define __FFLASFFPACK_fadd_INL
```

13.72 fflas_fassign.h File Reference

```
#include "fflas_fassign.inl"
```

13.73 fflas_fassign.inl File Reference

```
#include <string.h>
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include <givaro/zring.h>
#include "fflas-ffpack/utils/debug.h"
```

Namespaces

- namespace [FFLAS](#)

Macros

- `#define __FFLASFFPACK_fassign_INL`

Functions

- `template<class Field >`
`void fassign (const Field &F, const size_t N, typename Field::ConstElement_ptr Y, const size_t incY, typename`
`Field::Element_ptr X, const size_t incX)`

$$fassign : x \leftarrow y.$$
- `template<> void fassign (const Givaro::Modular< float > &F, const size_t N, const float *Y, const size_t incY,`
`float *X, const size_t incX)`
- `template<> void fassign (const Givaro::ModularBalanced< float > &F, const size_t N, const float *Y, const`
`size_t incY, float *X, const size_t incX)`
- `template<> void fassign (const Givaro::ZRing< float > &F, const size_t N, const float *Y, const size_t incY,`
`float *X, const size_t incX)`
- `template<> void fassign (const Givaro::Modular< double > &F, const size_t N, const double *Y, const size_t incY,`
`double *X, const size_t incX)`

- template<> void [fassign](#) (const [Givaro::ModularBalanced](#)< double > &F, const size_t N, const double *Y, const size_t incY, double *X, const size_t incX)
- template<> void [fassign](#) (const [Givaro::ZRing](#)< double > &F, const size_t N, const double *Y, const size_t incY, double *X, const size_t incX)
- template<class [Field](#) >
void [fassign](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) A, const size_t lda)

fassign : A ← B.

13.73.1 Macro Definition Documentation

13.73.1.1 __FFLASFFPACK_fassign_INL

```
#define __FFLASFFPACK_fassign_INL
```

13.74 fflas_faxpy.inl File Reference

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::vectorised](#)
- namespace [FFLAS::vectorised::unswitch](#)
- namespace [FFLAS::details](#)

Macros

- #define [__FFLASFFPACK_faxpy_INL](#)

Functions

- template<class [Field](#) >
std::enable_if<![FFLAS::support_simd_mod](#)< typename [Field::Element](#) >::value &&[FFLAS::support_fast_mod](#)< typename [Field::Element](#) >::value, void >::type [axypy](#) (const [Field](#) &F, const typename [Field::Element](#) a, typename [Field::ConstElement_ptr](#) X, typename [Field::Element_ptr](#) Y, const size_t n, [HelperMod](#)< [Field](#) > &H)
- template<class [Field](#) >
std::enable_if< [FFLAS::support_fast_mod](#)< typename [Field::Element](#) >::value, void >::type [axypy](#) (const [Field](#) &F, const typename [Field::Element](#) a, typename [Field::ConstElement_ptr](#) X, typename [Field::Element_ptr](#) Y, const size_t n, const size_t incX, const size_t incY, [HelperMod](#)< [Field](#) > &H)
- template<class [Field](#) >
std::enable_if< [FFLAS::support_fast_mod](#)< typename [Field::Element](#) >::value, void >::type [axypy](#) (const [Field](#) &F, const typename [Field::Element](#) a, typename [Field::ConstElement_ptr](#) X, typename [Field::Element_ptr](#) Y, const size_t n)
- template<class [Field](#) >
std::enable_if< [FFLAS::support_fast_mod](#)< typename [Field::Element](#) >::value, void >::type [axypy](#) (const [Field](#) &F, const typename [Field::Element](#) a, typename [Field::ConstElement_ptr](#) X, typename [Field::Element_ptr](#) Y, const size_t n, const size_t incX, const size_t incY)
- template<class [Field](#) >
std::enable_if< [FFLAS::support_fast_mod](#)< typename [Field::Element](#) >::value, void >::type [faxpy](#) (const [Field](#) &F, const size_t N, const typename [Field::Element](#) a, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::Element_ptr](#) Y, const size_t incY, [FieldCategories::ModularTag](#))
- template<class [Field](#) , class FC >
void [faxpy](#) (const [Field](#) &F, const size_t N, const typename [Field::Element](#) a, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::Element_ptr](#) Y, const size_t incY, FC)
- template<class [Field](#) >
void [faxpy](#) (const [Field](#) &F, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::Element_ptr](#) Y, const size_t incY)

- $\text{faxpy} : y \leftarrow \alpha \cdot x + y.$
- `template<> void faxpy (const Givaro::DoubleDomain &, const size_t N, const Givaro::DoubleDomain::Element a, Givaro::DoubleDomain::ConstElement_ptr x, const size_t incx, Givaro::DoubleDomain::Element_ptr y, const size_t incy)`
 - `template<> void faxpy (const Givaro::FloatDomain &, const size_t N, const Givaro::FloatDomain::Element a, Givaro::FloatDomain::ConstElement_ptr x, const size_t incx, Givaro::FloatDomain::Element_ptr y, const size_t incy)`
 - `template<class Field >`
`void faxpy (const Field &F, const size_t m, const size_t n, const typename Field::Element alpha, typename Field::ConstElement_ptr X, const size_t ldx, typename Field::Element_ptr Y, const size_t ldy)`
 $\text{faxpy} : y \leftarrow \alpha \cdot x + y.$

13.74.1 Macro Definition Documentation

13.74.1.1 __FFLASFFPACK_faxpy_INL

```
#define __FFLASFFPACK_faxpy_INL
```

13.75 fflas_fdot.inl File Reference

```
#include "fflas-ffpack/fflas/fflas_helpers.inl"
```

Namespaces

- namespace `FFLAS`

Macros

- `#define __FFLASFFPACK_fdot_INL`

Functions

- `template<class Field >`
`Field::Element fdot (const Field &F, const size_t N, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, ModeCategories::DefaultTag &MT)`
- `template<class Field >`
`Field::Element fdot (const Field &F, const size_t N, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, ModeCategories::DelayedTag &MT)`
- `template<> Givaro::DoubleDomain::Element fdot (const Givaro::DoubleDomain &, const size_t N, Givaro::DoubleDomain::ConstElement_ptr x, const size_t incx, Givaro::DoubleDomain::ConstElement_ptr y, const size_t incy, ModeCategories::DefaultTag &MT)`
- `template<> Givaro::FloatDomain::Element fdot (const Givaro::FloatDomain &, const size_t N, Givaro::FloatDomain::ConstElement_ptr x, const size_t incx, Givaro::FloatDomain::ConstElement_ptr y, const size_t incy, ModeCategories::DefaultTag &MT)`
- `template<class Field, class T >`
`Field::Element fdot (const Field &F, const size_t N, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, ModeCategories::ConvertTo< T > &MT)`
- `template<class Field >`
`Field::Element fdot (const Field &F, const size_t N, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, ModeCategories::DefaultBoundedTag &dbt)`
- `template<class Field >`
`Field::Element fdot (const Field &F, const size_t N, typename Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t incy, const ParSeqHelper::Sequential seq)`
- `template<class Field >`
`Field::Element fdot (const Field &F, const size_t N, typename Field::ConstElement_ptr X, const size_t incX, typename Field::ConstElement_ptr Y, const size_t incY)`
 $\text{fdot} : \text{dot product } x^T y.$

13.75.1 Macro Definition Documentation

13.75.1.1 __FFLASFFPACK_fdot_INL

```
#define __FFLASFFPACK_fdot_INL
```

13.76 fflas_fgemm.inl File Reference

```
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/debug.h"
#include "fflas_fgemm/fgemm_classical.inl"
#include "fflas_fgemm/fgemm_winograd.inl"
```

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::Protected](#)

Macros

- #define [__FFLASFFPACK_fgemm_INL](#)

Functions

- template<class NewField, class [Field](#), class FieldMode >
[Field::Element_ptr fgemm_convert](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), FieldMode > &H)
- template<class [Field](#), class Element, class AlgoT, class ParSeqTrait >
bool [NeedPreAddReduction](#) (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, [MMHelper](#)< [Field](#), AlgoT, [ModeCategories::LazyTag](#), ParSeqTrait > &WH)
- template<class [Field](#), class Element, class AlgoT, class ModeT, class ParSeqTrait >
bool [NeedPreAddReduction](#) (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, [MMHelper](#)< [Field](#), AlgoT, ModeT, ParSeqTrait > &WH)
- template<class [Field](#), class Element, class AlgoT, class ParSeqTrait >
bool [NeedPreSubReduction](#) (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, [MMHelper](#)< [Field](#), AlgoT, [ModeCategories::LazyTag](#), ParSeqTrait > &WH)
- template<class [Field](#), class Element, class AlgoT, class ModeT, class ParSeqTrait >
bool [NeedPreSubReduction](#) (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, [MMHelper](#)< [Field](#), AlgoT, ModeT, ParSeqTrait > &WH)
- template<class [Field](#), class Element, class AlgoT, class ParSeqTrait >
bool [NeedDoublePreAddReduction](#) (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, Element beta, [MMHelper](#)< [Field](#), AlgoT, [ModeCategories::LazyTag](#), ParSeqTrait > &WH)
- template<class [Field](#), class Element, class AlgoT, class ModeT, class ParSeqTrait >
bool [NeedDoublePreAddReduction](#) (Element &Outmin, Element &Outmax, Element &Op1min, Element &Op1max, Element &Op2min, Element &Op2max, Element beta, [MMHelper](#)< [Field](#), AlgoT, ModeT, ParSeqTrait > &WH)
- template<class [Field](#), class AlgoT, class ParSeqTrait >
void [ScalAndReduce](#) (const [Field](#) &F, const size_t N, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) X, const size_t incX, const [MMHelper](#)< [Field](#), AlgoT, [ModeCategories::LazyTag](#), ParSeqTrait > &H)

- `template<class Field , class AlgoT , class ParSeqTrait >`
`void ScalAndReduce (const Field &F, const size_t M, const size_t N, const typename Field::Element alpha,`
`typename Field::Element_ptr A, const size_t lda, const MMHelper< Field, AlgoT, ModeCategories::LazyTag,`
`ParSeqTrait > &H)`
- `template<class Field >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE`
`tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, typename`
`Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb,`
`const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper<`
`Field, MMHelperAlgo::Winograd, ModeCategories::ConvertTo< ElementCategories::MachineFloatTag >,`
`ParSeqHelper::Sequential > &H)`
- `template<typename Field >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE`
`tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, type-`
`name Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t`
`ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const`
`ParSeqHelper::Sequential seq)`
- `template<typename Field , class Cut , class Param >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE`
`tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, type-`
`name Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t`
`ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const`
`ParSeqHelper::Parallel< Cut, Param > par)`
- `template<typename Field >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE`
`tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, typename`
`Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const`
`typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc)`

*fgemm: Field **GE**neral **M**atrix **M**ultiply.*
- `template<typename Field , class ModeT , class ParSeq >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE`
`tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, typename`
`Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb,`
`const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field,`
`MMHelperAlgo::Auto, ModeT, ParSeq > &H)`
- `template<class Field >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE`
`tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, typename`
`Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb,`
`const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field,`
`MMHelperAlgo::Winograd, ModeCategories::DelayedTag, ParSeqHelper::Sequential > &H)`
- `template<class Field >`
`Field::Element_ptr fsquare (const Field &F, const FFLAS_TRANSPOSE ta, const size_t n, const typename`
`Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, const typename Field::Element`
`beta, typename Field::Element_ptr C, const size_t ldc)`

fsquare: Squares a matrix.
- `template<class Field >`
`Field::Element_ptr fsquareCommon (const Field &F, const FFLAS_TRANSPOSE ta, const size_t n, const`
`typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, const typename`
`Field::Element beta, typename Field::Element_ptr C, const size_t ldc)`
- `template<> double * fsquare (const Givaro::ModularBalanced< double > &F, const FFLAS_TRANSPOSE`
`ta, const size_t n, const double alpha, const double *A, const size_t lda, const double beta, double *C, const`
`size_t ldc)`
- `template<> float * fsquare (const Givaro::ModularBalanced< float > &F, const FFLAS_TRANSPOSE ta,`
`const size_t n, const float alpha, const float *A, const size_t lda, const float beta, float *C, const size_t ldc)`
- `template<> double * fsquare (const Givaro::Modular< double > &F, const FFLAS_TRANSPOSE ta, const`
`size_t n, const double alpha, const double *A, const size_t lda, const double beta, double *C, const size_t`
`ldc)`

- `template<> float * fsquare (const Givaro::Modular< float > &F, const FFLAS_TRANSPOSE ta, const size_t n, const float alpha, const float *A, const size_t lda, const float beta, float *C, const size_t ldc)`

13.76.1 Macro Definition Documentation

13.76.1.1 __FFLASFFPACK_fgemm_INL

```
#define __FFLASFFPACK_fgemm_INL
```

13.77 fgemm_classical.inl File Reference

13.78 fgemm_classical_mp.inl File Reference

matrix multiplication with multiprecision input (either over Z or over Z/pZ)

```
#include <givaro/modular-integer.h>
#include <givaro/zring.h>
#include "fflas-ffpack/field/rns-double.h"
#include "fflas-ffpack/field/rns-integer.h"
#include "fflas-ffpack/field/rns-integer-mod.h"
#include "fflas-ffpack/field/field-traits.h"
#include "fflas-ffpack/fflas/fflas_helpers.inl"
#include "fflas-ffpack/fflas/fflas_bounds.inl"
```

Data Structures

- struct `MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeqTrait >`
- struct `MMHelper< FFPACK::RNSInteger< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >`
- struct `MMHelper< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >`

Namespaces

- namespace `FFLAS`

Macros

- `#define __FFPACK_fgemm_classical_INL`

Functions

- `template<typename RNS, typename ParSeqTrait > FFPACK::RNSInteger< RNS >::Element_ptr fgemm (const FFPACK::RNSInteger< RNS > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename FFPACK::RNSInteger< RNS >::Element alpha, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Ad, const size_t lda, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Bd, const size_t ldb, const typename FFPACK::RNSInteger< RNS >::Element beta, typename FFPACK::RNSInteger< RNS >::Element_ptr Cd, const size_t ldc, MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag, ParSeqHelper::Compose< ParSeqHelper::Sequential, ParSeqTrait > > &H)`
- `template<typename RNS > FFPACK::RNSInteger< RNS >::Element_ptr fgemm (const FFPACK::RNSInteger< RNS > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename FFPACK::RNSInteger< RNS >::Element alpha, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Ad, const size_t lda, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Bd, const size_t ldb, const typename FFPACK::RNSInteger< RNS >::Element beta, typename FFPACK::RNSInteger< RNS >::Element_ptr Cd, const size_t ldc, MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag, ParSeqHelper::Sequential > &H)`

- `template<typename RNS , typename ParSeqTrait >`
`FFPACK::RNSInteger< RNS >::Element_ptr fgemm (const FFPACK::RNSInteger< RNS > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename FFPACK::RNSInteger< RNS >::Element alpha, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Ad, const size_t lda, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Bd, const size_t ldb, const typename FFPACK::RNSInteger< RNS >::Element beta, typename FFPACK::RNSInteger< RNS >::Element_ptr Cd, const size_t ldc, MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag, ParSeqHelper::Compose< ParSeqHelper::Parallel< CuttingStrategy::RNSModulus, StrategyParameter::Threads >, ParSeqTrait > > &H)`
- `template<typename RNS , typename Cut , typename Param >`
`FFPACK::RNSInteger< RNS >::Element_ptr fgemm (const FFPACK::RNSInteger< RNS > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename FFPACK::RNSInteger< RNS >::Element alpha, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Ad, const size_t lda, typename FFPACK::RNSInteger< RNS >::ConstElement_ptr Bd, const size_t ldb, const typename FFPACK::RNSInteger< RNS >::Element beta, typename FFPACK::RNSInteger< RNS >::Element_ptr Cd, const size_t ldc, MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Classic, ModeCategories::DefaultTag, ParSeqHelper::Parallel< Cut, Param > > &H)`
- `template<class ParSeq >`
`Givaro::Integer * fgemm (const Givaro::ZRing< Givaro::Integer > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const Givaro::Integer alpha, const Givaro::Integer *A, const size_t lda, const Givaro::Integer *B, const size_t ldb, Givaro::Integer beta, Givaro::Integer *C, const size_t ldc, MMHelper< Givaro::ZRing< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeq > &H)`
- `template<typename RNS , class ModeT >`
`RNS::Element_ptr fgemm (const FFPACK::RNSInteger< RNS > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename RNS::Element alpha, typename RNS::ConstElement_ptr Ad, const size_t lda, typename RNS::ConstElement_ptr Bd, const size_t ldb, const typename RNS::Element beta, typename RNS::Element_ptr Cd, const size_t ldc, MMHelper< FFPACK::RNSInteger< RNS >, MMHelperAlgo::Winograd, ModeT, ParSeqHelper::Sequential > &H)`
- `template<typename RNS >`
`RNS::Element_ptr fgemm (const FFPACK::RNSIntegerMod< RNS > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename RNS::Element alpha, typename RNS::ConstElement_ptr Ad, const size_t lda, typename RNS::ConstElement_ptr Bd, const size_t ldb, const typename RNS::Element beta, typename RNS::Element_ptr Cd, const size_t ldc, MMHelper< FFPACK::RNSIntegerMod< RNS >, MMHelperAlgo::Winograd > &H)`
- `Givaro::Integer * fgemm (const Givaro::Modular< Givaro::Integer > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const Givaro::Integer alpha, const Givaro::Integer *A, const size_t lda, const Givaro::Integer *B, const size_t ldb, const Givaro::Integer beta, Givaro::Integer *C, const size_t ldc, MMHelper< Givaro::Modular< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo< ElementCategories::RNSElementTag > > &H)`
- `template<class ParSeq >`
`Givaro::Integer * fgemm (const Givaro::Modular< Givaro::Integer > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const Givaro::Integer alpha, const Givaro::Integer *A, const size_t lda, const Givaro::Integer *B, const size_t ldb, const Givaro::Integer beta, Givaro::Integer *C, const size_t ldc, MMHelper< Givaro::Modular< Givaro::Integer >, MMHelperAlgo::Auto, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeq > &H)`
- `template<size_t K1, size_t K2, class ParSeq >`
`Reclnt::ruint< K1 > * fgemm (const Givaro::Modular< Reclnt::ruint< K1 >, Reclnt::ruint< K2 > > &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const Reclnt::ruint< K1 > alpha, const Reclnt::ruint< K1 > *A, const size_t lda, const Reclnt::ruint< K1 > *B, const size_t ldb, Reclnt::ruint< K1 > beta, Reclnt::ruint< K1 > *C, const size_t ldc, MMHelper< Givaro::Modular< Reclnt::ruint< K1 >, Reclnt::ruint< K2 > >, MMHelperAlgo::Classic, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeq > &H)`

13.78.1 Detailed Description

matrix multiplication with multiprecision input (either over $\mathbb{Z}$ or over $\mathbb{Z}/p\mathbb{Z}$)

13.78.2 Macro Definition Documentation

13.78.2.1 __FFPACK_fgemm_classical_INL

```
#define __FFPACK_fgemm_classical_INL
```

13.79 fgemm_winograd.inl File Reference

```
#include <stdint.h>
#include <givaro/modular.h>
#include <givaro/zring.h>
#include "fgemm_classical.inl"
#include "schedule_winograd.inl"
#include "schedule_winograd_acc.inl"
#include "schedule_winograd_acc_ip.inl"
#include "schedule_winograd_ip.inl"
#include "fflas-ffpack/fflas-ffpack-config.h"
```

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::Protected](#)

Macros

- #define [__FFLASFFPACK_fflas_fflas_fgemm_winograd_INL](#)
- #define [NEWWINO](#)

Functions

- template<class [Field](#) >
int [WinogradThreshold](#) (const [Field](#) &F)
Computes the number of recursive levels to perform.
- template<> int [WinogradThreshold](#) (const Givaro::Modular< float > &F)
- template<> int [WinogradThreshold](#) (const [Givaro::ModularBalanced](#)< double > &F)
- template<> int [WinogradThreshold](#) (const [Givaro::ModularBalanced](#)< float > &F)
- template<class [Field](#) >
int [WinogradSteps](#) (const [Field](#) &F, const size_t &m)
Computes the number of recursive levels to perform.
- template<class [Field](#) , class [FieldMode](#) >
void [DynamicPeeling](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const size_t mr, const size_t nr, const size_t kr, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldMode](#) > &H, const typename [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldMode](#) >::DelayedField::Element Cmin, const typename [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldMode](#) >::DelayedField::Element Cmax)
- template<class [Field](#) , class [FieldMode](#) >
void [DynamicPeeling2](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const size_t mr, const size_t nr, const size_t kr, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldMode](#) > &H, const typename [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldMode](#) >::DelayedField::Element Cmin, const typename [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldMode](#) >::DelayedField::Element Cmax)

- `template<class Field , class FieldMode >`
`void WinogradCalc (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, FieldMode > &H)`
- `template<class Field , class ModeT >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, ModeT > &H)`
- `template<class Field , class ModeT , class Cut , class Param >`
`Field::Element_ptr fgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::WinogradPar, ModeT, ParSeqHelper::Parallel< Cut, Param > > &H)`

13.79.1 Macro Definition Documentation

13.79.1.1 __FFLASFFPACK_fflas_fflas_fgemm_winograd_INL

```
#define __FFLASFFPACK_fflas_fflas_fgemm_winograd_INL
```

13.79.1.2 NEWWINO

```
#define NEWWINO
```

13.80 matmul.doxy File Reference

13.81 schedule_bini.inl File Reference

Bini implementation.

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::BLAS3](#)

Macros

- `#define __FFLASFFPACK_fgemm_bini_INL`

Functions

- `template<class Field >`
`void Bini (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, const typename Field::Element_ptr A, const size_t lda, const typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const size_t kmax, const size_t w, const FFLAS_BASE base, const size_t rec_level)`

13.81.1 Detailed Description

Bini implementation.

13.81.2 Macro Definition Documentation

13.81.2.1 __FFLASFFPACK_fgemv_bini_INL

```
#define __FFLASFFPACK_fgemv_bini_INL
```

13.82 schedule_winograd.inl File Reference

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::BLAS3](#)

Macros

- #define [__FFLASFFPACK_fgemv_winograd_INL](#)

Functions

- template<class [Field](#) , class [FieldTrait](#) , class [Strat](#) , class [Param](#) >
[Field::Element_ptr](#) [WinoPar](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t mr, const size_t nr, const size_t kr, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::WinogradPar](#), [FieldTrait](#), [ParSeqHelper::Parallel](#)< [Strat](#), [Param](#) > > &WH)
- template<class [Field](#) , class [FieldTrait](#) >
void [Winograd](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t mr, const size_t nr, const size_t kr, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldTrait](#) > &WH)

13.82.1 Macro Definition Documentation

13.82.1.1 __FFLASFFPACK_fgemv_winograd_INL

```
#define __FFLASFFPACK_fgemv_winograd_INL
```

13.83 schedule_winograd_acc.inl File Reference

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::BLAS3](#)

Macros

- #define [__FFLASFFPACK_fgemv_winograd_acc_INL](#)

Functions

- template<class [Field](#) , class [FieldTrait](#) >
void [WinogradAcc_3_23](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t mr, const size_t nr, const size_t kr, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldTrait](#) > &WH)

- `template<class Field , class FieldTrait >`
`void WinogradAcc_3_21 (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > &WH)`
- `template<class Field , class FieldTrait >`
`void WinogradAcc_2_24 (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, const typename Field::Element_ptr A, const size_t lda, const typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > &WH)`
- `template<class Field , class FieldTrait >`
`void WinogradAcc_2_27 (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, const typename Field::Element_ptr A, const size_t lda, const typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > &WH)`

13.83.1 Macro Definition Documentation

13.83.1.1 __FFLASFFPACK_fgemm_winograd_acc_INL

```
#define __FFLASFFPACK_fgemm_winograd_acc_INL
```

13.84 schedule_winograd_acc_ip.inl File Reference

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::BLAS3](#)

Macros

- `#define __FFLASFFPACK_fgemm_winograd_acc_ip_INL`

Functions

- `template<class Field , class FieldTrait >`
`void WinogradAcc_LR (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > &WH)`
- `template<class Field , class FieldTrait >`
`void WinogradAcc_R_S (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, const typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > &WH)`
- `template<class Field , class FieldTrait >`
`void WinogradAcc_L_S (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t mr, const size_t nr, const size_t kr, const typename Field::Element alpha, typename Field::Element_ptr A, const size_t lda, const typename Field::Element_ptr B, const size_t ldb, const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, const MMHelper< Field, MMHelperAlgo::Winograd, FieldTrait > &WH)`

13.84.1 Macro Definition Documentation

13.84.1.1 __FFLASFFPACK_fgemm_winograd_acc_ip_INL

```
#define __FFLASFFPACK_fgemm_winograd_acc_ip_INL
```

13.85 schedule_winograd_ip.inl File Reference

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::BLAS3](#)

Macros

- #define [__FFLASFFPACK_fgemm_winograd_ip_INL](#)

Functions

- template<class [Field](#) , class FieldTrait >
void [Winograd_LR_S](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t mr, const size_t nr, const size_t kr, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, const [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), Field↵Trait > &WH)
- template<class [Field](#) , class FieldTrait >
void [Winograd_L_S](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t mr, const size_t nr, const size_t kr, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t lda, const typename [Field::Element_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, const [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), FieldTrait > &WH)
- template<class [Field](#) , class FieldTrait >
void [Winograd_R_S](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t mr, const size_t nr, const size_t kr, const typename [Field::Element](#) alpha, const typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb, const type-
name [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, const [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), FieldTrait > &WH)

13.85.1 Macro Definition Documentation

13.85.1.1 __FFLASFFPACK_fgemm_winograd_ip_INL

```
#define __FFLASFFPACK_fgemm_winograd_ip_INL
```

13.86 fflas_fgemv.inl File Reference

```
#include <givaro/zring.h>
```

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::Protected](#)

Macros

- #define [__FFLASFFPACK_fgemv_INL](#)

Functions

- `template<typename FloatElement, class Field>`
`Field::Element_ptr fgemv_convert` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `size_t` M, const `size_t` N, const `typename Field::Element` alpha, `typename Field::ConstElement_ptr` A, const `size_t` lda, `typename Field::ConstElement_ptr` X, const `size_t` incX, const `typename Field::Element` beta, `typename Field::Element_ptr` Y, const `size_t` incY)
- `template<class Field>`
`Field::Element_ptr fgemv` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `size_t` M, const `size_t` N, const `typename Field::Element` alpha, `typename Field::ConstElement_ptr` A, const `size_t` lda, `typename Field::ConstElement_ptr` X, const `size_t` incX, const `typename Field::Element` beta, `typename Field::Element_ptr` Y, const `size_t` incY, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `ModeCategories::ConvertTo`< `ElementCategories::MachineFloatTag` > > &H)
- `template<class Field>`
`Field::Element_ptr fgemv` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `size_t` M, const `size_t` N, const `typename Field::Element` alpha, `typename Field::ConstElement_ptr` A, const `size_t` lda, `typename Field::ConstElement_ptr` X, const `size_t` incX, const `typename Field::Element` beta, `typename Field::Element_ptr` Y, const `size_t` incY, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `ModeCategories::DelayedTag` > &H)
- `template<class Field>`
`Field::Element_ptr fgemv` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `size_t` M, const `size_t` N, const `typename Field::Element` alpha, `typename Field::ConstElement_ptr` A, const `size_t` lda, `typename Field::ConstElement_ptr` X, const `size_t` incX, const `typename Field::Element` beta, `typename Field::Element_ptr` Y, const `size_t` incY, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `ModeCategories::DefaultTag` > &H)
- `template<class Field>`
`Field::Element_ptr fgemv` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `size_t` M, const `size_t` N, const `typename Field::Element` alpha, `typename Field::ConstElement_ptr` A, const `size_t` lda, `typename Field::ConstElement_ptr` X, const `size_t` incX, const `typename Field::Element` beta, `typename Field::Element_ptr` Y, const `size_t` incY, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `ModeCategories::LazyTag` > &H)
- `template<class Field>`
`Field::Element_ptr fgemv` (const `Field` &F, const `FFLAS_TRANSPOSE` TransA, const `size_t` M, const `size_t` N, const `typename Field::Element` alpha, `typename Field::ConstElement_ptr` A, const `size_t` lda, `typename Field::ConstElement_ptr` X, const `size_t` incX, const `typename Field::Element` beta, `typename Field::Element_ptr` Y, const `size_t` incY)
finite prime Field GEneral Matrix Vector multiplication.
- `Givaro::ZRing< int64_t >::Element_ptr fgemv` (const `Givaro::ZRing< int64_t >` &F, const `FFLAS_TRANSPOSE` ta, const `size_t` M, const `size_t` N, const `int64_t` alpha, const `int64_t` *A, const `size_t` lda, const `int64_t` *X, const `size_t` incX, const `int64_t` beta, `int64_t` *Y, const `size_t` incY, `MMHelper`< `Givaro::ZRing< int64_t >`, `MMHelperAlgo::Classic`, `ModeCategories::DefaultTag` > &H)
- `Givaro::DoubleDomain::Element_ptr fgemv` (const `Givaro::DoubleDomain` &F, const `FFLAS_TRANSPOSE` ta, const `size_t` M, const `size_t` N, const `Givaro::DoubleDomain::Element` alpha, const `Givaro::DoubleDomain::ConstElement_ptr` A, const `size_t` lda, const `Givaro::DoubleDomain::ConstElement_ptr` X, const `size_t` incX, const `Givaro::DoubleDomain::Element` beta, `Givaro::DoubleDomain::Element_ptr` Y, const `size_t` incY, `MMHelper`< `Givaro::DoubleDomain`, `MMHelperAlgo::Classic`, `ModeCategories::DefaultTag` > &H)
- `template<class Field>`
`Field::Element_ptr fgemv` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `size_t` M, const `size_t` N, const `typename Field::Element` alpha, const `typename Field::ConstElement_ptr` A, const `size_t` lda, const `typename Field::ConstElement_ptr` X, const `size_t` incX, const `typename Field::Element` beta, `typename Field::Element_ptr` Y, const `size_t` incY, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `ModeCategories::DefaultBoundedTag` > &H)
- `Givaro::FloatDomain::Element_ptr fgemv` (const `Givaro::FloatDomain` &F, const `FFLAS_TRANSPOSE` ta, const `size_t` M, const `size_t` N, const `Givaro::FloatDomain::Element` alpha, const `Givaro::FloatDomain::ConstElement_ptr` A, const `size_t` lda, const `Givaro::FloatDomain::ConstElement_ptr` X, const `size_t` incX, const `Givaro::FloatDomain::Element` beta, `Givaro::FloatDomain::Element_ptr` Y, const `size_t` incY, `MMHelper`< `Givaro::FloatDomain`, `MMHelperAlgo::Classic`, `ModeCategories::DefaultTag` > &H)

- `template<class Field , class Cut , class Param >`
`Field::Element_ptr fgmv (const Field &F, const FFLAS_TRANSPOSE ta, const size_t m, const size_t n,`
`const typename Field::Element alpha, const typename Field::ConstElement_ptr A, const size_t lda, const`
`typename Field::ConstElement_ptr X, const size_t incX, const typename Field::Element beta, typename`
`Field::Element_ptr Y, const size_t incY, ParSeqHelper::Parallel< Cut, Param > &parH)`
- `template<class Field >`
`Field::Element_ptr fgmv (const Field &F, const FFLAS_TRANSPOSE ta, const size_t m, const size_t n,`
`const typename Field::Element alpha, const typename Field::ConstElement_ptr A, const size_t lda, const`
`typename Field::ConstElement_ptr X, const size_t incX, const typename Field::Element beta, typename`
`Field::Element_ptr Y, const size_t incY, ParSeqHelper::Sequential &seqH)`

13.86.1 Macro Definition Documentation

13.86.1.1 __FFLASFFPACK_fgmv_INL

```
#define __FFLASFFPACK_fgmv_INL
```

13.87 fflas_fgmv_mp.inl File Reference

```
#include "fflas-ffpack/field/rns-integer-mod.h"
```

Namespaces

- namespace `FFLAS`

Macros

- #define `__FFLASFFPACK_fgmv_mp_INL`

Functions

- `FFPACK::rns_double::Element_ptr fgmv (const FFPACK::RNSInteger< FFPACK::rns_double > &F, const`
`FFLAS_TRANSPOSE ta, const size_t M, const size_t N, const FFPACK::rns_double::Element alpha,`
`FFPACK::rns_double::ConstElement_ptr A, const size_t lda, FFPACK::rns_double::ConstElement_ptr`
`X, const size_t incX, const FFPACK::rns_double::Element beta, FFPACK::rns_double::Element_ptr Y,`
`const size_t incY, MMHelper< FFPACK::RNSInteger< FFPACK::rns_double >, MMHelperAlgo::Classic,`
`ModeCategories::DefaultTag > &H)`
- `FFPACK::rns_double::Element_ptr fgmv (const FFPACK::RNSIntegerMod< FFPACK::rns_double > &F,`
`const FFLAS_TRANSPOSE ta, const size_t M, const size_t N, const FFPACK::rns_double::Element alpha,`
`FFPACK::rns_double::ConstElement_ptr A, const size_t lda, FFPACK::rns_double::ConstElement_ptr X,`
`const size_t incX, const FFPACK::rns_double::Element beta, FFPACK::rns_double::Element_ptr Y, const`
`size_t incY, MMHelper< FFPACK::RNSIntegerMod< FFPACK::rns_double >, MMHelperAlgo::Classic,`
`ModeCategories::DefaultTag > &H)`
- `Givaro::Integer * fgmv (const Givaro::ZRing< Givaro::Integer > &F, const FFLAS_TRANSPOSE`
`ta, const size_t m, const size_t n, const Givaro::Integer alpha, Givaro::Integer *A, const size_t`
`lda, Givaro::Integer *X, const size_t ldx, Givaro::Integer beta, Givaro::Integer *Y, const size_t`
`ldy, MMHelper< Givaro::ZRing< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo<`
`ElementCategories::RNSElementTag > > &H)`
- `Givaro::Integer * fgmv (const Givaro::Modular< Givaro::Integer > &F, const FFLAS_TRANSPOSE`
`ta, const size_t m, const size_t n, const Givaro::Integer alpha, Givaro::Integer *A, const size_t`
`lda, Givaro::Integer *X, const size_t ldx, Givaro::Integer beta, Givaro::Integer *Y, const size_t`
`ldy, MMHelper< Givaro::Modular< Givaro::Integer >, MMHelperAlgo::Classic, ModeCategories::ConvertTo<`
`ElementCategories::RNSElementTag > > &H)`
- `template<size_t K1, size_t K2, class ParSeq >`
`Reclnt::ruint< K1 > * fgmv (const Givaro::Modular< Reclnt::ruint< K1 >, Reclnt::ruint< K2 > >`
`&F, const FFLAS_TRANSPOSE ta, const size_t m, const size_t n, const Reclnt::ruint< K1 > al-`
`pha, const Reclnt::ruint< K1 > *A, const size_t lda, const Reclnt::ruint< K1 > *X, const size_t incx,`

```
Reclnt::ruint< K1 > beta, Reclnt::ruint< K1 > *Y, const size_t incy, MMHelper< Givaro::Modular<
Reclnt::ruint< K1 >, Reclnt::ruint< K2 > >, MMHelperAlgo::Classic, ModeCategories::ConvertTo<
ElementCategories::RNSElementTag >, ParSeq > &H)
```

13.87.1 Macro Definition Documentation

13.87.1.1 __FFLASFFPACK_fgmv_mp_INL

```
#define __FFLASFFPACK_fgmv_mp_INL
```

13.88 fflas_fger.inl File Reference

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::Protected](#)

Macros

- #define [__FFLASFFPACK_fger_INL](#)

Functions

- template<class [Field](#) >
void [fger](#) (const [Field](#) &F, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) x, const size_t incx, typename [Field::ConstElement_ptr](#) y, const size_t incy, typename [Field::Element_ptr](#) A, const size_t lda)
fger: rank one update of a general matrix
- template<class [FloatElement](#) , class [Field](#) >
void [fger_convert](#) (const [Field](#) &F, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) x, const size_t incx, typename [Field::ConstElement_ptr](#) y, const size_t incy, typename [Field::Element_ptr](#) A, const size_t lda)
- template<class [Field](#) >
void [fger](#) (const [Field](#) &F, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) x, const size_t incx, typename [Field::ConstElement_ptr](#) y, const size_t incy, typename [Field::Element_ptr](#) A, const size_t lda, [MMHelper](#)< [Field](#), [MMHelperAlgo::Classic](#), [ModeCategories::ConvertTo](#)< [ElementCategories::MachineFloatTag](#) > > &H)
- template<class [Field](#) , class [AnyTag](#) >
void [fger](#) (const [Field](#) &F, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) x, const size_t incx, typename [Field::ConstElement_ptr](#) y, const size_t incy, typename [Field::Element_ptr](#) A, const size_t lda, [MMHelper](#)< [Field](#), [MMHelperAlgo::Classic](#), [AnyTag](#) > &H)
- void [fger](#) (const [Givaro::DoubleDomain](#) &F, const size_t M, const size_t N, const [Givaro::DoubleDomain::Element](#) alpha, const [Givaro::DoubleDomain::ConstElement_ptr](#) x, const size_t incx, const [Givaro::DoubleDomain::ConstElement_ptr](#) y, const size_t incy, [Givaro::DoubleDomain::Element_ptr](#) A, const size_t lda, [MMHelper](#)< [Givaro::DoubleDomain](#), [MMHelperAlgo::Classic](#), [ModeCategories::DefaultTag](#) > &H)
- template<class [Field](#) >
void [fger](#) (const [Field](#) &F, const size_t M, const size_t N, const typename [Field::Element](#) alpha, const typename [Field::ConstElement_ptr](#) x, const size_t incx, const typename [Field::ConstElement_ptr](#) y, const size_t incy, typename [Field::Element_ptr](#) A, const size_t lda, [MMHelper](#)< [Field](#), [MMHelperAlgo::Classic](#), [ModeCategories::DefaultBoundedTag](#) > &H)
- void [fger](#) (const [Givaro::FloatDomain](#) &F, const size_t M, const size_t N, const [Givaro::FloatDomain::Element](#) alpha, const [Givaro::FloatDomain::ConstElement_ptr](#) x, const size_t incx, const [Givaro::FloatDomain::ConstElement_ptr](#) y, const size_t incy, [Givaro::FloatDomain::Element_ptr](#) A, const size_t lda, [MMHelper](#)< [Givaro::FloatDomain](#), [MMHelperAlgo::Classic](#), [ModeCategories::DefaultTag](#) > &H)
- template<class [Field](#) >
void [fger](#) (const [Field](#) &F, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) x, const size_t incx, typename [Field::ConstElement_ptr](#) y, const size_t incy, typename [Field::Element_ptr](#) A, const size_t lda, [MMHelper](#)< [Field](#), [MMHelperAlgo::Classic](#), [ModeCategories::LazyTag](#) > &H)

- `template<class Field >`
`void fger (const Field &F, const size_t M, const size_t N, const typename Field::Element alpha, type-`
`name Field::ConstElement_ptr x, const size_t incx, typename Field::ConstElement_ptr y, const size_t`
`incy, typename Field::Element_ptr A, const size_t lda, MMHelper< Field, MMHelperAlgo::Classic,`
`ModeCategories::DelayedTag > &H)`

13.88.1 Macro Definition Documentation

13.88.1.1 __FFLASFFPACK_fger_INL

```
#define __FFLASFFPACK_fger_INL
```

13.89 fflas_fger_mp.inl File Reference

```
#include <givaro/modular-integer.h>
#include <givaro/zring.h>
#include "fflas-ffpack/fflas/fflas_helpers.inl"
#include "fflas-ffpack/fflas/fflas_fgemm/fgemm_classical_mp.inl"
#include "fflas-ffpack/field/rns-integer.h"
#include "fflas-ffpack/field/rns-integer-mod.h"
```

Namespaces

- namespace [FFLAS](#)

Macros

- `#define __FFPACK_fger_mp_INL`

Functions

- `void fger (const Givaro::Modular< Givaro::Integer > &F, const size_t M, const size_t N, const typename`
`Givaro::Integer alpha, typename Givaro::Integer *x, const size_t incx, typename Givaro::Integer *y, const`
`size_t incy, typename Givaro::Integer *A, const size_t lda, MMHelper< Givaro::Modular< Givaro::Integer >,`
`MMHelperAlgo::Classic, ModeCategories::ConvertTo< ElementCategories::RNSElementTag > > &H)`
- `template<typename RNS >`
`void fger (const FFPACK::RNSInteger< RNS > &F, const size_t M, const size_t N, const typename`
`FFPACK::RNSInteger< RNS >::Element alpha, typename FFPACK::RNSInteger< RNS >::Element_ptr x,`
`const size_t incx, typename FFPACK::RNSInteger< RNS >::Element_ptr y, const size_t incy, typename`
`FFPACK::RNSInteger< RNS >::Element_ptr A, const size_t lda, MMHelper< FFPACK::RNSInteger< RNS`
`>, MMHelperAlgo::Classic, ModeCategories::DefaultTag > &H)`
- `template<typename RNS >`
`void fger (const FFPACK::RNSIntegerMod< RNS > &F, const size_t M, const size_t N, const type-`
`name FFPACK::RNSIntegerMod< RNS >::Element alpha, typename FFPACK::RNSIntegerMod< RNS`
`>::Element_ptr x, const size_t incx, typename FFPACK::RNSIntegerMod< RNS >::Element_ptr y, const`
`size_t incy, typename FFPACK::RNSIntegerMod< RNS >::Element_ptr A, const size_t lda, MMHelper<`
`FFPACK::RNSIntegerMod< RNS >, MMHelperAlgo::Classic > &H)`

13.89.1 Macro Definition Documentation

13.89.1.1 __FFPACK_fger_mp_INL

```
#define __FFPACK_fger_mp_INL
```

13.90 fflas_freduce.h File Reference

```
#include "fflas-ffpack/fflas/fflas_simd.h"
#include "fflas-ffpack/field/field-traits.h"
#include "fflas-ffpack/utils/cast.h"
#include "fflas-ffpack/fflas/fflas_freduce.inl"
```

Data Structures

- struct [support_simd_mod< T >](#)
- struct [support_fast_mod< T >](#)
- struct [support_fast_mod< float >](#)
- struct [support_fast_mod< double >](#)
- struct [support_fast_mod< int64_t >](#)

Namespaces

- namespace [FFLAS](#)

Functions

- template<class [Field](#) >
void [freduce](#) (const [Field](#) &F, const size_t n, typename [Field::ConstElement_ptr](#) Y, const size_t incY, typename [Field::Element_ptr](#) X, const size_t incX)
$$\text{freduce } x \leftarrow y \bmod F.$$
- template<class [Field](#) >
void [freduce](#) (const [Field](#) &F, const size_t n, typename [Field::Element_ptr](#) X, const size_t incX)
$$\text{freduce } x \leftarrow x \bmod F.$$
- template<class [Field](#) >
void [freduce_constoverride](#) (const [Field](#) &F, const size_t m, typename [Field::ConstElement_ptr](#) A, const size_t incX)
- template<class [Field](#) , class ConstOtherElement_ptr >
void [finit](#) (const [Field](#) &F, const size_t n, ConstOtherElement_ptr Y, const size_t incY, typename [Field::Element_ptr](#) X, const size_t incX)
- template<class [Field](#) >
void [finit](#) (const [Field](#) &F, const size_t n, typename [Field::Element_ptr](#) X, const size_t incX)
$$\text{finit initializes } X \text{ in } F^{\$}.$$
- template<class [Field](#) >
void [freduce](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
$$\text{freduce } A \leftarrow A \bmod F.$$
- template<class [Field](#) >
void [freduce](#) (const [Field](#) &F, const [FFLAS_UPLO](#) uplo, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda)
$$\text{freduce for square symmetric matrices}$$
- template<class [Field](#) >
void [pfreduce](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda, const size_t numths)
- template<class [Field](#) >
void [freduce](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) A, const size_t lda)
$$\text{freduce } A \leftarrow B \bmod F.$$
- template<class [Field](#) >
void [freduce_constoverride](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::ConstElement_ptr](#) A, const size_t lda)

- `template<class Field, class OtherElement_ptr >`
`void finit (const Field &F, const size_t m, const size_t n, const OtherElement_ptr B, const size_t ldb, typename Field::Element_ptr A, const size_t lda)`

$$\text{finit } A \leftarrow B \bmod F.$$
- `template<class Field >`
`void finit (const Field &F, const size_t m, const size_t n, typename Field::Element_ptr A, const size_t lda)`

13.91 fflas_freduce.inl File Reference

```
#include <givaro/udl.h>
#include "fflas-ffpack/fflas/fflas_fassign.h"
```

Data Structures

- struct `HelperMod< Field, ElementCategories::MachineIntTag >`
- struct `HelperMod< Field, FFLAS::ElementCategories::MachineFloatTag >`
- struct `HelperMod< Field, FFLAS::ElementCategories::ArbitraryPrecIntTag >`
- struct `HelperMod< Field, FFLAS::ElementCategories::FixedPrecIntTag >`

Namespaces

- namespace `FFLAS`
- namespace `FFLAS::vectorised`
- namespace `FFLAS::vectorised::unswitch`
- namespace `FFLAS::details`

Macros

- `#define __FFLASFFPACK_fflas_freduce_INL`
- `#define FFLASFFPACK_COPY_REDUCE 32 /* TODO TO BENCHMARK LATER */`

Functions

- `template<class T >`
`std::enable_if<!std::is_integral< T >::value, T >::type reduce (T A, T B)`
- `template<class T >`
`std::enable_if< std::is_integral< T >::value, T >::type reduce (T A, T B)`
- `template<> Givaro::Integer reduce (Givaro::Integer A, Givaro::Integer B)`
- `float reduce (float A, float B, float invB, float min, float max)`
- `double reduce (double A, double B, double invB, double min, double max)`
- `int64_t reduce (int64_t A, int64_t p, double invp, double min, double max, int64_t pow50rem)`
- `template<class Field >`
`Field::Element reduce (typename Field::Element A, HelperMod< Field, ElementCategories::MachineIntTag > &H)`
- `template<class Field >`
`Field::Element reduce (typename Field::Element A, HelperMod< Field, ElementCategories::MachineFloatTag > &H)`
- `template<class Field >`
`Field::Element reduce (typename Field::Element A, HelperMod< Field, ElementCategories::ArbitraryPrecIntTag > &H)`
- `template<class Field >`
`std::enable_if< !FFLAS::support_simd_mod< typename Field::Element >::value && FFLAS::support_fast_mod< typename Field::Element >::value, void >::type modp (const Field &F, typename Field::ConstElement_ptr U, const size_t &n, typename Field::Element_ptr T, HelperMod< Field > &H)`

- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type modp`
`(const Field &F, typename Field::ConstElement_ptr U, const size_t &n, const size_t &incX, typename`
`Field::Element_ptr T, HelperMod< Field > &H)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type modp` (const
`Field &F, typename Field::ConstElement_ptr U, const size_t &n, typename Field::Element_ptr T)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type modp`
`(const Field &F, typename Field::ConstElement_ptr U, const size_t &n, const size_t &incX, typename`
`Field::Element_ptr T)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type freduce` (const
`Field &F, const size_t m, typename Field::Element_ptr A, const size_t incX, FieldCategories::ModularTag)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type freduce`
`(const Field &F, const size_t m, typename Field::ConstElement_ptr B, const size_t incY, typename`
`Field::Element_ptr A, const size_t incX, FieldCategories::ModularTag)`
- `template<class Field, class FC >`
`void freduce` (const `Field &F`, const `size_t m`, typename `Field::Element_ptr A`, const `size_t incX`, `FC`)
- `template<class Field, class FC >`
`void freduce` (const `Field &F`, const `size_t m`, typename `Field::ConstElement_ptr B`, const `size_t incY`, type-
name `Field::Element_ptr A`, const `size_t incX`, `FC`)

13.91.1 Macro Definition Documentation

13.91.1.1 __FFLASFFPACK_fflas_freduces_INL

```
#define __FFLASFFPACK_fflas_freduces_INL
```

13.91.1.2 FFLASFFPACK_COPY_REDUCE

```
#define FFLASFFPACK_COPY_REDUCE 32 /* TODO TO BENCHMARK LATER */
```

13.92 fflas_freduces_mp.inl File Reference

```
#include "fflas-ffpack/field/rns-integer-mod.h"
```

Namespaces

- namespace `FFLAS`

Macros

- `#define __FFLASFFPACK_fflas_freduces_mp_INL`

Functions

- `template<> void freduce` (const `FFPACK::RNSIntegerMod< FFPACK::rns_double > &F`, const `size_t n`,
`FFPACK::RNSIntegerMod< FFPACK::rns_double >::Element_ptr A`, `size_t inc`)
- `template<> void freduce` (const `FFPACK::RNSIntegerMod< FFPACK::rns_double > &F`, const `size_t m`,
const `size_t n`, `FFPACK::rns_double::Element_ptr A`, `size_t lda`)

13.92.1 Macro Definition Documentation

13.92.1.1 __FFLASFFPACK_fflas_freduces_mp_INL

```
#define __FFLASFFPACK_fflas_freduces_mp_INL
```


13.93 fflas_freivalds.inl File Reference

Namespaces

- namespace [FFLAS](#)

Macros

- `#define __FFLASFFPACK_freivalds_INL`

Functions

- `template<class Field >`
`bool freivalds (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb, const size_t m,`
`const size_t n, const size_t k, const typename Field::Element alpha, typename Field::ConstElement_ptr A,`
`const size_t lda, typename Field::ConstElement_ptr B, const size_t ldb, typename Field::ConstElement_ptr`
`C, const size_t ldc)`

freivalds: Freivalds GEneral Matrix Multiply Random Check.

13.93.1 Macro Definition Documentation

13.93.1.1 __FFLASFFPACK_freivalds_INL

```
#define __FFLASFFPACK_freivalds_INL
```

13.94 fflas_fscal.h File Reference

```
#include "fflas_fscal.inl"
```

13.95 fflas_fscal.inl File Reference

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::vectorised](#)
- namespace [FFLAS::vectorised::unswitch](#)
- namespace [FFLAS::details](#)

Macros

- `#define __FFLASFFPACK_fscal_INL`

Functions

- `template<class Field >`
`std::enable_if<!FFLAS::support_simd_mod< typenameField::Element >::value &&FFLAS::support_fast_mod<`
`typenameField::Element >::value, void >::type scalp (const Field &F, typename Field::Element_ptr T, const`
`typename Field::Element alpha, typename Field::ConstElement_ptr U, const size_t n, HelperMod< Field >`
`&H)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp`
`(const Field &F, typename Field::Element_ptr T, const typename Field::Element alpha, typename`
`Field::ConstElement_ptr U, const size_t n, const size_t &incX, HelperMod< Field > &H)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp`
`(const Field &F, typename Field::Element_ptr T, const typename Field::Element alpha, typename`
`Field::ConstElement_ptr U, const size_t n, const size_t &incX, const size_t &incY, HelperMod< Field >`
`&H)`

- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp`
`(const Field &F, typename Field::Element_ptr T, const typename Field::Element alpha, typename`
`Field::ConstElement_ptr U, const size_t n)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp`
`(const Field &F, typename Field::Element_ptr T, const typename Field::Element alpha, typename`
`Field::ConstElement_ptr U, const size_t n, const size_t &incX)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type scalp`
`(const Field &F, typename Field::Element_ptr T, const typename Field::Element alpha, typename`
`Field::ConstElement_ptr U, const size_t n, const size_t &incX, const size_t &incY)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type fscaln`
`(const Field &F, const size_t N, const typename Field::Element a, typename Field::Element_ptr X, const size_t incX,`
`FieldCategories::ModularTag)`
- `template<class Field >`
`std::enable_if< FFLAS::support_fast_mod< typenameField::Element >::value, void >::type fscal`
`(const Field &F, const size_t N, const typename Field::Element a, typename Field::ConstElement_ptr X, const size_t incX,`
`typename Field::Element_ptr Y, const size_t incY, FieldCategories::ModularTag)`
- `template<class Field, class FC >`
`void fscaln`
`(const Field &F, const size_t n, const typename Field::Element a, typename Field::Element_ptr X,`
`const size_t incX, FC)`
- `template<class Field, class FC >`
`void fscal`
`(const Field &F, const size_t N, const typename Field::Element a, typename Field::ConstElement_ptr`
`X, const size_t incX, typename Field::Element_ptr Y, const size_t incY, FC)`
- `template<class Field >`
`void fscaln`
`(const Field &F, const size_t n, const typename Field::Element alpha, typename Field::Element_ptr`
`X, const size_t incX)`

$$fscaln\ x \leftarrow \alpha \cdot x.$$
- `template<class Field >`
`void fscal`
`(const Field &F, const size_t n, const typename Field::Element alpha, typename Field::ConstElement_ptr`
`X, const size_t incX, typename Field::Element_ptr Y, const size_t incY)`

$$fscal\ y \leftarrow \alpha \cdot x.$$
- `template<> void fscal`
`(const Givaro::DoubleDomain &, const size_t N, const Givaro::DoubleDomain::Element a, Givaro::DoubleDomain::ConstElement_ptr x, const size_t incx, Givaro::DoubleDomain::Element_ptr y, const size_t incy)`
- `template<> void fscal`
`(const Givaro::FloatDomain &, const size_t N, const Givaro::FloatDomain::Element a, Givaro::FloatDomain::ConstElement_ptr x, const size_t incx, Givaro::FloatDomain::Element_ptr y, const size_t incy)`
- `template<> void fscaln`
`(const Givaro::DoubleDomain &, const size_t N, const Givaro::DoubleDomain::Element a, Givaro::DoubleDomain::Element_ptr y, const size_t incy)`
- `template<> void fscaln`
`(const Givaro::FloatDomain &, const size_t N, const Givaro::FloatDomain::Element a, Givaro::FloatDomain::Element_ptr y, const size_t incy)`
- `template<class Field >`
`void fscaln`
`(const Field &F, const size_t m, const size_t n, const typename Field::Element alpha, typename`
`Field::Element_ptr A, const size_t lda)`

$$fscaln\ A \leftarrow a \cdot A.$$
- `template<class Field >`
`void fscal`
`(const Field &F, const size_t m, const size_t n, const typename Field::Element alpha, typename`
`Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr B, const size_t ldb)`

$$fscal\ B \leftarrow a \cdot A.$$

13.95.1 Macro Definition Documentation

13.95.1.1 __FFLASFFPACK_fscal_INL

```
#define __FFLASFFPACK_fscal_INL
```

13.96 fflas_fscal_mp.inl File Reference

```
#include "fflas-ffpack/field/rns-integer.h"
#include "fflas_fscal.h"
#include "fflas_fgemm.inl"
#include "fflas-ffpack/fflas/fflas_freduce_mp.inl"
```

Namespaces

- namespace [FFLAS](#)

Macros

- #define [__FFLASFFPACK_fscal_mp_INL](#)

Functions

- template<> void [fscal](#) (const [FFPACK::RNSInteger](#)< [FFPACK::rns_double](#) > &F, const size_t n, const [FFPACK::rns_double::Element](#) alpha, [FFPACK::rns_double::Element_ptr](#) A, const size_t inc)
- template<> void [fscal](#) (const [FFPACK::RNSInteger](#)< [FFPACK::rns_double](#) > &F, const size_t n, const [FFPACK::rns_double::Element](#) alpha, [FFPACK::rns_double::ConstElement_ptr](#) A, const size_t Ainc, [FFPACK::rns_double::Element_ptr](#) B, const size_t Binc)
- template<> void [fscal](#) (const [FFPACK::RNSInteger](#)< [FFPACK::rns_double](#) > &F, const size_t m, const size_t n, const [FFPACK::rns_double::Element](#) alpha, [FFPACK::rns_double::Element_ptr](#) A, const size_t lda)
- template<> void [fscal](#) (const [FFPACK::RNSInteger](#)< [FFPACK::rns_double](#) > &F, const size_t m, const size_t n, const [FFPACK::rns_double::Element](#) alpha, [FFPACK::rns_double::ConstElement_ptr](#) A, const size_t lda, [FFPACK::rns_double::Element_ptr](#) B, const size_t ldb)
- template<> void [fscal](#) (const [FFPACK::RNSIntegerMod](#)< [FFPACK::rns_double](#) > &F, const size_t n, const typename [FFPACK::RNSIntegerMod](#)< [FFPACK::rns_double](#) >::Element alpha, typename [FFPACK::RNSIntegerMod](#)< [FFPACK::rns_double](#) >::Element_ptr A, const size_t inc)
- template<> void [fscal](#) (const [FFPACK::RNSIntegerMod](#)< [FFPACK::rns_double](#) > &F, const size_t n, const [FFPACK::rns_double::Element](#) alpha, [FFPACK::rns_double::ConstElement_ptr](#) A, const size_t Ainc, [FFPACK::rns_double::Element_ptr](#) B, const size_t Binc)
- template<> void [fscal](#) (const [FFPACK::RNSIntegerMod](#)< [FFPACK::rns_double](#) > &F, const size_t m, const size_t n, const [FFPACK::rns_double::Element](#) alpha, [FFPACK::rns_double::Element_ptr](#) A, const size_t lda)
- template<> void [fscal](#) (const [FFPACK::RNSIntegerMod](#)< [FFPACK::rns_double](#) > &F, const size_t m, const size_t n, const [FFPACK::rns_double::Element](#) alpha, [FFPACK::rns_double::ConstElement_ptr](#) A, const size_t lda, [FFPACK::rns_double::Element_ptr](#) B, const size_t ldb)

13.96.1 Macro Definition Documentation

13.96.1.1 __FFLASFFPACK_fscal_mp_INL

```
#define __FFLASFFPACK_fscal_mp_INL
```

13.97 fflas_fsyr2k.inl File Reference

```
#include <fflas-ffpack/utils/fflas_io.h>
```

Namespaces

- namespace [FFLAS](#)

Macros

- #define [__FFLASFFPACK_fflas_fsyr2k_INL](#)

Functions

- `template<class Field >`
`Field::Element_ptr fsyr2k` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` B, const `size_t` ldb, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc)
fsyr2k: Symmetric Rank 2K update

13.97.1 Macro Definition Documentation

13.97.1.1 __FFLASFFPACK_fflas_fsyr2k_INL

```
#define __FFLASFFPACK_fflas_fsyr2k_INL
```

13.98 fflas_fsyrk.inl File Reference

Namespaces

- namespace `FFLAS`
- namespace `FFLAS::Protected`

Macros

- `#define __FFLASFFPACK_fflas_fsyrk_INL`

Functions

- `template<class NewField , class Field , class FieldMode >`
`Field::Element_ptr fsyrk_convert` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `FieldMode` > &H)
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc)
fsyrk: Symmetric Rank K update
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `ParSeqHelper::Sequential` seq)
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `ModeCategories::DefaultTag` > &H)
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `ModeCategories::ConvertTo`< `ElementCategories::MachineFloatTag` >, `ParSeqHelper::Sequential` > &H)
- `template<class Field , class AlgoT , class ParSeqTrait >`
`void ScalAndReduce` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `size_t` N, const typename `Field::Element` alpha, typename `Field::Element_ptr` A, const `size_t` lda, const `MMHelper`< `Field`, `AlgoT`, `ModeCategories::LazyTag`, `ParSeqTrait` > &H)

- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `ModeCategories::DelayedTag` > &H)
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `ModeCategories::LazyTag` > &H)
- `template<class Field , typename Mode >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Field`, `MMHelperAlgo::DivideAndConquer`, `Mode` > &H)
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Field`, `MMHelperAlgo::Classic`, `ModeCategories::DefaultBoundedTag` > &H)
- `Givaro::FloatDomain::Element_ptr fsyrk` (const `Givaro::FloatDomain` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const `Givaro::FloatDomain::Element` alpha, `Givaro::FloatDomain::ConstElement_ptr` A, const `size_t` lda, const `Givaro::FloatDomain::Element` beta, `Givaro::FloatDomain::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Givaro::FloatDomain`, `MMHelperAlgo::Classic`, `ModeCategories::DefaultTag` > &H)
- `Givaro::DoubleDomain::Element_ptr fsyrk` (const `Givaro::DoubleDomain` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const `Givaro::DoubleDomain::Element` alpha, `Givaro::DoubleDomain::ConstElement_ptr` A, const `size_t` lda, const `Givaro::DoubleDomain::Element` beta, `Givaro::DoubleDomain::Element_ptr` C, const `size_t` ldc, `MMHelper`< `Givaro::DoubleDomain`, `MMHelperAlgo::Classic`, `ModeCategories::DefaultTag` > &H)
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, typename `Field::Element_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` D, const `size_t` incD, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `size_t` threshold=`__FFLASFFPACK_FSYRK_THRESHOLD`)
fsyrk: Symmetric Rank K update with diagonal scaling
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::Element_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` D, const `size_t` incD, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `ParSeqHelper::Sequential` seq, const `size_t` threshold)
- `template<class Field , class Cut , class Param >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::Element_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` D, const `size_t` incD, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `ParSeqHelper::Parallel`< `Cut`, `Param` > par, const `size_t` threshold)
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, typename `Field::Element_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` D, const `size_t` incD, const `std::vector< bool >` &twoBlock, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `size_t` threshold=`__FFLASFFPACK_FSYRK_THRESHOLD`)
fsyrk: Symmetric Rank K update with diagonal scaling

13.98.1 Macro Definition Documentation

13.98.1.1 __FFLASFFPACK_fflas_fsyrr_INL

```
#define __FFLASFFPACK_fflas_fsyrr_INL
```

13.99 fflas_fsyrr_strassen.inl File Reference

```
#include <givaro/givintsqrootmod.h>
```

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::Protected](#)

Macros

- #define [__FFLASFFPACK_fflas_fsyrr_strassen_INL](#)

Functions

- template<class [Field](#) , class [Element](#) , class [AlgoT](#) , class [ParSeqTrait](#) >
bool [NeedPreScalReduction](#) ([Element](#) &Outmin, [Element](#) &Outmax, [Element](#) &Op1min, [Element](#) &Op1max, const [Element](#) &x, [MMHelper](#)< [Field](#), [AlgoT](#), [ModeCategories::LazyTag](#), [ParSeqTrait](#) > &WH)
- template<class [Field](#) , class [Element](#) , class [AlgoT](#) , class [ModeT](#) , class [ParSeqTrait](#) >
bool [NeedPreScalReduction](#) ([Element](#) &Outmin, [Element](#) &Outmax, [Element](#) &Op1min, [Element](#) &Op1max, const [Element](#) &x, [MMHelper](#)< [Field](#), [AlgoT](#), [ModeT](#), [ParSeqTrait](#) > &WH)
- template<class [Field](#) , class [Element](#) , class [AlgoT](#) , class [ParSeqTrait](#) >
bool [NeedPreApxyReduction](#) ([Element](#) &Outmin, [Element](#) &Outmax, [Element](#) &Op1min, [Element](#) &Op1max, [Element](#) &Op2min, [Element](#) &Op2max, const [Element](#) &x, [MMHelper](#)< [Field](#), [AlgoT](#), [ModeCategories::LazyTag](#), [ParSeqTrait](#) > &WH)
- template<class [Field](#) , class [Element](#) , class [AlgoT](#) , class [ModeT](#) , class [ParSeqTrait](#) >
bool [NeedPreApxyReduction](#) ([Element](#) &Outmin, [Element](#) &Outmax, [Element](#) &Op1min, [Element](#) &Op1max, [Element](#) &Op2min, [Element](#) &Op2max, const [Element](#) &x, [MMHelper](#)< [Field](#), [AlgoT](#), [ModeT](#), [ParSeqTrait](#) > &WH)
- template<class [Field](#) , class [FieldTrait](#) >
void [computeS1S2](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) trans, const size_t N, const size_t K, const typename [Field::Element](#) x, const typename [Field::Element](#) y, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) S, const size_t lds, typename [Field::Element_ptr](#) T, const size_t ldt, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldTrait](#) > &WH)
- template<class [Field](#) >
[Field::Element_ptr](#) [fsyrr](#) (const [Field](#) &F, const [FFLAS_UPLO](#) UpLo, const [FFLAS_TRANSPOSE](#) trans, const size_t N, const size_t K, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [ModeCategories::DelayedTag](#), [ParSeqHelper::Sequential](#) > &H)
- template<class [Field](#) , class [Mode](#) >
[Field::Element_ptr](#) [fsyrr](#) (const [Field](#) &F, const [FFLAS_UPLO](#) UpLo, const [FFLAS_TRANSPOSE](#) trans, const size_t N, const size_t K, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [Mode](#) > &H)
- template<class [Field](#) , class [FieldTrait](#) >
[Field::Element_ptr](#) [fsyrr_strassen](#) (const [Field](#) &F, const [FFLAS_UPLO](#) uplo, const [FFLAS_TRANSPOSE](#) trans, const size_t N, const size_t K, const typename [Field::Element](#) y1, const typename [Field::Element](#) y2, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t lda, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [FieldTrait](#) > &WH)

13.99.1 Macro Definition Documentation

13.99.1.1 __FFLASFFPACK_fflas_fsyrrk_strassen_INL

```
#define __FFLASFFPACK_fflas_fsyrrk_strassen_INL
```

13.100 fflas_ftrmm.inl File Reference

Namespaces

- namespace [FFLAS](#)

Macros

- #define [__FFLASFFPACK_ftrmm_INL](#)

Functions

- template<class [Field](#) >
void [ftrmm](#) (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb)
*ftrmm: **TR**angular **M**atrix **M**ultiply.*
- template<class [Field](#) >
void [ftrmm](#) (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc)
*ftrmm: **TR**angular **M**atrix **M**ultiply with 3 operands Computes $C \leftarrow \alpha \text{op}(A)B + \text{beta}C$ or $C \leftarrow \alpha \text{Bop}(A) + \text{beta}C$.*

13.100.1 Macro Definition Documentation

13.100.1.1 __FFLASFFPACK_ftrmm_INL

```
#define __FFLASFFPACK_ftrmm_INL
```

13.101 fflas_ftrsm.inl File Reference

Namespaces

- namespace [FFLAS](#)

Macros

- #define [__FFLASFFPACK_ftrsm_INL](#)

Functions

- template<class [Field](#) >
void [ftrsm](#) (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb)
- template<class [Field](#) >
void [ftrsm](#) (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb, const [ParSeqHelper::Sequential](#) &PSH)

- `template<class Field, class Cut, class Param >`
`void ftrsm (const Field &F, const FFLAS_SIDE Side, const FFLAS_UPLO Uplo, const FFLAS_TRANSPOSE`
`TransA, const FFLAS_DIAG Diag, const size_t M, const size_t N, const typename Field::Element alpha,`
`typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr B, const size_t ldb, const`
`ParSeqHelper::Parallel< Cut, Param > &PSH)`
- `template<class Field, class ParSeqTrait = ParSeqHelper::Sequential>`
`void ftrsm (const Field &F, const FFLAS_SIDE Side, const FFLAS_UPLO Uplo, const FFLAS_TRANSPOSE`
`TransA, const FFLAS_DIAG Diag, const size_t M, const size_t N, const typename Field::Element alpha, type-`
`name Field::Element_ptr A, const size_t lda, typename Field::Element_ptr B, const size_t ldb, TRSMHelper<`
`StructureHelper::Recursive, ParSeqTrait > &H)`

13.101.1 Macro Definition Documentation

13.101.1.1 __FFLASFFPACK_ftrsm_INL

```
#define __FFLASFFPACK_ftrsm_INL
```

13.102 fflas_ftrsm_mp.inl File Reference

triangular system with matrix right hand side over multiprecision domain (either over Z or over Z/pZ)

```
#include <cmath>
#include <givaro/modular-integer.h>
#include <givaro/givinteger.h>
#include "fflas-ffpack/fflas/fflas_bounds.inl"
#include "fflas-ffpack/fflas/fflas_level3.inl"
#include "fflas-ffpack/field/rns-integer-mod.h"
#include "fflas-ffpack/field/rns-integer.h"
```

Namespaces

- namespace [FFLAS](#)

Macros

- `#define __FFPACK_ftrsm_mp_INL`

Functions

- `void ftrsm (const Givaro::Modular< Givaro::Integer > &F, const FFLAS_SIDE Side, const FFLAS_UPLO`
`Uplo, const FFLAS_TRANSPOSE TransA, const FFLAS_DIAG Diag, const size_t M, const size_t N, const`
`Givaro::Integer alpha, const Givaro::Integer *A, const size_t lda, Givaro::Integer *B, const size_t ldb)`
- `void cblas_impftrsm (const enum FFLAS_ORDER Order, const enum FFLAS_SIDE Side, const enum`
`FFLAS_UPLO Uplo, const enum FFLAS_TRANSPOSE TransA, const enum FFLAS_DIAG Diag, const`
`int M, const int N, const FFPACK::rns_double_elt alpha, FFPACK::rns_double_elt_cstptr A, const int lda,`
`FFPACK::rns_double_elt_ptr B, const int ldb)`

13.102.1 Detailed Description

triangular system with matrix right hand side over multiprecision domain (either over Z or over Z/pZ)

13.102.2 Macro Definition Documentation

13.102.2.1 __FFPACK_ftrsm_mp_INL

```
#define __FFPACK_ftrsm_mp_INL
```


13.103 fflas_ftrsv.inl File Reference

Namespaces

- namespace [FFLAS](#)

Macros

- `#define` [__FFLASFFPACK_ftrsv_INL](#)

Functions

- `template<class Field >`
`void ftrsv (const Field &F, const FFLAS\_UPLO Uplo, const FFLAS\_TRANSPOSE TransA, const FFLAS\_DIAG Diag, const size_t N, typename Field::ConstElement\_ptr A, const size_t lda, typename Field::Element\_ptr X, int incX)`
ftrsv: TRIangular System solve with Vector Computes $X \leftarrow \text{op}(A^{-1})X$

13.103.1 Macro Definition Documentation

13.103.1.1 [__FFLASFFPACK_ftrsv_INL](#)

```
#define __FFLASFFPACK_ftrsv_INL
```

13.104 fflas_helpers.inl File Reference

```
#include "fflas-ffpack/field/field-traits.h"
#include "fflas-ffpack/paladin/parallel.h"
#include "fflas-ffpack/utils/flimits.h"
#include <algorithm>
```

Data Structures

- struct [Auto](#)
- struct [Classic](#)
- struct [DivideAndConquer](#)
- struct [Winograd](#)
- struct [WinogradPar](#)
- struct [Bini](#)
- struct [AlgoChooser](#)< [ModeT](#), [ParSeq](#) >
- struct [AlgoChooser](#)< [ModeCategories::ConvertTo](#)< [ElementCategories::RNSElementTag](#) >, [ParSeq](#) >
- struct [MMHelper](#)< [Field](#), [AlgoTrait](#), [ModeCategories::DefaultTag](#), [ParSeqTrait](#) >
FGEMM Helper for Default and ConvertTo modes of operation.
- struct [MMHelper](#)< [Field](#), [AlgoTrait](#), [ModeCategories::ConvertTo](#)< [Dest](#) >, [ParSeqTrait](#) >
- struct [MMHelper](#)< [Field](#), [AlgoTrait](#), [ModeTrait](#), [ParSeqTrait](#) >
- struct [Recursive](#)
- struct [Iterative](#)
- struct [Hybrid](#)
- struct [TRSMHelper](#)< [ReclterTrait](#), [ParSeqTrait](#) >
TRSM Helper.

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::Protected](#)
- namespace [FFLAS::MMHelperAlgo](#)
- namespace [FFLAS::StructureHelper](#)
StructureHelper for ftrsm.

Macros

- `#define __FFLASFFPACK_fflas_fflas_mmhelper_INL`

Functions

- `template<class Field >`
`int WinogradSteps (const Field &F, const size_t &m)`
Computes the number of recursive levels to perform.
- `template<class DFE >`
`size_t min_types (const DFE &k)`
- `template<> size_t min_types (const Reclnt::rint< 6 > &k)`
- `template<> size_t min_types (const Reclnt::rint< 7 > &k)`
- `template<> size_t min_types (const Reclnt::rint< 8 > &k)`
- `template<> size_t min_types (const Reclnt::rint< 9 > &k)`
- `template<> size_t min_types (const Reclnt::rint< 10 > &k)`
- `template<> size_t min_types (const Givaro::Integer &k)`
- `template<class T >`
`bool unfit (T x)`
- `template<> bool unfit (int64_t x)`
- `template<size_t K>`
`bool unfit (Reclnt::rint< K > x)`
- `template<> bool unfit (Reclnt::rint< 6 > x)`

13.104.1 Macro Definition Documentation

13.104.1.1 __FFLASFFPACK_fflas_fflas_mmhelper_INL

```
#define __FFLASFFPACK_fflas_fflas_mmhelper_INL
```

13.105 igemm.doxy File Reference

13.106 igemm.h File Reference

```
#include "igemm_kernels.h"
#include "igemm_tools.h"
#include "fflas-ffpack/utils/fflas_memory.h"
#include "igemm.inl"
```

Namespaces

- namespace `FFLAS`
- namespace `FFLAS::Protected`

Enumerations

- enum `number_kind` { `zero` =0 , `one` =1 , `mone` =-1 , `other` =2 }

Functions

- `template<enum FFLAS_TRANSPOSE tA, enum FFLAS_TRANSPOSE tB>`
`void igemm_colmajor (size_t rows, size_t cols, size_t depth, const int64_t alpha, const int64_t *A, size_t lda, const int64_t *B, size_t ldb, int64_t *C, size_t ldc)`
- `template<enum FFLAS_TRANSPOSE tA, enum FFLAS_TRANSPOSE tB, enum number_kind alpha_kind>`
`void igemm_colmajor (size_t rows, size_t cols, size_t depth, const int64_t alpha, const int64_t *A, size_t lda, const int64_t *B, size_t ldb, int64_t *C, size_t ldc)`

- void [igemm](#) (const enum [FFLAS_TRANSPOSE](#) TransA, const enum [FFLAS_TRANSPOSE](#) TransB, size_t rows, size_t cols, size_t depth, const int64_t alpha, const int64_t *A, size_t lda, const int64_t *B, size_t ldb, const int64_t beta, int64_t *C, size_t ldc)
- void [igemm_](#) (const enum [FFLAS_ORDER](#) Order, const enum [FFLAS_TRANSPOSE](#) TransA, const enum [FFLAS_TRANSPOSE](#) TransB, const size_t M, const size_t N, const size_t K, const int64_t alpha, const int64_t *A, const size_t lda, const int64_t *B, const size_t ldb, const int64_t beta, int64_t *C, const size_t ldc)

13.107 igemm.inl File Reference

```
#include "fflas-ffpack/utils/fflas_memory.h"
```

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::Protected](#)

Macros

- #define [__FFLASFFPACK_fflas_igemm_igemm_INL](#)

Functions

- template<enum [FFLAS_TRANSPOSE](#) tA, enum [FFLAS_TRANSPOSE](#) tB>
void [igemm_colmajor](#) (size_t rows, size_t cols, size_t depth, const int64_t alpha, const int64_t *A, size_t lda, const int64_t *B, size_t ldb, int64_t *C, size_t ldc)
- template<enum [FFLAS_TRANSPOSE](#) tA, enum [FFLAS_TRANSPOSE](#) tB, enum [number_kind](#) alpha_kind>
void [igemm_colmajor](#) (size_t rows, size_t cols, size_t depth, const int64_t alpha, const int64_t *A, size_t lda, const int64_t *B, size_t ldb, int64_t *C, size_t ldc)
- void [igemm](#) (const enum [FFLAS_TRANSPOSE](#) TransA, const enum [FFLAS_TRANSPOSE](#) TransB, size_t rows, size_t cols, size_t depth, const int64_t alpha, const int64_t *A, size_t lda, const int64_t *B, size_t ldb, const int64_t beta, int64_t *C, size_t ldc)
- void [igemm_](#) (const enum [FFLAS_ORDER](#) Order, const enum [FFLAS_TRANSPOSE](#) TransA, const enum [FFLAS_TRANSPOSE](#) TransB, const size_t M, const size_t N, const size_t K, const int64_t alpha, const int64_t *A, const size_t lda, const int64_t *B, const size_t ldb, const int64_t beta, int64_t *C, const size_t ldc)

13.107.1 Macro Definition Documentation

13.107.1.1 [__FFLASFFPACK_fflas_igemm_igemm_INL](#)

```
#define __FFLASFFPACK_fflas_igemm_igemm_INL
```

13.108 igemm_kernels.h File Reference

```
#include "igemm_kernels.inl"
```

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::details](#)

Functions

- template<enum [number_kind](#) K>
void [igebb44](#) (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *bIA, const int64_t *bIB, int64_t *C, size_t ldc)

- `template<enum number\_kind K>`
`void igebb24 (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)`
- `template<enum number\_kind K>`
`void igebb14 (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)`
- `template<enum number\_kind K>`
`void igebb41 (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)`
- `template<enum number\_kind K>`
`void igebb21 (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)`
- `template<enum number\_kind K>`
`void igebb11 (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)`
- `template<enum number\_kind K>`
`void igebp (size_t rows, size_t cols, size_t depth, const int64_t alpha, const int64_t *blockA, size_t lda, const int64_t *blockB, size_t ldb, int64_t *C, size_t ldc)`

13.109 `igemm_kernels.inl` File Reference

```
#include "fflas-ffpack/utils/fflas_memory.h"
#include "igemm_tools.h"
```

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::details](#)

Macros

- `#define \_\_FFLASFFPACK\_fflas\_igemm\_igemm\_kernels\_INL`

Functions

- `template<enum number\_kind K>`
`void igebb44 (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)`
- `template<enum number\_kind K>`
`void igebb24 (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)`
- `template<enum number\_kind K>`
`void igebb14 (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)`
- `template<enum number\_kind K>`
`void igebb41 (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)`
- `template<enum number\_kind K>`
`void igebb21 (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)`
- `template<enum number\_kind K>`
`void igebb11 (size_t i, size_t j, size_t depth, size_t pdeth, const int64_t alpha, const int64_t *blA, const int64_t *blB, int64_t *C, size_t ldc)`
- `template<enum number\_kind K>`
`void igebp (size_t rows, size_t cols, size_t depth, const int64_t alpha, const int64_t *blockA, size_t lda, const int64_t *blockB, size_t ldb, int64_t *C, size_t ldc)`

13.109.1 Macro Definition Documentation

13.109.1.1 __FFLASFFPACK_fflas_igemm_igemm_kernels_INL

```
#define __FFLASFFPACK_fflas_igemm_igemm_kernels_INL
```

13.110 igemm_tools.h File Reference

```
#include "igemm_tools.inl"
```

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::details](#)

Functions

- template<size_t k, bool transpose>
void [pack_lhs](#) (int64_t *XX, const int64_t *X, size_t ldx, size_t rows, size_t cols)
- template<size_t k, bool transpose>
void [pack_rhs](#) (int64_t *XX, const int64_t *X, size_t ldx, size_t rows, size_t cols)
- void [gebp](#) (size_t rows, size_t cols, size_t depth, int64_t *C, size_t ldc, const int64_t *blockA, size_t lda, const int64_t *BlockB, size_t ldb, int64_t *BlockW)
- void [BlockingFactor](#) (size_t &m, size_t &n, size_t &k)

13.111 igemm_tools.inl File Reference

```
#include "fflas-ffpack/fflas/fflas_simd.h"
```

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::details](#)

Macros

- #define [__FFLASFFPACK_fflas_igemm_igemm_tools_INL](#)

Functions

- template<size_t k, bool transpose>
void [pack_rhs](#) (int64_t *XX, const int64_t *X, size_t ldx, size_t rows, size_t cols)
- template<size_t k, bool transpose>
void [pack_lhs](#) (int64_t *XX, const int64_t *X, size_t ldx, size_t rows, size_t cols)
- void [BlockingFactor](#) (size_t &m, size_t &n, size_t &k)

13.111.1 Macro Definition Documentation

13.111.1.1 __FFLASFFPACK_fflas_igemm_igemm_tools_INL

```
#define __FFLASFFPACK_fflas_igemm_igemm_tools_INL
```

13.112 fflas_level1.inl File Reference

Namespaces

- namespace [FFLAS](#)

Macros

- `#define __FFLASFFPACK_fflas_fflas_level1_INL`

Functions

- `template<class Field >`
`void freduce (const Field &F, const size_t n, typename Field::Element_ptr X, const size_t incX)`

$$freduce\ x \leftarrow x \bmod F.$$
- `template<class Field >`
`void freduce (const Field &F, const size_t n, typename Field::ConstElement_ptr Y, const size_t incY, typename Field::Element_ptr X, const size_t incX)`

$$freduce\ x \leftarrow y \bmod F.$$
- `template<class Field, class OtherElement_ptr >`
`void finit (const Field &F, const size_t n, const OtherElement_ptr Y, const size_t incY, typename Field::Element_ptr X, const size_t incX)`

$$finit\ x \leftarrow y \bmod F.$$
- `template<class Field >`
`void finit (const Field &F, const size_t n, typename Field::Element_ptr X, const size_t incX)`

$$finit\ \text{Initializes } X \text{ in } F.$$
- `template<class Field, class OtherElement_ptr >`
`void fconvert (const Field &F, const size_t n, OtherElement_ptr X, const size_t incX, typename Field::ConstElement_ptr Y, const size_t incY)`

$$fconvert\ x \leftarrow y \bmod F.$$
- `template<class Field >`
`void fnegin (const Field &F, const size_t n, typename Field::Element_ptr X, const size_t incX)`

$$fnegin\ x \leftarrow -x.$$
- `template<class Field >`
`void fneg (const Field &F, const size_t n, typename Field::ConstElement_ptr Y, const size_t incY, typename Field::Element_ptr X, const size_t incX)`

$$fneg\ x \leftarrow -y.$$
- `template<class Field >`
`void fzero (const Field &F, const size_t n, typename Field::Element_ptr X, const size_t incX)`

$$fzero : A \leftarrow 0.$$
- `template<class Field, class Randlter >`
`void frand (const Field &F, Randlter &G, const size_t n, typename Field::Element_ptr X, const size_t incX)`

$$frand : A \leftarrow random.$$
- `template<class Field >`
`bool fiszero (const Field &F, const size_t n, typename Field::ConstElement_ptr X, const size_t incX)`

$$fiszero : test\ X = 0.$$
- `template<class Field >`
`bool fequal (const Field &F, const size_t n, typename Field::ConstElement_ptr X, const size_t incX, typename Field::ConstElement_ptr Y, const size_t incY)`

$$fequal : test\ X = Y.$$
- `template<class Field >`
`void fassign (const Field &F, const size_t N, typename Field::ConstElement_ptr Y, const size_t incY, typename Field::Element_ptr X, const size_t incX)`

$$fassign : x \leftarrow y.$$
- `template<class Field >`
`void fscaln (const Field &F, const size_t n, const typename Field::Element alpha, typename Field::Element_ptr X, const size_t incX)`

$$fscaln\ x \leftarrow \alpha \cdot x.$$
- `template<class Field >`
`void fscal (const Field &F, const size_t n, const typename Field::Element alpha, typename Field::ConstElement_ptr X, const size_t incX, typename Field::Element_ptr Y, const size_t incY)`

- $$fscal\ y \leftarrow \alpha \cdot x.$$
 - template<class [Field](#) >
void [faxpy](#) (const [Field](#) &F, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::Element_ptr](#) Y, const size_t incY)

$$faxpy : y \leftarrow \alpha \cdot x + y.$$
- template<class [Field](#) >
void [faxpby](#) (const [Field](#) &F, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) X, const size_t incX, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) Y, const size_t incY)

$$faxpby : y \leftarrow \alpha \cdot x + \beta \cdot y.$$
- template<class [Field](#) >
[Field::Element](#) [fdot](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::ConstElement_ptr](#) Y, const size_t incY)

$$fdot: \text{dot product } x^T y.$$
- template<class [Field](#) >
[Field::Element](#) [fdot](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) x, const size_t incx, typename [Field::ConstElement_ptr](#) y, const size_t incy, const [ParSeqHelper::Sequential](#) seq)
- template<typename [Field](#) , class Cut , class Param >
[Field::Element](#) [fdot](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) X, const size_t incX, typename [Field::ConstElement_ptr](#) Y, const size_t incY, const [ParSeqHelper::Parallel](#)< Cut, Param > par)
- template<class [Field](#) >
void [fswap](#) (const [Field](#) &F, const size_t N, typename [Field::Element_ptr](#) X, const size_t incX, typename [Field::Element_ptr](#) Y, const size_t incY)

$$fswap: X \leftrightarrow Y.$$
- template<class [Field](#) >
void [pfadd](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc, const size_t numths)
- template<class [Field](#) >
void [pfsub](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc, const size_t numths)
- template<class [Field](#) >
void [pfaddin](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc, size_t numths)
- template<class [Field](#) >
void [pfsubin](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc, size_t numths)
- template<class [Field](#) >
void [fadd](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t inca, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc)
- template<class [Field](#) >
void [fsub](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t inca, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc)
- template<class [Field](#) >
void [faddin](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc)
- template<class [Field](#) >
void [fsubin](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc)
- template<class [Field](#) >
void [fadd](#) (const [Field](#) &F, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t inca, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) B, const size_t incb, typename [Field::Element_ptr](#) C, const size_t incc)

13.112.1 Macro Definition Documentation

13.112.1.1 __FFLASFFPACK_fflas_fflas_level1_INL

```
#define __FFLASFFPACK_fflas_fflas_level1_INL
```

13.113 fflas_level2.inl File Reference

```
#include "givaro/zring.h"
```

Namespaces

- namespace [FFLAS](#)

Macros

- #define [__FFLASFFPACK_fflas_fflas_level2_INL](#)

Functions

- template<class [Field](#) >
void [fassign](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) A, const size_t lda)
fassign : $A \leftarrow B$.
- template<class [Field](#) >
void [fzero](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
fzero : $A \leftarrow 0$.
- template<class [Field](#) >
void [fzero](#) (const [Field](#) &F, const [FFLAS_UPLO](#) shape, const [FFLAS_DIAG](#) diag, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
fzero : $A \leftarrow 0$ for a triangular matrix.
- template<class [Field](#) , class RandIter >
void [frand](#) (const [Field](#) &F, RandIter &G, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
frand : $A \leftarrow \text{random}$.
- template<class [Field](#) >
bool [fequal](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb)
fequal : test $A = B$.
- template<class [Field](#) >
bool [fiszero](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::ConstElement_ptr](#) A, const size_t m, const size_t n, const size_t lda)
fiszero : test $A = 0$.
- template<class [Field](#) >
void [fidentity](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda, const typename [Field::Element](#) &d)
creates a diagonal matrix
- template<class [Field](#) >
void [fidentity](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
creates a diagonal matrix
- template<class [Field](#) >
void [freduce](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
freduce $A \leftarrow A \bmod F$.
- template<class [Field](#) >
void [freduce](#) (const [Field](#) &F, const [FFLAS_UPLO](#) uplo, const size_t N, typename [Field::Element_ptr](#) A, const size_t lda)

- freduce for square symmetric matrices*
- template<class [Field](#) >
void [freduce](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) A, const size_t lda)
freduce $A \leftarrow B \bmod F$.
 - template<class [Field](#) , class [OtherElement_ptr](#) >
void [finit](#) (const [Field](#) &F, const size_t m, const size_t n, const [OtherElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) A, const size_t lda)
finit $A \leftarrow B \bmod F$.
 - template<class [Field](#) , class [OtherElement_ptr](#) >
void [finit](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
finit Initializes A in F^S .
 - template<class [Field](#) , class [OtherElement_ptr](#) >
void [fconvert](#) (const [Field](#) &F, const size_t m, const size_t n, [OtherElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb)
fconvert $A \leftarrow B \bmod F$.
 - template<class [Field](#) >
void [fnegin](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda)
fnegin $A \leftarrow -A$.
 - template<class [Field](#) >
void [fneg](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) A, const size_t lda)
fneg $A \leftarrow -B$.
 - template<class [Field](#) >
void [fscaln](#) (const [Field](#) &F, const size_t m, const size_t n, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t lda)
fscaln $A \leftarrow a \cdot A$.
 - template<class [Field](#) >
void [fscal](#) (const [Field](#) &F, const size_t m, const size_t n, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb)
fscal $B \leftarrow a \cdot A$.
 - template<class [Field](#) >
void [faxpy](#) (const [Field](#) &F, const size_t m, const size_t n, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) X, const size_t ldx, typename [Field::Element_ptr](#) Y, const size_t ldy)
faxpy : $y \leftarrow \alpha \cdot x + y$.
 - template<class [Field](#) >
void [faxpby](#) (const [Field](#) &F, const size_t m, const size_t n, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) X, const size_t ldx, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) Y, const size_t ldy)
faxpby : $y \leftarrow \alpha \cdot x + \beta \cdot y$.
 - template<class [Field](#) >
void [fmove](#) (const [Field](#) &F, const size_t m, const size_t n, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb)
fmove : $A \leftarrow B$ and $B \leftarrow 0$.
 - template<class [Field](#) >
void [fadd](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc)
fadd : matrix addition.
 - template<class [Field](#) >
void [fsub](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc)
fsub : matrix subtraction.
 - template<class [Field](#) >
void [fsubin](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc)

- fsubin* $C = C - B$
- template<class [Field](#) >
void [fadd](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc)
fadd : matrix addition with scaling.
 - template<class [Field](#) >
void [faddin](#) (const [Field](#) &F, const size_t M, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc)
faddin
 - template<class [Field](#) >
void [faddin](#) (const [Field](#) &F, const [FFLAS_UPLO](#) uplo, const size_t N, typename [Field::ConstElement_ptr](#) B, const size_t ldb, typename [Field::Element_ptr](#) C, const size_t ldc)
fadding for symmetric matrices
 - template<class [Field](#) >
[Field::Element_ptr](#) [fgemv](#) (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) TransA, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) X, const size_t incX, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) Y, const size_t incY)
finite prime Field GEneral Matrix Vector multiplication.
 - template<class [Field](#) >
void [fger](#) (const [Field](#) &F, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) x, const size_t incx, typename [Field::ConstElement_ptr](#) y, const size_t incy, typename [Field::Element_ptr](#) A, const size_t lda)
fger: rank one update of a general matrix
 - template<class [Field](#) >
void [ftrsv](#) (const [Field](#) &F, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) X, int incX)
ftrsv: *TRiangular System solve with Vector Computes* $X \leftarrow \text{op}(A^{-1})X$
 - template<class [Field](#) >
size_t [bitsize](#) (const [Field](#) &F, size_t M, size_t N, const typename [Field::ConstElement_ptr](#) A, size_t lda)
bitsize: Computes the largest bitsize of the matrix' coefficients.
 - template<> size_t [bitsize](#)< [Givaro::ZRing](#)< [Givaro::Integer](#) > > (const [Givaro::ZRing](#)< [Givaro::Integer](#) > &F, size_t M, size_t N, const [Givaro::Integer](#) *A, size_t lda)
 - template<class [Field](#) >
void [ftmrv](#) (const [Field](#) &F, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t N, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) X, int incX)
ftsm: *TRiangular Matrix Vector prodcut Computes* $X \leftarrow \text{op}(A)X$

13.113.1 Macro Definition Documentation

13.113.1.1 __FFLASFFPACK_fflas_fflas_level2_INL

```
#define __FFLASFFPACK_fflas_fflas_level2_INL
```

13.114 fflas_level3.inl File Reference

```
#include "fflas_bounds.inl"
#include "fflas_helpers.inl"
#include "fflas-ffpack/paladin/parallel.h"
```

Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::Protected](#)

Macros

- `#define` [__FFLASFFPACK_fflas_fflas_level3_INL](#)
- `#define` [__FFLAS__TRSM_READONLY](#)

Functions

- `template<class Field >`
void [MatF2MatD_Triangular](#) (const [Field](#) &F, Givaro::DoubleDomain::Element_ptr S, const size_t lds, typename [Field::ConstElement_ptr](#) const E, const size_t lde, const size_t m, const size_t n)
- `template<class Field >`
void [MatF2MatFI_Triangular](#) (const [Field](#) &F, Givaro::FloatDomain::Element_ptr S, const size_t lds, typename [Field::ConstElement_ptr](#) const E, const size_t lde, const size_t m, const size_t n)
- `template<class Field >`
void [ftrsm](#) (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb)
*ftrsm: **TRI**angular **S**ystem solve with **M**atrix.*
- `template<class Field >`
void [ftrmm](#) (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb)
*ftrmm: **TRI**angular **M**atrix **M**ultiply.*
- `template<class Field >`
void [ftrmm](#) (const [Field](#) &F, const [FFLAS_SIDE](#) Side, const [FFLAS_UPLO](#) Uplo, const [FFLAS_TRANSPOSE](#) TransA, const [FFLAS_DIAG](#) Diag, const size_t M, const size_t N, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc)
*ftrmm: **TRI**angular **M**atrix **M**ultiply with 3 operands Computes $C \leftarrow \alpha op(A)B + beta C$ or $C \leftarrow \alpha B op(A) + beta C$.*
- `template<class Field >`
[Field::Element_ptr](#) [fsyrk](#) (const [Field](#) &F, const [FFLAS_UPLO](#) UpLo, const [FFLAS_TRANSPOSE](#) trans, const size_t n, const size_t k, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc)
fsyrk: Symmetric Rank K update
- `template<class Field, typename FieldTrait >`
[Field::Element_ptr](#) [fsyrk_strassen](#) (const [Field](#) &F, const [FFLAS_UPLO](#) UpLo, const [FFLAS_TRANSPOSE](#) trans, const size_t N, const size_t K, const typename [Field::Element](#) y1, const typename [Field::Element](#) y2, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), FieldTrait > &H)
- `template<class Field >`
[Field::Element_ptr](#) [fsyr2k](#) (const [Field](#) &F, const [FFLAS_UPLO](#) UpLo, const [FFLAS_TRANSPOSE](#) trans, const size_t n, const size_t k, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc)
fsyr2k: Symmetric Rank 2K update
- `template<class Field >`
[Field::Element_ptr](#) [fsyrk](#) (const [Field](#) &F, const [FFLAS_UPLO](#) UpLo, const [FFLAS_TRANSPOSE](#) trans, const size_t n, const size_t k, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) D, const size_t incD, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, const size_t threshold=[__FFLASFFPACK_FSYRK_THRESHOLD](#))
fsyrk: Symmetric Rank K update with diagonal scaling

- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::Element_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` D, const `size_t` incD, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `ParSeqHelper::Sequential` seq, const `size_t` threshold)
- `template<class Field , class Cut , class Param >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` N, const `size_t` K, const typename `Field::Element` alpha, typename `Field::Element_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` D, const `size_t` incD, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `ParSeqHelper::Parallel`< Cut, Param > par, const `size_t` threshold)
- `template<class Field >`
`Field::Element_ptr fsyrk` (const `Field` &F, const `FFLAS_UPLO` UpLo, const `FFLAS_TRANSPOSE` trans, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, typename `Field::Element_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` D, const `size_t` incD, const `std::vector< bool >` &two←Block, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `size_t` threshold=__FFLASFFPACK_FSYRK_THRESHOLD)
fsyrk: Symmetric Rank K update with diagonal scaling
- `template<typename Field >`
`Field::Element_ptr fgemm` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const `size_t` m, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` B, const `size_t` ldb, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc)
fgemm: Field GENERAL Matrix Multiply.
- `template<typename Field >`
`Field::Element_ptr fgemm` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const `size_t` m, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` B, const `size_t` ldb, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `ParSeqHelper::Sequential` seq)
- `template<typename Field , class Cut , class Param >`
`Field::Element_ptr fgemm` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const `size_t` m, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` B, const `size_t` ldb, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, const `ParSeqHelper::Parallel`< Cut, Param > par)
- `template<typename Field >`
`Field::Element_ptr pfgemm` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const `size_t` m, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, typename `Field::ConstElement_ptr` A, const `size_t` lda, typename `Field::ConstElement_ptr` B, const `size_t` ldb, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `size_t` numthreads=0)
- `template<class Field >`
`Field::Element * pfgemm_1D_rec` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const `size_t` m, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, const typename `Field::Element_ptr` A, const `size_t` lda, const typename `Field::Element_ptr` B, const `size_t` ldb, const typename `Field::Element` beta, typename `Field::Element` *C, const `size_t` ldc, `size_t` seuil)
- `template<class Field >`
`Field::Element * pfgemm_2D_rec` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const `size_t` m, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, const typename `Field::Element_ptr` A, const `size_t` lda, const typename `Field::Element_ptr` B, const `size_t` ldb, const typename `Field::Element` beta, typename `Field::Element` *C, const `size_t` ldc, `size_t` seuil)
- `template<class Field >`
`Field::Element * pfgemm_3D_rec` (const `Field` &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const `size_t` m, const `size_t` n, const `size_t` k, const typename `Field::Element` alpha, const typename `Field::Element_ptr` A, const `size_t` lda, const typename `Field::Element_ptr` B, const `size_t` ldb, const typename `Field::Element` beta, typename `Field::Element_ptr` C, const `size_t` ldc, `size_t` seuil, `size_t` *x)

- template<class [Field](#) >
[Field::Element_ptr](#) pfgemm_3D_rec2 (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const [FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const typename [Field::Element](#) alpha, const typename [Field::Element_ptr](#) A, const size_t lda, const typename [Field::Element_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, size_t seuil, size_t *x)
- template<class [Field](#) >
[Field::Element_ptr](#) fsquare (const [Field](#) &F, const [FFLAS_TRANSPOSE](#) ta, const size_t n, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc)

fsquare: Squares a matrix.

13.114.1 Macro Definition Documentation

13.114.1.1 __FFLASFFPACK_fflas_fflas_level3_INL

```
#define __FFLASFFPACK_fflas_fflas_level3_INL
```

13.114.1.2 __FFLAS__TRSM_READONLY

```
#define __FFLAS__TRSM_READONLY
```

13.115 fflas_pfgemm.inl File Reference

```
#include "fflas-ffpack/paladin/blockcuts.inl"
#include "fflas-ffpack/paladin/parallel.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/paladin/pfgemm_variants.inl"
```

Namespaces

- namespace [FFLAS](#)

Macros

- #define [__FFLASFFPACK_fflas_pfgemm_INL](#)
- #define [__FFLASFFPACK_SEQPARTHRESHOLD](#) 220
- #define [__FFLASFFPACK_DIMKPENALTY](#) 1

Functions

- template<class [Field](#) , class [ModeTrait](#) , class [Strat](#) , class [Param](#) >
std::enable_if<!std::is_same< [ModeTrait](#), [ModeCategories::ConvertTo](#)< [ElementCategories::RNSElementTag](#) > >::value, typename [Field::Element_ptr](#) >::type fgemm (const [Field](#) &F, const [FFLAS::FFLAS_TRANSPOSE](#) ta, const [FFLAS::FFLAS_TRANSPOSE](#) tb, const size_t m, const size_t n, const size_t k, const typename [Field::Element](#) alpha, typename [Field::ConstElement_ptr](#) A, const size_t lda, typename [Field::ConstElement_ptr](#) B, const size_t ldb, const typename [Field::Element](#) beta, typename [Field::Element_ptr](#) C, const size_t ldc, [MMHelper](#)< [Field](#), [MMHelperAlgo::Winograd](#), [ModeTrait](#), [ParSeqHelper::Parallel](#)< [Strat](#), [Param](#) > > &H)

13.115.1 Macro Definition Documentation

13.115.1.1 __FFLASFFPACK_fflas_pfgemm_INL

```
#define __FFLASFFPACK_fflas_pfgemm_INL
```

13.115.1.2 __FFLASFFPACK_SEQPARTHRESHOLD

```
#define __FFLASFFPACK_SEQPARTHRESHOLD 220
```

13.115.1.3 __FFLASFFPACK_DIMKPENALTY

```
#define __FFLASFFPACK_DIMKPENALTY 1
```

13.116 fflas_pftrsm.inl File Reference

```
#include "fflas-ffpack/paladin/parallel.h"
```

Namespaces

- namespace [FFLAS](#)

Macros

- #define [__FFLASFFPACK_fflas_pftrsm_INL](#)
- #define [PTRSM_HYBRID_THRESHOLD](#) 256

Functions

- template<class [Field](#), class Cut, class Param >
[Field::Element_ptr](#) ftrsm (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) Side, const [FFLAS::FFLAS_UPLO](#) UpLo, const [FFLAS::FFLAS_TRANSPOSE](#) TA, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t m, const size_t n, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb, [TRSMHelper](#)< [StructureHelper::Iterative](#), [ParSeqHelper::Parallel](#)< Cut, Param > > &H)
- template<class [Field](#), class Cut, class Param >
[Field::Element_ptr](#) ftrsm (const [Field](#) &F, const [FFLAS::FFLAS_SIDE](#) Side, const [FFLAS::FFLAS_UPLO](#) UpLo, const [FFLAS::FFLAS_TRANSPOSE](#) TA, const [FFLAS::FFLAS_DIAG](#) Diag, const size_t m, const size_t n, const typename [Field::Element](#) alpha, typename [Field::Element_ptr](#) A, const size_t lda, typename [Field::Element_ptr](#) B, const size_t ldb, [TRSMHelper](#)< [StructureHelper::Hybrid](#), [ParSeqHelper::Parallel](#)< Cut, Param > > &H)

13.116.1 Macro Definition Documentation

13.116.1.1 __FFLASFFPACK_fflas_pftrsm_INL

```
#define __FFLASFFPACK_fflas_pftrsm_INL
```

13.116.1.2 PTRSM_HYBRID_THRESHOLD

```
#define PTRSM_HYBRID_THRESHOLD 256
```

13.117 fflas_simd.h File Reference

```
#include "fflas-ffpack/utils/fflas_intrinsic.h"
#include <iostream>
#include <type_traits>
#include <limits>
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/utils/debug.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include <vector>
#include "givaro/givtypestring.h"
#include <fflas-ffpack/fflas/fflas_simd/simd_modular.inl>
```

Data Structures

- struct [support_simd](#)< T >
- struct [is_simd](#)< T >
- struct [NoSimd](#)< T >
- struct [SimdChooser](#)< T, bool, bool >
- struct [SimdChooser](#)< T, false, b >
- struct [SimdChooser](#)< T, true, false >
- struct [SimdChooser](#)< T, true, true >

Namespaces

- namespace [FFLAS](#)

Macros

- `#define` [SIMD_INT](#) 1
- `#define` [INLINE](#) inline
- `#define` [CONST](#)
- `#define` [PURE](#)
- `#define` [NORML_MOD](#)(C, P, NEGP, MIN, MAX, Q, T)
- `#define` [FLOAT_MOD](#)(C, P, INVP, Q)

Typedefs

- `template<class T >`
using [Simd](#) = typename [SimdChooser](#)< T >::value

13.117.1 Macro Definition Documentation

13.117.1.1 SIMD_INT

```
#define SIMD_INT 1
```

13.117.1.2 INLINE

```
#define INLINE inline
```

13.117.1.3 CONST

```
#define CONST
```

13.117.1.4 PURE

```
#define PURE
```

13.117.1.5 NORML_MOD

```
#define NORML_MOD(  
    C,  
    P,  
    NEGP,  
    MIN,  
    MAX,  
    Q,  
    T )
```

Value:

```
{  
    \  
    Q = greater(C, MAX);  
    \
```

```

    T = lesser(C, MIN);
    \
    Q = vand(Q, NEGP);
    \
    T = vand(T, P);
    \
    Q = vor(Q, T);
    \
    C = add(C, Q);
    \
}

```

13.117.1.6 FLOAT_MOD

```

#define FLOAT_MOD(
    C,
    P,
    INVP,
    Q )

```

Value:

```

{
    \
    Q = mul(C, INVP);
    \
    Q = floor(Q);
    \
    C = fnmadd(C, Q, P);
    \
}

```

13.117.2 Typedef Documentation

13.117.2.1 Simd

```

template<class T >
using Simd = typename SimdChooser<T>::value

```

13.118 simd.doxy File Reference

13.119 simd128.inl File Reference

```

#include "simd128_float.inl"
#include "simd128_double.inl"

```

Data Structures

- struct [Simd128i_base](#)

Macros

- #define [__FFLASFFPACK_fflas_ffpack_utils_simd128_INL](#)

Typedefs

- template<class T >
using [Simd128](#) = [Simd128_impl](#)< std::is_arithmetic< T >::value, std::is_integral< T >::value, std::is_↵
signed< T >::value, sizeof(T)>

13.119.1 Macro Definition Documentation

13.119.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd128_INL

```

#define __FFLASFFPACK_fflas_ffpack_utils_simd128_INL

```


13.119.2 Typedef Documentation

13.119.2.1 Simd128

```
template<class T >
using Simd128 = Simd128_impl<std::is_arithmetic<T>::value, std::is_integral<T>::value, std::is_signed<T>::value, sizeof(T)>
```

13.120 simd128_double.inl File Reference

```
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd128_impl< true, false, true, 8 >](#)

Macros

- #define [__FFLASFFPACK_fflas_ffpack_utils_simd128_double_INL](#)

13.120.1 Macro Definition Documentation

13.120.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd128_double_INL

```
#define __FFLASFFPACK_fflas_ffpack_utils_simd128_double_INL
```

13.121 simd128_float.inl File Reference

```
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd128_impl< true, false, true, 4 >](#)

Macros

- #define [__FFLASFFPACK_fflas_ffpack_utils_simd128_float_INL](#)

13.121.1 Macro Definition Documentation

13.121.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd128_float_INL

```
#define __FFLASFFPACK_fflas_ffpack_utils_simd128_float_INL
```

13.122 simd128_int16.inl File Reference

```
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd128_impl< true, true, true, 2 >](#)
- union [Simd128_impl< true, true, true, 2 >::Converter](#)
- struct [Simd128_impl< true, true, false, 2 >](#)
- union [Simd128_impl< true, true, false, 2 >::Converter](#)

Macros

- [#define __FFLASFFPACK_fflas_ffpack_utils_simd128_int16_INL](#)

13.122.1 Macro Definition Documentation**13.122.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd128_int16_INL**

```
#define __FFLASFFPACK_fflas_ffpack_utils_simd128_int16_INL
```

13.123 simd128_int32.inl File Reference

```
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd128_impl< true, true, true, 4 >](#)
- union [Simd128_impl< true, true, true, 4 >::Converter](#)
- struct [Simd128_impl< true, true, false, 4 >](#)
- union [Simd128_impl< true, true, false, 4 >::Converter](#)

Macros

- [#define __FFLASFFPACK_fflas_ffpack_utils_simd128_int32_INL](#)

13.123.1 Macro Definition Documentation**13.123.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd128_int32_INL**

```
#define __FFLASFFPACK_fflas_ffpack_utils_simd128_int32_INL
```

13.124 simd128_int64.inl File Reference

```
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include "fflas-ffpack/utils/bit_manipulation.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd128_impl< true, true, true, 8 >](#)
- union [Simd128_impl< true, true, true, 8 >::Converter](#)
- struct [Simd128_impl< true, true, false, 8 >](#)
- union [Simd128_impl< true, true, false, 8 >::Converter](#)

Macros

- `#define \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd128\_int64\_INL`
- `#define vect\_t Simd128\_impl<true,true,true,8>::vect_t`

13.124.1 Macro Definition Documentation**13.124.1.1 [__FFLASFFPACK_fflas_ffpack_utils_simd128_int64_INL](#)**

```
#define __FFLASFFPACK_fflas_ffpack_utils_simd128_int64_INL
```

13.124.1.2 [vect_t](#)

```
#define vect_t Simd128\_impl<true,true,true,8>::vect_t
```

13.125 simd256.inl File Reference

```
#include "simd256_float.inl"
#include "simd256_double.inl"
```

Data Structures

- struct [Simd256fp_base](#)
- struct [Simd256i_base](#)

Macros

- `#define \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd256\_INL`

Typedefs

- `template<class T >`
`using Simd256 = Simd256\_impl< std::is_arithmetic< T >::value, std::is_integral< T >::value, std::is_↵`
`signed< T >::value, sizeof(T)>`

13.125.1 Macro Definition Documentation**13.125.1.1 [__FFLASFFPACK_fflas_ffpack_utils_simd256_INL](#)**

```
#define __FFLASFFPACK_fflas_ffpack_utils_simd256_INL
```

13.125.2 Typedef Documentation**13.125.2.1 [Simd256](#)**

```
template<class T >
using Simd256 = Simd256\_impl<std::is_arithmetic<T>::value, std::is_integral<T>::value, std↵
::is_signed<T>::value, sizeof(T)>
```

13.126 simd256_double.inl File Reference

```
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd256_impl< true, false, true, 8 >](#)
- union [Simd256_impl< true, false, true, 8 >::Converter](#)

Macros

- [#define __FFLASFFPACK_fflas_ffpack_utils_simd256_double_INL](#)

13.126.1 Macro Definition Documentation**13.126.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd256_double_INL**

```
#define __FFLASFFPACK_fflas_ffpack_utils_simd256_double_INL
```

13.127 simd256_float.inl File Reference

```
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd256_impl< true, false, true, 4 >](#)

Macros

- [#define __FFLASFFPACK_fflas_ffpack_utils_simd256_float_INL](#)

13.127.1 Macro Definition Documentation**13.127.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd256_float_INL**

```
#define __FFLASFFPACK_fflas_ffpack_utils_simd256_float_INL
```

13.128 simd256_int16.inl File Reference

```
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd256_impl< true, true, true, 2 >](#)
- union [Simd256_impl< true, true, true, 2 >::Converter](#)
- struct [Simd256_impl< true, true, false, 2 >](#)
- union [Simd256_impl< true, true, false, 2 >::Converter](#)

Macros

- [#define __FFLASFFPACK_fflas_ffpack_utils_simd256_int16_INL](#)

13.128.1 Macro Definition Documentation

13.128.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd256_int16_INL

```
#define __FFLASFFPACK_fflas_ffpack_utils_simd256_int16_INL
```

13.129 simd256_int32.inl File Reference

```
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd256_impl< true, true, true, 4 >](#)
- union [Simd256_impl< true, true, true, 4 >::Converter](#)
- struct [Simd256_impl< true, true, false, 4 >](#)
- union [Simd256_impl< true, true, false, 4 >::Converter](#)

Macros

- #define [__FFLASFFPACK_fflas_ffpack_utils_simd256_int32_INL](#)

13.129.1 Macro Definition Documentation

13.129.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd256_int32_INL

```
#define __FFLASFFPACK_fflas_ffpack_utils_simd256_int32_INL
```

13.130 simd256_int64.inl File Reference

```
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include "fflas-ffpack/utils/bit_manipulation.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd256_impl< true, true, true, 8 >](#)
- union [Simd256_impl< true, true, true, 8 >::Converter](#)
- struct [Simd256_impl< true, true, false, 8 >](#)
- union [Simd256_impl< true, true, false, 8 >::Converter](#)

Macros

- #define [__FFLASFFPACK_fflas_ffpack_utils_simd256_int64_INL](#)
- #define [vect_t Simd256_impl<true, true, true, 8>::vect_t](#)

13.130.1 Macro Definition Documentation

13.130.1.1 __FFLASFFPACK_fflas_ffpack_utils_simd256_int64_INL

```
#define __FFLASFFPACK_fflas_ffpack_utils_simd256_int64_INL
```

13.130.1.2 vect_t

```
#define vect_t Simd256_impl<true, true, true, 8>::vect_t
```

13.131 simd512.inl File Reference

```
#include "simd512_float.inl"
#include "simd512_double.inl"
#include "simd512_int64.inl"
```

Data Structures

- struct [Simd512i_base](#)

Macros

- #define [__FFLASFFPACK_simd512_INL](#)

Typedefs

- template<class T >
using [Simd512](#) = [Simd512_impl](#)< std::is_arithmetic< T >::value, std::is_integral< T >::value, std::is_↵
signed< T >::value, sizeof(T)>

13.131.1 Macro Definition Documentation

13.131.1.1 __FFLASFFPACK_simd512_INL

```
#define __FFLASFFPACK_simd512_INL
```

13.131.2 Typedef Documentation

13.131.2.1 Simd512

```
template<class T >
using Simd512 = Simd512\_impl<std::is_arithmetic<T>::value, std::is_integral<T>::value, std↵  
::is_signed<T>::value, sizeof(T)>
```

13.132 simd512_double.inl File Reference

```
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd512_impl](#)< true, false, true, 8 >

Macros

- #define [__FFLASFFPACK_simd512_double_INL](#)

13.132.1 Macro Definition Documentation

13.132.1.1 __FFLASFFPACK_simd512_double_INL

```
#define __FFLASFFPACK_simd512_double_INL
```

13.133 simd512_float.inl File Reference

```
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd512_impl< true, false, true, 4 >](#)

Macros

- #define [__FFLASFFPACK_simd512_float_INL](#)

13.133.1 Macro Definition Documentation

13.133.1.1 __FFLASFFPACK_simd512_float_INL

```
#define __FFLASFFPACK_simd512_float_INL
```

13.134 simd512_int32.inl File Reference

```
#include "fflas-ffpack/fflas/fflas_simd/simd512_int64.inl"
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd256_impl< true, true, true, 4 >](#)
- union [Simd256_impl< true, true, true, 4 >::Converter](#)
- struct [Simd256_impl< true, true, false, 4 >](#)
- union [Simd256_impl< true, true, false, 4 >::Converter](#)

Macros

- #define [__FFLASFFPACK_simd512_int32_INL](#)

13.134.1 Macro Definition Documentation

13.134.1.1 __FFLASFFPACK_simd512_int32_INL

```
#define __FFLASFFPACK_simd512_int32_INL
```

13.135 simd512_int64.inl File Reference

```
#include "givaro/givtypestring.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include "fflas-ffpack/utils/bit_manipulation.h"
#include <vector>
#include <type_traits>
```

Data Structures

- struct [Simd512_impl< true, true, true, 8 >](#)
- union [Simd512_impl< true, true, true, 8 >::Converter](#)
- struct [Simd512_impl< true, true, false, 8 >](#)
- union [Simd512_impl< true, true, false, 8 >::Converter](#)

Macros

- `#define` [_simd512_int64_INL](#)
- `#define` [vect_t Simd512_impl<true, true, true, 8>::vect_t](#)

13.135.1 Macro Definition Documentation

13.135.1.1 [_simd512_int64_INL](#)

```
#define _simd512_int64_INL
```

13.135.1.2 [vect_t](#)

```
#define vect_t Simd512_impl<true, true, true, 8>::vect_t
```

13.136 [simd_modular.inl](#) File Reference

Data Structures

- class [FieldSimd< _Field >](#)

13.137 [fflas_sparse.h](#) File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/config.h"
#include "fflas-ffpack/config-blas.h"
#include "fflas-ffpack/paladin/parallel.h"
#include <recint/recint.h>
#include <givaro/udl.h>
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/field/field-traits.h"
#include "fflas-ffpack/fflas/fflas_bounds.inl"
#include "fflas-ffpack/utils/fflas_memory.h"
#include <type_traits>
#include <vector>
#include <iostream>
#include "fflas-ffpack/fflas/fflas_sparse/sparse_matrix_traits.h"
#include "fflas-ffpack/fflas/fflas_sparse/utils.h"
#include "fflas-ffpack/fflas/fflas_sparse/csr.h"
#include "fflas-ffpack/fflas/fflas_sparse/coo.h"
#include "fflas-ffpack/fflas/fflas_sparse/ell.h"
#include "fflas-ffpack/fflas/fflas_sparse/sell.h"
#include "fflas-ffpack/fflas/fflas_sparse/csr_hyb.h"
#include "fflas-ffpack/fflas/fflas_sparse/ell_simd.h"
#include "fflas-ffpack/fflas/fflas_sparse/hyb_zo.h"
#include "fflas-ffpack/fflas/fflas_sparse.inl"
#include "fflas-ffpack/fflas/fflas_sparse/read_sparse.h"
```


Data Structures

- struct [HelperFlag](#)
- struct [CsrMat< Field >](#)
- struct [CooMat< Field >](#)
- struct [EllMat< Field >](#)
- struct [SpMat< Field, flag >](#)

Namespaces

- namespace [MKL_CONFIG](#)
- namespace [FFLAS](#)
- namespace [FFLAS::sparse_details](#)

Macros

- `#define` [index_t](#) `uint32_t`
- `#define` [ROUND_DOWN](#)(x, s) `((x) & ~((s)-1))`
- `#define` [__FFLASFFPACK_CACHE_LINE_SIZE](#) `64`
- `#define` [assume_aligned](#)(pout, pin, v) `decltype(pin) pout = pin;`
- `#define` [DENSE_THRESHOLD](#) `0.5`

Enumerations

- enum class [SparseMatrix_t](#) {
[CSR](#) , [CSR_ZO](#) , [CSC](#) , [CSC_ZO](#) ,
[COO](#) , [COO_ZO](#) , [ELL](#) , [ELL_ZO](#) ,
[SELL](#) , [SELL_ZO](#) , [ELL_simd](#) , [ELL_simd_ZO](#) ,
[CSR_HYB](#) , [HYB_ZO](#) }

Functions

- template<class [Field](#) >
void [init_y](#) (const [Field](#) &F, const `size_t` m, const typename [Field::Element](#) b, typename [Field::Element_ptr](#) y)
- template<class [Field](#) >
void [init_y](#) (const [Field](#) &F, const `size_t` m, const `size_t` n, const typename [Field::Element](#) b, typename [Field::Element_ptr](#) y, const `int` ldy)
- template<class [Field](#) , class SM , class FC , class MZO >
std::enable_if<!(std::is_same< typenameElementTraits< typenameField::Element >::value, [ElementCategories::MachineFloat](#) >::value||std::is_same< typenameElementTraits< typenameField::Element >::value, [ElementCategories::MachineIntTag](#) >::value)>::type [fspmv_dispatch](#) (const [Field](#) &F, const SM &A, typename [Field::ConstElement_ptr](#) x, typename [Field::Element_ptr](#) y, FC fc, MZO mzo)
- template<class [Field](#) , class SM , class FC , class MZO >
std::enable_if< std::is_same< typenameElementTraits< typenameField::Element >::value, [ElementCategories::MachineFloat](#) >::value||std::is_same< typenameElementTraits< typenameField::Element >::value, [ElementCategories::MachineIntTag](#) >::value >::type [fspmv_dispatch](#) (const [Field](#) &F, const SM &A, typename [Field::ConstElement_ptr](#) x, typename [Field::Element_ptr](#) y, FC fc, MZO mzo)
- template<class [Field](#) , class SM >
void [fspmv](#) (const [Field](#) &F, const SM &A, typename [Field::ConstElement_ptr](#) x, typename [Field::Element_ptr](#) y, [FieldCategories::GenericTag](#), [NotZOSparseMatrix](#))
- template<class [Field](#) , class SM >
std::enable_if< [isSparseMatrixSimdFormat](#)< [Field](#), SM >::value >::type [fspmv](#) (const [Field](#) &F, const SM &A, typename [Field::ConstElement_ptr](#) x, typename [Field::Element_ptr](#) y, [FieldCategories::UnparametricTag](#), [NotZOSparseMatrix](#))
- template<class [Field](#) , class SM >
std::enable_if< [isSparseMatrixSimdFormat](#)< [Field](#), SM >::value >::type [fspmv](#) (const [Field](#) &F, const SM &A, typename [Field::ConstElement_ptr](#) x, typename [Field::Element_ptr](#) y, [FieldCategories::UnparametricTag](#), [NotZOSparseMatrix](#))

- `template<class Field , class SM >`
`std::enable_if< !isSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (const Field &F, const SM`
`&A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::ModularTag,`
`NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (const Field &F, const SM`
`&A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::ModularTag,`
`NotZOSparseMatrix)`
- `template<class Field , class SM >`
`void fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr`
`y, FieldCategories::GenericTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< !isSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (const Field &F, const SM`
`&A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag,`
`ZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (const Field &F, const SM`
`&A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag,`
`ZOSparseMatrix)`
- `template<class Field , class SM >`
`void fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr`
`y, FieldCategories::ModularTag, std::true_type)`
- `template<class Field , class SM , class FCat , class MZO >`
`std::enable_if< !(std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat`
`>::value)|std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag`
`>::value)>::type fspmm_dispatch (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr`
`x, int ldx, typename Field::Element_ptr y, int ldy, FCat, MZO)`
- `template<class Field , class SM , class FCat , class MZO >`
`std::enable_if< std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat`
`>::value)|std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag`
`>::value >::type fspmm_dispatch (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr`
`x, int ldx, typename Field::Element_ptr y, int ldy, FCat, MZO)`
- `template<class Field , class SM >`
`void fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx,`
`typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM`
`&A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy,`
`FieldCategories::UnparametricTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< !support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM`
`&A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy,`
`FieldCategories::UnparametricTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM`
`&A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy,`
`FieldCategories::ModularTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< !support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM`
`&A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy,`
`FieldCategories::ModularTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`void fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx,`
`typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM`
`&A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy,`
`FieldCategories::UnparametricTag, ZOSparseMatrix)`

- `template<class Field , class SM >`
`std::enable_if<!support\_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::UnparametricTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`void fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::ModularTag, ZOSparseMatrix)`
- `template<class Field , class SM , class FCat , class MZO >`
`std::enable_if<!(std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat >::value)||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag >::value)>::type pfspmm_dispatch (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FCat, MZO)`
- `template<class Field , class SM , class FCat , class MZO >`
`std::enable_if< std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat >::value)||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag >::value >::type pfspmm_dispatch (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FCat, MZO)`
- `template<class Field , class SM >`
`void pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::GenericTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< support\_simd< typenameField::Element >::value >::type pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::UnparametricTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if<!support\_simd< typenameField::Element >::value >::type pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::UnparametricTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< support\_simd< typenameField::Element >::value >::type pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::ModularTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if<!support\_simd< typenameField::Element >::value >::type pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::ModularTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`void pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::GenericTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< support\_simd< typenameField::Element >::value >::type pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::UnparametricTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if<!support\_simd< typenameField::Element >::value >::type pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::UnparametricTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`void pfspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement\_ptr x, int ldx, typename Field::Element\_ptr y, int ldy, FieldCategories::ModularTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`void pfspmv (const Field &F, const SM &A, typename Field::ConstElement\_ptr x, typename Field::Element\_ptr y, FieldCategories::GenericTag, std::false_type)`
- `template<class Field , class SM >`
`void pfspmv (const Field &F, const SM &A, typename Field::ConstElement\_ptr x, typename Field::Element\_ptr y, FieldCategories::UnparametricTag, std::false_type)`

- `template<class Field, class SM >`
`void pfspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::ModularTag, std::false_type)`
- `template<class Field, class SM >`
`void pfspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::GenericTag, std::true_type)`
- `template<class Field, class SM >`
`void pfspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag, std::true_type)`
- `template<class Field, class SM >`
`void pfspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::ModularTag, std::true_type)`
- `template<class Field, class SM >`
`void fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, const typename Field::Element &beta, typename Field::Element_ptr y)`
- `template<class Field, class SM >`
`void fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, const typename Field::Element &beta, typename Field::Element_ptr y, int ldy)`

13.137.1 Macro Definition Documentation

13.137.1.1 `index_t`

```
#define index_t uint32_t
```

13.137.1.2 `ROUND_DOWN`

```
#define ROUND_DOWN(  
    x,  
    s ) ((x) & ~((s)-1))
```

13.137.1.3 `__FFLASFFPACK_CACHE_LINE_SIZE`

```
#define __FFLASFFPACK_CACHE_LINE_SIZE 64
```

13.137.1.4 `assume_aligned`

```
#define assume_aligned(  
    pout,  
    pin,  
    v ) decltype(pin) pout = pin;
```

13.137.1.5 `DENSE_THRESHOLD`

```
#define DENSE_THRESHOLD 0.5
```

13.138 `fflas_sparse.inl` File Reference

Namespaces

- namespace `FFLAS`
- namespace `FFLAS::sparse_details`

Macros

- `#define __FFLASFFPACK_fflas_fflas_sparse_INL`

Functions

- `template<class Field >`
`void init_y (const Field &F, const size_t m, const typename Field::Element b, typename Field::Element_ptr y)`
- `template<class Field >`
`void init_y (const Field &F, const size_t m, const size_t n, const typename Field::Element b, typename Field::Element_ptr y, const int ldy)`
- `template<class Field , class SM , class FC , class MZO >`
`std::enable_if<!(std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat >::value)||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag >::value)>::type fspmv_dispatch (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FC fc, MZO mzo)`
- `template<class Field , class SM , class FC , class MZO >`
`std::enable_if< std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat >::value)||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag >::value >::type fspmv_dispatch (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FC fc, MZO mzo)`
- `template<class Field , class SM >`
`void fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::GenericTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if<lisSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value &&support_simd< typenameField::Element >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if<lisSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::ModularTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value &&support_simd< typenameField::Element >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::ModularTag, NotZOSparseMatrix)`
- `template<class Field , class SM >`
`void fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::GenericTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if<lisSparseMatrixSimdFormat< Field, SM >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`std::enable_if< isSparseMatrixSimdFormat< Field, SM >::value &&support_simd< typenameField::Element >::value >::type fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag, ZOSparseMatrix)`
- `template<class Field , class SM >`
`void fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::ModularTag, std::true_type)`
- `template<class Field , class SM , class FCat , class MZO >`
`std::enable_if<!(std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat >::value)||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag >::value)>::type fspmm_dispatch (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FCat, MZO)`
- `template<class Field , class SM , class FCat , class MZO >`
`std::enable_if< std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineFloat >::value)||std::is_same< typenameElementTraits< typenameField::Element >::value, ElementCategories::MachineIntTag >::value >::type fspmm_dispatch (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FCat, MZO)`

- ```
>::value >::type fspmm_dispatch (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr
x, int ldx, typename Field::Element_ptr y, int ldy, FCat, MZO)
```
- `template<class Field, class SM >`  
`void fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx,`  
`typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag, NotZOSparseMatrix)`
  - `template<class Field, class SM >`  
`std::enable_if< support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM`  
`&A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy,`  
`FieldCategories::UnparametricTag, NotZOSparseMatrix)`
  - `template<class Field, class SM >`  
`std::enable_if<!support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM`  
`&A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy,`  
`FieldCategories::UnparametricTag, NotZOSparseMatrix)`
  - `template<class Field, class SM >`  
`std::enable_if< support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM`  
`&A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy,`  
`FieldCategories::ModularTag, NotZOSparseMatrix)`
  - `template<class Field, class SM >`  
`std::enable_if<!support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM`  
`&A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy,`  
`FieldCategories::ModularTag, NotZOSparseMatrix)`
  - `template<class Field, class SM >`  
`void fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx,`  
`typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag, ZOSparseMatrix)`
  - `template<class Field, class SM >`  
`std::enable_if< support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM`  
`&A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy,`  
`FieldCategories::UnparametricTag, ZOSparseMatrix)`
  - `template<class Field, class SM >`  
`std::enable_if<!support_simd< typenameField::Element >::value >::type fspmm (const Field &F, const SM`  
`&A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy,`  
`FieldCategories::UnparametricTag, ZOSparseMatrix)`
  - `template<class Field, class SM >`  
`void fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx,`  
`typename Field::Element_ptr y, int ldy, FieldCategories::ModularTag, ZOSparseMatrix)`
  - `template<class Field, class SM >`  
`void fspmv (const Field &F, const SM &A, typename Field::ConstElement_ptr x, const typename`  
`Field::Element &beta, typename Field::Element_ptr y)`
  - `template<class Field, class SM >`  
`void fspmm (const Field &F, const SM &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx,`  
`const typename Field::Element &beta, typename Field::Element_ptr y, int ldy)`

## 13.138.1 Macro Definition Documentation

### 13.138.1.1 \_\_FFLASFFPACK\_fflas\_fflas\_sparse\_INL

```
#define __FFLASFFPACK_fflas_fflas_sparse_INL
```

## 13.139 coo.h File Reference

```
#include "fflas-ffpack/fflas/fflas_sparse/coo/coo_utils.inl"
#include "fflas-ffpack/fflas/fflas_sparse/coo/coo_spmv.inl"
#include "fflas-ffpack/fflas/fflas_sparse/coo/coo_spmmm.inl"
```



## Data Structures

- struct [Sparse](#)< [\\_Field](#), [SparseMatrix\\_t::COO](#) >
- struct [Sparse](#)< [\\_Field](#), [SparseMatrix\\_t::COO\\_ZO](#) >

## Namespaces

- namespace [FFLAS](#)

## Functions

- template<class [Field](#) , class [IndexT](#) >  
void [sparse\\_init](#) (const [Field](#) &F, [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO](#) > &A, const [IndexT](#) \*row, const [IndexT](#) \*col, typename [Field::ConstElement\\_ptr](#) dat, [uint64\\_t](#) rowdim, [uint64\\_t](#) coldim, [uint64\\_t](#) nnz)
- template<class [Field](#) , class [IndexT](#) >  
void [sparse\\_init](#) (const [Field](#) &F, [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO\\_ZO](#) > &A, const [IndexT](#) \*row, const [IndexT](#) \*col, typename [Field::ConstElement\\_ptr](#) dat, [uint64\\_t](#) rowdim, [uint64\\_t](#) coldim, [uint64\\_t](#) nnz)
- template<class [Field](#) >  
void [sparse\\_delete](#) (const [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO](#) > &A)
- template<class [Field](#) >  
void [sparse\\_delete](#) (const [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO\\_ZO](#) > &A)

# 13.140 coo\_spmv.inl File Reference

## Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

## Macros

- #define [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_coo\\_spmv\\_INL](#)

## Functions

- template<class [Field](#) >  
void [fspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO](#) > &A, [size\\_t](#) blockSize, typename [Field::ConstElement\\_ptr](#) x\_, int ldx, typename [Field::Element\\_ptr](#) y\_, int ldy, [FieldCategories::GenericTag](#))
- template<class [Field](#) >  
void [fspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO](#) > &A, [size\\_t](#) blockSize, typename [Field::ConstElement\\_ptr](#) x\_, int ldx, typename [Field::Element\\_ptr](#) y\_, int ldy, [FieldCategories::UnparametricTag](#))
- template<class [Field](#) >  
void [fspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO](#) > &A, [size\\_t](#) blockSize, typename [Field::ConstElement\\_ptr](#) x\_, int ldx, typename [Field::Element\\_ptr](#) y\_, int ldy, const [int64\\_t](#) kmax)
- template<class [Field](#) >  
void [fspmv\\_simd\\_aligned](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO](#) > &A, [size\\_t](#) blockSize, typename [Field::ConstElement\\_ptr](#) x\_, int ldx, typename [Field::Element\\_ptr](#) y\_, int ldy, const [int64\\_t](#) kmax)
- template<class [Field](#) >  
void [fspmv\\_simd\\_unaligned](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO](#) > &A, [size\\_t](#) blockSize, typename [Field::ConstElement\\_ptr](#) x\_, int ldx, typename [Field::Element\\_ptr](#) y\_, int ldy, const [int64\\_t](#) kmax)
- template<class [Field](#) >  
void [fspmv\\_one](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO\\_ZO](#) > &A, [size\\_t](#) blockSize, typename [Field::ConstElement\\_ptr](#) x\_, int ldx, typename [Field::Element\\_ptr](#) y\_, int ldy, [FieldCategories::GenericTag](#))

- `template<class Field >`  
`void fspmm_mone (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmm_one_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm_one_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm_mone_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm_mone_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`

### 13.140.1 Macro Definition Documentation

#### 13.140.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_coo\_spmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_coo_spmv_INL
```

## 13.141 coo\_spmv.inl File Reference

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

### Macros

- `#define __FFLASFFPACK_fflas_sparse_coo_spmv_INL`

### Functions

- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::COO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::COO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::COO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const uint64_t kmax)`
- `template<class Field >`  
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::COO_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`



- template<class [Field](#) >  
void [fspmv\\_mone](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::UnparametricTag](#))

### 13.141.1 Macro Definition Documentation

#### 13.141.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_coo\_spmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_coo_spmv_INL
```

## 13.142 coo\_utils.inl File Reference

### Namespaces

- namespace [FFLAS](#)

### Macros

- #define [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_coo\\_utils\\_INL](#)

### Functions

- template<class [Field](#) >  
void [sparse\\_delete](#) (const [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO](#) > &A)
- template<class [Field](#) >  
void [sparse\\_delete](#) (const [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO\\_ZO](#) > &A)
- template<class [Field](#), class [IndexT](#) >  
void [sparse\\_init](#) (const [Field](#) &F, [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO](#) > &A, const [IndexT](#) \*row, const [IndexT](#) \*col, typename [Field::ConstElement\\_ptr](#) dat, [uint64\\_t](#) rowdim, [uint64\\_t](#) coldim, [uint64\\_t](#) nnz)
- template<class [Field](#), class [IndexT](#) >  
void [sparse\\_init](#) (const [Field](#) &F, [Sparse](#)< [Field](#), [SparseMatrix\\_t::COO\\_ZO](#) > &A, const [IndexT](#) \*row, const [IndexT](#) \*col, typename [Field::ConstElement\\_ptr](#) dat, [uint64\\_t](#) rowdim, [uint64\\_t](#) coldim, [uint64\\_t](#) nnz)

### 13.142.1 Macro Definition Documentation

#### 13.142.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_coo\_utils\_INL

```
#define __FFLASFFPACK_fflas_sparse_coo_utils_INL
```

## 13.143 csr.h File Reference

```
#include "fflas-ffpack/fflas/fflas_sparse/csr/csr_utils.inl"
#include "fflas-ffpack/fflas/fflas_sparse/csr/csr_spmv.inl"
#include "fflas-ffpack/fflas/fflas_sparse/csr/csr_spmv.inl"
```

### Data Structures

- struct [Sparse](#)< [\\_Field](#), [SparseMatrix\\_t::CSR](#) >
- struct [Sparse](#)< [\\_Field](#), [SparseMatrix\\_t::CSR\\_ZO](#) >

### Namespaces

- namespace [FFLAS](#)

## Functions

- `template<class Field, class IndexT >`  
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::CSR > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field, class IndexT >`  
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::CSR_ZO > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field >`  
`void sparse_delete (const Sparse< Field, SparseMatrix_t::CSR > &A)`
- `template<class Field >`  
`void sparse_delete (const Sparse< Field, SparseMatrix_t::CSR_ZO > &A)`

## 13.144 csr\_pspmm.inl File Reference

### Namespaces

- namespace `FFLAS`
- namespace `FFLAS::sparse_details_impl`

### Macros

- `#define __FFLASFFPACK_fflas_sparse_CSR_pspmm_INL`

### Functions

- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, const int64_t kmax)`
- `template<class Field >`  
`void pfspmm_one (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfspmm_mone (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfspmm_one (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void pfspmm_mone (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`

### 13.144.1 Macro Definition Documentation

#### 13.144.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_pspmm\_INL

```
#define __FFLASFFPACK_fflas_sparse_CSR_pspmm_INL
```

## 13.145 csr\_pspmv.inl File Reference

```
#include <thread>
```

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

### Macros

- #define [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_CSR\\_pspmv\\_INL](#)

### Functions

- template<class [Field](#) >  
void [pfpsmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::CSR](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::GenericTag](#))
- template<class [Field](#) >  
void [pfpsmv\\_task](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::CSR](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, const [index\\_t](#) iStart, const [index\\_t](#) iStop, [FieldCategories::UnparametricTag](#))
- template<class [Field](#) >  
void [pfpsmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::CSR](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::UnparametricTag](#))
- template<class [Field](#) >  
void [pfpsmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::CSR](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, const [int64\\_t](#) kmax)
- template<class [Field](#) >  
void [pfpsmv\\_one](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::CSR\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::GenericTag](#))
- template<class [Field](#) >  
void [pfpsmv\\_mone](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::CSR\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::GenericTag](#))
- template<class [Field](#) >  
void [pfpsmv\\_one](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::CSR\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::UnparametricTag](#))
- template<class [Field](#) >  
void [pfpsmv\\_mone](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::CSR\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::UnparametricTag](#))

### 13.145.1 Macro Definition Documentation

#### 13.145.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_pspmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_CSR_pspmv_INL
```

## 13.146 csr\_spmv.inl File Reference

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

### Macros

- #define [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_CSR\\_spmv\\_INL](#)

## Functions

- `template<class Field >`  
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, index_t blockSize, typename Field::ConstElement_ptr x_, index_t ldx, typename Field::Element_ptr y_, index_t ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, const int64_t kmax)`
- `template<class Field >`  
`void fspmm_one (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmm_mone (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmm_one_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm_one_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm_mone_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm_mone_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`

## 13.146.1 Macro Definition Documentation

### 13.146.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_spmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_CSR_spmv_INL
```

## 13.147 csr\_spmv.inl File Reference

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

## Macros

- `#define __FFLASFFPACK_fflas_sparse_CSR_spmv_INL`

## Functions

- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const int64_t kmax)`
- `template<class Field >`  
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`

### 13.147.1 Macro Definition Documentation

#### 13.147.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_spmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_CSR_spmv_INL
```

## 13.148 csr\_utils.inl File Reference

### Namespaces

- namespace `FFLAS`

### Functions

- `template<class Field >`  
`void sparse_delete (const Sparse< Field, SparseMatrix_t::CSR > &A)`
- `template<class Field >`  
`void sparse_delete (const Sparse< Field, SparseMatrix_t::CSR_ZO > &A)`
- `template<class Field >`  
`std::ostream & sparse_print (std::ostream &os, const Sparse< Field, SparseMatrix_t::CSR > &A)`
- `template<class IndexT >`  
`void sparse_init (const Givaro::Modular< Givaro::Integer > &F, Sparse< Givaro::Modular< Givaro::Integer >, SparseMatrix_t::CSR > &A, const IndexT *row, const IndexT *col, Givaro::Integer *dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class IndexT >`  
`void sparse_init (const Givaro::ZRing< Givaro::Integer > &F, Sparse< Givaro::ZRing< Givaro::Integer >, SparseMatrix_t::CSR_ZO > &A, const IndexT *row, const IndexT *col, Givaro::Integer *dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`

- `template<class IndexT, size_t RECINT_SIZE>`  
`void sparse_init (const Givaro::ZRing< RecInt::rmint< RECINT_SIZE > > &F, Sparse< Givaro::ZRing< RecInt::rmint< RECINT_SIZE > >, SparseMatrix_t::CSR_ZO > &A, const IndexT *row, const IndexT *col, typename Givaro::ZRing< RecInt::rmint< RECINT_SIZE > >::Element_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class IndexT, size_t RECINT_SIZE>`  
`void sparse_init (const Givaro::ZRing< RecInt::rmint< RECINT_SIZE > > &F, Sparse< Givaro::ZRing< RecInt::rmint< RECINT_SIZE > >, SparseMatrix_t::CSR > &A, const IndexT *row, const IndexT *col, typename Givaro::ZRing< RecInt::rmint< RECINT_SIZE > >::Element_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field, class IndexT >`  
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::CSR > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field, class IndexT >`  
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::CSR_ZO > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`

## 13.149 csr\_hyb.h File Reference

```
#include "fflas-ffpack/fflas/fflas_sparse/csr_hyb/csr_hyb_utils.inl"
#include "fflas-ffpack/fflas/fflas_sparse/csr_hyb/csr_hyb_spmv.inl"
#include "fflas-ffpack/fflas/fflas_sparse/csr_hyb/csr_hyb_spmmm.inl"
```

### Data Structures

- struct `Sparse< _Field, SparseMatrix_t::CSR_HYB >`

### Namespaces

- namespace `FFLAS`

### Functions

- `template<class Field >`  
`void sparse_delete (const Sparse< Field, SparseMatrix_t::CSR_HYB > &A)`
- `template<class Field, class IndexT >`  
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::CSR_HYB > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`

## 13.150 csr\_hyb\_pspmm.inl File Reference

### Namespaces

- namespace `FFLAS`
- namespace `FFLAS::sparse_details_impl`

### Macros

- `#define __FFLASFFPACK_fflas_sparse_CSR_HYB_pspmm_INL`

### Functions

- `template<class Field >`  
`void pspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::GenericTag)`

- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, type-`  
`name Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, type-`  
`name Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, type-`  
`name Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, type-`  
`name Field::ConstElement_ptr x, typename Field::Element_ptr y, const int64_t kmax)`
- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, type-`  
`name Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, const int64_t kmax)`

### 13.150.1 Macro Definition Documentation

#### 13.150.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_pspmm\_INL

```
#define __FFLASFFPACK_fflas_sparse_CSR_HYB_pspmm_INL
```

## 13.151 csr\_hyb\_pspmv.inl File Reference

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

### Macros

- `#define` [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_CSR\\_HYB\\_pspmv\\_INL](#)

### Functions

- `template<class Field >`  
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const int64_t kmax)`

### 13.151.1 Macro Definition Documentation

#### 13.151.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_pspmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_CSR_HYB_pspmv_INL
```

## 13.152 csr\_hyb\_spmv.inl File Reference

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

## Macros

- `#define __FFLASFFPACK_fflas_sparse_CSR_HYB_spmv_INL`

## Functions

- `template<class Field >`  
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, type-`  
`name Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, type-`  
`name Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, size_t blockSize, type-`  
`name Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, const int64_t kmax)`

### 13.152.1 Macro Definition Documentation

#### 13.152.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_spmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_CSR_HYB_spmv_INL
```

## 13.153 csr\_hyb\_spmv.inl File Reference

### Namespaces

- namespace `FFLAS`
- namespace `FFLAS::sparse_details_impl`

### Macros

- `#define __FFLASFFPACK_fflas_sparse_CSR_HYB_spmv_INL`

### Functions

- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::CSR_HYB > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const uint64_t kmax)`

### 13.153.1 Macro Definition Documentation

#### 13.153.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_spmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_CSR_HYB_spmv_INL
```

## 13.154 csr\_hyb\_utils.inl File Reference

### Data Structures

- struct `Info`
- struct `Coo< ValT, ldxT >`



## Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::csr\\_hyb\\_details](#)

## Macros

- `#define` [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_CSR\\_HYB\\_utils\\_INL](#)

## Functions

- `template<class Field >`  
void [sparse\\_delete](#) (const [Sparse](#)< [Field](#), [SparseMatrix\\_t::CSR\\_HYB](#) > &A)
- `template<class Field , class IndexT >`  
void [sparse\\_init](#) (const [Field](#) &F, [Sparse](#)< [Field](#), [SparseMatrix\\_t::CSR\\_HYB](#) > &A, const [IndexT](#) \*row, const [IndexT](#) \*col, typename [Field::ConstElement\\_ptr](#) dat, [uint64\\_t](#) rowdim, [uint64\\_t](#) coldim, [uint64\\_t](#) nnz)

## 13.154.1 Macro Definition Documentation

### 13.154.1.1 [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_CSR\\_HYB\\_utils\\_INL](#)

```
#define __FFLASFFPACK_fflas_sparse_CSR_HYB_utils_INL
```

## 13.155 ell.h File Reference

```
#include "fflas-ffpack/fflas/fflas_sparse/ell/ell_utils.inl"
#include "fflas-ffpack/fflas/fflas_sparse/ell/ell_spmv.inl"
#include "fflas-ffpack/fflas/fflas_sparse/ell/ell_spmmm.inl"
```

## Data Structures

- struct [Sparse](#)< [\\_Field](#), [SparseMatrix\\_t::ELL](#) >
- struct [Sparse](#)< [\\_Field](#), [SparseMatrix\\_t::ELL\\_ZO](#) >

## Namespaces

- namespace [FFLAS](#)

## Functions

- `template<class Field , class IndexT >`  
void [sparse\\_init](#) (const [Field](#) &F, [Sparse](#)< [Field](#), [SparseMatrix\\_t::ELL](#) > &A, const [IndexT](#) \*row, const [IndexT](#) \*col, typename [Field::ConstElement\\_ptr](#) dat, [uint64\\_t](#) rowdim, [uint64\\_t](#) coldim, [uint64\\_t](#) nnz)
- `template<class Field , class IndexT >`  
void [sparse\\_init](#) (const [Field](#) &F, [Sparse](#)< [Field](#), [SparseMatrix\\_t::ELL\\_ZO](#) > &A, const [IndexT](#) \*row, const [IndexT](#) \*col, typename [Field::ConstElement\\_ptr](#) dat, [uint64\\_t](#) rowdim, [uint64\\_t](#) coldim, [uint64\\_t](#) nnz)
- `template<class Field >`  
void [sparse\\_delete](#) (const [Sparse](#)< [Field](#), [SparseMatrix\\_t::ELL](#) > &A)
- `template<class Field >`  
void [sparse\\_delete](#) (const [Sparse](#)< [Field](#), [SparseMatrix\\_t::ELL\\_ZO](#) > &A)

## 13.156 ell\_pspmm.inl File Reference

## Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

## Macros

- `#define __FFLASFFPACK_fflas_sparse_ELL_pspmm_INL`

## Functions

- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, const int64_t kmax)`
- `template<class Field >`  
`void pfspmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, const int64_t kmax)`
- `template<class Field, class Func >`  
`void pfspmm_zo (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, Func &&func)`
- `template<class Field, class Func >`  
`void pfspmm_zo (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, Func &&func)`

## 13.156.1 Macro Definition Documentation

### 13.156.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_pspmm\_INL

```
#define __FFLASFFPACK_fflas_sparse_ELL_pspmm_INL
```

## 13.157 ell\_pspmv.inl File Reference

### Namespaces

- namespace `FFLAS`
- namespace `FFLAS::sparse_details_impl`

### Macros

- `#define __FFLASFFPACK_fflas_sparse_ELL_pspmv_INL`

### Functions

- `template<class Field >`  
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const int64_t kmax)`

- `template<class Field >`  
`void pfspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void pfspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`

### 13.157.1 Macro Definition Documentation

#### 13.157.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_pspmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_ELL_pspmv_INL
```

## 13.158 ell\_spmv.inl File Reference

### Namespaces

- namespace `FFLAS`
- namespace `FFLAS::sparse_details_impl`

### Macros

- `#define __FFLASFFPACK_fflas_sparse_ELL_spmv_INL`

### Functions

- `template<class Field >`  
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, const int64_t kmax)`
- `template<class Field >`  
`void fspmm_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmm_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmm_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy, FieldCategories::UnparametricTag)`

- `template<class Field >`  
`void fspmm_one_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A,`  
`size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy,`  
`FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm_one_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A,`  
`size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy,`  
`FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm_mone_simd_aligned (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A,`  
`size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy,`  
`FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmm_mone_simd_unaligned (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A,`  
`size_t blockSize, typename Field::ConstElement_ptr x_, int ldx, typename Field::Element_ptr y_, int ldy,`  
`FieldCategories::UnparametricTag)`

## 13.158.1 Macro Definition Documentation

### 13.158.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_spmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_ELL_spmv_INL
```

## 13.159 ell\_spmv.inl File Reference

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

### Macros

- `#define` [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_ELL\\_spmv\\_INL](#)

### Functions

- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, typename Field::ConstElement_ptr`  
`x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, typename Field::ConstElement_ptr`  
`x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL > &A, typename Field::ConstElement_ptr`  
`x_, typename Field::Element_ptr y_, const uint64_t kmax)`
- `template<class Field >`  
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_ZO > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`

## 13.159.1 Macro Definition Documentation

### 13.159.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_spmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_ELL_spmv_INL
```

## 13.160 ell\_utils.inl File Reference

```
#include <vector>
```

### Namespaces

- namespace [FFLAS](#)

### Macros

- #define [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_ELL\\_utils\\_INL](#)

### Functions

- template<class [Field](#) >  
void [sparse\\_delete](#) (const [Sparse](#)< [Field](#), [SparseMatrix\\_t::ELL](#) > &A)
- template<class [Field](#) >  
void [sparse\\_delete](#) (const [Sparse](#)< [Field](#), [SparseMatrix\\_t::ELL\\_ZO](#) > &A)
- template<class [Field](#) , class [IndexT](#) >  
void [sparse\\_init](#) (const [Field](#) &F, [Sparse](#)< [Field](#), [SparseMatrix\\_t::ELL](#) > &A, const [IndexT](#) \*row, const [IndexT](#) \*col, typename [Field::ConstElement\\_ptr](#) dat, uint64\_t rowdim, uint64\_t coldim, uint64\_t nnz)
- template<class [Field](#) , class [IndexT](#) >  
void [sparse\\_init](#) (const [Field](#) &F, [Sparse](#)< [Field](#), [SparseMatrix\\_t::ELL\\_ZO](#) > &A, const [IndexT](#) \*row, const [IndexT](#) \*col, typename [Field::ConstElement\\_ptr](#) dat, uint64\_t rowdim, uint64\_t coldim, uint64\_t nnz)

## 13.160.1 Macro Definition Documentation

### 13.160.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_utils\_INL

```
#define __FFLASFFPACK_fflas_sparse_ELL_utils_INL
```

## 13.161 ell\_simd.h File Reference

```
#include "fflas-ffpack/fflas/fflas_sparse/ell_simd/ell_simd_utils.inl"
#include "fflas-ffpack/fflas/fflas_sparse/ell_simd/ell_simd_spmv.inl"
```

### Data Structures

- struct [Sparse](#)< [\\_Field](#), [SparseMatrix\\_t::ELL\\_simd](#) >
- struct [Sparse](#)< [\\_Field](#), [SparseMatrix\\_t::ELL\\_simd\\_ZO](#) >

### Namespaces

- namespace [FFLAS](#)

### Functions

- template<class [Field](#) , class [IndexT](#) >  
void [sparse\\_init](#) (const [Field](#) &F, [Sparse](#)< [Field](#), [SparseMatrix\\_t::ELL\\_simd](#) > &A, const [IndexT](#) \*row, const [IndexT](#) \*col, typename [Field::ConstElement\\_ptr](#) dat, uint64\_t rowdim, uint64\_t coldim, uint64\_t nnz)

- `template<class Field, class IndexT >`  
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, const IndexT *row,`  
`const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field >`  
`void sparse_delete (const Sparse< Field, SparseMatrix_t::ELL_simd > &A)`
- `template<class Field >`  
`void sparse_delete (const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A)`

## 13.162 ell\_simd\_pspmv.inl File Reference

### Namespaces

- namespace `FFLAS`
- namespace `FFLAS::sparse_details_impl`

### Macros

- `#define __FFLASFFPACK_fflas_sparse_ELL_simd_pspmv_INL`

### Functions

- `template<class Field >`  
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void pfspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const uint64_t kmax)`
- `template<class Field >`  
`void pfspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void pfspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename`  
`Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`

### 13.162.1 Macro Definition Documentation

#### 13.162.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_simd\_pspmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_ELL_simd_pspmv_INL
```

## 13.163 ell\_simd\_spmv.inl File Reference

### Namespaces

- namespace `FFLAS`
- namespace `FFLAS::sparse_details_impl`

## Macros

- `#define __FFLASFFPACK_fflas_sparse_ELL_simd_spmv_INL`

## Functions

- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmv_simd (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmv_simd (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const uint64_t kmax)`
- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, const uint64_t kmax)`
- `template<class Field >`  
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::GenericTag)`
- `template<class Field >`  
`void fspmv_one (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmv_mone (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmv_one_simd (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void fspmv_mone_simd (const Field &F, const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, typename Field::ConstElement_ptr x_, typename Field::Element_ptr y_, FieldCategories::UnparametricTag)`

### 13.163.1 Macro Definition Documentation

#### 13.163.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_simd\_spmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_ELL_simd_spmv_INL
```

## 13.164 ell\_simd\_utils.inl File Reference

### Namespaces

- namespace `FFLAS`

### Macros

- `#define __FFLASFFPACK_fflas_sparse_ELL_simd_utils_INL`

## Functions

- `template<class Field >`  
`void sparse_delete (const Sparse< Field, SparseMatrix_t::ELL_simd > &A)`
- `template<class Field >`  
`void sparse_delete (const Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A)`
- `template<class Field >`  
`void sparse_print (const Sparse< Field, SparseMatrix_t::ELL_simd > &A)`
- `template<class Field , class IndexT >`  
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::ELL_simd > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`
- `template<class Field , class IndexT >`  
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`

## 13.164.1 Macro Definition Documentation

### 13.164.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_simd\_utils\_INL

```
#define __FFLASFFPACK_fflas_sparse_ELL_simd_utils_INL
```

## 13.165 hyb\_zo.h File Reference

```
#include "fflas-ffpack/fflas/fflas_sparse/hyb_zo/hyb_zo_utils.inl"
#include "fflas-ffpack/fflas/fflas_sparse/hyb_zo/hyb_zo_spmv.inl"
#include "fflas-ffpack/fflas/fflas_sparse/hyb_zo/hyb_zo_spm্ম.inl"
```

## Data Structures

- `struct Sparse< _Field, SparseMatrix_t::HYB_ZO >`

## Namespaces

- namespace `FFLAS`

## 13.166 hyb\_zo\_pspmm.inl File Reference

## Namespaces

- namespace `FFLAS`
- namespace `FFLAS::sparse_details_impl`

## Macros

- `#define __FFLASFFPACK_fflas_sparse_HYB_ZO_pspmm_INL`

## Functions

- `template<class Field >`  
`void pfsppmm (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, size_t blockSize, type-  
name Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::GenericTag)`
- `template<class Field >`  
`void pfsppmm (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, size_t blockSize, type-  
name Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, FieldCategories::UnparametricTag)`
- `template<class Field >`  
`void pfsppmm (const Field &F, const Sparse< Field, SparseMatrix_t::HYB_ZO > &A, size_t blockSize, type-  
name Field::ConstElement_ptr x, int ldx, typename Field::Element_ptr y, int ldy, uint64_t kmax)`



## 13.166.1 Macro Definition Documentation

### 13.166.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_pspmm\_INL

```
#define __FFLASFFPACK_fflas_sparse_HYB_ZO_pspmm_INL
```

## 13.167 hyb\_zo\_pspmv.inl File Reference

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

### Macros

- #define [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_HYB\\_ZO\\_pspmv\\_INL](#)

### Functions

- template<class [Field](#) >  
void [pfspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::HYB\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x, typename [Field::Element\\_ptr](#) y, [FieldCategories::GenericTag](#))
- template<class [Field](#) >  
void [pfspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::HYB\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x, typename [Field::Element\\_ptr](#) y, [FieldCategories::UnparametricTag](#))
- template<class [Field](#) >  
void [pfspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::HYB\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x, typename [Field::Element\\_ptr](#) y, uint64\_t kmax)

## 13.167.1 Macro Definition Documentation

### 13.167.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_pspmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_HYB_ZO_pspmv_INL
```

## 13.168 hyb\_zo\_spmv.inl File Reference

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

### Macros

- #define [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_HYB\\_ZO\\_spmv\\_INL](#)

### Functions

- template<class [Field](#) >  
void [fspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::HYB\\_ZO](#) > &A, size\_t blockSize, typename [Field::ConstElement\\_ptr](#) x, int ldx, typename [Field::Element\\_ptr](#) y, int ldy, [FieldCategories::GenericTag](#))
- template<class [Field](#) >  
void [fspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::HYB\\_ZO](#) > &A, size\_t blockSize, typename [Field::ConstElement\\_ptr](#) x, int ldx, typename [Field::Element\\_ptr](#) y, int ldy, [FieldCategories::UnparametricTag](#))
- template<class [Field](#) >  
void [fspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::HYB\\_ZO](#) > &A, size\_t blockSize, typename [Field::ConstElement\\_ptr](#) x, int ldx, typename [Field::Element\\_ptr](#) y, int ldy, uint64\_t kmax)

### 13.168.1 Macro Definition Documentation

#### 13.168.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_spmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_HYB_ZO_spmv_INL
```

## 13.169 hyb\_zo\_spmv.inl File Reference

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

### Macros

- #define [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_HYB\\_ZO\\_spmv\\_INL](#)

### Functions

- template<class [Field](#) >  
void [fspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::HYB\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x, typename [Field::Element\\_ptr](#) y, [FieldCategories::GenericTag](#))
- template<class [Field](#) >  
void [fspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::HYB\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x, typename [Field::Element\\_ptr](#) y, [FieldCategories::UnparametricTag](#))
- template<class [Field](#) >  
void [fspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::HYB\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x, typename [Field::Element\\_ptr](#) y, [uint64\\_t](#) kmax)

### 13.169.1 Macro Definition Documentation

#### 13.169.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_spmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_HYB_ZO_spmv_INL
```

## 13.170 hyb\_zo\_utils.inl File Reference

### Namespaces

- namespace [FFLAS](#)

### Macros

- #define [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_HYB\\_ZO\\_utils\\_INL](#)

### Functions

- template<class [Field](#) >  
void [sparse\\_delete](#) (const [Sparse](#)< [Field](#), [SparseMatrix\\_t::HYB\\_ZO](#) > &A)
- template<class [Field](#) , class [IndexT](#) >  
void [sparse\\_init](#) (const [Field](#) &F, [Sparse](#)< [Field](#), [SparseMatrix\\_t::HYB\\_ZO](#) > &A, const [IndexT](#) \*row, const [IndexT](#) \*col, typename [Field::ConstElement\\_ptr](#) dat, [uint64\\_t](#) rowdim, [uint64\\_t](#) coldim, [uint64\\_t](#) nnz)
- template<typename [\\_Field](#) >  
std::ostream & [operator<<](#) (std::ostream &os, const [Sparse](#)< [\\_Field](#), [SparseMatrix\\_t::HYB\\_ZO](#) > &A)

### 13.170.1 Macro Definition Documentation

#### 13.170.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_utils\_INL

```
#define __FFLASFFPACK_fflas_sparse_HYB_ZO_utils_INL
```

## 13.171 read\_sparse.h File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <fstream>
#include <string>
#include <cstdlib>
#include <iterator>
```

### Data Structures

- struct [Coo< Field >](#)
- struct [readMyMachineType< Field, T >](#)
- struct [readMyMachineType< Field, mpz\\_t >](#)

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::details\\_spmv](#)

### Macros

- [#define DNS\\_BIN\\_VER 0](#)
- [#define mask\\_t uint64\\_t](#)

### Functions

- [template<class Field, bool sorted = true, bool read\\_integer = false>  
void readSmsFormat \(const std::string &path, const Field &f, index\\_t \\*&row, index\\_t \\*&col, typename Field::Element\\_ptr &val, index\\_t &rowdim, index\\_t &coldim, uint64\\_t &n nz\)](#)
- [template<class Field >  
void readSprFormat \(const std::string &path, const Field &f, index\\_t \\*&row, index\\_t \\*&col, typename Field::Element\\_ptr &val, index\\_t &rowdim, index\\_t &coldim, uint64\\_t &n nz\)](#)
- [template<class T >  
std::enable\\_if< std::is\\_integral< T >::value, int > getDataType \(\)](#)
- [template<class T >  
std::enable\\_if< std::is\\_floating\\_point< T >::value, int > getDataType \(\)](#)
- [template<class T >  
std::enable\\_if< std::is\\_same< T, mpz\\_t >::value, int > getDataType \(\)](#)
- [template<class T >  
int getDataType \(\)](#)
- [template<class Field >  
void readMachineType \(const Field &F, typename Field::Element &modulo, typename Field::Element\\_ptr val, std::ifstream &file, const uint64\\_t dims, const mask\\_t data\\_type, const mask\\_t field\\_desc\)](#)
- [template<class Field >  
void readDnsFormat \(const std::string &path, const Field &F, index\\_t &rowdim, index\\_t &coldim, typename Field::Element\\_ptr &val\)](#)
- [template<class Field >  
void writeDnsFormat \(const std::string &path, const Field &F, const index\\_t &rowdim, const index\\_t &coldim, typename Field::Element\\_ptr A, index\\_t ldA\)](#)

### 13.171.1 Macro Definition Documentation

#### 13.171.1.1 DNS\_BIN\_VER

```
#define DNS_BIN_VER 0
```

### 13.171.1.2 mask\_t

```
#define mask_t uint64_t
```

## 13.172 sell.h File Reference

```
#include "fflas-ffpack/fflas/fflas_sparse/sell/sell_utils.inl"
#include "fflas-ffpack/fflas/fflas_sparse/sell/sell_spmv.inl"
```

### Data Structures

- struct [Sparse<\\_Field, SparseMatrix\\_t::SELL>](#)
- struct [Sparse<\\_Field, SparseMatrix\\_t::SELL\\_ZO>](#)

### Namespaces

- namespace [FFLAS](#)

## 13.173 sell\_pspmv.inl File Reference

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

### Macros

- #define [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_sell\\_pspmv\\_INL](#)

### Functions

- template<class [Field](#)>  
void [pfspmv](#) (const [Field](#) &F, const [Sparse<Field, SparseMatrix\\_t::SELL>](#) &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::GenericTag](#))
- template<class [Field](#)>  
void [pfspmv](#) (const [Field](#) &F, const [Sparse<Field, SparseMatrix\\_t::SELL>](#) &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::UnparametricTag](#))
- template<class [Field](#)>  
void [pfspmv](#) (const [Field](#) &F, const [Sparse<Field, SparseMatrix\\_t::SELL>](#) &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, const int64\_t kmax)
- template<class [Field](#)>  
void [pfspmv\\_one](#) (const [Field](#) &F, const [Sparse<Field, SparseMatrix\\_t::SELL\\_ZO>](#) &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::GenericTag](#))
- template<class [Field](#)>  
void [pfspmv\\_mone](#) (const [Field](#) &F, const [Sparse<Field, SparseMatrix\\_t::SELL\\_ZO>](#) &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::GenericTag](#))
- template<class [Field](#)>  
void [pfspmv\\_one](#) (const [Field](#) &F, const [Sparse<Field, SparseMatrix\\_t::SELL\\_ZO>](#) &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::UnparametricTag](#))
- template<class [Field](#)>  
void [pfspmv\\_mone](#) (const [Field](#) &F, const [Sparse<Field, SparseMatrix\\_t::SELL\\_ZO>](#) &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::UnparametricTag](#))

## 13.173.1 Macro Definition Documentation

### 13.173.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_sell\_pspmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_sell_pspmv_INL
```

## 13.174 sell\_spmv.inl File Reference

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sparse\\_details\\_impl](#)

### Macros

- `#define` [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_sell\\_spmv\\_INL](#)

### Functions

- `template<class Field >`  
void [fspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::SELL](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::GenericTag](#))
- `template<class Field >`  
void [fspmv\\_simd](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::SELL](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::UnparametricTag](#))
- `template<class Field >`  
void [fspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::SELL](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::UnparametricTag](#))
- `template<class Field >`  
void [fspmv\\_simd](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::SELL](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, const [uint64\\_t](#) kmax)
- `template<class Field >`  
void [fspmv](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::SELL](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, const [uint64\\_t](#) kmax)
- `template<class Field >`  
void [fspmv\\_one](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::SELL\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::GenericTag](#))
- `template<class Field >`  
void [fspmv\\_mone](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::SELL\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::GenericTag](#))
- `template<class Field >`  
void [fspmv\\_one\\_simd](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::SELL\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::UnparametricTag](#))
- `template<class Field >`  
void [fspmv\\_mone\\_simd](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::SELL\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::UnparametricTag](#))
- `template<class Field >`  
void [fspmv\\_one](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::SELL\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::UnparametricTag](#))
- `template<class Field >`  
void [fspmv\\_mone](#) (const [Field](#) &F, const [Sparse](#)< [Field](#), [SparseMatrix\\_t::SELL\\_ZO](#) > &A, typename [Field::ConstElement\\_ptr](#) x\_, typename [Field::Element\\_ptr](#) y\_, [FieldCategories::UnparametricTag](#))

### 13.174.1 Macro Definition Documentation

#### 13.174.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_sell\_spmv\_INL

```
#define __FFLASFFPACK_fflas_sparse_sell_spmv_INL
```

## 13.175 sell\_utils.inl File Reference

### Data Structures

- struct [Info](#)
- struct [Coo](#)< [ValT](#), [IdxT](#) >

## Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::sell\\_details](#)

## Macros

- `#define` [\\_\\_FFLASFFPACK\\_fflas\\_sparse\\_sell\\_utils\\_INL](#)

## Functions

- `template<class Field >`  
`void fspmv (const Field &F, const Sparse< Field, SparseMatrix_t::SELL_ZO > &A, typename Field::ConstElement_ptr x, typename Field::Element_ptr y, FieldCategories::ModularTag)`
- `template<class Field >`  
`void sparse_delete (const Sparse< Field, SparseMatrix_t::SELL > &A)`
- `template<class Field >`  
`void sparse_delete (const Sparse< Field, SparseMatrix_t::SELL_ZO > &A)`
- `template<class Field >`  
`void sparse_print (const Sparse< Field, SparseMatrix_t::SELL > &A)`
- `template<class Field, class IndexT >`  
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::SELL > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz, uint64_t sigma=0)`
- `template<class Field, class IndexT >`  
`void sparse_init (const Field &F, Sparse< Field, SparseMatrix_t::SELL_ZO > &A, const IndexT *row, const IndexT *col, typename Field::ConstElement_ptr dat, uint64_t rowdim, uint64_t coldim, uint64_t nnz)`

### 13.175.1 Macro Definition Documentation

#### 13.175.1.1 \_\_FFLASFFPACK\_fflas\_sparse\_sell\_utils\_INL

```
#define __FFLASFFPACK_fflas_sparse_sell_utils_INL
```

## 13.176 sparse\_matrix\_traits.h File Reference

```
#include <type_traits>
```

## Data Structures

- struct [isSparseMatrix< Field, M >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::CSR > >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::CSR\\_ZO > >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::COO > >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::COO\\_ZO > >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::ELL > >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::ELL\\_ZO > >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::SELL > >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::SELL\\_ZO > >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::ELL\\_simd > >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::ELL\\_simd\\_ZO > >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::CSR\\_HYB > >](#)
- struct [isSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::HYB\\_ZO > >](#)
- struct [isZOSparseMatrix< F, M >](#)
- struct [isZOSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::CSR\\_ZO > >](#)
- struct [isZOSparseMatrix< Field, Sparse< Field, SparseMatrix\\_t::COO\\_ZO > >](#)

- struct `isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_ZO > >`
- struct `isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::SELL_ZO > >`
- struct `isZOSparseMatrix< Field, Sparse< Field, SparseMatrix_t::ELL_simd_ZO > >`
- struct `isSparseMatrixSimdFormat< F, M >`
- struct `isSparseMatrixMKLFormat< F, M >`
- struct `tfn_plus`
- struct `tfn_mul`
- struct `tfn_mul_eq`
- struct `tfn_minus`
- struct `tfn_plus_eq`
- struct `tfn_minus_eq`
- struct `has_plus_impl< C >`
- struct `has_mul_impl< C >`
- struct `has_mul_eq_impl< C >`
- struct `has_plus_eq_impl< C >`
- struct `has_minus_eq_impl< C >`
- struct `has_minus_impl< C >`
- struct `has_operation< T >`

## Namespaces

- namespace `FFLAS`

## Typedefs

- using `ZOSparseMatrix` = `std::true_type`
- using `NotZOSparseMatrix` = `std::false_type`
- using `SimdSparseMatrix` = `std::true_type`
- using `NoSimdSparseMatrix` = `std::false_type`
- using `MKLSparseMatrixFormat` = `std::true_type`
- using `NotMKLSparseMatrixFormat` = `std::false_type`
- template<class T >  
using `has_plus` = `typename std::conditional< std::is_arithmetic< T >::value, std::true_type, has_plus_impl< T > >::type`
- template<class T >  
using `has_minus` = `typename std::conditional< std::is_arithmetic< T >::value, std::true_type, has_minus_impl< T > >::type`
- template<class T >  
using `has_equal` = `typename std::conditional< std::is_arithmetic< T >::value, std::true_type, std::is_copyable_&assignable< T > >::type`
- template<class T >  
using `has_plus_eq` = `typename std::conditional< std::is_arithmetic< T >::value, std::true_type, has_plus_eq_impl< T > >::type`
- template<class T >  
using `has_minus_eq` = `typename std::conditional< std::is_arithmetic< T >::value, std::true_type, has_minus_eq_impl< T > >::type`
- template<class T >  
using `has_mul` = `typename std::conditional< std::is_arithmetic< T >::value, std::true_type, has_mul_impl< T > >::type`
- template<class T >  
using `has_mul_eq` = `typename std::conditional< std::is_arithmetic< T >::value, std::true_type, has_mul_eq_impl< T > >::type`

## 13.177 utils.h File Reference

```
#include <algorithm>
#include <numeric>
#include <vector>
```

### Data Structures

- struct [StatsMatrix](#)

### Namespaces

- namespace [FFLAS](#)

### Functions

- template<class It >  
double [computeDeviation](#) (It begin, It end)
- template<class Field >  
[StatsMatrix](#) [getStat](#) (const [Field](#) &F, const [index\\_t](#) \*row, const [index\\_t](#) \*col, typename [Field::ConstElement\\_ptr](#) val, uint64\_t rowdim, uint64\_t coldim, uint64\_t nnz)

## 13.178 fflas\_transpose.h File Reference

transpose the storage of the matrix (switch between row and col major mode)

```
#include "fflas-ffpack/utils/debug.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/fflas_memory.h"
#include "fflas-ffpack/fflas/fflas_simd.h"
```

### Data Structures

- struct [BlockTransposeSIMD](#)< [Field](#), [Simd](#), >

### Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::\\_ftranspose\\_impl](#)

### Macros

- #define [FFLAS\\_TRANSPOSE\\_BLOCKSIZE](#) 32
- #define [LD](#)(i) [R##i=Simd::loadu\(A+lda\\*i\)](#)
- #define [ST](#)(i) [Simd::storeu\(B+ldb\\*i,R##i\)](#)

### Functions

- template<size\_t bs, typename [Field](#) , typename [BTSimd](#) >  
void [not\\_inplace](#) (const [Field](#) &F, const [BTSimd](#) &BTS, const size\_t m, const size\_t n, typename [Field::ConstElement\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) B, const size\_t ldb)
- template<size\_t bs, typename [Field](#) , typename [BTSimd](#) >  
void [square\\_inplace](#) (const [Field](#) &F, const [BTSimd](#) &BTS, const size\_t m, typename [Field::Element\\_ptr](#) A, const size\_t lda)
- template<size\_t bs, typename [Field](#) , typename [BTSimd](#) >  
void [nonsquare\\_inplace\\_v1](#) (const [Field](#) &F, const [BTSimd](#) &BTS, const size\_t m, const size\_t n, typename [Field::Element\\_ptr](#) A)



- `template<size_t bs, typename Field, typename BTSimd >`  
`void nonsquare_inplace_v2 (const Field &F, const BTSimd &BTS, const size_t m, const size_t n, typename Field::Element_ptr A)`

### 13.178.1 Detailed Description

transpose the storage of the matrix (switch between row and col major mode)

### 13.178.2 Macro Definition Documentation

#### 13.178.2.1 FFLAS\_TRANSPOSE\_BLOCKSIZE

```
#define FFLAS_TRANSPOSE_BLOCKSIZE 32
```

#### 13.178.2.2 LD

```
#define LD(
 i) R##i=Simd::loadu(A+lda*i)
```

#### 13.178.2.3 ST

```
#define ST(
 i) Simd::storeu(B+ldb*i,R##i)
```

## 13.179 ffpack.dox File Reference

## 13.180 ffpack.h File Reference

Set of elimination based routines for dense linear algebra.

```
#include "givaro/givpoly1.h"
#include <fflas-ffpack/fflas-ffpack-config.h>
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/fflas/fflas_helpers.inl"
#include <list>
#include <vector>
#include <iostream>
#include <algorithm>
#include "fflas-ffpack/checkers/checkers_ffpack.h"
#include "ffpack_fgesv.inl"
#include "ffpack_fgetrs.inl"
#include "fflas-ffpack/checkers/checkers_ffpack.inl"
#include "ffpack_pluq.inl"
#include "ffpack_pluq_mp.inl"
#include "ffpack_ppluq.inl"
#include "ffpack_ludivine.inl"
#include "ffpack_ludivine_mp.inl"
#include "ffpack_echelonforms.inl"
#include "ffpack_fsytrf.inl"
#include "ffpack_invert.inl"
#include "ffpack_ftrtr.inl"
#include "ffpack_ftrstr.inl"
#include "ffpack_ftrssyr2k.inl"
#include "ffpack_charpoly_kglu.inl"
#include "ffpack_charpoly_kgfast.inl"
#include "ffpack_charpoly_kgfastgeneralized.inl"
#include "ffpack_charpoly_danilevski.inl"
#include "ffpack_charpoly.inl"
#include "ffpack_frobenius.inl"
```

```
#include "ffpack_minpoly.inl"
#include "ffpack_krylovelim.inl"
#include "ffpack_permutation.inl"
#include "ffpack_rankprofiles.inl"
#include "ffpack_det_mp.inl"
#include "ffpack_bruhatgen.inl"
#include "ffpack.inl"
```

## Data Structures

- class [CharpolyFailed](#)

## Namespaces

- namespace [FFPACK](#)  
*Finite Field PACK Set of elimination based routines for dense linear algebra.*
- namespace [FFPACK::Protected](#)

## Macros

- `#define __FFLASFFPACK_FTRSTR_THRESHOLD 64`
- `#define __FFLASFFPACK_FTRSSYR2K_THRESHOLD 64`

## Functions

- void [LAPACKPerm2MathPerm](#) (size\_t \*MathP, const size\_t \*LapackP, const size\_t N)  
*Conversion of a permutation from LAPACK format to Math format.*
- void [MathPerm2LAPACKPerm](#) (size\_t \*LapackP, const size\_t \*MathP, const size\_t N)  
*Conversion of a permutation from Maths format to LAPACK format.*
- template<class [Field](#) >  
void [applyP](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const [FFLAS::FFLAS\\_TRANSPOSE](#) Trans, const size\_t M, const size\_t ibeg, const size\_t iend, typename [Field::Element\\_ptr](#) A, const size\_t lda, const size\_t \*P)  
*Computes  $P1 \times \text{Diag}(I_R, P2)$  where  $P1$  is a LAPACK and  $P2$  a LAPACK permutation and store the result in  $P1$  as a LAPACK permutation.*
- template<class [Field](#) >  
void [applyP](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const [FFLAS::FFLAS\\_TRANSPOSE](#) Trans, const size\_t m, const size\_t ibeg, const size\_t iend, typename [Field::Element\\_ptr](#) A, const size\_t lda, const size\_t \*P, const [FFLAS::ParSeqHelper::Sequential](#) seq)
- template<class [Field](#) , class Cut , class Param >  
void [applyP](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const [FFLAS::FFLAS\\_TRANSPOSE](#) Trans, const size\_t m, const size\_t ibeg, const size\_t iend, typename [Field::Element\\_ptr](#) A, const size\_t lda, const size\_t \*P, const [FFLAS::ParSeqHelper::Parallel](#)< Cut, Param > par)
- template<class [Field](#) >  
void [MonotonicApplyP](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const [FFLAS::FFLAS\\_TRANSPOSE](#) Trans, const size\_t M, const size\_t ibeg, const size\_t iend, typename [Field::Element\\_ptr](#) A, const size\_t lda, const size\_t \*P, const size\_t R)  
*Apply a R-monotonically increasing permutation P, to the matrix A.*
- template<class [Field](#) >  
void [fgetrs](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t R, typename [Field::Element\\_ptr](#) A, const size\_t lda, const size\_t \*P, const size\_t \*Q, typename [Field::Element\\_ptr](#) B, const size\_t ldb, int \*info)  
*Solve the system  $AX = B$  or  $XA = B$ .*

- template<class [Field](#) >  
[Field::Element\\_ptr](#) fgetrs (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t NRHS, const size\_t R, typename [Field::Element\\_ptr](#) A, const size\_t lda, const size\_t \*P, const size\_t \*Q, typename [Field::Element\\_ptr](#) X, const size\_t ldX, typename [Field::ConstElement\\_ptr](#) B, const size\_t ldb, int \*info)  
*Solve the system  $A X = B$  or  $X A = B$ .*
- template<class [Field](#) >  
size\_t fgesv (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) B, const size\_t ldb, int \*info)  
*Square system solver.*
- template<class [Field](#) >  
size\_t fgesv (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t NRHS, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) X, const size\_t ldX, typename [Field::ConstElement\\_ptr](#) B, const size\_t ldb, int \*info)  
*Rectangular system solver.*
- template<class [Field](#) >  
void ftrtri (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) Uplo, const [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, const size\_t threshold=\_\_FFLASFFPACK\_FTRTRI\_THRESHOLD)  
*Compute the inverse of a triangular matrix.*
- template<class [Field](#) >  
void trinv\_left (const [Field](#) &F, const size\_t N, typename [Field::ConstElement\\_ptr](#) L, const size\_t ldL, typename [Field::Element\\_ptr](#) X, const size\_t ldX)
- template<class [Field](#) >  
void ftrtrm (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) side, const [FFLAS::FFLAS\\_DIAG](#) diag, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda)  
*Compute the product of two triangular matrices of opposite shape.*
- template<class [Field](#) >  
void ftrstr (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) side, const [FFLAS::FFLAS\\_UPLO](#) Uplo, const [FFLAS::FFLAS\\_DIAG](#) diagA, const [FFLAS::FFLAS\\_DIAG](#) diagB, const size\_t N, typename [Field::ConstElement\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) B, const size\_t ldb, const size\_t threshold=\_\_FFLASFFPACK\_FTRSTR\_THRESHOLD)  
*Solve a triangular system with a triangular right hand side of the same shape.*
- template<class [Field](#) >  
void ftrssyr2k (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) Uplo, const [FFLAS::FFLAS\\_DIAG](#) diagA, const size\_t N, typename [Field::ConstElement\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) B, const size\_t ldb, const size\_t threshold=\_\_FFLASFFPACK\_FTRSSYR2K\_THRESHOLD)  
*Solve a triangular system in a symmetric sum: find B upper/lower triangular such that  $A^T B + B^T A = C$  where C is symmetric.*
- template<class [Field](#) >  
bool fsytrf (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) UpLo, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, const size\_t threshold=\_\_FFLASFFPACK\_FSYTRF\_THRESHOLD)  
*Triangular factorization of symmetric matrices.*
- template<class [Field](#) >  
bool fsytrf (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) UpLo, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, const [FFLAS::ParSeqHelper::Sequential](#) seq, const size\_t threshold=\_\_FFLASFFPACK\_FSYTRF\_THRESHOLD)
- template<class [Field](#) , class [Cut](#) , class [Param](#) >  
bool fsytrf (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) UpLo, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, const [FFLAS::ParSeqHelper::Parallel](#)< [Cut](#) , [Param](#) > par, const size\_t threshold=\_\_FFLASFFPACK\_FSYTRF\_THRESHOLD)
- template<class [Field](#) >  
bool fsytrf\_nonunit (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) UpLo, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) D, const size\_t incD, const size\_t threshold=\_\_FFLASFFPACK\_FSYTRF\_THRESHOLD)  
*Triangular factorization of symmetric matrices.*
- template<class [Field](#) >  
size\_t PLUQ (const [Field](#) &F, const [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*P, size\_t \*Q)

*Compute a PLUQ factorization of the given matrix.*

- `template<class Field >`  
`size_t pPLUQ (const Field &F, const FFLAS::FFLAS_DIAG Diag, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Q)`
- `template<class Field >`  
`size_t PLUQ (const Field &F, const FFLAS::FFLAS_DIAG Diag, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Q, const FFLAS::ParSeqHelper::Sequential &PSHelper, size_t BCThreshold=__FFLASFFPACK_PLUQ_THRESHOLD)`
- `template<class Field, class Cut, class Param >`  
`size_t PLUQ (const Field &F, const FFLAS::FFLAS_DIAG Diag, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Q, const FFLAS::ParSeqHelper::Parallel< Cut, Param > &PSHelper)`
- `template<class Field >`  
`size_t LUdivine (const Field &F, const FFLAS::FFLAS_DIAG Diag, const FFLAS::FFLAS_TRANSPOSE trans, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const FFPACK_LU_TAG LuTag=FfpackSlabRecursive, const size_t cutoff=__FFLASFFPACK_LUDIVINE_THRESHOLD)`

*Compute the CUP or PLE factorization of the given matrix.*

- `template<class Field >`  
`size_t LUdivine_construct (const Field &F, const FFLAS::FFLAS_DIAG Diag, const size_t M, const size_t N, typename Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr X, const size_t ldx, typename Field::Element_ptr u, const size_t incu, size_t *P, bool computeX, const FFPACK_MINPOLY_TAG MinTag=FfpackDense, const size_t kg_mc=0, const size_t kg_mb=0, const size_t kg_j=0)`
- `template<class Field >`  
`size_t ColumnEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, bool transform=false, const FFPACK_LU_TAG LuTag=FfpackSlabRecursive)`

*Compute the Column Echelon form of the input matrix in-place.*

- `template<class Field >`  
`size_t pColumnEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, bool transform=false, size_t numthreads=0, const FFPACK_LU_TAG LuTag=FfpackTileRecursive)`
- `template<class Field, class PSHelper >`  
`size_t ColumnEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const bool transform, const FFPACK_LU_TAG LuTag, const PSHelper &psH)`
- `template<class Field >`  
`size_t RowEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const bool transform=false, const FFPACK_LU_TAG LuTag=FfpackSlabRecursive)`

*Compute the Row Echelon form of the input matrix in-place.*

- `template<class Field >`  
`size_t pRowEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const bool transform=false, size_t numthreads=0, const FFPACK_LU_TAG LuTag=FfpackTileRecursive)`
- `template<class Field, class PSHelper >`  
`size_t RowEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const bool transform, const FFPACK_LU_TAG LuTag, const PSHelper &psH)`
- `template<class Field >`  
`size_t ReducedColumnEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const bool transform=false, const FFPACK_LU_TAG LuTag=FfpackSlabRecursive)`

*Compute the Reduced Column Echelon form of the input matrix in-place.*

- `template<class Field >`  
`size_t pReducedColumnEchelonForm (const Field &F, const size_t M, const size_t N, typename`

- `Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const bool transform=false, size_t numthreads=0, const FFPACK_LU_TAG LuTag=FfpackTileRecursive)`
- `template<class Field, class PSHelper >`  
`size_t ReducedColumnEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const bool transform, const FFPACK_LU_TAG LuTag, const PSHelper &psH)`
  - `template<class Field >`  
`size_t ReducedRowEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const bool transform=false, const FFPACK_LU_TAG LuTag=FfpackSlabRecursive)`  
*Compute the Reduced Row Echelon form of the input matrix in-place.*
  - `template<class Field >`  
`size_t pReducedRowEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const bool transform=false, size_t numthreads=0, const FFPACK_LU_TAG LuTag=FfpackTileRecursive)`
  - `template<class Field, class PSHelper >`  
`size_t ReducedRowEchelonForm (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Qt, const bool transform, const FFPACK_LU_TAG LuTag, const PSHelper &psH)`
  - `template<class Field >`  
`size_t GaussJordan (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, const size_t colbeg, const size_t rowbeg, const size_t colsize, size_t *P, size_t *Q, const FFPACK::FFPACK_LU_TAG LuTag)`  
*Gauss-Jordan algorithm computing the Reduced Row echelon form and its transform matrix.*
  - `template<class Field >`  
`Field::Element_ptr Invert (const Field &F, const size_t M, typename Field::Element_ptr A, const size_t lda, int &>nullity)`  
*Invert the given matrix in place or computes its nullity if it is singular.*
  - `template<class Field >`  
`Field::Element_ptr Invert (const Field &F, const size_t M, typename Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr X, const size_t ldx, int &>nullity)`  
*Invert the given matrix or computes its nullity if it is singular.*
  - `template<class Field >`  
`Field::Element_ptr Invert2 (const Field &F, const size_t M, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr X, const size_t ldx, int &>nullity)`  
*Invert the given matrix or computes its nullity if it is singular.*
  - `template<class PolRing >`  
`std::list< typename PolRing::Element > & CharPoly (const PolRing &R, std::list< typename PolRing::Element > &charp, const size_t N, typename PolRing::Domain_t::Element_ptr A, const size_t lda, typename PolRing::Domain_t::RandIter &G, const FFPACK_CHARPOLY_TAG CharpTag=FfpackAuto, const size_t degree=__FFLASFFPACK_ARITHPROG_THRESHOLD)`  
*Compute the characteristic polynomial of the matrix A.*
  - `template<class PolRing >`  
`PolRing::Element & CharPoly (const PolRing &R, typename PolRing::Element &charp, const size_t N, typename PolRing::Domain_t::Element_ptr A, const size_t lda, typename PolRing::Domain_t::RandIter &G, const FFPACK_CHARPOLY_TAG CharpTag=FfpackAuto, const size_t degree=__FFLASFFPACK_ARITHPROG_THRESHOLD)`  
*Compute the characteristic polynomial of the matrix A.*
  - `template<class PolRing >`  
`PolRing::Element & CharPoly (const PolRing &R, typename PolRing::Element &charp, const size_t N, typename PolRing::Domain_t::Element_ptr A, const size_t lda, const FFPACK_CHARPOLY_TAG CharpTag=FfpackAuto, const size_t degree=__FFLASFFPACK_ARITHPROG_THRESHOLD)`  
*Compute the characteristic polynomial of the matrix A.*
  - `template<class Field, class Polynomial >`  
`std::list< Polynomial > & KellerGehrig (const Field &F, std::list< Polynomial > &charp, const size_t N, typename Field::ConstElement_ptr A, const size_t lda)`

- `template<class Field , class Polynomial >`  
`int KGFast (const Field &F, std::list< Polynomial > &charp, const size_t N, typename Field::Element_ptr A,`  
`const size_t lda, size_t *kg_mc, size_t *kg_mb, size_t *kg_j)`
- `template<class Field , class Polynomial >`  
`std::list< Polynomial > & KGFast_generalized (const Field &F, std::list< Polynomial > &charp, const size_t`  
`N, typename Field::Element_ptr A, const size_t lda)`
- `template<class Field >`  
`void fgemv_kgf (const Field &F, const size_t N, typename Field::ConstElement_ptr A, const size_t lda, type-`  
`name Field::ConstElement_ptr X, const size_t incX, typename Field::Element_ptr Y, const size_t incY, const`  
`size_t kg_mc, const size_t kg_mb, const size_t kg_j)`
- `template<class Field , class Polynomial , class Randlter >`  
`std::list< Polynomial > & LUKrylov (const Field &F, std::list< Polynomial > &charp, const size_t N, typename`  
`Field::Element_ptr A, const size_t lda, typename Field::Element_ptr U, const size_t ldu, Randlter &G)`
- `template<class Field , class Polynomial >`  
`std::list< Polynomial > & Danilevski (const Field &F, std::list< Polynomial > &charp, const size_t N, type-`  
`name Field::Element_ptr A, const size_t lda)`
- `template<class PolRing >`  
`void RandomKrylovPrecond (const PolRing &PR, std::list< typename PolRing::Element > &completed,`  
`Factors, const size_t N, typename PolRing::Domain_t::Element_ptr A, const size_t lda, size_t &Nb, typename`  
`PolRing::Domain_t::Element_ptr &B, size_t &ldb, typename PolRing::Domain_t::Randlter &g, const size_t`  
`degree=__FFLASFFPACK_ARITHPROG_THRESHOLD)`
- `template<class PolRing >`  
`std::list< typename PolRing::Element > & ArithProg (const PolRing &PR, std::list< typename PolRing::`  
`Element > &frobeniusForm, const size_t N, typename PolRing::Domain_t::Element_ptr A, const size_t lda,`  
`const size_t degree)`
- `template<class Field , class Polynomial >`  
`std::list< Polynomial > & LUKrylov_KGFast (const Field &F, std::list< Polynomial > &charp, const size_t N,`  
`typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr X, const size_t ldx)`
- `template<class Field , class Polynomial >`  
`Polynomial & MinPoly (const Field &F, Polynomial &minP, const size_t N, typename Field::ConstElement_ptr`  
`A, const size_t lda)`  
*Compute the minimal polynomial of the matrix A.*
- `template<class Field , class Polynomial , class Randlter >`  
`Polynomial & MinPoly (const Field &F, Polynomial &minP, const size_t N, typename Field::ConstElement_ptr`  
`A, const size_t lda, Randlter &G)`  
*Compute the minimal polynomial of the matrix A.*
- `template<class Field , class Polynomial >`  
`Polynomial & MatVecMinPoly (const Field &F, Polynomial &minP, const size_t N, typename Field::ConstElement_ptr`  
`A, const size_t lda, typename Field::ConstElement_ptr v, const size_t incv)`  
*Compute the minimal polynomial of the matrix A and a vector v, namely the first linear dependency relation in the*  
*Krylov basis  $(v, Av, \dots, A^N v)$ .*
- `template<class Field , class Polynomial >`  
`Polynomial & MatVecMinPoly (const Field &F, Polynomial &minP, const size_t N, typename Field::ConstElement_ptr`  
`A, const size_t lda, typename Field::Element_ptr v, const size_t incv, typename Field::Element_ptr K, const`  
`size_t ldk, size_t *P)`
- `template<class Field , class Polynomial >`  
`Polynomial & Hybrid_KGF_LUK_MinPoly (const Field &F, Polynomial &minP, const size_t N, typename`  
`Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr X, const size_t ldx, size_t *P,`  
`const FFPACK_MINPOLY_TAG MinTag=FFPACK::FpackDense, const size_t kg_mc=0, const size_t kg_`  
`mb=0, const size_t kg_j=0)`
- `template<class Field >`  
`size_t Rank (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda)`  
*Computes the rank of the given matrix using a PLUQ factorization.*
- `template<class Field >`  
`size_t pRank (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda,`  
`size_t numthreads=0)`



- template<class [Field](#) , class PSHelper >  
size\_t [Rank](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, const PSHelper &psH)  
  
Returns true if the given matrix is singular.
- template<class [Field](#) >  
bool [IsSingular](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda)  
  
Returns the determinant of the given square matrix.
- template<class [Field](#) >  
[Field::Element](#) & [pDet](#) (const [Field](#) &F, typename [Field::Element](#) &det, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t numthreads=0, size\_t \*P=NULL, size\_t \*Q=NULL)  
  
Returns the determinant of the given square matrix.
- template<class [Field](#) , class PSHelper >  
[Field::Element](#) & [Det](#) (const [Field](#) &F, typename [Field::Element](#) &det, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, const PSHelper &psH, size\_t \*P=NULL, size\_t \*Q=NULL)
- template<class [Field](#) >  
[Field::Element\\_ptr](#) [Solve](#) (const [Field](#) &F, const size\_t M, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) x, const int incx, typename [Field::ConstElement\\_ptr](#) b, const int incb)  
  
Solves a linear system  $AX = b$  using PLUQ factorization.
- template<class [Field](#) , class PSHelper >  
[Field::Element\\_ptr](#) [Solve](#) (const [Field](#) &F, const size\_t M, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) x, const int incx, typename [Field::ConstElement\\_ptr](#) b, const int incb, PSHelper &psH)
- template<class [Field](#) >  
[Field::Element\\_ptr](#) [pSolve](#) (const [Field](#) &F, const size\_t M, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) x, const int incx, typename [Field::ConstElement\\_ptr](#) b, const int incb, size\_t numthreads=0)
- template<class [Field](#) >  
\*void [RandomNullSpaceVector](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) X, const size\_t incX)  
  
Solve  $LX = B$  or  $XL = B$  in place.
- template<class [Field](#) >  
size\_t [NullSpaceBasis](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) &NS, size\_t &ldn, size\_t &NSdim)  
  
Computes a basis of the Left/Right nullspace of the matrix A.
- template<class [Field](#) >  
size\_t [RowRankProfile](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*&rkprofile, const FFPACK\_LU\_TAG LuTag=[FfpackSlabRecursive](#))  
  
Computes the row rank profile of A.
- template<class [Field](#) >  
size\_t [pRowRankProfile](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*&rkprofile, size\_t numthreads=0, const FFPACK\_LU\_TAG LuTag=[FfpackTileRecursive](#))
- template<class [Field](#) , class PSHelper >  
size\_t [RowRankProfile](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*&rkprofile, const FFPACK\_LU\_TAG LuTag, PSHelper &psH)
- template<class [Field](#) >  
size\_t [ColumnRankProfile](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*&rkprofile, const FFPACK\_LU\_TAG LuTag=[FfpackSlabRecursive](#))  
  
Computes the column rank profile of A.
- template<class [Field](#) >  
size\_t [pColumnRankProfile](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*&rkprofile, size\_t numthreads=0, const FFPACK\_LU\_TAG LuTag=[FfpackTileRecursive](#))

- `template<class Field, class PSHelper >`  
`size_t ColumnRankProfile (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr A,`  
`const size_t lda, size_t *rkprofile, const FFPACK_LU_TAG LuTag, PSHelper &psH)`
- `void RankProfileFromLU (const size_t *P, const size_t N, const size_t R, size_t *rkprofile, const FFPACK_↵`  
`LU_TAG LuTag)`  
*Recovers the column/row rank profile from the permutation of an LU decomposition.*
- `size_t LeadingSubmatrixRankProfiles (const size_t M, const size_t N, const size_t R, const size_t LSm, const`  
`size_t LSn, const size_t *P, const size_t *Q, size_t *RRP, size_t *CRP)`  
*Recovers the row and column rank profiles of any leading submatrix from the PLUQ decomposition.*
- `template<class Field >`  
`size_t RowRankProfileSubmatrixIndices (const Field &F, const size_t M, const size_t N, typename`  
`Field::Element_ptr A, const size_t lda, size_t *rowindices, size_t *colindices, size_t &R)`  
*RowRankProfileSubmatrixIndices.*
- `template<class Field >`  
`size_t ColRankProfileSubmatrixIndices (const Field &F, const size_t M, const size_t N, typename`  
`Field::Element_ptr A, const size_t lda, size_t *rowindices, size_t *colindices, size_t &R)`  
*Computes the indices of the submatrix  $r \times r$   $X$  of  $A$  whose columns correspond to the column rank profile of  $A$ .*
- `template<class Field >`  
`size_t RowRankProfileSubmatrix (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr`  
`A, const size_t lda, typename Field::Element_ptr &X, size_t &R)`  
*Computes the  $r \times r$  submatrix  $X$  of  $A$ , by picking the row rank profile rows of  $A$ .*
- `template<class Field >`  
`size_t ColRankProfileSubmatrix (const Field &F, const size_t M, const size_t N, typename Field::Element_ptr`  
`A, const size_t lda, typename Field::Element_ptr &X, size_t &R)`  
*Compute the  $r \times r$  submatrix  $X$  of  $A$ , by picking the row rank profile rows of  $A$ .*
- `template<class Field >`  
`void getTriangular (const Field &F, const FFLAS::FFLAS_UPLO Uplo, const FFLAS::FFLAS_DIAG diag, const`  
`size_t M, const size_t N, const size_t R, typename Field::ConstElement_ptr A, const size_t lda, typename`  
`Field::Element_ptr T, const size_t ldt, const bool OnlyNonZeroVectors=false)`  
*Extracts a triangular matrix from a compact storage  $A=L\backslash U$  of rank  $R$ .*
- `template<class Field >`  
`void getTriangular (const Field &F, const FFLAS::FFLAS_UPLO Uplo, const FFLAS::FFLAS_DIAG diag, const`  
`size_t M, const size_t N, const size_t R, typename Field::Element_ptr A, const size_t lda)`  
*Cleans up a compact storage  $A=L\backslash U$  to reveal a triangular matrix of rank  $R$ .*
- `template<class Field >`  
`void getEchelonForm (const Field &F, const FFLAS::FFLAS_UPLO Uplo, const FFLAS::FFLAS_DIAG diag,`  
`const size_t M, const size_t N, const size_t R, const size_t *P, typename Field::ConstElement_ptr A, const`  
`size_t lda, typename Field::Element_ptr T, const size_t ldt, const bool OnlyNonZeroVectors=false, const`  
`FFPACK_LU_TAG LuTag=FpackSlabRecursive)`  
*Extracts a matrix in echelon form from a compact storage  $A=L\backslash U$  of rank  $R$  obtained by RowEchelonForm or Column↵*  
*EchelonForm.*
- `template<class Field >`  
`void getEchelonForm (const Field &F, const FFLAS::FFLAS_UPLO Uplo, const FFLAS::FFLAS_DIAG diag,`  
`const size_t M, const size_t N, const size_t R, const size_t *P, typename Field::Element_ptr A, const size_t`  
`lda, const FFPACK_LU_TAG LuTag=FpackSlabRecursive)`  
*Cleans up a compact storage  $A=L\backslash U$  obtained by RowEchelonForm or ColumnEchelonForm to reveal an echelon*  
*form of rank  $R$ .*
- `template<class Field >`  
`void getEchelonTransform (const Field &F, const FFLAS::FFLAS_UPLO Uplo, const FFLAS::FFLAS_DIAG`  
`diag, const size_t M, const size_t N, const size_t R, const size_t *P, const size_t *Q, typename`  
`Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr T, const size_t ldt, const FFPACK_↵`  
`LU_TAG LuTag=FpackSlabRecursive)`  
*Extracts a transformation matrix to echelon form from a compact storage  $A=L\backslash U$  of rank  $R$  obtained by RowEchelon↵*  
*Form or ColumnEchelonForm.*



- `template<class Field >`  
`void getReducedEchelonForm (const Field &F, const FFLAS::FFLAS_UPLO Uplo, const size_t M, const size_t N, const size_t R, const size_t *P, typename Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr T, const size_t ldt, const bool OnlyNonZeroVectors=false, const FFPACK_LU_TAG LuTag=FFpackSlabRecursive)`  
*Extracts a matrix in echelon form from a compact storage  $A=L\backslash U$  of rank  $R$  obtained by `ReducedRowEchelonForm` or `ReducedColumnEchelonForm` with `transform = true`.*
- `template<class Field >`  
`void getReducedEchelonForm (const Field &F, const FFLAS::FFLAS_UPLO Uplo, const size_t M, const size_t N, const size_t R, const size_t *P, typename Field::Element_ptr A, const size_t lda, const FFPACK_LU_TAG LuTag=FFpackSlabRecursive)`  
*Cleans up a compact storage  $A=L\backslash U$  of rank  $R$  obtained by `ReducedRowEchelonForm` or `ReducedColumnEchelonForm` with `transform = true`.*
- `template<class Field >`  
`void getReducedEchelonTransform (const Field &F, const FFLAS::FFLAS_UPLO Uplo, const size_t M, const size_t N, const size_t R, const size_t *P, const size_t *Q, typename Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr T, const size_t ldt, const FFPACK_LU_TAG LuTag=FFpackSlabRecursive)`  
*Extracts a transformation matrix to echelon form from a compact storage  $A=L\backslash U$  of rank  $R$  obtained by `RowEchelonForm` or `ColumnEchelonForm`.*
- `void PLUQtoEchelonPermutation (const size_t N, const size_t R, const size_t *P, size_t *outPerm)`  
*Auxiliary routine: determines the permutation that changes a PLUQ decomposition into a echelon form revealing PLUQ decomposition.*
- `template<class Field >`  
`size_t LTBruhatGen (const Field &Fi, const FFLAS::FFLAS_DIAG diag, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Q)`  
*LTBruhatGen Suppose  $A$  is Left Triangular Matrix This procedure computes the Bruhat Representation of  $A$  and return the rank of  $A$ .*
- `template<class Field >`  
`void getLTBruhatGen (const Field &Fi, const size_t N, const size_t r, const size_t *P, const size_t *Q, typename Field::Element_ptr R, const size_t ldr)`  
*GetLTBruhatGen This procedure Computes the Rank Revealing Matrix based on the Bruhat representation of a Matrix.*
- `template<class Field >`  
`void getLTBruhatGen (const Field &Fi, const FFLAS::FFLAS_UPLO Uplo, const FFLAS::FFLAS_DIAG diag, const size_t N, const size_t r, const size_t *P, const size_t *Q, typename Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr T, const size_t ldt)`  
*GetLTBruhatGen This procedure computes the matrix  $L$  or  $U$  of the Bruhat Representation Suppose that  $A$  is the bruhat representation of a matrix.*
- `size_t LTQSorder (const size_t N, const size_t r, const size_t *P, const size_t *Q)`  
*LTQSorder This procedure computes the order of quasiseparability of a matrix.*
- `template<class Field >`  
`size_t CompressToBlockBiDiagonal (const Field &Fi, const FFLAS::FFLAS_UPLO Uplo, size_t N, size_t s, size_t r, const size_t *P, const size_t *Q, typename Field::Element_ptr A, size_t lda, typename Field::Element_ptr X, size_t ldx, size_t *K, size_t *M, size_t *T)`  
*CompressToBlockBiDiagonal This procedure compress a compact representation of a row echelon form or column echelon form.*
- `template<class Field >`  
`void ExpandBlockBiDiagonalToBruhat (const Field &Fi, const FFLAS::FFLAS_UPLO Uplo, size_t N, size_t s, size_t r, typename Field::Element_ptr A, size_t lda, typename Field::Element_ptr X, size_t ldx, size_t NbBlocks, size_t *K, size_t *M, size_t *T)`  
*ExpandBlockBiDiagonal This procedure expand a compact representation of a row echelon form or column echelon form.*
- `void Bruhat2EchelonPermutation (size_t N, size_t R, const size_t *P, const size_t *Q, size_t *M)`  
*Bruhat2EchelonPermutation ( $N, R, P, Q$ ) Compute  $M$  such that  $LM$  or  $MU$  is in echelon form where  $L$  or  $U$  are factors of the Bruhat Representation.*
- `size_t * Tinverter (size_t *T, size_t r)`

- template<class [Field](#) >  
void [ComputeRPermutation](#) (const [Field](#) &Fi, size\_t N, size\_t r, const size\_t \*P, const size\_t \*Q, size\_t \*R, size\_t \*MU, size\_t \*ML)
- template<class [Field](#) >  
void [productBruhatxTS](#) (const [Field](#) &Fi, size\_t N, size\_t s, size\_t r, const size\_t \*P, const size\_t \*Q, const typename [Field::Element\\_ptr](#) Xu, size\_t ldu, size\_t NbBlocksU, size\_t \*Ku, size\_t \*Tu, size\_t \*MU, const typename [Field::Element\\_ptr](#) XI, size\_t ldl, size\_t NbBlocksL, size\_t \*KI, size\_t \*TI, size\_t \*ML, typename [Field::Element\\_ptr](#) B, size\_t t, size\_t ldb, typename [Field::Element\\_ptr](#) C, size\_t ldc)  
*productBruhatxTS Compute the product between the CRE compact representation of a matrix A and B a tall matrix*
- template<class [Field](#) >  
[Field::Element\\_ptr](#) [LQUPtoInverseOfFullRankMinor](#) (const [Field](#) &F, const size\_t rank, typename [Field::Element\\_ptr](#) A\_factors, const size\_t lda, const size\_t \*QtPointer, typename [Field::Element\\_ptr](#) X, const size\_t ldx)  
*LQUPtoInverseOfFullRankMinor.*

### 13.180.1 Detailed Description

Set of elimination based routines for dense linear algebra.

Matrices are supposed over finite prime field of characteristic less than  $2^{26}$ .

### 13.180.2 Macro Definition Documentation

#### 13.180.2.1 \_\_FFLASFFPACK\_FTRSTR\_THRESHOLD

```
#define __FFLASFFPACK_FTRSTR_THRESHOLD 64
```

#### 13.180.2.2 \_\_FFLASFFPACK\_FTRSSYR2K\_THRESHOLD

```
#define __FFLASFFPACK_FTRSSYR2K_THRESHOLD 64
```

## 13.181 ffpack.inl File Reference

### Namespaces

- namespace [FFPACK](#)  
*Finite **Field** **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- #define [\\_\\_FFLASFFPACK\\_ffpack\\_INL](#)

### Functions

- template<class [Field](#) >  
size\_t [Rank](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda)  
*Computes the rank of the given matrix using a PLUQ factorization.*
- template<class [Field](#) >  
size\_t [pRank](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t numthreads=0)
- template<class [Field](#) , class PSHelper >  
size\_t [Rank](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, const PSHelper &psH)
- template<class [Field](#) >  
bool [IsSingular](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda)  
*Returns true if the given matrix is singular.*

- template<class [Field](#) >  
[Field::Element](#) & [Det](#) (const [Field](#) &F, typename [Field::Element](#) &det, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*P=NULL, size\_t \*Q=NULL)  
*Returns the determinant of the given square matrix.*
- template<class [Field](#) >  
[Field::Element](#) & [pDet](#) (const [Field](#) &F, typename [Field::Element](#) &det, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t numthreads=0, size\_t \*P=NULL, size\_t \*Q=NULL)
- template<class [Field](#) , class PSHelper >  
[Field::Element](#) & [Det](#) (const [Field](#) &F, typename [Field::Element](#) &det, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, const PSHelper &psH, size\_t \*P=NULL, size\_t \*Q=NULL)
- template<class [Field](#) >  
[Field::Element\\_ptr](#) [Solve](#) (const [Field](#) &F, const size\_t M, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) x, const int incx, typename [Field::ConstElement\\_ptr](#) b, const int incb)  
*Solves a linear system  $AX = b$  using PLUQ factorization.*
- template<class [Field](#) , class PSHelper >  
[Field::Element\\_ptr](#) [Solve](#) (const [Field](#) &F, const size\_t M, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) x, const int incx, typename [Field::ConstElement\\_ptr](#) b, const int incb, PSHelper &psH)
- template<class [Field](#) >  
[Field::Element\\_ptr](#) [pSolve](#) (const [Field](#) &F, const size\_t M, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) x, const int incx, typename [Field::ConstElement\\_ptr](#) b, const int incb, size\_t numthreads=0)
- template<class [Field](#) >  
void [RandomNullSpaceVector](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) X, const size\_t incX)  
*Solve  $LX = B$  or  $XL = B$  in place.*
- template<class [Field](#) >  
size\_t [NullSpaceBasis](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) &NS, size\_t &ldn, size\_t &NSdim)  
*Computes a basis of the Left/Right nullspace of the matrix A.*
- template<class [Field](#) >  
void [solveLB](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t R, typename [Field::Element\\_ptr](#) L, const size\_t ldl, const size\_t \*Q, typename [Field::Element\\_ptr](#) B, const size\_t ldb)
- template<class [Field](#) >  
void [solveLB2](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t R, typename [Field::Element\\_ptr](#) L, const size\_t ldl, const size\_t \*Q, typename [Field::Element\\_ptr](#) B, const size\_t ldb)

## 13.181.1 Macro Definition Documentation

### 13.181.1.1 \_\_FFLASFFPACK\_ffpack\_INL

```
#define __FFLASFFPACK_ffpack_INL
```

## 13.182 ffpack\_bruhatgen.inl File Reference

### Namespaces

- namespace [FFPACK](#)  
*Finite **Field** **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- #define [\\_\\_FFLASFFPACK\\_ffpack\\_bruhatgen\\_inl](#)

## Functions

- `template<class Field >`  
`size_t LTBruhatGen (const Field &Fi, const FFLAS::FFLAS_DIAG diag, const size_t N, typename Field::Element_ptr A, const size_t lda, size_t *P, size_t *Q)`  
*LTBruhatGen Suppose A is Left Triangular Matrix This procedure computes the Bruhat Representation of A and return the rank of A.*
- `template<class Field >`  
`void getLTBruhatGen (const Field &Fi, const size_t N, const size_t r, const size_t *P, const size_t *Q, typename Field::Element_ptr R, const size_t ldr)`  
*GetLTBruhatGen This procedure Computes the Rank Revealing Matrix based on the Bruhta representation of a Matrix.*
- `template<class Field >`  
`void getLTBruhatGen (const Field &Fi, const FFLAS::FFLAS_UPLO Uplo, const FFLAS::FFLAS_DIAG diag, const size_t N, const size_t r, const size_t *P, const size_t *Q, typename Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr T, const size_t ldt)`  
*GetLTBruhatGen This procedure computes the matrix L or U f the Bruhat Representation Suppose that A is the bruhat representation of a matrix.*
- `size_t LTQSorder (const size_t N, const size_t r, const size_t *P, const size_t *Q)`  
*LTQSorder This procedure computes the order of quasiseparability of a matrix.*
- `template<class Field >`  
`size_t CompressToBlockBiDiagonal (const Field &Fi, const FFLAS::FFLAS_UPLO Uplo, size_t N, size_t s, size_t r, const size_t *P, const size_t *Q, typename Field::Element_ptr A, size_t lda, typename Field::Element_ptr X, size_t ldx, size_t *K, size_t *M, size_t *T)`  
*CompressToBlockBiDiagonal This procedure compress a compact representation of a row echelon form or column echelon form.*
- `template<class Field >`  
`void ExpandBlockBiDiagonalToBruhat (const Field &Fi, const FFLAS::FFLAS_UPLO Uplo, size_t N, size_t s, size_t r, typename Field::Element_ptr A, size_t lda, typename Field::Element_ptr X, size_t ldx, size_t NbBlocks, size_t *K, size_t *M, size_t *T)`  
*ExpandBlockBiDiagonal This procedure expand a compact representation of a row echelon form or column echelon form.*
- `void Bruhat2EchelonPermutation (size_t N, size_t R, const size_t *P, const size_t *Q, size_t *M)`  
*Bruhat2EchelonPermutation (N,R,P,Q) Compute M such that LM or MU is in echelon form where L or U are factors of the Bruhat Rpresentation.*
- `size_t * TInverter (const size_t *T, size_t r)`
- `template<class Field >`  
`void ComputeRPermutation (const Field &Fi, size_t N, size_t r, const size_t *P, const size_t *Q, size_t *R, const size_t *MU, const size_t *ML)`
- `template<class Field >`  
`Field::Element_ptr expandLCRE (const Field &Fi, size_t N, size_t s, size_t r, size_t *R, size_t i, typename Field::ConstElement_ptr Xu, size_t ldu, size_t NbBlocksU, const size_t *Ku, const size_t *Tuinv, typename Field::ConstElement_ptr Xl, size_t ldl, size_t NbBlocksL, const size_t *Kl, const size_t *Tlinv, typename Field::Element_ptr CRE, size_t ldcre)`  
*Expands an anti-diagonal block of a left triangular matrix from its compact Bruhat representation.*
- `template<class Field >`  
`void productBruhatxTS (const Field &Fi, size_t N, size_t s, size_t r, size_t t, const size_t *P, const size_t *Q, typename Field::ConstElement_ptr Xu, size_t ldu, size_t NbBlocksU, const size_t *Ku, const size_t *Tu, const size_t *MU, typename Field::ConstElement_ptr Xl, size_t ldl, size_t NbBlocksL, const size_t *Kl, const size_t *Tl, const size_t *ML, typename Field::Element_ptr B, size_t ldb, const typename Field::Element beta, typename Field::Element_ptr D, size_t ldd)`  
*Compute the product of a left-triangular quasi-separable matrix A, represented by a compact Bruhat generator, with a dense rectangular matrix B:  $C \leftarrow A \times B + \text{beta}C$ .*

## 13.182.1 Macro Definition Documentation

### 13.182.1.1 \_\_FFLASFFPACK\_ffpack\_bruhatgen\_inl

```
#define __FFLASFFPACK_ffpack_bruhatgen_inl
```

## 13.183 ffpack\_charpoly.inl File Reference

```
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include "ffpack_charpoly_mp.inl"
```

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*
- namespace [FFPACK::Protected](#)

### Macros

- #define [\\_\\_FFLASFFPACK\\_charpoly\\_INL](#)

### Functions

- template<class PolRing >  
std::list< typename PolRing::Element > & [CharPoly](#) (const PolRing &R, std::list< typename PolRing::Element > &charp, const size\_t N, typename PolRing::Domain\_t::Element\_ptr A, const size\_t lda, typename PolRing::Domain\_t::RandIter &G, const FFPACK\_CHARPOLY\_TAG CharpTag=FpackAuto, const size\_t degree=[\\_\\_FFLASFFPACK\\_ARITHPROG\\_THRESHOLD](#))  
*Compute the characteristic polynomial of the matrix A.*
- template<class PolRing >  
PolRing::Element & [CharPoly](#) (const PolRing &R, typename PolRing::Element &charp, const size\_t N, typename PolRing::Domain\_t::Element\_ptr A, const size\_t lda, typename PolRing::Domain\_t::RandIter &G, const FFPACK\_CHARPOLY\_TAG CharpTag=FpackAuto, const size\_t degree=[\\_\\_FFLASFFPACK\\_ARITHPROG\\_THRESHOLD](#))  
*Compute the characteristic polynomial of the matrix A.*
- template<class [Field](#) , class Polynomial , class RandIter >  
std::list< Polynomial > & [LUKrylov](#) (const [Field](#) &F, std::list< Polynomial > &charp, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) U, const size\_t ldu, RandIter &G)
- template<class [Field](#) , class Polynomial >  
std::list< Polynomial > & [LUKrylov\\_KGFast](#) (const [Field](#) &F, std::list< Polynomial > &charp, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) X, const size\_t ldx)

## 13.183.1 Macro Definition Documentation

### 13.183.1.1 \_\_FFLASFFPACK\_charpoly\_INL

```
#define __FFLASFFPACK_charpoly_INL
```

## 13.184 ffpack\_charpoly\_danilevski.inl File Reference

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- #define [\\_\\_FFLASFFPACK\\_ffpack\\_charpoly\\_danilveski\\_INL](#)

## Functions

- `template<class Field , class Polynomial >`  
`std::list< Polynomial > & Danilevski (const Field &F, std::list< Polynomial > &charp, const size_t N, type-`  
`name Field::Element\_ptr A, const size_t lda)`

## 13.184.1 Macro Definition Documentation

### 13.184.1.1 `__FFLASFFPACK_ffpack_charpoly_danilveski_INL`

```
#define __FFLASFFPACK_ffpack_charpoly_danilveski_INL
```

## 13.185 `ffpack_charpoly_kgfast.inl` File Reference

### Namespaces

- namespace [FFPACK](#)  
*Finite **Field** **PACK** Set of elimination based routines for dense linear algebra.*
- namespace [FFPACK::Protected](#)

### Macros

- `#define \_\_FFLASFFPACK\_ffpack\_charpoly\_kgfast\_INL`

### Functions

- `template<class Field , class Polynomial >`  
`int KGFast (const Field &F, std::list< Polynomial > &charp, const size_t N, typename Field::Element\_ptr A,`  
`const size_t lda, size_t *kg_mc, size_t *kg_mb, size_t *kg_j)`
- `template<class Field >`  
`void fgemv\_kgf (const Field &F, const size_t N, typename Field::ConstElement\_ptr A, const size_t lda, type-`  
`name Field::ConstElement\_ptr X, const size_t incX, typename Field::Element\_ptr Y, const size_t incY, const`  
`size_t kg_mc, const size_t kg_mb, const size_t kg_j)`

## 13.185.1 Macro Definition Documentation

### 13.185.1.1 `__FFLASFFPACK_ffpack_charpoly_kgfast_INL`

```
#define __FFLASFFPACK_ffpack_charpoly_kgfast_INL
```

## 13.186 `ffpack_charpoly_kgfastgeneralized.inl` File Reference

```
#include <iostream>
#include "fflas-ffpack/utils/fflas_io.h"
```

### Namespaces

- namespace [FFPACK](#)  
*Finite **Field** **PACK** Set of elimination based routines for dense linear algebra.*
- namespace [FFPACK::Protected](#)

### Macros

- `#define \_\_FFLASFFPACK\_ffpack\_charpoly\_kgfastgeneralized\_INL`

## Functions

- template<class [Field](#) >  
[Field::Element\\_ptr](#) buildMatrix (const [Field](#) &F, typename [Field::ConstElement\\_ptr](#) E, typename [Field::ConstElement\\_ptr](#) C, const size\_t lda, const size\_t \*B, const size\_t \*T, const size\_t me, const size\_t mc, const size\_t lambda, const size\_t mu)
- template<class [Field](#) , class Polynomial >  
std::list< Polynomial > & [KGFast\\_generalized](#) (const [Field](#) &F, std::list< Polynomial > &charp, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda)

## 13.186.1 Macro Definition Documentation

### 13.186.1.1 \_\_FFLASFFPACK\_ffpack\_charpoly\_kgfastgeneralized\_INL

```
#define __FFLASFFPACK_ffpack_charpoly_kgfastgeneralized_INL
```

## 13.187 ffpack\_charpoly\_kglu.inl File Reference

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*
- namespace [FFPACK::Protected](#)

### Macros

- #define [\\_\\_FFLASFFPACK\\_ffpack\\_charpoly\\_kglu\\_INL](#)

## Functions

- template<class [Field](#) >  
size\_t [updated](#) (const [Field](#) &F, size\_t \*d, size\_t k, std::vector< std::vector< typename [Field::Element](#) > > &minpt)
- template<class [Field](#) >  
size\_t [newD](#) (const [Field](#) &F, size\_t \*d, bool &KeepOn, const size\_t l, const size\_t N, typename [Field::Element\\_ptr](#) X, const size\_t \*Q, std::vector< std::vector< typename [Field::Element](#) > > &minpt)
- template<class [Field](#) , class Polynomial >  
std::list< Polynomial > & [KellerGehrig](#) (const [Field](#) &F, std::list< Polynomial > &charp, const size\_t N, typename [Field::ConstElement\\_ptr](#) A, const size\_t lda)

## 13.187.1 Macro Definition Documentation

### 13.187.1.1 \_\_FFLASFFPACK\_ffpack\_charpoly\_kglu\_INL

```
#define __FFLASFFPACK_ffpack_charpoly_kglu_INL
```

## 13.188 ffpack\_charpoly\_mp.inl File Reference

```
#include <givaro/zring.h>
#include "givaro/givinteger.h"
#include "givaro/givpoly1.h"
#include "fflas-ffpack/field/rns-integer.h"
#include "fflas-ffpack/fflas-ffpack.h"
```

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

## Macros

- `#define __FFPACK_charpoly_mp_INL`

## Functions

- `FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr CharPoly` (const `FFPACK::RNSInteger< FFPACK::rns_double > &F`, typename `FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr` charp, const `size_t N`, typename `FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr` A, const `size_t lda`, `Givaro::ZRing< Givaro::Integer >::RandIter &G`, const `FFPACK_CHARPOLY_TAG` CharpTag, `size_t degree`)
- `template<> Givaro::Poly1Dom< Givaro::ZRing< Givaro::Integer > >::Element & CharPoly` (const `Givaro::Poly1Dom< Givaro::ZRing< Givaro::Integer > > &R`, `Givaro::Poly1Dom< Givaro::ZRing< Givaro::Integer > >::Element &charp`, const `size_t N`, `Givaro::Integer *A`, const `size_t lda`, `Givaro::ZRing< Givaro::Integer >::RandIter &G`, const `FFPACK_CHARPOLY_TAG` CharpTag, `size_t degree`)

## 13.188.1 Macro Definition Documentation

### 13.188.1.1 \_\_FFPACK\_charpoly\_mp\_INL

```
#define __FFPACK_charpoly_mp_INL
```

## 13.189 ffpack\_det\_mp.inl File Reference

```
#include <givaro/zring.h>
#include "givaro/givinteger.h"
#include "fflas-ffpack/field/rns-integer.h"
#include "fflas-ffpack/fflas-ffpack.h"
```

## Namespaces

- namespace `FFPACK`  
*Finite Field PACK Set of elimination based routines for dense linear algebra.*

## Macros

- `#define __FFPACK_det_mp_INL`

## Functions

- `template<class PSHelper > FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr & Det` (const `FFPACK::RNSInteger< FFPACK::rns_double > &F`, typename `FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr` &det, const `size_t N`, typename `FFPACK::RNSInteger< FFPACK::rns_double >::Element_ptr` A, const `size_t lda`, const `PSHelper &psH`)
- `template<class PSHelper > Givaro::Integer & Det` (const `Givaro::ZRing< Givaro::Integer > &F`, `Givaro::Integer &det`, const `size_t N`, `Givaro::Integer *A`, const `size_t lda`, const `PSHelper &psH`, `size_t *P`, `size_t *Q`)

## 13.189.1 Macro Definition Documentation

### 13.189.1.1 \_\_FFPACK\_det\_mp\_INL

```
#define __FFPACK_det_mp_INL
```



## 13.190 ffpack\_echelonforms.inl File Reference

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- #define [\\_\\_FFLASFFPACK\\_ffpack\\_echelon\\_forms\\_INL](#)
- #define [\\_\\_FFLASFFPACK\\_GAUSSJORDAN\\_BASECASE](#) 256

### Functions

- template<class [Field](#) >  
void [getTriangular](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) Uplo, const [FFLAS::FFLAS\\_DIAG](#) diag, const size\_t M, const size\_t N, const size\_t R, typename [Field::ConstElement\\_ptr](#) A, const size\_t Ida, typename [Field::Element\\_ptr](#) T, const size\_t Idt, const bool OnlyNonZeroVectors=false)  
*Extracts a triangular matrix from a compact storage  $A=L\backslash U$  of rank  $R$ .*
- template<class [Field](#) >  
void [getTriangular](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) Uplo, const [FFLAS::FFLAS\\_DIAG](#) diag, const size\_t M, const size\_t N, const size\_t R, typename [Field::Element\\_ptr](#) A, const size\_t Ida)  
*Cleans up a compact storage  $A=L\backslash U$  to reveal a triangular matrix of rank  $R$ .*
- void [PLUQtoEchelonPermutation](#) (const size\_t N, const size\_t R, const size\_t \*P, size\_t \*outPerm)  
*Auxiliary routine: determines the permutation that changes a PLUQ decomposition into a echelon form revealing PLUQ decomposition.*
- template<class [Field](#) >  
void [getEchelonForm](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) Uplo, const [FFLAS::FFLAS\\_DIAG](#) diag, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, typename [Field::ConstElement\\_ptr](#) A, const size\_t Ida, typename [Field::Element\\_ptr](#) T, const size\_t Idt, const bool OnlyNonZeroVectors=false, const [FFPACK\\_LU\\_TAG](#) LuTag=[FfpackSlabRecursive](#))  
*Extracts a matrix in echelon form from a compact storage  $A=L\backslash U$  of rank  $R$  obtained by RowEchelonForm or Column↔EchelonForm.*
- template<class [Field](#) >  
void [getEchelonForm](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) Uplo, const [FFLAS::FFLAS\\_DIAG](#) diag, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, typename [Field::Element\\_ptr](#) A, const size\_t Ida, const [FFPACK\\_LU\\_TAG](#) LuTag=[FfpackSlabRecursive](#))  
*Cleans up a compact storage  $A=L\backslash U$  obtained by RowEchelonForm or ColumnEchelonForm to reveal an echelon form of rank  $R$ .*
- template<class [Field](#) >  
void [getEchelonTransform](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) Uplo, const [FFLAS::FFLAS\\_DIAG](#) diag, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, const size\_t \*Q, typename [Field::ConstElement\\_ptr](#) A, const size\_t Ida, typename [Field::Element\\_ptr](#) T, const size\_t Idt, const [FFPACK\\_LU\\_TAG](#) LuTag=[FfpackSlabRecursive](#))  
*Extracts a transformation matrix to echelon form from a compact storage  $A=L\backslash U$  of rank  $R$  obtained by RowEchelon↔Form or ColumnEchelonForm.*
- template<class [Field](#) >  
void [getReducedEchelonForm](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) Uplo, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, typename [Field::ConstElement\\_ptr](#) A, const size\_t Ida, typename [Field::Element\\_ptr](#) T, const size\_t Idt, const bool OnlyNonZeroVectors=false, const [FFPACK\\_LU\\_TAG](#) LuTag=[FfpackSlabRecursive](#))  
*Extracts a matrix in echelon form from a compact storage  $A=L\backslash U$  of rank  $R$  obtained by ReducedRowEchelonForm or ReducedColumnEchelonForm with transform = true.*
- template<class [Field](#) >  
void [getReducedEchelonForm](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) Uplo, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, typename [Field::Element\\_ptr](#) A, const size\_t Ida, const [FFPACK\\_LU\\_TAG](#) LuTag=[FfpackSlabRecursive](#))

*Cleans up a compact storage  $A=L\backslash U$  of rank  $R$  obtained by `ReducedRowEchelonForm` or `ReducedColumnEchelonForm` with `transform = true`.*

- `template<class Field >`  
`void getReducedEchelonTransform (const Field &F, const FFLAS::FFLAS_UPLO Uplo, const size_t M, const size_t N, const size_t R, const size_t *P, const size_t *Q, typename Field::ConstElement_ptr A, const size_t lda, typename Field::Element_ptr T, const size_t ldt, const FFPACK_LU_TAG LuTag=FpackSlabRecursive)`

*Extracts a transformation matrix to echelon form from a compact storage  $A=L\backslash U$  of rank  $R$  obtained by `RowEchelonForm` or `ColumnEchelonForm`.*

## 13.190.1 Macro Definition Documentation

### 13.190.1.1 \_\_FFLASFFPACK\_ffpack\_echelon\_forms\_INL

```
#define __FFLASFFPACK_ffpack_echelon_forms_INL
```

### 13.190.1.2 \_\_FFLASFFPACK\_GAUSSJORDAN\_BASECASE

```
#define __FFLASFFPACK_GAUSSJORDAN_BASECASE 256
```

## 13.191 fpack\_fgesv.inl File Reference

### Namespaces

- namespace `FFPACK`  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- `#define __FFLASFFPACK_ffpack_fgesv_INL`

### Functions

- `template<class Field >`  
`size_t fgesv (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, const size_t N, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr B, const size_t ldb, int *info)`  
*Square system solver.*
- `template<class Field >`  
`size_t fgesv (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, const size_t N, const size_t NRHS, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr X, const size_t ldx, typename Field::ConstElement_ptr B, const size_t ldb, int *info)`  
*Rectangular system solver.*

## 13.191.1 Macro Definition Documentation

### 13.191.1.1 \_\_FFLASFFPACK\_ffpack\_fgesv\_INL

```
#define __FFLASFFPACK_ffpack_fgesv_INL
```

## 13.192 fpack\_fgetrs.inl File Reference

### Namespaces

- namespace `FFPACK`  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- `#define __FFLASFFPACK_ffpack_fgetrs_INL`

## Functions

- template<class [Field](#) >  
void [fgetrs](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t R, typename [Field::Element\\_ptr](#) A, const size\_t lda, const size\_t \*P, const size\_t \*Q, typename [Field::Element\\_ptr](#) B, const size\_t ldb, int \*info)  
*Solve the system  $AX = B$  or  $XA = B$ .*
- template<class [Field](#) >  
[Field::Element\\_ptr](#) [fgetrs](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t NRHS, const size\_t R, typename [Field::Element\\_ptr](#) A, const size\_t lda, const size\_t \*P, const size\_t \*Q, typename [Field::Element\\_ptr](#) X, const size\_t idx, typename [Field::ConstElement\\_ptr](#) B, const size\_t ldb, int \*info)  
*Solve the system  $AX = B$  or  $XA = B$ .*

## 13.192.1 Macro Definition Documentation

### 13.192.1.1 \_\_FFLASFFPACK\_ffpack\_fgetrs\_INL

```
#define __FFLASFFPACK_ffpack_fgetrs_INL
```

## 13.193 ffpack\_frobenius.inl File Reference

```
#include <givaro/givranditer.h>
```

## Namespaces

- namespace [FFPACK](#)  
*Finite **Field** **PACK** Set of elimination based routines for dense linear algebra.*
- namespace [FFPACK::Protected](#)

## Functions

- template<class [Field](#) >  
void [CompressRows](#) ([Field](#) &F, const size\_t M, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) tmp, const size\_t ldtmp, const size\_t \*d, const size\_t nb\_blocs)
- template<class [Field](#) >  
void [CompressRowsQK](#) ([Field](#) &F, const size\_t M, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) tmp, const size\_t ldtmp, const size\_t \*d, const size\_t deg, const size\_t nb\_blocs)
- template<class [Field](#) >  
void [DeCompressRows](#) ([Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) tmp, const size\_t ldtmp, const size\_t \*d, const size\_t nb\_blocs)
- template<class [Field](#) >  
void [DeCompressRowsQK](#) ([Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) tmp, const size\_t ldtmp, const size\_t \*d, const size\_t deg, const size\_t nb\_blocs)
- template<class [Field](#) >  
void [CompressRowsQA](#) ([Field](#) &F, const size\_t M, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) tmp, const size\_t ldtmp, const size\_t \*d, const size\_t nb\_blocs)
- template<class [Field](#) >  
void [DeCompressRowsQA](#) ([Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) tmp, const size\_t ldtmp, const size\_t \*d, const size\_t nb\_blocs)
- template<class [PolRing](#) >  
void [RandomKrylovPrecond](#) (const [PolRing](#) &PR, std::list< typename [PolRing::Element](#) > &completedFactors, const size\_t N, typename [PolRing::Domain\\_t::Element\\_ptr](#) A, const size\_t lda, size\_t &Nb, typename [PolRing::Domain\\_t::Element\\_ptr](#) &B, size\_t &ldb, typename [PolRing::Domain\\_t::RandIter](#) &g, const size\_t degree=\_\_FFLASFFPACK\_ARITHPROG\_THRESHOLD)

- `template<class PolRing >`  
`std::list< typename PolRing::Element > & ArithProg (const PolRing &PR, std::list< typename PolRing::Element > &frobeniusForm, const size_t N, typename PolRing::Domain_t::Element_ptr A, const size_t lda, const size_t degree)`

## 13.194 ffpack\_fsytrf.inl File Reference

```
#include "fflas-ffpack/utils/fflas_io.h"
```

### Namespaces

- namespace `FFPACK`  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- `#define __FFLASFFPACK_ffpack_fsytrf_INL`

### Functions

- `template<class Field >`  
`bool fsytrf_BC_Crout (const Field &F, const FFLAS::FFLAS_UPLO UpLo, const size_t N, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr Dinv, const size_t incDinv)`
- `template<class Field >`  
`size_t fsytrf_BC_RL (const Field &F, const FFLAS::FFLAS_UPLO UpLo, const size_t N, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr Dinv, const size_t incDinv)`
- `template<class Field >`  
`size_t fsytrf_UP_RPM_BC_RL (const Field &F, const size_t N, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr Dinv, const size_t incDinv, size_t *P)`
- `template<class Field >`  
`size_t fsytrf_LOW_RPM_BC_Crout (const Field &F, const size_t N, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr Dinv, const size_t incDinv, size_t *P)`
- `template<class Field >`  
`size_t fsytrf_UP_RPM_BC_Crout (const Field &F, const size_t N, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr Dinv, const size_t incDinv, size_t *P)`
- `template<class Field >`  
`size_t fsytrf_UP_RPM (const Field &Fi, const size_t N, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr Dinv, const size_t incDinv, size_t *P, size_t BCThreshold)`
- `template<class Field >`  
`bool fsytrf_nonunit (const Field &F, const FFLAS::FFLAS_UPLO UpLo, const size_t N, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr Dinv, const size_t incDinv, FFLAS::ParSeqHelper::Sequential seq, size_t threshold)`
- `template<class Field, class Cut, class Param >`  
`bool fsytrf_nonunit (const Field &F, const FFLAS::FFLAS_UPLO UpLo, const size_t N, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr Dinv, const size_t incDinv, FFLAS::ParSeqHelper::Parallel< Cut, Param > par, size_t threshold)`
- `template<class Field >`  
`bool fsytrf (const Field &F, const FFLAS::FFLAS_UPLO UpLo, const size_t N, typename Field::Element_ptr A, const size_t lda, const size_t threshold=__FFLASFFPACK_FSYTRF_THRESHOLD)`  
*Triangular factorization of symmetric matrices.*
- `template<class Field >`  
`bool fsytrf (const Field &F, const FFLAS::FFLAS_UPLO UpLo, const size_t N, typename Field::Element_ptr A, const size_t lda, const FFLAS::ParSeqHelper::Sequential seq, const size_t threshold=__FFLASFFPACK_FSYTRF_THRESHOLD)`
- `template<class Field, class Cut, class Param >`  
`bool fsytrf (const Field &F, const FFLAS::FFLAS_UPLO UpLo, const size_t N, typename Field::Element_ptr A, const size_t lda, const FFLAS::ParSeqHelper::Parallel< Cut, Param > par, const size_t threshold=__FFLASFFPACK_FSYTRF_THRESHOLD)`

- template<class [Field](#) >  
size\_t [fsytrf\\_RPM](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) UpLo, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*P, size\_t threshold)
- template<class [Field](#) >  
void [getTridiagonal](#) (const [Field](#) &F, const size\_t N, const size\_t R, typename [Field::ConstElement\\_ptr](#) A, const size\_t lda, size\_t \*P, typename [Field::Element\\_ptr](#) T, const size\_t ldt)

### 13.194.1 Macro Definition Documentation

#### 13.194.1.1 \_\_FFLASFFPACK\_ffpack\_fsytrf\_INL

```
#define __FFLASFFPACK_ffpack_fsytrf_INL
```

## 13.195 ffpack\_ftrssyr2k.inl File Reference

```
#include "fflas-ffpack/utils/fflas_io.h"
```

### Namespaces

- namespace [FFPACK](#)  
*Finite **Field** **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- #define [\\_\\_FFLASFFPACK\\_ffpack\\_ftrssyr2k\\_INL](#)

### Functions

- template<class [Field](#) >  
void [ftrssyr2k](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) Uplo, const [FFLAS::FFLAS\\_DIAG](#) diagA, const size\_t N, typename [Field::ConstElement\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) B, const size\_t ldb, const size\_t threshold=[\\_\\_FFLASFFPACK\\_FTRSSYR2K\\_THRESHOLD](#))  
*Solve a triangular system in a symmetric sum: find B upper/lower triangular such that  $A^T B + B^T A = C$  where C is symmetric.*

### 13.195.1 Macro Definition Documentation

#### 13.195.1.1 \_\_FFLASFFPACK\_ffpack\_ftrssyr2k\_INL

```
#define __FFLASFFPACK_ffpack_ftrssyr2k_INL
```

## 13.196 ffpack\_ftrstr.inl File Reference

```
#include "fflas-ffpack/utils/fflas_io.h"
```

### Namespaces

- namespace [FFPACK](#)  
*Finite **Field** **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- #define [\\_\\_FFLASFFPACK\\_ffpack\\_ftrstr\\_INL](#)

## Functions

- template<class [Field](#) >  
void [ftrstr](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) side, const [FFLAS::FFLAS\\_UPLO](#) Uplo, const [FFLAS::FFLAS\\_DIAG](#) diagA, const [FFLAS::FFLAS\\_DIAG](#) diagB, const size\_t N, typename [Field::ConstElement\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) B, const size\_t ldb, const size\_t threshold=[\\_\\_FFLASFFPACK\\_FTRSTR\\_THRESHOLD](#))

*Solve a triangular system with a triangular right hand side of the same shape.*

## 13.196.1 Macro Definition Documentation

### 13.196.1.1 [\\_\\_FFLASFFPACK\\_ffpack\\_ftrstr\\_INL](#)

```
#define __FFLASFFPACK_ffpack_ftrstr_INL
```

## 13.197 [ffpack\\_ftrtr.inl](#) File Reference

### Namespaces

- namespace [FFPACK](#)  
*Finite **Field** **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- #define [ENABLE\\_ALL\\_CHECKINGS](#) 1
- #define [\\_\\_FFLASFFPACK\\_ffpack\\_ftrtr\\_INL](#)

## Functions

- template<class [Field](#) >  
void [ftrtri](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_UPLO](#) Uplo, const [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, const size\_t threshold=[\\_\\_FFLASFFPACK\\_FTRTRI\\_THRESHOLD](#))  
*Compute the inverse of a triangular matrix.*
- template<class [Field](#) >  
void [ftrtrm](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_SIDE](#) side, const [FFLAS::FFLAS\\_DIAG](#) diag, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda)  
*Compute the product of two triangular matrices of opposite shape.*
- template<class [Field](#) >  
void [trinv\\_left](#) (const [Field](#) &F, const size\_t N, typename [Field::ConstElement\\_ptr](#) L, const size\_t ldl, typename [Field::Element\\_ptr](#) X, const size\_t ldx)

## 13.197.1 Macro Definition Documentation

### 13.197.1.1 [ENABLE\\_ALL\\_CHECKINGS](#)

```
#define ENABLE_ALL_CHECKINGS 1
```

### 13.197.1.2 [\\_\\_FFLASFFPACK\\_ffpack\\_ftrtr\\_INL](#)

```
#define __FFLASFFPACK_ffpack_ftrtr_INL
```

## 13.198 [ffpack\\_invert.inl](#) File Reference

### Namespaces

- namespace [FFPACK](#)  
*Finite **Field** **PACK** Set of elimination based routines for dense linear algebra.*

## Macros

- `#define __FFLASFFPACK_ffpack_invert_INL`

## Functions

- `template<class Field >`  
`Field::Element_ptr Invert` (const `Field` &F, const `size_t` M, typename `Field::Element_ptr` A, const `size_t` lda, int &>nullity)  
*Invert the given matrix in place or computes its nullity if it is singular.*
- `template<class Field >`  
`Field::Element_ptr Invert` (const `Field` &F, const `size_t` M, typename `Field::ConstElement_ptr` A, const `size_t` lda, typename `Field::Element_ptr` X, const `size_t` ldx, int &>nullity)  
*Invert the given matrix or computes its nullity if it is singular.*
- `template<class Field >`  
`Field::Element_ptr Invert2` (const `Field` &F, const `size_t` M, typename `Field::Element_ptr` A, const `size_t` lda, typename `Field::Element_ptr` X, const `size_t` ldx, int &>nullity)  
*Invert the given matrix or computes its nullity if it is singular.*

## 13.198.1 Macro Definition Documentation

### 13.198.1.1 \_\_FFLASFFPACK\_ffpack\_invert\_INL

```
#define __FFLASFFPACK_ffpack_invert_INL
```

## 13.199 ffpack\_krylovelim.inl File Reference

## Macros

- `#define __FFLASFFPACK_ffpack_krylovelim_INL`

## 13.199.1 Macro Definition Documentation

### 13.199.1.1 \_\_FFLASFFPACK\_ffpack\_krylovelim\_INL

```
#define __FFLASFFPACK_ffpack_krylovelim_INL
```

## 13.200 ffpack\_ludivine.inl File Reference

```
#include "fflas-ffpack/fflas/fflas_bounds.inl"
```

## Data Structures

- class `callLUdivine_small< Element >`
- class `callLUdivine_small< double >`
- class `callLUdivine_small< float >`

## Namespaces

- namespace `FFPACK`  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*
- namespace `FFPACK::Protected`

## Macros

- `#define __FFLASFFPACK_ffpack_ludivine_INL`

## Functions

- `template<class Field >`  
`size_t LUdivine_gauss` (const `Field` &F, const `FFLAS::FFLAS_DIAG` Diag, const `size_t` M, const `size_t` N, typename `Field::Element_ptr` A, const `size_t` lda, `size_t` \*P, `size_t` \*Q, const `FFPACK::FFPACK_LU_TAG` LuTag)
- `template<class Field >`  
`size_t LUdivine_small` (const `Field` &F, const `FFLAS::FFLAS_DIAG` Diag, const `FFLAS::FFLAS_TRANSPOSE` trans, const `size_t` M, const `size_t` N, typename `Field::Element_ptr` A, const `size_t` lda, `size_t` \*P, `size_t` \*Q, const `FFPACK::FFPACK_LU_TAG` LuTag)
- `template<class Field >`  
`size_t LUdivine` (const `Field` &F, const `FFLAS::FFLAS_DIAG` Diag, const `FFLAS::FFLAS_TRANSPOSE` trans, const `size_t` M, const `size_t` N, typename `Field::Element_ptr` A, const `size_t` lda, `size_t` \*P, `size_t` \*Q, const `FFPACK::FFPACK_LU_TAG` LuTag, const `size_t` cutoff)
- `template<class Field >`  
`size_t LUdivine_construct` (const `Field` &F, const `FFLAS::FFLAS_DIAG` Diag, const `size_t` M, const `size_t` N, typename `Field::ConstElement_ptr` A, const `size_t` lda, typename `Field::Element_ptr` X, const `size_t` idx, typename `Field::Element_ptr` u, const `size_t` incu, `size_t` \*P, bool computeX, const `FFPACK::FFPACK_MINPOLY_TAG` MinTag, const `size_t` kg\_mc, const `size_t` kg\_mb, const `size_t` kg\_j)

### 13.200.1 Macro Definition Documentation

#### 13.200.1.1 \_\_FFLASFFPACK\_ffpack\_ludivine\_INL

```
#define __FFLASFFPACK_ffpack_ludivine_INL
```

## 13.201 ffpack\_ludivine\_mp.inl File Reference

```
#include <givaro/modular-integer.h>
#include <givaro/givinteger.h>
#include "fflas-ffpack/field/rns-integer-mod.h"
#include "fflas-ffpack/field/rns-integer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/ffpack/ffpack_ludivine.inl"
```

## Namespaces

- namespace `FFPACK`  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

## Macros

- `#define __FFPACK_ludivine_mp_INL`

## Functions

- `template<> size_t LUdivine` (const `Givaro::Modular< Givaro::Integer >` &F, const `FFLAS::FFLAS_DIAG` Diag, const `FFLAS::FFLAS_TRANSPOSE` trans, const `size_t` M, const `size_t` N, typename `Givaro::Integer` \*A, const `size_t` lda, `size_t` \*P, `size_t` \*Q, const `FFPACK::FFPACK_LU_TAG` LuTag, const `size_t` cutoff)

### 13.201.1 Macro Definition Documentation

#### 13.201.1.1 \_\_FFPACK\_ludivine\_mp\_INL

```
#define __FFPACK_ludivine_mp_INL
```



## 13.202 ffpack\_minpoly.inl File Reference

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*
- namespace [FFPACK::Protected](#)

### Macros

- `#define` [\\_\\_FFLASFFPACK\\_ffpack\\_minpoly\\_INL](#)

### Functions

- `template<class Field , class Polynomial >`  
Polynomial & [MinPoly](#) (const [Field](#) &F, Polynomial &minP, const size\_t N, typename [Field::ConstElement\\_ptr](#) A, const size\_t lda)  
*Compute the minimal polynomial of the matrix A.*
- `template<class Field , class Polynomial , class RandIter >`  
Polynomial & [MinPoly](#) (const [Field](#) &F, Polynomial &minP, const size\_t N, typename [Field::ConstElement\\_ptr](#) A, const size\_t lda, RandIter &G)  
*Compute the minimal polynomial of the matrix A.*
- `template<class Field , class Polynomial >`  
Polynomial & [MatVecMinPoly](#) (const [Field](#) &F, Polynomial &minP, const size\_t N, typename [Field::ConstElement\\_ptr](#) A, const size\_t lda, typename [Field::ConstElement\\_ptr](#) v, const size\_t incv)  
*Compute the minimal polynomial of the matrix A and a vector v, namely the first linear dependency relation in the Krylov basis  $(v, Av, \dots, A^N v)$ .*
- `template<class Field , class Polynomial >`  
Polynomial & [MatVecMinPoly](#) (const [Field](#) &F, Polynomial &minP, const size\_t N, typename [Field::ConstElement\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) v, const size\_t incv, typename [Field::Element\\_ptr](#) K, const size\_t ldk, size\_t \*P)  
*Compute the minimal polynomial of the matrix A and a vector v, namely the first linear dependency relation in the Krylov basis  $(v, Av, \dots, A^N v)$ .*
- `template<class Field , class Polynomial >`  
Polynomial & [Hybrid\\_KGF\\_LUK\\_MinPoly](#) (const [Field](#) &F, Polynomial &minP, const size\_t N, typename [Field::ConstElement\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) X, const size\_t ldx, size\_t \*P, const FFPACK\_MINPOLY\_TAG MinTag=FFPACK::FfpackDense, const size\_t kg\_mc=0, const size\_t kg\_↔ mb=0, const size\_t kg\_j=0)

### 13.202.1 Macro Definition Documentation

#### 13.202.1.1 \_\_FFLASFFPACK\_ffpack\_minpoly\_INL

```
#define __FFLASFFPACK_ffpack_minpoly_INL
```

## 13.203 ffpack\_permutation.inl File Reference

```
#include <givaro/zring.h>
#include "fflas-ffpack/fflas/fflas_fassign.h"
```

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- `#define` [\\_\\_FFLASFFPACK\\_ffpack\\_permutation\\_INL](#)
- `#define` [FFLASFFPACK\\_PERM\\_BKSIZE](#) 32

## Functions

- `template<class Field >`  
`void MonotonicApplyP (const Field &F, const FFLAS::FFLAS_SIDE Side, const FFLAS::FFLAS_TRANSPOSE Trans, const size_t M, const size_t ibeg, const size_t iend, typename Field::Element_ptr A, const size_t lda, const size_t *P, const size_t R)`  
*Apply a R-monotonically increasing permutation P, to the matrix A.*
- `template<class Field >`  
`void MonotonicCompress (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, typename Field::Element_ptr A, const size_t lda, const size_t incA, const size_t *MathP, const size_t R, const size_t maxpiv, const size_t rowstomove, const std::vector< bool > &ispiv)`
- `template<class Field >`  
`void MonotonicCompressMorePivots (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, typename Field::Element_ptr A, const size_t lda, const size_t incA, const size_t *MathP, const size_t R, const size_t rowstomove, const size_t lenP)`
- `template<class Field >`  
`void MonotonicCompressCycles (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, typename Field::Element_ptr A, const size_t lda, const size_t incA, const size_t *MathP, const size_t lenP)`
- `template<class Field >`  
`void MonotonicExpand (const Field &F, const FFLAS::FFLAS_SIDE Side, const size_t M, typename Field::Element_ptr A, const size_t lda, const size_t incA, const size_t *MathP, const size_t R, const size_t maxpiv, const size_t rowstomove, const std::vector< bool > &ispiv)`
- `template<class Field >`  
`void applyP_block (const Field &F, const FFLAS::FFLAS_SIDE Side, const FFLAS::FFLAS_TRANSPOSE Trans, const size_t M, const size_t ibeg, const size_t iend, typename Field::Element_ptr A, const size_t lda, const size_t *P)`
- `template<class Field >`  
`void applyP (const Field &F, const FFLAS::FFLAS_SIDE Side, const FFLAS::FFLAS_TRANSPOSE Trans, const size_t m, const size_t ibeg, const size_t iend, typename Field::Element_ptr A, const size_t lda, const size_t *P, const FFLAS::ParSeqHelper::Sequential seq)`
- `template<class Field >`  
`void doApplyS (const Field &F, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr tmp, const size_t width, const size_t M2, const size_t R1, const size_t R2, const size_t R3, const size_t R4)`
- `template<class Field >`  
`void MatrixApplyS (const Field &F, typename Field::Element_ptr A, const size_t lda, const size_t width, const size_t M2, const size_t R1, const size_t R2, const size_t R3, const size_t R4)`
- `template<class Field >`  
`void MatrixApplyS (const Field &F, typename Field::Element_ptr A, const size_t lda, const size_t width, const size_t M2, const size_t R1, const size_t R2, const size_t R3, const size_t R4, const FFLAS::ParSeqHelper::Sequential seq)`
- `template<class Field, class Cut, class Param >`  
`void MatrixApplyS (const Field &F, typename Field::Element_ptr A, const size_t lda, const size_t width, const size_t M2, const size_t R1, const size_t R2, const size_t R3, const size_t R4, const FFLAS::ParSeqHelper::Parallel< Cut, Param > par)`
- `template<class T >`  
`void PermApplyS (T *A, const size_t lda, const size_t width, const size_t M2, const size_t R1, const size_t R2, const size_t R3, const size_t R4)`
- `template<class Field >`  
`void doApplyT (const Field &F, typename Field::Element_ptr A, const size_t lda, typename Field::Element_ptr tmp, const size_t width, const size_t N2, const size_t R1, const size_t R2, const size_t R3, const size_t R4)`
- `template<class Field >`  
`void MatrixApplyT (const Field &F, typename Field::Element_ptr A, const size_t lda, const size_t width, const size_t N2, const size_t R1, const size_t R2, const size_t R3, const size_t R4)`
- `template<class Field >`  
`void MatrixApplyT (const Field &F, typename Field::Element_ptr A, const size_t lda, const size_t width, const size_t N2, const size_t R1, const size_t R2, const size_t R3, const size_t R4, const FFLAS::ParSeqHelper::Sequential seq)`

- `template<class Field , class Cut , class Param >`  
`void MatrixApplyT (const Field &F, typename Field::Element_ptr A, const size_t lda, const size_t width, const size_t N2, const size_t R1, const size_t R2, const size_t R3, const size_t R4, const FFLAS::ParSeqHelper::Parallel< Cut, Param > par)`
- `template<class T >`  
`void PermApplyT (T *A, const size_t lda, const size_t width, const size_t N2, const size_t R1, const size_t R2, const size_t R3, const size_t R4)`
- `void LAPACKPerm2MathPerm (size_t *MathP, const size_t *LapackP, const size_t N)`  
*Conversion of a permutation from LAPACK format to Math format.*
- `void MathPerm2LAPACKPerm (size_t *LapackP, const size_t *MathP, const size_t N)`  
*Conversion of a permutation from Maths format to LAPACK format.*
- `void composePermutationsLLL (size_t *P1, const size_t *P2, const size_t R, const size_t N)`  
*Computes  $P1 \times \text{Diag}(I_R, P2)$  where  $P1$  is a LAPACK and  $P2$  a LAPACK permutation and store the result in  $P1$  as a LAPACK permutation.*
- `void composePermutationsLLM (size_t *MathP, const size_t *P1, const size_t *P2, const size_t R, const size_t N)`  
*Computes  $P1 \times \text{Diag}(I_R, P2)$  where  $P1$  is a LAPACK and  $P2$  a LAPACK permutation and store the result in  $MathP$  as a MathPermutation format.*
- `void composePermutationsMLM (size_t *MathP1, const size_t *P2, const size_t R, const size_t N)`  
*Computes  $MathP1 \times \text{Diag}(I_R, P2)$  where  $MathP1$  is a MathPermutation and  $P2$  a LAPACK permutation and store the result in  $MathP1$  as a MathPermutation format.*
- `void cyclic_shift_mathPerm (size_t *P, const size_t s)`
- `template<class Field >`  
`void cyclic_shift_row_col (const Field &F, typename Field::Element_ptr A, size_t m, size_t n, size_t lda)`
- `template<class Field >`  
`void cyclic_shift_row (const Field &F, typename Field::Element_ptr A, size_t m, size_t n, size_t lda)`
- `template<typename T >`  
`void cyclic_shift_row (const RNSIntegerMod< T > &F, typename T::Element_ptr A, size_t m, size_t n, size_t lda)`
- `template<class Field >`  
`void cyclic_shift_col (const Field &F, typename Field::Element_ptr A, size_t m, size_t n, size_t lda)`
- `template<typename T >`  
`void cyclic_shift_col (const RNSIntegerMod< T > &F, typename T::Element_ptr A, size_t m, size_t n, size_t lda)`
- `template<class Field >`  
`void applyP (const Field &F, const FFLAS::FFLAS_SIDE Side, const FFLAS::FFLAS_TRANSPOSE Trans, const size_t M, const size_t ibeg, const size_t iend, typename Field::Element_ptr A, const size_t lda, const size_t *P)`  
*Computes  $P1 \times \text{Diag}(I_R, P2)$  where  $P1$  is a LAPACK and  $P2$  a LAPACK permutation and store the result in  $P1$  as a LAPACK permutation.*
- `template<class Field , class Cut , class Param >`  
`void applyP (const Field &F, const FFLAS::FFLAS_SIDE Side, const FFLAS::FFLAS_TRANSPOSE Trans, const size_t m, const size_t ibeg, const size_t iend, typename Field::Element_ptr A, const size_t lda, const size_t *P, const FFLAS::ParSeqHelper::Parallel< Cut, Param > par)`

## 13.203.1 Macro Definition Documentation

### 13.203.1.1 \_\_FFLASFFPACK\_ffpack\_permutation\_INL

```
#define __FFLASFFPACK_ffpack_permutation_INL
```

### 13.203.1.2 FFLASFFPACK\_PERM\_BKSIZE

```
#define FFLASFFPACK_PERM_BKSIZE 32
```

## 13.204 ffpack\_pluq.inl File Reference

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- #define [\\_\\_FFLASFFPACK\\_ffpack\\_pluq\\_INL](#)
- #define [CROUT](#)

### Functions

- template<class [Field](#) >  
size\_t [PLUQ\\_basecaseV3](#) (const [Field](#) &Fi, const [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, typename [Field::Element](#) \*A, const size\_t lda, size\_t \*P, size\_t \*Q)
- template<class [Field](#) >  
size\_t [PLUQ\\_basecaseV2](#) (const [Field](#) &Fi, const [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, typename [Field::Element](#) \*A, const size\_t lda, size\_t \*P, size\_t \*Q)
- template<class [Field](#) >  
size\_t [PLUQ\\_basecaseCrout](#) (const [Field](#) &Fi, const [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*P, size\_t \*Q)
- template<class [Field](#) >  
size\_t [\\_PLUQ](#) (const [Field](#) &Fi, const [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*P, size\_t \*Q, size\_t BCThreshold)
- template<class [Field](#) >  
size\_t [PLUQ](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*P, size\_t \*Q, const [FFLAS::ParSeqHelper::Sequential](#) &PHelper, size\_t BCThreshold=[\\_\\_FFLASFFPACK\\_PLUQ\\_THRESHOLD](#))
- template<class [Field](#) >  
size\_t [PLUQ](#) (const [Field](#) &F, const [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*P, size\_t \*Q)

*Compute a PLUQ factorization of the given matrix.*

### 13.204.1 Macro Definition Documentation

#### 13.204.1.1 [\\_\\_FFLASFFPACK\\_ffpack\\_pluq\\_INL](#)

```
#define __FFLASFFPACK_ffpack_pluq_INL
```

#### 13.204.1.2 [CROUT](#)

```
#define CROUT
```

## 13.205 ffpack\_pluq\_mp.inl File Reference

```
#include "fflas-ffpack/field/rns-integer-mod.h"
#include "fflas-ffpack/field/rns-integer.h"
#include "fflas-ffpack/fflas-ffpack.h"
#include "givaro/givinteger.h"
#include "givaro/modular-integer.h"
```

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

## Macros

- `#define __FFPACK_pluq_mp_INL`

## Functions

- `template<class Cut , class Param >`  
`size_t PLUQ (const Givaro::Modular< Givaro::Integer > &F, const FFLAS::FFLAS_DIAG Diag, const size_t`  
`M, const size_t N, typename Givaro::Integer *A, const size_t lda, size_t *P, size_t *Q, size_t BCThreshold,`  
`FFLAS::ParSeqHelper::Parallel< Cut, Param > &PSHelper)`

## 13.205.1 Macro Definition Documentation

### 13.205.1.1 \_\_FFPACK\_pluq\_mp\_INL

```
#define __FFPACK_pluq_mp_INL
```

## 13.206 ffpack\_ppluq.inl File Reference

## Namespaces

- namespace `FFPACK`  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

## Macros

- `#define __FFLASFFPACK_ffpack_ppluq_INL`
- `#define __FFLAS__TRSM_READONLY`
- `#define PBASECASE_K 256`

## Functions

- `template<class Field >`  
`void threads_fgemm (const size_t m, const size_t n, const size_t r, int nbthreads, size_t *W1, size_t *W2,`  
`size_t *W3, size_t gamma)`
- `template<class Field >`  
`void threads_ftsm (const size_t m, const size_t n, int nbthreads, size_t *t1, size_t *t2)`
- `template<class Field >`  
`size_t PLUQ (const Field &Fi, const FFLAS::FFLAS_DIAG Diag, const size_t M, const size_t N, type-`  
`name Field::Element_ptr A, const size_t lda, size_t *P, size_t *Q, const FFLAS::ParSeqHelper::Parallel<`  
`FFLAS::CuttingStrategy::Recursive, FFLAS::StrategyParameter::Threads > &PSHelper)`
- `template<class Field >`  
`size_t pPLUQ (const Field &F, const FFLAS::FFLAS_DIAG Diag, const size_t M, const size_t N, typename`  
`Field::Element_ptr A, const size_t lda, size_t *P, size_t *Q)`

## 13.206.1 Macro Definition Documentation

### 13.206.1.1 \_\_FFLASFFPACK\_ffpack\_ppluq\_INL

```
#define __FFLASFFPACK_ffpack_ppluq_INL
```

### 13.206.1.2 \_\_FFLAS\_\_TRSM\_READONLY

```
#define __FFLAS__TRSM_READONLY
```

### 13.206.1.3 PBASECASE\_K

```
#define PBASECASE_K 256
```

## 13.207 ffpack\_rankprofiles.inl File Reference

### Namespaces

- namespace [FFPACK](#)  
*Finite Field PACK Set of elimination based routines for dense linear algebra.*

### Macros

- #define [\\_\\_FFLASFFPACK\\_ffpack\\_rank\\_profiles\\_INL](#)

### Functions

- template<class [Field](#) >  
size\_t [RowRankProfile](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*rkprofile, const FFPACK\_LU\_TAG LuTag=[FfpackSlabRecursive](#))  
*Computes the row rank profile of A.*
- template<class [Field](#) >  
size\_t [pRowRankProfile](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*rkprofile, size\_t numthreads=0, const FFPACK\_LU\_TAG LuTag=[FfpackTileRecursive](#))
- template<class [Field](#), class PSHelper >  
size\_t [RowRankProfile](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*rkprofile, const FFPACK\_LU\_TAG LuTag, PSHelper &psH)
- template<class [Field](#) >  
size\_t [ColumnRankProfile](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*rkprofile, const FFPACK\_LU\_TAG LuTag=[FfpackSlabRecursive](#))  
*Computes the column rank profile of A.*
- template<class [Field](#) >  
size\_t [pColumnRankProfile](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*rkprofile, size\_t numthreads=0, const FFPACK\_LU\_TAG LuTag=[FfpackTileRecursive](#))
- template<class [Field](#), class PSHelper >  
size\_t [ColumnRankProfile](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*rkprofile, const FFPACK\_LU\_TAG LuTag, PSHelper &psH)
- void [RankProfileFromLU](#) (const size\_t \*P, const size\_t N, const size\_t R, size\_t \*rkprofile, const FFPACK\_LU\_TAG LuTag)  
*Recovers the column/row rank profile from the permutation of an LU decomposition.*
- size\_t [LeadingSubmatrixRankProfiles](#) (const size\_t M, const size\_t N, const size\_t R, const size\_t LSm, const size\_t LSn, const size\_t \*P, const size\_t \*Q, size\_t \*RRP, size\_t \*CRP)  
*Recovers the row and column rank profiles of any leading submatrix from the PLUQ decomposition.*
- template<class [Field](#) >  
size\_t [RowRankProfileSubmatrixIndices](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*&rowindices, size\_t \*&colindices, size\_t &R)  
*RowRankProfileSubmatrixIndices.*
- template<class [Field](#) >  
size\_t [ColRankProfileSubmatrixIndices](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, size\_t \*&rowindices, size\_t \*&colindices, size\_t &R)  
*Computes the indices of the submatrix  $r \times r$  X of A whose columns correspond to the column rank profile of A.*
- template<class [Field](#) >  
size\_t [RowRankProfileSubmatrix](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) &X, size\_t &R)  
*Computes the  $r \times r$  submatrix X of A, by picking the row rank profile rows of A.*
- template<class [Field](#) >  
size\_t [ColRankProfileSubmatrix](#) (const [Field](#) &F, const size\_t M, const size\_t N, typename [Field::Element\\_ptr](#) A, const size\_t lda, typename [Field::Element\\_ptr](#) &X, size\_t &R)  
*Compute the  $r \times r$  submatrix X of A, by picking the row rank profile rows of A.*

- `template<class Field >`  
`Field::Element_ptr LQUPtoInverseOfFullRankMinor (const Field &F, const size_t rank, typename`  
`Field::Element_ptr A_factors, const size_t lda, const size_t *QtPointer, typename Field::Element_ptr X,`  
`const size_t ldx)`  
`LQUPtoInverseOfFullRankMinor.`

## 13.207.1 Macro Definition Documentation

### 13.207.1.1 \_\_FFLASFFPACK\_ffpack\_rank\_profiles\_INL

```
#define __FFLASFFPACK_ffpack_rank_profiles_INL
```

## 13.208 field-traits.h File Reference

Field Traits.

```
#include <type_traits>
#include "fflas-ffpack/field/rns-double-elt.h"
#include "recint/rmint.h"
#include "givaro/modular-general.h"
#include "givaro/zring.h"
```

### Data Structures

- struct [GenericTag](#)  
*generic ring.*
- struct [ModularTag](#)  
*This is a modular field like e.g. Modular<T> or ModularBalanced<T>*
- struct [UnparametricTag](#)  
*If the field uses a representation with infix operators.*
- struct [DefaultTag](#)  
*No specific mode of action: use standard field operations.*
- struct [DefaultBoundedTag](#)  
*Use standard field operations, but keeps track of bounds on input and output.*
- struct [ConvertTo< T >](#)  
*Force conversion to appropriate element type of ElementCategory T.*
- struct [DelayedTag](#)  
*Performs field operations with delayed mod reductions. Ensures result is reduced.*
- struct [LazyTag](#)  
*Performs field operations with delayed mod only when necessary. Result may not be reduced.*
- struct [GenericTag](#)  
*default is generic*
- struct [MachineFloatTag](#)  
*float or double*
- struct [MachineIntTag](#)  
*short, int, long, long long, and unsigned variants*
- struct [FixedPrecIntTag](#)  
*Fixed precision integers above machine precision: Givaro::recInt.*
- struct [ArbitraryPrecIntTag](#)  
*Arbitrary precision integers: GMP.*
- struct [RNSElementTag](#)  
*Representation in a Residue Number System.*
- struct [ElementTraits< Element >](#)

*ElementTraits.*

- struct `ElementTraits< float >`
- struct `ElementTraits< double >`
- struct `ElementTraits< int8_t >`
- struct `ElementTraits< int16_t >`
- struct `ElementTraits< int32_t >`
- struct `ElementTraits< int64_t >`
- struct `ElementTraits< uint8_t >`
- struct `ElementTraits< uint16_t >`
- struct `ElementTraits< uint32_t >`
- struct `ElementTraits< uint64_t >`
- struct `ElementTraits< Givaro::Integer >`
- struct `ElementTraits< Reclnt::rint< K > >`
- struct `ElementTraits< Reclnt::ruint< K > >`
- struct `ElementTraits< Reclnt::rmint< K, MG > >`
- struct `ElementTraits< FFPACK::rns_double_elt >`
- struct `ModeTraits< Field >`

*ModeTraits.*

- struct `ModeTraits< Givaro::Modular< Element, Compute > >`
- struct `ModeTraits< Givaro::Modular< int64_t, uint64_t > >`
- struct `ModeTraits< Givaro::Modular< int8_t, Compute > >`
- struct `ModeTraits< Givaro::Modular< int16_t, Compute > >`
- struct `ModeTraits< Givaro::Modular< int32_t, Compute > >`
- struct `ModeTraits< Givaro::Modular< uint8_t, Compute > >`
- struct `ModeTraits< Givaro::Modular< uint16_t, Compute > >`
- struct `ModeTraits< Givaro::Modular< uint32_t, Compute > >`
- struct `ModeTraits< Givaro::Modular< Givaro::Integer, Compute > >`
- struct `ModeTraits< Givaro::Modular< Reclnt::ruint< K >, Compute > >`
- struct `ModeTraits< Givaro::ModularBalanced< Element > >`
- struct `ModeTraits< Givaro::ModularBalanced< int8_t > >`
- struct `ModeTraits< Givaro::ModularBalanced< int16_t > >`
- struct `ModeTraits< Givaro::ModularBalanced< int32_t > >`
- struct `ModeTraits< Givaro::ModularBalanced< Givaro::Integer > >`
- struct `ModeTraits< Givaro::ZRing< Givaro::Integer > >`
- struct `ModeTraits< Givaro::ZRing< float > >`
- struct `ModeTraits< Givaro::ZRing< double > >`
- struct `ModeTraits< Givaro::Montgomery< T > >`
- struct `FieldTraits< Field >`

*FieldTrait.*

- struct `FieldTraits< Givaro::ZRing< Reclnt::ruint< K > > >`
- struct `FieldTraits< Givaro::Modular< Element > >`
- struct `FieldTraits< Givaro::ModularBalanced< Element > >`
- struct `FieldTraits< Givaro::ZRing< double > >`
- struct `FieldTraits< Givaro::ZRing< float > >`
- struct `FieldTraits< Givaro::ZRing< int16_t > >`
- struct `FieldTraits< Givaro::ZRing< uint16_t > >`
- struct `FieldTraits< Givaro::ZRing< int32_t > >`
- struct `FieldTraits< Givaro::ZRing< uint32_t > >`
- struct `FieldTraits< Givaro::ZRing< int64_t > >`
- struct `FieldTraits< Givaro::ZRing< uint64_t > >`
- struct `FieldTraits< Givaro::ZRing< Givaro::Integer > >`
- struct `FieldTraits< FFPACK::RNSInteger< T > >`
- struct `FieldTraits< FFPACK::RNSIntegerMod< T > >`
- struct `associatedDelayedField< Field >`
- struct `associatedDelayedField< const Givaro::Modular< T, X > >`
- struct `associatedDelayedField< const Givaro::ModularBalanced< T > >`
- struct `associatedDelayedField< const Givaro::ZRing< T > >`
- struct `associatedDelayedField< const FFPACK::RNSIntegerMod< RNS > >`



## Namespaces

- namespace [Reclnt](#)
- namespace [Givaro](#)
- namespace [FFPACK](#)

*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

- namespace [FFLAS](#)
- namespace [FFLAS::FieldCategories](#)

*Traits and categories will need to be placed in a proper file later.*

- namespace [FFLAS::ModeCategories](#)
- namespace [FFLAS::ElementCategories](#)

*Specifies the mode of action for an algorithm w.r.t.*

## Functions

- template<class [Field](#) , class enable = void>  
Field::Residu\_t [maxCardinality](#) ()
- template<> uint64\_t [maxCardinality](#)< [Givaro::Modular](#)< int64\_t > > ()
- template<> uint32\_t [maxCardinality](#)< [Givaro::Modular](#)< int32\_t > > ()
- template<class [Field](#) >  
Field::Residu\_t [minCardinality](#) ()

### 13.208.1 Detailed Description

Field Traits.

## 13.209 field.doxy File Reference

### 13.210 rns-double-elt.h File Reference

rns elt structure with double support

```
#include "fflas-ffpack/utils/fflas_memory.h"
#include "fflas-ffpack/utils/cast.h"
```

## Data Structures

- struct [rns\\_double\\_elt](#)
- struct [rns\\_double\\_elt\\_ptr](#)
- struct [rns\\_double\\_elt\\_cstptr](#)

## Namespaces

- namespace [FFPACK](#)

*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

## Functions

- template<> [rns\\_double\\_elt\\_ptr](#) fflas\_const\_cast ([rns\\_double\\_elt\\_cstptr](#) x)
- template<> [rns\\_double\\_elt\\_cstptr](#) fflas\_const\_cast ([rns\\_double\\_elt\\_ptr](#) x)

### 13.210.1 Detailed Description

rns elt structure with double support

## 13.211 rns-double-recint.inl File Reference

```
#include "fflas-ffpack/fflas/fflas_freduce.h"
```

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- #define [\\_\\_FFLASFFPACK\\_field\\_rns\\_double\\_recint\\_INL](#)

### 13.211.1 Macro Definition Documentation

#### 13.211.1.1 [\\_\\_FFLASFFPACK\\_field\\_rns\\_double\\_recint\\_INL](#)

```
#define __FFLASFFPACK_field_rns_double_recint_INL
```

## 13.212 rns-double.h File Reference

rns structure with double support

```
#include <iterator>
#include <vector>
#include <givaro/modular-floating.h>
#include <givaro/givinteger.h>
#include <givaro/givintprime.h>
#include "givaro/modular-extended.h"
#include <recint/ruint.h>
#include "fflas-ffpack/config-blas.h"
#include "fflas-ffpack/utils/fflas_memory.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include "fflas-ffpack/field/rns-double-elt.h"
#include "rns-double.inl"
#include "rns-double-recint.inl"
```

### Data Structures

- struct [rns\\_double](#)
- struct [rns\\_double\\_extended](#)
- class [rnsRandIter](#)< [RNS](#) >

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*
- namespace [FFLAS](#)

### Macros

- #define [ROUND\\_DOWN](#)(x, s) ((x) & ~((s)-1))

### Functions

- template<> void [fflas\\_delete](#) (FFPACK::rns\_double\_elt\_ptr A)
- template<> void [fflas\\_delete](#) (FFPACK::rns\_double\_elt\_cstptr A)

### 13.212.1 Detailed Description

rns structure with double support

### 13.212.2 Macro Definition Documentation

#### 13.212.2.1 ROUND\_DOWN

```
#define ROUND_DOWN(
 x,
 s) ((x) & ~((s)-1))
```

## 13.213 rns-double.inl File Reference

```
#include "fflas-ffpack/fflas/fflas_freduce.h"
```

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- #define [\\_\\_FFLASFFPACK\\_field\\_rns\\_double\\_INL](#)

### 13.213.1 Macro Definition Documentation

#### 13.213.1.1 \_\_FFLASFFPACK\_field\_rns\_double\_INL

```
#define __FFLASFFPACK_field_rns_double_INL
```

## 13.214 rns-integer-mod.h File Reference

representation of  $\mathbb{Z}/p\mathbb{Z}$  using RNS representation (note: fixed precision)

```
#include <vector>
#include <cmath>
#include <recint/recint.h>
#include <givaro/modular-integer.h>
#include <givaro/givinteger.h>
#include <givaro/udl.h>
#include "givaro/modular-extended.h"
#include "fflas-ffpack/field/rns-double.h"
#include "fflas-ffpack/field/rns-integer.h"
#include "fflas-ffpack/fflas/fflas_level1.inl"
#include "fflas-ffpack/fflas/fflas_level2.inl"
#include "fflas-ffpack/fflas/fflas_level3.inl"
#include "fflas-ffpack/fflas/fflas_enum.h"
#include "fflas-ffpack/fflas/fflas_fscal_mp.inl"
```

### Data Structures

- class [RNSIntegerMod< RNS >](#)
- class [RNSIntegerMod< RNS >::RandIter](#)

## Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*
- namespace [FFLAS](#)

## Functions

- `template<> FFPACK::rns_double_elt_ptr fflas_new` (const [FFPACK::RNSIntegerMod](#)< [FFPACK::rns\\_double](#) > &F, const `size_t` m, const `Alignment` align)
- `template<> FFPACK::rns_double_elt_ptr fflas_new` (const [FFPACK::RNSIntegerMod](#)< [FFPACK::rns\\_double](#) > &F, const `size_t` m, const `size_t` n, const `Alignment` align)
- `template<typename RNS >`  
`void finit_rns` (const [FFPACK::RNSIntegerMod](#)< [RNS](#) > &F, const `size_t` m, const `size_t` n, `size_t` k, const `Givaro::Integer` \*B, const `size_t` ldb, `typename RNS::Element_ptr` A)
- `template<typename RNS >`  
`void finit_trans_rns` (const [FFPACK::RNSIntegerMod](#)< [RNS](#) > &F, const `size_t` m, const `size_t` n, `size_t` k, const `Givaro::Integer` \*B, const `size_t` ldb, `typename RNS::Element_ptr` A)
- `template<typename RNS >`  
`void fconvert_rns` (const [FFPACK::RNSIntegerMod](#)< [RNS](#) > &F, const `size_t` m, const `size_t` n, `Givaro::Integer` alpha, `Givaro::Integer` \*B, const `size_t` ldb, `typename RNS::ConstElement_ptr` A)
- `template<typename RNS >`  
`void fconvert_trans_rns` (const [FFPACK::RNSIntegerMod](#)< [RNS](#) > &F, const `size_t` m, const `size_t` n, `Givaro::Integer` alpha, `Givaro::Integer` \*B, const `size_t` ldb, `typename RNS::ConstElement_ptr` A)

### 13.214.1 Detailed Description

representation of  $\mathbb{Z}/p\mathbb{Z}$  using RNS representation (note: fixed precision)

## 13.215 rns-integer.h File Reference

representation of  $\mathbb{Z}$  using RNS representation (note: fixed precision)

```
#include <givaro/givinteger.h>
#include "fflas-ffpack/field/rns-double.h"
```

## Data Structures

- class [RNSInteger](#)< [RNS](#) >
- class [RNSInteger](#)< [RNS](#) >::RandIter

## Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*
- namespace [FFLAS](#)

## Functions

- `template<> FFPACK::rns_double_elt_ptr fflas_new` (const [FFPACK::RNSInteger](#)< [FFPACK::rns\\_double](#) > &F, const `size_t` m, const `Alignment` align)
- `template<> FFPACK::rns_double_elt_ptr fflas_new` (const [FFPACK::RNSInteger](#)< [FFPACK::rns\\_double](#) > &F, const `size_t` m, const `size_t` n, const `Alignment` align)
- `template<typename RNS >`  
`void finit_rns` (const [FFPACK::RNSInteger](#)< [RNS](#) > &F, const `size_t` m, const `size_t` n, `size_t` k, const `Givaro::Integer` \*B, const `size_t` ldb, `typename FFPACK::RNSInteger< RNS >::Element_ptr A)`
- `template<typename RNS >`  
`void fconvert_rns` (const [FFPACK::RNSInteger](#)< [RNS](#) > &F, const `size_t` m, const `size_t` n, `Givaro::Integer` alpha, `Givaro::Integer` \*B, const `size_t` ldb, `typename FFPACK::RNSInteger< RNS >::ConstElement_ptr A)`

### 13.215.1 Detailed Description

representation of  $\mathbb{Z}$  using RNS representation (note: fixed precision)

## 13.216 rns.h File Reference

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

### 13.217 rns.inl File Reference

```
#include "rns-double.h"
#include "rns-integer.h"
#include "rns-integer-mod.h"
```

### Macros

- #define [\\_\\_FFLASFFPACK\\_field\\_rns\\_INL](#)

### 13.217.1 Macro Definition Documentation

#### 13.217.1.1 \_\_FFLASFFPACK\_field\_rns\_INL

```
#define __FFLASFFPACK_field_rns_INL
```

### 13.218 interfaces.doxy File Reference

### 13.219 fflas\_c.h File Reference

```
#include <stdbool.h>
#include <stdlib.h>
#include <inttypes.h>
```

### Macros

- #define [FFLAS\\_COMPILED](#)

### Enumerations

- enum [FFLAS\\_C\\_ORDER](#) { [FflasRowMajor](#) = 101 , [FflasColMajor](#) = 102 }  
*Storage by row or col ?*
- enum [FFLAS\\_C\\_TRANSPOSE](#) { [FflasNoTrans](#) = 111 , [FflasTrans](#) = 112 }  
*Is matrix transposed ?*
- enum [FFLAS\\_C\\_UPLO](#) { [FflasUpper](#) = 121 , [FflasLower](#) = 122 }  
*Is triangular matrix's shape upper ?*
- enum [FFLAS\\_C\\_DIAG](#) { [FflasNonUnit](#) = 131 , [FflasUnit](#) = 132 }  
*Is the triangular matrix implicitly unit diagonal ?*
- enum [FFLAS\\_C\\_SIDE](#) { [FflasLeft](#) = 141 , [FflasRight](#) = 142 }  
*On what side ?*
- enum [FFLAS\\_C\\_BASE](#) { [FflasDouble](#) = 151 , [FflasFloat](#) = 152 , [FflasGeneric](#) = 153 }  
*FFLAS\_C\_BASE determines the type of the element representation for Matrix Mult kernel.*

## Functions

- void [freducein\\_1\\_modular\\_double](#) (const double p, const size\_t n, double \*X, const size\_t incX, bool positive)
- void [freduce\\_1\\_modular\\_double](#) (const double F, const size\_t n, const double \*Y, const size\_t incY, double \*X, const size\_t incX, bool positive)
- void [fnegin\\_1\\_modular\\_double](#) (const double F, const size\_t n, double \*X, const size\_t incX, bool positive)
- void [fneg\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*Y, const size\_t incY, double \*X, const size\_t incX, bool positive)
- void [fzero\\_1\\_modular\\_double](#) (const double p, const size\_t n, double \*X, const size\_t incX, bool positive)
- bool [fiszero\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*X, const size\_t incX, bool positive)
- bool [fequal\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*X, const size\_t incX, const double \*Y, const size\_t incY, bool positive)
- void [fassign\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*Y, const size\_t incY, double \*X, const size\_t incX, bool positive)
- void [fscal\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double alpha, double \*X, const size\_t incX, bool positive)
- void [fscal\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double alpha, const double \*X, const size\_t incX, double \*Y, const size\_t incY, bool positive)
- void [faxpy\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double alpha, const double \*X, const size\_t incX, double \*Y, const size\_t incY, bool positive)
- double [fdot\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*X, const size\_t incX, const double \*Y, const size\_t incY, bool positive)
- void [fswap\\_1\\_modular\\_double](#) (const double p, const size\_t n, double \*X, const size\_t incX, double \*Y, const size\_t incY, bool positive)
- void [fadd\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*A, const size\_t incA, const double \*B, const size\_t incB, double \*C, const size\_t incC, bool positive)
- void [fsub\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*A, const size\_t incA, const double \*B, const size\_t incB, double \*C, const size\_t incC, bool positive)
- void [faddin\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*B, const size\_t incB, double \*C, const size\_t incC, bool positive)
- void [fsubin\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*B, const size\_t incB, double \*C, const size\_t incC, bool positive)
- void [fassign\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*B, const size\_t incB, double \*A, const size\_t incA, bool positive)
- void [fzero\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, double \*A, const size\_t incA, bool positive)
- bool [fequal\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*A, const size\_t incA, const double \*B, const size\_t incB, bool positive)
- bool [fiszero\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*A, const size\_t incA, bool positive)
- void [fidentity\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, double \*A, const size\_t incA, const double d, bool positive)
- void [freducein\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, double \*A, const size\_t incA, bool positive)
- void [freduce\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*B, const size\_t incB, double \*A, const size\_t incA, bool positive)
- void [fnegin\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, double \*A, const size\_t incA, bool positive)
- void [fneg\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*B, const size\_t incB, double \*A, const size\_t incA, bool positive)
- void [fscal\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double alpha, double \*A, const size\_t incA, bool positive)
- void [fscal\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double alpha, const double \*A, const size\_t incA, double \*B, const size\_t incB, bool positive)
- void [faxpy\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double alpha, const double \*X, const size\_t incX, double \*Y, const size\_t incY, bool positive)

- void [fmove\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, double \*A, const size\_t ldA, double \*B, const size\_t ldB, bool positive)
- void [fadd\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*A, const size\_t ldA, const double \*B, const size\_t ldB, double \*C, const size\_t ldC, bool positive)
- void [fsub\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*A, const size\_t ldA, const double \*B, const size\_t ldB, double \*C, const size\_t ldC, bool positive)
- void [fsubin\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*B, const size\_t ldB, double \*C, const size\_t ldC, bool positive)
- void [faddin\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*B, const size\_t ldB, double \*C, const size\_t ldC, bool positive)
- double \* [fgemv\\_2\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_TRANSPOSE](#) TransA, const size\_t m, const size\_t n, const double alpha, const double \*A, const size\_t ldA, const double \*X, const size\_t incX, const double beta, double \*Y, const size\_t incY, bool positive)
- void [fger\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double alpha, const double \*x, const size\_t incX, const double \*y, const size\_t incY, double \*A, const size\_t ldA, bool positive)
- void [ftrsv\\_2\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const enum [FFLAS\\_C\\_TRANSPOSE](#) TransA, const enum [FFLAS\\_C\\_DIAG](#) Diag, const size\_t n, const double \*A, const size\_t ldA, double \*X, int incX, bool positive)
- void [ftrsm\\_3\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_SIDE](#) Side, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const enum [FFLAS\\_C\\_TRANSPOSE](#) TransA, const enum [FFLAS\\_C\\_DIAG](#) Diag, const size\_t m, const size\_t n, const double alpha, const double \*A, const size\_t ldA, double \*B, const size\_t ldB, bool positive)
- void [ftrmm\\_3\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_SIDE](#) Side, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const enum [FFLAS\\_C\\_TRANSPOSE](#) TransA, const enum [FFLAS\\_C\\_DIAG](#) Diag, const size\_t m, const size\_t n, const double alpha, double \*A, const size\_t ldA, double \*B, const size\_t ldB, bool positive)
- double \* [fgemm\\_3\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_TRANSPOSE](#) tA, const enum [FFLAS\\_C\\_TRANSPOSE](#) tB, const size\_t m, const size\_t n, const size\_t k, const double alpha, const double \*A, const size\_t ldA, const double \*B, const size\_t ldB, const double beta, double \*C, const size\_t ldC, bool positive)
- double \* [fsquare\\_3\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_TRANSPOSE](#) tA, const size\_t n, const double alpha, const double \*A, const size\_t ldA, const double beta, double \*C, const size\_t ldC, bool positive)

## 13.219.1 Macro Definition Documentation

### 13.219.1.1 FFLAS\_COMPILED

```
#define FFLAS_COMPILED
```

## 13.219.2 Enumeration Type Documentation

### 13.219.2.1 FFLAS\_C\_ORDER

```
enum FFLAS_C_ORDER
```

Storage by row or col ?

Enumerator

|                               |           |
|-------------------------------|-----------|
| <a href="#">FflasRowMajor</a> | row major |
| <a href="#">FflasColMajor</a> | col major |

### 13.219.2.2 FFLAS\_C\_TRANSPOSE

```
enum FFLAS_C_TRANSPOSE
```

Is matrix transposed ?

**Enumerator**

|              |                           |
|--------------|---------------------------|
| FflasNoTrans | Matrix is not transposed. |
| FflasTrans   | Matrix is transposed.     |

**13.219.2.3 FFLAS\_C\_UPLO**enum [FFLAS\\_C\\_UPLO](#)

Is triangular matrix's shape upper ?

**Enumerator**

|            |                                                                        |
|------------|------------------------------------------------------------------------|
| FflasUpper | Triangular matrix is Upper triangular (if $i > j$ then $T_{i,j} = 0$ ) |
| FflasLower | Triangular matrix is Lower triangular (if $i < j$ then $T_{i,j} = 0$ ) |

**13.219.2.4 FFLAS\_C\_DIAG**enum [FFLAS\\_C\\_DIAG](#)

Is the triangular matrix implicitly unit diagonal ?

**Enumerator**

|              |                                                                   |
|--------------|-------------------------------------------------------------------|
| FflasNonUnit | Triangular matrix has an explicit arbitrary diagonal.             |
| FflasUnit    | Triangular matrix has an implicit unit diagonal ( $T_{i,i} = 1$ ) |

**13.219.2.5 FFLAS\_C\_SIDE**enum [FFLAS\\_C\\_SIDE](#)

On what side ?

**Enumerator**

|            |                                 |
|------------|---------------------------------|
| FflasLeft  | Operator applied on the left.   |
| FflasRight | Operator applied on the righth. |

**13.219.2.6 FFLAS\_C\_BASE**enum [FFLAS\\_C\\_BASE](#)

FFLAS\_C\_BASE determines the type of the element representation for Matrix Mult kernel.  
(deprecated, should not be used)

**Enumerator**

|              |                                                                            |
|--------------|----------------------------------------------------------------------------|
| FflasDouble  | to use the double precision BLAS                                           |
| FflasFloat   | to use the single precision BLAS                                           |
| FflasGeneric | for any other domain, that can not be converted to floating point integers |



## 13.219.3 Function Documentation

### 13.219.3.1 `freducein_1_modular_double()`

```
void freducein_1_modular_double (
 const double p,
 const size_t n,
 double * X,
 const size_t incX,
 bool positive)
```

### 13.219.3.2 `freduce_1_modular_double()`

```
void freduce_1_modular_double (
 const double F,
 const size_t n,
 const double * Y,
 const size_t incY,
 double * X,
 const size_t incX,
 bool positive)
```

### 13.219.3.3 `fnegin_1_modular_double()`

```
void fnegin_1_modular_double (
 const double F,
 const size_t n,
 double * X,
 const size_t incX,
 bool positive)
```

### 13.219.3.4 `fneg_1_modular_double()`

```
void fneg_1_modular_double (
 const double p,
 const size_t n,
 const double * Y,
 const size_t incY,
 double * X,
 const size_t incX,
 bool positive)
```

### 13.219.3.5 `fzero_1_modular_double()`

```
void fzero_1_modular_double (
 const double p,
 const size_t n,
 double * X,
 const size_t incX,
 bool positive)
```

### 13.219.3.6 `fiszero_1_modular_double()`

```
bool fiszero_1_modular_double (
 const double p,
 const size_t n,
 const double * X,
 const size_t incX,
 bool positive)
```

**13.219.3.7 fequal\_1\_modular\_double()**

```
bool fequal_1_modular_double (
 const double p,
 const size_t n,
 const double * X,
 const size_t incX,
 const double * Y,
 const size_t incY,
 bool positive)
```

**13.219.3.8 fassign\_1\_modular\_double()**

```
void fassign_1_modular_double (
 const double p,
 const size_t n,
 const double * Y,
 const size_t incY,
 double * X,
 const size_t incX,
 bool positive)
```

**13.219.3.9 fscal\_1\_modular\_double()**

```
void fscal_1_modular_double (
 const double p,
 const size_t n,
 const double alpha,
 double * X,
 const size_t incX,
 bool positive)
```

**13.219.3.10 fscale\_1\_modular\_double()**

```
void fscale_1_modular_double (
 const double p,
 const size_t n,
 const double alpha,
 const double * X,
 const size_t incX,
 double * Y,
 const size_t incY,
 bool positive)
```

**13.219.3.11 faxpy\_1\_modular\_double()**

```
void faxpy_1_modular_double (
 const double p,
 const size_t n,
 const double alpha,
 const double * X,
 const size_t incX,
 double * Y,
 const size_t incY,
 bool positive)
```

**13.219.3.12 fdot\_1\_modular\_double()**

```
double fdot_1_modular_double (
 const double p,
```

```
 const size_t n,
 const double * X,
 const size_t incX,
 const double * Y,
 const size_t incY,
 bool positive)
```

#### 13.219.3.13 fswap\_1\_modular\_double()

```
void fswap_1_modular_double (
 const double p,
 const size_t n,
 double * X,
 const size_t incX,
 double * Y,
 const size_t incY,
 bool positive)
```

#### 13.219.3.14 fadd\_1\_modular\_double()

```
void fadd_1_modular_double (
 const double p,
 const size_t n,
 const double * A,
 const size_t incA,
 const double * B,
 const size_t incB,
 double * C,
 const size_t incC,
 bool positive)
```

#### 13.219.3.15 fsub\_1\_modular\_double()

```
void fsub_1_modular_double (
 const double p,
 const size_t n,
 const double * A,
 const size_t incA,
 const double * B,
 const size_t incB,
 double * C,
 const size_t incC,
 bool positive)
```

#### 13.219.3.16 faddin\_1\_modular\_double()

```
void faddin_1_modular_double (
 const double p,
 const size_t n,
 const double * B,
 const size_t incB,
 double * C,
 const size_t incC,
 bool positive)
```

#### 13.219.3.17 fsubin\_1\_modular\_double()

```
void fsubin_1_modular_double (
 const double p,
```

```
 const size_t n,
 const double * B,
 const size_t incB,
 double * C,
 const size_t incC,
 bool positive)
```

#### 13.219.3.18 fassign\_2\_modular\_double()

```
void fassign_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * B,
 const size_t ldB,
 double * A,
 const size_t ldA,
 bool positive)
```

#### 13.219.3.19 fzero\_2\_modular\_double()

```
void fzero_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 double * A,
 const size_t ldA,
 bool positive)
```

#### 13.219.3.20 fequal\_2\_modular\_double()

```
bool fequal_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * A,
 const size_t ldA,
 const double * B,
 const size_t ldB,
 bool positive)
```

#### 13.219.3.21 fiszero\_2\_modular\_double()

```
bool fiszero_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * A,
 const size_t ldA,
 bool positive)
```

#### 13.219.3.22 fidentity\_2\_modular\_double()

```
void fidentity_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 double * A,
 const size_t ldA,
```

```
 const double d,
 bool positive)
```

#### 13.219.3.23 **freducein\_2\_modular\_double()**

```
void frducein_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 double * A,
 const size_t ldA,
 bool positive)
```

#### 13.219.3.24 **freduce\_2\_modular\_double()**

```
void frduce_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * B,
 const size_t ldB,
 double * A,
 const size_t ldA,
 bool positive)
```

#### 13.219.3.25 **fnegin\_2\_modular\_double()**

```
void fnegin_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 double * A,
 const size_t ldA,
 bool positive)
```

#### 13.219.3.26 **fneg\_2\_modular\_double()**

```
void fneg_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * B,
 const size_t ldB,
 double * A,
 const size_t ldA,
 bool positive)
```

#### 13.219.3.27 **fscaln\_2\_modular\_double()**

```
void fscaln_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double alpha,
 double * A,
 const size_t ldA,
 bool positive)
```

**13.219.3.28 fscal\_2\_modular\_double()**

```
void fscal_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double alpha,
 const double * A,
 const size_t ldA,
 double * B,
 const size_t ldB,
 bool positive)
```

**13.219.3.29 faxpy\_2\_modular\_double()**

```
void faxpy_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double alpha,
 const double * X,
 const size_t ldX,
 double * Y,
 const size_t ldY,
 bool positive)
```

**13.219.3.30 fmove\_2\_modular\_double()**

```
void fmove_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 double * A,
 const size_t ldA,
 double * B,
 const size_t ldB,
 bool positive)
```

**13.219.3.31 fadd\_2\_modular\_double()**

```
void fadd_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * A,
 const size_t ldA,
 const double * B,
 const size_t ldB,
 double * C,
 const size_t ldC,
 bool positive)
```

**13.219.3.32 fsub\_2\_modular\_double()**

```
void fsub_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * A,
```

```
 const size_t ldA,
 const double * B,
 const size_t ldB,
 double * C,
 const size_t ldC,
 bool positive)
```

#### 13.219.3.33 fsubin\_2\_modular\_double()

```
void fsubin_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * B,
 const size_t ldB,
 double * C,
 const size_t ldC,
 bool positive)
```

#### 13.219.3.34 faddin\_2\_modular\_double()

```
void faddin_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * B,
 const size_t ldB,
 double * C,
 const size_t ldC,
 bool positive)
```

#### 13.219.3.35 fgemv\_2\_modular\_double()

```
double * fgemv_2_modular_double (
 const double p,
 const enum FFLAS_C_TRANSPOSE TransA,
 const size_t m,
 const size_t n,
 const double alpha,
 const double * A,
 const size_t ldA,
 const double * X,
 const size_t incX,
 const double betaA,
 double * Y,
 const size_t incY,
 bool positive)
```

#### 13.219.3.36 fger\_2\_modular\_double()

```
void fger_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double alpha,
 const double * x,
 const size_t incX,
 const double * y,
 const size_t incY,
```

```
double * A,
const size_t ldA,
bool positive)
```

### 13.219.3.37 ftrsv\_2\_modular\_double()

```
void ftrsv_2_modular_double (
 const double p,
 const enum FFLAS_C_UPLO Uplo,
 const enum FFLAS_C_TRANSPOSE TransA,
 const enum FFLAS_C_DIAG Diag,
 const size_t n,
 const double * A,
 const size_t ldA,
 double * X,
 int incX,
 bool positive)
```

### 13.219.3.38 ftrsm\_3\_modular\_double()

```
void ftrsm_3_modular_double (
 const double p,
 const enum FFLAS_C_SIDE Side,
 const enum FFLAS_C_UPLO Uplo,
 const enum FFLAS_C_TRANSPOSE TransA,
 const enum FFLAS_C_DIAG Diag,
 const size_t m,
 const size_t n,
 const double alpha,
 const double * A,
 const size_t ldA,
 double * B,
 const size_t ldB,
 bool positive)
```

### 13.219.3.39 ftrmm\_3\_modular\_double()

```
void ftrmm_3_modular_double (
 const double p,
 const enum FFLAS_C_SIDE Side,
 const enum FFLAS_C_UPLO Uplo,
 const enum FFLAS_C_TRANSPOSE TransA,
 const enum FFLAS_C_DIAG Diag,
 const size_t m,
 const size_t n,
 const double alpha,
 double * A,
 const size_t ldA,
 double * B,
 const size_t ldB,
 bool positive)
```

### 13.219.3.40 fgemm\_3\_modular\_double()

```
double * fgemm_3_modular_double (
 const double p,
 const enum FFLAS_C_TRANSPOSE tA,
 const enum FFLAS_C_TRANSPOSE tB,
 const size_t m,
```



```

 const size_t n,
 const size_t k,
 const double alpha,
 const double * A,
 const size_t ldA,
 const double * B,
 const size_t ldB,
 const double betA,
 double * C,
 const size_t ldC,
 bool positive)

```

#### 13.219.3.41 fsquare\_3\_modular\_double()

```

double * fsquare_3_modular_double (
 const double p,
 const enum FFLAS_C_TRANSPOSE tA,
 const size_t n,
 const double alpha,
 const double * A,
 const size_t ldA,
 const double betA,
 double * C,
 const size_t ldC,
 bool positive)

```

## 13.220 fflas\_L1\_inst.C File Reference

```

#include "fflas-ffpack/fflas-ffpack-config.h"
#include "givaro/modular.h"
#include "givaro/modular-balanced.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/fflas/fflas_helpers.inl"
#include "fflas_L1_inst_implem.inl"

```

### Macros

- `#define __FFLAS_L1_INST_C`
- `#define INST_OR_DECL`
- `#define FFLAS_FIELD Givaro::ModularBalanced`
- `#define FFLAS_ELT double`
- `#define FFLAS_ELT float`
- `#define FFLAS_ELT int64_t`
- `#define FFLAS_FIELD Givaro::Modular`
- `#define FFLAS_ELT double`
- `#define FFLAS_ELT float`
- `#define FFLAS_ELT int64_t`

### 13.220.1 Macro Definition Documentation

#### 13.220.1.1 \_\_FFLAS\_L1\_INST\_C

```
#define __FFLAS_L1_INST_C
```

#### 13.220.1.2 INST\_OR\_DECL

```
#define INST_OR_DECL
```

**13.220.1.3 FFLAS\_FIELD [1/2]**

```
#define FFLAS_FIELD Givaro::ModularBalanced
```

**13.220.1.4 FFLAS\_ELT [1/6]**

```
#define FFLAS_ELT double
```

**13.220.1.5 FFLAS\_ELT [2/6]**

```
#define FFLAS_ELT float
```

**13.220.1.6 FFLAS\_ELT [3/6]**

```
#define FFLAS_ELT int64_t
```

**13.220.1.7 FFLAS\_FIELD [2/2]**

```
#define FFLAS_FIELD Givaro::Modular
```

**13.220.1.8 FFLAS\_ELT [4/6]**

```
#define FFLAS_ELT double
```

**13.220.1.9 FFLAS\_ELT [5/6]**

```
#define FFLAS_ELT float
```

**13.220.1.10 FFLAS\_ELT [6/6]**

```
#define FFLAS_ELT int64_t
```

**13.221 fflas\_L1\_inst.h File Reference**

```
#include "givaro/modular.h"
#include "givaro/modular-balanced.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/fflas/fflas_helpers.inl"
#include "fflas_L1_inst_implem.inl"
```

**Macros**

- #define [INST\\_OR\\_DECL](#) <>
- #define [FFLAS\\_FIELD](#) Givaro::ModularBalanced
- #define [FFLAS\\_ELT](#) double
- #define [FFLAS\\_ELT](#) float
- #define [FFLAS\\_ELT](#) int64\_t
- #define [FFLAS\\_FIELD](#) Givaro::Modular
- #define [FFLAS\\_ELT](#) double
- #define [FFLAS\\_ELT](#) float
- #define [FFLAS\\_ELT](#) int64\_t

**13.221.1 Macro Definition Documentation****13.221.1.1 INST\_OR\_DECL**

```
#define INST_OR_DECL <>
```

**13.221.1.2 FFLAS\_FIELD [1/2]**

```
#define FFLAS_FIELD Givaro::ModularBalanced
```

**13.221.1.3 FFLAS\_ELT [1/6]**

```
#define FFLAS_ELT double
```

**13.221.1.4 FFLAS\_ELT [2/6]**

```
#define FFLAS_ELT float
```

**13.221.1.5 FFLAS\_ELT [3/6]**

```
#define FFLAS_ELT int64_t
```

**13.221.1.6 FFLAS\_FIELD [2/2]**

```
#define FFLAS_FIELD Givaro::Modular
```

**13.221.1.7 FFLAS\_ELT [4/6]**

```
#define FFLAS_ELT double
```

**13.221.1.8 FFLAS\_ELT [5/6]**

```
#define FFLAS_ELT float
```

**13.221.1.9 FFLAS\_ELT [6/6]**

```
#define FFLAS_ELT int64_t
```

**13.222 fflas\_L1\_inst\_implem.inl File Reference****Namespaces**

- namespace [FFLAS](#)

**Functions**

- template [INST\\_OR\\_DECL](#) void [freduce](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, const size\_t n, [FFLAS\\_ELT](#) \*X, const size\_t incX)  

$$\text{freduce } x \leftarrow x \bmod F.$$
- template [INST\\_OR\\_DECL](#) void [freduce](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, const size\_t n, const [FFLAS\\_ELT](#) \*Y, const size\_t incY, [FFLAS\\_ELT](#) \*X, const size\_t incX)  

$$\text{freduce } x \leftarrow y \bmod F.$$
- template [INST\\_OR\\_DECL](#) void [finit](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, const size\_t n, const [FFLAS\\_ELT](#) \*Y, const size\_t incY, [FFLAS\\_ELT](#) \*X, const size\_t incX)  

$$\text{finit } x \leftarrow y \bmod F.$$
- template [INST\\_OR\\_DECL](#) void [fconvert](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, const size\_t n, [FFLAS\\_ELT](#) \*X, const size\_t incX, const [FFLAS\\_ELT](#) \*Y, const size\_t incY)  

$$\text{fconvert } x \leftarrow y \bmod F.$$
- template [INST\\_OR\\_DECL](#) void [fnegin](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, const size\_t n, [FFLAS\\_ELT](#) \*X, const size\_t incX)  

$$\text{fnegin } x \leftarrow -x.$$
- template [INST\\_OR\\_DECL](#) void [fneg](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, const size\_t n, const [FFLAS\\_ELT](#) \*Y, const size\_t incY, [FFLAS\\_ELT](#) \*X, const size\_t incX)  

$$\text{fneg } x \leftarrow -y.$$

- template `INST_OR_DECL` void `fzero` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t n, `FFLAS_ELT` \*X, const size\_t incX)  
 $fzero : A \leftarrow 0.$
- template `INST_OR_DECL` bool `fiszero` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t n, const `FFLAS_ELT` \*X, const size\_t incX)  
 $fiszero : test\ X = 0.$
- template `INST_OR_DECL` bool `fequal` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t n, const `FFLAS_ELT` \*X, const size\_t incX, const `FFLAS_ELT` \*Y, const size\_t incY)  
 $fequal : test\ X = Y.$
- template `INST_OR_DECL` void `fassign` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t N, const `FFLAS_ELT` \*Y, const size\_t incY, `FFLAS_ELT` \*X, const size\_t incX)  
 $fassign : x \leftarrow y.$
- template `INST_OR_DECL` void `fscal` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t n, const `FFLAS_ELT` alpha, `FFLAS_ELT` \*X, const size\_t incX)  
 $fscal\ x \leftarrow \alpha \cdot x.$
- template `INST_OR_DECL` void `fscal` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t n, const `FFLAS_ELT` alpha, const `FFLAS_ELT` \*X, const size\_t incX, `FFLAS_ELT` \*Y, const size\_t incY)  
 $fscal\ y \leftarrow \alpha \cdot x.$
- template `INST_OR_DECL` void `faxpy` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t N, const `FFLAS_ELT` alpha, const `FFLAS_ELT` \*X, const size\_t incX, `FFLAS_ELT` \*Y, const size\_t incY)  
 $faxpy : y \leftarrow \alpha \cdot x + y.$
- template `INST_OR_DECL` `FFLAS_ELT` `fdot` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t N, const `FFLAS_ELT` \*X, const size\_t incX, const `FFLAS_ELT` \*Y, const size\_t incY)  
 $faxpy : y \leftarrow \alpha \cdot x + \beta \cdot y.$
- template `INST_OR_DECL` void `fswap` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t N, `FFLAS_ELT` \*X, const size\_t incX, `FFLAS_ELT` \*Y, const size\_t incY)  
 $fswap : X \leftrightarrow Y.$
- template `INST_OR_DECL` void `fadd` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t N, const `FFLAS_ELT` \*A, const size\_t inca, const `FFLAS_ELT` \*B, const size\_t incb, `FFLAS_ELT` \*C, const size\_t incc)
- template `INST_OR_DECL` void `fsub` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t N, const `FFLAS_ELT` \*A, const size\_t inca, const `FFLAS_ELT` \*B, const size\_t incb, `FFLAS_ELT` \*C, const size\_t incc)
- template `INST_OR_DECL` void `faddin` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t N, const `FFLAS_ELT` \*B, const size\_t incb, `FFLAS_ELT` \*C, const size\_t incc)
- template `INST_OR_DECL` void `fadd` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t N, const `FFLAS_ELT` \*A, const size\_t inca, const `FFLAS_ELT` alpha, const `FFLAS_ELT` \*B, const size\_t incb, `FFLAS_ELT` \*C, const size\_t incc)

### 13.223 fflas\_L2\_inst.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "givaro/modular.h"
#include "givaro/modular-balanced.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/fflas/fflas_helpers.inl"
#include "fflas_L2_inst_implem.inl"
```

#### Macros

- #define `__FFLAS_L2_INST_C`
- #define `INST_OR_DECL`
- #define `FFLAS_FIELD` Givaro::ModularBalanced

- `#define FFLAS_ELT double`
- `#define FFLAS_ELT float`
- `#define FFLAS_ELT int64_t`
- `#define FFLAS_FIELD Givaro::Modular`
- `#define FFLAS_ELT double`
- `#define FFLAS_ELT float`
- `#define FFLAS_ELT int64_t`

### 13.223.1 Macro Definition Documentation

#### 13.223.1.1 \_\_FFLAS\_L2\_INST\_C

```
#define __FFLAS_L2_INST_C
```

#### 13.223.1.2 INST\_OR\_DECL

```
#define INST_OR_DECL
```

#### 13.223.1.3 FFLAS\_FIELD [1/2]

```
#define FFLAS_FIELD Givaro::ModularBalanced
```

#### 13.223.1.4 FFLAS\_ELT [1/6]

```
#define FFLAS_ELT double
```

#### 13.223.1.5 FFLAS\_ELT [2/6]

```
#define FFLAS_ELT float
```

#### 13.223.1.6 FFLAS\_ELT [3/6]

```
#define FFLAS_ELT int64_t
```

#### 13.223.1.7 FFLAS\_FIELD [2/2]

```
#define FFLAS_FIELD Givaro::Modular
```

#### 13.223.1.8 FFLAS\_ELT [4/6]

```
#define FFLAS_ELT double
```

#### 13.223.1.9 FFLAS\_ELT [5/6]

```
#define FFLAS_ELT float
```

#### 13.223.1.10 FFLAS\_ELT [6/6]

```
#define FFLAS_ELT int64_t
```

## 13.224 fflas\_L2\_inst.h File Reference

```
#include "givaro/modular.h"
#include "givaro/modular-balanced.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/fflas/fflas_helpers.inl"
#include "fflas_L2_inst_implem.inl"
```

## Macros

- `#define INST_OR_DECL <>`
- `#define FFLAS_FIELD Givaro::ModularBalanced`
- `#define FFLAS_ELT double`
- `#define FFLAS_ELT float`
- `#define FFLAS_ELT int64_t`
- `#define FFLAS_FIELD Givaro::Modular`
- `#define FFLAS_ELT double`
- `#define FFLAS_ELT float`
- `#define FFLAS_ELT int64_t`

## 13.224.1 Macro Definition Documentation

### 13.224.1.1 INST\_OR\_DECL

```
#define INST_OR_DECL <>
```

### 13.224.1.2 FFLAS\_FIELD [1/2]

```
#define FFLAS_FIELD Givaro::ModularBalanced
```

### 13.224.1.3 FFLAS\_ELT [1/6]

```
#define FFLAS_ELT double
```

### 13.224.1.4 FFLAS\_ELT [2/6]

```
#define FFLAS_ELT float
```

### 13.224.1.5 FFLAS\_ELT [3/6]

```
#define FFLAS_ELT int64_t
```

### 13.224.1.6 FFLAS\_FIELD [2/2]

```
#define FFLAS_FIELD Givaro::Modular
```

### 13.224.1.7 FFLAS\_ELT [4/6]

```
#define FFLAS_ELT double
```

### 13.224.1.8 FFLAS\_ELT [5/6]

```
#define FFLAS_ELT float
```

### 13.224.1.9 FFLAS\_ELT [6/6]

```
#define FFLAS_ELT int64_t
```

## 13.225 fflas\_L2\_inst\_implem.inl File Reference

### Namespaces

- namespace [FFLAS](#)

## Functions

- template `INST_OR_DECL` void `fassign` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, const `FFLAS_ELT` \*B, const size\_t ldb, `FFLAS_ELT` \*A, const size\_t lda)  
 $fassign : A \leftarrow B.$
- template `INST_OR_DECL` void `fzero` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, `FFLAS_ELT` \*A, const size\_t lda)  
 $fzero : A \leftarrow 0.$
- template `INST_OR_DECL` bool `fequal` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, const `FFLAS_ELT` \*A, const size\_t lda, const `FFLAS_ELT` \*B, const size\_t ldb)  
 $fequal : test A = B.$
- template `INST_OR_DECL` bool `fiszero` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, const `FFLAS_ELT` \*A, const size\_t lda)  
 $fiszero : test A = 0.$
- template `INST_OR_DECL` void `fidentity` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, `FFLAS_ELT` \*A, const size\_t lda, const `FFLAS_ELT` &d)  
 $creates\ a\ diagonal\ matrix$
- template `INST_OR_DECL` void `fidentity` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, `FFLAS_ELT` \*A, const size\_t lda)  
 $creates\ a\ diagonal\ matrix$
- template `INST_OR_DECL` void `freduce` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, `FFLAS_ELT` \*A, const size\_t lda)  
 $freduce\ A \leftarrow A mod F.$
- template `INST_OR_DECL` void `freduce` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, const `FFLAS_ELT` \*B, const size\_t ldb, `FFLAS_ELT` \*A, const size\_t lda)  
 $freduce\ A \leftarrow B mod F.$
- template `INST_OR_DECL` void `finit` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, const `FFLAS_ELT` \*B, const size\_t ldb, `FFLAS_ELT` \*A, const size\_t lda)  
 $finit\ A \leftarrow B mod F.$
- template `INST_OR_DECL` void `fnegin` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, `FFLAS_ELT` \*A, const size\_t lda)  
 $fnegin\ A \leftarrow -A.$
- template `INST_OR_DECL` void `fneg` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, const `FFLAS_ELT` \*B, const size\_t ldb, `FFLAS_ELT` \*A, const size\_t lda)  
 $fneg\ A \leftarrow -B.$
- template `INST_OR_DECL` void `fscaln` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, const `FFLAS_ELT` alpha, `FFLAS_ELT` \*A, const size\_t lda)  
 $fscaln\ A \leftarrow a \cdot A.$
- template `INST_OR_DECL` void `fscal` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, const `FFLAS_ELT` alpha, const `FFLAS_ELT` \*A, const size\_t lda, `FFLAS_ELT` \*B, const size\_t ldb)  
 $fscal\ B \leftarrow a \cdot A.$
- template `INST_OR_DECL` void `faxpy` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, const `FFLAS_ELT` alpha, const `FFLAS_ELT` \*X, const size\_t ldx, `FFLAS_ELT` \*Y, const size\_t ldy)  
 $faxpy : y \leftarrow \alpha \cdot x + y.$
- template `INST_OR_DECL` void `fmove` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t m, const size\_t n, `FFLAS_ELT` \*A, const size\_t lda, `FFLAS_ELT` \*B, const size\_t ldb)  
 $faxpy : y \leftarrow \alpha \cdot x + \beta \cdot y.$
- template `INST_OR_DECL` void `fadd` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t M, const size\_t N, const `FFLAS_ELT` \*A, const size\_t lda, const `FFLAS_ELT` \*B, const size\_t ldb, `FFLAS_ELT` \*C, const size\_t ldc)  
 $fadd : matrix\ addition.$
- template `INST_OR_DECL` void `fsub` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t M, const size\_t N, const `FFLAS_ELT` \*A, const size\_t lda, const `FFLAS_ELT` \*B, const size\_t ldb, `FFLAS_ELT` \*C, const size\_t ldc)

- fsub : matrix subtraction.*
- template `INST_OR_DECL` void `fsubin` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t M, const size\_t N, const `FFLAS_ELT` \*B, const size\_t ldb, `FFLAS_ELT` \*C, const size\_t ldc)
- fsubin  $C = C - B$*
- template `INST_OR_DECL` void `fadd` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t M, const size\_t N, const `FFLAS_ELT` \*A, const size\_t lda, const `FFLAS_ELT` alpha, const `FFLAS_ELT` \*B, const size\_t ldb, `FFLAS_ELT` \*C, const size\_t ldc)
- fadd : matrix addition with scaling.*
- template `INST_OR_DECL` void `faddin` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t M, const size\_t N, const `FFLAS_ELT` \*B, const size\_t ldb, `FFLAS_ELT` \*C, const size\_t ldc)
- faddin*
- template `INST_OR_DECL` `FFLAS_ELT` \* `fgemv` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS_TRANSPOSE` TransA, const size\_t M, const size\_t N, const `FFLAS_ELT` alpha, const `FFLAS_ELT` \*A, const size\_t lda, const `FFLAS_ELT` \*X, const size\_t incX, const `FFLAS_ELT` beta, `FFLAS_ELT` \*Y, const size\_t incY)
- finite prime FFLAS\_FIELD<FFLAS\_ELT> GEneral Matrix Vector multiplication.*
- template `INST_OR_DECL` void `fger` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t M, const size\_t N, const `FFLAS_ELT` alpha, const `FFLAS_ELT` \*x, const size\_t incx, const `FFLAS_ELT` \*y, const size\_t incy, `FFLAS_ELT` \*A, const size\_t lda)
- fger: rank one update of a general matrix*
- template `INST_OR_DECL` void `ftsv` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS_UPLO` Uplo, const `FFLAS_TRANSPOSE` TransA, const `FFLAS_DIAG` Diag, const size\_t N, const `FFLAS_ELT` \*A, const size\_t lda, `FFLAS_ELT` \*X, int incX)
- ftsv: TRIangular System solve with Vector Computes  $X \leftarrow \text{op}(A^{-1})X$*

## 13.226 fflas\_L3\_inst.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "givaro/modular.h"
#include "givaro/modular-balanced.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/fflas/fflas_helpers.inl"
#include "fflas_L3_inst_implem.inl"
```

### Macros

- #define `__FFLAS_L3_INST_C`
- #define `INST_OR_DECL`
- #define `FFLAS_FIELD` Givaro::ModularBalanced
- #define `FFLAS_ELT` double
- #define `FFLAS_ELT` float
- #define `FFLAS_ELT` int64\_t
- #define `FFLAS_FIELD` Givaro::Modular
- #define `FFLAS_ELT` double
- #define `FFLAS_ELT` float
- #define `FFLAS_ELT` int64\_t

### 13.226.1 Macro Definition Documentation

#### 13.226.1.1 \_\_FFLAS\_L3\_INST\_C

```
#define __FFLAS_L3_INST_C
```



### 13.226.1.2 INST\_OR\_DECL

```
#define INST_OR_DECL
```

### 13.226.1.3 FFLAS\_FIELD [1/2]

```
#define FFLAS_FIELD Givaro::ModularBalanced
```

### 13.226.1.4 FFLAS\_ELT [1/6]

```
#define FFLAS_ELT double
```

### 13.226.1.5 FFLAS\_ELT [2/6]

```
#define FFLAS_ELT float
```

### 13.226.1.6 FFLAS\_ELT [3/6]

```
#define FFLAS_ELT int64_t
```

### 13.226.1.7 FFLAS\_FIELD [2/2]

```
#define FFLAS_FIELD Givaro::Modular
```

### 13.226.1.8 FFLAS\_ELT [4/6]

```
#define FFLAS_ELT double
```

### 13.226.1.9 FFLAS\_ELT [5/6]

```
#define FFLAS_ELT float
```

### 13.226.1.10 FFLAS\_ELT [6/6]

```
#define FFLAS_ELT int64_t
```

## 13.227 fflas\_L3\_inst.h File Reference

```
#include "givaro/modular.h"
#include "givaro/modular-balanced.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/fflas/fflas_helpers.inl"
#include "fflas_L3_inst_implem.inl"
```

### Macros

- #define [INST\\_OR\\_DECL](#) <>
- #define [FFLAS\\_FIELD](#) [Givaro::ModularBalanced](#)
- #define [FFLAS\\_ELT](#) double
- #define [FFLAS\\_ELT](#) float
- #define [FFLAS\\_ELT](#) int64\_t
- #define [FFLAS\\_FIELD](#) [Givaro::Modular](#)
- #define [FFLAS\\_ELT](#) double
- #define [FFLAS\\_ELT](#) float
- #define [FFLAS\\_ELT](#) int64\_t

## 13.227.1 Macro Definition Documentation

### 13.227.1.1 INST\_OR\_DECL

```
#define INST_OR_DECL <>
```

### 13.227.1.2 FFLAS\_FIELD [1/2]

```
#define FFLAS_FIELD Givaro::ModularBalanced
```

### 13.227.1.3 FFLAS\_ELT [1/6]

```
#define FFLAS_ELT double
```

### 13.227.1.4 FFLAS\_ELT [2/6]

```
#define FFLAS_ELT float
```

### 13.227.1.5 FFLAS\_ELT [3/6]

```
#define FFLAS_ELT int64_t
```

### 13.227.1.6 FFLAS\_FIELD [2/2]

```
#define FFLAS_FIELD Givaro::Modular
```

### 13.227.1.7 FFLAS\_ELT [4/6]

```
#define FFLAS_ELT double
```

### 13.227.1.8 FFLAS\_ELT [5/6]

```
#define FFLAS_ELT float
```

### 13.227.1.9 FFLAS\_ELT [6/6]

```
#define FFLAS_ELT int64_t
```

## 13.228 fflas\_L3\_inst\_implem.inl File Reference

### Namespaces

- namespace [FFLAS](#)

### Macros

- #define [\\_\\_FFLAS\\_TRSM\\_READONLY](#)

### Functions

- template [INST\\_OR\\_DECL](#) void [ftrsm](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, const [FFLAS\\_SIDE](#) Side, const [FFLAS\\_UPLO](#) Uplo, const [FFLAS\\_TRANSPOSE](#) TransA, const [FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, const [FFLAS\\_ELT](#) alpha, const [FFLAS\\_ELT](#) \*A, const size\_t lda, [FFLAS\\_ELT](#) \*B, const size\_t ldb)  
*ftrsm: **TRI**angular **S**ystem solve with **M**atrix.*
- template [INST\\_OR\\_DECL](#) void [ftrmm](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, const [FFLAS\\_SIDE](#) Side, const [FFLAS\\_UPLO](#) Uplo, const [FFLAS\\_TRANSPOSE](#) TransA, const [FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, const [FFLAS\\_ELT](#) alpha, const [FFLAS\\_ELT](#) \*A, const size\_t lda, [FFLAS\\_ELT](#) \*B, const size\_t ldb)  
*ftrmm: **TRI**angular **M**atrix **M**ultiply.*

- template `INST_OR_DECL FFLAS_ELT * fgemm` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const `size_t` m, const `size_t` n, const `size_t` k, const `FFLAS_ELT` alpha, const `FFLAS_ELT` \*A, const `size_t` lda, const `FFLAS_ELT` \*B, const `size_t` ldb, const `FFLAS_ELT` beta, `FFLAS_ELT` \*C, const `size_t` ldc)

*fgemm: Field **GE**neral **M**atrix **M**ultiply.*

- template `INST_OR_DECL FFLAS_ELT * fgemm` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const `size_t` m, const `size_t` n, const `size_t` k, const `FFLAS_ELT` alpha, const `FFLAS_ELT` \*A, const `size_t` lda, const `FFLAS_ELT` \*B, const `size_t` ldb, const `FFLAS_ELT` beta, `FFLAS_ELT` \*C, const `size_t` ldc, const `ParSeqHelper::Sequential` seq)
- template `INST_OR_DECL FFLAS_ELT * fgemm` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const `size_t` m, const `size_t` n, const `size_t` k, const `FFLAS_ELT` alpha, const `FFLAS_ELT` \*A, const `size_t` lda, const `FFLAS_ELT` \*B, const `size_t` ldb, const `FFLAS_ELT` beta, `FFLAS_ELT` \*C, const `size_t` ldc, const `ParSeqHelper::Parallel< CuttingStrategy::Recursive, StrategyParameter::TwoDAdaptive >` par)
- template `INST_OR_DECL FFLAS_ELT * fgemm` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `FFLAS_TRANSPOSE` ta, const `FFLAS_TRANSPOSE` tb, const `size_t` m, const `size_t` n, const `size_t` k, const `FFLAS_ELT` alpha, const `FFLAS_ELT` \*A, const `size_t` lda, const `FFLAS_ELT` \*B, const `size_t` ldb, const `FFLAS_ELT` beta, `FFLAS_ELT` \*C, const `size_t` ldc, const `ParSeqHelper::Parallel< CuttingStrategy::Block, StrategyParameter::Threads >` par)
- template `INST_OR_DECL FFLAS_ELT * fsquare` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `FFLAS_TRANSPOSE` ta, const `size_t` n, const `FFLAS_ELT` alpha, const `FFLAS_ELT` \*A, const `size_t` lda, const `FFLAS_ELT` beta, `FFLAS_ELT` \*C, const `size_t` ldc)

*fsquare: Squares a matrix.*

## 13.228.1 Macro Definition Documentation

### 13.228.1.1 \_\_FFLAS\_TRSM\_READONLY

```
#define __FFLAS_TRSM_READONLY
```

## 13.229 fflas\_lvl1.C File Reference

C functions calls for level 1 `FFLAS` in `fflas-c.h`.

```
#include "fflas-ffpack/interfaces/libs/fflas_c.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "givaro/modular-balanced.h"
#include "givaro/modular.h"
```

### Functions

- void `freducein_1_modular_double` (const double p, const `size_t` n, double \*X, const `size_t` incX, bool positive)
- void `freduce_1_modular_double` (const double p, const `size_t` n, const double \*Y, const `size_t` incY, double \*X, const `size_t` incX, bool positive)
- void `fnegin_1_modular_double` (const double p, const `size_t` n, double \*X, const `size_t` incX, bool positive)
- void `fneg_1_modular_double` (const double p, const `size_t` n, const double \*Y, const `size_t` incY, double \*X, const `size_t` incX, bool positive)
- void `fzero_1_modular_double` (const double p, const `size_t` n, double \*X, const `size_t` incX, bool positive)
- bool `fiszero_1_modular_double` (const double p, const `size_t` n, const double \*X, const `size_t` incX, bool positive)
- bool `fequal_1_modular_double` (const double p, const `size_t` n, const double \*X, const `size_t` incX, const double \*Y, const `size_t` incY, bool positive)
- void `fassign_1_modular_double` (const double p, const `size_t` n, const double \*Y, const `size_t` incY, double \*X, const `size_t` incX, bool positive)
- void `fscaln_1_modular_double` (const double p, const `size_t` n, const double alpha, double \*X, const `size_t` incX, bool positive)

- void [fscal\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double alpha, const double \*X, const size\_t incX, double \*Y, const size\_t incY, bool positive)
- void [faxpy\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double alpha, const double \*X, const size\_t incX, double \*Y, const size\_t incY, bool positive)
- double [fdot\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*X, const size\_t incX, const double \*Y, const size\_t incY, bool positive)
- void [fswap\\_1\\_modular\\_double](#) (const double p, const size\_t n, double \*X, const size\_t incX, double \*Y, const size\_t incY, bool positive)
- void [fadd\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*A, const size\_t incA, const double \*B, const size\_t incB, double \*C, const size\_t incC, bool positive)
- void [fsub\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*A, const size\_t incA, const double \*B, const size\_t incB, double \*C, const size\_t incC, bool positive)
- void [faddin\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*B, const size\_t incB, double \*C, const size\_t incC, bool positive)
- void [fsubin\\_1\\_modular\\_double](#) (const double p, const size\_t n, const double \*B, const size\_t incB, double \*C, const size\_t incC, bool positive)

### 13.229.1 Detailed Description

C functions calls for level 1 [FFLAS](#) in [fflas-c.h](#).

Author

Brice Boyer

See also

[fflas/fflas\\_level1.inl](#)

### 13.229.2 Function Documentation

#### 13.229.2.1 [freducein\\_1\\_modular\\_double\(\)](#)

```
void freducein_1_modular_double (
 const double p,
 const size_t n,
 double * X,
 const size_t incX,
 bool positive)
```

#### 13.229.2.2 [freduce\\_1\\_modular\\_double\(\)](#)

```
void freduce_1_modular_double (
 const double p,
 const size_t n,
 const double * Y,
 const size_t incY,
 double * X,
 const size_t incX,
 bool positive)
```

#### 13.229.2.3 [fnegin\\_1\\_modular\\_double\(\)](#)

```
void fnegin_1_modular_double (
 const double p,
 const size_t n,
 double * X,
 const size_t incX,
 bool positive)
```

**13.229.2.4 fneg\_1\_modular\_double()**

```
void fneg_1_modular_double (
 const double p,
 const size_t n,
 const double * Y,
 const size_t incY,
 double * X,
 const size_t incX,
 bool positive)
```

**13.229.2.5 fzero\_1\_modular\_double()**

```
void fzero_1_modular_double (
 const double p,
 const size_t n,
 double * X,
 const size_t incX,
 bool positive)
```

**13.229.2.6 fiszero\_1\_modular\_double()**

```
bool fiszero_1_modular_double (
 const double p,
 const size_t n,
 const double * X,
 const size_t incX,
 bool positive)
```

**13.229.2.7 fequal\_1\_modular\_double()**

```
bool fequal_1_modular_double (
 const double p,
 const size_t n,
 const double * X,
 const size_t incX,
 const double * Y,
 const size_t incY,
 bool positive)
```

**13.229.2.8 fassign\_1\_modular\_double()**

```
void fassign_1_modular_double (
 const double p,
 const size_t n,
 const double * Y,
 const size_t incY,
 double * X,
 const size_t incX,
 bool positive)
```

**13.229.2.9 fscaln\_1\_modular\_double()**

```
void fscaln_1_modular_double (
 const double p,
 const size_t n,
 const double alpha,
 double * X,
 const size_t incX,
 bool positive)
```

**13.229.2.10 fscal\_1\_modular\_double()**

```
void fscal_1_modular_double (
 const double p,
 const size_t n,
 const double alpha,
 const double * X,
 const size_t incX,
 double * Y,
 const size_t incY,
 bool positive)
```

**13.229.2.11 faxpy\_1\_modular\_double()**

```
void faxpy_1_modular_double (
 const double p,
 const size_t n,
 const double alpha,
 const double * X,
 const size_t incX,
 double * Y,
 const size_t incY,
 bool positive)
```

**13.229.2.12 fdot\_1\_modular\_double()**

```
double fdot_1_modular_double (
 const double p,
 const size_t n,
 const double * X,
 const size_t incX,
 const double * Y,
 const size_t incY,
 bool positive)
```

**13.229.2.13 fswap\_1\_modular\_double()**

```
void fswap_1_modular_double (
 const double p,
 const size_t n,
 double * X,
 const size_t incX,
 double * Y,
 const size_t incY,
 bool positive)
```

**13.229.2.14 fadd\_1\_modular\_double()**

```
void fadd_1_modular_double (
 const double p,
 const size_t n,
 const double * A,
 const size_t incA,
 const double * B,
 const size_t incB,
 double * C,
 const size_t incC,
 bool positive)
```

**13.229.2.15 fsub\_1\_modular\_double()**

```
void fsub_1_modular_double (
 const double p,
 const size_t n,
 const double * A,
 const size_t incA,
 const double * B,
 const size_t incB,
 double * C,
 const size_t incC,
 bool positive)
```

**13.229.2.16 faddin\_1\_modular\_double()**

```
void faddin_1_modular_double (
 const double p,
 const size_t n,
 const double * B,
 const size_t incB,
 double * C,
 const size_t incC,
 bool positive)
```

**13.229.2.17 fsubin\_1\_modular\_double()**

```
void fsubin_1_modular_double (
 const double p,
 const size_t n,
 const double * B,
 const size_t incB,
 double * C,
 const size_t incC,
 bool positive)
```

**13.230 fflas\_lvl2.C File Reference**

C functions calls for level 2 [FFLAS](#) in fflas-c.h.

```
#include "fflas-ffpack/interfaces/libs/fflas_c.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "givaro//modular-balanced.h"
#include "givaro//modular.h"
```

**Functions**

- void [fassign\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*A, const size\_t lda, double \*B, const size\_t ldb, bool positive)
- void [fzero\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, double \*A, const size\_t lda, bool positive)
- bool [fequal\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*A, const size\_t lda, const double \*B, const size\_t ldb, bool positive)
- bool [fiszero\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*A, const size\_t lda, bool positive)
- void [fidentity\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, double \*A, const size\_t lda, const double d, bool positive)
- void [freducein\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, double \*A, const size\_t lda, bool positive)

- void [freduce\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*A, const size\_t lda, double \*B, const size\_t ldb, bool positive)
- void [fnegin\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, double \*A, const size\_t lda, bool positive)
- void [fneg\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*A, const size\_t lda, double \*B, const size\_t ldb, bool positive)
- void [fscalin\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double alpha, double \*A, const size\_t lda, bool positive)
- void [fscal\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double alpha, const double \*A, const size\_t lda, double \*B, const size\_t ldb, bool positive)
- void [faxpy\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double alpha, const double \*A, const size\_t lda, double \*B, const size\_t ldb, bool positive)
- void [fmove\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, double \*A, const size\_t lda, double \*B, const size\_t ldb, bool positive)
- void [fadd\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*A, const size\_t lda, const double \*B, const size\_t ldb, double \*C, const size\_t ldc, bool positive)
- void [fsub\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*A, const size\_t lda, const double \*B, const size\_t ldb, double \*C, const size\_t ldc, bool positive)
- void [fsubin\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*B, const size\_t ldb, double \*C, const size\_t ldc, bool positive)
- void [faddin\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double \*B, const size\_t ldb, double \*C, const size\_t ldc, bool positive)
- double \* [fgemv\\_2\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_TRANSPOSE](#) TransA, const size\_t m, const size\_t n, const double alpha, const double \*A, const size\_t lda, const double \*X, const size\_t incX, const double beta, double \*Y, const size\_t incY, bool positive)
- void [fger\\_2\\_modular\\_double](#) (const double p, const size\_t m, const size\_t n, const double alpha, const double \*X, const size\_t incX, const double \*Y, const size\_t incY, double \*A, const size\_t lda, bool positive)
- void [ftrsv\\_2\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const enum [FFLAS\\_C\\_TRANSPOSE](#) TransA, const enum [FFLAS\\_C\\_DIAG](#) Diag, const size\_t n, const double \*A, const size\_t lda, double \*X, int incX, bool positive)

### 13.230.1 Detailed Description

C functions calls for level 2 [FFLAS](#) in `fflas-c.h`.

Author

Brice Boyer

See also

[fflas/fflas\\_level2.inl](#)

### 13.230.2 Function Documentation

#### 13.230.2.1 `fassign_2_modular_double()`

```
void fassign_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * A,
 const size_t lda,
 double * B,
 const size_t ldb,
 bool positive)
```



**13.230.2.2 fzero\_2\_modular\_double()**

```
void fzero_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 double * A,
 const size_t lda,
 bool positive)
```

**13.230.2.3 fequal\_2\_modular\_double()**

```
bool fequal_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * A,
 const size_t lda,
 const double * B,
 const size_t ldb,
 bool positive)
```

**13.230.2.4 fiszero\_2\_modular\_double()**

```
bool fiszero_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * A,
 const size_t lda,
 bool positive)
```

**13.230.2.5 fidentity\_2\_modular\_double()**

```
void fidentity_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 double * A,
 const size_t lda,
 const double d,
 bool positive)
```

**13.230.2.6 freducein\_2\_modular\_double()**

```
void freducein_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 double * A,
 const size_t lda,
 bool positive)
```

**13.230.2.7 freduce\_2\_modular\_double()**

```
void freduce_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
```

```
 const double * A,
 const size_t lda,
 double * B,
 const size_t ldb,
 bool positive)
```

#### 13.230.2.8 fnegin\_2\_modular\_double()

```
void fnegin_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 double * A,
 const size_t lda,
 bool positive)
```

#### 13.230.2.9 fneg\_2\_modular\_double()

```
void fneg_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * A,
 const size_t lda,
 double * B,
 const size_t ldb,
 bool positive)
```

#### 13.230.2.10 fscaln\_2\_modular\_double()

```
void fscaln_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double alpha,
 double * A,
 const size_t lda,
 bool positive)
```

#### 13.230.2.11 fscal\_2\_modular\_double()

```
void fscal_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double alpha,
 const double * A,
 const size_t lda,
 double * B,
 const size_t ldb,
 bool positive)
```

#### 13.230.2.12 faxpy\_2\_modular\_double()

```
void faxpy_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double alpha,
```

```
 const double * A,
 const size_t lda,
 double * B,
 const size_t ldb,
 bool positive)
```

#### 13.230.2.13 fmove\_2\_modular\_double()

```
void fmove_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 double * A,
 const size_t lda,
 double * B,
 const size_t ldb,
 bool positive)
```

#### 13.230.2.14 fadd\_2\_modular\_double()

```
void fadd_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * A,
 const size_t lda,
 const double * B,
 const size_t ldb,
 double * C,
 const size_t ldc,
 bool positive)
```

#### 13.230.2.15 fsub\_2\_modular\_double()

```
void fsub_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * A,
 const size_t lda,
 const double * B,
 const size_t ldb,
 double * C,
 const size_t ldc,
 bool positive)
```

#### 13.230.2.16 fsubin\_2\_modular\_double()

```
void fsubin_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * B,
 const size_t ldb,
 double * C,
 const size_t ldc,
 bool positive)
```

**13.230.2.17 faddin\_2\_modular\_double()**

```
void faddin_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double * B,
 const size_t ldb,
 double * C,
 const size_t ldc,
 bool positive)
```

**13.230.2.18 fgemv\_2\_modular\_double()**

```
double * fgemv_2_modular_double (
 const double p,
 const enum FFLAS_C_TRANSPOSE TransA,
 const size_t m,
 const size_t n,
 const double alpha,
 const double * A,
 const size_t lda,
 const double * X,
 const size_t incX,
 const double beta,
 double * Y,
 const size_t incY,
 bool positive)
```

**13.230.2.19 fger\_2\_modular\_double()**

```
void fger_2_modular_double (
 const double p,
 const size_t m,
 const size_t n,
 const double alpha,
 const double * X,
 const size_t incX,
 const double * Y,
 const size_t incY,
 double * A,
 const size_t lda,
 bool positive)
```

**13.230.2.20 ftrsv\_2\_modular\_double()**

```
void ftrsv_2_modular_double (
 const double p,
 const enum FFLAS_C_UPLO Uplo,
 const enum FFLAS_C_TRANSPOSE TransA,
 const enum FFLAS_C_DIAG Diag,
 const size_t n,
 const double * A,
 const size_t lda,
 double * X,
 int incX,
 bool positive)
```

## 13.231 fflas\_lvl3.C File Reference

C functions calls for level 3 [FFLAS](#) in fflas-c.h.

```
#include "fflas-ffpack/interfaces/libs/fflas_c.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "givaro//modular-balanced.h"
#include "givaro//modular.h"
```

### Functions

- void [ftrsm\\_3\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_SIDE](#) Side, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const enum [FFLAS\\_C\\_TRANSPOSE](#) tA, const enum [FFLAS\\_C\\_DIAG](#) Diag, const size\_t m, const size\_t n, const double alpha, const double \*A, const size\_t ldA, double \*B, const size\_t ldB, bool positive)
- void [ftrmm\\_3\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_SIDE](#) Side, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const enum [FFLAS\\_C\\_TRANSPOSE](#) tA, const enum [FFLAS\\_C\\_DIAG](#) Diag, const size\_t m, const size\_t n, const double alpha, double \*A, const size\_t ldA, double \*B, const size\_t ldB, bool positive)
- double \* [fgemm\\_3\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_TRANSPOSE](#) tA, const enum [FFLAS\\_C\\_TRANSPOSE](#) tB, const size\_t m, const size\_t n, const size\_t k, const double alpha, const double \*A, const size\_t ldA, const double \*B, const size\_t ldB, const double betA, double \*C, const size\_t ldC, bool positive)
- double \* [fsquare\\_3\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_TRANSPOSE](#) tA, const size\_t n, const double alpha, const double \*A, const size\_t ldA, const double betA, double \*C, const size\_t ldC, bool positive)

### 13.231.1 Detailed Description

C functions calls for level 3 [FFLAS](#) in fflas-c.h.

Author

Brice Boyer

See also

[fflas/fflas\\_level3.inl](#)

### 13.231.2 Function Documentation

#### 13.231.2.1 ftrsm\_3\_modular\_double()

```
void ftrsm_3_modular_double (
 const double p,
 const enum FFLAS_C_SIDE Side,
 const enum FFLAS_C_UPLO Uplo,
 const enum FFLAS_C_TRANSPOSE tA,
 const enum FFLAS_C_DIAG Diag,
 const size_t m,
 const size_t n,
 const double alpha,
 const double * A,
 const size_t ldA,
 double * B,
 const size_t ldB,
 bool positive)
```

### 13.231.2.2 ftrmm\_3\_modular\_double()

```
void ftrmm_3_modular_double (
 const double p,
 const enum FFLAS_C_SIDE Side,
 const enum FFLAS_C_UPLO Uplo,
 const enum FFLAS_C_TRANSPOSE tA,
 const enum FFLAS_C_DIAG Diag,
 const size_t m,
 const size_t n,
 const double alpha,
 double * A,
 const size_t ldA,
 double * B,
 const size_t ldB,
 bool positive)
```

### 13.231.2.3 fgemv\_3\_modular\_double()

```
double * fgemv_3_modular_double (
 const double p,
 const enum FFLAS_C_TRANSPOSE tA,
 const enum FFLAS_C_TRANSPOSE tB,
 const size_t m,
 const size_t n,
 const size_t k,
 const double alpha,
 const double * A,
 const size_t ldA,
 const double * B,
 const size_t ldB,
 const double betaA,
 double * C,
 const size_t ldC,
 bool positive)
```

### 13.231.2.4 fsquare\_3\_modular\_double()

```
double * fsquare_3_modular_double (
 const double p,
 const enum FFLAS_C_TRANSPOSE tA,
 const size_t n,
 const double alpha,
 const double * A,
 const size_t ldA,
 const double betaA,
 double * C,
 const size_t ldC,
 bool positive)
```

## 13.232 fflas\_sparse.C File Reference

C functions calls for level 1.5 and 2.5 [FFLAS](#) in fflas-c.h.

### 13.232.1 Detailed Description

C functions calls for level 1.5 and 2.5 [FFLAS](#) in fflas-c.h.

## Author

Brice Boyer

## See also

[fflas/fflas\\_sparse.h](#)

## 13.233 ffpack.C File Reference

C functions calls for [FFPACK](#) in `ffpack-c.h`.

```
#include "fflas-ffpack/interfaces/libs/ffpack_c.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "givaro/modular-balanced.h"
#include "givaro/modular.h"
```

### Functions

- void [LAPACKPerm2MathPerm](#) (size\_t \*MathP, const size\_t \*LapackP, const size\_t N)
- void [MathPerm2LAPACKPerm](#) (size\_t \*LapackP, const size\_t \*MathP, const size\_t N)
- void [MatrixApplyS\\_modular\\_double](#) (const double p, double \*A, const size\_t lda, const size\_t width, const size\_t M2, const size\_t R1, const size\_t R2, const size\_t R3, const size\_t R4, bool positive)
- void [PermApplyS\\_double](#) (double \*A, const size\_t lda, const size\_t width, const size\_t M2, const size\_t R1, const size\_t R2, const size\_t R3, const size\_t R4)
- void [MatrixApplyT\\_modular\\_double](#) (const double p, double \*A, const size\_t lda, const size\_t width, const size\_t N2, const size\_t R1, const size\_t R2, const size\_t R3, const size\_t R4, bool positive)
- void [PermApplyT\\_double](#) (double \*A, const size\_t lda, const size\_t width, const size\_t N2, const size\_t R1, const size\_t R2, const size\_t R3, const size\_t R4)
- void [composePermutationsLLM](#) (size\_t \*MathP, const size\_t \*P1, const size\_t \*P2, const size\_t R, const size\_t N)
- void [composePermutationsLLL](#) (size\_t \*P1, const size\_t \*P2, const size\_t R, const size\_t N)
- void [composePermutationsMLM](#) (size\_t \*MathP1, const size\_t \*P2, const size\_t R, const size\_t N)
- void [cyclic\\_shift\\_mathPerm](#) (size\_t \*P, const size\_t s)
- void [cyclic\\_shift\\_row\\_modular\\_double](#) (const double p, double \*A, size\_t m, size\_t n, size\_t lda, bool positive)
- void [cyclic\\_shift\\_col\\_modular\\_double](#) (const double p, double \*A, size\_t m, size\_t n, size\_t lda, bool positive)
- void [applyP\\_modular\\_double](#) (const double p, const enum [FFLAS::FFLAS\\_SIDE](#) Side, const enum [FFLAS::FFLAS\\_TRANSPOSE](#) Trans, const size\_t M, const size\_t ibeg, const size\_t iend, double \*A, const size\_t lda, const size\_t \*P, bool positive)
- void [fgetrsin\\_modular\\_double](#) (const double p, const enum [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t R, double \*A, const size\_t lda, const size\_t \*P, const size\_t \*Q, double \*B, const size\_t ldb, int \*info, bool positive)
- double \* [fgetrsv\\_modular\\_double](#) (const double p, const enum [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t NRHS, const size\_t R, double \*A, const size\_t lda, const size\_t \*P, const size\_t \*Q, double \*X, const size\_t idx, const double \*B, const size\_t ldb, int \*info, bool positive)
- size\_t [fgesvin\\_modular\\_double](#) (const double p, const enum [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, double \*A, const size\_t lda, double \*B, const size\_t ldb, int \*info, bool positive)
- size\_t [fgesv\\_modular\\_double](#) (const double p, const enum [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t NRHS, double \*A, const size\_t lda, double \*X, const size\_t idx, const double \*B, const size\_t ldb, int \*info, bool positive)
- void [ftrtri\\_modular\\_double](#) (const double p, const enum [FFLAS::FFLAS\\_UPLO](#) Uplo, const enum [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t N, double \*A, const size\_t lda, bool positive)
- void [trinv\\_left\\_modular\\_double](#) (const double p, const size\_t N, const double \*L, const size\_t ldl, double \*X, const size\_t idx, bool positive)
- void [ftrtrm\\_modular\\_double](#) (const double p, const [FFLAS::FFLAS\\_SIDE](#) side, const enum [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t N, double \*A, const size\_t lda, bool positive)





- `size_t pReducedColumnEchelonForm_modular_int32_t` (const int32\_t p, const size\_t M, const size\_t N, int32\_t \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, const bool transform, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- `size_t pReducedRowEchelonForm_modular_int32_t` (const int32\_t p, const size\_t M, const size\_t N, int32\_t \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, const bool transform, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- `double * Invertin_modular_double` (const double p, const size\_t M, double \*A, const size\_t lda, int \*nullity, bool positive)
- `double * Invert_modular_double` (const double p, const size\_t M, const double \*A, const size\_t lda, double \*X, const size\_t idx, int \*nullity, bool positive)
- `double * Invert2_modular_double` (const double p, const size\_t M, double \*A, const size\_t lda, double \*X, const size\_t idx, int \*nullity, bool positive)
- `size_t KrylovElim_modular_double` (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, size\_t \*P, size\_t \*Q, const size\_t deg, size\_t \*iterates, size\_t \*inviterates, const size\_t maxit, size\_t virt, bool positive)
- `size_t SpecRankProfile_modular_double` (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, const size\_t deg, size\_t \*rankProfile, bool positive)
- `size_t Rank_modular_double` (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, bool positive)
- `bool IsSingular_modular_double` (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, bool positive)
- `double Det_modular_double` (const double p, const size\_t N, double \*A, const size\_t lda, bool positive)
- `double * Solve_modular_double` (const double p, const size\_t M, double \*A, const size\_t lda, double \*x, const int incx, const double \*b, const int incb, bool positive)
- `void solveLB_modular_double` (const double p, const enum [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t R, double \*L, const size\_t ldl, const size\_t \*Q, double \*B, const size\_t ldb, bool positive)
- `void solveLB2_modular_double` (const double p, const enum [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t R, double \*L, const size\_t ldl, const size\_t \*Q, double \*B, const size\_t ldb, bool positive)
- `void RandomNullSpaceVector_modular_double` (const double p, const enum [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, double \*A, const size\_t lda, double \*X, const size\_t incX, bool positive)
- `size_t NullSpaceBasis_modular_double` (const double p, const enum [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, double \*A, const size\_t lda, double \*\*NS, size\_t \*ldn, size\_t \*NSdim, bool positive)
- `size_t RowRankProfile_modular_double` (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, size\_t \*\*rkprofile, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- `size_t ColumnRankProfile_modular_double` (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, size\_t \*\*rkprofile, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- `void RankProfileFromLU` (const size\_t \*P, const size\_t N, const size\_t R, size\_t \*rkprofile, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag)
- `size_t LeadingSubmatrixRankProfiles` (const size\_t M, const size\_t N, const size\_t R, const size\_t LSm, const size\_t LSn, const size\_t \*P, const size\_t \*Q, size\_t \*RRP, size\_t \*CRP)
- `size_t RowRankProfileSubmatrixIndices_modular_double` (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, size\_t \*\*rowindices, size\_t \*\*colindices, size\_t \*R, bool positive)
- `size_t ColRankProfileSubmatrixIndices_modular_double` (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, size\_t \*\*rowindices, size\_t \*\*colindices, size\_t \*R, bool positive)
- `size_t RowRankProfileSubmatrix_modular_double` (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, double \*\*X, size\_t \*R, bool positive)
- `size_t ColRankProfileSubmatrix_modular_double` (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, double \*\*X, size\_t \*R, bool positive)
- `void getTriangular_modular_double` (const double p, const enum [FFLAS::FFLAS\\_UPLO](#) Uplo, const enum [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, const size\_t R, const double \*A, const size\_t lda, double \*T, const size\_t ldt, const bool OnlyNonZeroVectors, bool positive)
- `void getTriangularin_modular_double` (const double p, const enum [FFLAS::FFLAS\\_UPLO](#) Uplo, const enum [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, const size\_t R, double \*A, const size\_t lda, bool positive)

- void [getEchelonForm\\_modular\\_double](#) (const double p, const enum [FFLAS::FFLAS\\_UPLO](#) Uplo, const enum [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, const double \*A, const size\_t lda, double \*T, const size\_t ldt, const bool OnlyNonZeroVectors, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- void [getEchelonFormin\\_modular\\_double](#) (const double p, const enum [FFLAS::FFLAS\\_UPLO](#) Uplo, const enum [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, double \*A, const size\_t lda, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- void [getEchelonTransform\\_modular\\_double](#) (const double p, const enum [FFLAS::FFLAS\\_UPLO](#) Uplo, const enum [FFLAS::FFLAS\\_DIAG](#) Diag, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, const size\_t \*Q, const double \*A, const size\_t lda, double \*T, const size\_t ldt, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- void [getReducedEchelonForm\\_modular\\_double](#) (const double p, const enum [FFLAS::FFLAS\\_UPLO](#) Uplo, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, const double \*A, const size\_t lda, double \*T, const size\_t ldt, const bool OnlyNonZeroVectors, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- void [getReducedEchelonFormin\\_modular\\_double](#) (const double p, const enum [FFLAS::FFLAS\\_UPLO](#) Uplo, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, double \*A, const size\_t lda, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- void [getReducedEchelonTransform\\_modular\\_double](#) (const double p, const enum [FFLAS::FFLAS\\_UPLO](#) Uplo, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, const size\_t \*Q, const double \*A, const size\_t lda, double \*T, const size\_t ldt, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- void [PLUQtoEchelonPermutation](#) (const size\_t N, const size\_t R, const size\_t \*P, size\_t \*outPerm)

### 13.233.1 Detailed Description

C functions calls for [FFPACK](#) in `ffpack-c.h`.

Author

Brice Boyer

See also

[ffpack/ffpack.h](#)

### 13.233.2 Function Documentation

#### 13.233.2.1 LAPACKPerm2MathPerm()

```
void LAPACKPerm2MathPerm (
 size_t * MathP,
 const size_t * LapackP,
 const size_t N)
```

#### 13.233.2.2 MathPerm2LAPACKPerm()

```
void MathPerm2LAPACKPerm (
 size_t * LapackP,
 const size_t * MathP,
 const size_t N)
```

#### 13.233.2.3 MatrixApplyS\_modular\_double()

```
void MatrixApplyS_modular_double (
 const double p,
 double * A,
 const size_t lda,
 const size_t width,
 const size_t M2,
 const size_t R1,
 const size_t R2,
```

```
 const size_t R3,
 const size_t R4,
 bool positive)
```

#### 13.233.2.4 PermApplyS\_double()

```
void PermApplyS_double (
 double * A,
 const size_t lda,
 const size_t width,
 const size_t M2,
 const size_t R1,
 const size_t R2,
 const size_t R3,
 const size_t R4)
```

#### 13.233.2.5 MatrixApplyT\_modular\_double()

```
void MatrixApplyT_modular_double (
 const double p,
 double * A,
 const size_t lda,
 const size_t width,
 const size_t N2,
 const size_t R1,
 const size_t R2,
 const size_t R3,
 const size_t R4,
 bool positive)
```

#### 13.233.2.6 PermApplyT\_double()

```
void PermApplyT_double (
 double * A,
 const size_t lda,
 const size_t width,
 const size_t N2,
 const size_t R1,
 const size_t R2,
 const size_t R3,
 const size_t R4)
```

#### 13.233.2.7 composePermutationsLLM()

```
void composePermutationsLLM (
 size_t * MathP,
 const size_t * P1,
 const size_t * P2,
 const size_t R,
 const size_t N)
```

#### 13.233.2.8 composePermutationsLLL()

```
void composePermutationsLLL (
 size_t * P1,
 const size_t * P2,
 const size_t R,
 const size_t N)
```

**13.233.2.9 composePermutationsMLM()**

```
void composePermutationsMLM (
 size_t * MathP1,
 const size_t * P2,
 const size_t R,
 const size_t N)
```

**13.233.2.10 cyclic\_shift\_mathPerm()**

```
void cyclic_shift_mathPerm (
 size_t * P,
 const size_t s)
```

**13.233.2.11 cyclic\_shift\_row\_modular\_double()**

```
void cyclic_shift_row_modular_double (
 const double p,
 double * A,
 size_t m,
 size_t n,
 size_t lda,
 bool positive)
```

**13.233.2.12 cyclic\_shift\_col\_modular\_double()**

```
void cyclic_shift_col_modular_double (
 const double p,
 double * A,
 size_t m,
 size_t n,
 size_t lda,
 bool positive)
```

**13.233.2.13 applyP\_modular\_double()**

```
void applyP_modular_double (
 const double p,
 const enum FFLAS::FFLAS_SIDE Side,
 const enum FFLAS::FFLAS_TRANSPOSE Trans,
 const size_t M,
 const size_t ibeg,
 const size_t iend,
 double * A,
 const size_t lda,
 const size_t * P,
 bool positive)
```

**13.233.2.14 fgetrsin\_modular\_double()**

```
void fgetrsin_modular_double (
 const double p,
 const enum FFLAS::FFLAS_SIDE Side,
 const size_t M,
 const size_t N,
 const size_t R,
 double * A,
 const size_t lda,
 const size_t * P,
```

```
 const size_t * Q,
 double * B,
 const size_t ldb,
 int * info,
 bool positive)
```

#### 13.233.2.15 fgetrsv\_modular\_double()

```
double * fgetrsv_modular_double (
 const double p,
 const enum FFLAS::FFLAS_SIDE Side,
 const size_t M,
 const size_t N,
 const size_t NRHS,
 const size_t R,
 double * A,
 const size_t lda,
 const size_t * P,
 const size_t * Q,
 double * X,
 const size_t ldx,
 const double * B,
 const size_t ldb,
 int * info,
 bool positive)
```

#### 13.233.2.16 fgesvin\_modular\_double()

```
size_t fgesvin_modular_double (
 const double p,
 const enum FFLAS::FFLAS_SIDE Side,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 double * B,
 const size_t ldb,
 int * info,
 bool positive)
```

#### 13.233.2.17 fgesv\_modular\_double()

```
size_t fgesv_modular_double (
 const double p,
 const enum FFLAS::FFLAS_SIDE Side,
 const size_t M,
 const size_t N,
 const size_t NRHS,
 double * A,
 const size_t lda,
 double * X,
 const size_t ldx,
 const double * B,
 const size_t ldb,
 int * info,
 bool positive)
```

**13.233.2.18 ftrtri\_modular\_double()**

```
void ftrtri_modular_double (
 const double p,
 const enum FFLAS::FFLAS_UPLO Uplo,
 const enum FFLAS::FFLAS_DIAG Diag,
 const size_t N,
 double * A,
 const size_t lda,
 bool positive)
```

**13.233.2.19 trinv\_left\_modular\_double()**

```
void trinv_left_modular_double (
 const double p,
 const size_t N,
 const double * L,
 const size_t ldl,
 double * X,
 const size_t ldx,
 bool positive)
```

**13.233.2.20 ftrtrm\_modular\_double()**

```
void ftrtrm_modular_double (
 const double p,
 const FFLAS::FFLAS_SIDE side,
 const enum FFLAS::FFLAS_DIAG Diag,
 const size_t N,
 double * A,
 const size_t lda,
 bool positive)
```

**13.233.2.21 PLUQ\_modular\_double()**

```
size_t PLUQ_modular_double (
 const double p,
 const enum FFLAS::FFLAS_DIAG Diag,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Q,
 bool positive)
```

**13.233.2.22 LUdivine\_modular\_double()**

```
size_t LUdivine_modular_double (
 const double p,
 const enum FFLAS::FFLAS_DIAG Diag,
 const enum FFLAS::FFLAS_TRANSPOSE Trans,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const enum FFPACK_C_LU_TAG LuTag,
```

```
 const size_t cutoff,
 bool positive)
```

#### 13.233.2.23 ColumnEchelonForm\_modular\_double()

```
size_t ColumnEchelonForm_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

#### 13.233.2.24 RowEchelonForm\_modular\_double()

```
size_t RowEchelonForm_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

#### 13.233.2.25 ReducedColumnEchelonForm\_modular\_double()

```
size_t ReducedColumnEchelonForm_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

#### 13.233.2.26 ReducedRowEchelonForm\_modular\_double()

```
size_t ReducedRowEchelonForm_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

**13.233.2.27 ColumnEchelonForm\_modular\_float()**

```

size_t ColumnEchelonForm_modular_float (
 const float p,
 const size_t M,
 const size_t N,
 float * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

**13.233.2.28 RowEchelonForm\_modular\_float()**

```

size_t RowEchelonForm_modular_float (
 const float p,
 const size_t M,
 const size_t N,
 float * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

**13.233.2.29 ReducedColumnEchelonForm\_modular\_float()**

```

size_t ReducedColumnEchelonForm_modular_float (
 const float p,
 const size_t M,
 const size_t N,
 float * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

**13.233.2.30 ReducedRowEchelonForm\_modular\_float()**

```

size_t ReducedRowEchelonForm_modular_float (
 const float p,
 const size_t M,
 const size_t N,
 float * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

**13.233.2.31 ColumnEchelonForm\_modular\_int32\_t()**

```

size_t ColumnEchelonForm_modular_int32_t (
 const int32_t p,

```



```

 const size_t M,
 const size_t N,
 int32_t * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

#### 13.233.2.32 RowEchelonForm\_modular\_int32\_t()

```

size_t RowEchelonForm_modular_int32_t (
 const int32_t p,
 const size_t M,
 const size_t N,
 int32_t * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

#### 13.233.2.33 ReducedColumnEchelonForm\_modular\_int32\_t()

```

size_t ReducedColumnEchelonForm_modular_int32_t (
 const int32_t p,
 const size_t M,
 const size_t N,
 int32_t * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

#### 13.233.2.34 ReducedRowEchelonForm\_modular\_int32\_t()

```

size_t ReducedRowEchelonForm_modular_int32_t (
 const int32_t p,
 const size_t M,
 const size_t N,
 int32_t * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

#### 13.233.2.35 pColumnEchelonForm\_modular\_double()

```

size_t pColumnEchelonForm_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,

```

```

 const size_t lda,
 size_t * P,
 size_t * Qt,
 bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

### 13.233.2.36 pRowEchelonForm\_modular\_double()

```

size_t pRowEchelonForm_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

### 13.233.2.37 pReducedColumnEchelonForm\_modular\_double()

```

size_t pReducedColumnEchelonForm_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

### 13.233.2.38 pReducedRowEchelonForm\_modular\_double()

```

size_t pReducedRowEchelonForm_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

### 13.233.2.39 pColumnEchelonForm\_modular\_float()

```

size_t pColumnEchelonForm_modular_float (
 const float p,
 const size_t M,
 const size_t N,
 float * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,

```

```

 bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

#### 13.233.2.40 pRowEchelonForm\_modular\_float()

```

size_t pRowEchelonForm_modular_float (
 const float p,
 const size_t M,
 const size_t N,
 float * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

#### 13.233.2.41 pReducedColumnEchelonForm\_modular\_float()

```

size_t pReducedColumnEchelonForm_modular_float (
 const float p,
 const size_t M,
 const size_t N,
 float * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

#### 13.233.2.42 pReducedRowEchelonForm\_modular\_float()

```

size_t pReducedRowEchelonForm_modular_float (
 const float p,
 const size_t M,
 const size_t N,
 float * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

#### 13.233.2.43 pColumnEchelonForm\_modular\_int32\_t()

```

size_t pColumnEchelonForm_modular_int32_t (
 const int32_t p,
 const size_t M,
 const size_t N,
 int32_t * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

**13.233.2.44 pRowEchelonForm\_modular\_int32\_t()**

```
size_t pRowEchelonForm_modular_int32_t (
 const int32_t p,
 const size_t M,
 const size_t N,
 int32_t * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

**13.233.2.45 pReducedColumnEchelonForm\_modular\_int32\_t()**

```
size_t pReducedColumnEchelonForm_modular_int32_t (
 const int32_t p,
 const size_t M,
 const size_t N,
 int32_t * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

**13.233.2.46 pReducedRowEchelonForm\_modular\_int32\_t()**

```
size_t pReducedRowEchelonForm_modular_int32_t (
 const int32_t p,
 const size_t M,
 const size_t N,
 int32_t * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

**13.233.2.47 Invertin\_modular\_double()**

```
double * Invertin_modular_double (
 const double p,
 const size_t M,
 double * A,
 const size_t lda,
 int * nullity,
 bool positive)
```

**13.233.2.48 Invert\_modular\_double()**

```
double * Invert_modular_double (
 const double p,
 const size_t M,
 const double * A,
 const size_t lda,
```

```
double * X,
const size_t ldx,
int * nullity,
bool positive)
```

#### 13.233.2.49 Invert2\_modular\_double()

```
double * Invert2_modular_double (
 const double p,
 const size_t M,
 double * A,
 const size_t lda,
 double * X,
 const size_t ldx,
 int * nullity,
 bool positive)
```

#### 13.233.2.50 KrylovElim\_modular\_double()

```
size_t KrylovElim_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Q,
 const size_t deg,
 size_t * iterates,
 size_t * inviterates,
 const size_t maxit,
 size_t virt,
 bool positive)
```

#### 13.233.2.51 SpecRankProfile\_modular\_double()

```
size_t SpecRankProfile_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 const size_t deg,
 size_t * rankProfile,
 bool positive)
```

#### 13.233.2.52 Rank\_modular\_double()

```
size_t Rank_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 bool positive)
```

#### 13.233.2.53 IsSingular\_modular\_double()

```
bool IsSingular_modular_double (

```

```

 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 bool positive)

```

#### 13.233.2.54 Det\_modular\_double()

```

double Det_modular_double (
 const double p,
 const size_t N,
 double * A,
 const size_t lda,
 bool positive)

```

#### 13.233.2.55 Solve\_modular\_double()

```

double * Solve_modular_double (
 const double p,
 const size_t M,
 double * A,
 const size_t lda,
 double * x,
 const int incx,
 const double * b,
 const int incb,
 bool positive)

```

#### 13.233.2.56 solveLB\_modular\_double()

```

void solveLB_modular_double (
 const double p,
 const enum FFLAS::FFLAS_SIDE Side,
 const size_t M,
 const size_t N,
 const size_t R,
 double * L,
 const size_t ldl,
 const size_t * Q,
 double * B,
 const size_t ldb,
 bool positive)

```

#### 13.233.2.57 solveLB2\_modular\_double()

```

void solveLB2_modular_double (
 const double p,
 const enum FFLAS::FFLAS_SIDE Side,
 const size_t M,
 const size_t N,
 const size_t R,
 double * L,
 const size_t ldl,
 const size_t * Q,
 double * B,
 const size_t ldb,
 bool positive)

```

**13.233.2.58 RandomNullSpaceVector\_modular\_double()**

```
void RandomNullSpaceVector_modular_double (
 const double p,
 const enum FFLAS::FFLAS_SIDE Side,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 double * X,
 const size_t incX,
 bool positive)
```

**13.233.2.59 NullSpaceBasis\_modular\_double()**

```
size_t NullSpaceBasis_modular_double (
 const double p,
 const enum FFLAS::FFLAS_SIDE Side,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 double ** NS,
 size_t * ldn,
 size_t * NSdim,
 bool positive)
```

**13.233.2.60 RowRankProfile\_modular\_double()**

```
size_t RowRankProfile_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t ** rkprofile,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

**13.233.2.61 ColumnRankProfile\_modular\_double()**

```
size_t ColumnRankProfile_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t ** rkprofile,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

**13.233.2.62 RankProfileFromLU()**

```
void RankProfileFromLU (
 const size_t * P,
 const size_t N,
 const size_t R,
 size_t * rkprofile,
 const enum FFPACK_C_LU_TAG LuTag)
```

**13.233.2.63 LeadingSubmatrixRankProfiles()**

```
size_t LeadingSubmatrixRankProfiles (
 const size_t M,
 const size_t N,
 const size_t R,
 const size_t LSm,
 const size_t LSn,
 const size_t * P,
 const size_t * Q,
 size_t * RRP,
 size_t * CRP)
```

**13.233.2.64 RowRankProfileSubmatrixIndices\_modular\_double()**

```
size_t RowRankProfileSubmatrixIndices_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t ** rowindices,
 size_t ** colindices,
 size_t * R,
 bool positive)
```

**13.233.2.65 ColRankProfileSubmatrixIndices\_modular\_double()**

```
size_t ColRankProfileSubmatrixIndices_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t ** rowindices,
 size_t ** colindices,
 size_t * R,
 bool positive)
```

**13.233.2.66 RowRankProfileSubmatrix\_modular\_double()**

```
size_t RowRankProfileSubmatrix_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 double ** X,
 size_t * R,
 bool positive)
```

**13.233.2.67 ColRankProfileSubmatrix\_modular\_double()**

```
size_t ColRankProfileSubmatrix_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
```



```
double ** X,
size_t * R,
bool positive)
```

### 13.233.2.68 getTriangular\_modular\_double()

```
void getTriangular_modular_double (
 const double p,
 const enum FFLAS::FFLAS_UPLO Uplo,
 const enum FFLAS::FFLAS_DIAG Diag,
 const size_t M,
 const size_t N,
 const size_t R,
 const double * A,
 const size_t lda,
 double * T,
 const size_t ldt,
 const bool OnlyNonZeroVectors,
 bool positive)
```

### 13.233.2.69 getTriangularin\_modular\_double()

```
void getTriangularin_modular_double (
 const double p,
 const enum FFLAS::FFLAS_UPLO Uplo,
 const enum FFLAS::FFLAS_DIAG Diag,
 const size_t M,
 const size_t N,
 const size_t R,
 double * A,
 const size_t lda,
 bool positive)
```

### 13.233.2.70 getEchelonForm\_modular\_double()

```
void getEchelonForm_modular_double (
 const double p,
 const enum FFLAS::FFLAS_UPLO Uplo,
 const enum FFLAS::FFLAS_DIAG Diag,
 const size_t M,
 const size_t N,
 const size_t R,
 const size_t * P,
 const double * A,
 const size_t lda,
 double * T,
 const size_t ldt,
 const bool OnlyNonZeroVectors,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

### 13.233.2.71 getEchelonFormin\_modular\_double()

```
void getEchelonFormin_modular_double (
 const double p,
 const enum FFLAS::FFLAS_UPLO Uplo,
 const enum FFLAS::FFLAS_DIAG Diag,
 const size_t M,
 const size_t N,
```

```

 const size_t R,
 const size_t * P,
 double * A,
 const size_t lda,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

### 13.233.2.72 getEchelonTransform\_modular\_double()

```

void getEchelonTransform_modular_double (
 const double p,
 const enum FFLAS::FFLAS_UPLO Uplo,
 const enum FFLAS::FFLAS_DIAG Diag,
 const size_t M,
 const size_t N,
 const size_t R,
 const size_t * P,
 const size_t * Q,
 const double * A,
 const size_t lda,
 double * T,
 const size_t ldt,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

### 13.233.2.73 getReducedEchelonForm\_modular\_double()

```

void getReducedEchelonForm_modular_double (
 const double p,
 const enum FFLAS::FFLAS_UPLO Uplo,
 const size_t M,
 const size_t N,
 const size_t R,
 const size_t * P,
 const double * A,
 const size_t lda,
 double * T,
 const size_t ldt,
 const bool OnlyNonZeroVectors,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

### 13.233.2.74 getReducedEchelonFormin\_modular\_double()

```

void getReducedEchelonFormin_modular_double (
 const double p,
 const enum FFLAS::FFLAS_UPLO Uplo,
 const size_t M,
 const size_t N,
 const size_t R,
 const size_t * P,
 double * A,
 const size_t lda,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

### 13.233.2.75 getReducedEchelonTransform\_modular\_double()

```

void getReducedEchelonTransform_modular_double (

```

```

const double p,
const enum FFLAS::FFLAS_UPLO Uplo,
const size_t M,
const size_t N,
const size_t R,
const size_t * P,
const size_t * Q,
const double * A,
const size_t lda,
double * T,
const size_t ldt,
const enum FFPACK_C_LU_TAG LuTag,
bool positive)

```

### 13.233.2.76 PLUQtoEchelonPermutation()

```

void PLUQtoEchelonPermutation (
 const size_t N,
 const size_t R,
 const size_t * P,
 size_t * outPerm)

```

## 13.234 ffpack\_c.h File Reference

```

#include <stdbool.h>
#include <stdlib.h>
#include <inttypes.h>

```

### Macros

- #define [FFPACK\\_COMPILED](#)

### Enumerations

- enum [FFLAS\\_C\\_ORDER](#) { [FflasRowMajor](#) =101 , [FflasColMajor](#) =102 }
- enum [FFLAS\\_C\\_TRANSPOSE](#) { [FflasNoTrans](#) = 111 , [FflasTrans](#) = 112 }
- enum [FFLAS\\_C\\_UPLO](#) { [FflasUpper](#) = 121 , [FflasLower](#) = 122 }
- enum [FFLAS\\_C\\_DIAG](#) { [FflasNonUnit](#) = 131 , [FflasUnit](#) = 132 }
- enum [FFLAS\\_C\\_SIDE](#) { [FflasLeft](#) = 141 , [FflasRight](#) = 142 }
- enum [FFPACK\\_C\\_LU\\_TAG](#) { [FfpackSlabRecursive](#) = 1 , [FfpackTileRecursive](#) = 2 , [FfpackSingular](#) = 3 }
- enum [FFPACK\\_C\\_CHARPOLY\\_TAG](#) {  
[FfpackLUK](#) =1 , [FfpackKG](#) =2 , [FfpackHybrid](#) =3 , [FfpackKGFast](#) =4 ,  
[FfpackDanilevski](#) =5 , [FfpackArithProg](#) =6 , [FfpackKGFastG](#) =7 }
- enum [FFPACK\\_C\\_MINPOLY\\_TAG](#) { [FfpackDense](#) =1 , [FfpackKGF](#) =2 }

### Functions

- void [LAPACKPerm2MathPerm](#) (size\_t \*MathP, const size\_t \*LapackP, const size\_t N)
- void [MathPerm2LAPACKPerm](#) (size\_t \*LapackP, const size\_t \*MathP, const size\_t N)
- void [MatrixApplyS\\_modular\\_double](#) (const double p, double \*A, const size\_t lda, const size\_t width, const size\_t M2, const size\_t R1, const size\_t R2, const size\_t R3, const size\_t R4, bool positive)
- void [PermApplyS\\_double](#) (double \*A, const size\_t lda, const size\_t width, const size\_t M2, const size\_t R1, const size\_t R2, const size\_t R3, const size\_t R4)
- void [MatrixApplyT\\_modular\\_double](#) (const double p, double \*A, const size\_t lda, const size\_t width, const size\_t N2, const size\_t R1, const size\_t R2, const size\_t R3, const size\_t R4, bool positive)
- void [PermApplyT\\_double](#) (double \*A, const size\_t lda, const size\_t width, const size\_t N2, const size\_t R1, const size\_t R2, const size\_t R3, const size\_t R4)

- void [composePermutationsLLM](#) (size\_t \*MathP, const size\_t \*P1, const size\_t \*P2, const size\_t R, const size\_t N)
- void [composePermutationsLLL](#) (size\_t \*P1, const size\_t \*P2, const size\_t R, const size\_t N)
- void [composePermutationsMLM](#) (size\_t \*MathP1, const size\_t \*P2, const size\_t R, const size\_t N)
- void [cyclic\\_shift\\_mathPerm](#) (size\_t \*P, const size\_t s)
- void [cyclic\\_shift\\_row\\_modular\\_double](#) (const double p, double \*A, size\_t m, size\_t n, size\_t lda, bool positive)
- void [cyclic\\_shift\\_col\\_modular\\_double](#) (const double p, double \*A, size\_t m, size\_t n, size\_t lda, bool positive)
- void [applyP\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_SIDE](#) Side, const enum [FFLAS\\_C\\_TRANSPOSE](#) Trans, const size\_t M, const size\_t ibeg, const size\_t iend, double \*A, const size\_t lda, const size\_t \*P, bool positive)
- void [fgetrsin\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t R, double \*A, const size\_t lda, const size\_t \*P, const size\_t \*Q, double \*B, const size\_t ldb, int \*info, bool positive)
- double \* [fgetrs\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t NRHS, const size\_t R, double \*A, const size\_t lda, const size\_t \*P, const size\_t \*Q, double \*X, const size\_t ldx, const double \*B, const size\_t ldb, int \*info, bool positive)
- size\_t [fgesvin\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_SIDE](#) Side, const size\_t M, const size\_t N, double \*A, const size\_t lda, double \*B, const size\_t ldb, int \*info, bool positive)
- size\_t [fgesv\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t NRHS, double \*A, const size\_t lda, double \*X, const size\_t ldx, const double \*B, const size\_t ldb, int \*info)
- void [ftrtri\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const enum [FFLAS\\_C\\_DIAG](#) Diag, const size\_t N, double \*A, const size\_t lda, bool positive)
- void [trinv\\_left\\_modular\\_double](#) (const double p, const size\_t N, const double \*L, const size\_t ldl, double \*X, const size\_t ldx, bool positive)
- void [ftrtrm\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_DIAG](#) diag, const size\_t N, double \*A, const size\_t lda, bool positive)
- size\_t [PLUQ\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_DIAG](#) Diag, const size\_t M, const size\_t N, double \*A, const size\_t lda, size\_t \*P, size\_t \*Q, bool positive)
- size\_t [LUdivine\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_DIAG](#) Diag, const enum [FFLAS\\_C\\_TRANSPOSE](#) trans, const size\_t M, const size\_t N, double \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, const size\_t cutoff, bool positive)
- size\_t [LUdivine\\_small\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_DIAG](#) Diag, const enum [FFLAS\\_C\\_TRANSPOSE](#) trans, const size\_t M, const size\_t N, double \*A, const size\_t lda, size\_t \*P, size\_t \*Q, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- size\_t [LUdivine\\_gauss\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_DIAG](#) Diag, const size\_t M, const size\_t N, double \*A, const size\_t lda, size\_t \*P, size\_t \*Q, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- size\_t [ColumnEchelonForm\\_modular\\_double](#) (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, bool transform, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- size\_t [RowEchelonForm\\_modular\\_double](#) (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, const bool transform, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- size\_t [ColumnEchelonForm\\_modular\\_float](#) (const float p, const size\_t M, const size\_t N, float \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, bool transform, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- size\_t [RowEchelonForm\\_modular\\_float](#) (const float p, const size\_t M, const size\_t N, float \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, const bool transform, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- size\_t [ColumnEchelonForm\\_modular\\_int32\\_t](#) (const int32\_t p, const size\_t M, const size\_t N, int32\_t \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, bool transform, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- size\_t [RowEchelonForm\\_modular\\_int32\\_t](#) (const int32\_t p, const size\_t M, const size\_t N, int32\_t \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, const bool transform, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- size\_t [ReducedColumnEchelonForm\\_modular\\_double](#) (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, const bool transform, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- size\_t [ReducedRowEchelonForm\\_modular\\_double](#) (const double p, const size\_t M, const size\_t N, double \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, const bool transform, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)

- `size_t ReducedColumnEchelonForm_modular_float` (const float p, const `size_t` M, const `size_t` N, float \*A, const `size_t` lda, `size_t` \*P, `size_t` \*Qt, const bool transform, const enum `FFPACK_C_LU_TAG` LuTag, bool positive)
- `size_t ReducedRowEchelonForm_modular_float` (const float p, const `size_t` M, const `size_t` N, float \*A, const `size_t` lda, `size_t` \*P, `size_t` \*Qt, const bool transform, const enum `FFPACK_C_LU_TAG` LuTag, bool positive)
- `size_t ReducedColumnEchelonForm_modular_int32_t` (const `int32_t` p, const `size_t` M, const `size_t` N, `int32_t` \*A, const `size_t` lda, `size_t` \*P, `size_t` \*Qt, const bool transform, const enum `FFPACK_C_LU_TAG` LuTag, bool positive)
- `size_t ReducedRowEchelonForm_modular_int32_t` (const `int32_t` p, const `size_t` M, const `size_t` N, `int32_t` \*A, const `size_t` lda, `size_t` \*P, `size_t` \*Qt, const bool transform, const enum `FFPACK_C_LU_TAG` LuTag, bool positive)
- `size_t ReducedRowEchelonForm2_modular_double` (const double p, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, `size_t` \*P, `size_t` \*Qt, const bool transform, bool positive)
- `size_t REF_modular_double` (const double p, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, const `size_t` colbeg, const `size_t` rowbeg, const `size_t` colsize, `size_t` \*Qt, `size_t` \*P, bool positive)
- `double * Invertin_modular_double` (const double p, const `size_t` M, double \*A, const `size_t` lda, int \*nullity, bool positive)
- `double * Invert_modular_double` (const double p, const `size_t` M, const double \*A, const `size_t` lda, double \*X, const `size_t` ldx, int \*nullity, bool positive)
- `double * Invert2_modular_double` (const double p, const `size_t` M, double \*A, const `size_t` lda, double \*X, const `size_t` ldx, int \*nullity, bool positive)
- `size_t KrylovElim_modular_double` (const double p, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, `size_t` \*P, `size_t` \*Q, const `size_t` deg, `size_t` \*iterates, `size_t` \*inviterates, const `size_t` maxit, `size_t` virt, bool positive)
- `size_t SpecRankProfile_modular_double` (const double p, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, const `size_t` deg, `size_t` \*rankProfile, bool positive)
- `size_t Rank_modular_double` (const double p, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, bool positive)
- `bool IsSingular_modular_double` (const double p, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, bool positive)
- `double Det_modular_double` (const double p, const `size_t` N, double \*A, const `size_t` lda, bool positive)
- `double * Solve_modular_double` (const double p, const `size_t` M, double \*A, const `size_t` lda, double \*x, const int incx, const double \*b, const int incb, bool positive)
- `void solveLB_modular_double` (const double p, const enum `FFLAS_C_SIDE` Side, const `size_t` M, const `size_t` N, const `size_t` R, double \*L, const `size_t` ldl, const `size_t` \*Q, double \*B, const `size_t` ldb)
- `void solveLB2_modular_double` (const double p, const enum `FFLAS_C_SIDE` Side, const `size_t` M, const `size_t` N, const `size_t` R, double \*L, const `size_t` ldl, const `size_t` \*Q, double \*B, const `size_t` ldb, bool positive)
- `void RandomNullSpaceVector_modular_double` (const double p, const enum `FFLAS_C_SIDE` Side, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, double \*X, const `size_t` incX, bool positive)
- `size_t NullSpaceBasis_modular_double` (const double p, const enum `FFLAS_C_SIDE` Side, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, double \*\*NS, `size_t` \*ldn, `size_t` \*NSdim, bool positive)
- `size_t RowRankProfile_modular_double` (const double p, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, `size_t` \*\*rkprofile, const enum `FFPACK_C_LU_TAG` LuTag, bool positive)
- `size_t ColumnRankProfile_modular_double` (const double p, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, `size_t` \*\*rkprofile, const enum `FFPACK_C_LU_TAG` LuTag, bool positive)
- `void RankProfileFromLU` (const `size_t` \*P, const `size_t` N, const `size_t` R, `size_t` \*rkprofile, const enum `FFPACK_C_LU_TAG` LuTag)
- `size_t LeadingSubmatrixRankProfiles` (const `size_t` M, const `size_t` N, const `size_t` R, const `size_t` LSm, const `size_t` LSn, const `size_t` \*P, const `size_t` \*Q, `size_t` \*RRP, `size_t` \*CRP)
- `size_t RowRankProfileSubmatrixIndices_modular_double` (const double p, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, `size_t` \*\*rowindices, `size_t` \*\*colindices, `size_t` \*R, bool positive)
- `size_t ColRankProfileSubmatrixIndices_modular_double` (const double p, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, `size_t` \*\*rowindices, `size_t` \*\*colindices, `size_t` \*R, bool positive)
- `size_t RowRankProfileSubmatrix_modular_double` (const double p, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, double \*\*X, `size_t` \*R, bool positive)
- `size_t ColRankProfileSubmatrix_modular_double` (const double p, const `size_t` M, const `size_t` N, double \*A, const `size_t` lda, double \*\*X, `size_t` \*R, bool positive)

- void [getTriangular\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const enum [FFLAS\\_C\\_DIAG](#) diag, const size\_t M, const size\_t N, const size\_t R, const double \*A, const size\_t lda, double \*T, const size\_t ldt, const bool OnlyNonZeroVectors, bool positive)
- void [getTriangularin\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const enum [FFLAS\\_C\\_DIAG](#) diag, const size\_t M, const size\_t N, const size\_t R, double \*A, const size\_t lda, bool positive)
- void [getEchelonForm\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const enum [FFLAS\\_C\\_DIAG](#) diag, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, const double \*A, const size\_t lda, double \*T, const size\_t ldt, const bool OnlyNonZeroVectors, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- void [getEchelonFormin\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const enum [FFLAS\\_C\\_DIAG](#) diag, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, double \*A, const size\_t lda, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- void [getEchelonTransform\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const enum [FFLAS\\_C\\_DIAG](#) diag, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, const size\_t \*Q, const double \*A, const size\_t lda, double \*T, const size\_t ldt, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- void [getReducedEchelonForm\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, const double \*A, const size\_t lda, double \*T, const size\_t ldt, const bool OnlyNonZeroVectors, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- void [getReducedEchelonFormin\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, double \*A, const size\_t lda, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- void [getReducedEchelonTransform\\_modular\\_double](#) (const double p, const enum [FFLAS\\_C\\_UPLO](#) Uplo, const size\_t M, const size\_t N, const size\_t R, const size\_t \*P, const size\_t \*Q, const double \*A, const size\_t lda, double \*T, const size\_t ldt, const enum [FFPACK\\_C\\_LU\\_TAG](#) LuTag, bool positive)
- void [PLUQtoEchelonPermutation](#) (const size\_t N, const size\_t R, const size\_t \*P, size\_t \*outPerm)

### 13.234.1 Macro Definition Documentation

#### 13.234.1.1 FFPACK\_COMPILED

```
#define FFPACK_COMPILED
```

### 13.234.2 Enumeration Type Documentation

#### 13.234.2.1 FFLAS\_C\_ORDER

```
enum FFLAS_C_ORDER
```

Enumerator

|               |  |
|---------------|--|
| FflasRowMajor |  |
| FflasColMajor |  |

#### 13.234.2.2 FFLAS\_C\_TRANSPOSE

```
enum FFLAS_C_TRANSPOSE
```

Enumerator

|              |  |
|--------------|--|
| FflasNoTrans |  |
| FflasTrans   |  |

#### 13.234.2.3 FFLAS\_C\_UPLO

```
enum FFLAS_C_UPLO
```

## Enumerator

|            |  |
|------------|--|
| FflasUpper |  |
| FflasLower |  |

**13.234.2.4 FFLAS\_C\_DIAG**

enum [FFLAS\\_C\\_DIAG](#)

## Enumerator

|              |  |
|--------------|--|
| FflasNonUnit |  |
| FflasUnit    |  |

**13.234.2.5 FFLAS\_C\_SIDE**

enum [FFLAS\\_C\\_SIDE](#)

## Enumerator

|            |  |
|------------|--|
| FflasLeft  |  |
| FflasRight |  |

**13.234.2.6 FFPACK\_C\_LU\_TAG**

enum [FFPACK\\_C\\_LU\\_TAG](#)

## Enumerator

|                     |  |
|---------------------|--|
| FfpackSlabRecursive |  |
| FfpackTileRecursive |  |
| FfpackSingular      |  |

**13.234.2.7 FFPACK\_C\_CHARPOLY\_TAG**

enum [FFPACK\\_C\\_CHARPOLY\\_TAG](#)

## Enumerator

|                  |  |
|------------------|--|
| FfpackLUK        |  |
| FfpackKG         |  |
| FfpackHybrid     |  |
| FfpackKGFast     |  |
| FfpackDanilevski |  |
| FfpackArithProg  |  |
| FfpackKGFastG    |  |

**13.234.2.8 FFPACK\_C\_MINPOLY\_TAG**

enum [FFPACK\\_C\\_MINPOLY\\_TAG](#)

## Enumerator

|             |  |
|-------------|--|
| FfpackDense |  |
| FfpackKGF   |  |

### 13.234.3 Function Documentation

#### 13.234.3.1 LAPACKPerm2MathPerm()

```
void LAPACKPerm2MathPerm (
 size_t * MathP,
 const size_t * LapackP,
 const size_t N)
```

#### 13.234.3.2 MathPerm2LAPACKPerm()

```
void MathPerm2LAPACKPerm (
 size_t * LapackP,
 const size_t * MathP,
 const size_t N)
```

#### 13.234.3.3 MatrixApplyS\_modular\_double()

```
void MatrixApplyS_modular_double (
 const double p,
 double * A,
 const size_t lda,
 const size_t width,
 const size_t M2,
 const size_t R1,
 const size_t R2,
 const size_t R3,
 const size_t R4,
 bool positive)
```

#### 13.234.3.4 PermApplyS\_double()

```
void PermApplyS_double (
 double * A,
 const size_t lda,
 const size_t width,
 const size_t M2,
 const size_t R1,
 const size_t R2,
 const size_t R3,
 const size_t R4)
```

#### 13.234.3.5 MatrixApplyT\_modular\_double()

```
void MatrixApplyT_modular_double (
 const double p,
 double * A,
 const size_t lda,
 const size_t width,
 const size_t N2,
 const size_t R1,
 const size_t R2,
 const size_t R3,
```



```
 const size_t R4,
 bool positive)
```

#### 13.234.3.6 PermApplyT\_double()

```
void PermApplyT_double (
 double * A,
 const size_t lda,
 const size_t width,
 const size_t N2,
 const size_t R1,
 const size_t R2,
 const size_t R3,
 const size_t R4)
```

#### 13.234.3.7 composePermutationsLLM()

```
void composePermutationsLLM (
 size_t * MathP,
 const size_t * P1,
 const size_t * P2,
 const size_t R,
 const size_t N)
```

#### 13.234.3.8 composePermutationsLLL()

```
void composePermutationsLLL (
 size_t * P1,
 const size_t * P2,
 const size_t R,
 const size_t N)
```

#### 13.234.3.9 composePermutationsMLM()

```
void composePermutationsMLM (
 size_t * MathP1,
 const size_t * P2,
 const size_t R,
 const size_t N)
```

#### 13.234.3.10 cyclic\_shift\_mathPerm()

```
void cyclic_shift_mathPerm (
 size_t * P,
 const size_t s)
```

#### 13.234.3.11 cyclic\_shift\_row\_modular\_double()

```
void cyclic_shift_row_modular_double (
 const double p,
 double * A,
 size_t m,
 size_t n,
 size_t lda,
 bool positive)
```

#### 13.234.3.12 cyclic\_shift\_col\_modular\_double()

```
void cyclic_shift_col_modular_double (
 const double p,
```

```
double * A,
size_t m,
size_t n,
size_t lda,
bool positive)
```

### 13.234.3.13 applyP\_modular\_double()

```
void applyP_modular_double (
 const double p,
 const enum FFLAS_C_SIDE Side,
 const enum FFLAS_C_TRANSPOSE Trans,
 const size_t M,
 const size_t ibeg,
 const size_t iend,
 double * A,
 const size_t lda,
 const size_t * P,
 bool positive)
```

### 13.234.3.14 fgetrsin\_modular\_double()

```
void fgetrsin_modular_double (
 const double p,
 const enum FFLAS_C_SIDE Side,
 const size_t M,
 const size_t N,
 const size_t R,
 double * A,
 const size_t lda,
 const size_t * P,
 const size_t * Q,
 double * B,
 const size_t ldb,
 int * info,
 bool positive)
```

### 13.234.3.15 fgetrs\_modular\_double()

```
double * fgetrs_modular_double (
 const double p,
 const enum FFLAS_C_SIDE Side,
 const size_t M,
 const size_t N,
 const size_t NRHS,
 const size_t R,
 double * A,
 const size_t lda,
 const size_t * P,
 const size_t * Q,
 double * X,
 const size_t ldx,
 const double * B,
 const size_t ldb,
 int * info,
 bool positive)
```

**13.234.3.16 fgesvin\_modular\_double()**

```
size_t fgesvin_modular_double (
 const double p,
 const enum FFLAS_C_SIDE Side,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 double * B,
 const size_t ldb,
 int * info,
 bool positive)
```

**13.234.3.17 fgesv\_modular\_double()**

```
size_t fgesv_modular_double (
 const double p,
 const enum FFLAS_C_SIDE Side,
 const size_t M,
 const size_t N,
 const size_t NRHS,
 double * A,
 const size_t lda,
 double * X,
 const size_t ldx,
 const double * B,
 const size_t ldb,
 int * info)
```

**13.234.3.18 ftrtri\_modular\_double()**

```
void ftrtri_modular_double (
 const double p,
 const enum FFLAS_C_UPLO Uplo,
 const enum FFLAS_C_DIAG Diag,
 const size_t N,
 double * A,
 const size_t lda,
 bool positive)
```

**13.234.3.19 trinv\_left\_modular\_double()**

```
void trinv_left_modular_double (
 const double p,
 const size_t N,
 const double * L,
 const size_t ldl,
 double * X,
 const size_t ldx,
 bool positive)
```

**13.234.3.20 ftrtrm\_modular\_double()**

```
void ftrtrm_modular_double (
 const double p,
 const enum FFLAS_C_DIAG diag,
 const size_t N,
 double * A,
```

```
 const size_t lda,
 bool positive)
```

#### 13.234.3.21 PLUQ\_modular\_double()

```
size_t PLUQ_modular_double (
 const double p,
 const enum FFLAS_C_DIAG Diag,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Q,
 bool positive)
```

#### 13.234.3.22 LUdivine\_modular\_double()

```
size_t LUdivine_modular_double (
 const double p,
 const enum FFLAS_C_DIAG Diag,
 const enum FFLAS_C_TRANSPOSE trans,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const enum FFPACK_C_LU_TAG LuTag,
 const size_t cutoff,
 bool positive)
```

#### 13.234.3.23 LUdivine\_small\_modular\_double()

```
size_t LUdivine_small_modular_double (
 const double p,
 const enum FFLAS_C_DIAG Diag,
 const enum FFLAS_C_TRANSPOSE trans,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Q,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

#### 13.234.3.24 LUdivine\_gauss\_modular\_double()

```
size_t LUdivine_gauss_modular_double (
 const double p,
 const enum FFLAS_C_DIAG Diag,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Q,
```

```
const enum FFPACK_C_LU_TAG LuTag,
bool positive)
```

### 13.234.3.25 ColumnEchelonForm\_modular\_double()

```
size_t ColumnEchelonForm_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

### 13.234.3.26 RowEchelonForm\_modular\_double()

```
size_t RowEchelonForm_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

### 13.234.3.27 ColumnEchelonForm\_modular\_float()

```
size_t ColumnEchelonForm_modular_float (
 const float p,
 const size_t M,
 const size_t N,
 float * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

### 13.234.3.28 RowEchelonForm\_modular\_float()

```
size_t RowEchelonForm_modular_float (
 const float p,
 const size_t M,
 const size_t N,
 float * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

**13.234.3.29 ColumnEchelonForm\_modular\_int32\_t()**

```
size_t ColumnEchelonForm_modular_int32_t (
 const int32_t p,
 const size_t M,
 const size_t N,
 int32_t * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

**13.234.3.30 RowEchelonForm\_modular\_int32\_t()**

```
size_t RowEchelonForm_modular_int32_t (
 const int32_t p,
 const size_t M,
 const size_t N,
 int32_t * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

**13.234.3.31 ReducedColumnEchelonForm\_modular\_double()**

```
size_t ReducedColumnEchelonForm_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

**13.234.3.32 ReducedRowEchelonForm\_modular\_double()**

```
size_t ReducedRowEchelonForm_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

**13.234.3.33 ReducedColumnEchelonForm\_modular\_float()**

```
size_t ReducedColumnEchelonForm_modular_float (
 const float p,
```

```

 const size_t M,
 const size_t N,
 float * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

#### 13.234.3.34 ReducedRowEchelonForm\_modular\_float()

```

size_t ReducedRowEchelonForm_modular_float (
 const float p,
 const size_t M,
 const size_t N,
 float * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

#### 13.234.3.35 ReducedColumnEchelonForm\_modular\_int32\_t()

```

size_t ReducedColumnEchelonForm_modular_int32_t (
 const int32_t p,
 const size_t M,
 const size_t N,
 int32_t * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

#### 13.234.3.36 ReducedRowEchelonForm\_modular\_int32\_t()

```

size_t ReducedRowEchelonForm_modular_int32_t (
 const int32_t p,
 const size_t M,
 const size_t N,
 int32_t * A,
 const size_t lda,
 size_t * P,
 size_t * Qt,
 const bool transform,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)

```

#### 13.234.3.37 ReducedRowEchelonForm2\_modular\_double()

```

size_t ReducedRowEchelonForm2_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,

```

```
const size_t lda,
size_t * P,
size_t * Qt,
const bool transform,
bool positive)
```

#### 13.234.3.38 REF\_modular\_double()

```
size_t REF_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 const size_t colbeg,
 const size_t rowbeg,
 const size_t colsize,
 size_t * Qt,
 size_t * P,
 bool positive)
```

#### 13.234.3.39 Invertin\_modular\_double()

```
double * Invertin_modular_double (
 const double p,
 const size_t M,
 double * A,
 const size_t lda,
 int * nullity,
 bool positive)
```

#### 13.234.3.40 Invert\_modular\_double()

```
double * Invert_modular_double (
 const double p,
 const size_t M,
 const double * A,
 const size_t lda,
 double * X,
 const size_t ldx,
 int * nullity,
 bool positive)
```

#### 13.234.3.41 Invert2\_modular\_double()

```
double * Invert2_modular_double (
 const double p,
 const size_t M,
 double * A,
 const size_t lda,
 double * X,
 const size_t ldx,
 int * nullity,
 bool positive)
```

#### 13.234.3.42 KrylovElim\_modular\_double()

```
size_t KrylovElim_modular_double (
 const double p,
```



```
const size_t M,
const size_t N,
double * A,
const size_t lda,
size_t * P,
size_t * Q,
const size_t deg,
size_t * iterates,
size_t * inviterates,
const size_t maxit,
size_t virt,
bool positive)
```

#### 13.234.3.43 SpecRankProfile\_modular\_double()

```
size_t SpecRankProfile_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 const size_t deg,
 size_t * rankProfile,
 bool positive)
```

#### 13.234.3.44 Rank\_modular\_double()

```
size_t Rank_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 bool positive)
```

#### 13.234.3.45 IsSingular\_modular\_double()

```
bool IsSingular_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 bool positive)
```

#### 13.234.3.46 Det\_modular\_double()

```
double Det_modular_double (
 const double p,
 const size_t N,
 double * A,
 const size_t lda,
 bool positive)
```

#### 13.234.3.47 Solve\_modular\_double()

```
double * Solve_modular_double (
 const double p,
 const size_t M,
```

```

double * A,
const size_t lda,
double * x,
const int incx,
const double * b,
const int incb,
bool positive)

```

#### 13.234.3.48 solveLB\_modular\_double()

```

void solveLB_modular_double (
 const double p,
 const enum FFLAS_C_SIDE Side,
 const size_t M,
 const size_t N,
 const size_t R,
 double * L,
 const size_t ldl,
 const size_t * Q,
 double * B,
 const size_t ldb)

```

#### 13.234.3.49 solveLB2\_modular\_double()

```

void solveLB2_modular_double (
 const double p,
 const enum FFLAS_C_SIDE Side,
 const size_t M,
 const size_t N,
 const size_t R,
 double * L,
 const size_t ldl,
 const size_t * Q,
 double * B,
 const size_t ldb,
 bool positive)

```

#### 13.234.3.50 RandomNullSpaceVector\_modular\_double()

```

void RandomNullSpaceVector_modular_double (
 const double p,
 const enum FFLAS_C_SIDE Side,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 double * X,
 const size_t incX,
 bool positive)

```

#### 13.234.3.51 NullSpaceBasis\_modular\_double()

```

size_t NullSpaceBasis_modular_double (
 const double p,
 const enum FFLAS_C_SIDE Side,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,

```

```
double ** NS,
size_t * ldn,
size_t * NSdim,
bool positive)
```

#### 13.234.3.52 RowRankProfile\_modular\_double()

```
size_t RowRankProfile_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t ** rkprofile,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

#### 13.234.3.53 ColumnRankProfile\_modular\_double()

```
size_t ColumnRankProfile_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t ** rkprofile,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

#### 13.234.3.54 RankProfileFromLU()

```
void RankProfileFromLU (
 const size_t * P,
 const size_t N,
 const size_t R,
 size_t * rkprofile,
 const enum FFPACK_C_LU_TAG LuTag)
```

#### 13.234.3.55 LeadingSubmatrixRankProfiles()

```
size_t LeadingSubmatrixRankProfiles (
 const size_t M,
 const size_t N,
 const size_t R,
 const size_t LSm,
 const size_t LSn,
 const size_t * P,
 const size_t * Q,
 size_t * RRP,
 size_t * CRP)
```

#### 13.234.3.56 RowRankProfileSubmatrixIndices\_modular\_double()

```
size_t RowRankProfileSubmatrixIndices_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
```

```

 size_t ** rowindices,
 size_t ** colindices,
 size_t * R,
 bool positive)

```

### 13.234.3.57 ColRankProfileSubmatrixIndices\_modular\_double()

```

size_t ColRankProfileSubmatrixIndices_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 size_t ** rowindices,
 size_t ** colindices,
 size_t * R,
 bool positive)

```

### 13.234.3.58 RowRankProfileSubmatrix\_modular\_double()

```

size_t RowRankProfileSubmatrix_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 double ** X,
 size_t * R,
 bool positive)

```

### 13.234.3.59 ColRankProfileSubmatrix\_modular\_double()

```

size_t ColRankProfileSubmatrix_modular_double (
 const double p,
 const size_t M,
 const size_t N,
 double * A,
 const size_t lda,
 double ** X,
 size_t * R,
 bool positive)

```

### 13.234.3.60 getTriangular\_modular\_double()

```

void getTriangular_modular_double (
 const double p,
 const enum FFLAS_C_UPLO Uplo,
 const enum FFLAS_C_DIAG diag,
 const size_t M,
 const size_t N,
 const size_t R,
 const double * A,
 const size_t lda,
 double * T,
 const size_t ldt,
 const bool OnlyNonZeroVectors,
 bool positive)

```

**13.234.3.61 getTriangularin\_modular\_double()**

```
void getTriangularin_modular_double (
 const double p,
 const enum FFLAS_C_UPLO Uplo,
 const enum FFLAS_C_DIAG diag,
 const size_t M,
 const size_t N,
 const size_t R,
 double * A,
 const size_t lda,
 bool positive)
```

**13.234.3.62 getEchelonForm\_modular\_double()**

```
void getEchelonForm_modular_double (
 const double p,
 const enum FFLAS_C_UPLO Uplo,
 const enum FFLAS_C_DIAG diag,
 const size_t M,
 const size_t N,
 const size_t R,
 const size_t * P,
 const double * A,
 const size_t lda,
 double * T,
 const size_t ldt,
 const bool OnlyNonZeroVectors,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

**13.234.3.63 getEchelonFormin\_modular\_double()**

```
void getEchelonFormin_modular_double (
 const double p,
 const enum FFLAS_C_UPLO Uplo,
 const enum FFLAS_C_DIAG diag,
 const size_t M,
 const size_t N,
 const size_t R,
 const size_t * P,
 double * A,
 const size_t lda,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

**13.234.3.64 getEchelonTransform\_modular\_double()**

```
void getEchelonTransform_modular_double (
 const double p,
 const enum FFLAS_C_UPLO Uplo,
 const enum FFLAS_C_DIAG diag,
 const size_t M,
 const size_t N,
 const size_t R,
 const size_t * P,
 const size_t * Q,
 const double * A,
 const size_t lda,
```

```
double * T,
const size_t ldt,
const enum FFPACK_C_LU_TAG LuTag,
bool positive)
```

### 13.234.3.65 getReducedEchelonForm\_modular\_double()

```
void getReducedEchelonForm_modular_double (
 const double p,
 const enum FFLAS_C_UPLO Uplo,
 const size_t M,
 const size_t N,
 const size_t R,
 const size_t * P,
 const double * A,
 const size_t lda,
 double * T,
 const size_t ldt,
 const bool OnlyNonZeroVectors,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

### 13.234.3.66 getReducedEchelonFormin\_modular\_double()

```
void getReducedEchelonFormin_modular_double (
 const double p,
 const enum FFLAS_C_UPLO Uplo,
 const size_t M,
 const size_t N,
 const size_t R,
 const size_t * P,
 double * A,
 const size_t lda,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

### 13.234.3.67 getReducedEchelonTransform\_modular\_double()

```
void getReducedEchelonTransform_modular_double (
 const double p,
 const enum FFLAS_C_UPLO Uplo,
 const size_t M,
 const size_t N,
 const size_t R,
 const size_t * P,
 const size_t * Q,
 const double * A,
 const size_t lda,
 double * T,
 const size_t ldt,
 const enum FFPACK_C_LU_TAG LuTag,
 bool positive)
```

### 13.234.3.68 PLUQtoEchelonPermutation()

```
void PLUQtoEchelonPermutation (
 const size_t N,
 const size_t R,
```

```
const size_t * P,
size_t * outPerm)
```

## 13.235 ffpack\_inst.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "givaro/modular.h"
#include "givaro/modular-balanced.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "ffpack_inst_implem.inl"
```

### Macros

- `#define __FFPACK_INST_C`
- `#define FFLAS_COMPILED`
- `#define INST_OR_DECL`
- `#define FFLAS_FIELD Givaro::ModularBalanced`
- `#define FFLAS_ELT double`
- `#define FFLAS_ELT float`
- `#define FFLAS_ELT int64_t`
- `#define FFLAS_FIELD Givaro::Modular`
- `#define FFLAS_ELT double`
- `#define FFLAS_ELT float`
- `#define FFLAS_ELT int64_t`

### 13.235.1 Macro Definition Documentation

#### 13.235.1.1 \_\_FFPACK\_INST\_C

```
#define __FFPACK_INST_C
```

#### 13.235.1.2 FFLAS\_COMPILED

```
#define FFLAS_COMPILED
```

#### 13.235.1.3 INST\_OR\_DECL

```
#define INST_OR_DECL
```

#### 13.235.1.4 FFLAS\_FIELD [1/2]

```
#define FFLAS_FIELD Givaro::ModularBalanced
```

#### 13.235.1.5 FFLAS\_ELT [1/6]

```
#define FFLAS_ELT double
```

#### 13.235.1.6 FFLAS\_ELT [2/6]

```
#define FFLAS_ELT float
```

#### 13.235.1.7 FFLAS\_ELT [3/6]

```
#define FFLAS_ELT int64_t
```

#### 13.235.1.8 FFLAS\_FIELD [2/2]

```
#define FFLAS_FIELD Givaro::Modular
```

**13.235.1.9 FFLAS\_ELT [4/6]**

```
#define FFLAS_ELT double
```

**13.235.1.10 FFLAS\_ELT [5/6]**

```
#define FFLAS_ELT float
```

**13.235.1.11 FFLAS\_ELT [6/6]**

```
#define FFLAS_ELT int64_t
```

**13.236 ffpack\_inst.h File Reference**

```
#include "givaro/modular.h"
#include "givaro/modular-balanced.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "ffpack_inst_implem.inl"
```

**Macros**

- `#define FFLAS_COMPILED`
- `#define INST_OR_DECL <>`
- `#define FFLAS_FIELD Givaro::ModularBalanced`
- `#define FFLAS_ELT double`
- `#define FFLAS_ELT float`
- `#define FFLAS_ELT int64_t`
- `#define FFLAS_FIELD Givaro::Modular`
- `#define FFLAS_ELT double`
- `#define FFLAS_ELT float`
- `#define FFLAS_ELT int64_t`

**13.236.1 Macro Definition Documentation****13.236.1.1 FFLAS\_COMPILED**

```
#define FFLAS_COMPILED
```

**13.236.1.2 INST\_OR\_DECL**

```
#define INST_OR_DECL <>
```

**13.236.1.3 FFLAS\_FIELD [1/2]**

```
#define FFLAS_FIELD Givaro::ModularBalanced
```

**13.236.1.4 FFLAS\_ELT [1/6]**

```
#define FFLAS_ELT double
```

**13.236.1.5 FFLAS\_ELT [2/6]**

```
#define FFLAS_ELT float
```

**13.236.1.6 FFLAS\_ELT [3/6]**

```
#define FFLAS_ELT int64_t
```



**13.236.1.7 FFLAS\_FIELD [2/2]**

```
#define FFLAS_FIELD Givaro::Modular
```

**13.236.1.8 FFLAS\_ELT [4/6]**

```
#define FFLAS_ELT double
```

**13.236.1.9 FFLAS\_ELT [5/6]**

```
#define FFLAS_ELT float
```

**13.236.1.10 FFLAS\_ELT [6/6]**

```
#define FFLAS_ELT int64_t
```

**13.237 ffpack\_inst\_implem.inl File Reference****Namespaces**

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

**Functions**

- void [composePermutationsLLM](#) (size\_t \*MathP, const size\_t \*P1, const size\_t \*P2, const size\_t R, const size\_t N)  
*Computes  $P1 \times \text{Diag}(I_R, P2)$  where  $P1$  is a LAPACK and  $P2$  a LAPACK permutation and store the result in  $\text{MathP}$  as a  $\text{MathPermutation}$  format.*
- void [composePermutationsLLL](#) (size\_t \*P1, const size\_t \*P2, const size\_t R, const size\_t N)  
*Computes  $P1 \times \text{Diag}(I_R, P2)$  where  $P1$  is a LAPACK and  $P2$  a LAPACK permutation and store the result in  $P1$  as a LAPACK permutation.*
- void [composePermutationsMLM](#) (size\_t \*MathP1, const size\_t \*P2, const size\_t R, const size\_t N)  
*Computes  $\text{MathP1} \times \text{Diag}(I_R, P2)$  where  $\text{MathP1}$  is a  $\text{MathPermutation}$  and  $P2$  a LAPACK permutation and store the result in  $\text{MathP1}$  as a  $\text{MathPermutation}$  format.*
- void [cyclic\\_shift\\_mathPerm](#) (size\_t \*P, const size\_t s)
- template<typename Base\_t >  
void [cyclic\\_shift\\_row\\_col](#) (Base\_t \*A, size\_t m, size\_t n, size\_t lda)
- template [INST\\_OR\\_DECL](#) void [cyclic\\_shift\\_row](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, [FFLAS\\_ELT](#) \*A, size\_t m, size\_t n, size\_t lda)
- template [INST\\_OR\\_DECL](#) void [cyclic\\_shift\\_col](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, [FFLAS\\_ELT](#) \*A, size\_t m, size\_t n, size\_t lda)
- template [INST\\_OR\\_DECL](#) void [applyP](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const [FFLAS::FFLAS\\_TRANSPOSE](#) Trans, const size\_t M, const size\_t ibeg, const size\_t iend, [FFLAS\\_ELT](#) \*A, const size\_t lda, const size\_t \*P)
- template [INST\\_OR\\_DECL](#) void [fgetrs](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t R, [FFLAS\\_ELT](#) \*A, const size\_t lda, const size\_t \*P, const size\_t \*Q, [FFLAS\\_ELT](#) \*B, const size\_t ldb, int \*info)
- template [INST\\_OR\\_DECL](#) [FFLAS\\_ELT](#) \* [fgetrs](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t NRHS, const size\_t R, [FFLAS\\_ELT](#) \*A, const size\_t lda, const size\_t \*P, const size\_t \*Q, [FFLAS\\_ELT](#) \*X, const size\_t ldx, const [FFLAS\\_ELT](#) \*B, const size\_t ldb, int \*info)
- template [INST\\_OR\\_DECL](#) size\_t [fgesv](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, [FFLAS\\_ELT](#) \*A, const size\_t lda, [FFLAS\\_ELT](#) \*B, const size\_t ldb, int \*info)
- template [INST\\_OR\\_DECL](#) size\_t [fgesv](#) (const [FFLAS\\_FIELD](#)< [FFLAS\\_ELT](#) > &F, const [FFLAS::FFLAS\\_SIDE](#) Side, const size\_t M, const size\_t N, const size\_t NRHS, [FFLAS\\_ELT](#) \*A, const size\_t lda, [FFLAS\\_ELT](#) \*X, const size\_t ldx, const [FFLAS\\_ELT](#) \*B, const size\_t ldb, int \*info)

- template `INST_OR_DECL` void `fttri` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS::FFLAS_UPLO` Uplo, const `FFLAS::FFLAS_DIAG` Diag, const size\_t N, `FFLAS_ELT` \*A, const size\_t lda, const size\_t threshold)
- template `INST_OR_DECL` void `trinv_left` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t N, const `FFLAS_ELT` \*L, const size\_t ldl, `FFLAS_ELT` \*X, const size\_t ldx)
- template `INST_OR_DECL` void `fttrm` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS::FFLAS_SIDE` side, const `FFLAS::FFLAS_DIAG` diag, const size\_t N, `FFLAS_ELT` \*A, const size\_t lda)
- template `INST_OR_DECL` size\_t `PLUQ` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS::FFLAS_DIAG` Diag, const size\_t M, const size\_t N, `FFLAS_ELT` \*A, const size\_t lda, size\_t \*P, size\_t \*Q)
- template `INST_OR_DECL` size\_t `LUdivine` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS::FFLAS_DIAG` Diag, const `FFLAS::FFLAS_TRANSPOSE` trans, const size\_t M, const size\_t N, `FFLAS_ELT` \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, const `FFPACK_LU_TAG` LuTag, const size\_t cutoff)
- template `INST_OR_DECL` size\_t `LUdivine_small` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS::FFLAS_DIAG` Diag, const `FFLAS::FFLAS_TRANSPOSE` trans, const size\_t M, const size\_t N, `FFLAS_ELT` \*A, const size\_t lda, size\_t \*P, size\_t \*Q, const `FFPACK_LU_TAG` LuTag)
- template `INST_OR_DECL` size\_t `LUdivine_gauss` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS::FFLAS_DIAG` Diag, const size\_t M, const size\_t N, `FFLAS_ELT` \*A, const size\_t lda, size\_t \*P, size\_t \*Q, const `FFPACK_LU_TAG` LuTag)
- template `INST_OR_DECL` size\_t `RowEchelonForm` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t M, const size\_t N, `FFLAS_ELT` \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, const bool transform, const `FFPACK_LU_TAG` LuTag)
- template `INST_OR_DECL` size\_t `ReducedRowEchelonForm` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t M, const size\_t N, `FFLAS_ELT` \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, const bool transform, const `FFPACK_LU_TAG` LuTag)
- template `INST_OR_DECL` size\_t `ColumnEchelonForm` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t M, const size\_t N, `FFLAS_ELT` \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, const bool transform, const `FFPACK_LU_TAG` LuTag)
- template `INST_OR_DECL` size\_t `ReducedColumnEchelonForm` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t M, const size\_t N, `FFLAS_ELT` \*A, const size\_t lda, size\_t \*P, size\_t \*Qt, const bool transform, const `FFPACK_LU_TAG` LuTag)
- template `INST_OR_DECL` `FFLAS_ELT` \* `Invert` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t M, `FFLAS_ELT` \*A, const size\_t lda, int &nullity)
- template `INST_OR_DECL` `FFLAS_ELT` \* `Invert` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t M, const `FFLAS_ELT` \*A, const size\_t lda, `FFLAS_ELT` \*X, const size\_t ldx, int &nullity)
- template `INST_OR_DECL` `FFLAS_ELT` \* `Invert2` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const size\_t M, `FFLAS_ELT` \*A, const size\_t lda, `FFLAS_ELT` \*X, const size\_t ldx, int &nullity)
- template `INST_OR_DECL` std::list< Givaro::Poly1Dom< `FFLAS_FIELD`< `FFLAS_ELT` > >::Element > & `CharPoly` (const Givaro::Poly1Dom< `FFLAS_FIELD`< `FFLAS_ELT` > > &R, std::list< Givaro::Poly1Dom< `FFLAS_FIELD`< `FFLAS_ELT` > >::Element > &charp, const size\_t N, `FFLAS_ELT` \*A, const size\_t lda, `FFLAS_FIELD`< `FFLAS_ELT` >::RandIter &G, const `FFPACK_CHARPOLY_TAG` CharpTag, const size\_t degree)
- template `INST_OR_DECL` Givaro::Poly1Dom< `FFLAS_FIELD`< `FFLAS_ELT` > >::Element & `CharPoly` (const Givaro::Poly1Dom< `FFLAS_FIELD`< `FFLAS_ELT` > > &R, Givaro::Poly1Dom< `FFLAS_FIELD`< `FFLAS_ELT` > >::Element &charp, const size\_t N, `FFLAS_ELT` \*A, const size\_t lda, `FFLAS_FIELD`< `FFLAS_ELT` >::RandIter &G, const `FFPACK_CHARPOLY_TAG` CharpTag, const size\_t degree)
- template `INST_OR_DECL` Givaro::Poly1Dom< `FFLAS_FIELD`< `FFLAS_ELT` > >::Element & `CharPoly` (const Givaro::Poly1Dom< `FFLAS_FIELD`< `FFLAS_ELT` > > &R, Givaro::Poly1Dom< `FFLAS_FIELD`< `FFLAS_ELT` > >::Element &charp, const size\_t N, `FFLAS_ELT` \*A, const size\_t lda, const `FFPACK_CHARPOLY_TAG` CharpTag, const size\_t degree)
- template `INST_OR_DECL` std::vector< `FFLAS_ELT` > & `MinPoly` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, std::vector< `FFLAS_ELT` > &minP, const size\_t N, const `FFLAS_ELT` \*A, const size\_t lda, `FFLAS_FIELD`< `FFLAS_ELT` >::RandIter &G)
- template `INST_OR_DECL` std::vector< `FFLAS_ELT` > & `MinPoly` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, std::vector< `FFLAS_ELT` > &minP, const size\_t N, const `FFLAS_ELT` \*A, const size\_t lda)
- template `INST_OR_DECL` std::vector< `FFLAS_ELT` > & `MatVecMinPoly` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, std::vector< `FFLAS_ELT` > &minP, const size\_t N, const `FFLAS_ELT` \*A, const size\_t lda, const `FFLAS_ELT` \*V, const size\_t incv)

- template `INST_OR_DECL` `size_t KrylovElim` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `size_t` M, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda, `size_t` \*P, `size_t` \*Q, const `size_t` deg, `size_t` \*iterates, `size_t` \*inviterates, const `size_t` maxit, `size_t` virt)
- template `INST_OR_DECL` `size_t SpecRankProfile` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `size_t` M, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda, const `size_t` deg, `size_t` \*rankProfile)
- template `INST_OR_DECL` `size_t Rank` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `size_t` M, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda)
- template `INST_OR_DECL` `bool IsSingular` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `size_t` M, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda)
- template `INST_OR_DECL` `FFLAS_ELT & Det` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, `FFLAS_ELT` &det, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda, `size_t` \*P, `size_t` \*Q)
- template `INST_OR_DECL` `FFLAS_ELT & Det` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, `FFLAS_ELT` &det, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda, const `FFLAS::ParSeqHelper::Parallel`< `FFLAS::CuttingStrategy::Recursive`, `FFLAS::StrategyParameter::Threads` > &parH, `size_t` \*P, `size_t` \*Q)
- template `INST_OR_DECL` `FFLAS_ELT * Solve` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `size_t` M, `FFLAS_ELT` \*A, const `size_t` lda, `FFLAS_ELT` \*x, const `int` incx, const `FFLAS_ELT` \*b, const `int` incb)
- template `INST_OR_DECL` `void solveLB` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS::FFLAS_SIDE` Side, const `size_t` M, const `size_t` N, const `size_t` R, `FFLAS_ELT` \*L, const `size_t` ldl, const `size_t` \*Q, `FFLAS_ELT` \*B, const `size_t` ldb)
- template `INST_OR_DECL` `void solveLB2` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS::FFLAS_SIDE` Side, const `size_t` M, const `size_t` N, const `size_t` R, `FFLAS_ELT` \*L, const `size_t` ldl, const `size_t` \*Q, `FFLAS_ELT` \*B, const `size_t` ldb)
- template `INST_OR_DECL` `void RandomNullSpaceVector` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS::FFLAS_SIDE` Side, const `size_t` M, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda, `FFLAS_ELT` \*X, const `size_t` incX)
- template `INST_OR_DECL` `size_t NullSpaceBasis` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS::FFLAS_SIDE` Side, const `size_t` M, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda, `FFLAS_ELT` \*&NS, `size_t` &ldn, `size_t` &NSdim)
- template `INST_OR_DECL` `size_t RowRankProfile` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `size_t` M, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda, `size_t` \*rkprofile, const `FFPACK_LU_TAG` LuTag)
- template `INST_OR_DECL` `size_t ColumnRankProfile` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `size_t` M, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda, `size_t` \*rkprofile, const `FFPACK_LU_TAG` LuTag)
- `void RankProfileFromLU` (const `size_t` \*P, const `size_t` N, const `size_t` R, `size_t` \*rkprofile, const `FFPACK_LU_TAG` LuTag)

*Recovers the column/row rank profile from the permutation of an LU decomposition.*

- `size_t LeadingSubmatrixRankProfiles` (const `size_t` M, const `size_t` N, const `size_t` R, const `size_t` LSm, const `size_t` LSn, const `size_t` \*P, const `size_t` \*Q, `size_t` \*RRP, `size_t` \*CRP)

*Recovers the row and column rank profiles of any leading submatrix from the PLUQ decomposition.*

- template `INST_OR_DECL` `size_t RowRankProfileSubmatrixIndices` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `size_t` M, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda, `size_t` \*rowindices, `size_t` \*colindices, `size_t` &R)
- template `INST_OR_DECL` `size_t ColRankProfileSubmatrixIndices` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `size_t` M, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda, `size_t` \*rowindices, `size_t` \*colindices, `size_t` &R)
- template `INST_OR_DECL` `size_t RowRankProfileSubmatrix` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `size_t` M, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda, `FFLAS_ELT` \*&X, `size_t` &R)
- template `INST_OR_DECL` `size_t ColRankProfileSubmatrix` (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `size_t` M, const `size_t` N, `FFLAS_ELT` \*A, const `size_t` lda, `FFLAS_ELT` \*&X, `size_t` &R)
- template `INST_OR_DECL` `void getTriangular`< `FFLAS_FIELD`< `FFLAS_ELT` > > (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS::FFLAS_UPLO` Uplo, const `FFLAS::FFLAS_DIAG` diag, const `size_t` M, const `size_t` N, const `size_t` R, const `FFLAS_ELT` \*A, const `size_t` lda, `FFLAS_ELT` \*T, const `size_t` ldt, const `bool` OnlyNonZeroVectors)
- template `INST_OR_DECL` `void getTriangular`< `FFLAS_FIELD`< `FFLAS_ELT` > > (const `FFLAS_FIELD`< `FFLAS_ELT` > &F, const `FFLAS::FFLAS_UPLO` Uplo, const `FFLAS::FFLAS_DIAG` diag, const `size_t` M, const `size_t` N, const `size_t` R, `FFLAS_ELT` \*A, const `size_t` lda)

- template `INST_OR_DECL` void `getEchelonForm< FFLAS_FIELD< FFLAS_ELT > >` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `FFLAS::FFLAS_UPLO` Uplo, const `FFLAS::FFLAS_DIAG` diag, const `size_t` M, const `size_t` N, const `size_t` R, const `size_t` \*P, const `FFLAS_ELT` \*A, const `size_t` lda, `FFLAS_ELT` \*T, const `size_t` ldt, const bool OnlyNonZeroVectors, const `FFPACK_LU_TAG` LuTag)
- template `INST_OR_DECL` void `getEchelonForm< FFLAS_FIELD< FFLAS_ELT > >` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `FFLAS::FFLAS_UPLO` Uplo, const `FFLAS::FFLAS_DIAG` diag, const `size_t` M, const `size_t` N, const `size_t` R, const `size_t` \*P, `FFLAS_ELT` \*A, const `size_t` lda, const `FFPACK_LU_TAG` LuTag)
- template `INST_OR_DECL` void `getEchelonTransform< FFLAS_FIELD< FFLAS_ELT > >` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `FFLAS::FFLAS_UPLO` Uplo, const `FFLAS::FFLAS_DIAG` diag, const `size_t` M, const `size_t` N, const `size_t` R, const `size_t` \*P, const `size_t` \*Q, const `FFLAS_ELT` \*A, const `size_t` lda, `FFLAS_ELT` \*T, const `size_t` ldt, const `FFPACK_LU_TAG` LuTag)
- template `INST_OR_DECL` void `getReducedEchelonForm< FFLAS_FIELD< FFLAS_ELT > >` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `FFLAS::FFLAS_UPLO` Uplo, const `size_t` M, const `size_t` N, const `size_t` R, const `size_t` \*P, const `FFLAS_ELT` \*A, const `size_t` lda, `FFLAS_ELT` \*T, const `size_t` ldt, const bool OnlyNonZeroVectors, const `FFPACK_LU_TAG` LuTag)
- template `INST_OR_DECL` void `getReducedEchelonForm< FFLAS_FIELD< FFLAS_ELT > >` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `FFLAS::FFLAS_UPLO` Uplo, const `size_t` M, const `size_t` N, const `size_t` R, const `size_t` \*P, `FFLAS_ELT` \*A, const `size_t` lda, const `FFPACK_LU_TAG` LuTag)
- template `INST_OR_DECL` void `getReducedEchelonTransform< FFLAS_FIELD< FFLAS_ELT > >` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `FFLAS::FFLAS_UPLO` Uplo, const `size_t` M, const `size_t` N, const `size_t` R, const `size_t` \*P, const `size_t` \*Q, const `FFLAS_ELT` \*A, const `size_t` lda, `FFLAS_ELT` \*T, const `size_t` ldt, const `FFPACK_LU_TAG` LuTag)
- void `PLUQtoEchelonPermutation` (const `size_t` N, const `size_t` R, const `size_t` \*P, `size_t` \*outPerm)  
*Auxiliary routine: determines the permutation that changes a PLUQ decomposition into a echelon form revealing PLUQ decomposition.*
- template `INST_OR_DECL` `FFLAS_ELT` \* `LQUPtoInverseOfFullRankMinor` (const `FFLAS_FIELD< FFLAS_ELT >` &F, const `size_t` rank, `FFLAS_ELT` \*A\_factors, const `size_t` lda, const `size_t` \*QtPointer, `FFLAS_ELT` \*X, const `size_t` ldx)

## 13.238 blockcuts.inl File Reference

```
#include <fflas-ffpack/fflas/fflas_enum.h>
#include <math.h>
#include <cassert>
```

### Data Structures

- struct [Single](#)
- struct [Row](#)
- struct [Column](#)
- struct [Block](#)
- struct [Recursive](#)
- struct [Fixed](#)
- struct [Threads](#)
- struct [Grain](#)
- struct [TwoD](#)
- struct [TwoDAdaptive](#)
- struct [ThreeD](#)
- struct [ThreeDInPlace](#)
- struct [ThreeDAdaptive](#)
- struct [Parallel< C, P >](#)
- struct [Sequential](#)
- struct [Compose< H1, H2 >](#)
- struct [ForStrategy1D< blocksize\\_t, Cut, Param >](#)
- struct [ForStrategy2D< blocksize\\_t, Cut, Param >](#)

## Namespaces

- namespace [FFLAS](#)
- namespace [FFLAS::CuttingStrategy](#)
- namespace [FFLAS::StrategyParameter](#)
- namespace [FFLAS::ParSeqHelper](#)

*[ParSeqHelper](#) for both [fgemm](#) and [ftrsm](#).*

## Macros

- `#define \_\_FFLASFFPACK\_fflas\_blockcuts\_INL`
- `#define \_\_FFLASFFPACK\_MINBLOCKCUTS ((size_t)256)`

## Typedefs

- typedef [Row](#) [RNSModulus](#)

## Functions

- `template<class Cut = CuttingStrategy::Block, class Strat = StrategyParameter::Threads>  
void BlockCuts (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<> void BlockCuts< CuttingStrategy::Single, StrategyParameter::Threads > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<> void BlockCuts< CuttingStrategy::Row, StrategyParameter::Fixed > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<> void BlockCuts< CuttingStrategy::Row, StrategyParameter::Grain > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t grainsize)`
- `template<> void BlockCuts< CuttingStrategy::Block, StrategyParameter::Grain > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t grainsize)`
- `template<> void BlockCuts< CuttingStrategy::Column, StrategyParameter::Fixed > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<> void BlockCuts< CuttingStrategy::Column, StrategyParameter::Grain > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t grainsize)`
- `template<> void BlockCuts< CuttingStrategy::Block, StrategyParameter::Fixed > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<> void BlockCuts< CuttingStrategy::Row, StrategyParameter::Threads > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<> void BlockCuts< CuttingStrategy::Column, StrategyParameter::Threads > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<> void BlockCuts< CuttingStrategy::Block, StrategyParameter::Threads > (size_t &RBLOCKSIZE, size_t &CBLOCKSIZE, const size_t m, const size_t n, const size_t numthreads)`
- `template<class Cut = CuttingStrategy::Block, class Param = StrategyParameter::Threads>  
void BlockCuts (size_t &rowBlockSize, size_t &colBlockSize, size_t &lastRBS, size_t &lastCBS, size_t &changeRBS, size_t &changeCBS, size_t &numRowBlock, size_t &numColBlock, size_t m, size_t n, const size_t numthreads)`

## 13.238.1 Macro Definition Documentation

### 13.238.1.1 [\\_\\_FFLASFFPACK\\_fflas\\_blockcuts\\_INL](#)

```
#define __FFLASFFPACK_fflas_blockcuts_INL
```

### 13.238.1.2 [\\_\\_FFLASFFPACK\\_MINBLOCKCUTS](#)

```
#define __FFLASFFPACK_MINBLOCKCUTS ((size_t)256)
```

## 13.239 fflas\_plevel1.h File Reference

```
#include "fflas-ffpack/paladin/parallel.h"
```

### Namespaces

- namespace [FFLAS](#)

### Functions

- template<class [Field](#) >  
void [pfzero](#) (const [Field](#) &F, size\_t m, size\_t n, typename [Field::Element\\_ptr](#) C, size\_t BS=0)
- template<class [Field](#) , class [RandIter](#) >  
void [pfrand](#) (const [Field](#) &F, [RandIter](#) &G, size\_t m, size\_t n, typename [Field::Element\\_ptr](#) C, size\_t BS=0)
- template<class [Field](#) , class [Cut](#) , class [Param](#) >  
[Field::Element](#) & [fdot](#) (const [Field](#) &F, const size\_t N, typename [Field::ConstElement\\_ptr](#) x, const size\_t incx, typename [Field::ConstElement\\_ptr](#) y, const size\_t incy, typename [Field::Element](#) &d, const [ParSeqHelper::Parallel](#)< [Cut](#), [Param](#) > par)
- template<typename [Field](#) , class [Cut](#) , class [Param](#) >  
[Field::Element](#) [fdot](#) (const [Field](#) &F, const size\_t N, typename [Field::ConstElement\\_ptr](#) X, const size\_t incX, typename [Field::ConstElement\\_ptr](#) Y, const size\_t incY, const [ParSeqHelper::Parallel](#)< [Cut](#), [Param](#) > par)

## 13.240 kaapi\_routines.inl File Reference

### Macros

- #define [\\_\\_FFLASFFPACK\\_KAAPI\\_ROUTINES\\_INL](#)

### 13.240.1 Macro Definition Documentation

#### 13.240.1.1 [\\_\\_FFLASFFPACK\\_KAAPI\\_ROUTINES\\_INL](#)

```
#define __FFLASFFPACK_KAAPI_ROUTINES_INL
```

## 13.241 parallel.h File Reference

```
#include "fflas-ffpack/config.h"
#include "fflas-ffpack/paladin/blockcuts.inl"
```

### Macros

- #define [\\_\\_FFLASFFPACK\\_SEQUENTIAL](#)
- #define [index\\_t](#) size\_t
- #define [TASK](#)(M, l) {l;}
- #define [WAIT](#)
- #define [CHECK\\_DEPENDENCIES](#)
- #define [BARRIER](#)
- #define [PAR\\_BLOCK](#)
- #define [SYNCH\\_GROUP](#)(Args...) {{Args};}
- #define [THREAD\\_INDEX](#) 0
- #define [NUM\\_THREADS](#) 1
- #define [SET\\_THREADS](#)(num\_threads) {}
- #define [MAX\\_THREADS](#) 1
- #define [READ](#)(Args...)
- #define [WRITE](#)(Args...)

- `#define READWRITE(Args...)`
- `#define CONSTREFERENCE(...)`
- `#define VALUE(...)`
- `#define BEGIN_PARALLEL_MAIN(Args...) int main(Args) {`
- `#define END_PARALLEL_MAIN(void) return 0; }`
- `#define FORBLOCK1D(iter, m, Helper, Args...)`
- `#define FOR1D(i, m, Helper, Args...)`
- `#define PARFORBLOCK1D(iter, m, Helper, Args...)`
- `#define PARFOR1D(iter, m, Helper, Args...)`
- `#define FORBLOCK2D(iter, m, n, Helper, Args...)`
- `#define FOR2D(i, j, m, n, Helper, Args...)`
- `#define PARFORBLOCK2D(iter, m, n, Helper, Args...) FORBLOCK2D(iter, m, n, Helper, Args)`
- `#define PARFOR2D(i, j, m, n, Helper, Args...) FOR2D(i, j, m, n, Helper, Args)`
- `#define COMMA ,`
- `#define MODE(...) __VA_ARGS__`
- `#define RETURNPARAM(f, P1, Args...) P1=f(Args)`
- `#define NUMARGS(...) PP_NARG(__VA_ARGS__, PP_RSEQ_N())`
- `#define PP_NARG(...) PP_ARG_N(__VA_ARGS__)`
- `#define PP_ARG_N(_1, _2, _3, _4, _5, _6, _7, _8, _9, _10, _11, _12, _13, _14, _15, _16, _17, _18, _19, _20, _21, _22, _23, _24, _25, _26, _27, _28, _29, _30, _31, _32, _33, _34, _35, _36, _37, _38, _39, _40, _41, _42, _43, _44, _45, _46, _47, _48, _49, _50, _51, _52, _53, _54, _55, _56, _57, _58, _59, _60, _61, _62, _63, N, ...) N`
- `#define PP_RSEQ_N()`
- `#define NOSPLIT() FFLAS::ParSeqHelper::Sequential()`
- `#define splitting_0() FFLAS::ParSeqHelper::Parallel<FFLAS::CuttingStrategy::Block, FFLAS::StrategyParameter::Threads>()`
- `#define splitting_1(a) FFLAS::ParSeqHelper::Parallel<FFLAS::CuttingStrategy::Block, FFLAS::StrategyParameter::Threads>(a)`
- `#define splitting_2(a, c) FFLAS::ParSeqHelper::Parallel<FFLAS::CuttingStrategy::Block, c>(a)`
- `#define splitting_3(a, b, c) FFLAS::ParSeqHelper::Parallel<b, c>(a)`
- `#define splitt(_1, _2, _3, NAME, ...) NAME`
- `#define SPLITTER(...) splitt(__VA_ARGS__, splitting_3, splitting_2, splitting_1, splitting_0)(__VA_ARGS__)`

## 13.241.1 Macro Definition Documentation

### 13.241.1.1 \_\_FFLASFFPACK\_SEQUENTIAL

```
#define __FFLASFFPACK_SEQUENTIAL
```

### 13.241.1.2 index\_t

```
#define index_t size_t
```

### 13.241.1.3 TASK

```
#define TASK(
 M,
 I) {I;}
```

### 13.241.1.4 WAIT

```
#define WAIT
```

### 13.241.1.5 CHECK\_DEPENDENCIES

```
#define CHECK_DEPENDENCIES
```

### 13.241.1.6 BARRIER

```
#define BARRIER
```

**13.241.1.7 PAR\_BLOCK**

```
#define PAR_BLOCK
```

**13.241.1.8 SYNCH\_GROUP**

```
#define SYNCH_GROUP(
 Args...) {{Args}};
```

**13.241.1.9 THREAD\_INDEX**

```
#define THREAD_INDEX 0
```

**13.241.1.10 NUM\_THREADS**

```
#define NUM_THREADS 1
```

**13.241.1.11 SET\_THREADS**

```
#define SET_THREADS(
 num_threads) {}
```

**13.241.1.12 MAX\_THREADS**

```
#define MAX_THREADS 1
```

**13.241.1.13 READ**

```
#define READ(
 Args...)
```

**13.241.1.14 WRITE**

```
#define WRITE(
 Args...)
```

**13.241.1.15 READWRITE**

```
#define READWRITE(
 Args...)
```

**13.241.1.16 CONSTREFERENCE**

```
#define CONSTREFERENCE(
 ...)
```

**13.241.1.17 VALUE**

```
#define VALUE(
 ...)
```

**13.241.1.18 BEGIN\_PARALLEL\_MAIN**

```
#define BEGIN_PARALLEL_MAIN(
 Args...) int main(Args) {
```

**13.241.1.19 END\_PARALLEL\_MAIN**

```
#define END_PARALLEL_MAIN(
 void) return 0; }
```



**13.241.1.20 FORBLOCK1D**

```
#define FORBLOCK1D(
 iter,
 m,
 Helper,
 Args...)
```

**Value:**

```
{ FFLAS::ForStrategy1D<std::remove_const<decltype(m)>::type, typename decltype(Helper)::Cut, typename
 decltype(Helper)::Param> iter(m, Helper); \
 for(iter.initialize(); !iter.isTerminated(); ++iter) \
 {Args; } }
```

**13.241.1.21 FOR1D**

```
#define FOR1D(
 i,
 m,
 Helper,
 Args...)
```

**Value:**

```
FORBLOCK1D(_internal_iterator, m, Helper, \
 for(auto i=_internal_iterator.begin(); i!=_internal_iterator.end(); ++i) \
 { Args; })
```

**13.241.1.22 PARFORBLOCK1D**

```
#define PARFORBLOCK1D(
 iter,
 m,
 Helper,
 Args...)
```

**Value:**

```
for(std::remove_const<decltype(m)>::type iter=0; iter<m; ++iter) \
{ Args; }
```

**13.241.1.23 PARFOR1D**

```
#define PARFOR1D(
 iter,
 m,
 Helper,
 Args...)
```

**Value:**

```
for(std::remove_const<decltype(m)>::type iter=0; iter<m; ++iter) \
{ Args; }
```

**13.241.1.24 FORBLOCK2D**

```
#define FORBLOCK2D(
 iter,
 m,
 n,
 Helper,
 Args...)
```

**Value:**

```
{ FFLAS::ForStrategy2D<std::remove_const<decltype(m)>::type, typename decltype(Helper)::Cut, typename
 decltype(Helper)::Param> iter(m,n,Helper); \
 for(iter.initialize(); !iter.isTerminated(); ++iter) \
 { Args; } }
```

**13.241.1.25 FOR2D**

```
#define FOR2D(
 i,
```

```

 j,
 m,
 n,
 Helper,
 Args...)

```

**Value:**

```

FORBLOCK2D(_internal_iterator, m, n, Helper,
 for(auto i=_internal_iterator.ibegin(); i!=_internal_iterator.iend(); ++i) \
 for(auto j=_internal_iterator.jbegin(); j!=_internal_iterator.jend(); ++j) \
 { Args; })

```

**13.241.1.26 PARFORBLOCK2D**

```

#define PARFORBLOCK2D(
 iter,
 m,
 n,
 Helper,
 Args...) FORBLOCK2D(iter, m, n, Helper, Args)

```

**13.241.1.27 PARFOR2D**

```

#define PARFOR2D(
 i,
 j,
 m,
 n,
 Helper,
 Args...) FOR2D(i, j, m, n, Helper, Args)

```

**13.241.1.28 COMMA**

```

#define COMMA ,

```

**13.241.1.29 MODE**

```

#define MODE(
 ...) __VA_ARGS__

```

**13.241.1.30 RETURNPARAM**

```

#define RETURNPARAM(
 f,
 Pl,
 Args...) Pl=f(Args)

```

**13.241.1.31 NUMARGS**

```

#define NUMARGS(
 ...) PP_NARG__(__VA_ARGS__, PP_RSEQ_N())

```

**13.241.1.32 PP\_NARG\_**

```

#define PP_NARG_(
 ...) PP_ARG_N(__VA_ARGS__)

```

**13.241.1.33 PP\_ARG\_N**

```

#define PP_ARG_N(
 _1,
 _2,

```

\_3,  
\_4,  
\_5,  
\_6,  
\_7,  
\_8,  
\_9,  
\_10,  
\_11,  
\_12,  
\_13,  
\_14,  
\_15,  
\_16,  
\_17,  
\_18,  
\_19,  
\_20,  
\_21,  
\_22,  
\_23,  
\_24,  
\_25,  
\_26,  
\_27,  
\_28,  
\_29,  
\_30,  
\_31,  
\_32,  
\_33,  
\_34,  
\_35,  
\_36,  
\_37,  
\_38,  
\_39,  
\_40,  
\_41,  
\_42,  
\_43,  
\_44,  
\_45,  
\_46,  
\_47,  
\_48,  
\_49,  
\_50,  
\_51,  
\_52,  
\_53,  
\_54,  
\_55,  
\_56,  
\_57,  
\_58,  
\_59,  
\_60,

```

 _61,
 _62,
 _63,
 N,
 ...) N

```

### 13.241.1.34 PP\_RSEQ\_N

```
#define PP_RSEQ_N()
```

**Value:**

```

63, 62, 61, 60, \
59, 58, 57, 56, 55, 54, 53, 52, 51, 50, \
49, 48, 47, 46, 45, 44, 43, 42, 41, 40, \
39, 38, 37, 36, 35, 34, 33, 32, 31, 30, \
29, 28, 27, 26, 25, 24, 23, 22, 21, 20, \
19, 18, 17, 16, 15, 14, 13, 12, 11, 10, \
9, 8, 7, 6, 5, 4, 3, 2, 1, 0

```

### 13.241.1.35 NOSPLIT

```
#define NOSPLIT() FFLAS::ParSeqHelper::Sequential()
```

### 13.241.1.36 splitting\_0

```
#define splitting_0() FFLAS::ParSeqHelper::Parallel<FFLAS::CuttingStrategy::Block, FFLAS::StrategyParameter::...
```

### 13.241.1.37 splitting\_1

```
#define splitting_1(
 a) FFLAS::ParSeqHelper::Parallel<FFLAS::CuttingStrategy::Block, FFLAS::StrategyParameter::Thread...
```

### 13.241.1.38 splitting\_2

```
#define splitting_2(
 a,
 c) FFLAS::ParSeqHelper::Parallel<FFLAS::CuttingStrategy::Block, c>(a)
```

### 13.241.1.39 splitting\_3

```
#define splitting_3(
 a,
 b,
 c) FFLAS::ParSeqHelper::Parallel<b, c>(a)
```

### 13.241.1.40 splitt

```
#define splitt(
 _1,
 _2,
 _3,
 NAME,
 ...) NAME

```

### 13.241.1.41 SPLITTER

```
#define SPLITTER(
 ...) splitt(__VA_ARGS__, splitting_3, splitting_2, splitting_1, splitting_0) (↔
__VA_ARGS__)
```

## 13.242 pfgemm\_variants.inl File Reference

### Namespaces

- namespace [FFLAS](#)

### Functions

- `template<class Field , class AlgoT , class FieldTrait >`  
`Field::Element * pfgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb,`  
`const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, const typename`  
`Field::ConstElement_ptr A, const size_t lda, const typename Field::ConstElement_ptr B, const size_t ldb,`  
`const typename Field::Element beta, typename Field::Element *C, const size_t ldc, MMHelper< Field, Al-`  
`goT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Block, StrategyParameter::Threads > > &H)`
- `template<class Field , class AlgoT , class FieldTrait >`  
`Field::Element * pfgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb,`  
`const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, const typename`  
`Field::ConstElement_ptr AA, const size_t lda, const typename Field::ConstElement_ptr BB, const size_t`  
`ldb, const typename Field::Element beta, typename Field::Element *C, const size_t ldc, MMHelper< Field,`  
`AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive, StrategyParameter::ThreeDAdaptive`  
`> > &H)`
- `template<class Field , class AlgoT , class FieldTrait >`  
`Field::Element * pfgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb,`  
`const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, const typename`  
`Field::ConstElement_ptr AA, const size_t lda, const typename Field::ConstElement_ptr BB, const size_t`  
`ldb, const typename Field::Element beta, typename Field::Element *C, const size_t ldc, MMHelper< Field,`  
`AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive, StrategyParameter::TwoDAdaptive >`  
`> &H)`
- `template<class Field , class AlgoT , class FieldTrait >`  
`Field::Element * pfgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb,`  
`const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, const typename`  
`Field::ConstElement_ptr AA, const size_t lda, const typename Field::ConstElement_ptr BB, const size_t`  
`ldb, const typename Field::Element beta, typename Field::Element *C, const size_t ldc, MMHelper< Field,`  
`AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive, StrategyParameter::TwoD > > &H)`
- `template<class Field , class AlgoT , class FieldTrait >`  
`Field::Element_ptr pfgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE`  
`tb, const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, const typename`  
`Field::ConstElement_ptr A, const size_t lda, const typename Field::ConstElement_ptr B, const size_t ldb,`  
`const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field,`  
`AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive, StrategyParameter::ThreeD > > &H)`
- `template<class Field , class AlgoT , class FieldTrait >`  
`Field::Element * pfgemm (const Field &F, const FFLAS_TRANSPOSE ta, const FFLAS_TRANSPOSE tb,`  
`const size_t m, const size_t n, const size_t k, const typename Field::Element alpha, const typename`  
`Field::ConstElement_ptr A, const size_t lda, const typename Field::ConstElement_ptr B, const size_t ldb,`  
`const typename Field::Element beta, typename Field::Element_ptr C, const size_t ldc, MMHelper< Field, Al-`  
`goT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Recursive, StrategyParameter::ThreeDInPlace >`  
`> &H)`

## 13.243 pfgemv.inl File Reference

### Namespaces

- namespace [FFLAS](#)

### Functions

- `template<class Field , class AlgoT , class FieldTrait >`  
`Field::Element_ptr fgemv (const Field &F, const FFLAS_TRANSPOSE ta, const size_t m, const size_t`  
`n, const typename Field::Element alpha, const typename Field::ConstElement_ptr A, const size_t lda,`

```
const typename Field::ConstElement_ptr X, const size_t incX, const typename Field::Element beta, type-
name Field::Element_ptr Y, const size_t incY, MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel<
CuttingStrategy::Recursive, StrategyParameter::Threads > > &H)
```

- template<class Field, class AlgoT, class FieldTrait, class Cut >  
Field::Element\_ptr fgemv (const Field &F, const FFLAS\_TRANSPOSE ta, const size\_t m, const size\_t n, const typename Field::Element alpha, const typename Field::ConstElement\_ptr A, const size\_t lda, const typename Field::ConstElement\_ptr X, const size\_t incX, const typename Field::Element beta, type-  
name Field::Element\_ptr Y, const size\_t incY, MMHelper< Field, AlgoT, FieldTrait, ParSeqHelper::Parallel< CuttingStrategy::Row, Cut > > &H)

## 13.244 align-allocator.h File Reference

```
#include "fflas-ffpack/config.h"
```

## 13.245 args-parser.h File Reference

```
#include <fflas-ffpack/fflas-ffpack-config.h>
#include <givaro/givinteger.h>
#include <givaro/givprint.h>
#include <iostream>
#include <fstream>
#include <vector>
#include <string>
#include <cstring>
#include <list>
#include <stdlib.h>
```

### Data Structures

- struct [Argument](#)

### Namespaces

- namespace [FFLAS](#)

### Macros

- #define [TYPE\\_BOOL](#) [TYPE\\_NONE](#)
- #define [END\\_OF\\_ARGUMENTS](#) { '\0', "\0", "\0", [TYPE\\_NONE](#), NULL }
- #define [type\\_integer](#) long int

### Enumerations

- enum [ArgumentType](#) {  
[TYPE\\_NONE](#), [TYPE\\_INT](#), [TYPE\\_UINT64](#), [TYPE\\_LONGLONG](#),  
[TYPE\\_INTEGER](#), [TYPE\\_DOUBLE](#), [TYPE\\_INTLIST](#), [TYPE\\_STR](#) }

### Functions

- void [parseArguments](#) (int argc, char \*\*argv, [Argument](#) \*args, bool printDefaults=true)
- void [printHelpMessage](#) (const char \*program, [Argument](#) \*args, bool printDefaults=false)
- [Argument](#) \* [findArgument](#) ([Argument](#) \*args, char c)
- int [getListArgs](#) (std::list< int > &outlist, std::string &instring)  
*transforms a string list of ints to a list of int string "12,13,15" is turned into list of ints {12,13,15}*
- char \* [getArgumentValue](#) (int argc, char \*\*argv, int i)

*Get the value of an argument and avoid core dump when no value was given after an argument.*

- `std::ostream & writeCommandString (std::ostream &os, Argument *args, const char *programName=nullptr)`  
*writes the values of all arguments, preceded by the programName*

## 13.245.1 Macro Definition Documentation

### 13.245.1.1 TYPE\_BOOL

```
#define TYPE_BOOL TYPE_NONE
```

### 13.245.1.2 END\_OF\_ARGUMENTS

```
#define END_OF_ARGUMENTS { '\0', "", "\0", TYPE_NONE, NULL }
```

### 13.245.1.3 type\_integer

```
#define type_integer long int
```

## 13.245.2 Enumeration Type Documentation

### 13.245.2.1 ArgumentType

```
enum ArgumentType
```

Enumerator

|               |  |
|---------------|--|
| TYPE_NONE     |  |
| TYPE_INT      |  |
| TYPE_UINT64   |  |
| TYPE_LONGLONG |  |
| TYPE_INTEGER  |  |
| TYPE_DOUBLE   |  |
| TYPE_INTLIST  |  |
| TYPE_STR      |  |

## 13.245.3 Function Documentation

### 13.245.3.1 printHelpMessage()

```
void printHelpMessage (
 const char * program,
 Argument * args,
 bool printDefaults = false)
```

### 13.245.3.2 findArgument()

```
Argument * findArgument (
 Argument * args,
 char c)
```

### 13.245.3.3 getListArgs()

```
int getListArgs (
 std::list< int > & outlist,
 std::string & instring)
```

transforms a string list of ints to a list of int string "12,13,15" is turned into list of ints {12,13,15}

## Parameters

|                 |                      |
|-----------------|----------------------|
| <i>outlist</i>  | list once converted  |
| <i>instring</i> | list to be converted |

## Returns

status message.

## 13.246 bit\_manipulation.h File Reference

```
#include <givaro/udl.h>
#include "fflas-ffpack/fflas-ffpack-config.h"
```

## Macros

- `#define __has_builtin(x) 0`

## Functions

- `int32_t clz (uint64_t val)`
- `int32_t clz (uint32_t val)`
- `int32_t ctz (uint32_t val)`
- `int32_t ctz (uint64_t val)`

### 13.246.1 Macro Definition Documentation

#### 13.246.1.1 \_\_has\_builtin

```
#define __has_builtin(
 x) 0
```

### 13.246.2 Function Documentation

#### 13.246.2.1 clz() [1/2]

```
int32_t clz (
 uint64_t val) [inline]
```

#### 13.246.2.2 clz() [2/2]

```
int32_t clz (
 uint32_t val) [inline]
```

#### 13.246.2.3 ctz() [1/2]

```
int32_t ctz (
 uint32_t val) [inline]
```

#### 13.246.2.4 ctz() [2/2]

```
int32_t ctz (
 uint64_t val) [inline]
```



## 13.247 cast.h File Reference

### Namespaces

- namespace [FFPACK](#)

*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

### Functions

- template<class T, class CT = const T>  
T [fflas\\_const\\_cast](#) (CT x)

## 13.248 debug.h File Reference

Various utilities for debugging.

```
#include <fflas-ffpack/fflas-ffpack-config.h>
#include <iostream>
#include <sstream>
#include <cmath>
#include <stdexcept>
```

### Data Structures

- class [Failure](#)

*A precondition failed.*

### Namespaces

- namespace [FFPACK](#)

*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

### Macros

- #define [FFLASFFPACK\\_check](#)(check)
- #define [FFLASFFPACK\\_abort](#)(msg)

### Functions

- [Failure](#) & [failure](#) ()
- template<class T >  
bool [isOdd](#) (const T &a)
- bool [isOdd](#) (const float &a)
- bool [isOdd](#) (const double &a)

### 13.248.1 Detailed Description

Various utilities for debugging.

**Todo** we should put vector printing elsewhere.

### 13.248.2 Macro Definition Documentation

#### 13.248.2.1 FFLASFFPACK\_check

```
#define FFLASFFPACK_check(
 check)
```

**Value:**

```
if (!(check)) {\
```

```

FFPACK::failure() (__func__, __FILE__, __LINE__, #check); \
throw std::runtime_error(#check); \
}

```

### 13.248.2.2 FFLASFFPACK\_abort

```

#define FFLASFFPACK_abort(
 msg)

```

**Value:**

```

{ \
 FFPACK::failure() (__func__, __FILE__, __LINE__, msg); \
 throw std::runtime_error(msg); \
}

```

## 13.249 fflas\_intrinsic.h File Reference

## 13.250 fflas\_io.h File Reference

```

#include <cstring>
#include <stdio.h>
#include <stdlib.h>
#include <fstream>
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas_memory.h"

```

### Namespaces

- namespace [FFLAS](#)

### Enumerations

- enum [FFLAS\\_FORMAT](#) {  
[FflasAuto](#) = 0 , [FflasDense](#) = 1 , [FflasSMS](#) = 2 , [FflasBinary](#) = 3 ,  
[FflasMath](#) = 4 , [FflasMaple](#) = 5 , [FflasSageMath](#) = 6 }

### Functions

- template<class [Field](#) >  
std::ostream & [WriteMatrix](#) (std::ostream &c, const [Field](#) &F, size\_t m, size\_t n, typename [Field::ConstElement\\_ptr](#) A, size\_t lda, [FFLAS\\_FORMAT](#) format, bool column\_major)  
*WriteMatrix: write a matrix to an output stream.*
- void [preamble](#) (std::ifstream &ifs, [FFLAS\\_FORMAT](#) &format)
- template<class [Field](#) >  
[Field::Element\\_ptr](#) [ReadMatrix](#) (std::ifstream &ifs, [Field](#) &F, size\_t &m, size\_t &n, typename [Field::Element\\_ptr](#) &A, [FFLAS\\_FORMAT](#) format=[FflasAuto](#))  
*ReadMatrix: read a matrix from an input stream.*
- template<class [Field](#) >  
[Field::Element\\_ptr](#) [ReadMatrix](#) (const std::string &matrix\_file, [Field](#) &F, size\_t &m, size\_t &n, typename [Field::Element\\_ptr](#) &A, [FFLAS\\_FORMAT](#) format=[FflasAuto](#))  
*ReadMatrix: read a matrix from a file.*
- template<class [Field](#) >  
void [WriteMatrix](#) (std::string &matrix\_file, const [Field](#) &F, int m, int n, typename [Field::ConstElement\\_ptr](#) A, size\_t lda, [FFLAS\\_FORMAT](#) format=[FflasDense](#), bool column\_major=false)  
*WriteMatrix: write a matrix to a file.*
- std::ostream & [WritePermutation](#) (std::ostream &c, const size\_t \*P, size\_t N)  
*WritePermutation: write a permutation matrix to an output stream.*

## 13.251 fflas\_memory.h File Reference

```
#include "fflas-ffpack/utils/align-allocator.h"
#include <givaro/givinteger.h>
```

### Namespaces

- namespace [FFLAS](#)

### Functions

- template<class Element >  
bool [alignable](#) ()
- template<> bool [alignable](#)< Givaro::Integer \* > ()
- template<class Field >  
[Field::Element\\_ptr](#) [fflas\\_new](#) (const [Field](#) &F, const size\_t m, const Alignment align=Alignment::DEFAULT)
- template<class Field >  
[Field::Element\\_ptr](#) [fflas\\_new](#) (const [Field](#) &F, const size\_t m, const size\_t n, const Alignment align=Alignment::DEFAULT)
- template<class Element >  
Element \* [fflas\\_new](#) (const size\_t m, const Alignment align=Alignment::DEFAULT)
- template<class Element\_ptr >  
void [fflas\\_delete](#) (Element\_ptr A)
- template<class Ptr , class ... Args>  
void [fflas\\_delete](#) (Ptr p, Args ... args)
- void [prefetch](#) (const int64\_t \*)
- void [getTLBSize](#) (int &tlb)
- void [queryCacheSizes](#) (int &l1, int &l2, int &l3)
- int [queryL1CacheSize](#) ()
- int [queryTopLevelCacheSize](#) ()

## 13.252 fflas\_randommatrix.h File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/utils/debug.h"
#include "fflas-ffpack/fflas/fflas.h"
#include <givaro/givinteger.h>
#include <givaro/givintprime.h>
#include <givaro/givranditer.h>
#include "fflas-ffpack/ffpack/ffpack.h"
```

### Namespaces

- namespace [FFPACK](#)  
*Finite Field **PACK** Set of elimination based routines for dense linear algebra.*

### Functions

- template<class Field , class RandIter >  
[Field::Element\\_ptr](#) [NonZeroRandomMatrix](#) (const [Field](#) &F, size\_t m, size\_t n, typename [Field::Element\\_ptr](#) A, size\_t lda, RandIter &G)  
*Random non-zero Matrix.*
- template<class Field , class RandIter >  
[Field::Element\\_ptr](#) [NonZeroRandomMatrix](#) (const [Field](#) &F, size\_t m, size\_t n, typename [Field::Element\\_ptr](#) A, size\_t lda)

*Random non-zero Matrix.*

- template<class [Field](#) , class [Randlter](#) >  
[Field::Element\\_ptr](#) [RandomMatrix](#) (const [Field](#) &F, size\_t m, size\_t n, typename [Field::Element\\_ptr](#) A, size\_t lda, [Randlter](#) &G)

*Random Matrix.*

- template<class [Field](#) >  
[Field::Element\\_ptr](#) [RandomMatrix](#) (const [Field](#) &F, size\_t m, size\_t n, typename [Field::Element\\_ptr](#) A, size\_t lda)

*Random Matrix.*

- template<class [Field](#) , class [Randlter](#) >  
[Field::Element\\_ptr](#) [RandomTriangularMatrix](#) (const [Field](#) &F, size\_t m, size\_t n, const [FFLAS::FFLAS\\_UPLO](#) UpLo, const [FFLAS::FFLAS\\_DIAG](#) Diag, bool nonsingular, typename [Field::Element\\_ptr](#) A, size\_t lda, [Randlter](#) &G)

*Random Triangular Matrix.*

- template<class [Field](#) >  
[Field::Element\\_ptr](#) [RandomTriangularMatrix](#) (const [Field](#) &F, size\_t m, size\_t n, const [FFLAS::FFLAS\\_UPLO](#) UpLo, const [FFLAS::FFLAS\\_DIAG](#) Diag, bool nonsingular, typename [Field::Element\\_ptr](#) A, size\_t lda)

*Random Triangular Matrix.*

- size\_t [RandInt](#) (size\_t a, size\_t b)
- template<class [Field](#) , class [Randlter](#) >  
[Field::Element\\_ptr](#) [RandomSymmetricMatrix](#) (const [Field](#) &F, size\_t n, bool nonsingular, typename [Field::Element\\_ptr](#) A, size\_t lda, [Randlter](#) &G)

*Random Symmetric Matrix.*

- template<class [Field](#) , class [Randlter](#) >  
[Field::Element\\_ptr](#) [RandomMatrixWithRank](#) (const [Field](#) &F, size\_t m, size\_t n, size\_t r, typename [Field::Element\\_ptr](#) A, size\_t lda, [Randlter](#) &G)

*Random Matrix with prescribed rank.*

- template<class [Field](#) >  
[Field::Element\\_ptr](#) [RandomMatrixWithRank](#) (const [Field](#) &F, size\_t m, size\_t n, size\_t r, typename [Field::Element\\_ptr](#) A, size\_t lda)

*Random Matrix with prescribed rank.*

- size\_t \* [RandomIndexSubset](#) (size\_t N, size\_t R, size\_t \*P)  
*Pick uniformly at random a sequence of  $R$  distinct elements from the set  $\{0, \dots, N - 1\}$  using Knuth's shuffle.*
- size\_t \* [RandomPermutation](#) (size\_t N, size\_t \*P)  
*Pick uniformly at random a permutation of size  $N$  stored in LAPACK format using Knuth's shuffle.*
- void [RandomRankProfileMatrix](#) (size\_t M, size\_t N, size\_t R, size\_t \*rows, size\_t \*cols)  
*Pick uniformly at random an  $R$ -subpermutation of dimension  $M \times N$  : a matrix with only  $R$  non-zeros equal to one, in a random rook placement.*

- void [swapval](#) (size\_t k, size\_t N, size\_t \*P, size\_t val)
- void [RandomSymmetricRankProfileMatrix](#) (size\_t N, size\_t R, size\_t \*rows, size\_t \*cols)  
*Pick uniformly at random a symmetric  $R$ -subpermutation of dimension  $N \times N$  : a symmetric matrix with only  $R$  non-zeros, all equal to one, in a random rook placement.*

- void [RandomLTQSRankProfileMatrix](#) (size\_t n, size\_t r, size\_t t, size\_t \*rows, size\_t \*cols)
- template<class [Field](#) , class [Randlter](#) >  
[Field::Element\\_ptr](#) [RandomMatrixWithRankandRPM](#) (const [Field](#) &F, size\_t M, size\_t N, size\_t R, typename [Field::Element\\_ptr](#) A, size\_t lda, const size\_t \*RRP, const size\_t \*CRP, [Randlter](#) &G)

*Random Matrix with prescribed rank and rank profile matrix Creates an  $m \times n$  matrix with random entries and rank  $r$ .*

- template<class [Field](#) >  
[Field::Element\\_ptr](#) [RandomMatrixWithRankandRPM](#) (const [Field](#) &F, size\_t M, size\_t N, size\_t R, typename [Field::Element\\_ptr](#) A, size\_t lda, const size\_t \*RRP, const size\_t \*CRP)

*Random Matrix with prescribed rank and rank profile matrix Creates an  $m \times n$  matrix with random entries and rank  $r$ .*

- template<class [Field](#) , class [Randlter](#) >  
[Field::Element\\_ptr](#) [RandomSymmetricMatrixWithRankandRPM](#) (const [Field](#) &F, size\_t N, size\_t R, typename [Field::Element\\_ptr](#) A, size\_t lda, const size\_t \*RRP, const size\_t \*CRP, [Randlter](#) &G)

- Random Symmetric Matrix with prescribed rank and rank profile matrix* Creates an  $n \times n$  symmetric matrix with random entries and rank  $r$ .
- `template<class Field >`  
`Field::Element_ptr RandomSymmetricMatrixWithRankandRPM` (const `Field` &F, size\_t M, size\_t N, size\_t R, typename `Field::Element_ptr` A, size\_t lda, const size\_t \*RRP, const size\_t \*CRP)  
*Random Symmetric Matrix with prescribed rank and rank profile matrix* Creates an  $n \times n$  symmetric matrix with random entries and rank  $r$ .
  - `template<class Field , class RandIter >`  
`Field::Element_ptr RandomMatrixWithRankandRandomRPM` (const `Field` &F, size\_t M, size\_t N, size\_t R, typename `Field::Element_ptr` A, size\_t lda, RandIter &G)  
*Random Matrix with prescribed rank, with random rank profile matrix* Creates an  $m \times n$  matrix with random entries, rank  $r$  and with a rank profile matrix chosen uniformly at random.
  - `template<class Field >`  
`Field::Element_ptr RandomMatrixWithRankandRandomRPM` (const `Field` &F, size\_t M, size\_t N, size\_t R, typename `Field::Element_ptr` A, size\_t lda)  
*Random Matrix with prescribed rank, with random rank profile matrix* Creates an  $m \times n$  matrix with random entries, rank  $r$  and with a rank profile matrix chosen uniformly at random.
  - `template<class Field , class RandIter >`  
`Field::Element_ptr RandomSymmetricMatrixWithRankandRandomRPM` (const `Field` &F, size\_t N, size\_t R, typename `Field::Element_ptr` A, size\_t lda, RandIter &G)  
*Random Symmetric Matrix with prescribed rank, with random rank profile matrix* Creates an  $n \times n$  matrix with random entries, rank  $r$  and with a rank profile matrix chosen uniformly at random.
  - `template<class Field >`  
`Field::Element_ptr RandomSymmetricMatrixWithRankandRandomRPM` (const `Field` &F, size\_t N, size\_t R, typename `Field::Element_ptr` A, size\_t lda)  
*Random Symmetric Matrix with prescribed rank, with random rank profile matrix* Creates an  $n \times n$  matrix with random entries, rank  $r$  and with a rank profile matrix chosen uniformly at random.
  - `template<class Field >`  
`Field::Element_ptr RandomMatrixWithDet` (const `Field` &F, size\_t n, const typename `Field::Element` d, typename `Field::Element_ptr` A, size\_t lda)  
*Random Matrix with prescribed det.*
  - `template<class Field , class RandIter >`  
`Field::Element_ptr RandomMatrixWithDet` (const `Field` &F, size\_t n, const typename `Field::Element` d, typename `Field::Element_ptr` A, size\_t lda, RandIter &G)  
*Random Matrix with prescribed det.*
  - `template<class Field , class RandIter >`  
`Field::Element_ptr RandomLTQSMMatrixWithRankandQSorder` (`Field` &F, size\_t n, size\_t r, size\_t t, typename `Field::Element_ptr` A, size\_t lda, RandIter &G)

## 13.253 flimits.h File Reference

```
#include <climits>
#include <limits>
#include <type_traits>
#include <givaro/givinteger.h>
```

### Data Structures

- struct `limits< unsigned char >`
- struct `limits< signed char >`
- struct `limits< char >`
- struct `limits< unsigned short int >`
- struct `limits< short int >`
- struct `limits< unsigned int >`
- struct `limits< int >`

- struct `limits< unsigned long >`
- struct `limits< long >`
- struct `limits< unsigned long long >`
- struct `limits< long long >`
- struct `limits< float >`
- struct `limits< double >`
- struct `limits< Givaro::Integer >`
- struct `limits< Reclnt::ruint< K > >`
- struct `limits< Reclnt::rint< K > >`

## Functions

- template<class T , class E >  
std::enable\_if< std::is\_signed< T >::value==std::is\_signed< E >::value, bool >::type `in_range` (E e)
- template<class T , class E >  
std::enable\_if<(std::is\_signed< T >::value)&&!(std::is\_signed< E >::value), bool >::type `in_range` (E e)
- template<class T , class E >  
std::enable\_if<!(std::is\_signed< T >::value)&&(std::is\_signed< E >::value), bool >::type `in_range` (E e)

## 13.253.1 Function Documentation

### 13.253.1.1 `in_range()` [1/3]

```
template<class T , class E >
std::enable_if< std::is_signed< T >::value==std::is_signed< E >::value, bool >::type in_↵
range (
 E e)
```

### 13.253.1.2 `in_range()` [2/3]

```
template<class T , class E >
std::enable_if<(std::is_signed< T >::value)&&!(std::is_signed< E >::value), bool >::type
in_range (
 E e)
```

### 13.253.1.3 `in_range()` [3/3]

```
template<class T , class E >
std::enable_if<!(std::is_signed< T >::value)&&(std::is_signed< E >::value), bool >::type
in_range (
 E e)
```

## 13.254 Matio.h File Reference

```
#include <cstring>
#include <stdio.h>
#include <stdlib.h>
#include "fflas_memory.h"
```

## Functions

- template<class `Field` >  
`Field::Element_ptr read_field` (const `Field` &F, const char \*mat\_file, size\_t \*tni, size\_t \*tnj)
- template<class `Field` >  
std::ostream & `write_field` (const `Field` &F, std::ostream &c, typename `Field::ConstElement_ptr` E, int n, int m, int id, bool mapleFormat=false, bool column\_major=false)

## 13.254.1 Function Documentation

### 13.254.1.1 read\_field()

```
template<class Field >
Field::Element_ptr read_field (
 const Field & F,
 const char * mat_file,
 size_t * tni,
 size_t * tnj)
```

### 13.254.1.2 write\_field()

```
template<class Field >
std::ostream & write_field (
 const Field & F,
 std::ostream & c,
 typename Field::ConstElement_ptr E,
 int n,
 int m,
 int id,
 bool mapleFormat = false,
 bool column_major = false)
```

## 13.255 test-utils.h File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/utils/debug.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include <givaro/givinteger.h>
#include <givaro/givintprime.h>
#include <givaro/givranditer.h>
#include <givaro/givtimer.h>
#include <random>
#include <functional>
```

### Namespaces

- namespace [FFLAS](#)
- namespace [FFPACK](#)

*Finite Field PACK Set of elimination based routines for dense linear algebra.*

### Functions

- uint64\_t [getSeed](#) ()
- template<typename Field >  
Field \* [chooseField](#) (Givaro::Integer q, uint64\_t b, uint64\_t seed)
- template<> Givaro::ZRing< int32\_t > \* [chooseField](#)< Givaro::ZRing< int32\_t > > (Givaro::Integer q, uint64\_t b, uint64\_t seed)
- template<> Givaro::ZRing< int64\_t > \* [chooseField](#)< Givaro::ZRing< int64\_t > > (Givaro::Integer q, uint64\_t b, uint64\_t seed)
- template<> Givaro::ZRing< float > \* [chooseField](#)< Givaro::ZRing< float > > (Givaro::Integer q, uint64\_t b, uint64\_t seed)
- template<> Givaro::ZRing< double > \* [chooseField](#)< Givaro::ZRing< double > > (Givaro::Integer q, uint64\_t b, uint64\_t seed)

## 13.256 timer.h File Reference

```
#include <time.h>
#include <givaro/givtimer.h>
```

### Namespaces

- namespace [FFLAS](#)

### Typedefs

- typedef Givaro::Timer [Timer](#)
- typedef Givaro::BaseTimer [BaseTimer](#)
- typedef Givaro::UserTimer [UserTimer](#)
- typedef Givaro::SysTimer [SysTimer](#)

## 13.257 cblas.C File Reference

```
#include "fflas-ffpack/config-blas.h"
```

### Macros

- #define [\\_\\_FFLASFFPACK\\_CONFIGURATION](#)
- #define [\\_\\_FFLASFFPACK\\_HAVE\\_CBLAS](#) 1

### Functions

- int [main](#) ()

### 13.257.1 Macro Definition Documentation

#### 13.257.1.1 [\\_\\_FFLASFFPACK\\_CONFIGURATION](#)

```
#define __FFLASFFPACK_CONFIGURATION
```

#### 13.257.1.2 [\\_\\_FFLASFFPACK\\_HAVE\\_CBLAS](#)

```
#define __FFLASFFPACK_HAVE_CBLAS 1
```

### 13.257.2 Function Documentation

#### 13.257.2.1 [main\(\)](#)

```
int main (
 void)
```

## 13.258 clapack.C File Reference

```
#include "fflas-ffpack/config-blas.h"
```

### Macros

- #define [\\_\\_FFLASFFPACK\\_CONFIGURATION](#)
- #define [\\_\\_FFLASFFPACK\\_HAVE\\_LAPACK](#) 1
- #define [\\_\\_FFLASFFPACK\\_HAVE\\_CLAPACK](#) 1



**Functions**

- int [main](#) ()

**13.258.1 Macro Definition Documentation****13.258.1.1 \_\_FFLASFFPACK\_CONFIGURATION**

```
#define __FFLASFFPACK_CONFIGURATION
```

**13.258.1.2 \_\_FFLASFFPACK\_HAVE\_LAPACK**

```
#define __FFLASFFPACK_HAVE_LAPACK 1
```

**13.258.1.3 \_\_FFLASFFPACK\_HAVE\_CLAPACK**

```
#define __FFLASFFPACK_HAVE_CLAPACK 1
```

**13.258.2 Function Documentation****13.258.2.1 main()**

```
int main (
 void)
```

**13.259 cuda.C File Reference**

```
#include <stdio.h>
#include <cuda_runtime.h>
#include <cusparse.h>
```

**Functions**

- int [main](#) ()

**13.259.1 Function Documentation****13.259.1.1 main()**

```
int main (
 void)
```

**13.260 fblas.C File Reference**

```
#include "fflas-ffpack/config-blas.h"
```

**Macros**

- #define [\\_\\_FFLASFFPACK\\_CONFIGURATION](#)

**Functions**

- void [dgemm\\_](#) (const char \*, const char \*, const int \*, const int \*, const int \*, const double \*, const double \*, const int \*, const double \*, const int \*, const double \*, double \*, const int \*)
- int [main](#) ()

### 13.260.1 Macro Definition Documentation

#### 13.260.1.1 \_\_FFLASFFPACK\_CONFIGURATION

```
#define __FFLASFFPACK_CONFIGURATION
```

### 13.260.2 Function Documentation

#### 13.260.2.1 dgemm\_()

```
void dgemm_ (
 const char * ,
 const char * ,
 const int * ,
 const int * ,
 const int * ,
 const double * ,
 const double * ,
 const int * ,
 const double * ,
 const int * ,
 const double * ,
 double * ,
 const int *)
```

#### 13.260.2.2 main()

```
int main (
 void)
```

## 13.261 lapack.C File Reference

```
#include "fflas-ffpack/config-blas.h"
```

### Macros

- [#define \\_\\_FFLASFFPACK\\_CONFIGURATION](#)
- [#define \\_\\_FFLASFFPACK\\_HAVE\\_LAPACK 1](#)

### Functions

- [int main\(\)](#)

### 13.261.1 Macro Definition Documentation

#### 13.261.1.1 \_\_FFLASFFPACK\_CONFIGURATION

```
#define __FFLASFFPACK_CONFIGURATION
```

#### 13.261.1.2 \_\_FFLASFFPACK\_HAVE\_LAPACK

```
#define __FFLASFFPACK_HAVE_LAPACK 1
```

### 13.261.2 Function Documentation

#### 13.261.2.1 main()

```
int main (
 void)
```

## 13.262 regression-check.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack.h"
```

### Functions

- bool [check1](#) ()
- bool [check2](#) ()
- bool [check3](#) ()
- bool [check4](#) ()
- bool [checkZeroDimCharpoly](#) ()
- bool [checkZeroDimMinPoly](#) ()
- bool [gf2ModularBalanced](#) ()
- int [main](#) ()

### 13.262.1 Function Documentation

#### 13.262.1.1 [check1\(\)](#)

```
bool check1 ()
```

#### 13.262.1.2 [check2\(\)](#)

```
bool check2 ()
```

#### 13.262.1.3 [check3\(\)](#)

```
bool check3 ()
```

#### 13.262.1.4 [check4\(\)](#)

```
bool check4 ()
```

#### 13.262.1.5 [checkZeroDimCharpoly\(\)](#)

```
bool checkZeroDimCharpoly ()
```

#### 13.262.1.6 [checkZeroDimMinPoly\(\)](#)

```
bool checkZeroDimMinPoly ()
```

#### 13.262.1.7 [gf2ModularBalanced\(\)](#)

```
bool gf2ModularBalanced ()
```

#### 13.262.1.8 [main\(\)](#)

```
int main (
 void)
```

## 13.263 test-charpoly-check.C File Reference

```
#include <iostream>
#include <stdlib.h>
#include <time.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/fflas_io.h"
```

### Macros

- `#define` [ENABLE\\_CHECKER\\_charpoly](#) 1
- `#define` [TIME\\_CHECKER\\_CHARPOLY](#) 1

### Functions

- `template<class Field, class Polynomial >`  
`void printPolynomial (const Field &F, Polynomial &v)`
- `int main (int argc, char **argv)`

### 13.263.1 Macro Definition Documentation

#### 13.263.1.1 [ENABLE\\_CHECKER\\_charpoly](#)

```
#define ENABLE_CHECKER_charpoly 1
```

#### 13.263.1.2 [TIME\\_CHECKER\\_CHARPOLY](#)

```
#define TIME_CHECKER_CHARPOLY 1
```

### 13.263.2 Function Documentation

#### 13.263.2.1 [printPolynomial\(\)](#)

```
template<class Field, class Polynomial >
void printPolynomial (
 const Field & F,
 Polynomial & v)
```

#### 13.263.2.2 [main\(\)](#)

```
int main (
 int argc,
 char ** argv)
```

## 13.264 test-charpoly.C File Reference

```
#include <iostream>
#include <iomanip>
#include "givaro/modular.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <random>
```

```
#include <chrono>
```

## Functions

- `template<class Field, class RandIter >`  
`bool launch\_test (const Field &F, size_t n, typename Field::Element *A, size_t lda, size_t nbit, RandIter &G, FFPACK::FFPACK_CHARPOLY_TAG CT)`
- `template<class Field >`  
`bool run\_with\_field (const Givaro::Integer p, uint64_t bits, size_t n, std::string file, int variant, size_t iter, uint64_t seed)`
- `int main (int argc, char **argv)`

## 13.264.1 Function Documentation

### 13.264.1.1 [launch\\_test\(\)](#)

```
template<class Field , class RandIter >
bool launch_test (
 const Field & F,
 size_t n,
 typename Field::Element * A,
 size_t lda,
 size_t nbit,
 RandIter & G,
 FFPACK::FFPACK_CHARPOLY_TAG CT)
```

### 13.264.1.2 [run\\_with\\_field\(\)](#)

```
template<class Field >
bool run_with_field (
 const Givaro::Integer p,
 uint64_t bits,
 size_t n,
 std::string file,
 int variant,
 size_t iter,
 uint64_t seed)
```

### 13.264.1.3 [main\(\)](#)

```
int main (
 int argc,
 char ** argv)
```

## 13.265 test-compressQ.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <list>
#include <vector>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
```

## Typedefs

- typedef Givaro::Modular< double > [Field](#)

## Functions

- template<class T >  
std::ostream & [printvect](#) (std::ostream &o, vector< T > &vect)
- int [main](#) (int argc, char \*\*argv)

### 13.265.1 Typedef Documentation

#### 13.265.1.1 Field

```
typedef Givaro::Modular<double> Field
```

### 13.265.2 Function Documentation

#### 13.265.2.1 printvect()

```
template<class T >
std::ostream & printvect (
 std::ostream & o,
 vector< T > & vect)
```

[Bug](#) does not belong here

#### 13.265.2.2 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.266 test-det-check.C File Reference

```
#include <iostream>
#include <stdlib.h>
#include <time.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/checkers/checkers_ffpack.h"
#include "fflas-ffpack/checkers/checkers_ffpack.inl"
```

## Macros

- #define [ENABLE\\_CHECKER\\_Det](#) 1
- #define [TIME\\_CHECKER\\_Det](#) 1

## Functions

- int [main](#) (int argc, char \*\*argv)

### 13.266.1 Macro Definition Documentation

#### 13.266.1.1 ENABLE\_CHECKER\_Det

```
#define ENABLE_CHECKER_Det 1
```

### 13.266.1.2 TIME\_CHECKER\_Det

```
#define TIME_CHECKER_Det 1
```

## 13.266.2 Function Documentation

### 13.266.2.1 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.267 test-det.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iomanip>
#include <iostream>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
```

### Functions

- template<class [Field](#) , class RandIter >  
bool [test\\_det](#) ([Field](#) &F, size\_t n, int iter, RandIter &G)
- int [main](#) (int argc, char \*\*argv)

### 13.267.1 Function Documentation

#### 13.267.1.1 test\_det()

```
template<class Field , class RandIter >
bool test_det (
 Field & F,
 size_t n,
 int iter,
 RandIter & G)
```

[Todo](#) test with stride

#### 13.267.1.2 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.268 test-echelon.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <iomanip>
#include <givaro/modular-balanced.h>
#include <givaro/udl.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/ffpack/ffpack.h"
```

```
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include <random>
#include <chrono>
```

## Macros

- `#define __FFLASFFPACK_SEQUENTIAL`
- `#define __FFLASFFPACK_GAUSSJORDAN_BASECASE 25`
- `#define __FFLASFFPACK_PLUQ_THRESHOLD 25`

## Functions

- `template<class Field , class RandIter >`  
`bool test_colechelon (Field &F, size_t m, size_t n, size_t r, size_t iters, FFPACK::FFPACK_LU_TAG LuTag,`  
`RandIter &G, bool par)`
- `template<class Field , class RandIter >`  
`bool test_rowechelon (Field &F, size_t m, size_t n, size_t r, size_t iters, FFPACK::FFPACK_LU_TAG LuTag,`  
`RandIter &G, bool par)`
- `template<class Field , class RandIter >`  
`bool test_redcolechelon (Field &F, size_t m, size_t n, size_t r, size_t iters, FFPACK::FFPACK_LU_TAG LuTag,`  
`RandIter &G, bool par)`
- `template<class Field , class RandIter >`  
`bool test_redrowechelon (Field &F, size_t m, size_t n, size_t r, size_t iters, FFPACK::FFPACK_LU_TAG LuTag,`  
`RandIter &G, bool par)`
- `template<class Field >`  
`bool run_with_field (Givaro::Integer q, uint64_t b, size_t m, size_t n, size_t r, size_t iters, uint64_t seed)`
- `int main (int argc, char **argv)`

## 13.268.1 Macro Definition Documentation

### 13.268.1.1 \_\_FFLASFFPACK\_SEQUENTIAL

```
#define __FFLASFFPACK_SEQUENTIAL
```

### 13.268.1.2 \_\_FFLASFFPACK\_GAUSSJORDAN\_BASECASE

```
#define __FFLASFFPACK_GAUSSJORDAN_BASECASE 25
```

### 13.268.1.3 \_\_FFLASFFPACK\_PLUQ\_THRESHOLD

```
#define __FFLASFFPACK_PLUQ_THRESHOLD 25
```

## 13.268.2 Function Documentation

### 13.268.2.1 test\_colechelon()

```
template<class Field , class RandIter >
bool test_colechelon (
 Field & F,
 size_t m,
 size_t n,
 size_t r,
 size_t iters,
 FFPACK::FFPACK_LU_TAG LuTag,
 RandIter & G,
 bool par)
```



**Todo** check Ida

### 13.268.2.2 test\_rowechelon()

```
template<class Field , class RandIter >
bool test_rowechelon (
 Field & F,
 size_t m,
 size_t n,
 size_t r,
 size_t iters,
 FFPACK::FFPACK_LU_TAG LuTag,
 RandIter & G,
 bool par)
```

**Todo** check Ida

### 13.268.2.3 test\_redcolechelon()

```
template<class Field , class RandIter >
bool test_redcolechelon (
 Field & F,
 size_t m,
 size_t n,
 size_t r,
 size_t iters,
 FFPACK::FFPACK_LU_TAG LuTag,
 RandIter & G,
 bool par)
```

**Todo** check Ida

### 13.268.2.4 test\_redrowechelon()

```
template<class Field , class RandIter >
bool test_redrowechelon (
 Field & F,
 size_t m,
 size_t n,
 size_t r,
 size_t iters,
 FFPACK::FFPACK_LU_TAG LuTag,
 RandIter & G,
 bool par)
```

**Todo** check Ida

### 13.268.2.5 run\_with\_field()

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 uint64_t b,
 size_t m,
 size_t n,
 size_t r,
 size_t iters,
 uint64_t seed)
```

### 13.268.2.6 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.269 test-fadd.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <typeinfo>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "assert.h"
```

### Functions

- template<class [Field](#) >  
bool [test\\_fadd](#) (const [Field](#) &F, size\_t m, size\_t k, size\_t n, bool timing, uint64\_t seed)
- template<class [Field](#) >  
bool [test\\_faddin](#) (const [Field](#) &F, size\_t m, size\_t k, size\_t n, bool timing, uint64\_t seed)
- template<class [Field](#) >  
bool [test\\_fsub](#) (const [Field](#) &F, size\_t m, size\_t k, size\_t n, bool timing, uint64\_t seed)
- template<class [Field](#) >  
bool [test\\_fsubin](#) (const [Field](#) &F, size\_t m, size\_t k, size\_t n, bool timing, uint64\_t seed)
- int [main](#) (int ac, char \*\*av)

### 13.269.1 Function Documentation

#### 13.269.1.1 test\_fadd()

```
template<class Field >
bool test_fadd (
 const Field & F,
 size_t m,
 size_t k,
 size_t n,
 bool timing,
 uint64_t seed)
```

#### 13.269.1.2 test\_faddin()

```
template<class Field >
bool test_faddin (
 const Field & F,
 size_t m,
 size_t k,
 size_t n,
 bool timing,
 uint64_t seed)
```

#### 13.269.1.3 test\_fsub()

```
template<class Field >
bool test_fsub (
 const Field & F,
```

```

 size_t m,
 size_t k,
 size_t n,
 bool timing,
 uint64_t seed)

```

#### 13.269.1.4 test\_fsubin()

```

template<class Field >
bool test_fsubin (
 const Field & F,
 size_t m,
 size_t k,
 size_t n,
 bool timing,
 uint64_t seed)

```

#### 13.269.1.5 main()

```

int main (
 int ac,
 char ** av)

```

## 13.270 test-fdot.C File Reference

```

#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iomanip>
#include <iostream>
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/paladin/parallel.h"
#include "fflas-ffpack/paladin/fflas_plevel1.h"
#include <givaro/zring.h>
#include <givaro/modular.h>
#include <random>
#include <chrono>

```

### Macros

- #define [ENABLE\\_ALL\\_CHECKINGS](#) 1

### Functions

- template<typename [Field](#) >  
bool [check\\_fdot](#) (const [Field](#) &F, size\_t n, typename [Field::ConstElement\\_ptr](#) a, size\_t inca, typename [Field::ConstElement\\_ptr](#) b, size\_t incb)
- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, size\_t BS, size\_t n, size\_t iters, uint64\_t seed)
- bool [run\\_with\\_Integer](#) (size\_t BS, size\_t n, size\_t iters, uint64\_t seed)
- int [main](#) (int argc, char \*\*argv)

## 13.270.1 Macro Definition Documentation

### 13.270.1.1 ENABLE\_ALL\_CHECKINGS

```

#define ENABLE_ALL_CHECKINGS 1

```

## 13.270.2 Function Documentation

### 13.270.2.1 check\_fdot()

```
template<typename Field >
bool check_fdot (
 const Field & F,
 size_t n,
 typename Field::ConstElement_ptr a,
 size_t inca,
 typename Field::ConstElement_ptr b,
 size_t incb)
```

### 13.270.2.2 run\_with\_field()

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 size_t BS,
 size_t n,
 size_t iters,
 uint64_t seed)
```

### 13.270.2.3 run\_with\_Integer()

```
bool run_with_Integer (
 size_t BS,
 size_t n,
 size_t iters,
 uint64_t seed)
```

### 13.270.2.4 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.271 test-fgemm-check.C File Reference

```
#include <iostream>
#include <stdlib.h>
#include <time.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
```

### Macros

- #define `ENABLE_ALL_CHECKINGS` 1

### Functions

- template<class `Field` , class `RandIter` >  
bool `launch_MM_dispatch` (const `Field` &F, const int mm, const int nn, const int kk, const typename `Field::Element` alpha, const typename `Field::Element` beta, const size\_t iters, `RandIter` &G)
- template<class `Field` >  
bool `run_with_field` (`Givaro::Integer` q, `uint64_t` b, int m, int n, int k, size\_t iters, `uint64_t` seed)
- int `main` (int argc, char \*\*argv)

## 13.271.1 Macro Definition Documentation

### 13.271.1.1 ENABLE\_ALL\_CHECKINGS

```
#define ENABLE_ALL_CHECKINGS 1
```

## 13.271.2 Function Documentation

### 13.271.2.1 launch\_MM\_dispatch()

```
template<class Field , class RandIter >
bool launch_MM_dispatch (
 const Field & F,
 const int mm,
 const int nn,
 const int kk,
 const typename Field::Element alpha,
 const typename Field::Element beta,
 const size_t iters,
 RandIter & G)
```

**Bug** test for ldX equal

**Bug**

**Bug** test for transpo

**Bug**

**Todo** does nbw actually do nbw recursive calls and then call blas (check ?) ?

### 13.271.2.2 run\_with\_field()

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 uint64_t b,
 int m,
 int n,
 int k,
 size_t iters,
 uint64_t seed)
```

### 13.271.2.3 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.272 test-fgemm.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include <iomanip>
#include <iostream>
#include <givaro/modular.h>
#include <recint/rint.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
```

```
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <random>
```

## Macros

- #define [ENABLE\\_CHECKER\\_fgemm](#) 1

## Functions

- template<class [Field](#) >  
bool [check\\_MM](#) (const [Field](#) &F, const typename [Field::Element\\_ptr](#) Cd, enum [FFLAS\\_TRANSPOSE](#) &ta, enum [FFLAS\\_TRANSPOSE](#) &tb, const size\_t m, const size\_t n, const size\_t k, const typename [Field::Element](#) &alpha, const typename [Field::Element\\_ptr](#) A, size\_t lda, const typename [Field::Element\\_ptr](#) B, size\_t ldb, const typename [Field::Element](#) &beta, const typename [Field::Element\\_ptr](#) C, size\_t ldc)
- template<class [Field](#) , class RandIter >  
bool [launch\\_MM](#) (const [Field](#) &F, const size\_t m, const size\_t n, const size\_t k, const typename [Field::Element](#) alpha, const typename [Field::Element](#) beta, const size\_t ldc, const size\_t lda, enum [FFLAS\\_TRANSPOSE](#) ta, const size\_t ldb, enum [FFLAS\\_TRANSPOSE](#) tb, size\_t iters, int nbw, bool par, RandIter &G)
- template<class [Field](#) , class RandIter >  
bool [launch\\_MM\\_dispatch](#) (const [Field](#) &F, const int mm, const int nn, const int kk, const typename [Field::Element](#) alpha, const typename [Field::Element](#) beta, const size\_t iters, const int nbw, const bool par, RandIter &G)
- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, uint64\_t b, int m, int n, int k, int nbw, size\_t iters, bool par, size\_t seed)
- int [main](#) (int argc, char \*\*argv)

## 13.272.1 Macro Definition Documentation

### 13.272.1.1 [ENABLE\\_CHECKER\\_fgemm](#)

```
#define ENABLE_CHECKER_fgemm 1
```

## 13.272.2 Function Documentation

### 13.272.2.1 [check\\_MM\(\)](#)

```
template<class Field >
bool check_MM (
 const Field & F,
 const typename Field::Element_ptr Cd,
 enum FFLAS_TRANSPOSE & ta,
 enum FFLAS_TRANSPOSE & tb,
 const size_t m,
 const size_t n,
 const size_t k,
 const typename Field::Element & alpha,
 const typename Field::Element_ptr A,
 size_t lda,
 const typename Field::Element_ptr B,
 size_t ldb,
 const typename Field::Element & beta,
 const typename Field::Element_ptr C,
 size_t ldc)
```

### 13.272.2.2 [launch\\_MM\(\)](#)

```
template<class Field , class RandIter >
bool launch_MM (
```

```

 const Field & F,
 const size_t m,
 const size_t n,
 const size_t k,
 const typename Field::Element alpha,
 const typename Field::Element beta,
 const size_t ldc,
 const size_t lda,
 enum FFLAS_TRANSPOSE ta,
 const size_t ldb,
 enum FFLAS_TRANSPOSE tb,
 size_t iters,
 int nbw,
 bool par,
 RandIter & G)

```

### 13.272.2.3 launch\_MM\_dispatch()

```

template<class Field , class RandIter >
bool launch_MM_dispatch (
 const Field & F,
 const int mm,
 const int nn,
 const int kk,
 const typename Field::Element alpha,
 const typename Field::Element beta,
 const size_t iters,
 const int nbw,
 const bool par,
 RandIter & G)

```

**Bug** test for ldX equal

**Bug**

**Bug** test for transpo

**Bug**

**Todo** does nbw actually do nbw recursive calls and then call blas (check ?) ?

### 13.272.2.4 run\_with\_field()

```

template<class Field >
bool run_with_field (
 Givaro::Integer q,
 uint64_t b,
 int m,
 int n,
 int k,
 int nbw,
 size_t iters,
 bool par,
 size_t seed)

```

### 13.272.2.5 main()

```

int main (
 int argc,
 char ** argv)

```

## 13.273 test-fgemv.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iomanip>
#include <iostream>
#include <givaro/modular.h>
#include <recint/rint.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
```

### Functions

- template<class [Field](#) >  
bool [check\\_MV](#) (const [Field](#) &F, const typename [Field::Element\\_ptr](#) Cd, enum [FFLAS\\_TRANSPOSE](#) &ta, const size\_t m, const size\_t k, const typename [Field::Element](#) &alpha, const typename [Field::Element\\_ptr](#) A, size\_t lda, const typename [Field::Element\\_ptr](#) X, size\_t incX, const typename [Field::Element](#) &beta, const typename [Field::Element\\_ptr](#) Y, size\_t incY)
- template<class [Field](#) , class RandIter >  
bool [launch\\_MV](#) (const [Field](#) &F, const size\_t m, const size\_t k, const typename [Field::Element](#) alpha, const typename [Field::Element](#) beta, const size\_t lda, enum [FFLAS\\_TRANSPOSE](#) ta, const size\_t incX, const size\_t incY, size\_t iters, bool par, RandIter &G)
- template<class [Field](#) , class RandIter >  
bool [launch\\_MV\\_dispatch](#) (const [Field](#) &F, const int mm, const int kk, const typename [Field::Element](#) alpha, const typename [Field::Element](#) beta, const size\_t iters, const bool par, RandIter &G)
- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, uint64\_t b, int m, int k, size\_t iters, bool par, uint64\_t seed)
- int [main](#) (int argc, char \*\*argv)

### 13.273.1 Function Documentation

#### 13.273.1.1 [check\\_MV\(\)](#)

```
template<class Field >
bool check_MV (
 const Field & F,
 const typename Field::Element_ptr Cd,
 enum FFLAS_TRANSPOSE & ta,
 const size_t m,
 const size_t k,
 const typename Field::Element & alpha,
 const typename Field::Element_ptr A,
 size_t lda,
 const typename Field::Element_ptr X,
 size_t incX,
 const typename Field::Element & beta,
 const typename Field::Element_ptr Y,
 size_t incY)
```

#### 13.273.1.2 [launch\\_MV\(\)](#)

```
template<class Field , class RandIter >
bool launch_MV (
 const Field & F,
 const size_t m,
 const size_t k,
 const typename Field::Element alpha,
```



```

 const typename Field::Element beta,
 const size_t lda,
 enum FFLAS_TRANSPOSE ta,
 const size_t incX,
 const size_t incY,
 size_t iters,
 bool par,
 RandIter & G)

```

### 13.273.1.3 launch\_MV\_dispatch()

```

template<class Field , class RandIter >
bool launch_MV_dispatch (
 const Field & F,
 const int mm,
 const int kk,
 const typename Field::Element alpha,
 const typename Field::Element beta,
 const size_t iters,
 const bool par,
 RandIter & G)

```

### 13.273.1.4 run\_with\_field()

```

template<class Field >
bool run_with_field (
 Givaro::Integer q,
 uint64_t b,
 int m,
 int k,
 size_t iters,
 bool par,
 uint64_t seed)

```

### 13.273.1.5 main()

```

int main (
 int argc,
 char ** argv)

```

## 13.274 test-fger.C File Reference

```

#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iomanip>
#include <iostream>
#include <givaro/modular-integral.h>
#include <givaro/modular-balanced.h>
#include <givaro/givintprime.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/fflas_io.h"

```

### Macros

- #define TIME 1

## Functions

- `template<class Field >`  
`bool check_fger (const Field &F, const typename Field::Element_ptr Cd, const size_t m, const size_t n, const`  
`typename Field::Element &alpha, const typename Field::Element_ptr x, const size_t incx, const typename`  
`Field::Element_ptr y, const size_t incy, const typename Field::Element_ptr C, const size_t ldc)`
- `template<class Field, class RandIter >`  
`bool launch_fger (const Field &F, const size_t m, const size_t n, const typename Field::Element alpha, const`  
`size_t ldc, const size_t inca, const size_t incb, size_t iters, RandIter &G)`
- `template<class Field, class RandIter >`  
`bool launch_fger_dispatch (const Field &F, const size_t nn, const typename Field::Element alpha, const`  
`size_t iters, RandIter &G)`
- `template<class Field >`  
`bool run_with_field (int64_t q, uint64_t b, size_t n, size_t iters, uint64_t seed)`
- `int main (int argc, char **argv)`

## 13.274.1 Macro Definition Documentation

### 13.274.1.1 TIME

```
#define TIME 1
```

## 13.274.2 Function Documentation

### 13.274.2.1 check\_fger()

```
template<class Field >
bool check_fger (
 const Field & F,
 const typename Field::Element_ptr Cd,
 const size_t m,
 const size_t n,
 const typename Field::Element & alpha,
 const typename Field::Element_ptr x,
 const size_t incx,
 const typename Field::Element_ptr y,
 const size_t incy,
 const typename Field::Element_ptr C,
 const size_t ldc)
```

### 13.274.2.2 launch\_fger()

```
template<class Field, class RandIter >
bool launch_fger (
 const Field & F,
 const size_t m,
 const size_t n,
 const typename Field::Element alpha,
 const size_t ldc,
 const size_t inca,
 const size_t incb,
 size_t iters,
 RandIter & G)
```

### 13.274.2.3 launch\_fger\_dispatch()

```
template<class Field, class RandIter >
bool launch_fger_dispatch (
 const Field & F,
 const size_t nn,
```

```
const typename Field::Element alpha,
const size_t iters,
RandIter & G)
```

**Bug** test for incx equal

**Bug**

**Bug** test for transpo

**Bug**

**Todo** does nbw actually do nbw recursive calls and then call blas (check ?) ?

#### 13.274.2.4 run\_with\_field()

```
template<class Field >
bool run_with_field (
 int64_t q,
 uint64_t b,
 size_t n,
 size_t iters,
 uint64_t seed)
```

#### 13.274.2.5 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.275 test-fgesv.C File Reference

```
#include <iostream>
#include <iomanip>
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <givaro/modular.h>
```

### Functions

- template<class Field, class RandIter >  
bool **test\_square\_fgesv** (Field &F, FFLAS\_SIDE side, string fileA, string fileB, size\_t m, size\_t k, size\_t r, RandIter &G)
- template<class Field, class RandIter >  
bool **test\_rect\_fgesv** (Field &F, FFLAS\_SIDE side, string fileA, string fileB, size\_t m, size\_t n, size\_t k, size\_t r, RandIter &G)
- template<class Field >  
bool **run\_with\_field** (Givaro::Integer q, uint64\_t b, size\_t m, size\_t n, size\_t k, size\_t r, size\_t iters, string fileA, string fileB, uint64\_t &seed)
- int **main** (int argc, char \*\*argv)

## 13.275.1 Function Documentation

### 13.275.1.1 test\_square\_fgesv()

```
template<class Field , class RandIter >
bool test_square_fgesv (
 Field & F,
 FFLAS_SIDE side,
 string fileA,
 string fileB,
 size_t m,
 size_t k,
 size_t r,
 RandIter & G)
```

### 13.275.1.2 test\_rect\_fgesv()

```
template<class Field , class RandIter >
bool test_rect_fgesv (
 Field & F,
 FFLAS_SIDE side,
 string fileA,
 string fileB,
 size_t m,
 size_t n,
 size_t k,
 size_t r,
 RandIter & G)
```

### 13.275.1.3 run\_with\_field()

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 uint64_t b,
 size_t m,
 size_t n,
 size_t k,
 size_t r,
 size_t iters,
 string fileA,
 string fileB,
 uint64_t & seed)
```

### 13.275.1.4 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.276 test-finit.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <typeinfo>
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
```

```
#include "fflas-ffpack/utils/test-utils.h"
#include "assert.h"
#include <random>
#include <chrono>
```

## Functions

- template<class [Field](#) >  
bool [test\\_freduce](#) (const [Field](#) &F, size\_t m, size\_t k, size\_t n, bool timing, uint64\_t seed)
- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, size\_t b, size\_t m, size\_t k, size\_t n, size\_t iters, bool timing, uint64\_t seed)
- int [main](#) (int ac, char \*\*av)

## 13.276.1 Function Documentation

### 13.276.1.1 test\_freduce()

```
template<class Field >
bool test_freduce (
 const Field & F,
 size_t m,
 size_t k,
 size_t n,
 bool timing,
 uint64_t seed)
```

### 13.276.1.2 run\_with\_field()

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 size_t b,
 size_t m,
 size_t k,
 size_t n,
 size_t iters,
 bool timing,
 uint64_t seed)
```

### 13.276.1.3 main()

```
int main (
 int ac,
 char ** av)
```

## 13.277 test-fscal.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <typeinfo>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "assert.h"
```

## Functions

- `template<class Field , class RandIter >`  
`bool test_fscal (const Field &F, const typename Field::Element &alpha, size_t m, size_t k, size_t n, bool timing, RandIter &G)`
- `template<class Field >`  
`bool test_fscal (const Field &F, size_t m, size_t k, size_t n, bool timing, uint64_t seed)`
- `template<class Field , class RandIter >`  
`bool test_fscalin (const Field &F, const typename Field::Element &alpha, size_t m, size_t k, size_t n, bool timing, RandIter &G)`
- `template<class Field >`  
`bool test_fscalin (const Field &F, size_t m, size_t k, size_t n, bool timing, uint64_t seed)`
- `int main (int ac, char **av)`

## 13.277.1 Function Documentation

### 13.277.1.1 test\_fscal() [1/2]

```
template<class Field , class RandIter >
bool test_fscal (
 const Field & F,
 const typename Field::Element & alpha,
 size_t m,
 size_t k,
 size_t n,
 bool timing,
 RandIter & G)
```

### 13.277.1.2 test\_fscal() [2/2]

```
template<class Field >
bool test_fscal (
 const Field & F,
 size_t m,
 size_t k,
 size_t n,
 bool timing,
 uint64_t seed)
```

### 13.277.1.3 test\_fscalin() [1/2]

```
template<class Field , class RandIter >
bool test_fscalin (
 const Field & F,
 const typename Field::Element & alpha,
 size_t m,
 size_t k,
 size_t n,
 bool timing,
 RandIter & G)
```

### 13.277.1.4 test\_fscalin() [2/2]

```
template<class Field >
bool test_fscalin (
 const Field & F,
 size_t m,
 size_t k,
 size_t n,
```

```
bool timing,
uint64_t seed)
```

### 13.277.1.5 main()

```
int main (
 int ac,
 char ** av)
```

## 13.278 test-fsyr2k.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iomanip>
#include <iostream>
#include <random>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <givaro/modular.h>
```

### Macros

- #define [ENABLE\\_ALL\\_CHECKINGS](#) 1

### Functions

- template<typename [Field](#) , class RandIter >  
bool [check\\_fsyr2k](#) (const [Field](#) &F, size\_t n, size\_t k, const typename [Field::Element](#) &alpha, const typename [Field::Element](#) &beta, [FFLAS::FFLAS\\_UPLO](#) uplo, [FFLAS::FFLAS\\_TRANSPOSE](#) trans, RandIter &Rand)
- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, size\_t b, size\_t n, size\_t k, int a, int c, size\_t iters, uint64\_t seed)
- int [main](#) (int argc, char \*\*argv)

## 13.278.1 Macro Definition Documentation

### 13.278.1.1 ENABLE\_ALL\_CHECKINGS

```
#define ENABLE_ALL_CHECKINGS 1
```

## 13.278.2 Function Documentation

### 13.278.2.1 check\_fsyr2k()

```
template<typename Field , class RandIter >
bool check_fsyr2k (
 const Field & F,
 size_t n,
 size_t k,
 const typename Field::Element & alpha,
 const typename Field::Element & beta,
 FFLAS::FFLAS_UPLO uplo,
 FFLAS::FFLAS_TRANSPOSE trans,
 RandIter & Rand)
```

### 13.278.2.2 run\_with\_field()

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 size_t b,
 size_t n,
 size_t k,
 int a,
 int c,
 size_t iters,
 uint64_t seed)
```

### 13.278.2.3 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.279 test-fsyrrk.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iomanip>
#include <iostream>
#include <random>
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <givaro/modular.h>
```

### Macros

- #define `ENABLE_ALL_CHECKINGS` 1

### Functions

- template<typename `Field` , class `RandIter` >  
bool `check_fsyrrk` (const `Field` &F, size\_t n, size\_t k, size\_t w, const typename `Field::Element` &alpha, const typename `Field::Element` &beta, `FFLAS::FFLAS_UPLO` uplo, `FFLAS::FFLAS_TRANSPOSE` trans, `RandIter` &Rand)
- template<typename `Field` , class `RandIter` >  
bool `check_fsyrrk_diag` (const `Field` &F, size\_t n, size\_t k, const typename `Field::Element` &alpha, const typename `Field::Element` &beta, `FFLAS::FFLAS_UPLO` uplo, `FFLAS::FFLAS_TRANSPOSE` trans, `RandIter` &Rand)
- template<typename `Field` , class `RandIter` >  
bool `check_fsyrrk_bkdiag` (const `Field` &F, size\_t n, size\_t k, const typename `Field::Element` &alpha, const typename `Field::Element` &beta, `FFLAS_UPLO` uplo, `FFLAS_TRANSPOSE` trans, `RandIter` &Rand)
- template<class `Field` , class `RandIter` >  
bool `check_computeS1S2` (const `Field` &F, size\_t N, size\_t K, `FFLAS_TRANSPOSE` trans, `RandIter` &G)
- template<class `Field` >  
bool `run_with_field` (Givaro::Integer q, size\_t b, size\_t n, size\_t k, size\_t w, int a, int c, size\_t iters, uint64\_t seed)
- int `main` (int argc, char \*\*argv)



## 13.279.1 Macro Definition Documentation

### 13.279.1.1 ENABLE\_ALL\_CHECKINGS

```
#define ENABLE_ALL_CHECKINGS 1
```

## 13.279.2 Function Documentation

### 13.279.2.1 check\_fsyrc()

```
template<typename Field , class RandIter >
bool check_fsyrc (
 const Field & F,
 size_t n,
 size_t k,
 size_t w,
 const typename Field::Element & alpha,
 const typename Field::Element & beta,
 FFLAS::FFLAS_UPLO uplo,
 FFLAS::FFLAS_TRANSPOSE trans,
 RandIter & Rand)
```

### 13.279.2.2 check\_fsyrc\_diag()

```
template<typename Field , class RandIter >
bool check_fsyrc_diag (
 const Field & F,
 size_t n,
 size_t k,
 const typename Field::Element & alpha,
 const typename Field::Element & beta,
 FFLAS::FFLAS_UPLO uplo,
 FFLAS::FFLAS_TRANSPOSE trans,
 RandIter & Rand)
```

### 13.279.2.3 check\_fsyrc\_bkdiag()

```
template<typename Field , class RandIter >
bool check_fsyrc_bkdiag (
 const Field & F,
 size_t n,
 size_t k,
 const typename Field::Element & alpha,
 const typename Field::Element & beta,
 FFLAS_UPLO uplo,
 FFLAS_TRANSPOSE trans,
 RandIter & Rand)
```

### 13.279.2.4 check\_computeS1S2()

```
template<class Field , class RandIter >
bool check_computeS1S2 (
 const Field & F,
 size_t N,
 size_t K,
 FFLAS_TRANSPOSE trans,
 RandIter & G)
```

### 13.279.2.5 run\_with\_field()

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 size_t b,
 size_t n,
 size_t k,
 size_t w,
 int a,
 int c,
 size_t iters,
 uint64_t seed)
```

### 13.279.2.6 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.280 test-fsytrf.C File Reference

```
#include <iostream>
#include <iterator>
#include <vector>
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include <iomanip>
#include <random>
#include <chrono>
#include <givaro/modular.h>
#include "fflas-ffpack/utils/test-utils.h"
```

### Functions

- template<typename T >  
std::ostream & [operator<<](#) (std::ostream &os, const std::vector< T > &x)
- template<class Field , class RandIter >  
bool [test\\_RPM\\_fsytrf](#) (Field &F, FFLAS\_UPLO uplo, string file, size\_t n, size\_t r, RandIter &G, size\_t threshold)
- template<class Field , class RandIter >  
bool [test\\_generic\\_fsytrf](#) (Field &F, FFLAS\_UPLO uplo, string file, size\_t n, RandIter &G, size\_t threshold)
- template<class Field >  
bool [run\\_with\\_field](#) (Givaro::Integer q, uint64\_t b, size\_t n, size\_t r, size\_t iters, string file, size\_t threshold, uint64\_t &seed)
- int [main](#) (int argc, char \*\*argv)

### 13.280.1 Function Documentation

#### 13.280.1.1 operator<<()

```
template<typename T >
std::ostream & operator<< (
 std::ostream & os,
 const std::vector< T > & x)
```

**13.280.1.2 test\_RPM\_fsytrf()**

```
template<class Field , class RandIter >
bool test_RPM_fsytrf (
 Field & F,
 FFLAS_UPLO uplo,
 string file,
 size_t n,
 size_t r,
 RandIter & G,
 size_t threshold)
```

**13.280.1.3 test\_generic\_fsytrf()**

```
template<class Field , class RandIter >
bool test_generic_fsytrf (
 Field & F,
 FFLAS_UPLO uplo,
 string file,
 size_t n,
 RandIter & G,
 size_t threshold)
```

**13.280.1.4 run\_with\_field()**

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 uint64_t b,
 size_t n,
 size_t r,
 size_t iters,
 string file,
 size_t threshold,
 uint64_t & seed)
```

**13.280.1.5 main()**

```
int main (
 int argc,
 char ** argv)
```

**13.281 test-fftrmm.C File Reference**

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <givaro/modular-integer.h>
#include <iomanip>
#include <iostream>
#include <random>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
```

## Macros

- `#define __FFLASFFPACK_SEQUENTIAL`

## Functions

- `template<typename Field, class RandIter >`  
`bool check_ftmm (const Field &F, size_t m, size_t n, const typename Field::Element &alpha,`  
`FFLAS::FFLAS_SIDE side, FFLAS::FFLAS_UPLO uplo, FFLAS::FFLAS_TRANSPOSE trans, FFLAS::FFLAS_DIAG`  
`diag, RandIter &Rand)`
- `template<class Field >`  
`bool run_with_field (Givaro::Integer q, size_t b, size_t m, size_t n, uint64_t a, size_t iters, uint64_t seed)`
- `int main (int argc, char **argv)`

## 13.281.1 Macro Definition Documentation

### 13.281.1.1 \_\_FFLASFFPACK\_SEQUENTIAL

```
#define __FFLASFFPACK_SEQUENTIAL
```

## 13.281.2 Function Documentation

### 13.281.2.1 check\_ftmm()

```
template<typename Field, class RandIter >
bool check_ftmm (
 const Field & F,
 size_t m,
 size_t n,
 const typename Field::Element & alpha,
 FFLAS::FFLAS_SIDE side,
 FFLAS::FFLAS_UPLO uplo,
 FFLAS::FFLAS_TRANSPOSE trans,
 FFLAS::FFLAS_DIAG diag,
 RandIter & Rand)
```

### 13.281.2.2 run\_with\_field()

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 size_t b,
 size_t m,
 size_t n,
 uint64_t a,
 size_t iters,
 uint64_t seed)
```

### 13.281.2.3 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.282 test-ftmmv.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iomanip>
#include <iostream>
```

```
#include <chrono>
#include <random>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <givaro/modular.h>
```

## Macros

- `#define __FFLASFFPACK_SEQUENTIAL`
- `#define ENABLE_ALL_CHECKINGS 1`

## Functions

- `template<typename Field , class RandIter >`  
`bool check_ffrmv (const Field &F, size_t n, FFLAS_UPLO uplo, FFLAS_TRANSPOSE trans, FFLAS_DIAG diag, RandIter &Rand)`
- `template<class Field >`  
`bool run_with_field (Givaro::Integer q, size_t b, size_t n, size_t iters, uint64_t seed)`
- `int main (int argc, char **argv)`

## 13.282.1 Macro Definition Documentation

### 13.282.1.1 \_\_FFLASFFPACK\_SEQUENTIAL

```
#define __FFLASFFPACK_SEQUENTIAL
```

### 13.282.1.2 ENABLE\_ALL\_CHECKINGS

```
#define ENABLE_ALL_CHECKINGS 1
```

## 13.282.2 Function Documentation

### 13.282.2.1 check\_ffrmv()

```
template<typename Field , class RandIter >
bool check_ffrmv (
 const Field & F,
 size_t n,
 FFLAS_UPLO uplo,
 FFLAS_TRANSPOSE trans,
 FFLAS_DIAG diag,
 RandIter & Rand)
```

### 13.282.2.2 run\_with\_field()

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 size_t b,
 size_t n,
 size_t iters,
 uint64_t seed)
```

**13.282.2.3 main()**

```
int main (
 int argc,
 char ** argv)
```

**13.283 test-ffrsm-check.C File Reference**

```
#include <iostream>
#include <stdlib.h>
#include <time.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/fflas_io.h"
```

**Macros**

- `#define` [ENABLE\\_ALL\\_CHECKINGS](#) 1

**Functions**

- `int` [main](#) (int argc, char \*\*argv)

**13.283.1 Macro Definition Documentation****13.283.1.1 ENABLE\_ALL\_CHECKINGS**

```
#define ENABLE_ALL_CHECKINGS 1
```

**13.283.2 Function Documentation****13.283.2.1 main()**

```
int main (
 int argc,
 char ** argv)
```

**13.284 test-ffrsm.C File Reference**

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <givaro/modular-integer.h>
#include <iomanip>
#include <iostream>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include <random>
```

**Macros**

- `#define` [\\_\\_FFLASFFPACK\\_SEQUENTIAL](#)
- `#define` [ENABLE\\_ALL\\_CHECKINGS](#) 1

## Functions

- `template<typename Field , class RandIter >`  
`bool check\_ftsm (const Field &F, size_t m, size_t n, const typename Field::Element &alpha,`  
`FFLAS::FFLAS\_SIDE side, FFLAS::FFLAS\_UPLO uplo, FFLAS::FFLAS\_TRANSPOSE trans, FFLAS::FFLAS\_DIAG`  
`diag, RandIter &Rand)`
- `template<class Field >`  
`bool run\_with\_field (Givaro::Integer q, size_t b, size_t m, size_t n, uint64_t a, size_t iters, uint64_t seed)`
- `int main (int argc, char **argv)`

## 13.284.1 Macro Definition Documentation

### 13.284.1.1 `__FFLASFFPACK_SEQUENTIAL`

```
#define __FFLASFFPACK_SEQUENTIAL
```

### 13.284.1.2 `ENABLE_ALL_CHECKINGS`

```
#define ENABLE_ALL_CHECKINGS 1
```

## 13.284.2 Function Documentation

### 13.284.2.1 `check_ftsm()`

```
template<typename Field , class RandIter >
bool check_ftsm (
 const Field & F,
 size_t m,
 size_t n,
 const typename Field::Element & alpha,
 FFLAS::FFLAS_SIDE side,
 FFLAS::FFLAS_UPLO uplo,
 FFLAS::FFLAS_TRANSPOSE trans,
 FFLAS::FFLAS_DIAG diag,
 RandIter & Rand)
```

### 13.284.2.2 `run_with_field()`

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 size_t b,
 size_t m,
 size_t n,
 uint64_t a,
 size_t iters,
 uint64_t seed)
```

### 13.284.2.3 `main()`

```
int main (
 int argc,
 char ** argv)
```

## 13.285 test-ffrssyr2k.C File Reference

```
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <givaro/modular-integer.h>
```

```
#include <iomanip>
#include <iostream>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include <random>
```

## Macros

- #define [ENABLE\\_ALL\\_CHECKINGS](#) 1

## Functions

- template<typename [Field](#) , class RandIter >  
bool [check\\_ftrssyr2k](#) (const [Field](#) &F, size\_t n, [FFLAS::FFLAS\\_UPLO](#) uplo, [FFLAS::FFLAS\\_DIAG](#) diagA, RandIter &Rand)
- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, size\_t b, size\_t n, size\_t iters, uint64\_t seed)
- int [main](#) (int argc, char \*\*argv)

## 13.285.1 Macro Definition Documentation

### 13.285.1.1 [ENABLE\\_ALL\\_CHECKINGS](#)

```
#define ENABLE_ALL_CHECKINGS 1
```

## 13.285.2 Function Documentation

### 13.285.2.1 [check\\_ftrssyr2k\(\)](#)

```
template<typename Field , class RandIter >
bool check_ftrssyr2k (
 const Field & F,
 size_t n,
 FFLAS::FFLAS_UPLO uplo,
 FFLAS::FFLAS_DIAG diagA,
 RandIter & Rand)
```

### 13.285.2.2 [run\\_with\\_field\(\)](#)

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 size_t b,
 size_t n,
 size_t iters,
 uint64_t seed)
```

### 13.285.2.3 [main\(\)](#)

```
int main (
 int argc,
 char ** argv)
```



## 13.286 test-ftrstr.C File Reference

```
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <givaro/modular-integer.h>
#include <iomanip>
#include <iostream>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include <random>
```

### Macros

- #define [ENABLE\\_ALL\\_CHECKINGS](#) 1

### Functions

- template<typename [Field](#) , class RandIter >  
bool [check\\_ftrstr](#) (const [Field](#) &F, size\_t n, [FFLAS::FFLAS\\_SIDE](#) side, [FFLAS::FFLAS\\_UPLO](#) uplo, [FFLAS::FFLAS\\_DIAG](#) diagA, [FFLAS::FFLAS\\_DIAG](#) diagB, RandIter &Rand)
- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, size\_t b, size\_t n, size\_t iters, uint64\_t seed)
- int [main](#) (int argc, char \*\*argv)

## 13.286.1 Macro Definition Documentation

### 13.286.1.1 [ENABLE\\_ALL\\_CHECKINGS](#)

```
#define ENABLE_ALL_CHECKINGS 1
```

## 13.286.2 Function Documentation

### 13.286.2.1 [check\\_ftrstr\(\)](#)

```
template<typename Field , class RandIter >
bool check_ftrstr (
 const Field & F,
 size_t n,
 FFLAS::FFLAS_SIDE side,
 FFLAS::FFLAS_UPLO uplo,
 FFLAS::FFLAS_DIAG diagA,
 FFLAS::FFLAS_DIAG diagB,
 RandIter & Rand)
```

### 13.286.2.2 [run\\_with\\_field\(\)](#)

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 size_t b,
 size_t n,
 size_t iters,
 uint64_t seed)
```

### 13.286.2.3 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.287 test-fftrsv.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iomanip>
#include <iostream>
#include <random>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <givaro/modular.h>
```

### Macros

- `#define __FFLASFFPACK_SEQUENTIAL`
- `#define ENABLE_ALL_CHECKINGS 1`

### Functions

- `template<typename Field , class RandIter >`  
`bool check_fftrsv (const Field &F, size_t n, FFLAS_UPLO uplo, FFLAS_TRANSPOSE trans, FFLAS_DIAG diag, RandIter &Rand)`
- `template<class Field >`  
`bool run_with_field (Givaro::Integer q, size_t b, size_t n, size_t iters, uint64_t seed)`
- `int main (int argc, char **argv)`

## 13.287.1 Macro Definition Documentation

### 13.287.1.1 \_\_FFLASFFPACK\_SEQUENTIAL

```
#define __FFLASFFPACK_SEQUENTIAL
```

### 13.287.1.2 ENABLE\_ALL\_CHECKINGS

```
#define ENABLE_ALL_CHECKINGS 1
```

## 13.287.2 Function Documentation

### 13.287.2.1 check\_fftrsv()

```
template<typename Field , class RandIter >
bool check_fftrsv (
 const Field & F,
 size_t n,
 FFLAS_UPLO uplo,
 FFLAS_TRANSPOSE trans,
 FFLAS_DIAG diag,
 RandIter & Rand)
```

### 13.287.2.2 run\_with\_field()

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 size_t b,
 size_t n,
 size_t iters,
 uint64_t seed)
```

### 13.287.2.3 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.288 test-fftrtri.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iomanip>
#include <iostream>
#include <random>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <givaro/modular.h>
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/ffpack/ffpack.h"
```

### Macros

- #define [\\_\\_FFLASFFPACK\\_SEQUENTIAL](#)
- #define [ENABLE\\_ALL\\_CHECKINGS](#) 1

### Functions

- template<typename [Field](#) , class RandIter >  
bool [check\\_fftrtri](#) (const [Field](#) &F, size\_t n, [FFLAS\\_UPLO](#) uplo, [FFLAS\\_DIAG](#) diag, RandIter &Rand)
- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, size\_t b, size\_t n, size\_t iters, uint64\_t seed)
- int [main](#) (int argc, char \*\*argv)

## 13.288.1 Macro Definition Documentation

### 13.288.1.1 \_\_FFLASFFPACK\_SEQUENTIAL

```
#define __FFLASFFPACK_SEQUENTIAL
```

### 13.288.1.2 ENABLE\_ALL\_CHECKINGS

```
#define ENABLE_ALL_CHECKINGS 1
```

## 13.288.2 Function Documentation

### 13.288.2.1 check\_fftrtri()

```
template<typename Field , class RandIter >
bool check_fftrtri (
```

```

 const Field & F,
 size_t n,
 FFLAS_UPLO uplo,
 FFLAS_DIAG diag,
 RandIter & Rand)

```

### 13.288.2.2 run\_with\_field()

```

template<class Field >
bool run_with_field (
 Givaro::Integer q,
 size_t b,
 size_t n,
 size_t iters,
 uint64_t seed)

```

### 13.288.2.3 main()

```

int main (
 int argc,
 char ** argv)

```

## 13.289 test-interfaces-c.c File Reference

```

#include <fflas-ffpack/interfaces/libs/fflas_c.h>
#include <fflas-ffpack/interfaces/libs/ffpack_c.h>
#include <stdlib.h>
#include <stdio.h>

```

### Functions

- int [main](#) ()

### 13.289.1 Function Documentation

#### 13.289.1.1 main()

```

int main (
 void)

```

## 13.290 test-invert-check.C File Reference

```

#include <iostream>
#include <stdlib.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"

```

### Macros

- #define [ENABLE\\_ALL\\_CHECKINGS](#) 1

### Functions

- int [main](#) (int argc, char \*\*argv)

## 13.290.1 Macro Definition Documentation

### 13.290.1.1 ENABLE\_ALL\_CHECKINGS

```
#define ENABLE_ALL_CHECKINGS 1
```

## 13.290.2 Function Documentation

### 13.290.2.1 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.291 test-io.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <random>
#include <givaro/modular.h>
#include <givaro/zring.h>
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/args-parser.h"
```

### Data Structures

- struct [CompactElement](#)< [Element](#) >
- struct [CompactElement](#)< [double](#) >
- struct [CompactElement](#)< [float](#) >
- struct [CompactElement](#)< [int64\\_t](#) >
- struct [CompactElement](#)< [int32\\_t](#) >
- struct [CompactElement](#)< [int16\\_t](#) >

### Functions

- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, uint64\_t b, size\_t m, size\_t n, size\_t iters, uint64\_t seed)
- int [main](#) (int argc, char \*\*argv)

## 13.291.1 Function Documentation

### 13.291.1.1 run\_with\_field()

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 uint64_t b,
 size_t m,
 size_t n,
 size_t iters,
 uint64_t seed)
```

### 13.291.1.2 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.292 test-lu.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <givaro/modular-balanced.h>
#include <iostream>
#include <iomanip>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/args-parser.h"
#include <random>
```

### Macros

- #define [BASECASE\\_K](#) 37
- #define [\\_\\_FFLASFFPACK\\_SEQUENTIAL](#)
- #define [\\_\\_LUDIVINE\\_CUTOFF](#) 1

### Functions

- template<class [Field](#), [FFLAS\\_DIAG](#) diag, [FFLAS\\_TRANSPOSE](#) trans>  
bool [test\\_LUdivine](#) (const [Field](#) &F, typename [Field::ConstElement\\_ptr](#) A, size\_t lda, size\_t r, size\_t m, size\_t n)  
*Tests the LUdivine routine.*
- template<class [Field](#), [FFLAS\\_DIAG](#) diag>  
bool [verifPLUQ](#) (const [Field](#) &F, typename [Field::ConstElement\\_ptr](#) A, size\_t lda, typename [Field::Element\\_ptr](#) PLUQ, size\_t ldpluq, size\_t \*P, size\_t \*Q, size\_t m, size\_t n, size\_t R)  
*Verifies that  $B = PLUQ$  where A stores  $[L|U]$ .*
- template<class [Field](#), [FFLAS\\_DIAG](#) diag, class [RandIter](#) >  
bool [test\\_pluq](#) (const [Field](#) &F, typename [Field::ConstElement\\_ptr](#) A, size\_t r, size\_t m, size\_t n, size\_t lda, [RandIter](#) &G)  
*Tests the LUdivine routine.*
- template<class [Field](#), [FFLAS\\_DIAG](#) diag, [FFLAS\\_TRANSPOSE](#) trans, class [RandIter](#) >  
bool [launch\\_test](#) (const [Field](#) &F, size\_t r, size\_t m, size\_t n, [RandIter](#) &G)
- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, uint64\_t b, size\_t m, size\_t n, size\_t r, size\_t iters, uint64\_t seed)
- int [main](#) (int argc, char \*\*argv)

### Variables

- Givaro::Timer [tperm](#)
- Givaro::Timer [tgemm](#)
- Givaro::Timer [tBC](#)
- Givaro::Timer [ttrsm](#)
- Givaro::Timer [trest](#)
- Givaro::Timer [timtot](#)
- size\_t [mvcnt](#) = 0

## 13.292.1 Macro Definition Documentation

### 13.292.1.1 BASECASE\_K

```
#define BASECASE_K 37
```

### 13.292.1.2 \_\_FFLASFFPACK\_SEQUENTIAL

```
#define __FFLASFFPACK_SEQUENTIAL
```

### 13.292.1.3 \_\_LUDIVINE\_CUTOFF

```
#define __LUDIVINE_CUTOFF 1
```

## 13.292.2 Function Documentation

### 13.292.2.1 test\_LUdivine()

```
template<class Field , FFLAS::FFLAS_DIAG diag, FFLAS_TRANSPOSE trans>
bool test_LUdivine (
 const Field & F,
 typename Field::ConstElement_ptr A,
 size_t lda,
 size_t r,
 size_t m,
 size_t n)
```

Tests the LUdivine routine.

#### Template Parameters

|              |                    |
|--------------|--------------------|
| <i>Field</i> | Field              |
| <i>Diag</i>  | Unit diagonal in U |
| <i>Trans</i> |                    |

#### Parameters

|            |                       |
|------------|-----------------------|
| <i>F</i>   | field                 |
| <i>A</i>   | Matrix (preallocated) |
| <i>r</i>   | rank of A             |
| <i>m</i>   | rows                  |
| <i>n</i>   | cols                  |
| <i>lda</i> | leading dim of A      |

#### Returns

0 iff correct, 1 otherwise

### 13.292.2.2 verifPLUQ()

```
template<class Field , FFLAS_DIAG diag>
bool verifPLUQ (
 const Field & F,
 typename Field::ConstElement_ptr A,
 size_t lda,
 typename Field::Element_ptr PLUQ,
 size_t ldpluq,
 size_t * P,
 size_t * Q,
 size_t m,
 size_t n,
 size_t R)
```

Verifies that  $B = PLUQ$  where A stores  $[L|U]$ .

## Template Parameters

|              |                    |
|--------------|--------------------|
| <i>Field</i> | Field              |
| <i>Diag</i>  | Unit diagonal in U |

## Parameters

|            |                       |
|------------|-----------------------|
| <i>F</i>   | field                 |
| <i>A</i>   | Matrix (preallocated) |
| <i>r</i>   | rank of A             |
| <i>m</i>   | rows                  |
| <i>n</i>   | cols                  |
| <i>lda</i> | leading dim of A      |

## Returns

0 iff correct, 1 otherwise

**13.292.2.3 test\_pluq()**

```
template<class Field , FFLAS_DIAG diag, class RandIter >
bool test_pluq (
 const Field & F,
 typename Field::ConstElement_ptr A,
 size_t r,
 size_t m,
 size_t n,
 size_t lda,
 RandIter & G)
```

Tests the LUdivine routine.

## Template Parameters

|              |                    |
|--------------|--------------------|
| <i>Field</i> | Field              |
| <i>Diag</i>  | Unit diagonal in U |
| <i>Trans</i> |                    |

## Parameters

|            |                       |
|------------|-----------------------|
| <i>F</i>   | field                 |
| <i>A</i>   | Matrix (preallocated) |
| <i>r</i>   | rank of A             |
| <i>m</i>   | rows                  |
| <i>n</i>   | cols                  |
| <i>lda</i> | leading dim of A      |

## Returns

0 iff correct, 1 otherwise

**13.292.2.4 launch\_test()**

```
template<class Field , FFLAS_DIAG diag, FFLAS_TRANSPOSE trans, class RandIter >
```



```
bool launch_test (
 const Field & F,
 size_t r,
 size_t m,
 size_t n,
 RandIter & G)
```

#### 13.292.2.5 run\_with\_field()

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 uint64_t b,
 size_t m,
 size_t n,
 size_t r,
 size_t iters,
 uint64_t seed)
```

#### 13.292.2.6 main()

```
int main (
 int argc,
 char ** argv)
```

### 13.292.3 Variable Documentation

#### 13.292.3.1 tperm

Givaro::Timer tperm

#### 13.292.3.2 tgemm

Givaro::Timer tgemm

#### 13.292.3.3 tBC

Givaro::Timer tBC

#### 13.292.3.4 ttrsm

Givaro::Timer ttrsm

#### 13.292.3.5 trest

Givaro::Timer trest

#### 13.292.3.6 timtot

Givaro::Timer timtot

#### 13.292.3.7 mvcnt

size\_t mvcnt = 0

## 13.293 test-maxdelayeddim.C File Reference

```
#include <givaro/modular.h>
#include <recint/rint.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include <stdlib.h>
#include <stdio.h>
```

### Macros

- #define [MAX\\_WITH\\_SIZE\\_T](#)(x) ( (static\_cast<uint64\_t>(std::numeric\_limits<size\_t>::max()) < x)? std::numeric\_limits<size\_t>::max() : x )

### Functions

- template<class [Field](#) >  
bool [test](#) (Givaro::Integer p, size\_t kmax)
- int [main](#) ()

### 13.293.1 Macro Definition Documentation

#### 13.293.1.1 MAX\_WITH\_SIZE\_T

```
#define MAX_WITH_SIZE_T(
 x) ((static_cast<uint64_t>(std::numeric_limits<size_t>::max()) < x)? std::numeric_limits<size_t>::max() : x)
```

### 13.293.2 Function Documentation

#### 13.293.2.1 test()

```
template<class Field >
bool test (
 Givaro::Integer p,
 size_t kmax)
```

#### 13.293.2.2 main()

```
int main (
 void)
```

## 13.294 test-minpoly.C File Reference

```
#include <iomanip>
#include <iostream>
#include <random>
#include <chrono>
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include <givaro/modular-integer.h>
#include <givaro/givpoly1factor.h>
```

```
#include <givaro/givpoly1.h>
```

## Functions

- template<typename [Field](#) , class RandIter >  
bool [check\\_minpoly](#) (const [Field](#) &F, size\_t n, RandIter &G)
- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, size\_t b, size\_t n, size\_t iters, uint64\_t seed)
- int [main](#) (int argc, char \*\*argv)

## 13.294.1 Function Documentation

### 13.294.1.1 [check\\_minpoly\(\)](#)

```
template<typename Field , class RandIter >
bool check_minpoly (
 const Field & F,
 size_t n,
 RandIter & G)
```

### 13.294.1.2 [run\\_with\\_field\(\)](#)

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 size_t b,
 size_t n,
 size_t iters,
 uint64_t seed)
```

### 13.294.1.3 [main\(\)](#)

```
int main (
 int argc,
 char ** argv)
```

## 13.295 test-multifile1.C File Reference

```
#include "fflas-ffpack/fflas-ffpack.h"
```

## 13.296 test-multifile2.C File Reference

```
#include "fflas-ffpack/fflas-ffpack.h"
```

## Functions

- int [main](#) (void)

## 13.296.1 Function Documentation

### 13.296.1.1 [main\(\)](#)

```
int main (
 void)
```

## 13.297 test-nullspace.C File Reference

```
#include <iomanip>
#include <iostream>
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/timer.h"
```

### Functions

- template<class [Field](#) >  
std::string [checkingMessage](#) (const [Field](#) &F)
- template<class [Field](#) >  
[Field::Element\\_ptr](#) [readOrRandomMatrixWithRankAndRandomRPM](#) (const [Field](#) &F, std::string file, size\_t m, size\_t n, size\_t lda, size\_t r, uint64\_t seed)  
*If file is not empty, read it and set m, n, lda and r.*
- template<class [Field](#) >  
bool [test\\_nullspace](#) ([Field](#) &F, [FFLAS::FFLAS\\_SIDE](#) side, size\_t m, size\_t n, size\_t r, typename [Field::Element\\_ptr](#) A, size\_t lda)
- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, uint64\_t b, size\_t m, size\_t n, size\_t r, size\_t iters, std::string file, uint64\_t &seed)
- int [main](#) (int argc, char \*\*argv)

### 13.297.1 Function Documentation

#### 13.297.1.1 [checkingMessage\(\)](#)

```
template<class Field >
std::string checkingMessage (
 const Field & F)
```

#### 13.297.1.2 [readOrRandomMatrixWithRankAndRandomRPM\(\)](#)

```
template<class Field >
Field::Element_ptr readOrRandomMatrixWithRankAndRandomRPM (
 const Field & F,
 std::string file,
 size_t m,
 size_t n,
 size_t lda,
 size_t r,
 uint64_t seed)
```

If file is not empty, read it and set m, n, lda and r.

Otherwise, generate a random matrix of size m x n with random lda.

#### 13.297.1.3 [test\\_nullspace\(\)](#)

```
template<class Field >
bool test_nullspace (
 Field & F,
 FFLAS::FFLAS_SIDE side,
 size_t m,
 size_t n,
 size_t r,
```

```
typename Field::Element_ptr A,
size_t lda)
```

#### 13.297.1.4 run\_with\_field()

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 uint64_t b,
 size_t m,
 size_t n,
 size_t r,
 size_t iters,
 std::string file,
 uint64_t & seed)
```

#### 13.297.1.5 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.298 test-permutations.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <iostream>
#include <givaro/modular.h>
#include "fflas-ffpack/ffpack/ffpack.h"
```

### Functions

- bool [checkMonotonicApplyP](#) (FFLAS\_SIDE Side, FFLAS\_TRANSPOSE trans, size\_t \*P, size\_t N, size\_t R)
- int [main](#) ()

### Variables

- Givaro::Timer [tperm](#)
- Givaro::Timer [tgemm](#)
- Givaro::Timer [tBC](#)
- Givaro::Timer [ttrsm](#)
- Givaro::Timer [trest](#)
- Givaro::Timer [timtot](#)

## 13.298.1 Function Documentation

### 13.298.1.1 checkMonotonicApplyP()

```
bool checkMonotonicApplyP (
 FFLAS_SIDE Side,
 FFLAS_TRANSPOSE trans,
 size_t * P,
 size_t N,
 size_t R)
```

### 13.298.1.2 main()

```
int main (
 void)
```

## 13.298.2 Variable Documentation

### 13.298.2.1 tperm

Givaro::Timer tperm

### 13.298.2.2 tgemm

Givaro::Timer tgemm

### 13.298.2.3 tBC

Givaro::Timer tBC

### 13.298.2.4 ttrsm

Givaro::Timer ttrsm

### 13.298.2.5 trest

Givaro::Timer trest

### 13.298.2.6 timtot

Givaro::Timer timtot

## 13.299 test-pluq-check.C File Reference

```
#include <iostream>
#include <stdlib.h>
#include <time.h>
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
```

### Macros

- `#define` [ENABLE\\_ALL\\_CHECKINGS](#) 1

### Functions

- `int` [main](#) (`int` argc, `char **`argv)

## 13.299.1 Macro Definition Documentation

### 13.299.1.1 ENABLE\_ALL\_CHECKINGS

```
#define ENABLE_ALL_CHECKINGS 1
```

## 13.299.2 Function Documentation

### 13.299.2.1 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.300 test-quasisep.C File Reference

```
#include "fflas-ffpack/fflas-ffpack-config.h"
#include <givaro/modular-balanced.h>
#include <iostream>
#include <iomanip>
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utis/test-utis.h"
#include "fflas-ffpack/utis/args-parser.h"
#include <random>
```

### Functions

- template<class [Field](#), [FFLAS\\_DIAG](#) diag, class RandIter >  
bool [test\\_BruhatGenerator](#) (const [Field](#) &F, size\_t n, size\_t r, size\_t t, typename [Field::ConstElement\\_ptr](#) A, size\_t lda, typename [Field::Element\\_ptr](#) TS, size\_t l, RandIter &G)
- template<class [Field](#), [FFLAS\\_DIAG](#) diag, class RandIter >  
bool [launch\\_test](#) (const [Field](#) &F, size\_t n, size\_t r, size\_t t, size\_t l, RandIter &G)
- template<class [Field](#), class RandGen >  
bool [testLTQSRPM](#) (const [Field](#) &F, size\_t n, size\_t r, size\_t t, RandGen &G)
- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, uint64\_t b, size\_t n, size\_t r, size\_t t, size\_t l, size\_t iters, uint64\_t seed)
- int [main](#) (int argc, char \*\*argv)

### 13.300.1 Function Documentation

#### 13.300.1.1 test\_BruhatGenerator()

```
template<class Field, FFLAS_DIAG diag, class RandIter >
bool test_BruhatGenerator (
 const Field & F,
 size_t n,
 size_t r,
 size_t t,
 typename Field::ConstElement_ptr A,
 size_t lda,
 typename Field::Element_ptr TS,
 size_t l,
 RandIter & G)
```

#### 13.300.1.2 launch\_test()

```
template<class Field, FFLAS_DIAG diag, class RandIter >
bool launch_test (
 const Field & F,
 size_t n,
 size_t r,
 size_t t,
 size_t l,
 RandIter & G)
```

#### 13.300.1.3 testLTQSRPM()

```
template<class Field, class RandGen >
bool testLTQSRPM (
 const Field & F,
```

```

 size_t n,
 size_t r,
 size_t t,
 RandGen & G)

```

#### 13.300.1.4 run\_with\_field()

```

template<class Field >
bool run_with_field (
 Givaro::Integer q,
 uint64_t b,
 size_t n,
 size_t r,
 size_t t,
 size_t l,
 size_t iters,
 uint64_t seed)

```

#### 13.300.1.5 main()

```

int main (
 int argc,
 char ** argv)

```

## 13.301 test-rankprofiles.C File Reference

```

#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/ffpack/ffpack.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <givaro/modular.h>
#include <iostream>
#include <iomanip>
#include <random>
#include <chrono>

```

### Macros

- `#define __FFLASFFPACK_SEQUENTIAL`

### Functions

- `template<class Field >`  
`bool run_with_field (Givaro::Integer q, uint64_t b, size_t m, size_t n, size_t r, size_t iters, uint64_t seed, bool par)`
- `int main (int argc, char **argv)`

### 13.301.1 Macro Definition Documentation

#### 13.301.1.1 \_\_FFLASFFPACK\_SEQUENTIAL

```
#define __FFLASFFPACK_SEQUENTIAL
```

### 13.301.2 Function Documentation

#### 13.301.2.1 run\_with\_field()

```
template<class Field >
```



```
bool run_with_field (
 Givaro::Integer q,
 uint64_t b,
 size_t m,
 size_t n,
 size_t r,
 size_t iters,
 uint64_t seed,
 bool par)
```

### 13.301.2.2 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.302 test-rpm.C File Reference

```
#include <iostream>
#include "givaro/modular.h"
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/ffpack/ffpack.h"
```

### Functions

- bool [checkRPM](#) (size\_t M, size\_t N, size\_t R)
- bool [checkSymmetricRPM](#) (size\_t N, size\_t R)
- int [main](#) (int argc, char \*\*argv)

### 13.302.1 Function Documentation

#### 13.302.1.1 checkRPM()

```
bool checkRPM (
 size_t M,
 size_t N,
 size_t R)
```

#### 13.302.1.2 checkSymmetricRPM()

```
bool checkSymmetricRPM (
 size_t N,
 size_t R)
```

#### 13.302.1.3 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.303 test-simd.C File Reference

```
#include "givaro/givinteger.h"
#include "givaro/modular.h"
#include "fflas-ffpack/fflas-ffpack-config.h"
```

```

#include "fflas-ffpack/fflas/fflas_simd.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/align-allocator.h"
#include <array>
#include <vector>
#include <random>
#include <string>
#include <functional>
#include <limits>
#include <type_traits>
#include <algorithm>

```

## Data Structures

- struct [ALL< true, v... >](#)
- struct [ALL< false, v... >](#)
- struct [ALL<>](#)
- struct [count\\_nonconst\\_lvalue\\_reference< T, O... >](#)
- struct [count\\_nonconst\\_lvalue\\_reference< T &, O... >](#)
- struct [count\\_nonconst\\_lvalue\\_reference< const T &, O... >](#)
- struct [count\\_nonconst\\_lvalue\\_reference<>](#)
- struct [is\\_all\\_same< T, Args... >](#)
- struct [is\\_all\\_same<>](#)
- struct [width< T >](#)
- struct [width< float >](#)
- struct [width< double >](#)
- class [TestOneMethod< Simd >](#)
- struct [ScalFunctionsBase< Element, typename enable\\_if< is\\_floating\\_point< Element >::value >::type >](#)
- class [ScalFunctionsBase< Element, typename enable\\_if< is\\_floating\\_point< Element >::value >::type >::FloatingPointTestD](#)
- struct [ScalFunctionsBase< Element, typename enable\\_if< is\\_integral< Element >::value >::type >](#)
- struct [ScalFunctions< Element >](#)

## Macros

- [#define \\_TEST\\_ONE\(K, f1, f2, r, n\)](#)
- [#define TEST\\_ONE\\_OP\(f\)](#)
- [#define TEST\\_ONE\\_OP\\_WZ\(f\)](#)
- [#define TEST\\_IMPL\(SIZE, Elt\)](#)

## Functions

- [template<typename Element > enable\\_if< is\\_integral< Element >::value, bool >::type \[check\\\_eq\]\(#\) \(Element x, Element y\)](#)
- [template<typename Element > enable\\_if< is\\_floating\\_point< Element >::value, bool >::type \[check\\\_eq\]\(#\) \(Element x, Element y\)](#)
- [template<typename Element > bool \[cmp\]\(#\) \(vector< Element > out\\_scal, vector< Element > out\\_simd\)](#)
- [template<typename Ret , typename T > Ret \[eval\\\_func\\\_on\\\_array\]\(#\) \(function< Ret\(\)> f, array< T, 0 > &arr\)](#)
- [template<typename T , typename... TArgs> void \[eval\\\_func\\\_on\\\_array\]\(#\) \(function< void\(T, TArgs...\)> f, array< typename decay< T >::type, sizeof...\(TArgs\)+1 > &arr\)](#)
- [template<typename Ret , typename T , typename... TArgs> Ret \[eval\\\_func\\\_on\\\_array\]\(#\) \(function< Ret\(T, TArgs...\)> f, array< typename decay< T >::type, sizeof...\(TArgs\)+1 > &arr\)](#)

- `template<typename E >`  
`std::ostream & operator<< (std::ostream &o, const vector< E > &V)`
- `template<typename Simd, typename Element >`  
`enable_if< is_floating_point< Element >::value, bool >::type test_impl_base ()`
- `template<typename Simd, typename Element >`  
`enable_if< is_integral< Element >::value, bool >::type test_impl_base ()`
- `template<typename Simd, typename Element >`  
`bool test_impl ()`
- `int main (int argc, char *argv[])`

## 13.303.1 Macro Definition Documentation

### 13.303.1.1 \_TEST\_ONE

```
#define _TEST_ONE(
```

```
 K,
 f1,
 f2,
 r,
 n)
```

Value:

```
do { \
 K T(f1, f2, r, n); \
 bool b = T.writeResultLine(); \
 if (b == false) \
 T.writeDebugData(); \
 btest &= b; \
} while (0)
```

### 13.303.1.2 TEST\_ONE\_OP

```
#define TEST_ONE_OP(
```

```
 f)
```

Value:

```
_TEST_ONE(TestOneMethod<Simd>, \
function<decltype(Simd::f)>(Simd::f), \
function<decltype(Scal::f)>(Scal::f), \
function<decltype(Scal::genInputs)>(Scal::genInputs), #f)
```

### 13.303.1.3 TEST\_ONE\_OP\_WZ

```
#define TEST_ONE_OP_WZ(
```

```
 f)
```

Value:

```
_TEST_ONE(TestOneMethod<Simd>, \
function<decltype(Simd::f)>(Simd::f), \
function<decltype(Scal::f)>(Scal::f), \
function<decltype(Scal::genInputsWithZero)>(Scal::genInputsWithZero), \
#f " test with zero")
```

### 13.303.1.4 TEST\_IMPL

```
#define TEST_IMPL(
```

```
 SIZE,
 Elt)
```

Value:

```
do { \
 pass &= test_impl<Simd##SIZE<Elt>, Elt>(); \
 cout << endl; \
} while (0)
```

## 13.303.2 Function Documentation

### 13.303.2.1 check\_eq() [1/2]

```
template<typename Element >
```

```
enable_if< is_integral< Element >::value, bool >::type check_eq (
 Element x,
 Element y)
```

#### 13.303.2.2 check\_eq() [2/2]

```
template<typename Element >
enable_if< is_floating_point< Element >::value, bool >::type check_eq (
 Element x,
 Element y)
```

#### 13.303.2.3 cmp()

```
template<typename Element >
bool cmp (
 vector< Element > out_scal,
 vector< Element > out_simd)
```

#### 13.303.2.4 eval\_func\_on\_array() [1/3]

```
template<typename Ret , typename T >
Ret eval_func_on_array (
 function< Ret ()> f,
 array< T, 0 > & arr)
```

#### 13.303.2.5 eval\_func\_on\_array() [2/3]

```
template<typename T , typename... TArgs>
void eval_func_on_array (
 function< void(T, TArgs...)> f,
 array< typename decay< T >::type, sizeof...(TArgs)+1 > & arr)
```

#### 13.303.2.6 eval\_func\_on\_array() [3/3]

```
template<typename Ret , typename T , typename... TArgs>
Ret eval_func_on_array (
 function< Ret(T, TArgs...)> f,
 array< typename decay< T >::type, sizeof...(TArgs)+1 > & arr)
```

#### 13.303.2.7 operator<<()

```
template<typename E >
std::ostream & operator<< (
 std::ostream & o,
 const vector< E > & V)
```

#### 13.303.2.8 test\_impl\_base() [1/2]

```
template<typename Simd , typename Element >
enable_if< is_floating_point< Element >::value, bool >::type test_impl_base ()
```

#### 13.303.2.9 test\_impl\_base() [2/2]

```
template<typename Simd , typename Element >
enable_if< is_integral< Element >::value, bool >::type test_impl_base ()
```

#### 13.303.2.10 test\_impl()

```
template<typename Simd , typename Element >
bool test_impl ()
```

**13.303.2.11 main()**

```
int main (
 int argc,
 char * argv[])
```

**13.304 test-solve.C File Reference**

```
#include <givaro/modular-integer.h>
#include <iomanip>
#include <iostream>
#include "fflas-ffpack/utils/timer.h"
#include "fflas-ffpack/fflas/fflas.h"
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
```

**Functions**

- template<typename [Field](#) , class RandIter >  
bool [check\\_solve](#) (const [Field](#) &F, size\_t m, RandIter &Rand, bool isParallel)
- template<class [Field](#) >  
bool [run\\_with\\_field](#) (Givaro::Integer q, size\_t b, size\_t m, size\_t iters, uint64\_t seed)
- int [main](#) (int argc, char \*\*argv)

**13.304.1 Function Documentation****13.304.1.1 check\_solve()**

```
template<typename Field , class RandIter >
bool check_solve (
 const Field & F,
 size_t m,
 RandIter & Rand,
 bool isParallel)
```

**13.304.1.2 run\_with\_field()**

```
template<class Field >
bool run_with_field (
 Givaro::Integer q,
 size_t b,
 size_t m,
 size_t iters,
 uint64_t seed)
```

**13.304.1.3 main()**

```
int main (
 int argc,
 char ** argv)
```

**13.305 test-storage-transpose.C File Reference**

```
#include <iomanip>
#include <iostream>
```

```
#include <random>
#include "fflas-ffpack/utils/args-parser.h"
#include "fflas-ffpack/utils/test-utils.h"
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/fflas_memory.h"
#include <givaro/modular.h>
#include <recint/rint.h>
#include "fflas-ffpack/fflas/fflas_transpose.h"
```

## Data Structures

- class [Test< Elt >](#)

## Functions

- int [main](#) (int argc, char \*\*argv)

### 13.305.1 Function Documentation

#### 13.305.1.1 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.306 101-fgemm.C File Reference

```
#include <fflas-ffpack/fflas-ffpack-config.h>
#include <givaro/modular-balanced.h>
#include <fflas-ffpack/fflas/fflas.h>
#include <fflas-ffpack/utils/timer.h>
#include <fflas-ffpack/utils/fflas_io.h>
#include <fflas-ffpack/utils/args-parser.h>
#include <iostream>
```

## Functions

- int [main](#) (int argc, char \*\*argv)

### 13.306.1 Function Documentation

#### 13.306.1.1 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.307 2x2-fgemm.C File Reference

```
#include <fflas-ffpack/fflas-ffpack-config.h>
#include <givaro/modular-balanced.h>
#include <fflas-ffpack/fflas/fflas.h>
#include <fflas-ffpack/utils/timer.h>
#include <fflas-ffpack/utils/fflas_io.h>
#include <fflas-ffpack/utils/args-parser.h>
```

```
#include <iostream>
```

## Functions

- int [main](#) (int argc, char \*\*argv)

### 13.307.1 Function Documentation

#### 13.307.1.1 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.308 2x2-fftrsv.C File Reference

```
#include <fflas-ffpack/fflas-ffpack-config.h>
#include <givaro/modular-balanced.h>
#include <fflas-ffpack/fflas/fflas.h>
#include <fflas-ffpack/utils/timer.h>
#include <fflas-ffpack/utils/fflas_io.h>
#include <fflas-ffpack/utils/args-parser.h>
#include <iostream>
#include <array>
```

## Functions

- int [main](#) (int argc, char \*\*argv)

### 13.308.1 Function Documentation

#### 13.308.1.1 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.309 2x2-pluq.C File Reference

```
#include <iostream>
#include <vector>
#include <givaro/modular.h>
#include "fflas-ffpack/fflas-ffpack-config.h"
#include "fflas-ffpack/fflas-ffpack.h"
#include "fflas-ffpack/utils/fflas_io.h"
```

## Functions

- int [main](#) (int argc, char \*\*argv)

### 13.309.1 Function Documentation

#### 13.309.1.1 main()

```
int main (

```

```
int argc,
char ** argv)
```

## 13.310 fflas-101\_1.C File Reference

```
#include <fflas-ffpack/fflas/fflas.h>
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/fflas_io.h"
#include <iostream>
```

### Functions

- int [main](#) (int argc, char \*\*argv)

### 13.310.1 Function Documentation

#### 13.310.1.1 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.311 fflas-101\_3.C File Reference

```
#include <fflas-ffpack/fflas/fflas.h>
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/fflas_io.h"
#include "fflas-ffpack/utils/fflas_randommatrix.h"
#include <iostream>
```

### Functions

- int [main](#) (int argc, char \*\*argv)

### 13.311.1 Function Documentation

#### 13.311.1.1 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.312 fflas\_101.C File Reference

```
#include <fflas-ffpack/fflas/fflas.h>
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include <iostream>
```

### Functions

- int [main](#) (int argc, char \*\*argv)



### 13.312.1 Function Documentation

#### 13.312.1.1 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.313 fflas\_101\_lvl1.C File Reference

```
#include <fflas-ffpack/fflas/fflas.h>
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include <iostream>
#include "fflas-ffpack/utils/fflas_io.h"
```

### Functions

- int [main](#) (int argc, char \*\*argv)

### 13.313.1 Function Documentation

#### 13.313.1.1 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.314 ffpack-fgesv.C File Reference

```
#include <fflas-ffpack/fflas/fflas.h>
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/fflas_io.h"
#include <fflas-ffpack/ffpack/ffpack.h>
#include <iostream>
```

### Functions

- int [main](#) (int argc, char \*\*argv)

### 13.314.1 Function Documentation

#### 13.314.1.1 main()

```
int main (
 int argc,
 char ** argv)
```

## 13.315 ffpack-solve.C File Reference

```
#include <fflas-ffpack/fflas/fflas.h>
#include <givaro/modular.h>
#include <givaro/modular-balanced.h>
#include "fflas-ffpack/utils/fflas_io.h"
#include <fflas-ffpack/ffpack/ffpack.h>
```

```
#include <iostream>
```

## Functions

- int `main` (int argc, char \*\*argv)

### 13.315.1 Function Documentation

#### 13.315.1.1 `main()`

```
int main (
 int argc,
 char ** argv)
```

PS: the function Solve will modify the matrix A so here we used a duplicate matrix A2 otherwise  $A*x$  will not be equal to b for the later verification stage

# Index

- [\\_F](#)
  - [RNSIntegerMod< RNS >, 555](#)
- [\\_M](#)
  - [rns\\_double, 534](#)
  - [rns\\_double\\_extended, 545](#)
- [\\_MAX\\_SIZE\\_MATRICES](#)
  - [benchmark-checkers.C, 785](#)
- [\\_MMi](#)
  - [rns\\_double, 535](#)
  - [rns\\_double\\_extended, 545](#)
- [\\_Mi](#)
  - [rns\\_double, 534](#)
  - [rns\\_double\\_extended, 545](#)
- [\\_Mi\\_modp\\_rns](#)
  - [RNSIntegerMod< RNS >, 555](#)
- [\\_NR\\_TESTS](#)
  - [benchmark-checkers.C, 785](#)
- [\\_PLUQ](#)
  - [FFPACK, 368](#)
- [\\_RNSdelayed](#)
  - [RNSIntegerMod< RNS >, 556](#)
- [\\_TEST\\_ONE](#)
  - [test-simd.C, 1107](#)
- [\\_\\_FFLASFFPACK\\_ARITHPROG\\_THRESHOLD](#)
  - [fflas-ffpack-default-thresholds.h, 832](#)
- [\\_\\_FFLASFFPACK\\_CACHE\\_LINE\\_SIZE](#)
  - [fflas\\_sparse.h, 892](#)
- [\\_\\_FFLASFFPACK\\_CHARPOLY\\_Danilevskii\\_LUKrylov\\_THRESHOLD](#)
  - [fflas-ffpack-default-thresholds.h, 832](#)
- [\\_\\_FFLASFFPACK\\_CHARPOLY\\_LUKrylov\\_ArithProg\\_THRESHOLD](#)
  - [fflas-ffpack-default-thresholds.h, 832](#)
- [\\_\\_FFLASFFPACK\\_CONFIGURATION](#)
  - [cblas.C, 1056](#)
  - [clapack.C, 1057](#)
  - [fblas.C, 1058](#)
  - [lapack.C, 1058](#)
- [\\_\\_FFLASFFPACK\\_DIMKPENALTY](#)
  - [fflas\\_pfgemm.inl, 877](#)
- [\\_\\_FFLASFFPACK\\_FORCE\\_SEQ](#)
  - [benchmark-charpoly-mp.C, 784](#)
- [\\_\\_FFLASFFPACK\\_FSYRK\\_THRESHOLD](#)
  - [fflas-ffpack-default-thresholds.h, 832](#)
- [\\_\\_FFLASFFPACK\\_FSYTRF\\_THRESHOLD](#)
  - [fflas-ffpack-default-thresholds.h, 832](#)
- [\\_\\_FFLASFFPACK\\_FTRSSYR2K\\_THRESHOLD](#)
  - [ffpack.h, 930](#)
- [\\_\\_FFLASFFPACK\\_FTRSTR\\_THRESHOLD](#)
  - [ffpack.h, 930](#)
- [\\_\\_FFLASFFPACK\\_FTRTRI\\_THRESHOLD](#)
  - [fflas-ffpack-default-thresholds.h, 832](#)
- [\\_\\_FFLASFFPACK\\_GAUSSJORDAN\\_BASECASE](#)
  - [ffpack\\_echelonforms.inl, 938](#)
  - [test-echelon.C, 1064](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_BLAS](#)
  - [fflas-ffpack/config.h, 813](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_CBLAS](#)
  - [cblas.C, 1056](#)
  - [fflas-ffpack/config.h, 813](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_CLAPACK](#)
  - [clapack.C, 1057](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_CXX11](#)
  - [fflas-ffpack/config.h, 813](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_DGETRF](#)
  - [benchmark-dgetrf.C, 787](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_DLFCN\\_H](#)
  - [fflas-ffpack/config.h, 813](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_DTRTRI](#)
  - [benchmark-dtrtri.C, 790](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_FLOAT\\_H](#)
  - [fflas-ffpack/config.h, 813](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_INT128](#)
  - [fflas-ffpack/config.h, 813](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_INTTYPES\\_H](#)
  - [fflas-ffpack/config.h, 813](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_LAPACK](#)
  - [clapack.C, 1057](#)
  - [fflas-ffpack/config.h, 813](#)
  - [lapack.C, 1058](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_LIMITS\\_H](#)
  - [fflas-ffpack/config.h, 813](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_LITTLE\\_ENDIAN](#)
  - [fflas-ffpack/config.h, 813](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_PTHREAD\\_H](#)
  - [fflas-ffpack/config.h, 813](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_STDDEF\\_H](#)
  - [fflas-ffpack/config.h, 814](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_STDINT\\_H](#)
  - [fflas-ffpack/config.h, 814](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_STDIO\\_H](#)
  - [fflas-ffpack/config.h, 814](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_STDLIB\\_H](#)
  - [fflas-ffpack/config.h, 814](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_STRINGS\\_H](#)
  - [fflas-ffpack/config.h, 814](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_STRING\\_H](#)
  - [fflas-ffpack/config.h, 814](#)
- [\\_\\_FFLASFFPACK\\_HAVE\\_SYS\\_STAT\\_H](#)
  - [fflas-ffpack/config.h, 814](#)

- \_\_FFLASFFPACK\_HAVE\_SYS\_TIME\_H  
fflas-ffpack/config.h, [814](#)
- \_\_FFLASFFPACK\_HAVE\_SYS\_TYPES\_H  
fflas-ffpack/config.h, [814](#)
- \_\_FFLASFFPACK\_HAVE\_UNISTD\_H  
fflas-ffpack/config.h, [814](#)
- \_\_FFLASFFPACK\_KAAPI\_ROUTINES\_INL  
kaapi\_routines.inl, [1038](#)
- \_\_FFLASFFPACK\_LT\_OBJDIR  
fflas-ffpack/config.h, [814](#)
- \_\_FFLASFFPACK\_MINBLOCKCUTS  
blockcuts.inl, [1037](#)
- \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET  
benchmark-charpoly.C, [784](#)  
benchmark-fadd-lvl2.C, [790](#)  
benchmark-fdot.C, [791](#)  
benchmark-fgemm-mp.C, [792](#)  
benchmark-fgemm-rns.C, [793](#)  
benchmark-fgemv-mp.C, [795](#)  
benchmark-fgemv.C, [797](#)  
benchmark-fgesv.C, [799](#)  
benchmark-fsyrk.C, [800](#)  
benchmark-fsytrf.C, [801](#)  
benchmark-ftrsm-mp.C, [802](#)  
benchmark-ftrsm.C, [802](#)  
benchmark-ftrsv.C, [803](#)  
benchmark-ftrtri.C, [803](#)  
benchmark-pluq.C, [806](#)  
benchmark-quasisep.C, [807](#)
- \_\_FFLASFFPACK\_OPENBLAS\_NUM\_THREADS  
fflas-ffpack/config.h, [814](#)
- \_\_FFLASFFPACK\_PACKAGE  
fflas-ffpack/config.h, [814](#)
- \_\_FFLASFFPACK\_PACKAGE\_BUGREPORT  
fflas-ffpack/config.h, [814](#)
- \_\_FFLASFFPACK\_PACKAGE\_NAME  
fflas-ffpack/config.h, [814](#)
- \_\_FFLASFFPACK\_PACKAGE\_STRING  
fflas-ffpack/config.h, [815](#)
- \_\_FFLASFFPACK\_PACKAGE\_TARNAME  
fflas-ffpack/config.h, [815](#)
- \_\_FFLASFFPACK\_PACKAGE\_URL  
fflas-ffpack/config.h, [815](#)
- \_\_FFLASFFPACK\_PACKAGE\_VERSION  
fflas-ffpack/config.h, [815](#)
- \_\_FFLASFFPACK\_PLUQ\_THRESHOLD  
fflas-ffpack-default-thresholds.h, [832](#)  
test-echelon.C, [1064](#)
- \_\_FFLASFFPACK\_SEQPARTHRESHOLD  
fflas\_pfgemm.inl, [877](#)
- \_\_FFLASFFPACK\_SEQUENTIAL  
parallel.h, [1039](#)  
test-echelon.C, [1064](#)  
test-ftrmm.C, [1084](#)  
test-ftrmv.C, [1085](#)  
test-ftrsm.C, [1087](#)  
test-ftrsv.C, [1090](#)  
test-ftrtri.C, [1091](#)  
test-lu.C, [1094](#)  
test-rankprofiles.C, [1104](#)
- \_\_FFLASFFPACK\_SIZEOF\_CHAR  
fflas-ffpack/config.h, [815](#)
- \_\_FFLASFFPACK\_SIZEOF\_INT  
fflas-ffpack/config.h, [815](#)
- \_\_FFLASFFPACK\_SIZEOF\_LONG  
fflas-ffpack/config.h, [815](#)
- \_\_FFLASFFPACK\_SIZEOF\_LONG\_LONG  
fflas-ffpack/config.h, [815](#)
- \_\_FFLASFFPACK\_SIZEOF\_SHORT  
fflas-ffpack/config.h, [815](#)
- \_\_FFLASFFPACK\_SIZEOF\_\_INT64\_T  
fflas-ffpack/config.h, [815](#)
- \_\_FFLASFFPACK\_STDC\_HEADERS  
fflas-ffpack/config.h, [815](#)
- \_\_FFLASFFPACK\_USE\_OPENMP  
fflas-ffpack/config.h, [815](#)
- \_\_FFLASFFPACK\_VERSION  
fflas-ffpack/config.h, [815](#)
- \_\_FFLASFFPACK\_WINOTHRESHOLD  
fflas-ffpack-default-thresholds.h, [831](#)
- \_\_FFLASFFPACK\_WINOTHRESHOLD\_BAL  
fflas-ffpack-default-thresholds.h, [831](#)
- \_\_FFLASFFPACK\_WINOTHRESHOLD\_BAL\_FLT  
fflas-ffpack-default-thresholds.h, [832](#)
- \_\_FFLASFFPACK\_WINOTHRESHOLD\_FLT  
fflas-ffpack-default-thresholds.h, [831](#)
- \_\_FFLASFFPACK\_charpoly\_INL  
ffpack\_charpoly.inl, [933](#)
- \_\_FFLASFFPACK\_checker\_charpoly\_INL  
checker\_charpoly.inl, [820](#)
- \_\_FFLASFFPACK\_checker\_det\_INL  
checker\_det.inl, [820](#)
- \_\_FFLASFFPACK\_checker\_fgemm\_INL  
checker\_fgemm.inl, [821](#)
- \_\_FFLASFFPACK\_checker\_ftrsm\_INL  
checker\_ftrsm.inl, [821](#)
- \_\_FFLASFFPACK\_checker\_invert\_INL  
checker\_invert.inl, [822](#)
- \_\_FFLASFFPACK\_checker\_pluq\_INL  
checker\_pluq.inl, [822](#)
- \_\_FFLASFFPACK\_fadd\_INL  
fflas\_fadd.inl, [838](#)
- \_\_FFLASFFPACK\_fassign\_INL  
fflas\_fassign.inl, [839](#)
- \_\_FFLASFFPACK\_faxpy\_INL  
fflas\_faxpy.inl, [840](#)
- \_\_FFLASFFPACK\_fdot\_INL  
fflas\_fdot.inl, [841](#)
- \_\_FFLASFFPACK\_fflas\_blockcuts\_INL  
blockcuts.inl, [1037](#)
- \_\_FFLASFFPACK\_fflas\_bounds\_INL  
fflas\_bounds.inl, [835](#)
- \_\_FFLASFFPACK\_fflas\_fflas\_fgemm\_winograd\_INL  
fgemm\_winograd.inl, [846](#)
- \_\_FFLASFFPACK\_fflas\_fflas\_level1\_INL  
fflas\_level1.inl, [872](#)

- \_\_FFLASFFPACK\_fflas\_fflas\_level2\_INL  
fflas\_level2.inl, [874](#)
- \_\_FFLASFFPACK\_fflas\_fflas\_level3\_INL  
fflas\_level3.inl, [877](#)
- \_\_FFLASFFPACK\_fflas\_fflas\_mmhelper\_INL  
fflas\_helpers.inl, [866](#)
- \_\_FFLASFFPACK\_fflas\_fflas\_sparse\_INL  
fflas\_sparse.inl, [894](#)
- \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd128\_INL  
simd128.inl, [880](#)
- \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd128\_double\_INL  
simd128\_double.inl, [881](#)
- \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd128\_float\_INL  
simd128\_float.inl, [881](#)
- \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd128\_int16\_INL  
simd128\_int16.inl, [882](#)
- \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd128\_int32\_INL  
simd128\_int32.inl, [882](#)
- \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd128\_int64\_INL  
simd128\_int64.inl, [883](#)
- \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd256\_INL  
simd256.inl, [883](#)
- \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd256\_double\_INL  
simd256\_double.inl, [884](#)
- \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd256\_float\_INL  
simd256\_float.inl, [884](#)
- \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd256\_int16\_INL  
simd256\_int16.inl, [885](#)
- \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd256\_int32\_INL  
simd256\_int32.inl, [885](#)
- \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd256\_int64\_INL  
simd256\_int64.inl, [885](#)
- \_\_FFLASFFPACK\_fflas\_freduce\_INL  
fflas\_freduce.inl, [856](#)
- \_\_FFLASFFPACK\_fflas\_freduce\_mp\_INL  
fflas\_freduce\_mp.inl, [856](#)
- \_\_FFLASFFPACK\_fflas\_fsy2k\_INL  
fflas\_fsy2k.inl, [860](#)
- \_\_FFLASFFPACK\_fflas\_fsyrk\_INL  
fflas\_fsyrk.inl, [862](#)
- \_\_FFLASFFPACK\_fflas\_fsyrk\_strassen\_INL  
fflas\_fsyrk\_strassen.inl, [863](#)
- \_\_FFLASFFPACK\_fflas\_igemm\_igemm\_INL  
igemm.inl, [867](#)
- \_\_FFLASFFPACK\_fflas\_igemm\_igemm\_kernels\_INL  
igemm\_kernels.inl, [869](#)
- \_\_FFLASFFPACK\_fflas\_igemm\_igemm\_tools\_INL  
igemm\_tools.inl, [869](#)
- \_\_FFLASFFPACK\_fflas\_pfgemm\_INL  
fflas\_pfgemm.inl, [877](#)
- \_\_FFLASFFPACK\_fflas\_pftsrsm\_INL  
fflas\_pftsrsm.inl, [878](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_pspmm\_INL  
csr\_hyb\_pspmm.inl, [903](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_pspmv\_INL  
csr\_hyb\_pspmv.inl, [903](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_spm INL  
csr\_hyb\_spm.inl, [904](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_spmv\_INL  
csr\_hyb\_spmv.inl, [904](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_utils\_INL  
csr\_hyb\_utils.inl, [905](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_pspmm\_INL  
csr\_pspmm.inl, [898](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_pspmv\_INL  
csr\_pspmv.inl, [899](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_spm INL  
csr\_spm.inl, [900](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_spmv\_INL  
csr\_spmv.inl, [901](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_pspmm\_INL  
ell\_pspmm.inl, [906](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_pspmv\_INL  
ell\_pspmv.inl, [907](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_simd\_pspmv\_INL  
ell\_simd\_pspmv.inl, [910](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_simd\_spmv\_INL  
ell\_simd\_spmv.inl, [911](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_simd\_utils\_INL  
ell\_simd\_utils.inl, [912](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_spm INL  
ell\_spm.inl, [908](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_spmv\_INL  
ell\_spmv.inl, [909](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_utils\_INL  
ell\_utils.inl, [909](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_pspmm\_INL  
hyb\_zo\_pspmm.inl, [913](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_pspmv\_INL  
hyb\_zo\_pspmv.inl, [913](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_spm INL  
hyb\_zo\_spm.inl, [914](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_spmv\_INL  
hyb\_zo\_spmv.inl, [914](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_utils\_INL  
hyb\_zo\_utils.inl, [914](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_coo\_spm INL  
coo\_spm.inl, [896](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_coo\_spmv\_INL  
coo\_spmv.inl, [897](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_coo\_utils\_INL  
coo\_utils.inl, [897](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_sell\_pspmv\_INL  
sell\_pspmv.inl, [916](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_sell\_spmv\_INL  
sell\_spmv.inl, [917](#)
- \_\_FFLASFFPACK\_fflas\_sparse\_sell\_utils\_INL  
sell\_utils.inl, [918](#)
- \_\_FFLASFFPACK\_ffpack\_INL  
ffpack.inl, [931](#)
- \_\_FFLASFFPACK\_ffpack\_bruhatgen\_inl  
ffpack\_bruhatgen.inl, [933](#)
- \_\_FFLASFFPACK\_ffpack\_charpoly\_danilveski\_INL  
ffpack\_charpoly\_danilevski.inl, [934](#)
- \_\_FFLASFFPACK\_ffpack\_charpoly\_kgfast\_INL  
ffpack\_charpoly\_kgfast.inl, [934](#)

- \_\_FFLASFFPACK\_ffpack\_charpoly\_kgfastgeneralized\_INL
  - ffpack\_charpoly\_kgfastgeneralized.inl, 935
- \_\_FFLASFFPACK\_ffpack\_charpoly\_kglu\_INL
  - ffpack\_charpoly\_kglu.inl, 935
- \_\_FFLASFFPACK\_ffpack\_echelon\_forms\_INL
  - ffpack\_echelonforms.inl, 938
- \_\_FFLASFFPACK\_ffpack\_fgesv\_INL
  - ffpack\_fgesv.inl, 938
- \_\_FFLASFFPACK\_ffpack\_fgetrs\_INL
  - ffpack\_fgetrs.inl, 939
- \_\_FFLASFFPACK\_ffpack\_fsytrf\_INL
  - ffpack\_fsytrf.inl, 941
- \_\_FFLASFFPACK\_ffpack\_ftrssyr2k\_INL
  - ffpack\_ftrssyr2k.inl, 941
- \_\_FFLASFFPACK\_ffpack\_ftrstr\_INL
  - ffpack\_ftrstr.inl, 942
- \_\_FFLASFFPACK\_ffpack\_ftrtr\_INL
  - ffpack\_ftrtr.inl, 942
- \_\_FFLASFFPACK\_ffpack\_invert\_INL
  - ffpack\_invert.inl, 943
- \_\_FFLASFFPACK\_ffpack\_krylovelim\_INL
  - ffpack\_krylovelim.inl, 943
- \_\_FFLASFFPACK\_ffpack\_ludivine\_INL
  - ffpack\_ludivine.inl, 944
- \_\_FFLASFFPACK\_ffpack\_minpoly\_INL
  - ffpack\_minpoly.inl, 945
- \_\_FFLASFFPACK\_ffpack\_permutation\_INL
  - ffpack\_permutation.inl, 947
- \_\_FFLASFFPACK\_ffpack\_pluq\_INL
  - ffpack\_pluq.inl, 948
- \_\_FFLASFFPACK\_ffpack\_ppluq\_INL
  - ffpack\_ppluq.inl, 949
- \_\_FFLASFFPACK\_ffpack\_rank\_profiles\_INL
  - ffpack\_rankprofiles.inl, 951
- \_\_FFLASFFPACK\_ffgemm\_INL
  - fflas\_fgemm.inl, 843
- \_\_FFLASFFPACK\_ffgemm\_bini\_INL
  - schedule\_bini.inl, 847
- \_\_FFLASFFPACK\_ffgemm\_winograd\_INL
  - schedule\_winograd.inl, 847
- \_\_FFLASFFPACK\_ffgemm\_winograd\_acc\_INL
  - schedule\_winograd\_acc.inl, 848
- \_\_FFLASFFPACK\_ffgemm\_winograd\_acc\_ip\_INL
  - schedule\_winograd\_acc\_ip.inl, 849
- \_\_FFLASFFPACK\_ffgemm\_winograd\_ip\_INL
  - schedule\_winograd\_ip.inl, 849
- \_\_FFLASFFPACK\_ffgemv\_INL
  - fflas\_ffgemv.inl, 851
- \_\_FFLASFFPACK\_ffgemv\_mp\_INL
  - fflas\_ffgemv\_mp.inl, 852
- \_\_FFLASFFPACK\_ffger\_INL
  - fflas\_ffger.inl, 853
- \_\_FFLASFFPACK\_field\_rns\_INL
  - rns.inl, 957
- \_\_FFLASFFPACK\_field\_rns\_double\_INL
  - rns-double.inl, 955
- \_\_FFLASFFPACK\_field\_rns\_double\_recint\_INL
  - rns-double-recint.inl, 954
- \_\_FFLASFFPACK\_freivalds\_INL
  - fflas\_freivalds.inl, 857
- \_\_FFLASFFPACK\_fscal\_INL
  - fflas\_fscal.inl, 858
- \_\_FFLASFFPACK\_fscal\_mp\_INL
  - fflas\_fscal\_mp.inl, 859
- \_\_FFLASFFPACK\_ftrmm\_INL
  - fflas\_ftrmm.inl, 863
- \_\_FFLASFFPACK\_ftrsm\_INL
  - fflas\_ftrsm.inl, 864
- \_\_FFLASFFPACK\_ftrsv\_INL
  - fflas\_ftrsv.inl, 865
- \_\_FFLASFFPACK\_simd512\_INL
  - simd512.inl, 886
- \_\_FFLASFFPACK\_simd512\_double\_INL
  - simd512\_double.inl, 886
- \_\_FFLASFFPACK\_simd512\_float\_INL
  - simd512\_float.inl, 887
- \_\_FFLASFFPACK\_simd512\_int32\_INL
  - simd512\_int32.inl, 887
- \_\_FFLAS\_L1\_INST\_C
  - fflas\_L1\_inst.C, 969
- \_\_FFLAS\_L2\_INST\_C
  - fflas\_L2\_inst.C, 973
- \_\_FFLAS\_L3\_INST\_C
  - fflas\_L3\_inst.C, 976
- \_\_FFLAS\_\_TRSM\_READONLY
  - fflas\_L3\_inst\_implement.inl, 979
  - fflas\_level3.inl, 877
  - ffpack\_ppluq.inl, 949
- \_\_FFPACK\_FSYTRF\_BC\_CROUT
  - benchmark-fsytrf.C, 801
- \_\_FFPACK\_INST\_C
  - ffpack\_inst.C, 1031
- \_\_FFPACK\_charpoly\_mp\_INL
  - ffpack\_charpoly\_mp.inl, 936
- \_\_FFPACK\_det\_mp\_INL
  - ffpack\_det\_mp.inl, 936
- \_\_FFPACK\_ffgemm\_classical\_INL
  - ffgemm\_classical\_mp.inl, 845
- \_\_FFPACK\_fger\_mp\_INL
  - fflas\_fger\_mp.inl, 853
- \_\_FFPACK\_ftrsm\_mp\_INL
  - fflas\_ftrsm\_mp.inl, 864
- \_\_FFPACK\_ludivine\_mp\_INL
  - ffpack\_ludivine\_mp.inl, 944
- \_\_FFPACK\_pluq\_mp\_INL
  - ffpack\_pluq\_mp.inl, 949
- \_\_LUDIVINE\_CUTOFF
  - test-lu.C, 1095
- \_\_has\_builtin
  - bit\_manipulation.h, 1048
- \_alloc
  - rns\_double\_elt, 536
  - rns\_double\_elt\_cstptr, 539
  - rns\_double\_elt\_ptr, 542
- \_basis
  - rns\_double, 534

- rns\_double\_extended, [545](#)
- \_basisMax
  - rns\_double, [534](#)
  - rns\_double\_extended, [545](#)
- \_coo
  - SpMat< Field, flag >, [761](#)
- \_coo16
  - CooMat< Field >, [439](#)
- \_coo16\_zo
  - CooMat< Field >, [439](#)
- \_coo32
  - CooMat< Field >, [439](#)
- \_coo32\_zo
  - CooMat< Field >, [439](#)
- \_coo64
  - CooMat< Field >, [439](#)
- \_coo64\_zo
  - CooMat< Field >, [439](#)
- \_crt\_in
  - rns\_double, [535](#)
  - rns\_double\_extended, [545](#)
- \_crt\_out
  - rns\_double, [535](#)
  - rns\_double\_extended, [545](#)
- \_csr
  - SpMat< Field, flag >, [761](#)
- \_csr16
  - CsrMat< Field >, [441](#)
- \_csr16\_zo
  - CsrMat< Field >, [441](#)
- \_csr32
  - CsrMat< Field >, [441](#)
- \_csr32\_zo
  - CsrMat< Field >, [441](#)
- \_csr64
  - CsrMat< Field >, [441](#)
- \_csr64\_zo
  - CsrMat< Field >, [441](#)
- \_ell
  - SpMat< Field, flag >, [761](#)
- \_ell16
  - EllMat< Field >, [447](#)
- \_ell16\_zo
  - EllMat< Field >, [447](#)
- \_ell32
  - EllMat< Field >, [447](#)
- \_ell32\_zo
  - EllMat< Field >, [447](#)
- \_ell64
  - EllMat< Field >, [447](#)
- \_ell64\_zo
  - EllMat< Field >, [447](#)
- \_errorStream
  - Failure, [449](#)
- \_field\_rns
  - rns\_double, [534](#)
  - rns\_double\_extended, [545](#)
- \_iM\_modp\_rns
  - RNSIntegerMod< RNS >, [555](#)
- \_ibeg
  - ForStrategy2D< blocksize\_t, Cut, Param >, [469](#)
- \_iend
  - ForStrategy2D< blocksize\_t, Cut, Param >, [469](#)
- \_invbasis
  - rns\_double, [534](#)
  - rns\_double\_extended, [545](#)
- \_jbeg
  - ForStrategy2D< blocksize\_t, Cut, Param >, [469](#)
- \_jend
  - ForStrategy2D< blocksize\_t, Cut, Param >, [469](#)
- \_ldm
  - rns\_double, [535](#)
  - rns\_double\_extended, [545](#)
- \_mi\_sum
  - rns\_double, [535](#)
- \_mm
  - Test< Elt >, [768](#)
- \_negbasis
  - rns\_double, [534](#)
  - rns\_double\_extended, [545](#)
- \_nn
  - Test< Elt >, [768](#)
- \_p
  - RNSIntegerMod< RNS >, [555](#)
- \_pbits
  - rns\_double, [535](#)
  - rns\_double\_extended, [545](#)
- \_ptr
  - rns\_double\_elt, [536](#)
  - rns\_double\_elt\_cstptr, [539](#)
  - rns\_double\_elt\_ptr, [542](#)
- \_rns
  - RNSInteger< RNS >, [549](#)
  - RNSIntegerMod< RNS >, [555](#)
- \_simd512\_int64\_INL
  - simd512\_int64.inl, [888](#)
- \_size
  - rns\_double, [535](#)
  - rns\_double\_extended, [545](#)
- \_stride
  - rns\_double\_elt, [536](#)
  - rns\_double\_elt\_cstptr, [539](#)
  - rns\_double\_elt\_ptr, [542](#)
- \_zero
  - ScalFunctionsBase< Element, typename enable\_if< is\_floating\_point< Element >::value >::type >, [564](#)
  - ScalFunctionsBase< Element, typename enable\_if< is\_integral< Element >::value >::type >, [567](#)
- ~CheckerImplem\_Det
  - CheckerImplem\_Det< Field >, [419](#)
- ~CheckerImplem\_PLUQ
  - CheckerImplem\_PLUQ< Field >, [424](#)
- ~CheckerImplem\_charpoly
  - CheckerImplem\_charpoly< Field, Polynomial >, [417](#)



- CheckerImplem\_charpoly< Givaro::ZRing< Givaro::Integer >, Polynomial >, 418
- ~CheckerImplem\_fgemm
  - CheckerImplem\_fgemm< Field >, 421
- ~CheckerImplem\_ftsm
  - CheckerImplem\_ftsm< Field >, 422
- ~CheckerImplem\_invert
  - CheckerImplem\_invert< Field >, 423
- ~rns\_double\_elt
  - rns\_double\_elt, 536
- 101-fgemm.C, 1110
  - main, 1110
- 2x2-fgemm.C, 1110
  - main, 1111
- 2x2-ftsv.C, 1111
  - main, 1111
- 2x2-pluq.C, 1111
  - main, 1111
- add
  - FFLAS::vectorised, 285
  - FieldSimd< \_Field >, 452
  - RNSIntegerMod< RNS >, 553
  - ScalFunctions< Element >, 559
  - Simd128\_impl< true, true, false, 2 >, 576
  - Simd128\_impl< true, true, false, 4 >, 585
  - Simd128\_impl< true, true, false, 8 >, 596
  - Simd128\_impl< true, true, true, 2 >, 603
  - Simd128\_impl< true, true, true, 4 >, 612
  - Simd128\_impl< true, true, true, 8 >, 621
  - Simd256\_impl< true, false, true, 8 >, 632
  - Simd256\_impl< true, true, false, 2 >, 643
  - Simd256\_impl< true, true, false, 4 >, 660
  - Simd256\_impl< true, true, false, 8 >, 671
  - Simd256\_impl< true, true, true, 2 >, 679
  - Simd256\_impl< true, true, true, 4 >, 690, 696
  - Simd256\_impl< true, true, true, 8 >, 705
  - Simd512\_impl< true, false, true, 8 >, 714
  - Simd512\_impl< true, true, false, 8 >, 725
  - Simd512\_impl< true, true, true, 8 >, 733
- add\_r
  - FieldSimd< \_Field >, 452, 453
- addin
  - FieldSimd< \_Field >, 452
  - ScalFunctions< Element >, 559
  - Simd128\_impl< true, true, false, 2 >, 576
  - Simd128\_impl< true, true, false, 4 >, 586
  - Simd128\_impl< true, true, false, 8 >, 596
  - Simd128\_impl< true, true, true, 2 >, 604
  - Simd128\_impl< true, true, true, 4 >, 612
  - Simd128\_impl< true, true, true, 8 >, 622
  - Simd256\_impl< true, false, true, 8 >, 632
  - Simd256\_impl< true, true, false, 2 >, 643
  - Simd256\_impl< true, true, false, 4 >, 660
  - Simd256\_impl< true, true, false, 8 >, 671
  - Simd256\_impl< true, true, true, 2 >, 679
  - Simd256\_impl< true, true, true, 4 >, 690, 696
  - Simd256\_impl< true, true, true, 8 >, 705
  - Simd512\_impl< true, false, true, 8 >, 714
- Simd512\_impl< true, true, false, 8 >, 725
- Simd512\_impl< true, true, true, 8 >, 733
- addin\_r
  - FieldSimd< \_Field >, 453
- alignable
  - FFLAS, 191
- alignable< Givaro::Integer \* >
  - FFLAS, 192
- aligned\_allocator
  - NoSimd< T >, 525
  - Simd128\_impl< true, true, false, 2 >, 570
  - Simd128\_impl< true, true, false, 4 >, 580
  - Simd128\_impl< true, true, false, 8 >, 590
  - Simd128\_impl< true, true, true, 2 >, 600
  - Simd128\_impl< true, true, true, 4 >, 609
  - Simd128\_impl< true, true, true, 8 >, 619
  - Simd256\_impl< true, false, true, 8 >, 629
  - Simd256\_impl< true, true, false, 2 >, 637
  - Simd256\_impl< true, true, false, 4 >, 649
  - Simd256\_impl< true, true, false, 8 >, 666
  - Simd256\_impl< true, true, true, 2 >, 676
  - Simd256\_impl< true, true, true, 4 >, 686, 687
  - Simd256\_impl< true, true, true, 8 >, 702
  - Simd512\_impl< true, false, true, 8 >, 711
  - Simd512\_impl< true, true, false, 8 >, 719
  - Simd512\_impl< true, true, true, 8 >, 730
- aligned\_vector
  - NoSimd< T >, 525
  - Simd128\_impl< true, true, false, 2 >, 570
  - Simd128\_impl< true, true, false, 4 >, 580
  - Simd128\_impl< true, true, false, 8 >, 590
  - Simd128\_impl< true, true, true, 2 >, 601
  - Simd128\_impl< true, true, true, 4 >, 610
  - Simd128\_impl< true, true, true, 8 >, 619
  - Simd256\_impl< true, false, true, 8 >, 629
  - Simd256\_impl< true, true, false, 2 >, 637
  - Simd256\_impl< true, true, false, 4 >, 649
  - Simd256\_impl< true, true, false, 8 >, 666
  - Simd256\_impl< true, true, true, 2 >, 676
  - Simd256\_impl< true, true, true, 4 >, 686, 687
  - Simd256\_impl< true, true, true, 8 >, 702
  - Simd512\_impl< true, false, true, 8 >, 711
  - Simd512\_impl< true, true, false, 8 >, 719
  - Simd512\_impl< true, true, true, 8 >, 730
- alignment
  - FieldSimd< \_Field >, 456
  - NoSimd< T >, 525
  - Simd128\_impl< true, true, false, 2 >, 578
  - Simd128\_impl< true, true, false, 4 >, 588



- Simd128\_impl< true, true, false, 8 >, [598](#)
- Simd128\_impl< true, true, true, 2 >, [607](#)
- Simd128\_impl< true, true, true, 4 >, [616](#)
- Simd128\_impl< true, true, true, 8 >, [626](#)
- Simd256\_impl< true, false, true, 8 >, [635](#)
- Simd256\_impl< true, true, false, 2 >, [645](#)
- Simd256\_impl< true, true, false, 4 >, [664](#)
- Simd256\_impl< true, true, false, 8 >, [673](#)
- Simd256\_impl< true, true, true, 2 >, [682](#)
- Simd256\_impl< true, true, true, 4 >, [700](#)
- Simd256\_impl< true, true, true, 8 >, [709](#)
- Simd512\_impl< true, false, true, 8 >, [716](#)
- Simd512\_impl< true, true, false, 8 >, [727](#)
- Simd512\_impl< true, true, true, 8 >, [737](#)
- ALL< false, v... >, [406](#)
  - value, [406](#)
- ALL< true, v... >, [406](#)
  - value, [406](#)
- ALL< v >, [405](#)
- ALL<>, [406](#)
  - value, [406](#)
- Amax
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [506](#)
- Amin
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [506](#)
- applyP
  - FFPACK, [309](#), [310](#), [370](#)
- applyP\_block
  - FFPACK, [362](#)
- applyP\_modular\_double
  - ffpack.C, [996](#)
  - ffpack\_c.h, [1018](#)
- ArbitraryPrecIntTag, [406](#)
- Architecture of the library., [2](#)
- areEqual
  - RNSIntegerMod< RNS >, [554](#)
- AreEqual< X, X >, [407](#)
  - value, [407](#)
- AreEqual< X, Y >, [407](#)
  - value, [407](#)
- args-parser.h, [1046](#)
  - ArgumentType, [1047](#)
  - END\_OF\_ARGUMENTS, [1047](#)
  - findArgument, [1047](#)
  - getListArgs, [1047](#)
  - printHelpMessage, [1047](#)
  - TYPE\_BOOL, [1047](#)
  - TYPE\_DOUBLE, [1047](#)
  - TYPE\_INT, [1047](#)
  - TYPE\_INTEGER, [1047](#)
  - type\_integer, [1047](#)
  - TYPE\_INTLIST, [1047](#)
  - TYPE\_LONGLONG, [1047](#)
  - TYPE\_NONE, [1047](#)
  - TYPE\_STR, [1047](#)
  - TYPE\_UINT64, [1047](#)
- Argument, [407](#)
  - c, [407](#)
  - data, [408](#)
  - example, [407](#)
  - helpString, [407](#)
  - type, [408](#)
- ArgumentType
  - args-parser.h, [1047](#)
- ArithProg
  - FFPACK::Protected, [400](#)
- arithprog.C, [779](#)
  - CUBE, [779](#)
  - GFOPS, [779](#)
  - main, [780](#)
  - TTimer, [779](#)
- assign
  - RNSInteger< RNS >, [549](#)
  - RNSIntegerMod< RNS >, [553](#)
- associatedDelayedField< const FFPACK::RNSIntegerMod< RNS > >, [408](#)
  - field, [408](#)
  - type, [408](#)
- associatedDelayedField< const Givaro::Modular< T, X > >, [409](#)
  - field, [409](#)
  - type, [409](#)
- associatedDelayedField< const Givaro::ModularBalanced< T > >, [409](#)
  - field, [409](#)
  - type, [409](#)
- associatedDelayedField< const Givaro::ZRing< T > >, [410](#)
  - field, [410](#)
  - type, [410](#)
- associatedDelayedField< Field >, [408](#)
  - field, [408](#)
  - type, [408](#)
- assume\_aligned
  - fflas\_sparse.h, [892](#)
- AtlasConj
  - config-blas.h, [826](#)
- Aunfit
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [505](#)
- aut
  - HelperFlag, [478](#)
- Auto, [410](#)
- autotune/charpoly.C
  - CUBE, [816](#)
  - GFOPS, [816](#)
  - main, [816](#)
  - TTimer, [816](#)
- autotune/pluq.C
  - CUBE, [818](#)
  - GFOPS, [818](#)
  - main, [818](#)
  - TTimer, [818](#)
- averageCol

- StatsMatrix, 762
- averageColDifference
  - StatsMatrix, 763
- averageRow
  - StatsMatrix, 762
- averageRowDifference
  - StatsMatrix, 763
- axpy
  - FieldSimd< \_Field >, 454, 455
- axpy\_r
  - FieldSimd< \_Field >, 455
- axpyin
  - FieldSimd< \_Field >, 455
  - RNSIntegerMod< RNS >, 554
- axpyin\_r
  - FieldSimd< \_Field >, 455
- axpyp
  - FFLAS::vectorised, 285
  - FFLAS::vectorised::unswitch, 289
- balanced
  - FieldTraits< FFPACK::RNSInteger< T > >, 457
  - FieldTraits< FFPACK::RNSIntegerMod< T > >, 458
  - FieldTraits< Field >, 457
  - FieldTraits< Givaro::Modular< Element > >, 458
  - FieldTraits< Givaro::ModularBalanced< Element > >, 459
  - FieldTraits< Givaro::ZRing< double > >, 459
  - FieldTraits< Givaro::ZRing< float > >, 460
  - FieldTraits< Givaro::ZRing< Givaro::Integer > >, 460
  - FieldTraits< Givaro::ZRing< int16\_t > >, 461
  - FieldTraits< Givaro::ZRing< int32\_t > >, 461
  - FieldTraits< Givaro::ZRing< int64\_t > >, 461
  - FieldTraits< Givaro::ZRing< Reclnt::ruint< K > >, 462
  - FieldTraits< Givaro::ZRing< uint16\_t > >, 462
  - FieldTraits< Givaro::ZRing< uint32\_t > >, 463
  - FieldTraits< Givaro::ZRing< uint64\_t > >, 463
  - winograd.C, 783
- BARRIER
  - parallel.h, 1039
- BASECASE\_K
  - test-lu.C, 1094
- BaseTimer
  - FFLAS, 74
- BasisElement
  - rns\_double, 532
  - rns\_double\_extended, 543
  - RNSInteger< RNS >, 547
  - RNSIntegerMod< RNS >, 551
- begin
  - ForStrategy1D< blocksize\_t, Cut, Param >, 465
  - Info, 483, 484
- BEGIN\_PARALLEL\_MAIN
  - parallel.h, 1040
- Bench
  - Bench< Elt >, 412
- Bench< Elt >, 410
  - Bench, 412
  - cardinality, 412
  - doBenchs, 412
  - Elt\_ptr, 411
  - enable\_if\_no\_simd\_t, 411
  - enable\_if\_simd128\_t, 411
  - enable\_if\_simd256\_t, 411
  - enable\_if\_simd512\_t, 411
  - enable\_if\_t, 411
  - F, 412
  - Field, 411
  - inplace, 413
  - is\_same\_element, 411
  - iters, 413
  - m, 412
  - n, 412
  - Residu, 411
  - run, 412
- benchmark-charpoly-mp.C, 783
  - \_\_FFLASFFPACK\_FORCE\_SEQ, 784
  - main, 784
- benchmark-charpoly.C, 784
  - \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, 784
  - main, 785
  - run\_with\_field, 784
- benchmark-checkers.C, 785
  - \_MAX\_SIZE\_MATRICES, 785
  - \_NR\_TESTS, 785
  - CUBE, 785
  - ENABLE\_ALL\_CHECKINGS, 785
  - main, 786
- benchmark-dgemm.C, 786
  - CBLAS\_GEMM, 786
  - Floats, 786
  - main, 786
  - TTimer, 786
- benchmark-dgetrf.C, 787
  - \_\_FFLASFFPACK\_HAVE\_DGETRF, 787
  - main, 787
  - TTimer, 787
- benchmark-dgetri.C, 787
  - main, 788
  - TTimer, 788
- benchmark-dsytrf.C, 788
  - EFFGFF, 788
  - main, 789
  - TTimer, 788
- benchmark-dtrsm.C, 789
  - main, 789
  - TTimer, 789
- benchmark-dtrtri.C, 789
  - \_\_FFLASFFPACK\_HAVE\_DTRTRI, 790
  - main, 790
  - TTimer, 790
- benchmark-fadd-lvl2.C, 790

\_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, main, 800  
 790  
 main, 790  
 benchmark-fdot.C, 791  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, main, 800  
 791  
 main, 791  
 run\_with\_field, 791  
 benchmark-fgemm-mp.C, 791  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, CUBE, 801  
 792  
 main, 792  
 MG\_DEFAULT, 792  
 STD\_RECINT\_SIZE, 792  
 tmain, 792  
 benchmark-fgemm-rns.C, 792  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, 802  
 793  
 ConstElement\_ptr, 793  
 Element\_ptr, 793  
 Field, 793  
 GRAIN, 793  
 main, 794  
 PSeq, 794  
 RNS, 793  
 THREADS, 793  
 THREEED, 793  
 THREEEDA, 794  
 THREEEDIP, 794  
 TWOD, 793  
 TWODA, 793  
 benchmark-fgemm.C, 794  
 CLASSIC\_HYBRID, 794  
 main, 794  
 benchmark-fgemv-mp.C, 795  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, main, 805  
 795  
 main, 795  
 MG\_DEFAULT, 795  
 STD\_RECINT\_SIZE, 795  
 tmain, 795  
 write\_matrix, 795  
 benchmark-fgemv.C, 796  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, 806  
 797  
 benchmark\_disp, 798  
 benchmark\_in\_Field, 798  
 benchmark\_with\_field, 798  
 benchmark\_with\_timer, 797  
 check\_result, 797  
 fill\_value, 797  
 genData, 797  
 main, 799  
 benchmark-fgesv.C, 799  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, main, 808  
 799  
 main, 799  
 benchmark-fsyr2k.C, 799  
 main, 800  
 benchmark-fsyrk.C, 800  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, 800  
 main, 800  
 benchmark-fsytrf.C, 800  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, 801  
 \_\_FFPACK\_FSYTRF\_BC\_CROUT, 801  
 CUBE, 801  
 main, 801  
 benchmark-ftrsm-mp.C, 801  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, 802  
 802  
 main, 802  
 benchmark-ftrsm.C, 802  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, 802  
 802  
 main, 802  
 benchmark-ftrsv.C, 802  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, 803  
 803  
 main, 803  
 benchmark-ftrtri.C, 803  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, 803  
 803  
 CUBE, 803  
 main, 803  
 benchmark-inverse.C, 804  
 CUBE, 804  
 main, 804  
 benchmark-lqup-mp.C, 804  
 main, 804  
 benchmark-lqup.C, 805  
 CUBE, 805  
 main, 805  
 benchmark-pluq.C, 805  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, 806  
 806  
 CUBE, 806  
 Field, 806  
 main, 806  
 Rec\_Initialize, 806  
 verification\_PLUQ, 806  
 benchmark-quasisep.C, 806  
 \_\_FFLASFFPACK\_OPENBLAS\_NT\_ALREADY\_SET, 807  
 807  
 main, 807  
 run\_with\_field, 807  
 benchmark-storage-transpose.C, 807  
 main, 808  
 benchmark-wino.C, 808  
 CUBE, 808  
 launch\_wino, 808  
 main, 808  
 benchmark\_disp  
 benchmark-fgemv.C, 798  
 benchmark\_in\_Field

- benchmark-fgemv.C, [798](#)
- benchmark\_with\_field
  - benchmark-fgemv.C, [798](#)
- benchmark\_with\_timer
  - benchmark-fgemv.C, [797](#)
- Bibliography, [7](#)
- Bini, [413](#)
  - FFLAS::BLAS3, [196](#)
- bit\_manipulation.h, [1048](#)
  - \_\_has\_builtin, [1048](#)
  - clz, [1048](#)
  - ctz, [1048](#)
- bitsize
  - FFLAS, [142](#)
- bitsize< Givaro::ZRing< Givaro::Integer > >
  - FFLAS, [142](#)
- blas\_enum
  - config-blas.h, [825](#)
- blend
  - ScalFunctions< Element >, [562](#)
  - Simd128\_impl< true, true, false, 2 >, [576](#)
  - Simd128\_impl< true, true, false, 4 >, [585](#)
  - Simd128\_impl< true, true, false, 8 >, [595](#)
  - Simd128\_impl< true, true, true, 2 >, [603](#)
  - Simd128\_impl< true, true, true, 4 >, [612](#)
  - Simd128\_impl< true, true, true, 8 >, [621](#)
  - Simd256\_impl< true, false, true, 8 >, [632](#)
  - Simd256\_impl< true, true, false, 2 >, [643](#)
  - Simd256\_impl< true, true, false, 4 >, [659](#)
  - Simd256\_impl< true, true, false, 8 >, [671](#)
  - Simd256\_impl< true, true, true, 2 >, [679](#)
  - Simd256\_impl< true, true, true, 4 >, [690](#), [696](#)
  - Simd256\_impl< true, true, true, 8 >, [705](#)
  - Simd512\_impl< true, false, true, 8 >, [714](#)
  - Simd512\_impl< true, true, false, 8 >, [725](#)
  - Simd512\_impl< true, true, true, 8 >, [733](#)
- blendv
  - ScalFunctionsBase< Element, typename enable\_if< is\_floating\_point< Element >::value >::type >, [563](#)
  - Simd256\_impl< true, false, true, 8 >, [632](#)
  - Simd512\_impl< true, false, true, 8 >, [714](#)
- Block, [413](#)
- BlockCuts
  - FFLAS, [181](#), [183](#)
- BlockCuts< CuttingStrategy::Block, StrategyParameter::Fixed >
  - FFLAS, [183](#)
- BlockCuts< CuttingStrategy::Block, StrategyParameter::Grain >
  - FFLAS, [182](#)
- BlockCuts< CuttingStrategy::Block, StrategyParameter::Threads >
  - FFLAS, [183](#)
- BlockCuts< CuttingStrategy::Column, StrategyParameter::Fixed >
  - FFLAS, [182](#)
- BlockCuts< CuttingStrategy::Column, StrategyParameter::Threads >
  - FFLAS, [183](#)
- BlockCuts< CuttingStrategy::Row, StrategyParameter::Fixed >
  - FFLAS, [182](#)
- BlockCuts< CuttingStrategy::Row, StrategyParameter::Grain >
  - FFLAS, [182](#)
- BlockCuts< CuttingStrategy::Row, StrategyParameter::Threads >
  - FFLAS, [183](#)
- BlockCuts< CuttingStrategy::Single, StrategyParameter::Threads >
  - FFLAS, [181](#)
- blockcuts.inl, [1036](#)
  - \_\_FFLASFFPACK\_MINBLOCKCUTS, [1037](#)
  - \_\_FFLASFFPACK\_fflas\_blockcuts\_INL, [1037](#)
- blockindex
  - ForStrategy1D< blocksize\_t, Cut, Param >, [466](#)
  - ForStrategy2D< blocksize\_t, Cut, Param >, [469](#)
- BlockingFactor
  - FFLAS::details, [210](#)
- BLOCKS
  - ForStrategy2D< blocksize\_t, Cut, Param >, [470](#)
- BlockTransposeSIMD< Field, Simd, >, [413](#)
  - info, [413](#)
  - size, [413](#)
  - transpose, [414](#)
- Bmax
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeqTrait >, [506](#)
- Bmin
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeqTrait >, [506](#)
- Bruhat2EchelonPermutation
  - FFPACK, [350](#)
- Bug List, [3](#)
- build
  - ForStrategy1D< blocksize\_t, Cut, Param >, [465](#)
- buildMatrix
  - FFPACK, [356](#)
- Bunfit
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeqTrait >, [505](#)
- c
  - Argument, [407](#)
- callLUdivine\_small< double >, [415](#)
  - operator(), [415](#)
- callLUdivine\_small< Element >, [415](#)
  - operator(), [415](#)
- callLUdivine\_small< float >, [416](#)
  - operator(), [416](#)
- cardinality
  - Bench< Elt >, [412](#)

- RNSInteger< RNS >, [548](#)
- RNSIntegerMod< RNS >, [552](#)
- Test< Elt >, [767](#)
- cast.h, [1049](#)
- category
  - FieldTraits< FFPACK::RNSInteger< T > >, [457](#)
  - FieldTraits< FFPACK::RNSIntegerMod< T > >, [457](#)
  - FieldTraits< Field >, [456](#)
  - FieldTraits< Givaro::Modular< Element > >, [458](#)
  - FieldTraits< Givaro::ModularBalanced< Element > >, [458](#)
  - FieldTraits< Givaro::ZRing< double > >, [459](#)
  - FieldTraits< Givaro::ZRing< float > >, [459](#)
  - FieldTraits< Givaro::ZRing< Givaro::Integer > >, [460](#)
  - FieldTraits< Givaro::ZRing< int16\_t > >, [460](#)
  - FieldTraits< Givaro::ZRing< int32\_t > >, [461](#)
  - FieldTraits< Givaro::ZRing< int64\_t > >, [461](#)
  - FieldTraits< Givaro::ZRing< Reclnt::ruint< K > >, [462](#)
  - FieldTraits< Givaro::ZRing< uint16\_t > >, [462](#)
  - FieldTraits< Givaro::ZRing< uint32\_t > >, [463](#)
  - FieldTraits< Givaro::ZRing< uint64\_t > >, [463](#)
- cblas.C, [1056](#)
  - \_\_FFLASFFPACK\_CONFIGURATION, [1056](#)
  - \_\_FFLASFFPACK\_HAVE\_CBLAS, [1056](#)
  - main, [1056](#)
- CBLAS\_DIAG
  - config-blas.h, [826](#)
- cblas\_dsyrk
  - config-blas.h, [830](#)
- CBLAS\_ENUM\_DEFINED\_H
  - config-blas.h, [825](#)
- CBLAS\_EXTERNALS
  - config-blas.h, [825](#)
- CBLAS\_GEMM
  - benchmark-dgemm.C, [786](#)
- cblas\_imptrsm
  - FFLAS, [130](#)
- CBLAS\_INT
  - config-blas.h, [825](#)
- CBLAS\_ORDER
  - config-blas.h, [825](#)
- CBLAS\_SIDE
  - config-blas.h, [826](#)
- CBLAS\_TRANSPOSE
  - config-blas.h, [826](#)
- CBLAS\_UPLO
  - config-blas.h, [826](#)
- CblasColMajor
  - config-blas.h, [825](#)
- CblasConjTrans
  - config-blas.h, [826](#)
- CblasLeft
  - config-blas.h, [826](#)
- CblasLower
  - config-blas.h, [826](#)
- CblasNonUnit
  - config-blas.h, [826](#)
- CblasNoTrans
  - config-blas.h, [826](#)
- CblasRight
  - config-blas.h, [826](#)
- CblasRowMajor
  - config-blas.h, [825](#)
- CblasTrans
  - config-blas.h, [826](#)
- CblasUnit
  - config-blas.h, [826](#)
- CblasUpper
  - config-blas.h, [826](#)
- ceil
  - ScalFunctionsBase< Element, typename enable\_if< is\_floating\_point< Element >::value >::type >, [563](#)
  - Simd256\_impl< true, false, true, 8 >, [634](#)
  - Simd512\_impl< true, false, true, 8 >, [716](#)
- changeBS
  - ForStrategy1D< blocksize\_t, Cut, Param >, [466](#)
- changeCBS
  - ForStrategy2D< blocksize\_t, Cut, Param >, [470](#)
- changeRBS
  - ForStrategy2D< blocksize\_t, Cut, Param >, [470](#)
- characteristic
  - RNSInteger< RNS >, [548](#)
  - RNSIntegerMod< RNS >, [552](#)
- CharPoly
  - FFPACK, [327](#), [328](#), [356](#), [374](#), [375](#)
- charpoly.C, [816](#)
- CharpolyFailed, [416](#)
- check
  - Checker\_Empty< Field >, [417](#)
  - CheckerImplem\_charpoly< Field, Polynomial >, [418](#)
  - CheckerImplem\_charpoly< Givaro::ZRing< Givaro::Integer >, Polynomial >, [419](#)
  - CheckerImplem\_Det< Field >, [419](#)
  - CheckerImplem\_fgemm< Field >, [422](#)
  - CheckerImplem\_ftsm< Field >, [423](#)
  - CheckerImplem\_invert< Field >, [423](#)
  - CheckerImplem\_PLUQ< Field >, [424](#)
- check1
  - regression-check.C, [1059](#)
- check2
  - regression-check.C, [1059](#)
- check3
  - regression-check.C, [1059](#)
- check4
  - regression-check.C, [1059](#)
- check\_computeS1S2
  - test-fsyrk.C, [1081](#)
- CHECK\_DEPENDENCIES
  - parallel.h, [1039](#)
- check\_eq
  - test-simd.C, [1107](#), [1108](#)

- check\_fdot
  - test-fdot.C, [1068](#)
- check\_fger
  - test-fger.C, [1074](#)
- check\_fsyr2k
  - test-fsyr2k.C, [1079](#)
- check\_fsyk
  - test-fsyk.C, [1081](#)
- check\_fsyk\_bkdiag
  - test-fsyk.C, [1081](#)
- check\_fsyk\_diag
  - test-fsyk.C, [1081](#)
- check\_ftrmm
  - test-ftrmm.C, [1084](#)
- check\_ftrmv
  - test-ftrmv.C, [1085](#)
- check\_ftrsm
  - test-ftrsm.C, [1087](#)
- check\_ftrssyr2k
  - test-ftrssyr2k.C, [1088](#)
- check\_ftrstr
  - test-ftrstr.C, [1089](#)
- check\_ftrsv
  - test-ftrsv.C, [1090](#)
- check\_ftrtri
  - test-ftrtri.C, [1091](#)
- check\_minpoly
  - test-minpoly.C, [1099](#)
- check\_MM
  - test-fgemm.C, [1070](#)
- check\_MV
  - test-fgemv.C, [1072](#)
- check\_result
  - benchmark-fgemv.C, [797](#)
- check\_solve
  - test-solve.C, [1109](#)
- checkA
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [505](#)
- checkB
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [505](#)
- CHECKER, [41](#)
- Checker\_charpoly
  - FFPACK, [308](#)
- checker\_charpoly.inl, [820](#)
  - \_\_FFLASFFPACK\_checker\_charpoly\_INL, [820](#)
- Checker\_Det
  - FFPACK, [307](#)
- checker\_det.inl, [820](#)
  - \_\_FFLASFFPACK\_checker\_det\_INL, [820](#)
- Checker\_Empty
  - Checker\_Empty< Field >, [417](#)
- Checker\_Empty< Field >, [416](#)
  - check, [417](#)
  - Checker\_Empty, [417](#)
- checker\_empty.h, [820](#)
- Checker\_fgemm
  - FFLAS, [72](#)
- checker\_fgemm.inl, [821](#)
  - \_\_FFLASFFPACK\_checker\_fgemm\_INL, [821](#)
- Checker\_ftrsm
  - FFLAS, [72](#)
- checker\_ftrsm.inl, [821](#)
  - \_\_FFLASFFPACK\_checker\_ftrsm\_INL, [821](#)
- Checker\_invert
  - FFPACK, [308](#)
- checker\_invert.inl, [821](#)
  - \_\_FFLASFFPACK\_checker\_invert\_INL, [822](#)
- Checker\_PLUQ
  - FFPACK, [307](#)
- checker\_pluq.inl, [822](#)
  - \_\_FFLASFFPACK\_checker\_pluq\_INL, [822](#)
- CheckerImplem\_charpoly
  - CheckerImplem\_charpoly< Field, Polynomial >, [417](#)
  - CheckerImplem\_charpoly< Givaro::ZRing< Givaro::Integer >, Polynomial >, [418](#)
- CheckerImplem\_charpoly< Field, Polynomial >, [417](#)
  - ~CheckerImplem\_charpoly, [417](#)
  - check, [418](#)
  - CheckerImplem\_charpoly, [417](#)
- CheckerImplem\_charpoly< Givaro::ZRing< Givaro::Integer >, Polynomial >, [418](#)
  - ~CheckerImplem\_charpoly, [418](#)
  - check, [419](#)
  - CheckerImplem\_charpoly, [418](#)
  - Ring, [418](#)
- CheckerImplem\_Det
  - CheckerImplem\_Det< Field >, [419](#)
- CheckerImplem\_Det< Field >, [419](#)
  - ~CheckerImplem\_Det, [419](#)
  - check, [419](#)
  - CheckerImplem\_Det, [419](#)
- CheckerImplem\_fgemm
  - CheckerImplem\_fgemm< Field >, [421](#)
- CheckerImplem\_fgemm< Field >, [421](#)
  - ~CheckerImplem\_fgemm, [421](#)
  - check, [422](#)
  - CheckerImplem\_fgemm, [421](#)
- CheckerImplem\_ftrsm
  - CheckerImplem\_ftrsm< Field >, [422](#)
- CheckerImplem\_ftrsm< Field >, [422](#)
  - ~CheckerImplem\_ftrsm, [422](#)
  - check, [423](#)
  - CheckerImplem\_ftrsm, [422](#)
- CheckerImplem\_invert
  - CheckerImplem\_invert< Field >, [423](#)
- CheckerImplem\_invert< Field >, [423](#)
  - ~CheckerImplem\_invert, [423](#)
  - check, [423](#)
  - CheckerImplem\_invert, [423](#)
- CheckerImplem\_PLUQ
  - CheckerImplem\_PLUQ< Field >, [424](#)
- CheckerImplem\_PLUQ< Field >, [424](#)
  - ~CheckerImplem\_PLUQ, [424](#)

- check, [424](#)
- CheckerImplem\_PLUQ, [424](#)
- checkers.doxy, [822](#)
- checkers\_fflas.h, [822](#)
- checkers\_fflas.inl, [823](#)
  - FFLASFFPACK\_checkers\_fflas\_inl\_H, [823](#)
- checkers\_ffpack.h, [823](#)
- checkers\_ffpack.inl, [824](#)
  - FFLASFFPACK\_checkers\_ffpack\_inl\_H, [824](#)
- checkingMessage
  - test-nullspace.C, [1100](#)
- checkMonotonicApplyP
  - test-permutations.C, [1101](#)
- checkOut
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [505](#)
- checkRPM
  - test-rpm.C, [1105](#)
- checkSymmetricRPM
  - test-rpm.C, [1105](#)
- checkZeroDimCharpoly
  - regression-check.C, [1059](#)
- checkZeroDimMinPoly
  - regression-check.C, [1059](#)
- chooseField
  - FFPACK, [395](#)
- chooseField< Givaro::ZRing< double > >
  - FFPACK, [395](#)
- chooseField< Givaro::ZRing< float > >
  - FFPACK, [395](#)
- chooseField< Givaro::ZRing< int32\_t > >
  - FFPACK, [395](#)
- chooseField< Givaro::ZRing< int64\_t > >
  - FFPACK, [395](#)
- chunk
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd >, [750](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, [752](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL >, [757](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [759](#)
- chunkSize
  - Sparse< \_Field, SparseMatrix\_t::SELL >, [758](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [760](#)
- clapack.C, [1056](#)
  - \_\_FFLASFFPACK\_CONFIGURATION, [1057](#)
  - \_\_FFLASFFPACK\_HAVE\_CLAPACK, [1057](#)
  - \_\_FFLASFFPACK\_HAVE\_LAPACK, [1057](#)
  - main, [1057](#)
- Classic, [425](#)
- CLASSIC\_HYBRID
  - benchmark-fgemm.C, [794](#)
- clz
  - bit\_manipulation.h, [1048](#)
- Cmax
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [506](#)
- Cmin
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [506](#)
- cmp
  - test-simd.C, [1108](#)
- cmp\_false
  - ScalFunctionsBase< Element, typename enable\_if< is\_floating\_point< Element >::value >::type >, [564](#)
  - ScalFunctionsBase< Element, typename enable\_if< is\_integral< Element >::value >::type >, [567](#)
- cmp\_true
  - ScalFunctionsBase< Element, typename enable\_if< is\_floating\_point< Element >::value >::type >, [564](#)
  - ScalFunctionsBase< Element, typename enable\_if< is\_integral< Element >::value >::type >, [567](#)
- col
  - Coo< Field >, [436](#)
  - Coo< ValT, IdxT >, [435](#), [438](#)
  - Sparse< \_Field, SparseMatrix\_t::COO >, [741](#)
  - Sparse< \_Field, SparseMatrix\_t::COO\_ZO >, [742](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR >, [744](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, [745](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, [748](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL >, [749](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd >, [751](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, [753](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_ZO >, [754](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL >, [758](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [760](#)
- colblockindex
  - ForStrategy2D< blocksize\_t, Cut, Param >, [469](#)
- colBlockSize
  - ForStrategy2D< blocksize\_t, Cut, Param >, [470](#)
- coldim
  - StatsMatrix, [762](#)
- colnumblocks
  - ForStrategy2D< blocksize\_t, Cut, Param >, [468](#)
- ColRankProfileSubmatrix
  - FFPACK, [340](#), [379](#)
- ColRankProfileSubmatrix\_modular\_double
  - ffpack.C, [1008](#)
  - ffpack\_c.h, [1028](#)
- ColRankProfileSubmatrixIndices
  - FFPACK, [339](#), [379](#)
- ColRankProfileSubmatrixIndices\_modular\_double
  - ffpack.C, [1008](#)
  - ffpack\_c.h, [1028](#)
- Column, [425](#)
- ColumnEchelonForm
  - FFPACK, [321](#), [373](#)
- ColumnEchelonForm\_modular\_double
  - ffpack.C, [999](#)
  - ffpack\_c.h, [1021](#)
- ColumnEchelonForm\_modular\_float
  - ffpack.C, [999](#)



- ffpack\_c.h, [1021](#)
- ColumnEchelonForm\_modular\_int32\_t
  - ffpack.C, [1000](#)
  - ffpack\_c.h, [1021](#)
- ColumnRankProfile
  - FFPACK, [336](#), [337](#), [378](#)
- ColumnRankProfile\_modular\_double
  - ffpack.C, [1007](#)
  - ffpack\_c.h, [1027](#)
- COMMA
  - parallel.h, [1042](#)
- CompactElement< double >, [425](#)
  - type, [425](#)
- CompactElement< Element >, [425](#)
  - type, [425](#)
- CompactElement< float >, [426](#)
  - type, [426](#)
- CompactElement< int16\_t >, [426](#)
  - type, [426](#)
- CompactElement< int32\_t >, [426](#)
  - type, [426](#)
- CompactElement< int64\_t >, [426](#)
  - type, [426](#)
- compatible\_data\_type< Field >, [427](#)
  - value, [427](#)
- compatible\_data\_type< Givaro::ZRing< double > >, [427](#)
  - value, [427](#)
- compatible\_data\_type< Givaro::ZRing< float > >, [427](#)
  - value, [427](#)
- compliant
  - NoSimd< T >, [525](#)
  - Simd128\_impl< true, true, false, 2 >, [573](#)
  - Simd128\_impl< true, true, false, 4 >, [583](#)
  - Simd128\_impl< true, true, false, 8 >, [593](#)
  - Simd128\_impl< true, true, true, 2 >, [601](#)
  - Simd128\_impl< true, true, true, 4 >, [610](#)
  - Simd128\_impl< true, true, true, 8 >, [619](#)
  - Simd256\_impl< true, false, true, 8 >, [630](#)
  - Simd256\_impl< true, true, false, 2 >, [640](#)
  - Simd256\_impl< true, true, false, 4 >, [655](#)
  - Simd256\_impl< true, true, false, 8 >, [669](#)
  - Simd256\_impl< true, true, true, 2 >, [676](#)
  - Simd256\_impl< true, true, true, 4 >, [687](#), [693](#)
  - Simd256\_impl< true, true, true, 8 >, [703](#)
  - Simd512\_impl< true, false, true, 8 >, [712](#)
  - Simd512\_impl< true, true, false, 8 >, [722](#)
  - Simd512\_impl< true, true, true, 8 >, [730](#)
- Compose
  - Compose< H1, H2 >, [428](#)
- Compose< H1, H2 >, [427](#)
  - Compose, [428](#)
  - first\_component, [428](#)
  - operator<<, [428](#)
  - second\_component, [428](#)
- composePermutationsLLL
  - FFPACK, [365](#)
  - ffpack.C, [995](#)
  - ffpack\_c.h, [1017](#)
- composePermutationsLLM
  - FFPACK, [365](#)
  - ffpack.C, [995](#)
  - ffpack\_c.h, [1017](#)
- composePermutationsMLM
  - FFPACK, [366](#)
  - ffpack.C, [995](#)
  - ffpack\_c.h, [1017](#)
- CompressRows
  - FFPACK::Protected, [401](#)
- CompressRowsQA
  - FFPACK::Protected, [402](#)
- CompressRowsQK
  - FFPACK::Protected, [402](#)
- CompressToBlockBiDiagonal
  - FFPACK, [349](#)
- computeDeviation
  - FFLAS, [155](#)
- computeFactorClassic
  - FFLAS::Protected, [216](#)
- ComputeRPermutation
  - FFPACK, [351](#), [354](#)
- computeS1S2
  - FFLAS, [125](#)
- config-blas.h, [824](#)
  - AtlasConj, [826](#)
  - blas\_enum, [825](#)
  - CBLAS\_DIAG, [826](#)
  - cblas\_dsyrk, [830](#)
  - CBLAS\_ENUM\_DEFINED\_H, [825](#)
  - CBLAS\_EXTERNALS, [825](#)
  - CBLAS\_INT, [825](#)
  - CBLAS\_ORDER, [825](#)
  - CBLAS\_SIDE, [826](#)
  - CBLAS\_TRANSPOSE, [826](#)
  - CBLAS\_UPLO, [826](#)
  - CblasColMajor, [825](#)
  - CblasConjTrans, [826](#)
  - CblasLeft, [826](#)
  - CblasLower, [826](#)
  - CblasNonUnit, [826](#)
  - CblasNoTrans, [826](#)
  - CblasRight, [826](#)
  - CblasRowMajor, [825](#)
  - CblasTrans, [826](#)
  - CblasUnit, [826](#)
  - CblasUpper, [826](#)
  - dasum\_, [827](#)
  - daxpy\_, [826](#)
  - dcopy\_, [828](#)
  - ddot\_, [827](#)
  - dgemm\_, [830](#)
  - dgemv\_, [827](#)
  - dger\_, [828](#)
  - dnrm2\_, [827](#)
  - dscal\_, [828](#)
  - dtrmm\_, [829](#)



- dtrsm\_, 829
- idamax\_, 827
- saxpy\_, 826
- scopy\_, 828
- sdot\_, 827
- sgemm\_, 830
- sgemv\_, 827
- sger\_, 828
- sscal\_, 829
- strmm\_, 829
- strsm\_, 829
- config.h, 809, 812
  - HAVE\_BLAS, 809
  - HAVE\_CBLAS, 809
  - HAVE\_CXX11, 810
  - HAVE\_DLFCN\_H, 810
  - HAVE\_FLOAT\_H, 810
  - HAVE\_INT128, 810
  - HAVE\_INTPTR\_T, 810
  - HAVE\_INTTYPES\_H, 810
  - HAVE\_LAPACK, 810
  - HAVE\_LIMITS\_H, 810
  - HAVE\_LITTLE\_ENDIAN, 810
  - HAVE\_PTHREAD\_H, 810
  - HAVE\_STDDEF\_H, 810
  - HAVE\_STDINT\_H, 810
  - HAVE\_STDIO\_H, 810
  - HAVE\_STDLIB\_H, 810
  - HAVE\_STRING\_H, 810
  - HAVE\_STRINGS\_H, 810
  - HAVE\_SYS\_STAT\_H, 811
  - HAVE\_SYS\_TIME\_H, 811
  - HAVE\_SYS\_TYPES\_H, 811
  - HAVE\_UNISTD\_H, 811
  - LT\_OBJDIR, 811
  - OPENBLAS\_NUM\_THREADS, 811
  - PACKAGE, 811
  - PACKAGE\_BUGREPORT, 811
  - PACKAGE\_NAME, 811
  - PACKAGE\_STRING, 811
  - PACKAGE\_TARNAME, 811
  - PACKAGE\_URL, 811
  - PACKAGE\_VERSION, 811
  - SIZEOF\_\_\_INT64\_T, 812
  - SIZEOF\_CHAR, 811
  - SIZEOF\_INT, 811
  - SIZEOF\_LONG, 812
  - SIZEOF\_LONG\_LONG, 812
  - SIZEOF\_SHORT, 812
  - STDC\_HEADERS, 812
  - USE\_OPENMP, 812
  - VERSION, 812
- Configuring and Installing FFLAS-FFPACK, 2
- CONST
  - fflas\_simd.h, 879
- ConstElement\_ptr
  - benchmark-fgemm-rns.C, 793
  - rns\_double, 532
  - rns\_double\_extended, 543
  - RNSInteger< RNS >, 547
  - RNSIntegerMod< RNS >, 551
- CONSTREFERENCE
  - parallel.h, 1040
- convert
  - rns\_double, 533, 534
  - rns\_double\_extended, 544
  - RNSInteger< RNS >, 548
  - RNSIntegerMod< RNS >, 553
- convert\_transpose
  - rns\_double, 533
- ConvertTo< T >, 434
- COO
  - FFLAS, 76
- Coo
  - Coo< Field >, 436
  - Coo< ValT, IdxT >, 434, 435, 437, 438
- coo
  - HelperFlag, 478
- Coo< Field >, 435
  - col, 436
  - Coo, 436
  - deleted, 437
  - operator=, 436
  - row, 437
  - val, 436
- Coo< ValT, IdxT >, 434, 437
  - col, 435, 438
  - Coo, 434, 435, 437, 438
  - operator=, 435, 438
  - row, 435, 438
  - Self, 434, 437
  - val, 435, 438
- coo.h, 894
- coo\_spmv.inl, 895
  - \_\_FFLASFFPACK\_fflas\_sparse\_coo\_spmv\_INL, 896
- coo\_spmv.inl, 896
  - \_\_FFLASFFPACK\_fflas\_sparse\_coo\_spmv\_INL, 897
- coo\_utils.inl, 897
  - \_\_FFLASFFPACK\_fflas\_sparse\_coo\_utils\_INL, 897
- COO\_ZO
  - FFLAS, 76
- CooMat< Field >, 438
  - \_coo16, 439
  - \_coo16\_zo, 439
  - \_coo32, 439
  - \_coo32\_zo, 439
  - \_coo64, 439
  - \_coo64\_zo, 439
- Copying and Licence, 2
- count\_nonconst\_lvalue\_reference< const T &, O... >, 439
  - n, 439
- count\_nonconst\_lvalue\_reference< T >, 439
- count\_nonconst\_lvalue\_reference< T &, O... >, 440

- n, [440](#)
- count\_nonconst\_lvalue\_reference< T, O... >, [440](#)
- n, [440](#)
- count\_nonconst\_lvalue\_reference<>, [440](#)
- n, [440](#)
- CROUT
  - ffpack\_pluq.inl, [948](#)
- CSC
  - FFLAS, [76](#)
- CSC\_ZO
  - FFLAS, [76](#)
- CSR
  - FFLAS, [76](#)
- csr
  - HelperFlag, [478](#)
- csr.h, [897](#)
- CSR\_HYB
  - FFLAS, [76](#)
- csr\_hyb.h, [902](#)
- csr\_hyb\_pspmm.inl, [902](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_pspmm\_INL, [903](#)
- csr\_hyb\_pspmv.inl, [903](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_pspmv\_INL, [903](#)
- csr\_hyb\_spm.inl, [903](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_spm\_INL, [904](#)
- csr\_hyb\_spmv.inl, [904](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_spmv\_INL, [904](#)
- csr\_hyb\_utils.inl, [904](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_HYB\_utils\_INL, [905](#)
- csr\_pspmm.inl, [898](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_pspmm\_INL, [898](#)
- csr\_pspmv.inl, [899](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_pspmv\_INL, [899](#)
- csr\_spm.inl, [899](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_spm\_INL, [900](#)
- csr\_spmv.inl, [900](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_CSR\_spmv\_INL, [901](#)
- csr\_utils.inl, [901](#)
- CSR\_ZO
  - FFLAS, [76](#)
- CsrMat< Field >, [440](#)
  - \_csr16, [441](#)
  - \_csr16\_zo, [441](#)
  - \_csr32, [441](#)
  - \_csr32\_zo, [441](#)
  - \_csr64, [441](#)
  - \_csr64\_zo, [441](#)
- cst
  - Sparse< \_Field, SparseMatrix\_t::COO\_ZO >, [742](#)
- Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, [747](#)
- Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, [752](#)
- Sparse< \_Field, SparseMatrix\_t::ELL\_ZO >, [754](#)
- Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [759](#)
- ctz
  - bit\_manipulation.h, [1048](#)
- CUBE
  - arithprog.C, [779](#)
  - autotune/charpoly.C, [816](#)
  - autotune/pluq.C, [818](#)
  - benchmark-checkers.C, [785](#)
  - benchmark-fsytrf.C, [801](#)
  - benchmark-ftrtri.C, [803](#)
  - benchmark-inverse.C, [804](#)
  - benchmark-lqup.C, [805](#)
  - benchmark-pluq.C, [806](#)
  - benchmark-wino.C, [808](#)
  - fsyrk.C, [780](#)
  - fsytrf.C, [781](#)
  - cuda.C, [1057](#)
  - main, [1057](#)
- current
  - ForStrategy1D< blocksize\_t, Cut, Param >, [466](#)
  - ForStrategy2D< blocksize\_t, Cut, Param >, [470](#)
- cut
  - Parallel< C, P >, [526](#)
- cyclic\_shift\_col
  - FFPACK, [367](#), [370](#)
- cyclic\_shift\_col\_modular\_double
  - ffpack.C, [996](#)
  - ffpack\_c.h, [1017](#)
- cyclic\_shift\_mathPerm
  - FFPACK, [366](#)
  - ffpack.C, [996](#)
  - ffpack\_c.h, [1017](#)
- cyclic\_shift\_row
  - FFPACK, [366](#), [369](#)
- cyclic\_shift\_row\_col
  - FFPACK, [366](#), [369](#)
- cyclic\_shift\_row\_modular\_double
  - ffpack.C, [996](#)
  - ffpack\_c.h, [1017](#)
- Danilevski
  - FFPACK, [356](#)
  - FFPACK::Protected, [399](#)
- dasum\_
  - config-blas.h, [827](#)
- dat
  - Sparse< \_Field, SparseMatrix\_t::COO >, [741](#)
  - Sparse< \_Field, SparseMatrix\_t::COO\_ZO >, [742](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR >, [745](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, [746](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, [748](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL >, [750](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd >, [751](#)

- Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, 753
- Sparse< \_Field, SparseMatrix\_t::ELL\_ZO >, 754
- Sparse< \_Field, SparseMatrix\_t::HYB\_ZO >, 756
- Sparse< \_Field, SparseMatrix\_t::SELL >, 758
- Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, 760
- data
  - Argument, 408
- daxpy\_
  - config-blas.h, 826
- dcopy\_
  - config-blas.h, 828
- ddot\_
  - config-blas.h, 827
- debug.h, 1049
  - FFLASFFPACK\_abort, 1050
  - FFLASFFPACK\_check, 1049
- DeCompressRows
  - FFPACK::Protected, 402
- DeCompressRowsQA
  - FFPACK::Protected, 402
- DeCompressRowsQK
  - FFPACK::Protected, 402
- DefaultBoundedTag, 441
- DefaultTag, 441
- delayed
  - RNSIntegerMod< RNS >, 551
  - Sparse< \_Field, SparseMatrix\_t::COO >, 741
  - Sparse< \_Field, SparseMatrix\_t::COO\_ZO >, 742
  - Sparse< \_Field, SparseMatrix\_t::CSR >, 744
  - Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, 745
  - Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, 747
  - Sparse< \_Field, SparseMatrix\_t::ELL >, 749
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd >, 750
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, 752
  - Sparse< \_Field, SparseMatrix\_t::ELL\_ZO >, 754
  - Sparse< \_Field, SparseMatrix\_t::HYB\_ZO >, 755
  - Sparse< \_Field, SparseMatrix\_t::SELL >, 757
  - Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, 759
- DelayedField
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, 503
- delayedField
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, 507
- DelayedField\_t
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, 503
- DelayedTag, 442
- deleted
  - Coo< Field >, 437
- DENSE\_THRESHOLD
  - fflas\_sparse.h, 892
- denseCols
  - StatsMatrix, 763
- denseRows
  - StatsMatrix, 763
- Det
  - FFPACK, 332, 333, 356, 357, 376, 377
- det.C, 817
  - main, 817
- Det\_modular\_double
  - ffpack.C, 1006
  - ffpack\_c.h, 1025
- deviationCol
  - StatsMatrix, 762
- deviationColDifference
  - StatsMatrix, 763
- deviationRow
  - StatsMatrix, 762
- deviationRowDifference
  - StatsMatrix, 763
- DFElt
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, 503
- dgemm\_
  - config-blas.h, 830
  - fblas.C, 1058
- dgemv\_
  - config-blas.h, 827
- dger\_
  - config-blas.h, 828
- digits
  - limits< char >, 492
  - limits< double >, 493
  - limits< float >, 493
  - limits< int >, 495
  - limits< long >, 495
  - limits< long long >, 496
  - limits< short int >, 498
  - limits< signed char >, 498
  - limits< unsigned char >, 499
  - limits< unsigned int >, 500
  - limits< unsigned long >, 500
  - limits< unsigned long long >, 501
  - limits< unsigned short int >, 501
- div
  - ScalFunctions< Element >, 560
  - Simd256\_impl< true, false, true, 8 >, 632
  - Simd512\_impl< true, false, true, 8 >, 715
- DivideAndConquer, 442
- dnrm2\_
  - config-blas.h, 827
- DNS\_BIN\_VER
  - read\_sparse.h, 915
- doApplyS
  - FFPACK, 362
- doApplyT
  - FFPACK, 363
- doBenchs
  - Bench< Elt >, 412
- doTests
  - Test< Elt >, 768
- DotProdBoundClassic

- FFLAS::Protected, 216
- DOUBLE\_TO\_FLOAT\_CROSSOVER
  - fflas.h, 834
  - winograd.C, 783
- dscal\_
  - config-blas.h, 828
- dtrmm\_
  - config-blas.h, 829
- dtrsm\_
  - config-blas.h, 829
- DynamicPeeling
  - FFLAS::Protected, 221
- DynamicPeeling2
  - FFLAS::Protected, 221
- EFFGFF
  - benchmark-dsytrf.C, 788
- Element
  - FieldSimd< \_Field >, 451
  - readMyMachineType< Field, mpz\_t >, 530
  - readMyMachineType< Field, T >, 529
  - rns\_double, 532
  - rns\_double\_extended, 543
  - RNSInteger< RNS >, 547
  - RNSIntegerMod< RNS >, 551
  - TestOneMethod< Simd >, 769
- Element\_ptr
  - benchmark-fgemm-rns.C, 793
  - readMyMachineType< Field, mpz\_t >, 530
  - readMyMachineType< Field, T >, 529
  - rns\_double, 532
  - rns\_double\_extended, 543
  - RNSInteger< RNS >, 547
  - RNSIntegerMod< RNS >, 551
- ElementTraits< double >, 442
  - value, 443
- ElementTraits< Element >, 442
  - value, 442
- ElementTraits< FFPACK::rns\_double\_elt >, 443
  - value, 443
- ElementTraits< float >, 443
  - value, 443
- ElementTraits< Givaro::Integer >, 443
  - value, 443
- ElementTraits< int16\_t >, 444
  - value, 444
- ElementTraits< int32\_t >, 444
  - value, 444
- ElementTraits< int64\_t >, 444
  - value, 444
- ElementTraits< int8\_t >, 444
  - value, 445
- ElementTraits< Reclnt::rint< K > >, 445
  - value, 445
- ElementTraits< Reclnt::rmin< K, MG > >, 445
  - value, 445
- ElementTraits< Reclnt::ruint< K > >, 445
  - value, 446
- ElementTraits< uint16\_t >, 446
  - value, 446
- ElementTraits< uint32\_t >, 446
  - value, 446
- ElementTraits< uint64\_t >, 446
  - value, 446
- ElementTraits< uint8\_t >, 447
  - value, 447
- ELL
  - FFLAS, 76
- ell
  - HelperFlag, 478
- ell.h, 905
- ell\_pspmm.inl, 905
  - \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_pspmm\_INL, 906
- ell\_pspmv.inl, 906
  - \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_pspmv\_INL, 907
- ELL\_simd
  - FFLAS, 76
- ell\_simd.h, 909
- ell\_simd\_pspmv.inl, 910
  - \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_simd\_pspmv\_INL, 910
- ell\_simd\_spmv.inl, 910
  - \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_simd\_spmv\_INL, 911
- ell\_simd\_utils.inl, 911
  - \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_simd\_utils\_INL, 912
- ELL\_simd\_ZO
  - FFLAS, 76
- ell\_spm.inl, 907
  - \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_spm\_INL, 908
- ell\_spmv.inl, 908
  - \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_spmv\_INL, 909
- ell\_utils.inl, 909
  - \_\_FFLASFFPACK\_fflas\_sparse\_ELL\_utils\_INL, 909
- ELL\_ZO
  - FFLAS, 76
- EllMat< Field >, 447
  - \_ell16, 447
  - \_ell16\_zo, 447
  - \_ell32, 447
  - \_ell32\_zo, 447
  - \_ell64, 447
  - \_ell64\_zo, 447
- Elt\_ptr
  - Bench< Elt >, 411
  - Test< Elt >, 766
- ENABLE\_ALL\_CHECKINGS
  - benchmark-checkers.C, 785
  - ffpack\_ftrtr.inl, 942
  - test-fdot.C, 1067
  - test-fgemm-check.C, 1069

- test-fsyr2k.C, [1079](#)
- test-fsyrk.C, [1081](#)
- test-ftrmv.C, [1085](#)
- test-ftrsm-check.C, [1086](#)
- test-ftrsm.C, [1087](#)
- test-ftrssyr2k.C, [1088](#)
- test-ftrstr.C, [1089](#)
- test-ftrsv.C, [1090](#)
- test-ftrtri.C, [1091](#)
- test-invert-check.C, [1093](#)
- test-pluq-check.C, [1102](#)
- ENABLE\_CHECKER\_charpoly
  - test-charpoly-check.C, [1060](#)
- ENABLE\_CHECKER\_Det
  - test-det-check.C, [1062](#)
- ENABLE\_CHECKER\_fgemm
  - test-fgemm.C, [1070](#)
- enable\_if\_no\_simd\_t
  - Bench< Elt >, [411](#)
  - Test< Elt >, [767](#)
- enable\_if\_simd128\_t
  - Bench< Elt >, [411](#)
  - Test< Elt >, [767](#)
- enable\_if\_simd256\_t
  - Bench< Elt >, [411](#)
  - Test< Elt >, [767](#)
- enable\_if\_simd512\_t
  - Bench< Elt >, [411](#)
  - Test< Elt >, [767](#)
- enable\_if\_t
  - Bench< Elt >, [411](#)
  - Test< Elt >, [766](#)
  - TestOneMethod< Simd >, [769](#)
- end
  - ForStrategy1D< blocksize\_t, Cut, Param >, [466](#)
- END\_OF\_ARGUMENTS
  - args-parser.h, [1047](#)
- END\_PARALLEL\_MAIN
  - parallel.h, [1040](#)
- eq
  - ScalFunctions< Element >, [561](#)
  - Simd128\_impl< true, true, false, 2 >, [577](#)
  - Simd128\_impl< true, true, false, 4 >, [587](#)
  - Simd128\_impl< true, true, false, 8 >, [597](#)
  - Simd128\_impl< true, true, true, 2 >, [606](#)
  - Simd128\_impl< true, true, true, 4 >, [615](#)
  - Simd128\_impl< true, true, true, 8 >, [624](#)
  - Simd256\_impl< true, false, true, 8 >, [633](#)
  - Simd256\_impl< true, true, false, 2 >, [644](#)
  - Simd256\_impl< true, true, false, 4 >, [662](#)
  - Simd256\_impl< true, true, false, 8 >, [672](#)
  - Simd256\_impl< true, true, true, 2 >, [681](#)
  - Simd256\_impl< true, true, true, 4 >, [692](#), [698](#)
  - Simd256\_impl< true, true, true, 8 >, [707](#)
  - Simd512\_impl< true, false, true, 8 >, [715](#)
  - Simd512\_impl< true, true, false, 8 >, [726](#)
  - Simd512\_impl< true, true, true, 8 >, [735](#)
- eval\_func\_on\_array
  - test-simd.C, [1108](#)
- evaluate\_scalar\_method
  - TestOneMethod< Simd >, [770](#)
- evaluate\_simd\_method
  - TestOneMethod< Simd >, [770](#)
- example
  - Argument, [407](#)
- examples/charpoly.C
  - main, [817](#)
- examples/pluq.C
  - main, [819](#)
- ExpandBlockBiDiagonalToBruhat
  - FFPACK, [350](#)
- expandLCRE
  - FFPACK, [354](#)
- F
  - Bench< Elt >, [412](#)
  - Test< Elt >, [768](#)
- fadd
  - FFLAS, [78](#), [80](#), [82](#), [166](#), [173](#), [174](#)
  - FFLAS::details, [203](#), [204](#)
- fadd\_1\_modular\_double
  - fflas\_c.h, [963](#)
  - fflas\_lvl1.C, [982](#)
- fadd\_2\_modular\_double
  - fflas\_c.h, [966](#)
  - fflas\_lvl2.C, [987](#)
- faddin
  - FFLAS, [78](#), [81](#), [166](#), [175](#)
- faddin\_1\_modular\_double
  - fflas\_c.h, [963](#)
  - fflas\_lvl1.C, [983](#)
- faddin\_2\_modular\_double
  - fflas\_c.h, [967](#)
  - fflas\_lvl2.C, [987](#)
- Failure, [448](#)
  - \_errorStream, [449](#)
  - Failure, [448](#)
  - operator(), [448](#)
  - print, [449](#)
  - setErrorStream, [449](#)
- failure
  - FFPACK, [382](#)
- FailureCharpolyCheck, [449](#)
- FailureDetCheck, [449](#)
- FailureFgemmCheck, [449](#)
- FailureInvertCheck, [450](#)
- FailurePLUQCheck, [450](#)
- FailureTrsmCheck, [450](#)
- fassign
  - FFLAS, [82–84](#), [162](#), [166](#)
- fassign\_1\_modular\_double
  - fflas\_c.h, [962](#)
  - fflas\_lvl1.C, [981](#)
- fassign\_2\_modular\_double
  - fflas\_c.h, [964](#)
  - fflas\_lvl2.C, [984](#)
- faxpby

- FFLAS, [135](#), [141](#)
- faxpy
  - FFLAS, [86](#), [87](#), [164](#), [172](#)
  - FFLAS::details, [205](#)
- faxpy\_1\_modular\_double
  - fflas\_c.h, [962](#)
  - fflas\_lvl1.C, [982](#)
- faxpy\_2\_modular\_double
  - fflas\_c.h, [966](#)
  - fflas\_lvl2.C, [986](#)
- fblas.C, [1057](#)
  - \_\_FFLASFFPACK\_CONFIGURATION, [1058](#)
  - dgemm\_, [1058](#)
  - main, [1058](#)
- fconvert
  - FFLAS, [132](#), [140](#), [160](#)
- fconvert\_rns
  - FFLAS, [157](#), [158](#)
- fconvert\_trans\_rns
  - FFLAS, [158](#)
- fdot
  - FFLAS, [87–89](#), [135](#), [164](#), [184](#)
- fdot\_1\_modular\_double
  - fflas\_c.h, [962](#)
  - fflas\_lvl1.C, [982](#)
- fequal
  - FFLAS, [134](#), [138](#), [162](#), [167](#)
- fequal\_1\_modular\_double
  - fflas\_c.h, [961](#)
  - fflas\_lvl1.C, [981](#)
- fequal\_2\_modular\_double
  - fflas\_c.h, [964](#)
  - fflas\_lvl2.C, [985](#)
- FFLAS, [42](#), [45](#)
  - alignable, [191](#)
  - alignable< Givaro::Integer \* >, [192](#)
  - BaseTimer, [74](#)
  - bitsize, [142](#)
  - bitsize< Givaro::ZRing< Givaro::Integer > >, [142](#)
  - BlockCuts, [181](#), [183](#)
  - BlockCuts< CuttingStrategy::Block, StrategyParameter::Fixed >, [183](#)
  - BlockCuts< CuttingStrategy::Block, StrategyParameter::Grain >, [182](#)
  - BlockCuts< CuttingStrategy::Block, StrategyParameter::Threads >, [183](#)
  - BlockCuts< CuttingStrategy::Column, StrategyParameter::Fixed >, [182](#)
  - BlockCuts< CuttingStrategy::Column, StrategyParameter::Grain >, [182](#)
  - BlockCuts< CuttingStrategy::Column, StrategyParameter::Threads >, [183](#)
  - BlockCuts< CuttingStrategy::Row, StrategyParameter::Fixed >, [182](#)
  - BlockCuts< CuttingStrategy::Row, StrategyParameter::Grain >, [182](#)
  - BlockCuts< CuttingStrategy::Row, StrategyParameter::Threads >, [183](#)
- BlockCuts< CuttingStrategy::Single, StrategyParameter::Threads >, [181](#)
- cblas\_imptrsm, [130](#)
- Checker\_fgemm, [72](#)
- Checker\_ftsm, [72](#)
- computeDeviation, [155](#)
- computeS1S2, [125](#)
- COO, [76](#)
- COO\_ZO, [76](#)
- CSC, [76](#)
- CSC\_ZO, [76](#)
- CSR, [76](#)
- CSR\_HYB, [76](#)
- CSR\_ZO, [76](#)
- ELL, [76](#)
- ELL\_simd, [76](#)
- ELL\_simd\_ZO, [76](#)
- ELL\_ZO, [76](#)
- fadd, [78](#), [80](#), [82](#), [166](#), [173](#), [174](#)
- faddin, [78](#), [81](#), [166](#), [175](#)
- fassign, [82–84](#), [162](#), [166](#)
- faxpby, [135](#), [141](#)
- faxpy, [86](#), [87](#), [164](#), [172](#)
- fconvert, [132](#), [140](#), [160](#)
- fconvert\_rns, [157](#), [158](#)
- fconvert\_trans\_rns, [158](#)
- fdot, [87–89](#), [135](#), [164](#), [184](#)
- fequal, [134](#), [138](#), [162](#), [167](#)
- FFLAS\_BASE, [76](#)
- fflas\_delete, [156](#), [192](#)
- FFLAS\_DIAG, [75](#)
- FFLAS\_FORMAT, [76](#)
- fflas\_new, [157](#), [158](#), [192](#)
- FFLAS\_ORDER, [74](#)
- FFLAS\_SIDE, [75](#)
- FFLAS\_TRANSPOSE, [74](#)
- FFLAS\_UPLO, [75](#)
- FflasAuto, [77](#)
- FflasBinary, [77](#)
- FflasColMajor, [74](#)
- FflasDense, [77](#)
- FflasDouble, [76](#)
- FflasFloat, [76](#)
- FflasGeneric, [76](#)
- FflasLeft, [75](#)
- FflasLeftTri, [75](#)
- FflasLower, [75](#)
- FflasMaple, [77](#)
- FflasMath, [77](#)
- FflasNonUnit, [75](#)
- FflasNoTrans, [75](#)
- FflasRight, [75](#)
- FflasRightTri, [75](#)
- FflasRowMajor, [74](#)
- FflasSageMath, [77](#)
- FflasSMS, [77](#)
- FflasTrans, [75](#)
- FflasUnit, [75](#)

- FflasUpper, 75
- fgemm, 89–91, 93–98, 146, 179, 180
- fgemv, 98–103, 175, 187
- fger, 104–107, 176
- fidentity, 139, 168
- finit, 109, 112, 131, 139, 160, 170
- finit\_rns, 157, 158
- finit\_trans\_rns, 157
- fiszero, 134, 138, 162, 168
- fmove, 142, 172
- fneg, 132, 141, 161, 170
- fnegin, 132, 140, 160, 170
- ForceCheck\_fgemm, 72
- ForceCheck\_ftrsm, 72
- frand, 133, 138
- freduce, 108–110, 113, 159, 169
- freduce\_constoverride, 109, 112
- freivalds, 113
- fscal, 114–118, 163, 171
- fscaln, 114–118, 163, 171
- fspmm, 147
- fspmv, 147, 154
- fsquare, 92, 93, 181
- fsub, 78, 81, 166, 174
- fsubin, 78, 82, 174
- fswap, 135, 165
- fsyr2k, 118
- fsyrk, 119–126
- fsyrk\_strassen, 126, 144
- ftmm, 127, 128, 178
- ftmmv, 143
- ftrsm, 128–130, 143, 147, 177
- ftrsv, 130, 177
- fzero, 133, 137, 161, 167
- getArgumentValue, 188
- getDataType, 153, 154
- getSeed, 193
- getStat, 156
- getTLBSize, 193
- has\_equal, 73
- has\_minus, 73
- has\_minus\_eq, 73
- has\_mul, 73
- has\_mul\_eq, 74
- has\_plus, 73
- has\_plus\_eq, 73
- HYB\_ZO, 76
- igemm\_, 131
- InfNorm, 77
- max3, 77
- max4, 77
- maxCardinality, 156
- maxCardinality< Givaro::Modular< int32\_t > >, 156
- maxCardinality< Givaro::Modular< int64\_t > >, 156
- min3, 77
- min4, 77
- minCardinality, 156
- MKLSparseMatrixFormat, 73
- mone, 76
- NoSimdSparseMatrix, 73
- NotMKLSparseMatrixFormat, 73
- NotZOSparseMatrix, 72
- number\_kind, 76
- one, 76
- operator<<, 153
- other, 76
- parseArguments, 188
- pfadd, 79
- pfaddin, 79
- pfgemm, 144, 184–186
- pfgemm\_1D\_rec, 145
- pfgemm\_2D\_rec, 145
- pfgemm\_3D\_rec, 145
- pfgemm\_3D\_rec2, 146
- pfrand, 184
- pfreduce, 110
- pfsb, 79
- pfsb, 80
- pfzero, 184
- preamble, 190
- prefetch, 192
- queryCacheSizes, 193
- queryL1CacheSize, 193
- queryTopLevelCacheSize, 193
- readDnsFormat, 154
- readMachineType, 154
- ReadMatrix, 190
- readSmsFormat, 153
- readSprFormat, 153
- SELL, 76
- SELL\_ZO, 76
- SimdSparseMatrix, 72
- sparse\_delete, 148–152, 155
- sparse\_init, 148–153, 155
- sparse\_print, 149, 152, 155
- SparseMatrix\_t, 76
- SysTimer, 74
- Timer, 74
- UserTimer, 74
- writeCommandString, 188
- writeDnsFormat, 154
- WriteMatrix, 188, 191
- WritePermutation, 191
- zero, 76
- ZOSparseMatrix, 72
- fflas-101\_1.C, 1112
  - main, 1112
- fflas-101\_3.C, 1112
  - main, 1112
- FFLAS-FFPACK, 41
- FFLAS-FFPACK Documentation., 1
- FFLAS-FFPACK fields, 43
- fflas-ffpack-config.h, 831
  - GCC\_VERSION, 831



- fflas-ffpack-default-thresholds.h, [831](#)
  - \_\_FFLASFFPACK\_ARITHPROG\_THRESHOLD, [832](#)
  - \_\_FFLASFFPACK\_CHARPOLY\_Danilevskii\_LUKrylov\_THRESHOLD, [832](#)
  - \_\_FFLASFFPACK\_CHARPOLY\_LUKrylov\_ArithProg\_THRESHOLD, [832](#)
  - \_\_FFLASFFPACK\_FSYRK\_THRESHOLD, [832](#)
  - \_\_FFLASFFPACK\_FSYTRF\_THRESHOLD, [832](#)
  - \_\_FFLASFFPACK\_FTRTRI\_THRESHOLD, [832](#)
  - \_\_FFLASFFPACK\_PLUQ\_THRESHOLD, [832](#)
  - \_\_FFLASFFPACK\_WINOTHRESHOLD, [831](#)
  - \_\_FFLASFFPACK\_WINOTHRESHOLD\_BAL, [831](#)
  - \_\_FFLASFFPACK\_WINOTHRESHOLD\_BAL\_FLT, [832](#)
  - \_\_FFLASFFPACK\_WINOTHRESHOLD\_FLT, [831](#)
- fflas-ffpack-thresholds.h, [832](#)
- fflas-ffpack.doxy, [832](#)
- fflas-ffpack.h, [832](#)
- fflas-ffpack/config.h
  - \_\_FFLASFFPACK\_HAVE\_BLAS, [813](#)
  - \_\_FFLASFFPACK\_HAVE\_CBLAS, [813](#)
  - \_\_FFLASFFPACK\_HAVE\_CXX11, [813](#)
  - \_\_FFLASFFPACK\_HAVE\_DLFCN\_H, [813](#)
  - \_\_FFLASFFPACK\_HAVE\_FLOAT\_H, [813](#)
  - \_\_FFLASFFPACK\_HAVE\_INT128, [813](#)
  - \_\_FFLASFFPACK\_HAVE\_INTPTR\_T, [813](#)
  - \_\_FFLASFFPACK\_HAVE\_LAPACK, [813](#)
  - \_\_FFLASFFPACK\_HAVE\_LIMITS\_H, [813](#)
  - \_\_FFLASFFPACK\_HAVE\_LITTLE\_ENDIAN, [813](#)
  - \_\_FFLASFFPACK\_HAVE\_PTHREAD\_H, [813](#)
  - \_\_FFLASFFPACK\_HAVE\_STDDEF\_H, [814](#)
  - \_\_FFLASFFPACK\_HAVE\_STDINT\_H, [814](#)
  - \_\_FFLASFFPACK\_HAVE\_STDIO\_H, [814](#)
  - \_\_FFLASFFPACK\_HAVE\_STDLIB\_H, [814](#)
  - \_\_FFLASFFPACK\_HAVE\_STRINGS\_H, [814](#)
  - \_\_FFLASFFPACK\_HAVE\_STRING\_H, [814](#)
  - \_\_FFLASFFPACK\_HAVE\_SYS\_STAT\_H, [814](#)
  - \_\_FFLASFFPACK\_HAVE\_SYS\_TIME\_H, [814](#)
  - \_\_FFLASFFPACK\_HAVE\_SYS\_TYPES\_H, [814](#)
  - \_\_FFLASFFPACK\_HAVE\_UNISTD\_H, [814](#)
  - \_\_FFLASFFPACK\_LT\_OBJDIR, [814](#)
  - \_\_FFLASFFPACK\_OPENBLAS\_NUM\_THREADS, [814](#)
  - \_\_FFLASFFPACK\_PACKAGE, [814](#)
  - \_\_FFLASFFPACK\_PACKAGE\_BUGREPORT, [814](#)
  - \_\_FFLASFFPACK\_PACKAGE\_NAME, [814](#)
  - \_\_FFLASFFPACK\_PACKAGE\_STRING, [815](#)
  - \_\_FFLASFFPACK\_PACKAGE\_TARNAME, [815](#)
  - \_\_FFLASFFPACK\_PACKAGE\_URL, [815](#)
  - \_\_FFLASFFPACK\_PACKAGE\_VERSION, [815](#)
  - \_\_FFLASFFPACK\_SIZEOF\_CHAR, [815](#)
  - \_\_FFLASFFPACK\_SIZEOF\_INT, [815](#)
  - \_\_FFLASFFPACK\_SIZEOF\_LONG, [815](#)
  - \_\_FFLASFFPACK\_SIZEOF\_LONG\_LONG, [815](#)
  - \_\_FFLASFFPACK\_SIZEOF\_SHORT, [815](#)
  - \_\_FFLASFFPACK\_SIZEOF\_\_INT64\_T, [815](#)
  - \_\_FFLASFFPACK\_STDC\_HEADERS, [815](#)
  - \_\_FFLASFFPACK\_USE\_OPENMP, [815](#)
  - \_\_FFLASFFPACK\_VERSION, [815](#)
- fflas.doxy, [832](#)
  - DOUBLE\_TO\_FLOAT\_CROSSOVER, [834](#)
  - FFLAS::\_ftranspose\_impl, [194](#)
  - nonsquare\_inplace\_v1, [194](#)
  - nonsquare\_inplace\_v2, [194](#)
  - not\_inplace, [194](#)
  - square\_inplace, [194](#)
  - FFLAS::BLAS3, [195](#)
  - Bini, [196](#)
  - Winograd, [197](#)
  - Winograd\_L\_S, [200](#)
  - Winograd\_LR\_S, [200](#)
  - Winograd\_R\_S, [201](#)
  - WinogradAcc\_2\_24, [198](#)
  - WinogradAcc\_2\_27, [198](#)
  - WinogradAcc\_3\_21, [198](#)
  - WinogradAcc\_3\_23, [197](#)
  - WinogradAcc\_L\_S, [200](#)
  - WinogradAcc\_LR, [199](#)
  - WinogradAcc\_R\_S, [199](#)
  - WinoPar, [197](#)
  - FFLAS::csr\_hyb\_details, [201](#)
  - FFLAS::CuttingStrategy, [201](#)
  - RNSModulus, [202](#)
  - FFLAS::details, [202](#)
    - BlockingFactor, [210](#)
    - fadd, [203](#), [204](#)
    - faxpy, [205](#)
    - freduce, [205](#), [206](#)
    - fscal, [206](#), [207](#)
    - fscaln, [206](#), [207](#)
    - gebp, [210](#)
    - igebb11, [209](#)
    - igebb14, [208](#)
    - igebb21, [208](#)
    - igebb24, [207](#)
    - igebb41, [208](#)
    - igebb44, [207](#)
    - igebp, [209](#)
    - pack\_lhs, [209](#)
    - pack\_rhs, [209](#)
  - FFLAS::details\_spmv, [210](#)
  - FFLAS::ElementCategories, [211](#)
  - FFLAS::FieldCategories, [211](#)
  - FFLAS::MMHelperAlgo, [211](#)
  - FFLAS::ModeCategories, [212](#)
  - FFLAS::ParSeqHelper, [212](#)
  - FFLAS::Protected, [213](#)
    - computeFactorClassic, [216](#)
    - DotProdBoundClassic, [216](#)
    - DynamicPeeling, [221](#)
    - DynamicPeeling2, [221](#)
    - fgemm\_convert, [217](#)
    - fgemv\_convert, [222](#)



- fgemv\_convert, 223
- fsquareCommon, 220
- fsyrk\_convert, 223
- igemm, 226
- igemm\_colmajor, 226
- MatF2MatD\_Triangular, 227
- MatF2MatFI\_Triangular, 227
- min\_types, 224, 225
- NeedDoublePreAddReduction, 219
- NeedPreAddReduction, 218
- NeedPreAxyReduction, 224
- NeedPreScalReduction, 223, 224
- NeedPreSubReduction, 218
- ScalAndReduce, 219, 223
- TRSMBound, 216, 217
- unfit, 225, 226
- WinogradCalc, 222
- WinogradSteps, 221
- WinogradThreshold, 220
- FFLAS::sell\_details, 227
- FFLAS::sparse\_details, 228
  - fspmm, 234–236
  - fspmm\_dispatch, 233, 234
  - fspmv, 231–233, 241
  - fspmv\_dispatch, 231
  - init\_y, 231
  - pfspmm, 237–239
  - pfspmm\_dispatch, 236, 237
  - pfspmv, 239, 240
- FFLAS::sparse\_details\_impl, 242
  - fspmm, 250, 257, 258, 263, 264, 268, 277
  - fspmm\_mone, 251, 259, 269
  - fspmm\_mone\_simd\_aligned, 252, 259, 270
  - fspmm\_mone\_simd\_unaligned, 252, 260, 270
  - fspmm\_one, 251, 258, 269
  - fspmm\_one\_simd\_aligned, 252, 259, 270
  - fspmm\_one\_simd\_unaligned, 252, 259, 270
  - fspmm\_simd\_aligned, 251, 258
  - fspmm\_simd\_unaligned, 251, 258
  - fspmv, 253, 260, 264, 271, 273, 274, 278, 280
  - fspmv\_mone, 253, 254, 261, 271, 272, 275, 281, 282
  - fspmv\_mone\_simd, 275, 281
  - fspmv\_one, 253, 254, 260, 261, 271, 272, 274, 275, 281
  - fspmv\_one\_simd, 275, 281
  - fspmv\_simd, 274, 280
  - pfspmm, 254, 261, 262, 264–266, 276
  - pfspmm\_mone, 255
  - pfspmm\_one, 255
  - pfspmm\_zo, 266
  - pfspmv, 256, 263, 266, 267, 272, 276–279
  - pfspmv\_mone, 257, 267, 268, 273, 279
  - pfspmv\_one, 256, 257, 267, 273, 279
  - pfspmv\_task, 256
- FFLAS::StrategyParameter, 282
- FFLAS::StructureHelper, 282
- FFLAS::vectorised, 283
  - add, 285
  - addp, 284
  - axpyp, 285
  - modp, 287
  - reduce, 286, 287
  - scalp, 287, 288
  - sub, 285
  - subp, 285
  - VEC\_ADD, 284
  - VEC\_SUB, 284
- FFLAS::vectorised::unswitch, 288
  - axpyp, 289
  - modp, 289, 290
  - scalp, 290
- fflas\_101.C, 1112
  - main, 1113
- fflas\_101\_lvl1.C, 1113
  - main, 1113
- FFLAS\_BASE
  - FFLAS, 76
- fflas\_bounds.inl, 834
  - \_\_FFLASFFPACK\_fflas\_bounds\_INL, 835
  - FFLAS\_INT\_TYPE, 835
- fflas\_c.h, 957
  - fadd\_1\_modular\_double, 963
  - fadd\_2\_modular\_double, 966
  - faddin\_1\_modular\_double, 963
  - faddin\_2\_modular\_double, 967
  - fassign\_1\_modular\_double, 962
  - fassign\_2\_modular\_double, 964
  - faxpy\_1\_modular\_double, 962
  - faxpy\_2\_modular\_double, 966
  - fdot\_1\_modular\_double, 962
  - fequal\_1\_modular\_double, 961
  - fequal\_2\_modular\_double, 964
  - FFLAS\_C\_BASE, 960
  - FFLAS\_C\_DIAG, 960
  - FFLAS\_C\_ORDER, 959
  - FFLAS\_C\_SIDE, 960
  - FFLAS\_C\_TRANSPOSE, 959
  - FFLAS\_C\_UPLO, 960
  - FFLAS\_COMPILED, 959
  - FflasColMajor, 959
  - FflasDouble, 960
  - FflasFloat, 960
  - FflasGeneric, 960
  - FflasLeft, 960
  - FflasLower, 960
  - FflasNonUnit, 960
  - FflasNoTrans, 960
  - FflasRight, 960
  - FflasRowMajor, 959
  - FflasTrans, 960
  - FflasUnit, 960
  - FflasUpper, 960
  - fgemm\_3\_modular\_double, 968
  - fgemv\_2\_modular\_double, 967
  - fgemv\_2\_modular\_double, 967

- fidentity\_2\_modular\_double, [964](#)
- fiszero\_1\_modular\_double, [961](#)
- fiszero\_2\_modular\_double, [964](#)
- fmove\_2\_modular\_double, [966](#)
- fneg\_1\_modular\_double, [961](#)
- fneg\_2\_modular\_double, [965](#)
- fnegin\_1\_modular\_double, [961](#)
- fnegin\_2\_modular\_double, [965](#)
- freduce\_1\_modular\_double, [961](#)
- freduce\_2\_modular\_double, [965](#)
- freducein\_1\_modular\_double, [961](#)
- freducein\_2\_modular\_double, [965](#)
- fscal\_1\_modular\_double, [962](#)
- fscal\_2\_modular\_double, [965](#)
- fscalin\_1\_modular\_double, [962](#)
- fscalin\_2\_modular\_double, [965](#)
- fsquare\_3\_modular\_double, [969](#)
- fsub\_1\_modular\_double, [963](#)
- fsub\_2\_modular\_double, [966](#)
- fsubin\_1\_modular\_double, [963](#)
- fsubin\_2\_modular\_double, [967](#)
- fswap\_1\_modular\_double, [963](#)
- ftmm\_3\_modular\_double, [968](#)
- ftsm\_3\_modular\_double, [968](#)
- ftsv\_2\_modular\_double, [968](#)
- fzero\_1\_modular\_double, [961](#)
- fzero\_2\_modular\_double, [964](#)
- FFLAS\_C\_BASE
  - fflas\_c.h, [960](#)
- FFLAS\_C\_DIAG
  - fflas\_c.h, [960](#)
  - ffpack\_c.h, [1015](#)
- FFLAS\_C\_ORDER
  - fflas\_c.h, [959](#)
  - ffpack\_c.h, [1014](#)
- FFLAS\_C\_SIDE
  - fflas\_c.h, [960](#)
  - ffpack\_c.h, [1015](#)
- FFLAS\_C\_TRANSPOSE
  - fflas\_c.h, [959](#)
  - ffpack\_c.h, [1014](#)
- FFLAS\_C\_UPLO
  - fflas\_c.h, [960](#)
  - ffpack\_c.h, [1014](#)
- FFLAS\_COMPILED
  - fflas\_c.h, [959](#)
  - ffpack\_inst.C, [1031](#)
  - ffpack\_inst.h, [1032](#)
- fflas\_const\_cast
  - FFPACK, [369](#), [382](#)
- fflas\_delete
  - FFLAS, [156](#), [192](#)
- FFLAS\_DIAG
  - FFLAS, [75](#)
- FFLAS\_ELT
  - fflas\_L1\_inst.C, [970](#)
  - fflas\_L1\_inst.h, [971](#)
  - fflas\_L2\_inst.C, [973](#)
  - fflas\_L2\_inst.h, [974](#)
  - fflas\_L3\_inst.C, [977](#)
  - fflas\_L3\_inst.h, [978](#)
  - ffpack\_inst.C, [1031](#)
  - ffpack\_inst.h, [1032](#)
- fflas\_enum.h, [835](#)
- fflas\_fadd.h, [835](#)
- fflas\_fadd.inl, [837](#)
  - \_\_FFLASFFPACK\_fadd\_INL, [838](#)
- fflas\_fassign.h, [838](#)
- fflas\_fassign.inl, [838](#)
  - \_\_FFLASFFPACK\_fassign\_INL, [839](#)
- fflas\_faxpy.inl, [839](#)
  - \_\_FFLASFFPACK\_faxpy\_INL, [840](#)
- fflas\_fdot.inl, [840](#)
  - \_\_FFLASFFPACK\_fdot\_INL, [841](#)
- fflas\_fgemm.inl, [841](#)
  - \_\_FFLASFFPACK\_fgemm\_INL, [843](#)
- fflas\_fgmv.inl, [849](#)
  - \_\_FFLASFFPACK\_fgmv\_INL, [851](#)
- fflas\_fgmv\_mp.inl, [851](#)
  - \_\_FFLASFFPACK\_fgmv\_mp\_INL, [852](#)
- fflas\_fger.inl, [852](#)
  - \_\_FFLASFFPACK\_fger\_INL, [853](#)
- fflas\_fger\_mp.inl, [853](#)
  - \_\_FFPACK\_fger\_mp\_INL, [853](#)
- FFLAS\_FIELD
  - fflas\_L1\_inst.C, [969](#), [970](#)
  - fflas\_L1\_inst.h, [970](#), [971](#)
  - fflas\_L2\_inst.C, [973](#)
  - fflas\_L2\_inst.h, [974](#)
  - fflas\_L3\_inst.C, [977](#)
  - fflas\_L3\_inst.h, [978](#)
  - ffpack\_inst.C, [1031](#)
  - ffpack\_inst.h, [1032](#)
- FFLAS\_FORMAT
  - FFLAS, [76](#)
- fflas\_freduce.h, [854](#)
- fflas\_freduce.inl, [855](#)
  - \_\_FFLASFFPACK\_fflas\_freduce\_INL, [856](#)
  - FFLASFFPACK\_COPY\_REDUCE, [856](#)
- fflas\_freduce\_mp.inl, [856](#)
  - \_\_FFLASFFPACK\_fflas\_freduce\_mp\_INL, [856](#)
- fflas\_freivalds.inl, [857](#)
  - \_\_FFLASFFPACK\_freivalds\_INL, [857](#)
- fflas\_fscal.h, [857](#)
- fflas\_fscal.inl, [857](#)
  - \_\_FFLASFFPACK\_fscal\_INL, [858](#)
- fflas\_fscal\_mp.inl, [859](#)
  - \_\_FFLASFFPACK\_fscal\_mp\_INL, [859](#)
- fflas\_fsyr2k.inl, [859](#)
  - \_\_FFLASFFPACK\_fflas\_fsyr2k\_INL, [860](#)
- fflas\_fsyk.inl, [860](#)
  - \_\_FFLASFFPACK\_fflas\_fsyk\_INL, [862](#)
- fflas\_fsyk\_strassen.inl, [862](#)
  - \_\_FFLASFFPACK\_fflas\_fsyk\_strassen\_INL, [863](#)
- fflas\_ftmm.inl, [863](#)
  - \_\_FFLASFFPACK\_ftmm\_INL, [863](#)

- fflas\_ftrsm.inl, 863
  - \_\_FFLASFFPACK\_ftrsm\_INL, 864
- fflas\_ftrsm\_mp.inl, 864
  - \_\_FFPACK\_ftrsm\_mp\_INL, 864
- fflas\_ftrsv.inl, 865
  - \_\_FFLASFFPACK\_ftrsv\_INL, 865
- fflas\_helpers.inl, 865
  - \_\_FFLASFFPACK\_fflas\_fflas\_mmhelper\_INL, 866
- FFLAS\_INT\_TYPE
  - fflas\_bounds.inl, 835
- fflas\_intrinsic.h, 1050
- fflas\_io.h, 1050
- fflas\_L1\_inst.C, 969
  - \_\_FFLAS\_L1\_INST\_C, 969
  - FFLAS\_ELT, 970
  - FFLAS\_FIELD, 969, 970
  - INST\_OR\_DECL, 969
- fflas\_L1\_inst.h, 970
  - FFLAS\_ELT, 971
  - FFLAS\_FIELD, 970, 971
  - INST\_OR\_DECL, 970
- fflas\_L1\_inst\_implem.inl, 971
- fflas\_L2\_inst.C, 972
  - \_\_FFLAS\_L2\_INST\_C, 973
  - FFLAS\_ELT, 973
  - FFLAS\_FIELD, 973
  - INST\_OR\_DECL, 973
- fflas\_L2\_inst.h, 973
  - FFLAS\_ELT, 974
  - FFLAS\_FIELD, 974
  - INST\_OR\_DECL, 974
- fflas\_L2\_inst\_implem.inl, 974
- fflas\_L3\_inst.C, 976
  - \_\_FFLAS\_L3\_INST\_C, 976
  - FFLAS\_ELT, 977
  - FFLAS\_FIELD, 977
  - INST\_OR\_DECL, 976
- fflas\_L3\_inst.h, 977
  - FFLAS\_ELT, 978
  - FFLAS\_FIELD, 978
  - INST\_OR\_DECL, 978
- fflas\_L3\_inst\_implem.inl, 978
  - \_\_FFLAS\_TRSM\_READONLY, 979
- fflas\_level1.inl, 869
  - \_\_FFLASFFPACK\_fflas\_fflas\_level1\_INL, 872
- fflas\_level2.inl, 872
  - \_\_FFLASFFPACK\_fflas\_fflas\_level2\_INL, 874
- fflas\_level3.inl, 874
  - \_\_FFLASFFPACK\_fflas\_fflas\_level3\_INL, 877
  - \_\_FFLAS\_TRSM\_READONLY, 877
- fflas\_lvl1.C, 979
  - fadd\_1\_modular\_double, 982
  - faddin\_1\_modular\_double, 983
  - fassign\_1\_modular\_double, 981
  - faxpy\_1\_modular\_double, 982
  - fdot\_1\_modular\_double, 982
  - fequal\_1\_modular\_double, 981
  - fiszero\_1\_modular\_double, 981
  - fneg\_1\_modular\_double, 980
  - fnegin\_1\_modular\_double, 980
  - freduce\_1\_modular\_double, 980
  - freducein\_1\_modular\_double, 980
  - fscal\_1\_modular\_double, 981
  - fscalin\_1\_modular\_double, 981
  - fsub\_1\_modular\_double, 982
  - fsubin\_1\_modular\_double, 983
  - fswap\_1\_modular\_double, 982
  - fzero\_1\_modular\_double, 981
- fflas\_lvl2.C, 983
  - fadd\_2\_modular\_double, 987
  - faddin\_2\_modular\_double, 987
  - fassign\_2\_modular\_double, 984
  - faxpy\_2\_modular\_double, 986
  - fequal\_2\_modular\_double, 985
  - fgemv\_2\_modular\_double, 988
  - fger\_2\_modular\_double, 988
  - fidentity\_2\_modular\_double, 985
  - fiszero\_2\_modular\_double, 985
  - fmove\_2\_modular\_double, 987
  - fneg\_2\_modular\_double, 986
  - fnegin\_2\_modular\_double, 986
  - freduce\_2\_modular\_double, 985
  - freducein\_2\_modular\_double, 985
  - fscal\_2\_modular\_double, 986
  - fscalin\_2\_modular\_double, 986
  - fsub\_2\_modular\_double, 987
  - fsubin\_2\_modular\_double, 987
  - ftrsv\_2\_modular\_double, 988
  - fzero\_2\_modular\_double, 984
- fflas\_lvl3.C, 989
  - fgemm\_3\_modular\_double, 990
  - fsquare\_3\_modular\_double, 990
  - ftrmm\_3\_modular\_double, 989
  - ftrsm\_3\_modular\_double, 989
- fflas\_memory.h, 1051
- fflas\_new
  - FFLAS, 157, 158, 192
- FFLAS\_ORDER
  - FFLAS, 74
- fflas\_pfgemm.inl, 877
  - \_\_FFLASFFPACK\_DIMKPENALTY, 877
  - \_\_FFLASFFPACK\_SEQPARTHRESHOLD, 877
  - \_\_FFLASFFPACK\_fflas\_pfgemm\_INL, 877
- fflas\_pftrsm.inl, 878
  - \_\_FFLASFFPACK\_fflas\_pftrsm\_INL, 878
  - PTRSM\_HYBRID\_THRESHOLD, 878
- fflas\_plevel1.h, 1038
- fflas\_randommatrix.h, 1051
- FFLAS\_SIDE
  - FFLAS, 75
- fflas\_simd.h, 878
  - CONST, 879
  - FLOAT\_MOD, 880
  - INLINE, 879
  - NORML\_MOD, 879
  - PURE, 879

- Simd, 880
- SIMD\_INT, 879
- fflas\_sparse.C, 990
- fflas\_sparse.h, 888
  - \_\_FFLASFFPACK\_CACHE\_LINE\_SIZE, 892
  - assume\_aligned, 892
  - DENSE\_THRESHOLD, 892
  - index\_t, 892
  - ROUND\_DOWN, 892
- fflas\_sparse.inl, 892
  - \_\_FFLASFFPACK\_fflas\_fflas\_sparse\_INL, 894
- FFLAS\_TRANSPOSE
  - FFLAS, 74
- fflas\_transpose.h, 920
  - FFLAS\_TRANSPOSE\_BLOCKSIZE, 921
  - LD, 921
  - ST, 921
- FFLAS\_TRANSPOSE\_BLOCKSIZE
  - fflas\_transpose.h, 921
- FFLAS\_UPLO
  - FFLAS, 75
- FflasAuto
  - FFLAS, 77
- FflasBinary
  - FFLAS, 77
- FflasColMajor
  - FFLAS, 74
  - fflas\_c.h, 959
  - ffpack\_c.h, 1014
- FflasDense
  - FFLAS, 77
- FflasDouble
  - FFLAS, 76
  - fflas\_c.h, 960
- FFLASFFPACK\_abort
  - debug.h, 1050
- FFLASFFPACK\_check
  - debug.h, 1049
- FFLASFFPACK\_checkers\_fflas\_inl\_H
  - checkers\_fflas.inl, 823
- FFLASFFPACK\_checkers\_ffpack\_inl\_H
  - checkers\_ffpack.inl, 824
- FFLASFFPACK\_COPY\_REDUCE
  - fflas\_freduce.inl, 856
- FFLASFFPACK\_PERM\_BKSIZE
  - ffpack\_permutation.inl, 947
- FflasFloat
  - FFLAS, 76
  - fflas\_c.h, 960
- FflasGeneric
  - FFLAS, 76
  - fflas\_c.h, 960
- FflasLeft
  - FFLAS, 75
  - fflas\_c.h, 960
  - ffpack\_c.h, 1015
- FflasLeftTri
  - FFLAS, 75
- FflasLower
  - FFLAS, 75
  - fflas\_c.h, 960
  - ffpack\_c.h, 1015
- FflasMaple
  - FFLAS, 77
- FflasMath
  - FFLAS, 77
- FflasNonUnit
  - FFLAS, 75
  - fflas\_c.h, 960
  - ffpack\_c.h, 1015
- FflasNoTrans
  - FFLAS, 75
  - fflas\_c.h, 960
  - ffpack\_c.h, 1014
- FflasRight
  - FFLAS, 75
  - fflas\_c.h, 960
  - ffpack\_c.h, 1015
- FflasRightTri
  - FFLAS, 75
- FflasRowMajor
  - FFLAS, 74
  - fflas\_c.h, 959
  - ffpack\_c.h, 1014
- FflasSageMath
  - FFLAS, 77
- FflasSMS
  - FFLAS, 77
- FflasTrans
  - FFLAS, 75
  - fflas\_c.h, 960
  - ffpack\_c.h, 1014
- FflasUnit
  - FFLAS, 75
  - fflas\_c.h, 960
  - ffpack\_c.h, 1015
- FflasUpper
  - FFLAS, 75
  - fflas\_c.h, 960
  - ffpack\_c.h, 1015
- FFPACK, 43, 291
  - \_PLUQ, 368
  - applyP, 309, 310, 370
  - applyP\_block, 362
  - Bruhat2EchelonPermutation, 350
  - buildMatrix, 356
  - CharPoly, 327, 328, 356, 374, 375
  - Checker\_charpoly, 308
  - Checker\_Det, 307
  - Checker\_invert, 308
  - Checker\_PLUQ, 307
  - chooseField, 395
  - chooseField< Givaro::ZRing< double > >, 395
  - chooseField< Givaro::ZRing< float > >, 395
  - chooseField< Givaro::ZRing< int32\_t > >, 395
  - chooseField< Givaro::ZRing< int64\_t > >, 395

- ColRankProfileSubmatrix, [340](#), [379](#)
- ColRankProfileSubmatrixIndices, [339](#), [379](#)
- ColumnEchelonForm, [321](#), [373](#)
- ColumnRankProfile, [336](#), [337](#), [378](#)
- composePermutationsLLL, [365](#)
- composePermutationsLLM, [365](#)
- composePermutationsMLM, [366](#)
- CompressToBlockBiDiagonal, [349](#)
- ComputeRPermutation, [351](#), [354](#)
- cyclic\_shift\_col, [367](#), [370](#)
- cyclic\_shift\_mathPerm, [366](#)
- cyclic\_shift\_row, [366](#), [369](#)
- cyclic\_shift\_row\_col, [366](#), [369](#)
- Danilevski, [356](#)
- Det, [332](#), [333](#), [356](#), [357](#), [376](#), [377](#)
- doApplyS, [362](#)
- doApplyT, [363](#)
- ExpandBlockBiDiagonalToBruhat, [350](#)
- expandLCRE, [354](#)
- failure, [382](#)
- fflas\_const\_cast, [369](#), [382](#)
- fgesv, [312](#), [313](#), [371](#)
- fgetrs, [311](#), [312](#), [370](#)
- ForceCheck\_charpoly, [308](#)
- ForceCheck\_Det, [308](#)
- ForceCheck\_invert, [308](#)
- ForceCheck\_PLUQ, [308](#)
- fsytrf, [316](#), [317](#)
- fsytrf\_BC\_Crout, [357](#)
- fsytrf\_BC\_RL, [357](#)
- fsytrf\_LOW\_RPM\_BC\_Crout, [358](#)
- fsytrf\_nonunit, [317](#), [358](#), [359](#)
- fsytrf\_RPM, [359](#)
- fsytrf\_UP\_RPM, [358](#)
- fsytrf\_UP\_RPM\_BC\_Crout, [358](#)
- fsytrf\_UP\_RPM\_BC\_RL, [357](#)
- ftssyr2k, [316](#)
- ftstr, [315](#)
- fttri, [314](#), [371](#)
- fttrm, [315](#), [372](#)
- getEchelonForm, [342](#), [343](#)
- getEchelonForm< FFLAS\_FIELD< FFLAS\_ELT >  
>, [380](#)
- getEchelonTransform, [344](#)
- getEchelonTransform< FFLAS\_FIELD< FFLAS\_ELT  
> >, [380](#)
- getLTBruhatGen, [347](#), [348](#)
- getReducedEchelonForm, [344](#), [345](#)
- getReducedEchelonForm< FFLAS\_FIELD<  
FFLAS\_ELT > >, [381](#)
- getReducedEchelonTransform, [346](#)
- getReducedEchelonTransform< FFLAS\_FIELD<  
FFLAS\_ELT > >, [381](#)
- getTriangular, [341](#), [342](#)
- getTriangular< FFLAS\_FIELD< FFLAS\_ELT > >,  
[379](#), [380](#)
- getTridiagonal, [359](#)
- Invert, [325](#), [326](#), [374](#)
- Invert2, [326](#), [374](#)
- isOdd, [382](#)
- IsSingular, [331](#), [376](#)
- KrylovElim, [376](#)
- LAPACKPerm2MathPerm, [308](#)
- LeadingSubmatrixRankProfiles, [338](#)
- LQUPtoInverseOfFullRankMinor, [352](#), [382](#)
- LTBruhatGen, [347](#)
- LTQSorder, [349](#)
- LUdivine, [320](#), [360](#), [372](#)
- LUdivine\_gauss, [359](#), [373](#)
- LUdivine\_small, [360](#), [372](#)
- MathPerm2LAPACKPerm, [308](#)
- MatrixApplyS, [362](#), [363](#)
- MatrixApplyT, [364](#)
- MatVecMinPoly, [330](#), [375](#)
- MinPoly, [329](#), [375](#)
- MonotonicApplyP, [310](#)
- MonotonicCompress, [361](#)
- MonotonicCompressCycles, [361](#)
- MonotonicCompressMorePivots, [361](#)
- MonotonicExpand, [362](#)
- NonZeroRandomMatrix, [382](#), [383](#)
- NullSpaceBasis, [334](#), [378](#)
- pColumnEchelonForm, [321](#)
- pColumnRankProfile, [337](#)
- pDet, [332](#)
- PermApplyS, [363](#)
- PermApplyT, [365](#)
- PLUQ, [318](#), [319](#), [368](#), [369](#), [372](#)
- PLUQ\_basecaseCrout, [367](#)
- PLUQ\_basecaseV2, [367](#)
- PLUQ\_basecaseV3, [367](#)
- PLUQtoEchelonPermutation, [347](#)
- pPLUQ, [319](#)
- pRank, [331](#)
- pReducedColumnEchelonForm, [324](#)
- pReducedRowEchelonForm, [325](#)
- productBruhatxTS, [351](#), [354](#)
- pRowEchelonForm, [322](#)
- pRowRankProfile, [336](#)
- pSolve, [334](#)
- RandInt, [386](#)
- RandomIndexSubset, [388](#)
- RandomLTQSMatixWithRankandQSorder, [395](#)
- RandomLTQSRankProfileMatrix, [389](#)
- RandomMatrix, [384](#)
- RandomMatrixWithDet, [394](#)
- RandomMatrixWithRank, [386](#), [387](#)
- RandomMatrixWithRankandRandomRPM, [392](#)
- RandomMatrixWithRankandRPM, [389](#), [390](#)
- RandomNullSpaceVector, [334](#), [352](#), [378](#)
- RandomPermutation, [388](#)
- RandomRankProfileMatrix, [388](#)
- RandomSymmetricMatrix, [386](#)
- RandomSymmetricMatrixWithRankandRandom-  
RPM, [393](#)

- RandomSymmetricMatrixWithRankandRPM, 390, 391
- RandomSymmetricRankProfileMatrix, 389
- RandomTriangularMatrix, 385
- Rank, 330, 331, 376
- RankProfileFromLU, 337
- ReducedColumnEchelonForm, 323, 324, 374
- ReducedRowEchelonForm, 324, 325, 373
- RowEchelonForm, 322, 323, 373
- RowRankProfile, 335, 336, 378
- RowRankProfileSubmatrix, 340, 379
- RowRankProfileSubmatrixIndices, 338, 379
- Solve, 333, 377
- solveLB, 353, 377
- solveLB2, 353, 377
- SpecRankProfile, 376
- swapval, 389
- threads\_fgemm, 368
- threads\_ftrsm, 368
- TInverter, 351, 353
- trinv\_left, 314, 372
- ffpack-fgesv.C, 1113
  - main, 1113
- ffpack-solve.C, 1113
  - main, 1114
- ffpack.C, 991
  - applyP\_modular\_double, 996
  - ColRankProfileSubmatrix\_modular\_double, 1008
  - ColRankProfileSubmatrixIndices\_modular\_double, 1008
  - ColumnEchelonForm\_modular\_double, 999
  - ColumnEchelonForm\_modular\_float, 999
  - ColumnEchelonForm\_modular\_int32\_t, 1000
  - ColumnRankProfile\_modular\_double, 1007
  - composePermutationsLLL, 995
  - composePermutationsLLM, 995
  - composePermutationsMLM, 995
  - cyclic\_shift\_col\_modular\_double, 996
  - cyclic\_shift\_mathPerm, 996
  - cyclic\_shift\_row\_modular\_double, 996
  - Det\_modular\_double, 1006
  - fgesv\_modular\_double, 997
  - fgesvin\_modular\_double, 997
  - fgetrsin\_modular\_double, 996
  - fgetrsv\_modular\_double, 997
  - fttri\_modular\_double, 997
  - fttrm\_modular\_double, 998
  - getEchelonForm\_modular\_double, 1009
  - getEchelonFormin\_modular\_double, 1009
  - getEchelonTransform\_modular\_double, 1010
  - getReducedEchelonForm\_modular\_double, 1010
  - getReducedEchelonFormin\_modular\_double, 1010
  - getReducedEchelonTransform\_modular\_double, 1010
  - getTriangular\_modular\_double, 1009
  - getTriangularin\_modular\_double, 1009
  - Invert2\_modular\_double, 1005
  - Invert\_modular\_double, 1004
  - Invertin\_modular\_double, 1004
  - IsSingular\_modular\_double, 1005
  - KrylovElim\_modular\_double, 1005
  - LAPACKPerm2MathPerm, 994
  - LeadingSubmatrixRankProfiles, 1007
  - LUdivine\_modular\_double, 998
  - MathPerm2LAPACKPerm, 994
  - MatrixApplyS\_modular\_double, 994
  - MatrixApplyT\_modular\_double, 995
  - NullSpaceBasis\_modular\_double, 1007
  - pColumnEchelonForm\_modular\_double, 1001
  - pColumnEchelonForm\_modular\_float, 1002
  - pColumnEchelonForm\_modular\_int32\_t, 1003
  - PermApplyS\_double, 995
  - PermApplyT\_double, 995
  - PLUQ\_modular\_double, 998
  - PLUQtoEchelonPermutation, 1011
  - pReducedColumnEchelonForm\_modular\_double, 1002
  - pReducedColumnEchelonForm\_modular\_float, 1003
  - pReducedColumnEchelonForm\_modular\_int32\_t, 1004
  - pReducedRowEchelonForm\_modular\_double, 1002
  - pReducedRowEchelonForm\_modular\_float, 1003
  - pReducedRowEchelonForm\_modular\_int32\_t, 1004
  - pRowEchelonForm\_modular\_double, 1002
  - pRowEchelonForm\_modular\_float, 1003
  - pRowEchelonForm\_modular\_int32\_t, 1003
  - RandomNullSpaceVector\_modular\_double, 1006
  - Rank\_modular\_double, 1005
  - RankProfileFromLU, 1007
  - ReducedColumnEchelonForm\_modular\_double, 999
  - ReducedColumnEchelonForm\_modular\_float, 1000
  - ReducedColumnEchelonForm\_modular\_int32\_t, 1001
  - ReducedRowEchelonForm\_modular\_double, 999
  - ReducedRowEchelonForm\_modular\_float, 1000
  - ReducedRowEchelonForm\_modular\_int32\_t, 1001
  - RowEchelonForm\_modular\_double, 999
  - RowEchelonForm\_modular\_float, 1000
  - RowEchelonForm\_modular\_int32\_t, 1001
  - RowRankProfile\_modular\_double, 1007
  - RowRankProfileSubmatrix\_modular\_double, 1008
  - RowRankProfileSubmatrixIndices\_modular\_double, 1008
  - Solve\_modular\_double, 1006
  - solveLB2\_modular\_double, 1006
  - solveLB\_modular\_double, 1006
  - SpecRankProfile\_modular\_double, 1005
  - trinv\_left\_modular\_double, 998
- ffpack.doxy, 921
- ffpack.h, 921



- \_\_FFLASFFPACK\_FTRSSYR2K\_THRESHOLD, 930
- \_\_FFLASFFPACK\_FTRSTR\_THRESHOLD, 930
- ffpack.inl, 930
- \_\_FFLASFFPACK\_ffpack\_INL, 931
- FFPACK::Protected, 396
  - ArithProg, 400
  - CompressRows, 401
  - CompressRowsQA, 402
  - CompressRowsQK, 402
  - Danilevski, 399
  - DeCompressRows, 402
  - DeCompressRowsQA, 402
  - DeCompressRowsQK, 402
  - fgemv\_kgf, 399
  - GaussJordan, 398
  - Hybrid\_KGF\_LUK\_MinPoly, 401
  - KellerGehrig, 398
  - KGFast, 398
  - KGFast\_generalized, 399
  - LUdivine\_construct, 397, 403
  - LUKrylov, 399
  - LUKrylov\_KGFast, 400
  - MatVecMinPoly, 400
  - newD, 401
  - RandomKrylovPrecond, 400
  - updatedD, 401
- ffpack\_bruhatgen.inl, 931
- \_\_FFLASFFPACK\_ffpack\_bruhatgen\_inl, 933
- ffpack\_c.h, 1011
  - applyP\_modular\_double, 1018
  - ColRankProfileSubmatrix\_modular\_double, 1028
  - ColRankProfileSubmatrixIndices\_modular\_double, 1028
  - ColumnEchelonForm\_modular\_double, 1021
  - ColumnEchelonForm\_modular\_float, 1021
  - ColumnEchelonForm\_modular\_int32\_t, 1021
  - ColumnRankProfile\_modular\_double, 1027
  - composePermutationsLLL, 1017
  - composePermutationsLLM, 1017
  - composePermutationsMLM, 1017
  - cyclic\_shift\_col\_modular\_double, 1017
  - cyclic\_shift\_mathPerm, 1017
  - cyclic\_shift\_row\_modular\_double, 1017
  - Det\_modular\_double, 1025
  - FFLAS\_C\_DIAG, 1015
  - FFLAS\_C\_ORDER, 1014
  - FFLAS\_C\_SIDE, 1015
  - FFLAS\_C\_TRANSPOSE, 1014
  - FFLAS\_C\_UPLO, 1014
  - FflasColMajor, 1014
  - FflasLeft, 1015
  - FflasLower, 1015
  - FflasNonUnit, 1015
  - FflasNoTrans, 1014
  - FflasRight, 1015
  - FflasRowMajor, 1014
  - FflasTrans, 1014
  - FflasUnit, 1015
  - FflasUpper, 1015
  - FFPACK\_C\_CHARPOLY\_TAG, 1015
  - FFPACK\_C\_LU\_TAG, 1015
  - FFPACK\_C\_MINPOLY\_TAG, 1015
  - FFPACK\_COMPILED, 1014
  - FfpackArithProg, 1015
  - FfpackDanilevski, 1015
  - FfpackDense, 1016
  - FfpackHybrid, 1015
  - FfpackKG, 1015
  - FfpackKGF, 1016
  - FfpackKGFast, 1015
  - FfpackKGFastG, 1015
  - FfpackLUK, 1015
  - FfpackSingular, 1015
  - FfpackSlabRecursive, 1015
  - FfpackTileRecursive, 1015
  - fgesv\_modular\_double, 1019
  - fgesvin\_modular\_double, 1018
  - fgetrs\_modular\_double, 1018
  - fgetrsin\_modular\_double, 1018
  - fttrtri\_modular\_double, 1019
  - fttrrm\_modular\_double, 1019
  - getEchelonForm\_modular\_double, 1029
  - getEchelonFormin\_modular\_double, 1029
  - getEchelonTransform\_modular\_double, 1029
  - getReducedEchelonForm\_modular\_double, 1030
  - getReducedEchelonFormin\_modular\_double, 1030
  - getReducedEchelonTransform\_modular\_double, 1030
  - getTriangular\_modular\_double, 1028
  - getTriangularin\_modular\_double, 1028
  - Invert2\_modular\_double, 1024
  - Invert\_modular\_double, 1024
  - Invertin\_modular\_double, 1024
  - IsSingular\_modular\_double, 1025
  - KrylovElim\_modular\_double, 1024
  - LAPACKPerm2MathPerm, 1016
  - LeadingSubmatrixRankProfiles, 1027
  - LUdivine\_gauss\_modular\_double, 1020
  - LUdivine\_modular\_double, 1020
  - LUdivine\_small\_modular\_double, 1020
  - MathPerm2LAPACKPerm, 1016
  - MatrixApplyS\_modular\_double, 1016
  - MatrixApplyT\_modular\_double, 1016
  - NullSpaceBasis\_modular\_double, 1026
  - PermApplyS\_double, 1016
  - PermApplyT\_double, 1017
  - PLUQ\_modular\_double, 1020
  - PLUQtoEchelonPermutation, 1030
  - RandomNullSpaceVector\_modular\_double, 1026
  - Rank\_modular\_double, 1025
  - RankProfileFromLU, 1027
  - ReducedColumnEchelonForm\_modular\_double, 1022

- ReducedColumnEchelonForm\_modular\_float, 1022
- ReducedColumnEchelonForm\_modular\_int32\_t, 1023
- ReducedRowEchelonForm2\_modular\_double, 1023
- ReducedRowEchelonForm\_modular\_double, 1022
- ReducedRowEchelonForm\_modular\_float, 1023
- ReducedRowEchelonForm\_modular\_int32\_t, 1023
- REF\_modular\_double, 1024
- RowEchelonForm\_modular\_double, 1021
- RowEchelonForm\_modular\_float, 1021
- RowEchelonForm\_modular\_int32\_t, 1022
- RowRankProfile\_modular\_double, 1027
- RowRankProfileSubmatrix\_modular\_double, 1028
- RowRankProfileSubmatrixIndices\_modular\_double, 1027
- Solve\_modular\_double, 1025
- solveLB2\_modular\_double, 1026
- solveLB\_modular\_double, 1026
- SpecRankProfile\_modular\_double, 1025
- trinv\_left\_modular\_double, 1019
- FFPACK\_C\_CHARPOLY\_TAG
  - ffpack\_c.h, 1015
- FFPACK\_C\_LU\_TAG
  - ffpack\_c.h, 1015
- FFPACK\_C\_MINPOLY\_TAG
  - ffpack\_c.h, 1015
- ffpack\_charpoly.inl, 933
  - \_\_FFLASFFPACK\_charpoly\_INL, 933
- ffpack\_charpoly\_danilevski.inl, 933
  - \_\_FFLASFFPACK\_ffpack\_charpoly\_danilveski\_INL, 934
- ffpack\_charpoly\_kgfast.inl, 934
  - \_\_FFLASFFPACK\_ffpack\_charpoly\_kgfast\_INL, 934
- ffpack\_charpoly\_kgfastgeneralized.inl, 934
  - \_\_FFLASFFPACK\_ffpack\_charpoly\_kgfastgeneralized\_INL, 935
- ffpack\_charpoly\_kglu.inl, 935
  - \_\_FFLASFFPACK\_ffpack\_charpoly\_kglu\_INL, 935
- ffpack\_charpoly\_mp.inl, 935
  - \_\_FFPACK\_charpoly\_mp\_INL, 936
- FFPACK\_COMPILED
  - ffpack\_c.h, 1014
- ffpack\_det\_mp.inl, 936
  - \_\_FFPACK\_det\_mp\_INL, 936
- ffpack\_echelonforms.inl, 937
  - \_\_FFLASFFPACK\_GAUSSJORDAN\_BASECASE, 938
  - \_\_FFLASFFPACK\_ffpack\_echelon\_forms\_INL, 938
- ffpack\_fgesv.inl, 938
  - \_\_FFLASFFPACK\_ffpack\_fgesv\_INL, 938
- ffpack\_fgetrs.inl, 938
  - \_\_FFLASFFPACK\_ffpack\_fgetrs\_INL, 939
- ffpack\_frobenius.inl, 939
- ffpack\_fsytrf.inl, 940
  - \_\_FFLASFFPACK\_ffpack\_fsytrf\_INL, 941
- ffpack\_ftrssyr2k.inl, 941
  - \_\_FFLASFFPACK\_ffpack\_ftrssyr2k\_INL, 941
- ffpack\_ftrstr.inl, 941
  - \_\_FFLASFFPACK\_ffpack\_ftrstr\_INL, 942
- ffpack\_ftrtr.inl, 942
  - \_\_FFLASFFPACK\_ffpack\_ftrtr\_INL, 942
- ENABLE\_ALL\_CHECKINGS, 942
- ffpack\_inst.C, 1031
  - \_\_FFPACK\_INST\_C, 1031
  - FFLAS\_COMPILED, 1031
  - FFLAS\_ELT, 1031, 1032
  - FFLAS\_FIELD, 1031
  - INST\_OR\_DECL, 1031
- ffpack\_inst.h, 1032
  - FFLAS\_COMPILED, 1032
  - FFLAS\_ELT, 1032, 1033
  - FFLAS\_FIELD, 1032
  - INST\_OR\_DECL, 1032
- ffpack\_inst\_implem.inl, 1033
- ffpack\_invert.inl, 942
  - \_\_FFLASFFPACK\_ffpack\_invert\_INL, 943
- ffpack\_krylovelim.inl, 943
  - \_\_FFLASFFPACK\_ffpack\_krylovelim\_INL, 943
- ffpack\_ludivine.inl, 943
  - \_\_FFLASFFPACK\_ffpack\_ludivine\_INL, 944
- ffpack\_ludivine\_mp.inl, 944
  - \_\_FFPACK\_ludivine\_mp\_INL, 944
- ffpack\_minpoly.inl, 945
  - \_\_FFLASFFPACK\_ffpack\_minpoly\_INL, 945
- ffpack\_permutation.inl, 945
  - \_\_FFLASFFPACK\_ffpack\_permutation\_INL, 947
  - FFLASFFPACK\_PERM\_BKSIZE, 947
- ffpack\_pluq.inl, 948
  - \_\_FFLASFFPACK\_ffpack\_pluq\_INL, 948
  - CROUT, 948
- ffpack\_pluq\_mp.inl, 948
  - \_\_FFPACK\_pluq\_mp\_INL, 949
- ffpack\_ppluq.inl, 949
  - \_\_FFLASFFPACK\_ffpack\_ppluq\_INL, 949
  - \_\_FFLAS\_TRSM\_READONLY, 949
  - PBASECASE\_K, 949
- ffpack\_rankprofiles.inl, 950
  - \_\_FFLASFFPACK\_ffpack\_rank\_profiles\_INL, 951
- FfpackArithProg
  - ffpack\_c.h, 1015
- FfpackDanilevski
  - ffpack\_c.h, 1015
- FfpackDense
  - ffpack\_c.h, 1016
- FfpackHybrid
  - ffpack\_c.h, 1015
- FfpackKG
  - ffpack\_c.h, 1015
- FfpackKGF
  - ffpack\_c.h, 1016
- FfpackKGFast
  - ffpack\_c.h, 1015



- FpackKGFastG
  - ffpack\_c.h, [1015](#)
- FpackLUK
  - ffpack\_c.h, [1015](#)
- FpackSingular
  - ffpack\_c.h, [1015](#)
- FpackSlabRecursive
  - ffpack\_c.h, [1015](#)
- FpackTileRecursive
  - ffpack\_c.h, [1015](#)
- fgemm
  - FFLAS, [89–91](#), [93–98](#), [146](#), [179](#), [180](#)
- fgemm\_3\_modular\_double
  - fflas\_c.h, [968](#)
  - fflas\_lvl3.C, [990](#)
- fgemm\_classical.inl, [843](#)
- fgemm\_classical\_mp.inl, [843](#)
  - \_\_FFPACK\_fgemm\_classical\_INL, [845](#)
- fgemm\_convert
  - FFLAS::Protected, [217](#)
- fgemm\_winograd.inl, [845](#)
  - \_\_FFLASFFPACK\_fflas\_fflas\_fgemm\_winograd\_INL, [846](#)
  - NEWWINO, [846](#)
- fgemv
  - FFLAS, [98–103](#), [175](#), [187](#)
- fgemv\_2\_modular\_double
  - fflas\_c.h, [967](#)
  - fflas\_lvl2.C, [988](#)
- fgemv\_convert
  - FFLAS::Protected, [222](#)
- fgemv\_kgf
  - FFPACK::Protected, [399](#)
- fger
  - FFLAS, [104–107](#), [176](#)
- fger\_2\_modular\_double
  - fflas\_c.h, [967](#)
  - fflas\_lvl2.C, [988](#)
- fger\_convert
  - FFLAS::Protected, [223](#)
- fgesv
  - FFPACK, [312](#), [313](#), [371](#)
- fgesv\_modular\_double
  - ffpack.C, [997](#)
  - ffpack\_c.h, [1019](#)
- fgesvin\_modular\_double
  - ffpack.C, [997](#)
  - ffpack\_c.h, [1018](#)
- fgetrs
  - FFPACK, [311](#), [312](#), [370](#)
- fgetrs\_modular\_double
  - ffpack\_c.h, [1018](#)
- fgetrsin\_modular\_double
  - ffpack.C, [996](#)
  - ffpack\_c.h, [1018](#)
- fgetrsv\_modular\_double
  - ffpack.C, [997](#)
- fidentity
  - FFLAS, [139](#), [168](#)
- fidentity\_2\_modular\_double
  - fflas\_c.h, [964](#)
  - fflas\_lvl2.C, [985](#)
- Field
  - Bench< Elt >, [411](#)
  - benchmark-fgemm-rns.C, [793](#)
  - benchmark-pluq.C, [806](#)
  - FieldSimd< \_Field >, [451](#)
  - Sparse< \_Field, SparseMatrix\_t::COO >, [740](#)
  - Sparse< \_Field, SparseMatrix\_t::COO\_ZO >, [742](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR >, [744](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, [745](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, [747](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL >, [749](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_ZO >, [754](#)
  - Sparse< \_Field, SparseMatrix\_t::HYB\_ZO >, [755](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL >, [757](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [759](#)
  - Test< Elt >, [766](#)
  - test-compressQ.C, [1062](#)
- field
  - associatedDelayedField< const FFPACK::RNSIntegerMod< RNS > >, [408](#)
  - associatedDelayedField< const Givaro::Modular< T, X > >, [409](#)
  - associatedDelayedField< const Givaro::ModularBalanced< T > >, [409](#)
  - associatedDelayedField< const Givaro::ZRing< T > >, [410](#)
  - associatedDelayedField< Field >, [408](#)
- field-traits.h, [951](#)
- field.dox, [953](#)
- FieldMax
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [506](#)
- FieldMin
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [506](#)
- FieldSimd
  - FieldSimd< \_Field >, [451](#), [452](#)
- FieldSimd< \_Field >, [450](#)
  - add, [452](#)
  - add\_r, [452](#), [453](#)
  - addin, [452](#)
  - addin\_r, [453](#)
  - alignment, [456](#)
  - axpy, [454](#), [455](#)
  - axpy\_r, [455](#)
  - axpyin, [455](#)
  - axpyin\_r, [455](#)
  - Element, [451](#)
  - Field, [451](#)
  - FieldSimd, [451](#), [452](#)
  - init, [452](#)
  - maxpy, [455](#)
  - maxpyin, [456](#)

- mod, [454](#)
- mul, [454](#)
- mul\_r, [454](#)
- mulin, [454](#)
- operator=, [452](#)
- scalar\_t, [451](#)
- simd, [451](#)
- sub, [453](#)
- sub\_r, [453](#)
- subin, [453](#)
- subin\_r, [453](#)
- vect\_size, [456](#)
- vect\_t, [451](#)
- zero, [454](#)
- FieldTraits< FFPACK::RNSInteger< T > >, [457](#)
  - balanced, [457](#)
  - category, [457](#)
- FieldTraits< FFPACK::RNSIntegerMod< T > >, [457](#)
  - balanced, [458](#)
  - category, [457](#)
- FieldTraits< Field >, [456](#)
  - balanced, [457](#)
  - category, [456](#)
- FieldTraits< Givaro::Modular< Element > >, [458](#)
  - balanced, [458](#)
  - category, [458](#)
- FieldTraits< Givaro::ModularBalanced< Element > >, [458](#)
  - balanced, [459](#)
  - category, [458](#)
- FieldTraits< Givaro::ZRing< double > >, [459](#)
  - balanced, [459](#)
  - category, [459](#)
- FieldTraits< Givaro::ZRing< float > >, [459](#)
  - balanced, [460](#)
  - category, [459](#)
- FieldTraits< Givaro::ZRing< Givaro::Integer > >, [460](#)
  - balanced, [460](#)
  - category, [460](#)
- FieldTraits< Givaro::ZRing< int16\_t > >, [460](#)
  - balanced, [461](#)
  - category, [460](#)
- FieldTraits< Givaro::ZRing< int32\_t > >, [461](#)
  - balanced, [461](#)
  - category, [461](#)
- FieldTraits< Givaro::ZRing< int64\_t > >, [461](#)
  - balanced, [461](#)
  - category, [461](#)
- FieldTraits< Givaro::ZRing< ReclInt::ruint< K > > >, [462](#)
  - balanced, [462](#)
  - category, [462](#)
- FieldTraits< Givaro::ZRing< uint16\_t > >, [462](#)
  - balanced, [462](#)
  - category, [462](#)
- FieldTraits< Givaro::ZRing< uint32\_t > >, [462](#)
  - balanced, [463](#)
  - category, [463](#)
- FieldTraits< Givaro::ZRing< uint64\_t > >, [463](#)
  - balanced, [463](#)
  - category, [463](#)
- fill\_value
  - benchmark-fgemv.C, [797](#)
- findArgument
  - args-parser.h, [1047](#)
- finit
  - FFLAS, [109](#), [112](#), [131](#), [139](#), [160](#), [170](#)
- finit\_rns
  - FFLAS, [157](#), [158](#)
- finit\_trans\_rns
  - FFLAS, [157](#)
- first\_component
  - Compose< H1, H2 >, [428](#)
- firstBlockSize
  - ForStrategy1D< blocksize\_t, Cut, Param >, [466](#)
- fiszero
  - FFLAS, [134](#), [138](#), [162](#), [168](#)
- fiszero\_1\_modular\_double
  - fflas\_c.h, [961](#)
  - fflas\_lvl1.C, [981](#)
- fiszero\_2\_modular\_double
  - fflas\_c.h, [964](#)
  - fflas\_lvl2.C, [985](#)
- Fixed, [463](#)
- FixedPreclntTag, [463](#)
- flimits.h, [1053](#)
  - in\_range, [1054](#)
- FLOAT\_MOD
  - fflas\_simd.h, [880](#)
- FloatingPointTestDistribution
  - ScalFunctionsBase< Element, typename enable\_if< is\_floating\_point< Element >::value >::type >::FloatingPointTestDistribution, [464](#)
- Floats
  - benchmark-dgemm.C, [786](#)
- floor
  - ScalFunctionsBase< Element, typename enable\_if< is\_floating\_point< Element >::value >::type >, [563](#)
  - Simd256\_impl< true, false, true, 8 >, [634](#)
  - Simd512\_impl< true, false, true, 8 >, [716](#)
- fma
  - ScalFunctionsBase< Element, typename enable\_if< is\_floating\_point< Element >::value >::type >, [564](#)
  - ScalFunctionsBase< Element, typename enable\_if< is\_integral< Element >::value >::type >, [565](#)
- fmadd
  - ScalFunctions< Element >, [560](#)
  - Simd128\_impl< true, true, false, 2 >, [576](#)
  - Simd128\_impl< true, true, false, 4 >, [586](#)
  - Simd128\_impl< true, true, false, 8 >, [596](#)
  - Simd128\_impl< true, true, true, 2 >, [604](#)
  - Simd128\_impl< true, true, true, 4 >, [613](#)
  - Simd128\_impl< true, true, true, 8 >, [622](#)
  - Simd256\_impl< true, false, true, 8 >, [633](#)

[illegible]

- Simd256\_impl< true, true, true, 8 >, [707](#)
- Simd512\_impl< true, true, false, 8 >, [722](#)
- Simd512\_impl< true, true, true, 8 >, [735](#)
- fmsubxin
  - ScalFunctionsBase< Element, typename enable\_if< is\_integral< Element >::value >::type >, [566](#)
  - Simd128\_impl< true, true, false, 2 >, [573](#)
  - Simd128\_impl< true, true, false, 4 >, [583](#)
  - Simd128\_impl< true, true, false, 8 >, [593](#)
  - Simd128\_impl< true, true, true, 2 >, [606](#)
  - Simd128\_impl< true, true, true, 4 >, [614](#)
  - Simd128\_impl< true, true, true, 8 >, [624](#)
  - Simd256\_impl< true, true, false, 2 >, [640](#)
  - Simd256\_impl< true, true, false, 4 >, [652](#), [654](#)
  - Simd256\_impl< true, true, false, 8 >, [669](#)
  - Simd256\_impl< true, true, true, 2 >, [681](#)
  - Simd256\_impl< true, true, true, 4 >, [692](#), [698](#)
  - Simd256\_impl< true, true, true, 8 >, [707](#)
  - Simd512\_impl< true, true, false, 8 >, [722](#)
  - Simd512\_impl< true, true, true, 8 >, [735](#)
- fneg
  - FFLAS, [132](#), [141](#), [161](#), [170](#)
- fneg\_1\_modular\_double
  - fflas\_c.h, [961](#)
  - fflas\_lvl1.C, [980](#)
- fneg\_2\_modular\_double
  - fflas\_c.h, [965](#)
  - fflas\_lvl2.C, [986](#)
- fnegin
  - FFLAS, [132](#), [140](#), [160](#), [170](#)
- fnegin\_1\_modular\_double
  - fflas\_c.h, [961](#)
  - fflas\_lvl1.C, [980](#)
- fnegin\_2\_modular\_double
  - fflas\_c.h, [965](#)
  - fflas\_lvl2.C, [986](#)
- fnmadd
  - ScalFunctions< Element >, [560](#)
  - Simd128\_impl< true, true, false, 2 >, [576](#)
  - Simd128\_impl< true, true, false, 4 >, [586](#)
  - Simd128\_impl< true, true, false, 8 >, [596](#)
  - Simd128\_impl< true, true, true, 2 >, [605](#)
  - Simd128\_impl< true, true, true, 4 >, [614](#)
  - Simd128\_impl< true, true, true, 8 >, [623](#)
  - Simd256\_impl< true, false, true, 8 >, [633](#)
  - Simd256\_impl< true, true, false, 2 >, [644](#)
  - Simd256\_impl< true, true, false, 4 >, [661](#)
  - Simd256\_impl< true, true, false, 8 >, [672](#)
  - Simd256\_impl< true, true, true, 2 >, [680](#)
  - Simd256\_impl< true, true, true, 4 >, [691](#), [697](#)
  - Simd256\_impl< true, true, true, 8 >, [706](#)
  - Simd512\_impl< true, false, true, 8 >, [715](#)
  - Simd512\_impl< true, true, false, 8 >, [726](#)
  - Simd512\_impl< true, true, true, 8 >, [734](#)
- fnmaddin
  - ScalFunctions< Element >, [561](#)
  - Simd128\_impl< true, true, false, 2 >, [577](#)
  - Simd128\_impl< true, true, false, 4 >, [586](#)
- Simd128\_impl< true, true, false, 8 >, [596](#)
- Simd128\_impl< true, true, true, 2 >, [605](#)
- Simd128\_impl< true, true, true, 4 >, [614](#)
- Simd128\_impl< true, true, true, 8 >, [623](#)
- Simd128\_impl< true, true, true, 8 >, [623](#)
- Simd256\_impl< true, false, true, 8 >, [633](#)
- Simd256\_impl< true, true, false, 2 >, [644](#)
- Simd256\_impl< true, true, false, 4 >, [661](#), [662](#)
- Simd256\_impl< true, true, false, 8 >, [672](#)
- Simd256\_impl< true, true, true, 2 >, [680](#)
- Simd256\_impl< true, true, true, 4 >, [691](#), [697](#)
- Simd256\_impl< true, true, true, 8 >, [706](#)
- Simd512\_impl< true, false, true, 8 >, [715](#)
- Simd512\_impl< true, true, false, 8 >, [726](#)
- Simd512\_impl< true, true, true, 8 >, [735](#)
- fnmaddx
  - ScalFunctionsBase< Element, typename enable\_if< is\_integral< Element >::value >::type >, [566](#)
  - Simd128\_impl< true, true, false, 2 >, [572](#)
  - Simd128\_impl< true, true, false, 4 >, [582](#)
  - Simd128\_impl< true, true, false, 8 >, [592](#)
  - Simd128\_impl< true, true, true, 2 >, [605](#)
  - Simd128\_impl< true, true, true, 4 >, [614](#)
  - Simd128\_impl< true, true, true, 8 >, [623](#)
  - Simd256\_impl< true, true, false, 2 >, [640](#)
  - Simd256\_impl< true, true, false, 4 >, [652](#), [654](#)
  - Simd256\_impl< true, true, false, 8 >, [668](#)
  - Simd256\_impl< true, true, true, 2 >, [681](#)
  - Simd256\_impl< true, true, true, 4 >, [691](#), [698](#)
  - Simd256\_impl< true, true, true, 8 >, [707](#)
  - Simd512\_impl< true, true, false, 8 >, [721](#)
  - Simd512\_impl< true, true, true, 8 >, [735](#)
- fnmaddxin
  - ScalFunctionsBase< Element, typename enable\_if< is\_integral< Element >::value >::type >, [566](#)
  - Simd128\_impl< true, true, false, 2 >, [573](#)
  - Simd128\_impl< true, true, false, 4 >, [583](#)
  - Simd128\_impl< true, true, false, 8 >, [593](#)
  - Simd128\_impl< true, true, true, 2 >, [605](#)
  - Simd128\_impl< true, true, true, 4 >, [614](#)
  - Simd128\_impl< true, true, true, 8 >, [623](#)
  - Simd256\_impl< true, true, false, 2 >, [640](#)
  - Simd256\_impl< true, true, false, 4 >, [652](#), [654](#)
  - Simd256\_impl< true, true, false, 8 >, [668](#)
  - Simd256\_impl< true, true, true, 2 >, [681](#)
  - Simd256\_impl< true, true, true, 4 >, [691](#), [698](#)
  - Simd256\_impl< true, true, true, 8 >, [707](#)
  - Simd512\_impl< true, true, false, 8 >, [722](#)
  - Simd512\_impl< true, true, true, 8 >, [735](#)
- FOR1D
  - parallel.h, [1041](#)
- FOR2D
  - parallel.h, [1041](#)
- FORBLOCK1D
  - parallel.h, [1040](#)
- FORBLOCK2D
  - parallel.h, [1041](#)
- ForceCheck\_charpoly
  - FFPACK, [308](#)

- ForceCheck\_Det
  - FFPACK, 308
- ForceCheck\_fgemm
  - FFLAS, 72
- ForceCheck\_ftsm
  - FFLAS, 72
- ForceCheck\_invert
  - FFPACK, 308
- ForceCheck\_PLUQ
  - FFPACK, 308
- ForStrategy1D
  - ForStrategy1D< blocksize\_t, Cut, Param >, 465
- ForStrategy1D< blocksize\_t, Cut, Param >, 464
  - begin, 465
  - blockindex, 466
  - build, 465
  - changeBS, 466
  - current, 466
  - end, 466
  - firstBlockSize, 466
  - ForStrategy1D, 465
  - ibeg, 466
  - iend, 466
  - initialize, 465
  - isTerminated, 465
  - lastBlockSize, 466
  - numBlock, 467
  - numblocks, 466
  - operator++, 466
- ForStrategy2D
  - ForStrategy2D< blocksize\_t, Cut, Param >, 468
- ForStrategy2D< blocksize\_t, Cut, Param >, 467
  - \_ibeg, 469
  - \_iend, 469
  - \_jbeg, 469
  - \_jend, 469
  - blockindex, 469
  - BLOCKS, 470
  - changeCBS, 470
  - changeRBS, 470
  - colblockindex, 469
  - colBlockSize, 470
  - colnumblocks, 468
  - current, 470
  - ForStrategy2D, 468
  - ibegin, 468
  - iend, 468
  - initialize, 468
  - isTerminated, 468
  - jbegin, 468
  - jend, 468
  - lastCBS, 470
  - lastRBS, 470
  - numColBlock, 470
  - numRowBlock, 470
  - operator<<, 469
  - operator++, 468
  - rowblockindex, 469
  - rowBlockSize, 469
  - rownumblocks, 468
- frand
  - FFLAS, 133, 138
- freduce
  - FFLAS, 108–110, 113, 159, 169
  - FFLAS::details, 205, 206
- freduce\_1\_modular\_double
  - fflas\_c.h, 961
  - fflas\_lvl1.C, 980
- freduce\_2\_modular\_double
  - fflas\_c.h, 965
  - fflas\_lvl2.C, 985
- freduce\_constoverride
  - FFLAS, 109, 112
- freducein\_1\_modular\_double
  - fflas\_c.h, 961
  - fflas\_lvl1.C, 980
- freducein\_2\_modular\_double
  - fflas\_c.h, 965
  - fflas\_lvl2.C, 985
- freivalds
  - FFLAS, 113
- fscal
  - FFLAS, 114–118, 163, 171
  - FFLAS::details, 206, 207
- fscal\_1\_modular\_double
  - fflas\_c.h, 962
  - fflas\_lvl1.C, 981
- fscal\_2\_modular\_double
  - fflas\_c.h, 965
  - fflas\_lvl2.C, 986
- fscalin
  - FFLAS, 114–118, 163, 171
  - FFLAS::details, 206, 207
- fscalin\_1\_modular\_double
  - fflas\_c.h, 962
  - fflas\_lvl1.C, 981
- fscalin\_2\_modular\_double
  - fflas\_c.h, 965
  - fflas\_lvl2.C, 986
- fspmm
  - FFLAS, 147
  - FFLAS::sparse\_details, 234–236
  - FFLAS::sparse\_details\_impl, 250, 257, 258, 263, 264, 268, 277
- fspmm\_dispatch
  - FFLAS::sparse\_details, 233, 234
- fspmm\_mone
  - FFLAS::sparse\_details\_impl, 251, 259, 269
- fspmm\_mone\_simd\_aligned
  - FFLAS::sparse\_details\_impl, 252, 259, 270
- fspmm\_mone\_simd\_unaligned
  - FFLAS::sparse\_details\_impl, 252, 260, 270
- fspmm\_one
  - FFLAS::sparse\_details\_impl, 251, 258, 269
- fspmm\_one\_simd\_aligned
  - FFLAS::sparse\_details\_impl, 252, 259, 270

- fspmm\_one\_simd\_unaligned
  - FFLAS::sparse\_details\_impl, [252](#), [259](#), [270](#)
- fspmm\_simd\_aligned
  - FFLAS::sparse\_details\_impl, [251](#), [258](#)
- fspmm\_simd\_unaligned
  - FFLAS::sparse\_details\_impl, [251](#), [258](#)
- fspmv
  - FFLAS, [147](#), [154](#)
  - FFLAS::sparse\_details, [231–233](#), [241](#)
  - FFLAS::sparse\_details\_impl, [253](#), [260](#), [264](#), [271](#), [273](#), [274](#), [278](#), [280](#)
- fspmv\_dispatch
  - FFLAS::sparse\_details, [231](#)
- fspmv\_mone
  - FFLAS::sparse\_details\_impl, [253](#), [254](#), [261](#), [271](#), [272](#), [275](#), [281](#), [282](#)
- fspmv\_mone\_simd
  - FFLAS::sparse\_details\_impl, [275](#), [281](#)
- fspmv\_one
  - FFLAS::sparse\_details\_impl, [253](#), [254](#), [260](#), [261](#), [271](#), [272](#), [274](#), [275](#), [281](#)
- fspmv\_one\_simd
  - FFLAS::sparse\_details\_impl, [275](#), [281](#)
- fspmv\_simd
  - FFLAS::sparse\_details\_impl, [274](#), [280](#)
- fsquare
  - FFLAS, [92](#), [93](#), [181](#)
- fsquare\_3\_modular\_double
  - fflas\_c.h, [969](#)
  - fflas\_lvl3.C, [990](#)
- fsquareCommon
  - FFLAS::Protected, [220](#)
- fsub
  - FFLAS, [78](#), [81](#), [166](#), [174](#)
- fsub\_1\_modular\_double
  - fflas\_c.h, [963](#)
  - fflas\_lvl1.C, [982](#)
- fsub\_2\_modular\_double
  - fflas\_c.h, [966](#)
  - fflas\_lvl2.C, [987](#)
- fsubin
  - FFLAS, [78](#), [82](#), [174](#)
- fsubin\_1\_modular\_double
  - fflas\_c.h, [963](#)
  - fflas\_lvl1.C, [983](#)
- fsubin\_2\_modular\_double
  - fflas\_c.h, [967](#)
  - fflas\_lvl2.C, [987](#)
- fswap
  - FFLAS, [135](#), [165](#)
- fswap\_1\_modular\_double
  - fflas\_c.h, [963](#)
  - fflas\_lvl1.C, [982](#)
- fsyr2k
  - FFLAS, [118](#)
- fsyrk
  - FFLAS, [119–126](#)
- fsyrk.C, [780](#)
- CUBE, [780](#)
- GFOPS, [780](#)
- main, [780](#)
- TTimer, [780](#)
- fsyrk\_convert
  - FFLAS::Protected, [223](#)
- fsyrk\_strassen
  - FFLAS, [126](#), [144](#)
- fsytrf
  - FFPACK, [316](#), [317](#)
- fsytrf.C, [781](#)
- CUBE, [781](#)
- GFOPS, [781](#)
- main, [781](#)
- TTimer, [781](#)
- fsytrf\_BC\_Crout
  - FFPACK, [357](#)
- fsytrf\_BC\_RL
  - FFPACK, [357](#)
- fsytrf\_LOW\_RPM\_BC\_Crout
  - FFPACK, [358](#)
- fsytrf\_nonunit
  - FFPACK, [317](#), [358](#), [359](#)
- fsytrf\_RPM
  - FFPACK, [359](#)
- fsytrf\_UP\_RPM
  - FFPACK, [358](#)
- fsytrf\_UP\_RPM\_BC\_Crout
  - FFPACK, [358](#)
- fsytrf\_UP\_RPM\_BC\_RL
  - FFPACK, [357](#)
- ftmrm
  - FFLAS, [127](#), [128](#), [178](#)
- ftmrm\_3\_modular\_double
  - fflas\_c.h, [968](#)
  - fflas\_lvl3.C, [989](#)
- ftmrmLeftLowerNoTransNonUnit< Element >, [471](#)
- ftmrmLeftLowerNoTransUnit< Element >, [471](#)
- ftmrmLeftLowerTransNonUnit< Element >, [471](#)
- ftmrmLeftLowerTransUnit< Element >, [471](#)
- ftmrmLeftUpperNoTransNonUnit< Element >, [471](#)
- ftmrmLeftUpperNoTransUnit< Element >, [471](#)
- ftmrmLeftUpperTransNonUnit< Element >, [471](#)
- ftmrmLeftUpperTransUnit< Element >, [472](#)
- ftmrmRightLowerNoTransNonUnit< Element >, [472](#)
- ftmrmRightLowerNoTransUnit< Element >, [472](#)
- ftmrmRightLowerTransNonUnit< Element >, [472](#)
- ftmrmRightLowerTransUnit< Element >, [472](#)
- ftmrmRightUpperNoTransNonUnit< Element >, [472](#)
- ftmrmRightUpperNoTransUnit< Element >, [472](#)
- ftmrmRightUpperTransNonUnit< Element >, [472](#)
- ftmrmRightUpperTransUnit< Element >, [473](#)
- ftmrv
  - FFLAS, [143](#)
- ftsm
  - FFLAS, [128–130](#), [143](#), [147](#), [177](#)
- ftsm\_3\_modular\_double
  - fflas\_c.h, [968](#)



- fflas\_lvl3.C, 989
- ftsmLeftLowerNoTransNonUnit< Element >, 473
- ftsmLeftLowerNoTransUnit< Element >, 473
- ftsmLeftLowerTransNonUnit< Element >, 473
- ftsmLeftLowerTransUnit< Element >, 473
- ftsmLeftUpperNoTransNonUnit< Element >, 473
- ftsmLeftUpperNoTransUnit< Element >, 474
- ftsmLeftUpperTransNonUnit< Element >, 474
- ftsmLeftUpperTransUnit< Element >, 474
- ftsmRightLowerNoTransNonUnit< Element >, 474
- ftsmRightLowerNoTransUnit< Element >, 474
- ftsmRightLowerTransNonUnit< Element >, 474
- ftsmRightLowerTransUnit< Element >, 474
- ftsmRightUpperNoTransNonUnit< Element >, 475
- ftsmRightUpperNoTransUnit< Element >, 475
- ftsmRightUpperTransNonUnit< Element >, 475
- ftsmRightUpperTransUnit< Element >, 475
- ftssyr2k
  - FFPACK, 316
- ftstr
  - FFPACK, 315
- ftsv
  - FFLAS, 130, 177
- ftsv\_2\_modular\_double
  - fflas\_c.h, 968
  - fflas\_lvl2.C, 988
- fttri
  - FFPACK, 314, 371
- fttri.C, 781
  - CUBE, 782
  - GFOPS, 782
  - main, 782
  - TTimer, 782
- fttri\_modular\_double
  - ffpack.C, 997
  - ffpack\_c.h, 1019
- fttrm
  - FFPACK, 315, 372
- fttrm\_modular\_double
  - ffpack.C, 998
  - ffpack\_c.h, 1019
- fzero
  - FFLAS, 133, 137, 161, 167
- fzero\_1\_modular\_double
  - fflas\_c.h, 961
  - fflas\_lvl1.C, 981
- fzero\_2\_modular\_double
  - fflas\_c.h, 964
  - fflas\_lvl2.C, 984
- gather
  - Simd128\_impl< true, true, false, 2 >, 571, 574
  - Simd128\_impl< true, true, false, 4 >, 581, 583
  - Simd128\_impl< true, true, false, 8 >, 591, 593
  - Simd128\_impl< true, true, true, 2 >, 601
  - Simd128\_impl< true, true, true, 4 >, 610
  - Simd128\_impl< true, true, true, 8 >, 619
  - Simd256\_impl< true, false, true, 8 >, 630
  - Simd256\_impl< true, true, false, 2 >, 638, 641
- Simd256\_impl< true, true, false, 4 >, 650, 652, 656
- Simd256\_impl< true, true, false, 8 >, 667, 669
- Simd256\_impl< true, true, true, 2 >, 677
- Simd256\_impl< true, true, true, 4 >, 687, 694
- Simd256\_impl< true, true, true, 8 >, 703
- Simd512\_impl< true, false, true, 8 >, 712
- Simd512\_impl< true, true, false, 8 >, 720, 723
- Simd512\_impl< true, true, true, 8 >, 731
- GaussJordan
  - FFPACK::Protected, 398
- GCC\_VERSION
  - fflas-ffpack-config.h, 831
- gebp
  - FFLAS::details, 210
- genData
  - benchmark-fgemv.C, 797
- GenericTag, 475
- genInputs
  - ScalFunctions< Element >, 558
- genInputsWithZero
  - ScalFunctions< Element >, 558
- get
  - Simd128\_impl< true, true, false, 8 >, 594
  - Simd128\_impl< true, true, true, 8 >, 619
  - Simd256\_impl< true, true, false, 8 >, 669
  - Simd256\_impl< true, true, true, 8 >, 703
- get\_default\_random\_generator
  - ScalFunctionsBase< Element, typename enable\_if< is\_floating\_point< Element >::value >::type >, 563
  - ScalFunctionsBase< Element, typename enable\_if< is\_integral< Element >::value >::type >, 565
- getArgumentValue
  - FFLAS, 188
- getDataType
  - FFLAS, 153, 154
- getEchelonForm
  - FFPACK, 342, 343
- getEchelonForm< FFLAS\_FIELD< FFLAS\_ELT > >
  - FFPACK, 380
- getEchelonForm\_modular\_double
  - ffpack.C, 1009
  - ffpack\_c.h, 1029
- getEchelonFormin\_modular\_double
  - ffpack.C, 1009
  - ffpack\_c.h, 1029
- getEchelonTransform
  - FFPACK, 344
- getEchelonTransform< FFLAS\_FIELD< FFLAS\_ELT > >
  - FFPACK, 380
- getEchelonTransform\_modular\_double
  - ffpack.C, 1010
  - ffpack\_c.h, 1029
- getListArgs
  - args-parser.h, 1047
- getLTBruhatGen

- FFPACK, [347](#), [348](#)
- getReducedEchelonForm
  - FFPACK, [344](#), [345](#)
- getReducedEchelonForm< FFLAS\_FIELD< FFLAS\_ELT > >
  - FFPACK, [381](#)
- getReducedEchelonForm\_modular\_double
  - ffpack.C, [1010](#)
  - ffpack\_c.h, [1030](#)
- getReducedEchelonFormin\_modular\_double
  - ffpack.C, [1010](#)
  - ffpack\_c.h, [1030](#)
- getReducedEchelonTransform
  - FFPACK, [346](#)
- getReducedEchelonTransform< FFLAS\_FIELD< FFLAS\_ELT > >
  - FFPACK, [381](#)
- getReducedEchelonTransform\_modular\_double
  - ffpack.C, [1010](#)
  - ffpack\_c.h, [1030](#)
- getSeed
  - FFLAS, [193](#)
- getStat
  - FFLAS, [156](#)
- getStatus
  - TestOneMethod< Simd >, [771](#)
- getTestName
  - TestOneMethod< Simd >, [771](#)
- getTLBSize
  - FFLAS, [193](#)
- getTriangular
  - FFPACK, [341](#), [342](#)
- getTriangular< FFLAS\_FIELD< FFLAS\_ELT > >
  - FFPACK, [379](#), [380](#)
- getTriangular\_modular\_double
  - ffpack.C, [1009](#)
  - ffpack\_c.h, [1028](#)
- getTriangularin\_modular\_double
  - ffpack.C, [1009](#)
  - ffpack\_c.h, [1028](#)
- getTridiagonal
  - FFPACK, [359](#)
- gf2ModularBalanced
  - regression-check.C, [1059](#)
- GFOPS
  - arithprog.C, [779](#)
  - autotune/charpoly.C, [816](#)
  - autotune/pluq.C, [818](#)
  - fsyrk.C, [780](#)
  - fsytrf.C, [781](#)
  - fttri.C, [782](#)
  - winograd.C, [783](#)
- Givaro, [403](#)
- GRAIN
  - benchmark-fgemm-rns.C, [793](#)
- Grain, [475](#)
- greater
  - ScalFunctions< Element >, [561](#)
- Simd128\_impl< true, true, false, 2 >, [572](#)
- Simd128\_impl< true, true, false, 4 >, [582](#)
- Simd128\_impl< true, true, false, 8 >, [592](#)
- Simd128\_impl< true, true, true, 2 >, [606](#)
- Simd128\_impl< true, true, true, 4 >, [615](#)
- Simd128\_impl< true, true, true, 8 >, [624](#)
- Simd256\_impl< true, false, true, 8 >, [634](#)
- Simd256\_impl< true, true, false, 2 >, [639](#)
- Simd256\_impl< true, true, false, 4 >, [651](#), [653](#)
- Simd256\_impl< true, true, false, 8 >, [667](#)
- Simd256\_impl< true, true, true, 2 >, [681](#)
- Simd256\_impl< true, true, true, 4 >, [692](#), [698](#)
- Simd256\_impl< true, true, true, 8 >, [707](#)
- Simd512\_impl< true, false, true, 8 >, [716](#)
- Simd512\_impl< true, true, false, 8 >, [721](#)
- Simd512\_impl< true, true, true, 8 >, [736](#)
- greater\_eq
  - ScalFunctions< Element >, [561](#)
- Simd128\_impl< true, true, false, 2 >, [572](#)
- Simd128\_impl< true, true, false, 4 >, [582](#)
- Simd128\_impl< true, true, false, 8 >, [592](#)
- Simd128\_impl< true, true, true, 2 >, [606](#)
- Simd128\_impl< true, true, true, 4 >, [615](#)
- Simd128\_impl< true, true, true, 8 >, [624](#)
- Simd256\_impl< true, false, true, 8 >, [634](#)
- Simd256\_impl< true, true, false, 2 >, [639](#)
- Simd256\_impl< true, true, false, 4 >, [651](#), [653](#)
- Simd256\_impl< true, true, false, 8 >, [667](#)
- Simd256\_impl< true, true, true, 2 >, [682](#)
- Simd256\_impl< true, true, true, 4 >, [692](#), [699](#)
- Simd256\_impl< true, true, true, 8 >, [708](#)
- Simd512\_impl< true, false, true, 8 >, [716](#)
- Simd512\_impl< true, true, false, 8 >, [721](#)
- Simd512\_impl< true, true, true, 8 >, [736](#)
- hadd
  - Simd256\_impl< true, false, true, 8 >, [634](#)
  - Simd512\_impl< true, false, true, 8 >, [716](#)
- hadd\_to\_scal
  - Simd128\_impl< true, true, false, 2 >, [573](#)
  - Simd128\_impl< true, true, false, 4 >, [583](#)
  - Simd128\_impl< true, true, false, 8 >, [593](#)
  - Simd128\_impl< true, true, true, 2 >, [606](#)
  - Simd128\_impl< true, true, true, 4 >, [615](#)
  - Simd128\_impl< true, true, true, 8 >, [624](#)
  - Simd256\_impl< true, false, true, 8 >, [635](#)
  - Simd256\_impl< true, true, false, 2 >, [640](#)
  - Simd256\_impl< true, true, false, 4 >, [652](#), [654](#)
  - Simd256\_impl< true, true, false, 8 >, [669](#)
  - Simd256\_impl< true, true, true, 2 >, [682](#)
  - Simd256\_impl< true, true, true, 4 >, [692](#), [699](#)
  - Simd256\_impl< true, true, true, 8 >, [708](#)
  - Simd512\_impl< true, false, true, 8 >, [716](#)
  - Simd512\_impl< true, true, false, 8 >, [722](#)
  - Simd512\_impl< true, true, true, 8 >, [736](#)
- half\_t
  - Simd256\_impl< true, true, false, 2 >, [638](#)
  - Simd256\_impl< true, true, false, 4 >, [650](#)
  - Simd256\_impl< true, true, false, 8 >, [666](#)



- Simd256\_impl< true, true, true, 2 >, [675](#)
- Simd256\_impl< true, true, true, 4 >, [686](#)
- Simd256\_impl< true, true, true, 8 >, [702](#)
- Simd512\_impl< true, true, false, 8 >, [719](#)
- Simd512\_impl< true, true, true, 8 >, [730](#)
- has\_equal
  - FFLAS, [73](#)
- has\_minus
  - FFLAS, [73](#)
- has\_minus\_eq
  - FFLAS, [73](#)
- has\_minus\_eq\_impl< C >, [476](#)
  - value, [476](#)
- has\_minus\_impl< C >, [476](#)
  - value, [476](#)
- has\_mul
  - FFLAS, [73](#)
- has\_mul\_eq
  - FFLAS, [74](#)
- has\_mul\_eq\_impl< C >, [476](#)
  - value, [476](#)
- has\_mul\_impl< C >, [476](#)
  - value, [477](#)
- has\_operation< T >, [477](#)
  - value, [477](#)
- has\_plus
  - FFLAS, [73](#)
- has\_plus\_eq
  - FFLAS, [73](#)
- has\_plus\_eq\_impl< C >, [477](#)
  - value, [477](#)
- has\_plus\_impl< C >, [477](#)
  - value, [478](#)
- HAVE\_BLAS
  - config.h, [809](#)
- HAVE\_CBLAS
  - config.h, [809](#)
- HAVE\_CXX11
  - config.h, [810](#)
- HAVE\_DLFCN\_H
  - config.h, [810](#)
- HAVE\_FLOAT\_H
  - config.h, [810](#)
- HAVE\_INT128
  - config.h, [810](#)
- HAVE\_INTTYPES\_H
  - config.h, [810](#)
- HAVE\_LAPACK
  - config.h, [810](#)
- HAVE\_LIMITS\_H
  - config.h, [810](#)
- HAVE\_LITTLE\_ENDIAN
  - config.h, [810](#)
- HAVE\_PTHREAD\_H
  - config.h, [810](#)
- HAVE\_STDDEF\_H
  - config.h, [810](#)
- HAVE\_STDINT\_H
  - config.h, [810](#)
- HAVE\_STDIO\_H
  - config.h, [810](#)
- HAVE\_STDLIB\_H
  - config.h, [810](#)
- HAVE\_STRING\_H
  - config.h, [810](#)
- HAVE\_STRINGS\_H
  - config.h, [810](#)
- HAVE\_SYS\_STAT\_H
  - config.h, [811](#)
- HAVE\_SYS\_TIME\_H
  - config.h, [811](#)
- HAVE\_SYS\_TYPES\_H
  - config.h, [811](#)
- HAVE\_UNISTD\_H
  - config.h, [811](#)
- HelperFlag, [478](#)
  - aut, [478](#)
  - coo, [478](#)
  - csr, [478](#)
  - ell, [478](#)
  - none, [478](#)
  - pm1, [478](#)
- HelperMod
  - HelperMod< Field, ElementCategories::MachineIntTag >, [479](#)
  - HelperMod< Field, FFLAS::ElementCategories::ArbitraryPrecIntTag >, [480](#)
  - HelperMod< Field, FFLAS::ElementCategories::FixedPrecIntTag >, [480](#)
  - HelperMod< Field, FFLAS::ElementCategories::MachineFloatTag >, [481](#)
  - HelperMod< Field, ElementCategories::MachineIntTag >, [479](#)
    - HelperMod, [479](#)
    - invp, [479](#)
    - max, [479](#)
    - min, [479](#)
    - p, [479](#)
    - pow50rem, [479](#)
  - HelperMod< Field, ElementTraits >, [478](#)
  - HelperMod< Field, FFLAS::ElementCategories::ArbitraryPrecIntTag >, [480](#)
    - HelperMod, [480](#)
    - p, [480](#)
  - HelperMod< Field, FFLAS::ElementCategories::FixedPrecIntTag >, [480](#)
    - HelperMod, [480](#)
    - p, [481](#)
  - HelperMod< Field, FFLAS::ElementCategories::MachineFloatTag >, [481](#)
    - HelperMod, [481](#)
    - invp, [481](#)
    - max, [481](#)
    - min, [481](#)
    - p, [481](#)
- helpString

- Argument, [407](#)
- HYB\_ZO
  - FFLAS, [76](#)
- hyb\_zo.h, [912](#)
- hyb\_zo\_pspmm.inl, [912](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_pspmm\_INL, [913](#)
- hyb\_zo\_pspmv.inl, [913](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_pspmv\_INL, [913](#)
- hyb\_zo\_spm.inl, [913](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_spm\_INL, [914](#)
- hyb\_zo\_spmv.inl, [914](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_spmv\_INL, [914](#)
- hyb\_zo\_utils.inl, [914](#)
  - \_\_FFLASFFPACK\_fflas\_sparse\_HYB\_ZO\_utils\_INL, [914](#)
- Hybrid, [482](#)
- Hybrid\_KGF\_LUK\_MinPoly
  - FFPACK::Protected, [401](#)
- ibeg
  - ForStrategy1D< blocksize\_t, Cut, Param >, [466](#)
- ibegin
  - ForStrategy2D< blocksize\_t, Cut, Param >, [468](#)
- idamax\_
  - config-blas.h, [827](#)
- iend
  - ForStrategy1D< blocksize\_t, Cut, Param >, [466](#)
  - ForStrategy2D< blocksize\_t, Cut, Param >, [468](#)
- igebb11
  - FFLAS::details, [209](#)
- igebb14
  - FFLAS::details, [208](#)
- igebb21
  - FFLAS::details, [208](#)
- igebb24
  - FFLAS::details, [207](#)
- igebb41
  - FFLAS::details, [208](#)
- igebb44
  - FFLAS::details, [207](#)
- igebp
  - FFLAS::details, [209](#)
- igemm
  - FFLAS::Protected, [226](#)
- igemm.dox, [866](#)
- igemm.h, [866](#)
- igemm.inl, [867](#)
  - \_\_FFLASFFPACK\_fflas\_igemm\_igemm\_INL, [867](#)
- igemm\_
  - FFLAS, [131](#)
- igemm\_colmajor
  - FFLAS::Protected, [226](#)
- igemm\_kernels.h, [867](#)
- igemm\_kernels.inl, [868](#)
  - \_\_FFLASFFPACK\_fflas\_igemm\_igemm\_kernels\_INL, [869](#)
- igemm\_tools.h, [869](#)
- igemm\_tools.inl, [869](#)
  - \_\_FFLASFFPACK\_fflas\_igemm\_igemm\_tools\_INL, [869](#)
- in\_range
  - flimits.h, [1054](#)
- fflas\_sparse.h, [892](#)
- parallel.h, [1039](#)
- FFLAS, [77](#)
- Info, [482](#), [483](#)
  - begin, [483](#), [484](#)
  - Info, [482](#), [483](#)
  - operator=, [482](#), [484](#)
  - perm, [483](#), [484](#)
  - size, [483](#), [484](#)
- info
  - BlockTransposeSIMD< Field, Simd, >, [413](#)
- init
  - FieldSimd< \_Field >, [452](#)
  - rns\_double, [532](#)–[534](#)
  - rns\_double\_extended, [544](#)
  - RNSInteger< RNS >, [548](#)
  - RNSIntegerMod< RNS >, [552](#), [553](#)
- init\_transpose
  - rns\_double, [533](#)
- init\_y
  - FFLAS::sparse\_details, [231](#)
- initA
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [504](#)
- initB
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [504](#)
- initC
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [504](#)
- initialize
  - ForStrategy1D< blocksize\_t, Cut, Param >, [465](#)
  - ForStrategy2D< blocksize\_t, Cut, Param >, [468](#)
- initOut
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, [504](#)
- INLINE
  - fflas\_simd.h, [879](#)
- inplace
  - Bench< Elt >, [413](#)
- inputs
  - TestOneMethod< Simd >, [771](#)
- INST\_OR\_DECL
  - fflas\_L1\_inst.C, [969](#)
  - fflas\_L1\_inst.h, [970](#)
  - fflas\_L2\_inst.C, [973](#)
  - fflas\_L2\_inst.h, [974](#)
  - fflas\_L3\_inst.C, [976](#)

- fflas\_L3\_inst.h, 978
- ffpack\_inst.C, 1031
- ffpack\_inst.h, 1032
- integer
  - rns\_double, 531
  - rns\_double\_extended, 543
  - RNSInteger< RNS >, 547
  - RNSIntegerMod< RNS >, 551
- Interfaces, 42
- interfaces.doxy, 957
- IntType
  - ScalFunctionsBase< Element, typename enable\_if< is\_floating\_point< Element >::value >::type >::FloatingPointTestDistribution, 464
- inv
  - RNSIntegerMod< RNS >, 554
- Invert
  - FFPACK, 325, 326, 374
- Invert2
  - FFPACK, 326, 374
- Invert2\_modular\_double
  - ffpack.C, 1005
  - ffpack\_c.h, 1024
- Invert\_modular\_double
  - ffpack.C, 1004
  - ffpack\_c.h, 1024
- Invertin\_modular\_double
  - ffpack.C, 1004
  - ffpack\_c.h, 1024
- invp
  - HelperMod< Field, ElementCategories::MachineIntTag >, 479
  - HelperMod< Field, FFLAS::ElementCategories::MachineIntTag >, 481
- is\_all\_same< Args >, 484
- is\_all\_same< T, Args... >, 484
  - value, 484
- is\_all\_same<>, 484
  - value, 485
- is\_same\_element
  - Bench< Elt >, 411
  - NoSimd< T >, 525
  - Simd128\_impl< true, true, false, 2 >, 570
  - Simd128\_impl< true, true, false, 4 >, 580
  - Simd128\_impl< true, true, false, 8 >, 590
  - Simd128\_impl< true, true, true, 2 >, 601
  - Simd128\_impl< true, true, true, 4 >, 610
  - Simd128\_impl< true, true, true, 8 >, 619
  - Simd256\_impl< true, false, true, 8 >, 629
  - Simd256\_impl< true, true, false, 2 >, 637
  - Simd256\_impl< true, true, false, 4 >, 649
  - Simd256\_impl< true, true, false, 8 >, 666
  - Simd256\_impl< true, true, true, 2 >, 676
  - Simd256\_impl< true, true, true, 4 >, 686, 687
  - Simd256\_impl< true, true, true, 8 >, 702
  - Simd512\_impl< true, false, true, 8 >, 711
  - Simd512\_impl< true, true, false, 8 >, 719
  - Simd512\_impl< true, true, true, 8 >, 730
- Test< Elt >, 767
- is\_simd< T >, 485
  - type, 485
  - value, 485
- isMOne
  - RNSInteger< RNS >, 548
  - RNSIntegerMod< RNS >, 552
- isOdd
  - FFPACK, 382
- isOne
  - RNSInteger< RNS >, 547
  - RNSIntegerMod< RNS >, 552
- IsSingular
  - FFPACK, 331, 376
- IsSingular\_modular\_double
  - ffpack.C, 1005
  - ffpack\_c.h, 1025
- isSparseMatrix< Field, M >, 485
- isSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::COO > >, 485
- isSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::COO\_ZO > >, 486
- isSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::CSR > >, 486
- isSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::CSR\_HYB > >, 486
- isSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::CSR\_ZO > >, 487
- isSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::ELL > >, 487
- isSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::ELL\_simd > >, 487
- isSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::ELL\_simd\_ZO > >, 488
- isSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::ELL\_ZO > >, 488
- isSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::HYB\_ZO > >, 488
- isSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::SELL > >, 488
- isSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::SELL\_ZO > >, 489
- isSparseMatrixMKLFormat< F, M >, 489
- isSparseMatrixSimdFormat< F, M >, 489
- isTerminated
  - ForStrategy1D< blocksize\_t, Cut, Param >, 465
  - ForStrategy2D< blocksize\_t, Cut, Param >, 468
- isZero
  - RNSInteger< RNS >, 548
  - RNSIntegerMod< RNS >, 552
- isZOSparseMatrix< F, M >, 490
- isZOSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::COO\_ZO > >, 490
- isZOSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::CSR\_ZO > >, 490
- isZOSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::ELL\_simd\_ZO > >, 490
- isZOSparseMatrix< Field, Sparse< Field, SparseMa-

- trix\_t::ELL\_ZO > >, [491](#)
- isZOSparseMatrix< Field, Sparse< Field, SparseMatrix\_t::SELL\_ZO > >, [491](#)
- Iterative, [491](#)
- iters
  - Bench< Elt >, [413](#)
- jbegin
  - ForStrategy2D< blocksize\_t, Cut, Param >, [468](#)
- jend
  - ForStrategy2D< blocksize\_t, Cut, Param >, [468](#)
- kaapi\_routines.inl, [1038](#)
- \_\_FFLASFFPACK\_KAAPI\_ROUTINES\_INL, [1038](#)
- KellerGehrig
  - FFPACK::Protected, [398](#)
- KGFast
  - FFPACK::Protected, [398](#)
- KGFast\_generalized
  - FFPACK::Protected, [399](#)
- kmax
  - Sparse< \_Field, SparseMatrix\_t::COO >, [741](#)
  - Sparse< \_Field, SparseMatrix\_t::COO\_ZO >, [742](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR >, [744](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, [746](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, [747](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL >, [749](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd >, [751](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, [752](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_ZO >, [754](#)
  - Sparse< \_Field, SparseMatrix\_t::HYB\_ZO >, [755](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL >, [757](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [759](#)
- KrylovElim
  - FFPACK, [376](#)
- KrylovElim\_modular\_double
  - ffpack.C, [1005](#)
  - ffpack\_c.h, [1024](#)
- lapack.C, [1058](#)
- \_\_FFLASFFPACK\_CONFIGURATION, [1058](#)
- \_\_FFLASFFPACK\_HAVE\_LAPACK, [1058](#)
- main, [1058](#)
- LAPACKPerm2MathPerm
  - FFPACK, [308](#)
  - ffpack.C, [994](#)
  - ffpack\_c.h, [1016](#)
- lastBlockSize
  - ForStrategy1D< blocksize\_t, Cut, Param >, [466](#)
- lastCBS
  - ForStrategy2D< blocksize\_t, Cut, Param >, [470](#)
- lastRBS
  - ForStrategy2D< blocksize\_t, Cut, Param >, [470](#)
- launch\_fger
  - test-fger.C, [1074](#)
- launch\_fger\_dispatch
  - test-fger.C, [1074](#)
- launch\_MM
  - test-fgemm.C, [1070](#)
- launch\_MM\_dispatch
  - test-fgemm-check.C, [1069](#)
  - test-fgemm.C, [1071](#)
- launch\_MV
  - test-fgemv.C, [1072](#)
- launch\_MV\_dispatch
  - test-fgemv.C, [1073](#)
- launch\_test
  - test-charpoly.C, [1061](#)
  - test-lu.C, [1096](#)
  - test-quasisep.C, [1103](#)
- launch\_wino
  - benchmark-wino.C, [808](#)
- LazyTag, [491](#)
- LD
  - fflas\_transpose.h, [921](#)
- ld
  - Sparse< \_Field, SparseMatrix\_t::ELL >, [749](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd >, [751](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, [752](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_ZO >, [754](#)
- LeadingSubmatrixRankProfiles
  - FFPACK, [338](#)
  - ffpack.C, [1007](#)
  - ffpack\_c.h, [1027](#)
- lessor
  - ScalFunctions< Element >, [561](#)
  - Simd128\_impl< true, true, false, 2 >, [572](#)
  - Simd128\_impl< true, true, false, 4 >, [582](#)
  - Simd128\_impl< true, true, false, 8 >, [592](#)
  - Simd128\_impl< true, true, true, 2 >, [606](#)
  - Simd128\_impl< true, true, true, 4 >, [615](#)
  - Simd128\_impl< true, true, true, 8 >, [624](#)
  - Simd256\_impl< true, false, true, 8 >, [633](#)
  - Simd256\_impl< true, true, false, 2 >, [639](#)
  - Simd256\_impl< true, true, false, 4 >, [651](#), [653](#)
  - Simd256\_impl< true, true, false, 8 >, [667](#)
  - Simd256\_impl< true, true, true, 2 >, [681](#)
  - Simd256\_impl< true, true, true, 4 >, [692](#), [698](#)
  - Simd256\_impl< true, true, true, 8 >, [707](#)
  - Simd512\_impl< true, false, true, 8 >, [716](#)
  - Simd512\_impl< true, true, false, 8 >, [721](#)
  - Simd512\_impl< true, true, true, 8 >, [736](#)
- lessor\_eq
  - ScalFunctions< Element >, [561](#)
  - Simd128\_impl< true, true, false, 2 >, [572](#)
  - Simd128\_impl< true, true, false, 4 >, [582](#)
  - Simd128\_impl< true, true, false, 8 >, [592](#)
  - Simd128\_impl< true, true, true, 2 >, [606](#)
  - Simd128\_impl< true, true, true, 4 >, [615](#)
  - Simd128\_impl< true, true, true, 8 >, [624](#)
  - Simd256\_impl< true, false, true, 8 >, [633](#)
  - Simd256\_impl< true, true, false, 2 >, [639](#)
  - Simd256\_impl< true, true, false, 4 >, [651](#), [653](#)
  - Simd256\_impl< true, true, false, 8 >, [668](#)

- Simd256\_impl< true, true, true, 2 >, [682](#)
  - Simd256\_impl< true, true, true, 4 >, [692](#), [699](#)
  - Simd256\_impl< true, true, true, 8 >, [708](#)
  - Simd512\_impl< true, false, true, 8 >, [716](#)
  - Simd512\_impl< true, true, false, 8 >, [721](#)
  - Simd512\_impl< true, true, true, 8 >, [736](#)
- limits< char >, [492](#)
  - digits, [492](#)
  - max, [492](#)
  - min, [492](#)
  - T, [492](#)
- limits< double >, [492](#)
  - digits, [493](#)
  - max, [493](#)
  - min, [493](#)
  - T, [493](#)
- limits< float >, [493](#)
  - digits, [493](#)
  - max, [493](#)
  - min, [493](#)
  - T, [493](#)
- limits< Givaro::Integer >, [494](#)
  - max, [494](#)
  - min, [494](#)
  - T, [494](#)
- limits< int >, [494](#)
  - digits, [495](#)
  - max, [495](#)
  - min, [495](#)
  - T, [494](#)
- limits< long >, [495](#)
  - digits, [495](#)
  - max, [495](#)
  - min, [495](#)
  - T, [495](#)
- limits< long long >, [495](#)
  - digits, [496](#)
  - max, [496](#)
  - min, [496](#)
  - T, [496](#)
- limits< Reclnt::rint< K > >, [496](#)
  - max, [496](#)
  - min, [496](#)
  - T, [496](#)
- limits< Reclnt::ruint< K > >, [497](#)
  - max, [497](#)
  - min, [497](#)
  - T, [497](#)
- limits< short int >, [497](#)
  - digits, [498](#)
  - max, [498](#)
  - min, [498](#)
  - T, [498](#)
- limits< signed char >, [498](#)
  - digits, [498](#)
  - max, [498](#)
  - min, [498](#)
  - T, [498](#)
- limits< T >, [492](#)
- limits< unsigned char >, [499](#)
  - digits, [499](#)
  - max, [499](#)
  - min, [499](#)
  - T, [499](#)
- limits< unsigned int >, [499](#)
  - digits, [500](#)
  - max, [500](#)
  - min, [500](#)
  - T, [499](#)
- limits< unsigned long >, [500](#)
  - digits, [500](#)
  - max, [500](#)
  - min, [500](#)
  - T, [500](#)
- limits< unsigned long long >, [500](#)
  - digits, [501](#)
  - max, [501](#)
  - min, [501](#)
  - T, [501](#)
- limits< unsigned short int >, [501](#)
  - digits, [501](#)
  - max, [501](#)
  - min, [501](#)
  - T, [501](#)
- load
  - Simd128\_impl< true, true, false, 2 >, [571](#), [574](#)
  - Simd128\_impl< true, true, false, 4 >, [581](#), [584](#)
  - Simd128\_impl< true, true, false, 8 >, [591](#), [594](#)
  - Simd128\_impl< true, true, true, 2 >, [601](#)
  - Simd128\_impl< true, true, true, 4 >, [610](#)
  - Simd128\_impl< true, true, true, 8 >, [619](#)
  - Simd256\_impl< true, false, true, 8 >, [630](#)
  - Simd256\_impl< true, true, false, 2 >, [638](#), [641](#)
  - Simd256\_impl< true, true, false, 4 >, [650](#), [653](#), [656](#)
  - Simd256\_impl< true, true, false, 8 >, [667](#), [669](#)
  - Simd256\_impl< true, true, true, 2 >, [677](#)
  - Simd256\_impl< true, true, true, 4 >, [688](#), [694](#)
  - Simd256\_impl< true, true, true, 8 >, [703](#)
  - Simd512\_impl< true, false, true, 8 >, [712](#)
  - Simd512\_impl< true, true, false, 8 >, [720](#), [723](#)
  - Simd512\_impl< true, true, true, 8 >, [731](#)
- loadu
  - Simd128\_impl< true, true, false, 2 >, [571](#), [574](#)
  - Simd128\_impl< true, true, false, 4 >, [581](#), [584](#)
  - Simd128\_impl< true, true, false, 8 >, [591](#), [594](#)
  - Simd128\_impl< true, true, true, 2 >, [601](#)
  - Simd128\_impl< true, true, true, 4 >, [610](#)
  - Simd128\_impl< true, true, true, 8 >, [620](#)
  - Simd256\_impl< true, false, true, 8 >, [630](#)
  - Simd256\_impl< true, true, false, 2 >, [638](#), [641](#)
  - Simd256\_impl< true, true, false, 4 >, [650](#), [653](#), [656](#)
  - Simd256\_impl< true, true, false, 8 >, [667](#), [669](#)
  - Simd256\_impl< true, true, true, 2 >, [677](#)
  - Simd256\_impl< true, true, true, 4 >, [688](#), [694](#)

- Simd256\_impl< true, true, true, 8 >, [703](#)
  - Simd512\_impl< true, false, true, 8 >, [712](#)
  - Simd512\_impl< true, true, false, 8 >, [720](#), [723](#)
  - Simd512\_impl< true, true, true, 8 >, [731](#)
- LQUPtoInverseOfFullRankMinor
  - FFPACK, [352](#), [382](#)
- LT\_OBJDIR
  - config.h, [811](#)
- LTBruhatGen
  - FFPACK, [347](#)
- LTQSorter
  - FFPACK, [349](#)
- LUdivine
  - FFPACK, [320](#), [360](#), [372](#)
- LUdivine\_construct
  - FFPACK::Protected, [397](#), [403](#)
- LUdivine\_gauss
  - FFPACK, [359](#), [373](#)
- LUdivine\_gauss\_modular\_double
  - ffpack\_c.h, [1020](#)
- LUdivine\_modular\_double
  - ffpack.C, [998](#)
  - ffpack\_c.h, [1020](#)
- LUdivine\_small
  - FFPACK, [360](#), [372](#)
- LUdivine\_small\_modular\_double
  - ffpack\_c.h, [1020](#)
- LUKrylov
  - FFPACK::Protected, [399](#)
- LUKrylov\_KGFast
  - FFPACK::Protected, [400](#)
- m
  - Bench< Elt >, [412](#)
  - Sparse< \_Field, SparseMatrix\_t::COO >, [741](#)
  - Sparse< \_Field, SparseMatrix\_t::COO\_ZO >, [743](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR >, [744](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, [746](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, [747](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL >, [749](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd >, [750](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, [752](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_ZO >, [754](#)
  - Sparse< \_Field, SparseMatrix\_t::HYB\_ZO >, [755](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL >, [757](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [759](#)
- MachineFloatTag, [502](#)
- MachineIntTag, [502](#)
- main
  - 101-fgemm.C, [1110](#)
  - 2x2-fgemm.C, [1111](#)
  - 2x2-ftsv.C, [1111](#)
  - 2x2-pluq.C, [1111](#)
  - arithprog.C, [780](#)
  - autotune/charpoly.C, [816](#)
  - autotune/pluq.C, [818](#)
  - benchmark-charpoly-mp.C, [784](#)
  - benchmark-charpoly.C, [785](#)
  - benchmark-checkers.C, [786](#)
  - benchmark-dgemm.C, [786](#)
  - benchmark-dgetrf.C, [787](#)
  - benchmark-dgetri.C, [788](#)
  - benchmark-dsytrf.C, [789](#)
  - benchmark-dtrsm.C, [789](#)
  - benchmark-dtrtri.C, [790](#)
  - benchmark-fadd-lvl2.C, [790](#)
  - benchmark-fdot.C, [791](#)
  - benchmark-fgemm-mp.C, [792](#)
  - benchmark-fgemm-rns.C, [794](#)
  - benchmark-fgemm.C, [794](#)
  - benchmark-fgemv-mp.C, [795](#)
  - benchmark-fgemv.C, [799](#)
  - benchmark-fgesv.C, [799](#)
  - benchmark-fsyr2k.C, [800](#)
  - benchmark-fsytrf.C, [800](#)
  - benchmark-fsytrf.C, [801](#)
  - benchmark-ftsm-mp.C, [802](#)
  - benchmark-ftsm.C, [802](#)
  - benchmark-ftsv.C, [803](#)
  - benchmark-fttri.C, [803](#)
  - benchmark-inverse.C, [804](#)
  - benchmark-lqup-mp.C, [804](#)
  - benchmark-lqup.C, [805](#)
  - benchmark-pluq.C, [806](#)
  - benchmark-quasisep.C, [807](#)
  - benchmark-storage-transpose.C, [808](#)
  - benchmark-wino.C, [808](#)
  - cblas.C, [1056](#)
  - clapack.C, [1057](#)
  - cuda.C, [1057](#)
  - det.C, [817](#)
  - examples/charpoly.C, [817](#)
  - examples/pluq.C, [819](#)
  - fblas.C, [1058](#)
  - fflas-101\_1.C, [1112](#)
  - fflas-101\_3.C, [1112](#)
  - fflas\_101.C, [1113](#)
  - fflas\_101\_lvl1.C, [1113](#)
  - ffpack-fgesv.C, [1113](#)
  - ffpack-solve.C, [1114](#)
  - fsyrk.C, [780](#)
  - fsytrf.C, [781](#)
  - fttri.C, [782](#)
  - lapack.C, [1058](#)
  - matmul.C, [817](#)
  - rank.C, [819](#)
  - regression-check.C, [1059](#)
  - solve.C, [819](#)
  - test-charpoly-check.C, [1060](#)
  - test-charpoly.C, [1061](#)
  - test-compressQ.C, [1062](#)
  - test-det-check.C, [1063](#)
  - test-det.C, [1063](#)
  - test-echelon.C, [1065](#)
  - test-fadd.C, [1067](#)



- test-fdot.C, [1068](#)
- test-fgemm-check.C, [1069](#)
- test-fgemm.C, [1071](#)
- test-fgemv.C, [1073](#)
- test-fger.C, [1075](#)
- test-fgesv.C, [1076](#)
- test-finit.C, [1077](#)
- test-fscal.C, [1079](#)
- test-fsyr2k.C, [1080](#)
- test-fsyrrk.C, [1082](#)
- test-fsytrf.C, [1083](#)
- test-ftrmm.C, [1084](#)
- test-ftrmv.C, [1085](#)
- test-ftrsm-check.C, [1086](#)
- test-ftrsm.C, [1087](#)
- test-ftrssyr2k.C, [1088](#)
- test-ftrstr.C, [1089](#)
- test-ftrsv.C, [1091](#)
- test-ftrtri.C, [1092](#)
- test-interfaces-c.c, [1092](#)
- test-invert-check.C, [1093](#)
- test-io.C, [1093](#)
- test-lu.C, [1097](#)
- test-maxdelayeddim.C, [1098](#)
- test-minpoly.C, [1099](#)
- test-multifile2.C, [1099](#)
- test-nullspace.C, [1101](#)
- test-permutations.C, [1101](#)
- test-pluq-check.C, [1102](#)
- test-quasisep.C, [1104](#)
- test-rankprofiles.C, [1105](#)
- test-rpm.C, [1105](#)
- test-simd.C, [1108](#)
- test-solve.C, [1109](#)
- test-storage-transpose.C, [1110](#)
- winograd.C, [783](#)
- mainpage.doxy, [816](#)
- mask\_high
  - Simd128\_impl< true, true, false, 8 >, [597](#)
  - Simd128\_impl< true, true, true, 8 >, [624](#)
  - Simd256\_impl< true, true, false, 8 >, [673](#)
  - Simd256\_impl< true, true, true, 8 >, [708](#)
  - Simd512\_impl< true, true, false, 8 >, [726](#)
  - Simd512\_impl< true, true, true, 8 >, [736](#)
- mask\_t
  - read\_sparse.h, [915](#)
- maskstore
  - Simd512\_impl< true, true, false, 8 >, [720](#), [723](#)
  - Simd512\_impl< true, true, true, 8 >, [731](#)
- MatF2MatD\_Triangular
  - FFLAS::Protected, [227](#)
- MatF2MatFI\_Triangular
  - FFLAS::Protected, [227](#)
- MathPerm2LAPACKPerm
  - FFPACK, [308](#)
  - ffpack.C, [994](#)
  - ffpack\_c.h, [1016](#)
- Matio.h, [1054](#)
- read\_field, [1055](#)
- write\_field, [1055](#)
- matmul.C, [817](#)
  - main, [817](#)
- matmul.doxy, [846](#)
- Matrix Multiplication Algorithms, [42](#)
- MatrixApplyS
  - FFPACK, [362](#), [363](#)
- MatrixApplyS\_modular\_double
  - ffpack.C, [994](#)
  - ffpack\_c.h, [1016](#)
- MatrixApplyT
  - FFPACK, [364](#)
- MatrixApplyT\_modular\_double
  - ffpack.C, [995](#)
  - ffpack\_c.h, [1016](#)
- MatVecMinPoly
  - FFPACK, [330](#), [375](#)
  - FFPACK::Protected, [400](#)
- max
  - HelperMod< Field, ElementCategories::MachineIntTag >, [479](#)
  - HelperMod< Field, FFLAS::ElementCategories::MachineFloatTag >, [481](#)
  - limits< char >, [492](#)
  - limits< double >, [493](#)
  - limits< float >, [493](#)
  - limits< Givaro::Integer >, [494](#)
  - limits< int >, [495](#)
  - limits< long >, [495](#)
  - limits< long long >, [496](#)
  - limits< Reclnt::rint< K > >, [496](#)
  - limits< Reclnt::ruint< K > >, [497](#)
  - limits< short int >, [498](#)
  - limits< signed char >, [498](#)
  - limits< unsigned char >, [499](#)
  - limits< unsigned int >, [500](#)
  - limits< unsigned long >, [500](#)
  - limits< unsigned long long >, [501](#)
  - limits< unsigned short int >, [501](#)
- max3
  - FFLAS, [77](#)
- max4
  - FFLAS, [77](#)
- MAX\_THREADS
  - parallel.h, [1040](#)
- MAX\_WITH\_SIZE\_T
  - test-maxdelayeddim.C, [1098](#)
- maxCardinality
  - FFLAS, [156](#)
- maxCardinality< Givaro::Modular< int32\_t > >
  - FFLAS, [156](#)
- maxCardinality< Givaro::Modular< int64\_t > >
  - FFLAS, [156](#)
- maxCol
  - StatsMatrix, [762](#)
- maxColDifference
  - StatsMatrix, [763](#)

- MaxDelayedDim
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, 504
- maxElement
  - RNSIntegerMod< RNS >, 552
- maxpy
  - FieldSimd< \_Field >, 455
- maxpyin
  - FieldSimd< \_Field >, 456
- maxRow
  - StatsMatrix, 762
- maxrow
  - Sparse< \_Field, SparseMatrix\_t::COO >, 741
  - Sparse< \_Field, SparseMatrix\_t::COO\_ZO >, 743
  - Sparse< \_Field, SparseMatrix\_t::CSR >, 744
  - Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, 746
  - Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, 748
  - Sparse< \_Field, SparseMatrix\_t::ELL >, 749
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd >, 751
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, 753
  - Sparse< \_Field, SparseMatrix\_t::ELL\_ZO >, 754
  - Sparse< \_Field, SparseMatrix\_t::HYB\_ZO >, 756
  - Sparse< \_Field, SparseMatrix\_t::SELL >, 757
  - Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, 760
- maxRowDifference
  - StatsMatrix, 763
- MaxStorableValue
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, 507
- MG\_DEFAULT
  - benchmark-fgemm-mp.C, 792
  - benchmark-fgemv-mp.C, 795
- min
  - HelperMod< Field, ElementCategories::MachineIntTag >, 479
  - HelperMod< Field, FFLAS::ElementCategories::MachineFloatTag >, 481
  - limits< char >, 492
  - limits< double >, 493
  - limits< float >, 493
  - limits< Givaro::Integer >, 494
  - limits< int >, 495
  - limits< long >, 495
  - limits< long long >, 496
  - limits< RecInt::rint< K > >, 496
  - limits< RecInt::ruint< K > >, 497
  - limits< short int >, 498
  - limits< signed char >, 498
  - limits< unsigned char >, 499
  - limits< unsigned int >, 500
  - limits< unsigned long >, 500
  - limits< unsigned long long >, 501
  - limits< unsigned short int >, 501
- min3
  - FFLAS, 77
- min4
  - FFLAS, 77
- min\_types
  - FFLAS::Protected, 224, 225
- minCardinality
  - FFLAS, 156
- minCol
  - StatsMatrix, 762
- minColDifference
  - StatsMatrix, 763
- minElement
  - RNSIntegerMod< RNS >, 552
- MinPoly
  - FFPACK, 329, 375
- minRow
  - StatsMatrix, 762
- minRowDifference
  - StatsMatrix, 763
- MKL\_CONFIG, 403
- MKLSparseMatrixFormat
  - FFLAS, 73
- MMHelper
  - MMHelper< FFPACK::RNSInteger< E >, Algo-Trait, ModeCategories::DefaultTag, ParSeq-Trait >, 508
  - MMHelper< FFPACK::RNSIntegerMod< E >, Algo-Trait, ModeCategories::DefaultTag, ParSeq-Trait >, 510
  - MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< Dest >, ParSeqTrait >, 512
  - MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeqTrait >, 513, 514
  - MMHelper< Field, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 515, 516
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-Trait >, 503, 504
  - MMHelper< FFPACK::RNSInteger< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 507
  - MMHelper, 508
  - normA, 509
  - normB, 509
  - operator<<, 509
  - parseq, 509
  - recLevel, 509
  - Self\_t, 508
  - setNorm, 508
  - MMHelper< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 509
  - MMHelper, 510
  - normA, 511
  - normB, 511
  - operator<<, 511
  - parseq, 511
  - recLevel, 511
  - Self\_t, 510
  - setNorm, 510



- MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo<mod  
Dest >, ParSeqTrait >, 511
- MMHelper, 512
- operator<<, 512
- parseq, 512
- recLevel, 512
- Self\_t, 512
- MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo<  
ElementCategories::RNSElementTag >, ParSeqTrait >, 513
- MMHelper, 513, 514
- normA, 514
- normB, 514
- operator<<, 514
- parseq, 514
- recLevel, 514
- Self\_t, 513
- setNorm, 514
- MMHelper< Field, AlgoTrait, ModeCategories::DefaultTag,  
ParSeqTrait >, 515
- MMHelper, 515, 516
- operator<<, 516
- parseq, 516
- recLevel, 516
- Self\_t, 515
- MMHelper< Field, AlgoTrait, ModeTrait, ParSeqTrait >, 502
- Amax, 506
- Amin, 506
- Aunfit, 505
- Bmax, 506
- Bmin, 506
- Bunfit, 505
- checkA, 505
- checkB, 505
- checkOut, 505
- Cmax, 506
- Cmin, 506
- DelayedField, 503
- delayedField, 507
- DelayedField\_t, 503
- DFElt, 503
- FieldMax, 506
- FieldMin, 506
- initA, 504
- initB, 504
- initC, 504
- initOut, 504
- MaxDelayedDim, 504
- MaxStorableValue, 507
- MMHelper, 503, 504
- operator<<, 506
- Outmax, 507
- Outmin, 507
- parseq, 507
- recLevel, 506
- Self\_t, 503
- setOutBounds, 505
- FieldSimd< \_Field >, 454
- Simd128\_impl< true, true, false, 2 >, 577
- Simd128\_impl< true, true, false, 4 >, 587
- Simd128\_impl< true, true, false, 8 >, 597
- Simd128\_impl< true, true, true, 2 >, 606
- Simd128\_impl< true, true, true, 4 >, 615
- Simd128\_impl< true, true, true, 8 >, 624
- Simd256\_impl< true, false, true, 8 >, 635
- Simd256\_impl< true, true, false, 2 >, 645
- Simd256\_impl< true, true, false, 4 >, 663
- Simd256\_impl< true, true, false, 8 >, 673
- Simd256\_impl< true, true, true, 2 >, 682
- Simd256\_impl< true, true, true, 4 >, 693, 699
- Simd256\_impl< true, true, true, 8 >, 708
- Simd512\_impl< true, true, false, 8 >, 727
- Simd512\_impl< true, true, true, 8 >, 736
- MODE
- parallel.h, 1042
- ModeTraits< Field >, 516
- value, 516
- ModeTraits< Givaro::Modular< Element, Compute >  
>, 517
- value, 517
- ModeTraits< Givaro::Modular< Givaro::Integer, Com-  
pute > >, 517
- value, 517
- ModeTraits< Givaro::Modular< int16\_t, Compute > >, 517
- value, 517
- ModeTraits< Givaro::Modular< int32\_t, Compute > >, 518
- value, 518
- ModeTraits< Givaro::Modular< int64\_t, uint64\_t > >, 518
- value, 518
- ModeTraits< Givaro::Modular< int8\_t, Compute > >, 518
- value, 518
- ModeTraits< Givaro::Modular< RecInt::ruint< K >, Compute > >, 519
- value, 519
- ModeTraits< Givaro::Modular< uint16\_t, Compute > >, 519
- value, 519
- ModeTraits< Givaro::Modular< uint32\_t, Compute > >, 519
- value, 519
- ModeTraits< Givaro::Modular< uint8\_t, Compute > >, 520
- value, 520
- ModeTraits< Givaro::ModularBalanced< Element > >, 520
- value, 520
- ModeTraits< Givaro::ModularBalanced< Givaro::Integer  
> >, 520
- value, 520
- ModeTraits< Givaro::ModularBalanced< int16\_t > >, 520

- 521
- value, 521
- ModeTraits< Givaro::ModularBalanced< int32\_t > >, 521
- value, 521
- ModeTraits< Givaro::ModularBalanced< int8\_t > >, 521
- value, 521
- ModeTraits< Givaro::Montgomery< T > >, 521
- value, 522
- ModeTraits< Givaro::ZRing< double > >, 522
- value, 522
- ModeTraits< Givaro::ZRing< float > >, 522
- value, 522
- ModeTraits< Givaro::ZRing< Givaro::Integer > >, 522
- value, 523
- ModField
  - rns\_double, 531
  - rns\_double\_extended, 543
  - RNSIntegerMod< RNS >, 551
- modp
  - FFLAS::vectorised, 287
  - FFLAS::vectorised::unswitch, 289, 290
- ModularBalanced< T >, 523
- ModularTag, 523
- mOne
  - RNSInteger< RNS >, 549
  - RNSIntegerMod< RNS >, 556
- mone
  - FFLAS, 76
  - Sparse< \_Field, SparseMatrix\_t::HYB\_ZO >, 756
- MonotonicApplyP
  - FFPACK, 310
- MonotonicCompress
  - FFPACK, 361
- MonotonicCompressCycles
  - FFPACK, 361
- MonotonicCompressMorePivots
  - FFPACK, 361
- MonotonicExpand
  - FFPACK, 362
- Montgomery< T >, 523
- mul
  - FieldSimd< \_Field >, 454
  - RNSIntegerMod< RNS >, 554
  - ScalFunctions< Element >, 560
  - Simd128\_impl< true, true, false, 2 >, 576
  - Simd128\_impl< true, true, false, 4 >, 586
  - Simd128\_impl< true, true, false, 8 >, 596
  - Simd128\_impl< true, true, true, 2 >, 604
  - Simd128\_impl< true, true, true, 4 >, 613
  - Simd128\_impl< true, true, true, 8 >, 622
  - Simd256\_impl< true, false, true, 8 >, 632
  - Simd256\_impl< true, true, false, 2 >, 644
  - Simd256\_impl< true, true, false, 4 >, 661
  - Simd256\_impl< true, true, false, 8 >, 672
  - Simd256\_impl< true, true, true, 2 >, 680
  - Simd256\_impl< true, true, true, 4 >, 690, 697
- Simd256\_impl< true, true, true, 8 >, 706
- Simd512\_impl< true, false, true, 8 >, 714
- Simd512\_impl< true, true, false, 8 >, 725
- Simd512\_impl< true, true, true, 8 >, 734
- mul\_r
  - FieldSimd< \_Field >, 454
- mulhi
  - ScalFunctionsBase< Element, typename enable\_if< is\_integral< Element >::value >::type >, 565
  - Simd128\_impl< true, true, false, 2 >, 572
  - Simd128\_impl< true, true, false, 4 >, 582
  - Simd128\_impl< true, true, false, 8 >, 592
  - Simd128\_impl< true, true, true, 2 >, 604
  - Simd128\_impl< true, true, true, 4 >, 613
  - Simd128\_impl< true, true, true, 8 >, 622
  - Simd256\_impl< true, true, false, 2 >, 639
  - Simd256\_impl< true, true, false, 4 >, 651, 654
  - Simd256\_impl< true, true, false, 8 >, 668
  - Simd256\_impl< true, true, true, 2 >, 680
  - Simd256\_impl< true, true, true, 4 >, 690, 697
  - Simd256\_impl< true, true, true, 8 >, 706
  - Simd512\_impl< true, true, false, 8 >, 721
  - Simd512\_impl< true, true, true, 8 >, 734
- mulhi\_fast
  - Simd128\_impl< true, true, false, 8 >, 597
  - Simd128\_impl< true, true, true, 8 >, 624
  - Simd256\_impl< true, true, false, 8 >, 673
  - Simd256\_impl< true, true, true, 8 >, 708
  - Simd512\_impl< true, true, false, 8 >, 726
  - Simd512\_impl< true, true, true, 8 >, 736
- mulin
  - FieldSimd< \_Field >, 454
  - ScalFunctions< Element >, 560
  - Simd256\_impl< true, false, true, 8 >, 632
  - Simd512\_impl< true, false, true, 8 >, 715
- mullo
  - ScalFunctionsBase< Element, typename enable\_if< is\_integral< Element >::value >::type >, 565
  - Simd128\_impl< true, true, false, 2 >, 576
  - Simd128\_impl< true, true, false, 4 >, 586
  - Simd128\_impl< true, true, false, 8 >, 592
  - Simd128\_impl< true, true, true, 2 >, 604
  - Simd128\_impl< true, true, true, 4 >, 613
  - Simd128\_impl< true, true, true, 8 >, 622
  - Simd256\_impl< true, true, false, 2 >, 644
  - Simd256\_impl< true, true, false, 4 >, 660
  - Simd256\_impl< true, true, false, 8 >, 668
  - Simd256\_impl< true, true, true, 2 >, 679
  - Simd256\_impl< true, true, true, 4 >, 690, 696
  - Simd256\_impl< true, true, true, 8 >, 705
  - Simd512\_impl< true, true, false, 8 >, 721
  - Simd512\_impl< true, true, true, 8 >, 734
- mulx
  - ScalFunctionsBase< Element, typename enable\_if< is\_integral< Element >::value >::type >, 565
  - Simd128\_impl< true, true, false, 2 >, 572
  - Simd128\_impl< true, true, false, 4 >, 582
  - Simd128\_impl< true, true, false, 8 >, 592

- Simd128\_impl< true, true, true, 2 >, [604](#)
- Simd128\_impl< true, true, true, 4 >, [613](#)
- Simd128\_impl< true, true, true, 8 >, [622](#)
- Simd256\_impl< true, true, false, 2 >, [639](#)
- Simd256\_impl< true, true, false, 4 >, [651](#), [654](#)
- Simd256\_impl< true, true, false, 8 >, [668](#)
- Simd256\_impl< true, true, true, 2 >, [680](#)
- Simd256\_impl< true, true, true, 4 >, [690](#), [697](#)
- Simd256\_impl< true, true, true, 8 >, [706](#)
- Simd512\_impl< true, true, false, 8 >, [721](#)
- Simd512\_impl< true, true, true, 8 >, [734](#)
- mvcnt
  - test-lu.C, [1097](#)
- n
  - Bench< Elt >, [412](#)
  - count\_nonconst\_lvalue\_reference< const T &, O... >, [439](#)
  - count\_nonconst\_lvalue\_reference< T &, O... >, [440](#)
  - count\_nonconst\_lvalue\_reference< T, O... >, [440](#)
  - count\_nonconst\_lvalue\_reference<>, [440](#)
  - Sparse< \_Field, SparseMatrix\_t::COO >, [741](#)
  - Sparse< \_Field, SparseMatrix\_t::COO\_ZO >, [743](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR >, [744](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, [746](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, [747](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL >, [749](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd >, [750](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, [752](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_ZO >, [754](#)
  - Sparse< \_Field, SparseMatrix\_t::HYB\_ZO >, [755](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL >, [757](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [759](#)
- name
  - TestOneMethod< Simd >, [771](#)
- nb\_lref
  - TestOneMethod< Simd >, [771](#)
- nChunks
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd >, [751](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, [753](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL >, [758](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [760](#)
- nDenseCols
  - StatsMatrix, [763](#)
- nDenseRows
  - StatsMatrix, [763](#)
- need\_field\_characteristic< Field >, [523](#)
  - value, [523](#)
- need\_field\_characteristic< Givaro::Modular< Field > >, [523](#)
  - value, [524](#)
- need\_field\_characteristic< Givaro::ModularBalanced< Field > >, [524](#)
  - value, [524](#)
- NeedDoublePreAddReduction
  - FFLAS::Protected, [219](#)
- NeedPreAddReduction
  - FFLAS::Protected, [218](#)
- NeedPreApyReduction
  - FFLAS::Protected, [224](#)
- NeedPreScalReduction
  - FFLAS::Protected, [223](#), [224](#)
- NeedPreSubReduction
  - FFLAS::Protected, [218](#)
- neg
  - RNSIntegerMod< RNS >, [553](#)
- nElements
  - Sparse< \_Field, SparseMatrix\_t::COO >, [741](#)
  - Sparse< \_Field, SparseMatrix\_t::COO\_ZO >, [743](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR >, [744](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, [746](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, [748](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL >, [749](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd >, [751](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, [752](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_ZO >, [754](#)
  - Sparse< \_Field, SparseMatrix\_t::HYB\_ZO >, [756](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL >, [758](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [760](#)
- nEmptyCols
  - StatsMatrix, [763](#)
- nEmptyColsEnd
  - StatsMatrix, [763](#)
- nEmptyRows
  - StatsMatrix, [763](#)
- newD
  - FFPACK::Protected, [401](#)
- NEWWINO
  - fgemm\_winograd.inl, [846](#)
- nMOnes
  - Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, [746](#)
  - StatsMatrix, [762](#)
- nnz
  - Sparse< \_Field, SparseMatrix\_t::COO >, [741](#)
  - Sparse< \_Field, SparseMatrix\_t::COO\_ZO >, [743](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR >, [744](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, [746](#)
  - Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, [748](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL >, [749](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd >, [751](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, [752](#)
  - Sparse< \_Field, SparseMatrix\_t::ELL\_ZO >, [754](#)
  - Sparse< \_Field, SparseMatrix\_t::HYB\_ZO >, [756](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL >, [758](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [760](#)
  - StatsMatrix, [762](#)
- none
  - HelperFlag, [478](#)

- nOnes
  - Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, 746
  - StatsMatrix, 762
- nonsquare\_inplace\_v1
  - FFLAS::\_ftranspose\_impl, 194
- nonsquare\_inplace\_v2
  - FFLAS::\_ftranspose\_impl, 194
- NonZeroRandomMatrix
  - FFPACK, 382, 383
- normA
  - MMHelper< FFPACK::RNSInteger< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 509
  - MMHelper< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 511
  - MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo<ForStrategy2D< blocksize\_t, Cut, Param >, 470
  - ElementCategories::RNSElementTag >, ParSeqTrait >, 514
- normB
  - MMHelper< FFPACK::RNSInteger< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 509
  - MMHelper< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 511
  - MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo<ForStrategy2D< blocksize\_t, Cut, Param >, 470
  - ElementCategories::RNSElementTag >, ParSeqTrait >, 514
- NORML\_MOD
  - fflas\_simd.h, 879
- NoSimd< T >, 524
  - aligned\_allocator, 525
  - aligned\_vector, 525
  - alignment, 525
  - compliant, 525
  - is\_same\_element, 525
  - scalar\_t, 524
  - type\_string, 525
  - valid, 525
  - vect\_size, 525
  - vect\_t, 524
- NoSimdSparseMatrix
  - FFLAS, 73
- NOSPLIT
  - parallel.h, 1044
- not\_inplace
  - FFLAS::\_ftranspose\_impl, 194
- nOthers
  - Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, 746
  - StatsMatrix, 762
- NotMKLSparseMatrixFormat
  - FFLAS, 73
- NotZOSparseMatrix
  - FFLAS, 72
- NullSpaceBasis
  - FFPACK, 334, 378
  - NullSpaceBasis\_modular\_double
    - ffpack.C, 1007
    - ffpack\_c.h, 1026
- NUM\_THREADS
  - parallel.h, 1040
- NUMARGS
  - parallel.h, 1042
- number\_kind
  - FFLAS, 76
- numBlock
  - ForStrategy1D< blocksize\_t, Cut, Param >, 467
- numblocks
  - ForStrategy1D< blocksize\_t, Cut, Param >, 466
- numColBlock
  - ForStrategy2D< blocksize\_t, Cut, Param >, 470
- numRowBlock
  - ForStrategy2D< blocksize\_t, Cut, Param >, 470
- numthreads
  - Parallel< C, P >, 526
  - Sequential, 567
- one
  - FFLAS, 76
  - RNSInteger< RNS >, 549
  - RNSIntegerMod< RNS >, 556
  - Sparse< \_Field, SparseMatrix\_t::HYB\_ZO >, 756
- OPENBLAS\_NUM\_THREADS
  - config.h, 811
- operator!=
  - rns\_double\_elt\_cstptr, 539
  - rns\_double\_elt\_ptr, 541
- operator<
  - rns\_double\_elt\_cstptr, 539
  - rns\_double\_elt\_ptr, 541
- operator<<
  - Compose< H1, H2 >, 428
  - FFLAS, 153
  - ForStrategy2D< blocksize\_t, Cut, Param >, 469
  - MMHelper< FFPACK::RNSInteger< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 509
  - MMHelper< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 511
  - MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo<Dest >, ParSeqTrait >, 512
  - MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo<ElementCategories::RNSElementTag >, ParSeqTrait >, 514
  - MMHelper< Field, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 516
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeqTrait >, 506
  - Parallel< C, P >, 526
  - Sequential, 568
  - test-fsytrf.C, 1082
  - test-simd.C, 1108
- operator()

- callLdivine\_small< double >, [415](#)
- callLdivine\_small< Element >, [415](#)
- callLdivine\_small< float >, [416](#)
- Failure, [448](#)
- readMyMachineType< Field, mpz\_t >, [530](#)
- readMyMachineType< Field, T >, [529](#)
- RNSInteger< RNS >::RandIter, [527](#)
- RNSIntegerMod< RNS >::RandIter, [528](#)
- rnsRandIter< RNS >, [557](#)
- ScalFunctionsBase< Element, typename enable\_if<
  - is\_floating\_point< Element >::value >::type
  - >::FloatingPointTestDistribution, [464](#)
- tfn\_minus, [772](#)
- tfn\_minus\_eq, [772](#)
- tfn\_mul, [772](#)
- tfn\_mul\_eq, [773](#)
- tfn\_plus, [773](#)
- tfn\_plus\_eq, [773](#)
- operator+
  - rns\_double\_elt\_cstptr, [538](#)
  - rns\_double\_elt\_ptr, [541](#)
- operator++
  - ForStrategy1D< blocksize\_t, Cut, Param >, [466](#)
  - ForStrategy2D< blocksize\_t, Cut, Param >, [468](#)
  - rns\_double\_elt\_cstptr, [538](#)
  - rns\_double\_elt\_ptr, [541](#)
- operator+=
  - rns\_double\_elt\_cstptr, [538](#)
  - rns\_double\_elt\_ptr, [541](#)
- operator-
  - rns\_double\_elt\_cstptr, [538](#)
  - rns\_double\_elt\_ptr, [541](#)
- operator--
  - rns\_double\_elt\_cstptr, [538](#)
  - rns\_double\_elt\_ptr, [541](#)
- operator-=
  - rns\_double\_elt\_cstptr, [538](#)
  - rns\_double\_elt\_ptr, [541](#)
- operator=
  - Coo< Field >, [436](#)
  - Coo< ValT, IdxT >, [435](#), [438](#)
  - FieldSimd< \_Field >, [452](#)
  - Info, [482](#), [484](#)
  - rns\_double\_elt\_cstptr, [538](#)
  - rns\_double\_elt\_ptr, [541](#)
- operator&
  - rns\_double\_elt, [536](#)
  - rns\_double\_elt\_cstptr, [538](#), [539](#)
  - rns\_double\_elt\_ptr, [540](#), [541](#)
- operator[]
  - rns\_double\_elt\_cstptr, [538](#)
  - rns\_double\_elt\_ptr, [540](#), [541](#)
- operator\*
  - rns\_double\_elt\_cstptr, [538](#)
  - rns\_double\_elt\_ptr, [540](#)
- other
  - FFLAS, [76](#)
  - rns\_double\_elt\_cstptr, [539](#)
  - rns\_double\_elt\_ptr, [542](#)
- Outmax
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-
    - Trait >, [507](#)
- Outmin
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-
    - Trait >, [507](#)
- outputs\_scalar
  - TestOneMethod< Simd >, [771](#)
- outputs\_simd
  - TestOneMethod< Simd >, [771](#)
- P
  - HelperMod< Field, ElementCategories::MachineIntTag
    - >, [479](#)
  - HelperMod< Field, FFLAS::ElementCategories::ArbitraryPrecIntTag
    - >, [480](#)
  - HelperMod< Field, FFLAS::ElementCategories::FixedPrecIntTag
    - >, [481](#)
  - HelperMod< Field, FFLAS::ElementCategories::MachineFloatTag
    - >, [481](#)
- pack
  - ScalFunctions< Element >, [562](#)
  - Simd128\_impl< true, true, false, 2 >, [575](#)
  - Simd128\_impl< true, true, false, 4 >, [585](#)
  - Simd128\_impl< true, true, false, 8 >, [595](#)
  - Simd128\_impl< true, true, true, 2 >, [603](#)
  - Simd128\_impl< true, true, true, 4 >, [612](#)
  - Simd128\_impl< true, true, true, 8 >, [621](#)
  - Simd256\_impl< true, false, true, 8 >, [631](#)
  - Simd256\_impl< true, true, false, 2 >, [642](#)
  - Simd256\_impl< true, true, false, 4 >, [658](#), [659](#)
  - Simd256\_impl< true, true, false, 8 >, [671](#)
  - Simd256\_impl< true, true, true, 2 >, [678](#)
  - Simd256\_impl< true, true, true, 4 >, [689](#), [695](#)
  - Simd256\_impl< true, true, true, 8 >, [705](#)
  - Simd512\_impl< true, false, true, 8 >, [713](#)
  - Simd512\_impl< true, true, false, 8 >, [724](#)
  - Simd512\_impl< true, true, true, 8 >, [733](#)
- pack\_even
  - ScalFunctions< Element >, [562](#)
  - Simd128\_impl< true, true, false, 2 >, [575](#)
  - Simd128\_impl< true, true, false, 4 >, [585](#)
  - Simd128\_impl< true, true, false, 8 >, [595](#)
  - Simd128\_impl< true, true, true, 2 >, [603](#)
  - Simd128\_impl< true, true, true, 4 >, [612](#)
  - Simd128\_impl< true, true, true, 8 >, [621](#)
  - Simd256\_impl< true, false, true, 8 >, [631](#)
  - Simd256\_impl< true, true, false, 2 >, [642](#)
  - Simd256\_impl< true, true, false, 4 >, [658](#)
  - Simd256\_impl< true, true, false, 8 >, [671](#)
  - Simd256\_impl< true, true, true, 2 >, [678](#)
  - Simd256\_impl< true, true, true, 4 >, [689](#), [695](#)
  - Simd256\_impl< true, true, true, 8 >, [704](#)
  - Simd512\_impl< true, false, true, 8 >, [713](#)
  - Simd512\_impl< true, true, false, 8 >, [724](#)
  - Simd512\_impl< true, true, true, 8 >, [732](#)
- pack\_lhs
  - FFLAS::details, [209](#)

- pack\_odd
  - ScalFunctions< Element >, 562
  - Simd128\_impl< true, true, false, 2 >, 575
  - Simd128\_impl< true, true, false, 4 >, 585
  - Simd128\_impl< true, true, false, 8 >, 595
  - Simd128\_impl< true, true, true, 2 >, 603
  - Simd128\_impl< true, true, true, 4 >, 612
  - Simd128\_impl< true, true, true, 8 >, 621
  - Simd256\_impl< true, false, true, 8 >, 631
  - Simd256\_impl< true, true, false, 2 >, 642
  - Simd256\_impl< true, true, false, 4 >, 658
  - Simd256\_impl< true, true, false, 8 >, 671
  - Simd256\_impl< true, true, true, 2 >, 678
  - Simd256\_impl< true, true, true, 4 >, 689, 695
  - Simd256\_impl< true, true, true, 8 >, 705
  - Simd512\_impl< true, false, true, 8 >, 713
  - Simd512\_impl< true, true, false, 8 >, 724
  - Simd512\_impl< true, true, true, 8 >, 733
- pack\_rhs
  - FFLAS::details, 209
- PACKAGE
  - config.h, 811
- PACKAGE\_BUGREPORT
  - config.h, 811
- PACKAGE\_NAME
  - config.h, 811
- PACKAGE\_STRING
  - config.h, 811
- PACKAGE\_TARNAME
  - config.h, 811
- PACKAGE\_URL
  - config.h, 811
- PACKAGE\_VERSION
  - config.h, 811
- PAR\_BLOCK
  - parallel.h, 1039
- Parallel
  - Parallel< C, P >, 526
- Parallel< C, P >, 526
  - Cut, 526
  - numthreads, 526
  - operator<<, 526
  - Parallel, 526
  - Param, 526
  - set\_numthreads, 526
- parallel.h, 1038
  - \_\_FFLASFFPACK\_SEQUENTIAL, 1039
  - BARRIER, 1039
  - BEGIN\_PARALLEL\_MAIN, 1040
  - CHECK\_DEPENDENCIES, 1039
  - COMMA, 1042
  - CONSTREFERENCE, 1040
  - END\_PARALLEL\_MAIN, 1040
  - FOR1D, 1041
  - FOR2D, 1041
  - FORBLOCK1D, 1040
  - FORBLOCK2D, 1041
  - index\_t, 1039
  - MAX\_THREADS, 1040
  - MODE, 1042
  - NOSPLIT, 1044
  - NUM\_THREADS, 1040
  - NUMARGS, 1042
  - PAR\_BLOCK, 1039
  - PARFOR1D, 1041
  - PARFOR2D, 1042
  - PARFORBLOCK1D, 1041
  - PARFORBLOCK2D, 1042
  - PP\_ARG\_N, 1042
  - PP\_NARG\_, 1042
  - PP\_RSEQ\_N, 1044
  - READ, 1040
  - READWRITE, 1040
  - RETURNPARAM, 1042
  - SET\_THREADS, 1040
  - splitt, 1044
  - SPLITTER, 1044
  - splitting\_0, 1044
  - splitting\_1, 1044
  - splitting\_2, 1044
  - splitting\_3, 1044
  - SYNCH\_GROUP, 1040
  - TASK, 1039
  - THREAD\_INDEX, 1040
  - VALUE, 1040
  - WAIT, 1039
  - WRITE, 1040
- Param
  - Parallel< C, P >, 526
- PARFOR1D
  - parallel.h, 1041
- PARFOR2D
  - parallel.h, 1042
- PARFORBLOCK1D
  - parallel.h, 1041
- PARFORBLOCK2D
  - parallel.h, 1042
- parseArguments
  - FFLAS, 188
- parseq
  - MMHelper< FFPACK::RNSInteger< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 509
  - MMHelper< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 511
  - MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< Dest >, ParSeqTrait >, 512
  - MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeqTrait >, 514
  - MMHelper< Field, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 516
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeqTrait >, 507
  - TRSMHelper< ReclterTrait, ParSeqTrait >, 776



- PBASECASE\_K
  - ffpack\_ppluq.inl, [949](#)
- pColumnEchelonForm
  - FFPACK, [321](#)
- pColumnEchelonForm\_modular\_double
  - ffpack.C, [1001](#)
- pColumnEchelonForm\_modular\_float
  - ffpack.C, [1002](#)
- pColumnEchelonForm\_modular\_int32\_t
  - ffpack.C, [1003](#)
- pColumnRankProfile
  - FFPACK, [337](#)
- pDet
  - FFPACK, [332](#)
- perm
  - Info, [483](#), [484](#)
  - Sparse<\_Field, SparseMatrix\_t::SELL >, [758](#)
  - Sparse<\_Field, SparseMatrix\_t::SELL\_ZO >, [760](#)
- PermApplyS
  - FFPACK, [363](#)
- PermApplyS\_double
  - ffpack.C, [995](#)
  - ffpack\_c.h, [1016](#)
- PermApplyT
  - FFPACK, [365](#)
- PermApplyT\_double
  - ffpack.C, [995](#)
  - ffpack\_c.h, [1017](#)
- pfadd
  - FFLAS, [79](#)
- pfaddin
  - FFLAS, [79](#)
- pfgemm
  - FFLAS, [144](#), [184–186](#)
- pfgemm\_1D\_rec
  - FFLAS, [145](#)
- pfgemm\_2D\_rec
  - FFLAS, [145](#)
- pfgemm\_3D\_rec
  - FFLAS, [145](#)
- pfgemm\_3D\_rec2
  - FFLAS, [146](#)
- pfgemm\_variants.inl, [1045](#)
- pfgemv.inl, [1045](#)
- pfrend
  - FFLAS, [184](#)
- pfreduce
  - FFLAS, [110](#)
- pfspmm
  - FFLAS::sparse\_details, [237–239](#)
  - FFLAS::sparse\_details\_impl, [254](#), [261](#), [262](#), [264–266](#), [276](#)
- pfspmm\_dispatch
  - FFLAS::sparse\_details, [236](#), [237](#)
- pfspmm\_mone
  - FFLAS::sparse\_details\_impl, [255](#)
- pfspmm\_one
  - FFLAS::sparse\_details\_impl, [255](#)
- pfspmm\_zo
  - FFLAS::sparse\_details\_impl, [266](#)
- pfspmv
  - FFLAS::sparse\_details, [239](#), [240](#)
  - FFLAS::sparse\_details\_impl, [256](#), [263](#), [266](#), [267](#), [272](#), [276–279](#)
- pfspmv\_mone
  - FFLAS::sparse\_details\_impl, [257](#), [267](#), [268](#), [273](#), [279](#)
- pfspmv\_one
  - FFLAS::sparse\_details\_impl, [256](#), [257](#), [267](#), [273](#), [279](#)
- pfspmv\_task
  - FFLAS::sparse\_details\_impl, [256](#)
- pfsub
  - FFLAS, [79](#)
- pfsubin
  - FFLAS, [80](#)
- pfzero
  - FFLAS, [184](#)
- PLUQ
  - FFPACK, [318](#), [319](#), [368](#), [369](#), [372](#)
- pluq.C, [818](#)
- PLUQ\_basecaseCrout
  - FFPACK, [367](#)
- PLUQ\_basecaseV2
  - FFPACK, [367](#)
- PLUQ\_basecaseV3
  - FFPACK, [367](#)
- PLUQ\_modular\_double
  - ffpack.C, [998](#)
  - ffpack\_c.h, [1020](#)
- PLUQtoEchelonPermutation
  - FFPACK, [347](#)
  - ffpack.C, [1011](#)
  - ffpack\_c.h, [1030](#)
- pm1
  - HelperFlag, [478](#)
- pMMH
  - TRSMHelper< ReclterTrait, ParSeqTrait >, [775](#)
- pow50rem
  - HelperMod< Field, ElementCategories::MachineIntTag >, [479](#)
- PP\_ARG\_N
  - parallel.h, [1042](#)
- PP\_NARG\_
  - parallel.h, [1042](#)
- PP\_RSEQ\_N
  - parallel.h, [1044](#)
- pPLUQ
  - FFPACK, [319](#)
- pRank
  - FFPACK, [331](#)
- preamble
  - FFLAS, [190](#)
- precompute\_cst
  - rns\_double, [532](#)
  - rns\_double\_extended, [544](#)

- pReducedColumnEchelonForm
  - FFPACK, [324](#)
- pReducedColumnEchelonForm\_modular\_double
  - ffpack.C, [1002](#)
- pReducedColumnEchelonForm\_modular\_float
  - ffpack.C, [1003](#)
- pReducedColumnEchelonForm\_modular\_int32\_t
  - ffpack.C, [1004](#)
- pReducedRowEchelonForm
  - FFPACK, [325](#)
- pReducedRowEchelonForm\_modular\_double
  - ffpack.C, [1002](#)
- pReducedRowEchelonForm\_modular\_float
  - ffpack.C, [1003](#)
- pReducedRowEchelonForm\_modular\_int32\_t
  - ffpack.C, [1004](#)
- prefetch
  - FFLAS, [192](#)
- print
  - Failure, [449](#)
- printHelpMessage
  - args-parser.h, [1047](#)
- printPolynomial
  - test-charpoly-check.C, [1060](#)
- printvect
  - test-compressQ.C, [1062](#)
- productBruhatxTS
  - FFPACK, [351](#), [354](#)
- pRowEchelonForm
  - FFPACK, [322](#)
- pRowEchelonForm\_modular\_double
  - ffpack.C, [1002](#)
- pRowEchelonForm\_modular\_float
  - ffpack.C, [1003](#)
- pRowEchelonForm\_modular\_int32\_t
  - ffpack.C, [1003](#)
- pRowRankProfile
  - FFPACK, [336](#)
- PSeq
  - benchmark-fgemm-rns.C, [794](#)
- pSolve
  - FFPACK, [334](#)
- PTRSM\_HYBRID\_THRESHOLD
  - fflas\_ptrsm.inl, [878](#)
- PURE
  - fflas\_simd.h, [879](#)
- queryCacheSizes
  - FFLAS, [193](#)
- queryL1CacheSize
  - FFLAS, [193](#)
- queryTopLevelCacheSize
  - FFLAS, [193](#)
- RandInt
  - FFPACK, [386](#)
- RandIter
  - RNSInteger< RNS >::RandIter, [527](#)
  - RNSIntegerMod< RNS >::RandIter, [528](#)
- random
  - RNSInteger< RNS >::RandIter, [527](#)
  - RNSIntegerMod< RNS >::RandIter, [528](#)
  - rnsRandIter< RNS >, [557](#)
- RandomIndexSubset
  - FFPACK, [388](#)
- RandomKrylovPrecond
  - FFPACK::Protected, [400](#)
- RandomLTQSMatixWithRankandQSorder
  - FFPACK, [395](#)
- RandomLTQSRankProfileMatrix
  - FFPACK, [389](#)
- RandomMatrix
  - FFPACK, [384](#)
- RandomMatrixWithDet
  - FFPACK, [394](#)
- RandomMatrixWithRank
  - FFPACK, [386](#), [387](#)
- RandomMatrixWithRankandRandomRPM
  - FFPACK, [392](#)
- RandomMatrixWithRankandRPM
  - FFPACK, [389](#), [390](#)
- RandomNullSpaceVector
  - FFPACK, [334](#), [352](#), [378](#)
- RandomNullSpaceVector\_modular\_double
  - ffpack.C, [1006](#)
  - ffpack\_c.h, [1026](#)
- RandomPermutation
  - FFPACK, [388](#)
- RandomRankProfileMatrix
  - FFPACK, [388](#)
- RandomSymmetricMatrix
  - FFPACK, [386](#)
- RandomSymmetricMatrixWithRankandRandomRPM
  - FFPACK, [393](#)
- RandomSymmetricMatrixWithRankandRPM
  - FFPACK, [390](#), [391](#)
- RandomSymmetricRankProfileMatrix
  - FFPACK, [389](#)
- RandomTriangularMatrix
  - FFPACK, [385](#)
- Rank
  - FFPACK, [330](#), [331](#), [376](#)
- rank.C, [819](#)
  - main, [819](#)
- Rank\_modular\_double
  - ffpack.C, [1005](#)
  - ffpack\_c.h, [1025](#)
- RankProfileFromLU
  - FFPACK, [337](#)
  - ffpack.C, [1007](#)
  - ffpack\_c.h, [1027](#)
- READ
  - parallel.h, [1040](#)
- read\_field
  - Matio.h, [1055](#)
- read\_sparse.h, [915](#)
  - DNS\_BIN\_VER, [915](#)



- mask\_t, 915
- readDnsFormat
  - FFLAS, 154
- readMachineType
  - FFLAS, 154
- ReadMatrix
  - FFLAS, 190
- readMyMachineType< Field, mpz\_t >, 529
  - Element, 530
  - Element\_ptr, 530
  - operator(), 530
- readMyMachineType< Field, T >, 529
  - Element, 529
  - Element\_ptr, 529
  - operator(), 529
- readOrRandomMatrixWithRankAndRandomRPM
  - test-nullspace.C, 1100
- readSmsFormat
  - FFLAS, 153
- readSprFormat
  - FFLAS, 153
- READWRITE
  - parallel.h, 1040
- Rec\_Initialize
  - benchmark-pluq.C, 806
- RecInt, 403
- recLevel
  - MMHelper< FFPACK::RNSInteger< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 509
  - MMHelper< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 511
  - MMHelper< Field, AlgoTrait, ModeCategories::ConversionTag, Dest >, ParSeqTrait >, 512
  - MMHelper< Field, AlgoTrait, ModeCategories::ConversionTag, ElementCategories::RNSElementTag >, ParSeqTrait >, 514
  - MMHelper< Field, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, 516
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeqTrait >, 506
- Recursive, 530
- reduce
  - FFLAS::vectorised, 286, 287
  - rns\_double, 533
  - rns\_double\_extended, 544
  - RNSInteger< RNS >, 548
  - RNSIntegerMod< RNS >, 553
- reduce\_modp
  - RNSIntegerMod< RNS >, 554, 555
- reduce\_modp\_rnsmajor
  - RNSIntegerMod< RNS >, 555
- ReducedColumnEchelonForm
  - FFPACK, 323, 324, 374
- ReducedColumnEchelonForm\_modular\_double
  - ffpack.C, 999
  - ffpack\_c.h, 1022
- ReducedColumnEchelonForm\_modular\_float
  - ffpack.C, 1000
  - ffpack\_c.h, 1022
- ReducedColumnEchelonForm\_modular\_int32\_t
  - ffpack.C, 1001
  - ffpack\_c.h, 1023
- ReducedRowEchelonForm
  - FFPACK, 324, 325, 373
- ReducedRowEchelonForm2\_modular\_double
  - ffpack\_c.h, 1023
- ReducedRowEchelonForm\_modular\_double
  - ffpack.C, 999
  - ffpack\_c.h, 1022
- ReducedRowEchelonForm\_modular\_float
  - ffpack.C, 1000
  - ffpack\_c.h, 1023
- ReducedRowEchelonForm\_modular\_int32\_t
  - ffpack.C, 1001
  - ffpack\_c.h, 1023
- REF\_modular\_double
  - ffpack\_c.h, 1024
- regression-check.C, 1059
  - check1, 1059
  - check2, 1059
  - check3, 1059
  - check4, 1059
  - checkZeroDimCharpoly, 1059
  - checkZeroDimMinPoly, 1059
  - gf2ModularBalanced, 1059
  - main, 1059
- Residu
  - Bench< Elt >, 411
  - Test< Elt >, 766
- RETURNPARAM
  - parallel.h, 1042
- RTAG
  - CheckerImplem\_charpoly< Givaro::ZRing< Givaro::Integer >, Polynomial >, 418
- RNSInteger< RNS >::RandIter, 527
- RNSIntegerMod< RNS >::RandIter, 528
- rnsRandIter< RNS >, 557
- rint< K >, 530
- RNS, 43
  - benchmark-fgemm-rns.C, 793
- rns
  - RNSInteger< RNS >, 547
  - RNSIntegerMod< RNS >, 551
- rns-double-elt.h, 953
- rns-double-recint.inl, 954
  - \_\_FFLASFFPACK\_field\_rns\_double\_recint\_INL, 954
- rns-double.h, 954
  - ROUND\_DOWN, 955
- rns-double.inl, 955
  - \_\_FFLASFFPACK\_field\_rns\_double\_INL, 955
- rns-integer-mod.h, 955
- rns-integer.h, 956

- rns.h, [957](#)
- rns.inl, [957](#)
  - \_\_FFLASFFPACK\_field\_rns\_INL, [957](#)
- rns\_double, [530](#)
  - \_M, [534](#)
  - \_MMi, [535](#)
  - \_Mi, [534](#)
  - \_basis, [534](#)
  - \_basisMax, [534](#)
  - \_crt\_in, [535](#)
  - \_crt\_out, [535](#)
  - \_field\_rns, [534](#)
  - \_invbasis, [534](#)
  - \_ldm, [535](#)
  - \_mi\_sum, [535](#)
  - \_negbasis, [534](#)
  - \_pbits, [535](#)
  - \_size, [535](#)
  - BasisElement, [532](#)
  - ConstElement\_ptr, [532](#)
  - convert, [533](#), [534](#)
  - convert\_transpose, [533](#)
  - Element, [532](#)
  - Element\_ptr, [532](#)
  - init, [532–534](#)
  - init\_transpose, [533](#)
  - integer, [531](#)
  - ModField, [531](#)
  - precompute\_cst, [532](#)
  - reduce, [533](#)
  - rns\_double, [532](#)
- rns\_double\_elt, [535](#)
  - \_alloc, [536](#)
  - \_ptr, [536](#)
  - \_stride, [536](#)
  - ~rns\_double\_elt, [536](#)
  - operator&, [536](#)
  - rns\_double\_elt, [536](#)
- rns\_double\_elt\_cstptr, [537](#)
  - \_alloc, [539](#)
  - \_ptr, [539](#)
  - \_stride, [539](#)
  - operator!=, [539](#)
  - operator<, [539](#)
  - operator+, [538](#)
  - operator++, [538](#)
  - operator+=", [538](#)
  - operator-, [538](#)
  - operator--, [538](#)
  - operator=, [538](#)
  - operator=, [538](#)
  - operator&, [538](#), [539](#)
  - operator[], [538](#)
  - operator\*, [538](#)
  - other, [539](#)
  - rns\_double\_elt\_cstptr, [537](#), [538](#)
- rns\_double\_elt\_ptr, [539](#)
  - \_alloc, [542](#)
  - \_ptr, [542](#)
  - \_stride, [542](#)
  - operator!=, [541](#)
  - operator<, [541](#)
  - operator+, [541](#)
  - operator++, [541](#)
  - operator+=", [541](#)
  - operator-, [541](#)
  - operator--, [541](#)
  - operator=, [541](#)
  - operator=, [541](#)
  - operator&, [540](#), [541](#)
  - operator[], [540](#), [541](#)
  - operator\*, [540](#)
  - other, [542](#)
  - rns\_double\_elt\_ptr, [540](#)
- rns\_double\_extended, [542](#)
  - \_M, [545](#)
  - \_MMi, [545](#)
  - \_Mi, [545](#)
  - \_basis, [545](#)
  - \_basisMax, [545](#)
  - \_crt\_in, [545](#)
  - \_crt\_out, [545](#)
  - \_field\_rns, [545](#)
  - \_invbasis, [545](#)
  - \_ldm, [545](#)
  - \_negbasis, [545](#)
  - \_pbits, [545](#)
  - \_size, [545](#)
  - BasisElement, [543](#)
  - ConstElement\_ptr, [543](#)
  - convert, [544](#)
  - Element, [543](#)
  - Element\_ptr, [543](#)
  - init, [544](#)
  - integer, [543](#)
  - ModField, [543](#)
  - precompute\_cst, [544](#)
  - reduce, [544](#)
  - rns\_double\_extended, [543](#)
- RNSElementTag, [546](#)
- RNSInteger
  - RNSInteger< RNS >, [547](#)
- RNSInteger< RNS >, [546](#)
  - \_rns, [549](#)
  - assign, [549](#)
  - BasisElement, [547](#)
  - cardinality, [548](#)
  - characteristic, [548](#)
  - ConstElement\_ptr, [547](#)
  - convert, [548](#)
  - Element, [547](#)
  - Element\_ptr, [547](#)
  - init, [548](#)
  - integer, [547](#)
  - isMOne, [548](#)
  - isOne, [547](#)

- isZero, [548](#)
- mOne, [549](#)
- one, [549](#)
- reduce, [548](#)
- rns, [547](#)
- RNSInteger, [547](#)
- size, [547](#)
- write, [549](#)
- zero, [549](#)
- RNSInteger< RNS >::RandIter, [527](#)
  - operator(), [527](#)
  - RandIter, [527](#)
  - random, [527](#)
  - ring, [527](#)
- RNSIntegerMod
  - RNSIntegerMod< RNS >, [551](#)
- RNSIntegerMod< RNS >, [549](#)
  - \_F, [555](#)
  - \_Mi\_modp\_rns, [555](#)
  - \_RNSdelayed, [556](#)
  - \_iM\_modp\_rns, [555](#)
  - \_p, [555](#)
  - \_rns, [555](#)
  - add, [553](#)
  - areEqual, [554](#)
  - assign, [553](#)
  - axpyin, [554](#)
  - BasisElement, [551](#)
  - cardinality, [552](#)
  - characteristic, [552](#)
  - ConstElement\_ptr, [551](#)
  - convert, [553](#)
  - delayed, [551](#)
  - Element, [551](#)
  - Element\_ptr, [551](#)
  - init, [552](#), [553](#)
  - integer, [551](#)
  - inv, [554](#)
  - isMOne, [552](#)
  - isOne, [552](#)
  - isZero, [552](#)
  - maxElement, [552](#)
  - minElement, [552](#)
  - ModField, [551](#)
  - mOne, [556](#)
  - mul, [554](#)
  - neg, [553](#)
  - one, [556](#)
  - reduce, [553](#)
  - reduce\_modp, [554](#), [555](#)
  - reduce\_modp\_rnsmajor, [555](#)
  - rns, [551](#)
  - RNSIntegerMod, [551](#)
  - size, [551](#)
  - sub, [553](#)
  - write, [554](#)
  - write\_matrix, [554](#)
  - write\_matrix\_long, [555](#)
  - zero, [556](#)
- RNSIntegerMod< RNS >::RandIter, [528](#)
  - operator(), [528](#)
  - RandIter, [528](#)
  - random, [528](#)
  - ring, [528](#)
- RNSModulus
  - FFLAS::CuttingStrategy, [202](#)
- rnsRandIter
  - rnsRandIter< RNS >, [556](#)
- rnsRandIter< RNS >, [556](#)
  - operator(), [557](#)
  - random, [557](#)
  - ring, [557](#)
  - rnsRandIter, [556](#)
- round
  - ScalFunctionsBase< Element, typename enable\_if< is\_floating\_point< Element >::value >::type >, [563](#)
  - ScalFunctionsBase< Element, typename enable\_if< is\_integral< Element >::value >::type >, [565](#)
  - Simd128\_impl< true, true, false, 2 >, [577](#)
  - Simd128\_impl< true, true, false, 4 >, [587](#)
  - Simd128\_impl< true, true, false, 8 >, [597](#)
  - Simd128\_impl< true, true, true, 2 >, [606](#)
  - Simd128\_impl< true, true, true, 4 >, [615](#)
  - Simd128\_impl< true, true, true, 8 >, [624](#)
  - Simd256\_impl< true, false, true, 8 >, [634](#)
  - Simd256\_impl< true, true, false, 2 >, [645](#)
  - Simd256\_impl< true, true, false, 4 >, [662](#)
  - Simd256\_impl< true, true, false, 8 >, [673](#)
  - Simd256\_impl< true, true, true, 2 >, [682](#)
  - Simd256\_impl< true, true, true, 4 >, [693](#), [699](#)
  - Simd256\_impl< true, true, true, 8 >, [708](#)
  - Simd512\_impl< true, false, true, 8 >, [716](#)
  - Simd512\_impl< true, true, false, 8 >, [726](#)
  - Simd512\_impl< true, true, true, 8 >, [736](#)
- ROUND\_DOWN
  - fflas\_sparse.h, [892](#)
  - rns-double.h, [955](#)
- Row, [557](#)
- row
  - Coo< Field >, [437](#)
  - Coo< ValT, IdxT >, [435](#), [438](#)
  - Sparse< \_Field, SparseMatrix\_t::COO >, [741](#)
  - Sparse< \_Field, SparseMatrix\_t::COO\_ZO >, [742](#)
- rowblockindex
  - ForStrategy2D< blocksize\_t, Cut, Param >, [469](#)
- rowBlockSize
  - ForStrategy2D< blocksize\_t, Cut, Param >, [469](#)
- rowdim
  - StatsMatrix, [762](#)
- RowEchelonForm
  - FFPACK, [322](#), [323](#), [373](#)
- RowEchelonForm\_modular\_double
  - ffpack.C, [999](#)
  - ffpack\_c.h, [1021](#)
- RowEchelonForm\_modular\_float

- ffpack.C, [1000](#)
- ffpack\_c.h, [1021](#)
- RowEchelonForm\_modular\_int32\_t
  - ffpack.C, [1001](#)
  - ffpack\_c.h, [1022](#)
- rownumblocks
  - ForStrategy2D< blocksize\_t, Cut, Param >, [468](#)
- RowRankProfile
  - FFPACK, [335](#), [336](#), [378](#)
- RowRankProfile\_modular\_double
  - ffpack.C, [1007](#)
  - ffpack\_c.h, [1027](#)
- RowRankProfileSubmatrix
  - FFPACK, [340](#), [379](#)
- RowRankProfileSubmatrix\_modular\_double
  - ffpack.C, [1008](#)
  - ffpack\_c.h, [1028](#)
- RowRankProfileSubmatrixIndices
  - FFPACK, [338](#), [379](#)
- RowRankProfileSubmatrixIndices\_modular\_double
  - ffpack.C, [1008](#)
  - ffpack\_c.h, [1027](#)
- ruint< K >, [557](#)
- run
  - Bench< Elt >, [412](#)
  - Test< Elt >, [768](#)
- run\_with\_field
  - benchmark-charpoly.C, [784](#)
  - benchmark-fdot.C, [791](#)
  - benchmark-quasisep.C, [807](#)
  - test-charpoly.C, [1061](#)
  - test-echelon.C, [1065](#)
  - test-fdot.C, [1068](#)
  - test-fgemm-check.C, [1069](#)
  - test-fgemm.C, [1071](#)
  - test-fgemv.C, [1073](#)
  - test-fger.C, [1075](#)
  - test-fgesv.C, [1076](#)
  - test-finit.C, [1077](#)
  - test-fsyr2k.C, [1079](#)
  - test-fsyk.C, [1081](#)
  - test-fsytrf.C, [1083](#)
  - test-ftrmm.C, [1084](#)
  - test-ftrmv.C, [1085](#)
  - test-ftrsm.C, [1087](#)
  - test-ftrssyr2k.C, [1088](#)
  - test-ftrstr.C, [1089](#)
  - test-ftrsv.C, [1090](#)
  - test-ftrtri.C, [1092](#)
  - test-io.C, [1093](#)
  - test-lu.C, [1097](#)
  - test-minpoly.C, [1099](#)
  - test-nullspace.C, [1101](#)
  - test-quasisep.C, [1104](#)
  - test-rankprofiles.C, [1104](#)
  - test-solve.C, [1109](#)
- run\_with\_Integer
  - test-fdot.C, [1068](#)
- saxpy\_
  - config-blas.h, [826](#)
- ScalAndReduce
  - FFLAS::Protected, [219](#), [223](#)
- scalar\_t
  - FieldSimd< \_Field >, [451](#)
  - NoSimd< T >, [524](#)
  - Simd128\_impl< true, true, false, 2 >, [570](#)
  - Simd128\_impl< true, true, false, 4 >, [580](#)
  - Simd128\_impl< true, true, false, 8 >, [590](#)
  - Simd128\_impl< true, true, true, 2 >, [600](#)
  - Simd128\_impl< true, true, true, 4 >, [609](#)
  - Simd128\_impl< true, true, true, 8 >, [618](#)
  - Simd256\_impl< true, false, true, 8 >, [629](#)
  - Simd256\_impl< true, true, false, 2 >, [637](#)
  - Simd256\_impl< true, true, false, 4 >, [649](#)
  - Simd256\_impl< true, true, false, 8 >, [666](#)
  - Simd256\_impl< true, true, true, 2 >, [675](#)
  - Simd256\_impl< true, true, true, 4 >, [686](#)
  - Simd256\_impl< true, true, true, 8 >, [702](#)
  - Simd512\_impl< true, false, true, 8 >, [711](#)
  - Simd512\_impl< true, true, false, 8 >, [719](#)
  - Simd512\_impl< true, true, true, 8 >, [730](#)
- ScalFunctions< Element >, [557](#)
  - add, [559](#)
  - addin, [559](#)
  - blend, [562](#)
  - div, [560](#)
  - eq, [561](#)
  - fmadd, [560](#)
  - fmaddin, [560](#)
  - fmsub, [560](#)
  - fmsubin, [560](#)
  - fnmadd, [560](#)
  - fnmaddin, [561](#)
  - genInputs, [558](#)
  - genInputsWithZero, [558](#)
  - greater, [561](#)
  - greater\_eq, [561](#)
  - lesser, [561](#)
  - lesser\_eq, [561](#)
  - mul, [560](#)
  - mulin, [560](#)
  - pack, [562](#)
  - pack\_even, [562](#)
  - pack\_odd, [562](#)
  - sub, [559](#)
  - subin, [559](#)
  - unpackhi, [561](#)
  - unpacklo, [561](#)
  - unpacklohi, [562](#)
  - vand, [559](#)
  - vandnot, [559](#)
  - vectElt, [558](#)
  - vor, [559](#)
  - vxor, [559](#)
  - zero, [559](#)
- ScalFunctionsBase< Element, Enable >, [562](#)

- ScalFunctionsBase< Element, typename enable\_if<  
is\_floating\_point< Element >::value >::type  
>, 563
- \_zero, 564
- blendv, 563
- ceil, 563
- cmp\_false, 564
- cmp\_true, 564
- floor, 563
- fma, 564
- get\_default\_random\_generator, 563
- round, 563
- ScalFunctionsBase< Element, typename enable\_if<  
is\_floating\_point< Element >::value >::type  
>::FloatingPointTestDistribution, 464
- FloatingPointTestDistribution, 464
- IntType, 464
- operator(), 464
- ScalFunctionsBase< Element, typename enable\_if<  
is\_integral< Element >::value >::type >, 564
- \_zero, 567
- cmp\_false, 567
- cmp\_true, 567
- fma, 565
- fmaddx, 565
- fmaddxin, 565
- fmsubx, 566
- fmsubxin, 566
- fnmaddx, 566
- fnmaddxin, 566
- get\_default\_random\_generator, 565
- mulhi, 565
- mullo, 565
- mulx, 565
- round, 565
- sll, 566
- sra, 566
- srl, 566
- scalp
- FFLAS::vectorised, 287, 288
- FFLAS::vectorised::unswitch, 290
- schedule\_bini.inl, 846
- \_\_FFLASFFPACK\_fgemm\_bini\_INL, 847
- schedule\_winograd.inl, 847
- \_\_FFLASFFPACK\_fgemm\_winograd\_INL, 847
- schedule\_winograd\_acc.inl, 847
- \_\_FFLASFFPACK\_fgemm\_winograd\_acc\_INL, 848
- schedule\_winograd\_acc\_ip.inl, 848
- \_\_FFLASFFPACK\_fgemm\_winograd\_acc\_ip\_INL, 849
- schedule\_winograd\_ip.inl, 849
- \_\_FFLASFFPACK\_fgemm\_winograd\_ip\_INL, 849
- scopy\_
- config-blas.h, 828
- sdot\_
- config-blas.h, 827
- second\_component
- Compose< H1, H2 >, 428
- Self
- Coo< ValT, IdxT >, 434, 437
- Self\_t
- MMHelper< FFPACK::RNSInteger< E >, Algo-  
Trait, ModeCategories::DefaultTag, ParSeq-  
Trait >, 508
- MMHelper< FFPACK::RNSIntegerMod< E >, Al-  
goTrait, ModeCategories::DefaultTag, ParSeq-  
Trait >, 510
- MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo<  
Dest >, ParSeqTrait >, 512
- MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo<  
ElementCategories::RNSElementTag >,  
ParSeqTrait >, 513
- MMHelper< Field, AlgoTrait, ModeCategories::DefaultTag,  
ParSeqTrait >, 515
- MMHelper< Field, AlgoTrait, ModeTrait, ParSeq-  
Trait >, 503
- Sparse< \_Field, SparseMatrix\_t::HYB\_ZO >, 755
- SELL
- FFLAS, 76
- sell.h, 916
- sell\_pspmv.inl, 916
- \_\_FFLASFFPACK\_fflas\_sparse\_sell\_pspmv\_INL,  
916
- sell\_spmv.inl, 917
- \_\_FFLASFFPACK\_fflas\_sparse\_sell\_spmv\_INL,  
917
- sell\_utils.inl, 917
- \_\_FFLASFFPACK\_fflas\_sparse\_sell\_utils\_INL,  
918
- SELL\_ZO
- FFLAS, 76
- Sequential, 567
- numthreads, 567
- operator<<, 568
- Sequential, 567
- set
- Simd128\_impl< true, true, false, 2 >, 571, 573
- Simd128\_impl< true, true, false, 4 >, 581, 583
- Simd128\_impl< true, true, false, 8 >, 591, 593
- Simd128\_impl< true, true, true, 2 >, 601
- Simd128\_impl< true, true, true, 4 >, 610
- Simd128\_impl< true, true, true, 8 >, 619
- Simd256\_impl< true, false, true, 8 >, 630
- Simd256\_impl< true, true, false, 2 >, 638, 641
- Simd256\_impl< true, true, false, 4 >, 650, 652,  
655
- Simd256\_impl< true, true, false, 8 >, 666, 669
- Simd256\_impl< true, true, true, 2 >, 676
- Simd256\_impl< true, true, true, 4 >, 687, 693
- Simd256\_impl< true, true, true, 8 >, 703
- Simd512\_impl< true, false, true, 8 >, 712
- Simd512\_impl< true, true, false, 8 >, 720, 722,  
723
- Simd512\_impl< true, true, true, 8 >, 731
- set1

- Simd128\_impl< true, true, false, 2 >, [571](#), [573](#)
- Simd128\_impl< true, true, false, 4 >, [581](#), [583](#)
- Simd128\_impl< true, true, false, 8 >, [591](#), [593](#)
- Simd128\_impl< true, true, true, 2 >, [601](#)
- Simd128\_impl< true, true, true, 4 >, [610](#)
- Simd128\_impl< true, true, true, 8 >, [619](#)
- Simd256\_impl< true, false, true, 8 >, [630](#)
- Simd256\_impl< true, true, false, 2 >, [638](#), [640](#)
- Simd256\_impl< true, true, false, 4 >, [650](#), [652](#), [655](#)
- Simd256\_impl< true, true, false, 8 >, [666](#), [669](#)
- Simd256\_impl< true, true, true, 2 >, [676](#)
- Simd256\_impl< true, true, true, 4 >, [687](#), [693](#)
- Simd256\_impl< true, true, true, 8 >, [703](#)
- Simd512\_impl< true, false, true, 8 >, [712](#)
- Simd512\_impl< true, true, false, 8 >, [719](#), [722](#)
- Simd512\_impl< true, true, true, 8 >, [730](#)
- set\_numthreads
  - Parallel< C, P >, [526](#)
- SET\_THREADS
  - parallel.h, [1040](#)
- setErrorStream
  - Failure, [449](#)
- setNorm
  - MMHelper< FFPACK::RNSInteger< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, [508](#)
  - MMHelper< FFPACK::RNSIntegerMod< E >, AlgoTrait, ModeCategories::DefaultTag, ParSeqTrait >, [510](#)
  - MMHelper< Field, AlgoTrait, ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeqTrait >, [514](#)
- setOutBounds
  - MMHelper< Field, AlgoTrait, ModeTrait, ParSeqTrait >, [505](#)
- sgemm\_
  - config-blas.h, [830](#)
- sgemv\_
  - config-blas.h, [827](#)
- sger\_
  - config-blas.h, [828](#)
- shuffle
  - Simd128\_impl< true, true, false, 2 >, [574](#)
  - Simd128\_impl< true, true, false, 4 >, [584](#)
  - Simd128\_impl< true, true, false, 8 >, [594](#)
  - Simd128\_impl< true, true, true, 2 >, [602](#)
  - Simd128\_impl< true, true, true, 4 >, [611](#)
  - Simd128\_impl< true, true, true, 8 >, [620](#)
  - Simd256\_impl< true, true, false, 2 >, [642](#)
  - Simd256\_impl< true, true, false, 4 >, [657](#)
  - Simd256\_impl< true, true, false, 8 >, [670](#)
  - Simd256\_impl< true, true, true, 2 >, [677](#)
  - Simd256\_impl< true, true, true, 4 >, [688](#), [695](#)
  - Simd256\_impl< true, true, true, 8 >, [704](#)
  - Simd512\_impl< true, false, true, 8 >, [713](#)
  - Simd512\_impl< true, true, false, 8 >, [724](#)
  - Simd512\_impl< true, true, true, 8 >, [732](#)
- shuffle\_twice
  - Simd256\_impl< true, true, false, 4 >, [657](#)
  - Simd256\_impl< true, true, true, 4 >, [688](#), [694](#)
- sigma
  - Sparse< \_Field, SparseMatrix\_t::SELL >, [757](#)
  - Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [760](#)
- signbits
  - Simd128\_impl< true, true, false, 8 >, [597](#)
  - Simd128\_impl< true, true, true, 8 >, [625](#)
  - Simd256\_impl< true, true, false, 8 >, [673](#)
  - Simd256\_impl< true, true, true, 8 >, [708](#)
  - Simd512\_impl< true, true, false, 8 >, [727](#)
  - Simd512\_impl< true, true, true, 8 >, [737](#)
- Simd
  - fflas\_simd.h, [880](#)
- simd
  - FieldSimd< \_Field >, [451](#)
- SIMD wrapper, [42](#)
- simd.dox, [880](#)
- Simd128
  - simd128.inl, [881](#)
- simd128.inl, [880](#)
  - \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd128\_INL, [880](#)
  - Simd128, [881](#)
- simd128\_double.inl, [881](#)
  - \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd128\_double\_INL, [881](#)
- simd128\_float.inl, [881](#)
  - \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd128\_float\_INL, [881](#)
- Simd128\_impl< ArithType, Int, Signed, Size >, [568](#)
- Simd128\_impl< true, false, true, 4 >, [568](#)
- Simd128\_impl< true, false, true, 8 >, [568](#)
- Simd128\_impl< true, true, false, 2 >, [568](#)
  - add, [576](#)
  - addin, [576](#)
  - aligned\_allocator, [570](#)
  - aligned\_vector, [570](#)
  - alignment, [578](#)
  - blend, [576](#)
  - compliant, [573](#)
  - eq, [577](#)
  - fmadd, [576](#)
  - fmaddin, [576](#)
  - fmaddx, [572](#)
  - fmaddxin, [572](#)
  - fmsub, [577](#)
  - fmsubin, [577](#)
  - fmsubx, [573](#)
  - fmsubxin, [573](#)
  - fmadd, [576](#)
  - fmaddin, [577](#)
  - fmaddx, [572](#)
  - fmaddxin, [573](#)
  - gather, [571](#), [574](#)
  - greater, [572](#)
  - greater\_eq, [572](#)

- hadd\_to\_scal, [573](#)
- is\_same\_element, [570](#)
- lesser, [572](#)
- lesser\_eq, [572](#)
- load, [571](#), [574](#)
- loadu, [571](#), [574](#)
- mod, [577](#)
- mul, [576](#)
- mulhi, [572](#)
- mullo, [576](#)
- mulx, [572](#)
- pack, [575](#)
- pack\_even, [575](#)
- pack\_odd, [575](#)
- round, [577](#)
- scalar\_t, [570](#)
- set, [571](#), [573](#)
- set1, [571](#), [573](#)
- shuffle, [574](#)
- sll, [574](#)
- sll128, [577](#)
- sra, [571](#)
- srl, [574](#)
- srl128, [577](#)
- store, [571](#), [574](#)
- storeu, [571](#), [574](#)
- stream, [571](#), [574](#)
- sub, [576](#)
- subin, [576](#)
- transpose, [575](#)
- type\_string, [571](#)
- unpackhi, [575](#)
- unpackhi\_intrinsic, [575](#)
- unpacklo, [575](#)
- unpacklo\_intrinsic, [574](#)
- unpacklohi, [575](#)
- valid, [573](#)
- vand, [578](#)
- vandnot, [578](#)
- vect\_size, [578](#)
- vect\_t, [570](#)
- vor, [578](#)
- vxor, [578](#)
- zero, [577](#)
- Simd128\_impl< true, true, false, 2 >::Converter, [429](#)
- t, [429](#)
- v, [429](#)
- Simd128\_impl< true, true, false, 4 >, [578](#)
- add, [585](#)
- addin, [586](#)
- aligned\_allocator, [580](#)
- aligned\_vector, [580](#)
- alignment, [588](#)
- blend, [585](#)
- compliant, [583](#)
- eq, [587](#)
- fmadd, [586](#)
- fmaddin, [586](#)
- fmaddx, [582](#)
- fmaddxin, [582](#)
- fmsub, [587](#)
- fmsubin, [587](#)
- fmsubx, [583](#)
- fmsubxin, [583](#)
- fnmadd, [586](#)
- fnmaddin, [586](#)
- fnmaddx, [582](#)
- fnmaddxin, [583](#)
- gather, [581](#), [583](#)
- greater, [582](#)
- greater\_eq, [582](#)
- hadd\_to\_scal, [583](#)
- is\_same\_element, [580](#)
- lesser, [582](#)
- lesser\_eq, [582](#)
- load, [581](#), [584](#)
- loadu, [581](#), [584](#)
- mod, [587](#)
- mul, [586](#)
- mulhi, [582](#)
- mullo, [586](#)
- mulx, [582](#)
- pack, [585](#)
- pack\_even, [585](#)
- pack\_odd, [585](#)
- round, [587](#)
- scalar\_t, [580](#)
- set, [581](#), [583](#)
- set1, [581](#), [583](#)
- shuffle, [584](#)
- sll, [584](#)
- sll128, [587](#)
- sra, [582](#)
- srl, [584](#)
- srl128, [587](#)
- store, [581](#), [584](#)
- storeu, [581](#), [584](#)
- stream, [581](#), [584](#)
- sub, [586](#)
- subin, [586](#)
- transpose, [585](#)
- type\_string, [581](#)
- unpackhi, [585](#)
- unpackhi\_intrinsic, [584](#)
- unpacklo, [585](#)
- unpacklo\_intrinsic, [584](#)
- unpacklohi, [585](#)
- valid, [583](#)
- vand, [587](#)
- vandnot, [588](#)
- vect\_size, [588](#)
- vect\_t, [581](#)
- vor, [588](#)
- vxor, [588](#)
- zero, [587](#)
- Simd128\_impl< true, true, false, 4 >::Converter, [429](#)



- t, [429](#)
- v, [429](#)
- Simd128\_impl< true, true, false, 8 >, [588](#)
  - add, [596](#)
  - addin, [596](#)
  - aligned\_allocator, [590](#)
  - aligned\_vector, [590](#)
  - alignment, [598](#)
  - blend, [595](#)
  - compliant, [593](#)
  - eq, [597](#)
  - fmadd, [596](#)
  - fmaddin, [596](#)
  - fmaddx, [592](#)
  - fmaddxin, [592](#)
  - fmsub, [597](#)
  - fmsubin, [597](#)
  - fmsubx, [593](#)
  - fmsubxin, [593](#)
  - fnmadd, [596](#)
  - fnmaddin, [596](#)
  - fnmaddx, [592](#)
  - fnmaddxin, [593](#)
  - gather, [591](#), [593](#)
  - get, [594](#)
  - greater, [592](#)
  - greater\_eq, [592](#)
  - hadd\_to\_scal, [593](#)
  - is\_same\_element, [590](#)
  - lesser, [592](#)
  - lesser\_eq, [592](#)
  - load, [591](#), [594](#)
  - loadu, [591](#), [594](#)
  - mask\_high, [597](#)
  - mod, [597](#)
  - mul, [596](#)
  - mulhi, [592](#)
  - mulhi\_fast, [597](#)
  - mullo, [592](#)
  - mulx, [592](#)
  - pack, [595](#)
  - pack\_even, [595](#)
  - pack\_odd, [595](#)
  - round, [597](#)
  - scalar\_t, [590](#)
  - set, [591](#), [593](#)
  - set1, [591](#), [593](#)
  - shuffle, [594](#)
  - signbits, [597](#)
  - sll, [594](#)
  - sll128, [598](#)
  - sra, [591](#)
  - srl, [594](#)
  - srl128, [598](#)
  - store, [591](#), [594](#)
  - storeu, [591](#), [594](#)
  - stream, [591](#), [594](#)
  - sub, [596](#)
  - subin, [596](#)
  - transpose, [595](#)
  - type\_string, [591](#)
  - unpackhi, [595](#)
  - unpackhi\_intrinsic, [595](#)
  - unpacklo, [595](#)
  - unpacklo\_intrinsic, [594](#)
  - unpacklohi, [595](#)
  - valid, [593](#)
  - vand, [598](#)
  - vandnot, [598](#)
  - vect\_size, [598](#)
  - vect\_t, [591](#)
  - vor, [598](#)
  - vxor, [598](#)
  - zero, [597](#)
- Simd128\_impl< true, true, false, 8 >::Converter, [429](#)
  - t, [429](#)
  - v, [429](#)
- Simd128\_impl< true, true, true, 2 >, [598](#)
  - add, [603](#)
  - addin, [604](#)
  - aligned\_allocator, [600](#)
  - aligned\_vector, [601](#)
  - alignment, [607](#)
  - blend, [603](#)
  - compliant, [601](#)
  - eq, [606](#)
  - fmadd, [604](#)
  - fmaddin, [604](#)
  - fmaddx, [604](#)
  - fmaddxin, [605](#)
  - fmsub, [605](#)
  - fmsubin, [605](#)
  - fmsubx, [605](#)
  - fmsubxin, [606](#)
  - fnmadd, [605](#)
  - fnmaddin, [605](#)
  - fnmaddx, [605](#)
  - fnmaddxin, [605](#)
  - gather, [601](#)
  - greater, [606](#)
  - greater\_eq, [606](#)
  - hadd\_to\_scal, [606](#)
  - is\_same\_element, [601](#)
  - lesser, [606](#)
  - lesser\_eq, [606](#)
  - load, [601](#)
  - loadu, [601](#)
  - mod, [606](#)
  - mul, [604](#)
  - mulhi, [604](#)
  - mullo, [604](#)
  - mulx, [604](#)
  - pack, [603](#)
  - pack\_even, [603](#)
  - pack\_odd, [603](#)
  - round, [606](#)



- scalar\_t, 600
- set, 601
- set1, 601
- shuffle, 602
- sll, 602
- sll128, 607
- sra, 602
- srl, 602
- srl128, 607
- store, 602
- storeu, 602
- stream, 602
- sub, 604
- subin, 604
- transpose, 603
- type\_string, 601
- unpackhi, 603
- unpackhi\_intrinsic, 602
- unpacklo, 602
- unpacklo\_intrinsic, 602
- unpacklohi, 603
- valid, 601
- vand, 607
- vandnot, 607
- vect\_size, 607
- vect\_t, 600
- vor, 607
- vxor, 607
- zero, 607
- Simd128\_impl< true, true, true, 2 >::Converter, 430
- t, 430
- v, 430
- Simd128\_impl< true, true, true, 4 >, 608
- add, 612
- addin, 612
- aligned\_allocator, 609
- aligned\_vector, 610
- alignment, 616
- blend, 612
- compliant, 610
- eq, 615
- fmadd, 613
- fmaddin, 613
- fmaddx, 613
- fmaddxin, 613
- fmsub, 614
- fmsubin, 614
- fmsubx, 614
- fmsubxin, 614
- fmadd, 614
- fmaddin, 614
- fmaddx, 614
- fmaddxin, 614
- gather, 610
- greater, 615
- greater\_eq, 615
- hadd\_to\_scal, 615
- is\_same\_element, 610
- lesser, 615
- lesser\_eq, 615
- load, 610
- loadu, 610
- mod, 615
- mul, 613
- mulhi, 613
- mullo, 613
- mulx, 613
- pack, 612
- pack\_even, 612
- pack\_odd, 612
- round, 615
- scalar\_t, 609
- set, 610
- set1, 610
- shuffle, 611
- sll, 611
- sll128, 615
- sra, 611
- srl, 611
- srl128, 616
- store, 610
- storeu, 611
- stream, 611
- sub, 612
- subin, 613
- transpose, 612
- type\_string, 610
- unpackhi, 611
- unpackhi\_intrinsic, 611
- unpacklo, 611
- unpacklo\_intrinsic, 611
- unpacklohi, 612
- valid, 610
- vand, 616
- vandnot, 616
- vect\_size, 616
- vect\_t, 609
- vor, 616
- vxor, 616
- zero, 615
- Simd128\_impl< true, true, true, 4 >::Converter, 430
- t, 430
- v, 430
- Simd128\_impl< true, true, true, 8 >, 616
- add, 621
- addin, 622
- aligned\_allocator, 619
- aligned\_vector, 619
- alignment, 626
- blend, 621
- compliant, 619
- eq, 624
- fmadd, 622
- fmaddin, 622
- fmaddx, 622
- fmaddxin, 623

fmsub, 623  
 fmubin, 623  
 fmsubx, 623  
 fmsubxin, 624  
 fnmadd, 623  
 fnmaddin, 623  
 fnmaddx, 623  
 fnmaddxin, 623  
 gather, 619  
 get, 619  
 greater, 624  
 greater\_eq, 624  
 hadd\_to\_scal, 624  
 is\_same\_element, 619  
 lesser, 624  
 lesser\_eq, 624  
 load, 619  
 loadu, 620  
 mask\_high, 624  
 mod, 624  
 mul, 622  
 mulhi, 622  
 mulhi\_fast, 624  
 mullo, 622  
 mulx, 622  
 pack, 621  
 pack\_even, 621  
 pack\_odd, 621  
 round, 624  
 scalar\_t, 618  
 set, 619  
 set1, 619  
 shuffle, 620  
 signbits, 625  
 sll, 620  
 sll128, 625  
 sra, 620  
 srl, 620  
 srl128, 625  
 store, 620  
 storeu, 620  
 stream, 620  
 sub, 622  
 subin, 622  
 transpose, 621  
 type\_string, 619  
 unpackhi, 621  
 unpackhi\_intrinsic, 620  
 unpacklo, 621  
 unpacklo\_intrinsic, 620  
 unpacklohi, 621  
 valid, 619  
 vand, 625  
 vandnot, 625  
 vect\_size, 626  
 vect\_t, 618  
 vor, 625  
 vxor, 625  
 zero, 625  
 Simd128\_impl< true, true, true, 8 >::Converter, 430  
 t, 430  
 v, 430  
 simd128\_int16.inl, 881  
 \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd128\_int16\_INL, 882  
 simd128\_int32.inl, 882  
 \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd128\_int32\_INL, 882  
 simd128\_int64.inl, 882  
 \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd128\_int64\_INL, 883  
 vect\_t, 883  
 Simd128i\_base, 626  
 sll128, 626  
 srl128, 626  
 vand, 627  
 vandnot, 627  
 vect\_t, 626  
 vor, 627  
 vxor, 627  
 zero, 626  
 Simd256  
 simd256.inl, 883  
 simd256.inl, 883  
 \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd256\_INL, 883  
 Simd256, 883  
 simd256\_double.inl, 883  
 \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd256\_double\_INL, 884  
 simd256\_float.inl, 884  
 \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd256\_float\_INL, 884  
 Simd256\_impl< ArithType, Int, Signed, Size >, 627  
 Simd256\_impl< true, false, true, 4 >, 627  
 Simd256\_impl< true, false, true, 8 >, 628  
 add, 632  
 addin, 632  
 aligned\_allocator, 629  
 aligned\_vector, 629  
 alignment, 635  
 blend, 632  
 blendv, 632  
 ceil, 634  
 compliant, 630  
 div, 632  
 eq, 633  
 floor, 634  
 fmadd, 633  
 fmaddin, 633  
 fmsub, 633  
 fmubin, 633  
 fnmadd, 633  
 fnmaddin, 633  
 gather, 630  
 greater, 634

- greater\_eq, [634](#)
- hadd, [634](#)
- hadd\_to\_scal, [635](#)
- is\_same\_element, [629](#)
- lesser, [633](#)
- lesser\_eq, [633](#)
- load, [630](#)
- loadu, [630](#)
- mod, [635](#)
- mul, [632](#)
- mulin, [632](#)
- pack, [631](#)
- pack\_even, [631](#)
- pack\_odd, [631](#)
- round, [634](#)
- scalar\_t, [629](#)
- set, [630](#)
- set1, [630](#)
- store, [630](#)
- storeu, [630](#)
- stream, [630](#)
- sub, [632](#)
- subin, [632](#)
- transpose, [631](#)
- type\_string, [629](#)
- unpackhi, [631](#)
- unpackhi\_intrinsic, [631](#)
- unpacklo, [631](#)
- unpacklo\_intrinsic, [631](#)
- unpacklohi, [631](#)
- valid, [629](#)
- vand, [634](#)
- vandnot, [634](#)
- vect\_size, [635](#)
- vect\_t, [629](#)
- vor, [634](#)
- vxor, [634](#)
- zero, [630](#)
- Simd256\_impl< true, false, true, 8 >::Converter, [431](#)
- t, [431](#)
- v, [431](#)
- Simd256\_impl< true, true, false, 2 >, [635](#)
- add, [643](#)
- addin, [643](#)
- aligned\_allocator, [637](#)
- aligned\_vector, [637](#)
- alignment, [645](#)
- blend, [643](#)
- compliant, [640](#)
- eq, [644](#)
- fmadd, [644](#)
- fmaddin, [644](#)
- fmaddx, [639](#)
- fmaddxin, [640](#)
- fmsub, [644](#)
- fmsubin, [644](#)
- fmsubx, [640](#)
- fmsubxin, [640](#)
- fnmadd, [644](#)
- fnmaddin, [644](#)
- fnmaddx, [640](#)
- fnmaddxin, [640](#)
- gather, [638](#), [641](#)
- greater, [639](#)
- greater\_eq, [639](#)
- hadd\_to\_scal, [640](#)
- half\_t, [638](#)
- is\_same\_element, [637](#)
- lesser, [639](#)
- lesser\_eq, [639](#)
- load, [638](#), [641](#)
- loadu, [638](#), [641](#)
- mod, [645](#)
- mul, [644](#)
- mulhi, [639](#)
- mullo, [644](#)
- mulx, [639](#)
- pack, [642](#)
- pack\_even, [642](#)
- pack\_odd, [642](#)
- round, [645](#)
- scalar\_t, [637](#)
- set, [638](#), [641](#)
- set1, [638](#), [640](#)
- shuffle, [642](#)
- simdHalf, [637](#)
- sll, [641](#)
- sra, [639](#)
- srl, [642](#)
- store, [638](#), [641](#)
- storeu, [639](#), [641](#)
- stream, [639](#), [641](#)
- sub, [643](#)
- subin, [643](#)
- transpose, [643](#)
- type\_string, [638](#)
- unpackhi, [642](#)
- unpackhi\_intrinsic, [642](#)
- unpacklo, [642](#)
- unpacklo\_intrinsic, [642](#)
- unpacklohi, [642](#)
- valid, [640](#)
- vect\_size, [645](#)
- vect\_t, [638](#)
- zero, [645](#)
- Simd256\_impl< true, true, false, 2 >::Converter, [431](#)
- t, [431](#)
- v, [431](#)
- Simd256\_impl< true, true, false, 4 >, [645](#)
- add, [660](#)
- addin, [660](#)
- aligned\_allocator, [649](#)
- aligned\_vector, [649](#)
- alignment, [664](#)
- blend, [659](#)
- compliant, [655](#)

eq, [662](#)  
 fmadd, [661](#)  
 fmaddin, [661](#)  
 fmaddx, [651](#), [654](#)  
 fmaddxin, [651](#), [654](#)  
 fmsub, [662](#)  
 fmsubin, [662](#)  
 fmsubx, [652](#), [654](#)  
 fmsubxin, [652](#), [654](#)  
 fnmadd, [661](#)  
 fnmaddin, [661](#), [662](#)  
 fnmaddx, [652](#), [654](#)  
 fnmaddxin, [652](#), [654](#)  
 gather, [650](#), [652](#), [656](#)  
 greater, [651](#), [653](#)  
 greater\_eq, [651](#), [653](#)  
 hadd\_to\_scal, [652](#), [654](#)  
 half\_t, [650](#)  
 is\_same\_element, [649](#)  
 lesser, [651](#), [653](#)  
 lesser\_eq, [651](#), [653](#)  
 load, [650](#), [653](#), [656](#)  
 loadu, [650](#), [653](#), [656](#)  
 mod, [663](#)  
 mul, [661](#)  
 mulhi, [651](#), [654](#)  
 mullo, [660](#)  
 mulx, [651](#), [654](#)  
 pack, [658](#), [659](#)  
 pack\_even, [658](#)  
 pack\_odd, [658](#)  
 round, [662](#)  
 scalar\_t, [649](#)  
 set, [650](#), [652](#), [655](#)  
 set1, [650](#), [652](#), [655](#)  
 shuffle, [657](#)  
 shuffle\_twice, [657](#)  
 simdHalf, [649](#)  
 sll, [656](#)  
 sra, [651](#), [653](#)  
 srl, [656](#)  
 store, [650](#), [653](#), [656](#)  
 storeu, [650](#), [653](#), [656](#)  
 stream, [651](#), [653](#), [656](#)  
 sub, [660](#)  
 subin, [660](#)  
 transpose, [659](#)  
 type\_string, [650](#), [652](#)  
 unpackhi, [658](#)  
 unpackhi\_intrinsic, [657](#)  
 unpacklo, [657](#)  
 unpacklo\_intrinsic, [657](#)  
 unpacklohi, [658](#)  
 valid, [655](#)  
 vand, [663](#)  
 vandnot, [663](#)  
 vect\_size, [664](#)  
 vect\_t, [649](#)  
 vor, [663](#)  
 vxor, [663](#)  
 zero, [663](#)  
 Simd256\_impl< true, true, false, 4 >::Converter, [431](#)  
 t, [431](#)  
 v, [431](#)  
 Simd256\_impl< true, true, false, 8 >, [664](#)  
 add, [671](#)  
 addin, [671](#)  
 aligned\_allocator, [666](#)  
 aligned\_vector, [666](#)  
 alignment, [673](#)  
 blend, [671](#)  
 compliant, [669](#)  
 eq, [672](#)  
 fmadd, [672](#)  
 fmaddin, [672](#)  
 fmaddx, [668](#)  
 fmaddxin, [668](#)  
 fmsub, [672](#)  
 fmsubin, [672](#)  
 fmsubx, [668](#)  
 fmsubxin, [669](#)  
 fnmadd, [672](#)  
 fnmaddin, [672](#)  
 fnmaddx, [668](#)  
 fnmaddxin, [668](#)  
 gather, [667](#), [669](#)  
 get, [669](#)  
 greater, [667](#)  
 greater\_eq, [667](#)  
 hadd\_to\_scal, [669](#)  
 half\_t, [666](#)  
 is\_same\_element, [666](#)  
 lesser, [667](#)  
 lesser\_eq, [668](#)  
 load, [667](#), [669](#)  
 loadu, [667](#), [669](#)  
 mask\_high, [673](#)  
 mod, [673](#)  
 mul, [672](#)  
 mulhi, [668](#)  
 mulhi\_fast, [673](#)  
 mullo, [668](#)  
 mulx, [668](#)  
 pack, [671](#)  
 pack\_even, [671](#)  
 pack\_odd, [671](#)  
 round, [673](#)  
 scalar\_t, [666](#)  
 set, [666](#), [669](#)  
 set1, [666](#), [669](#)  
 shuffle, [670](#)  
 signbits, [673](#)  
 simdHalf, [666](#)  
 sll, [670](#)  
 sra, [667](#)  
 srl, [670](#)

- store, [667](#), [670](#)
- storeu, [667](#), [670](#)
- stream, [667](#), [670](#)
- sub, [671](#)
- subin, [672](#)
- transpose, [671](#)
- type\_string, [666](#)
- unpackhi, [670](#)
- unpackhi\_intrinsic, [670](#)
- unpacklo, [670](#)
- unpacklo\_intrinsic, [670](#)
- unpacklohi, [671](#)
- valid, [669](#)
- vect\_size, [673](#)
- vect\_t, [666](#)
- zero, [673](#)
- Simd256\_impl< true, true, false, 8 >::Converter, [432](#)
- t, [432](#)
- v, [432](#)
- Simd256\_impl< true, true, true, 2 >, [674](#)
- add, [679](#)
- addin, [679](#)
- aligned\_allocator, [676](#)
- aligned\_vector, [676](#)
- alignment, [682](#)
- blend, [679](#)
- compliant, [676](#)
- eq, [681](#)
- fmadd, [680](#)
- fmaddin, [680](#)
- fmaddx, [680](#)
- fmaddxin, [680](#)
- fmsub, [681](#)
- fmsubin, [681](#)
- fmsubx, [681](#)
- fmsubxin, [681](#)
- fnmadd, [680](#)
- fnmaddin, [680](#)
- fnmaddx, [681](#)
- fnmaddxin, [681](#)
- gather, [677](#)
- greater, [681](#)
- greater\_eq, [682](#)
- hadd\_to\_scal, [682](#)
- half\_t, [675](#)
- is\_same\_element, [676](#)
- lesser, [681](#)
- lesser\_eq, [682](#)
- load, [677](#)
- loadu, [677](#)
- mod, [682](#)
- mul, [680](#)
- mulhi, [680](#)
- mullo, [679](#)
- mulx, [680](#)
- pack, [678](#)
- pack\_even, [678](#)
- pack\_odd, [678](#)
- round, [682](#)
- scalar\_t, [675](#)
- set, [676](#)
- set1, [676](#)
- shuffle, [677](#)
- simdHalf, [676](#)
- sll, [677](#)
- sra, [677](#)
- srl, [677](#)
- store, [677](#)
- storeu, [677](#)
- stream, [677](#)
- sub, [679](#)
- subin, [679](#)
- transpose, [678](#)
- type\_string, [676](#)
- unpackhi, [678](#)
- unpackhi\_intrinsic, [678](#)
- unpacklo, [678](#)
- unpacklo\_intrinsic, [678](#)
- unpacklohi, [678](#)
- valid, [676](#)
- vect\_size, [682](#)
- vect\_t, [675](#)
- zero, [682](#)
- Simd256\_impl< true, true, true, 2 >::Converter, [432](#)
- t, [432](#)
- v, [432](#)
- Simd256\_impl< true, true, true, 4 >, [683](#)
- add, [690](#), [696](#)
- addin, [690](#), [696](#)
- aligned\_allocator, [686](#), [687](#)
- aligned\_vector, [686](#), [687](#)
- alignment, [700](#)
- blend, [690](#), [696](#)
- compliant, [687](#), [693](#)
- eq, [692](#), [698](#)
- fmadd, [691](#), [697](#)
- fmaddin, [691](#), [697](#)
- fmaddx, [691](#), [697](#)
- fmaddxin, [691](#), [697](#)
- fmsub, [692](#), [698](#)
- fmsubin, [692](#), [698](#)
- fmsubx, [692](#), [698](#)
- fmsubxin, [692](#), [698](#)
- fnmadd, [691](#), [697](#)
- fnmaddin, [691](#), [697](#)
- fnmaddx, [691](#), [698](#)
- fnmaddxin, [691](#), [698](#)
- gather, [687](#), [694](#)
- greater, [692](#), [698](#)
- greater\_eq, [692](#), [699](#)
- hadd\_to\_scal, [692](#), [699](#)
- half\_t, [686](#)
- is\_same\_element, [686](#), [687](#)
- lesser, [692](#), [698](#)
- lesser\_eq, [692](#), [699](#)
- load, [688](#), [694](#)

- loadu, [688](#), [694](#)
- mod, [693](#), [699](#)
- mul, [690](#), [697](#)
- mulhi, [690](#), [697](#)
- mullo, [690](#), [696](#)
- mulx, [690](#), [697](#)
- pack, [689](#), [695](#)
- pack\_even, [689](#), [695](#)
- pack\_odd, [689](#), [695](#)
- round, [693](#), [699](#)
- scalar\_t, [686](#)
- set, [687](#), [693](#)
- set1, [687](#), [693](#)
- shuffle, [688](#), [695](#)
- shuffle\_twice, [688](#), [694](#)
- simdHalf, [686](#), [687](#)
- sll, [688](#), [694](#)
- sra, [688](#), [694](#)
- srl, [688](#), [694](#)
- store, [688](#), [694](#)
- storeu, [688](#), [694](#)
- stream, [688](#), [694](#)
- sub, [690](#), [696](#)
- subin, [690](#), [696](#)
- transpose, [689](#), [696](#)
- type\_string, [687](#), [693](#)
- unpackhi, [689](#), [695](#)
- unpackhi\_intrinsic, [689](#), [695](#)
- unpacklo, [689](#), [695](#)
- unpacklo\_intrinsic, [689](#), [695](#)
- unpacklohi, [689](#), [695](#)
- valid, [687](#), [693](#)
- vand, [699](#)
- vandnot, [700](#)
- vect\_size, [700](#)
- vect\_t, [686](#)
- vor, [699](#)
- vxor, [699](#)
- zero, [699](#)
- Simd256\_impl< true, true, true, 4 >::Converter, [432](#)
- t, [432](#)
- v, [432](#)
- Simd256\_impl< true, true, true, 8 >, [700](#)
- add, [705](#)
- addin, [705](#)
- aligned\_allocator, [702](#)
- aligned\_vector, [702](#)
- alignment, [709](#)
- blend, [705](#)
- compliant, [703](#)
- eq, [707](#)
- fmadd, [706](#)
- fmaddin, [706](#)
- fmaddx, [706](#)
- fmaddxin, [706](#)
- fmsub, [707](#)
- fmsubin, [707](#)
- fmsubx, [707](#)
- fmsubxin, [707](#)
- fnmadd, [706](#)
- fnmaddin, [706](#)
- fnmaddx, [707](#)
- fnmaddxin, [707](#)
- gather, [703](#)
- get, [703](#)
- greater, [707](#)
- greater\_eq, [708](#)
- hadd\_to\_scal, [708](#)
- half\_t, [702](#)
- is\_same\_element, [702](#)
- lesser, [707](#)
- lesser\_eq, [708](#)
- load, [703](#)
- loadu, [703](#)
- mask\_high, [708](#)
- mod, [708](#)
- mul, [706](#)
- mulhi, [706](#)
- mulhi\_fast, [708](#)
- mullo, [705](#)
- mulx, [706](#)
- pack, [705](#)
- pack\_even, [704](#)
- pack\_odd, [705](#)
- round, [708](#)
- scalar\_t, [702](#)
- set, [703](#)
- set1, [703](#)
- shuffle, [704](#)
- signbits, [708](#)
- simdHalf, [702](#)
- sll, [704](#)
- sra, [704](#)
- srl, [704](#)
- store, [703](#)
- storeu, [703](#)
- stream, [703](#)
- sub, [705](#)
- subin, [705](#)
- transpose, [705](#)
- type\_string, [702](#)
- unpackhi, [704](#)
- unpackhi\_intrinsic, [704](#)
- unpacklo, [704](#)
- unpacklo\_intrinsic, [704](#)
- unpacklohi, [704](#)
- valid, [702](#)
- vect\_size, [709](#)
- vect\_t, [702](#)
- zero, [708](#)
- Simd256\_impl< true, true, true, 8 >::Converter, [433](#)
- t, [433](#)
- v, [433](#)
- simd256\_int16.inl, [884](#)
- \_\_FflasFfpack\_fflas\_ffpack\_utils\_simd256\_int16\_INL, [885](#)

- simd256\_int32.inl, [885](#)
  - \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd256\_int32\_INL, [885](#)
- simd256\_int64.inl, [885](#)
  - \_\_FFLASFFPACK\_fflas\_ffpack\_utils\_simd256\_int64\_INL, [885](#)
  - vect\_t, [885](#)
- Simd256fp\_base, [709](#)
- Simd256i\_base, [709](#)
  - vect\_t, [709](#)
  - zero, [709](#)
- Simd512
  - simd512.inl, [886](#)
- simd512.inl, [886](#)
  - \_\_FFLASFFPACK\_simd512\_INL, [886](#)
  - Simd512, [886](#)
- simd512\_double.inl, [886](#)
  - \_\_FFLASFFPACK\_simd512\_double\_INL, [886](#)
- simd512\_float.inl, [887](#)
  - \_\_FFLASFFPACK\_simd512\_float\_INL, [887](#)
- Simd512\_impl< ArithType, Int, Signed, Size >, [710](#)
- Simd512\_impl< true, false, true, 4 >, [710](#)
- Simd512\_impl< true, false, true, 8 >, [710](#)
  - add, [714](#)
  - addin, [714](#)
  - aligned\_allocator, [711](#)
  - aligned\_vector, [711](#)
  - alignment, [716](#)
  - blend, [714](#)
  - blendv, [714](#)
  - ceil, [716](#)
  - compliant, [712](#)
  - div, [715](#)
  - eq, [715](#)
  - floor, [716](#)
  - fmadd, [715](#)
  - fmaddin, [715](#)
  - fmsub, [715](#)
  - fmsubin, [715](#)
  - fnmadd, [715](#)
  - fnmaddin, [715](#)
  - gather, [712](#)
  - greater, [716](#)
  - greater\_eq, [716](#)
  - hadd, [716](#)
  - hadd\_to\_scal, [716](#)
  - is\_same\_element, [711](#)
  - lesser, [716](#)
  - lesser\_eq, [716](#)
  - load, [712](#)
  - loadu, [712](#)
  - mul, [714](#)
  - mulin, [715](#)
  - pack, [713](#)
  - pack\_even, [713](#)
  - pack\_odd, [713](#)
  - round, [716](#)
  - scalar\_t, [711](#)
  - set, [712](#)
  - set1, [712](#)
  - shuffle, [713](#)
  - store, [712](#)
  - storeu, [712](#)
  - stream, [712](#)
  - sub, [714](#)
  - subin, [714](#)
  - transpose, [714](#)
  - type\_string, [711](#)
  - unpackhi, [713](#)
  - unpackhi\_intrinsic, [713](#)
  - unpacklo, [713](#)
  - unpacklo\_intrinsic, [713](#)
  - unpacklohi, [713](#)
  - valid, [711](#)
  - vect\_size, [716](#)
  - vect\_t, [711](#)
  - zero, [712](#)
- Simd512\_impl< true, true, false, 8 >, [717](#)
  - add, [725](#)
  - addin, [725](#)
  - aligned\_allocator, [719](#)
  - aligned\_vector, [719](#)
  - alignment, [727](#)
  - blend, [725](#)
  - compliant, [722](#)
  - eq, [726](#)
  - fmadd, [725](#)
  - fmaddin, [726](#)
  - fmaddx, [721](#)
  - fmaddxin, [721](#)
  - fmsub, [726](#)
  - fmsubin, [726](#)
  - fmsubx, [722](#)
  - fmsubxin, [722](#)
  - fnmadd, [726](#)
  - fnmaddin, [726](#)
  - fnmaddx, [721](#)
  - fnmaddxin, [722](#)
  - gather, [720](#), [723](#)
  - greater, [721](#)
  - greater\_eq, [721](#)
  - hadd\_to\_scal, [722](#)
  - half\_t, [719](#)
  - is\_same\_element, [719](#)
  - lesser, [721](#)
  - lesser\_eq, [721](#)
  - load, [720](#), [723](#)
  - loadu, [720](#), [723](#)
  - mask\_high, [726](#)
  - maskstore, [720](#), [723](#)
  - mod, [727](#)
  - mul, [725](#)
  - mulhi, [721](#)
  - mulhi\_fast, [726](#)
  - mullo, [721](#)
  - mulx, [721](#)

- pack, [724](#)
- pack\_even, [724](#)
- pack\_odd, [724](#)
- round, [726](#)
- scalar\_t, [719](#)
- set, [720](#), [722](#), [723](#)
- set1, [719](#), [722](#)
- shuffle, [724](#)
- signbits, [727](#)
- simdHalf, [719](#)
- sll, [723](#)
- sra, [720](#)
- srl, [723](#)
- store, [720](#), [723](#)
- storeu, [720](#), [723](#)
- stream, [720](#), [723](#)
- sub, [725](#)
- subin, [725](#)
- transpose, [725](#)
- type\_string, [719](#)
- unpackhi, [724](#)
- unpackhi\_intrinsic, [724](#)
- unpacklo, [724](#)
- unpacklo\_intrinsic, [724](#)
- unpacklohi, [724](#)
- valid, [722](#)
- vand, [727](#)
- vandnot, [727](#)
- vect\_size, [727](#)
- vect\_t, [719](#)
- vor, [727](#)
- vxor, [727](#)
- zero, [727](#)
- Simd512\_impl< true, true, false, 8 >::Converter, [433](#)
- t, [433](#)
- v, [433](#)
- Simd512\_impl< true, true, true, 8 >, [728](#)
- add, [733](#)
- addin, [733](#)
- aligned\_allocator, [730](#)
- aligned\_vector, [730](#)
- alignment, [737](#)
- blend, [733](#)
- compliant, [730](#)
- eq, [735](#)
- fmadd, [734](#)
- fmaddin, [734](#)
- fmaddx, [734](#)
- fmaddxin, [734](#)
- fmsub, [735](#)
- fmsubin, [735](#)
- fmsubx, [735](#)
- fmsubxin, [735](#)
- fnmadd, [734](#)
- fnmaddin, [735](#)
- fnmaddx, [735](#)
- fnmaddxin, [735](#)
- gather, [731](#)
- greater, [736](#)
- greater\_eq, [736](#)
- hadd\_to\_scal, [736](#)
- half\_t, [730](#)
- is\_same\_element, [730](#)
- lesser, [736](#)
- lesser\_eq, [736](#)
- load, [731](#)
- loadu, [731](#)
- mask\_high, [736](#)
- maskstore, [731](#)
- mod, [736](#)
- mul, [734](#)
- mulhi, [734](#)
- mulhi\_fast, [736](#)
- mullo, [734](#)
- mulx, [734](#)
- pack, [733](#)
- pack\_even, [732](#)
- pack\_odd, [733](#)
- round, [736](#)
- scalar\_t, [730](#)
- set, [731](#)
- set1, [730](#)
- shuffle, [732](#)
- signbits, [737](#)
- simdHalf, [730](#)
- sll, [732](#)
- sra, [732](#)
- srl, [732](#)
- store, [731](#)
- storeu, [731](#)
- stream, [731](#)
- sub, [733](#)
- subin, [733](#)
- transpose, [733](#)
- type\_string, [730](#)
- unpackhi, [732](#)
- unpackhi\_intrinsic, [732](#)
- unpacklo, [732](#)
- unpacklo\_intrinsic, [732](#)
- unpacklohi, [732](#)
- valid, [730](#)
- vand, [737](#)
- vandnot, [737](#)
- vect\_size, [737](#)
- vect\_t, [730](#)
- vor, [737](#)
- vxor, [737](#)
- zero, [737](#)
- Simd512\_impl< true, true, true, 8 >::Converter, [433](#)
- t, [433](#)
- v, [433](#)
- simd512\_int32.inl, [887](#)
- \_\_FFLASFFPACK\_simd512\_int32\_INL, [887](#)
- simd512\_int64.inl, [887](#)
- \_simd512\_int64\_INL, [888](#)
- vect\_t, [888](#)



- Simd512i\_base, [737](#)
  - vand, [738](#)
  - vandnot, [738](#)
  - vect\_t, [738](#)
  - vor, [738](#)
  - vxor, [738](#)
  - zero, [738](#)
- SIMD\_INT
  - fflas\_simd.h, [879](#)
- simd\_modular.inl, [888](#)
- SimdChooser< T, bool, bool >, [739](#)
- SimdChooser< T, false, b >, [739](#)
  - value, [739](#)
- SimdChooser< T, true, false >, [739](#)
  - value, [739](#)
- SimdChooser< T, true, true >, [739](#)
  - value, [739](#)
- simdHalf
  - Simd256\_impl< true, true, false, 2 >, [637](#)
  - Simd256\_impl< true, true, false, 4 >, [649](#)
  - Simd256\_impl< true, true, false, 8 >, [666](#)
  - Simd256\_impl< true, true, true, 2 >, [676](#)
  - Simd256\_impl< true, true, true, 4 >, [686](#), [687](#)
  - Simd256\_impl< true, true, true, 8 >, [702](#)
  - Simd512\_impl< true, true, false, 8 >, [719](#)
  - Simd512\_impl< true, true, true, 8 >, [730](#)
- SimdSparseMatrix
  - FFLAS, [72](#)
- simdToType< T >, [740](#)
- Single, [740](#)
- size
  - BlockTransposeSIMD< Field, Simd, >, [413](#)
  - Info, [483](#), [484](#)
  - RNSInteger< RNS >, [547](#)
  - RNSIntegerMod< RNS >, [551](#)
- SIZEOF\_\_\_INT64\_T
  - config.h, [812](#)
- SIZEOF\_CHAR
  - config.h, [811](#)
- SIZEOF\_INT
  - config.h, [811](#)
- SIZEOF\_LONG
  - config.h, [812](#)
- SIZEOF\_LONG\_LONG
  - config.h, [812](#)
- SIZEOF\_SHORT
  - config.h, [812](#)
- sll
  - ScalFunctionsBase< Element, typename enable\_if< is\_integral< Element >::value >::type >, [566](#)
  - Simd128\_impl< true, true, false, 2 >, [574](#)
  - Simd128\_impl< true, true, false, 4 >, [584](#)
  - Simd128\_impl< true, true, false, 8 >, [594](#)
  - Simd128\_impl< true, true, true, 2 >, [602](#)
  - Simd128\_impl< true, true, true, 4 >, [611](#)
  - Simd128\_impl< true, true, true, 8 >, [620](#)
  - Simd256\_impl< true, true, false, 2 >, [641](#)
  - Simd256\_impl< true, true, false, 4 >, [656](#)
  - Simd256\_impl< true, true, false, 8 >, [670](#)
  - Simd256\_impl< true, true, true, 2 >, [677](#)
  - Simd256\_impl< true, true, true, 4 >, [688](#), [694](#)
  - Simd256\_impl< true, true, true, 8 >, [704](#)
  - Simd512\_impl< true, true, false, 8 >, [723](#)
  - Simd512\_impl< true, true, true, 8 >, [732](#)
- sll128
  - Simd128\_impl< true, true, false, 2 >, [577](#)
  - Simd128\_impl< true, true, false, 4 >, [587](#)
  - Simd128\_impl< true, true, false, 8 >, [598](#)
  - Simd128\_impl< true, true, true, 2 >, [607](#)
  - Simd128\_impl< true, true, true, 4 >, [615](#)
  - Simd128\_impl< true, true, true, 8 >, [625](#)
  - Simd128i\_base, [626](#)
- Solve
  - FFPACK, [333](#), [377](#)
- solve.C, [819](#)
  - main, [819](#)
- Solve\_modular\_double
  - ffpack.C, [1006](#)
  - ffpack\_c.h, [1025](#)
- solveLB
  - FFPACK, [353](#), [377](#)
- solveLB2
  - FFPACK, [353](#), [377](#)
- solveLB2\_modular\_double
  - ffpack.C, [1006](#)
  - ffpack\_c.h, [1026](#)
- solveLB\_modular\_double
  - ffpack.C, [1006](#)
  - ffpack\_c.h, [1026](#)
- Sparse< \_Field, SparseMatrix\_t::COO >, [740](#)
  - col, [741](#)
  - dat, [741](#)
  - delayed, [741](#)
  - Field, [740](#)
  - kmax, [741](#)
  - m, [741](#)
  - maxrow, [741](#)
  - n, [741](#)
  - nElements, [741](#)
  - nnz, [741](#)
  - row, [741](#)
- Sparse< \_Field, SparseMatrix\_t::COO\_ZO >, [741](#)
  - col, [742](#)
  - cst, [742](#)
  - dat, [742](#)
  - delayed, [742](#)
  - Field, [742](#)
  - kmax, [742](#)
  - m, [743](#)
  - maxrow, [743](#)
  - n, [743](#)
  - nElements, [743](#)
  - nnz, [743](#)
  - row, [742](#)
- Sparse< \_Field, SparseMatrix\_t::CSR >, [743](#)
  - col, [744](#)

- dat, [745](#)
- delayed, [744](#)
- Field, [744](#)
- kmax, [744](#)
- m, [744](#)
- maxrow, [744](#)
- n, [744](#)
- nElements, [744](#)
- nnz, [744](#)
- st, [744](#)
- stend, [744](#)
- Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, [745](#)
  - col, [745](#)
  - dat, [746](#)
  - delayed, [745](#)
  - Field, [745](#)
  - kmax, [746](#)
  - m, [746](#)
  - maxrow, [746](#)
  - n, [746](#)
  - nElements, [746](#)
  - nMOnes, [746](#)
  - nnz, [746](#)
  - nOnes, [746](#)
  - nOthers, [746](#)
  - st, [745](#)
- Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, [747](#)
  - col, [748](#)
  - cst, [747](#)
  - dat, [748](#)
  - delayed, [747](#)
  - Field, [747](#)
  - kmax, [747](#)
  - m, [747](#)
  - maxrow, [748](#)
  - n, [747](#)
  - nElements, [748](#)
  - nnz, [748](#)
  - st, [748](#)
  - stend, [748](#)
- Sparse< \_Field, SparseMatrix\_t::ELL >, [748](#)
  - col, [749](#)
  - dat, [750](#)
  - delayed, [749](#)
  - Field, [749](#)
  - kmax, [749](#)
  - ld, [749](#)
  - m, [749](#)
  - maxrow, [749](#)
  - n, [749](#)
  - nElements, [749](#)
  - nnz, [749](#)
- Sparse< \_Field, SparseMatrix\_t::ELL\_simd >, [750](#)
  - chunk, [750](#)
  - col, [751](#)
  - dat, [751](#)
  - delayed, [750](#)
  - kmax, [751](#)
  - ld, [751](#)
  - m, [750](#)
  - maxrow, [751](#)
  - n, [750](#)
  - nChunks, [751](#)
  - nElements, [751](#)
  - nnz, [751](#)
- Sparse< \_Field, SparseMatrix\_t::ELL\_simd\_ZO >, [751](#)
  - chunk, [752](#)
  - col, [753](#)
  - cst, [752](#)
  - dat, [753](#)
  - delayed, [752](#)
  - kmax, [752](#)
  - ld, [752](#)
  - m, [752](#)
  - maxrow, [753](#)
  - n, [752](#)
  - nChunks, [753](#)
  - nElements, [752](#)
  - nnz, [752](#)
- Sparse< \_Field, SparseMatrix\_t::ELL\_ZO >, [753](#)
  - col, [754](#)
  - cst, [754](#)
  - dat, [754](#)
  - delayed, [754](#)
  - Field, [754](#)
  - kmax, [754](#)
  - ld, [754](#)
  - m, [754](#)
  - maxrow, [754](#)
  - n, [754](#)
  - nElements, [754](#)
  - nnz, [754](#)
- Sparse< \_Field, SparseMatrix\_t::HYB\_ZO >, [755](#)
  - dat, [756](#)
  - delayed, [755](#)
  - Field, [755](#)
  - kmax, [755](#)
  - m, [755](#)
  - maxrow, [756](#)
  - mone, [756](#)
  - n, [755](#)
  - nElements, [756](#)
  - nnz, [756](#)
  - one, [756](#)
  - Self\_t, [755](#)
- Sparse< \_Field, SparseMatrix\_t::SELL >, [756](#)
  - chunk, [757](#)
  - chunkSize, [758](#)
  - col, [758](#)
  - dat, [758](#)
  - delayed, [757](#)
  - Field, [757](#)
  - kmax, [757](#)
  - m, [757](#)
  - maxrow, [757](#)
  - n, [757](#)

- nChunks, [758](#)
- nElements, [758](#)
- nnz, [758](#)
- perm, [758](#)
- sigma, [757](#)
- st, [758](#)
- Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [758](#)
  - chunk, [759](#)
  - chunkSize, [760](#)
  - col, [760](#)
  - cst, [759](#)
  - dat, [760](#)
  - delayed, [759](#)
  - Field, [759](#)
  - kmax, [759](#)
  - m, [759](#)
  - maxrow, [760](#)
  - n, [759](#)
  - nChunks, [760](#)
  - nElements, [760](#)
  - nnz, [760](#)
  - perm, [760](#)
  - sigma, [760](#)
  - st, [760](#)
- Sparse< Field, SparseMatrix\_t, IdxT, PtrT >, [740](#)
- sparse\_delete
  - FFLAS, [148–152](#), [155](#)
- sparse\_init
  - FFLAS, [148–153](#), [155](#)
- sparse\_matrix\_traits.h, [918](#)
- sparse\_print
  - FFLAS, [149](#), [152](#), [155](#)
- SparseMatrix\_t
  - FFLAS, [76](#)
- SpecRankProfile
  - FFPACK, [376](#)
- SpecRankProfile\_modular\_double
  - ffpack.C, [1005](#)
  - ffpack\_c.h, [1025](#)
- splitt
  - parallel.h, [1044](#)
- SPLITTER
  - parallel.h, [1044](#)
- splitting\_0
  - parallel.h, [1044](#)
- splitting\_1
  - parallel.h, [1044](#)
- splitting\_2
  - parallel.h, [1044](#)
- splitting\_3
  - parallel.h, [1044](#)
- SpMat< Field, flag >, [760](#)
  - \_coo, [761](#)
  - \_csr, [761](#)
  - \_ell, [761](#)
- square\_inplace
  - FFLAS::\_ftranspose\_impl, [194](#)
- sra
  - ScalFunctionsBase< Element, typename enable\_if<
    - is\_integral< Element >::value >::type >, [566](#)
 Simd128\_impl< true, true, false, 2 >, [571](#)
 Simd128\_impl< true, true, false, 4 >, [582](#)
 Simd128\_impl< true, true, false, 8 >, [591](#)
 Simd128\_impl< true, true, true, 2 >, [602](#)
 Simd128\_impl< true, true, true, 4 >, [611](#)
 Simd128\_impl< true, true, true, 8 >, [620](#)
 Simd256\_impl< true, true, false, 2 >, [639](#)
 Simd256\_impl< true, true, false, 4 >, [651](#), [653](#)
 Simd256\_impl< true, true, false, 8 >, [667](#)
 Simd256\_impl< true, true, true, 2 >, [677](#)
 Simd256\_impl< true, true, true, 4 >, [688](#), [694](#)
 Simd256\_impl< true, true, true, 8 >, [704](#)
 Simd512\_impl< true, true, false, 8 >, [720](#)
 Simd512\_impl< true, true, true, 8 >, [732](#)
 >, [566](#)
 Simd128\_impl< true, true, false, 2 >, [574](#)
 Simd128\_impl< true, true, false, 4 >, [584](#)
 Simd128\_impl< true, true, false, 8 >, [594](#)
 Simd128\_impl< true, true, true, 2 >, [602](#)
 Simd128\_impl< true, true, true, 4 >, [611](#)
 Simd128\_impl< true, true, true, 8 >, [620](#)
 Simd256\_impl< true, true, false, 2 >, [642](#)
 Simd256\_impl< true, true, false, 4 >, [656](#)
 Simd256\_impl< true, true, false, 8 >, [670](#)
 Simd256\_impl< true, true, true, 2 >, [677](#)
 Simd256\_impl< true, true, true, 4 >, [688](#), [694](#)
 Simd256\_impl< true, true, true, 8 >, [704](#)
 Simd512\_impl< true, true, false, 8 >, [723](#)
 Simd512\_impl< true, true, true, 8 >, [732](#)
 >, [566](#)
 Simd128\_impl< true, true, false, 2 >, [577](#)
 Simd128\_impl< true, true, false, 4 >, [587](#)
 Simd128\_impl< true, true, false, 8 >, [598](#)
 Simd128\_impl< true, true, true, 2 >, [607](#)
 Simd128\_impl< true, true, true, 4 >, [616](#)
 Simd128\_impl< true, true, true, 8 >, [625](#)
 Simd128i\_base, [626](#)
 >, [566](#)
 config-blas.h, [829](#)
 >, [566](#)
 fflas\_transpose.h, [921](#)
 Sparse< \_Field, SparseMatrix\_t::CSR >, [744](#)
 Sparse< \_Field, SparseMatrix\_t::CSR\_HYB >, [745](#)
 Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, [748](#)
 Sparse< \_Field, SparseMatrix\_t::SELL >, [758](#)
 Sparse< \_Field, SparseMatrix\_t::SELL\_ZO >, [760](#)
 StatsMatrix, [761](#)
 averageCol, [762](#)
 averageColDifference, [763](#)
 averageRow, [762](#)
 averageRowDifference, [763](#)
 coldim, [762](#)

- denseCols, 763
- denseRows, 763
- deviationCol, 762
- deviationColDifference, 763
- deviationRow, 762
- deviationRowDifference, 763
- maxCol, 762
- maxColDifference, 763
- maxRow, 762
- maxRowDifference, 763
- minCol, 762
- minColDifference, 763
- minRow, 762
- minRowDifference, 763
- nDenseCols, 763
- nDenseRows, 763
- nEmptyCols, 763
- nEmptyColsEnd, 763
- nEmptyRows, 763
- nMOnes, 762
- nnz, 762
- nOnes, 762
- nOthers, 762
- rowdim, 762
- STD\_RECINT\_SIZE
  - benchmark-fgemm-mp.C, 792
  - benchmark-fgemv-mp.C, 795
- STDC\_HEADERS
  - config.h, 812
- stend
  - Sparse< \_Field, SparseMatrix\_t::CSR >, 744
  - Sparse< \_Field, SparseMatrix\_t::CSR\_ZO >, 748
- store
  - Simd128\_impl< true, true, false, 2 >, 571, 574
  - Simd128\_impl< true, true, false, 4 >, 581, 584
  - Simd128\_impl< true, true, false, 8 >, 591, 594
  - Simd128\_impl< true, true, true, 2 >, 602
  - Simd128\_impl< true, true, true, 4 >, 610
  - Simd128\_impl< true, true, true, 8 >, 620
  - Simd256\_impl< true, false, true, 8 >, 630
  - Simd256\_impl< true, true, false, 2 >, 638, 641
  - Simd256\_impl< true, true, false, 4 >, 650, 653, 656
  - Simd256\_impl< true, true, false, 8 >, 667, 670
  - Simd256\_impl< true, true, true, 2 >, 677
  - Simd256\_impl< true, true, true, 4 >, 688, 694
  - Simd256\_impl< true, true, true, 8 >, 703
  - Simd512\_impl< true, false, true, 8 >, 712
  - Simd512\_impl< true, true, false, 8 >, 720, 723
  - Simd512\_impl< true, true, true, 8 >, 731
- storeu
  - Simd128\_impl< true, true, false, 2 >, 571, 574
  - Simd128\_impl< true, true, false, 4 >, 581, 584
  - Simd128\_impl< true, true, false, 8 >, 591, 594
  - Simd128\_impl< true, true, true, 2 >, 602
  - Simd128\_impl< true, true, true, 4 >, 611
  - Simd128\_impl< true, true, true, 8 >, 620
  - Simd256\_impl< true, false, true, 8 >, 630
- Simd256\_impl< true, true, false, 2 >, 639, 641
- Simd256\_impl< true, true, false, 4 >, 650, 653, 656
- Simd256\_impl< true, true, false, 8 >, 667, 670
- Simd256\_impl< true, true, true, 2 >, 677
- Simd256\_impl< true, true, true, 4 >, 688, 694
- Simd256\_impl< true, true, true, 8 >, 703
- Simd512\_impl< true, false, true, 8 >, 712
- Simd512\_impl< true, true, false, 8 >, 720, 723
- Simd512\_impl< true, true, true, 8 >, 731
- stream
  - Simd128\_impl< true, true, false, 2 >, 571, 574
  - Simd128\_impl< true, true, false, 4 >, 581, 584
  - Simd128\_impl< true, true, false, 8 >, 591, 594
  - Simd128\_impl< true, true, true, 2 >, 602
  - Simd128\_impl< true, true, true, 4 >, 611
  - Simd128\_impl< true, true, true, 8 >, 620
  - Simd256\_impl< true, false, true, 8 >, 630
  - Simd256\_impl< true, true, false, 2 >, 639, 641
  - Simd256\_impl< true, true, false, 4 >, 651, 653, 656
  - Simd256\_impl< true, true, false, 8 >, 667, 670
  - Simd256\_impl< true, true, true, 2 >, 677
  - Simd256\_impl< true, true, true, 4 >, 688, 694
  - Simd256\_impl< true, true, true, 8 >, 703
  - Simd512\_impl< true, false, true, 8 >, 712
  - Simd512\_impl< true, true, false, 8 >, 720, 723
  - Simd512\_impl< true, true, true, 8 >, 731
- strmm\_
  - config-blas.h, 829
- strsm\_
  - config-blas.h, 829
- sub
  - FFLAS::vectorised, 285
  - FieldSimd< \_Field >, 453
  - RNSIntegerMod< RNS >, 553
  - ScalFunctions< Element >, 559
  - Simd128\_impl< true, true, false, 2 >, 576
  - Simd128\_impl< true, true, false, 4 >, 586
  - Simd128\_impl< true, true, false, 8 >, 596
  - Simd128\_impl< true, true, true, 2 >, 604
  - Simd128\_impl< true, true, true, 4 >, 612
  - Simd128\_impl< true, true, true, 8 >, 622
  - Simd256\_impl< true, false, true, 8 >, 632
  - Simd256\_impl< true, true, false, 2 >, 643
  - Simd256\_impl< true, true, false, 4 >, 660
  - Simd256\_impl< true, true, false, 8 >, 671
  - Simd256\_impl< true, true, true, 2 >, 679
  - Simd256\_impl< true, true, true, 4 >, 690, 696
  - Simd256\_impl< true, true, true, 8 >, 705
  - Simd512\_impl< true, false, true, 8 >, 714
  - Simd512\_impl< true, true, false, 8 >, 725
  - Simd512\_impl< true, true, true, 8 >, 733
- sub\_r
  - FieldSimd< \_Field >, 453
- subin
  - FieldSimd< \_Field >, 453
  - ScalFunctions< Element >, 559

- Simd128\_impl< true, true, false, 2 >, [576](#)
  - Simd128\_impl< true, true, false, 4 >, [586](#)
  - Simd128\_impl< true, true, false, 8 >, [596](#)
  - Simd128\_impl< true, true, true, 2 >, [604](#)
  - Simd128\_impl< true, true, true, 4 >, [613](#)
  - Simd128\_impl< true, true, true, 8 >, [622](#)
  - Simd256\_impl< true, false, true, 8 >, [632](#)
  - Simd256\_impl< true, true, false, 2 >, [643](#)
  - Simd256\_impl< true, true, false, 4 >, [660](#)
  - Simd256\_impl< true, true, false, 8 >, [672](#)
  - Simd256\_impl< true, true, true, 2 >, [679](#)
  - Simd256\_impl< true, true, true, 4 >, [690](#), [696](#)
  - Simd256\_impl< true, true, true, 8 >, [705](#)
  - Simd512\_impl< true, false, true, 8 >, [714](#)
  - Simd512\_impl< true, true, false, 8 >, [725](#)
  - Simd512\_impl< true, true, true, 8 >, [733](#)
- subin\_r
  - FieldSimd< \_Field >, [453](#)
- subp
  - FFLAS::vectorised, [285](#)
- support\_fast\_mod< double >, [764](#)
- support\_fast\_mod< float >, [764](#)
- support\_fast\_mod< int64\_t >, [764](#)
- support\_fast\_mod< T >, [764](#)
- support\_simd< T >, [765](#)
- support\_simd\_add< T >, [765](#)
- support\_simd\_mod< T >, [765](#)
- swapval
  - FFPACK, [389](#)
- SYNCH\_GROUP
  - parallel.h, [1040](#)
- SysTimer
  - FFLAS, [74](#)
- T
  - limits< char >, [492](#)
  - limits< double >, [493](#)
  - limits< float >, [493](#)
  - limits< Givaro::Integer >, [494](#)
  - limits< int >, [494](#)
  - limits< long >, [495](#)
  - limits< long long >, [496](#)
  - limits< Reclnt::rint< K > >, [496](#)
  - limits< Reclnt::ruint< K > >, [497](#)
  - limits< short int >, [498](#)
  - limits< signed char >, [498](#)
  - limits< unsigned char >, [499](#)
  - limits< unsigned int >, [499](#)
  - limits< unsigned long >, [500](#)
  - limits< unsigned long long >, [501](#)
  - limits< unsigned short int >, [501](#)
- t
  - Simd128\_impl< true, true, false, 2 >::Converter, [429](#)
  - Simd128\_impl< true, true, false, 4 >::Converter, [429](#)
  - Simd128\_impl< true, true, false, 8 >::Converter, [429](#)
  - Simd128\_impl< true, true, true, 2 >::Converter, [430](#)
  - Simd128\_impl< true, true, true, 4 >::Converter, [430](#)
  - Simd128\_impl< true, true, true, 8 >::Converter, [430](#)
  - Simd256\_impl< true, false, true, 8 >::Converter, [431](#)
  - Simd256\_impl< true, true, false, 2 >::Converter, [431](#)
  - Simd256\_impl< true, true, false, 4 >::Converter, [431](#)
  - Simd256\_impl< true, true, false, 8 >::Converter, [432](#)
  - Simd256\_impl< true, true, true, 2 >::Converter, [432](#)
  - Simd256\_impl< true, true, true, 4 >::Converter, [432](#)
  - Simd256\_impl< true, true, true, 8 >::Converter, [433](#)
  - Simd512\_impl< true, true, false, 8 >::Converter, [433](#)
  - Simd512\_impl< true, true, true, 8 >::Converter, [433](#)
- TASK
  - parallel.h, [1039](#)
- tBC
  - test-lu.C, [1097](#)
  - test-permutations.C, [1102](#)
- Test
  - Test< Elt >, [767](#)
- test
  - test-maxdelayeddim.C, [1098](#)
- Test< Elt >, [766](#)
  - \_mm, [768](#)
  - \_nn, [768](#)
  - cardinality, [767](#)
  - doTests, [768](#)
  - Elt\_ptr, [766](#)
  - enable\_if\_no\_simd\_t, [767](#)
  - enable\_if\_simd128\_t, [767](#)
  - enable\_if\_simd256\_t, [767](#)
  - enable\_if\_simd512\_t, [767](#)
  - enable\_if\_t, [766](#)
  - F, [768](#)
  - Field, [766](#)
  - is\_same\_element, [767](#)
  - Residu, [766](#)
  - run, [768](#)
  - Test, [767](#)
  - test\_ftranspose, [767](#)
- test-charpoly-check.C, [1060](#)
  - ENABLE\_CHECKER\_charpoly, [1060](#)
  - main, [1060](#)
  - printPolynomial, [1060](#)
  - TIME\_CHECKER\_CHARPOLY, [1060](#)
- test-charpoly.C, [1060](#)
  - launch\_test, [1061](#)

- main, 1061
- run\_with\_field, 1061
- test-compressQ.C, 1061
  - Field, 1062
  - main, 1062
  - printvect, 1062
- test-det-check.C, 1062
  - ENABLE\_CHECKER\_Det, 1062
  - main, 1063
  - TIME\_CHECKER\_Det, 1062
- test-det.C, 1063
  - main, 1063
  - test\_det, 1063
- test-echelon.C, 1063
  - \_\_FFLASFFPACK\_GAUSSJORDAN\_BASECASE, 1064
  - \_\_FFLASFFPACK\_PLUQ\_THRESHOLD, 1064
  - \_\_FFLASFFPACK\_SEQUENTIAL, 1064
  - main, 1065
  - run\_with\_field, 1065
  - test\_colechelon, 1064
  - test\_redcoechelon, 1065
  - test\_redrowechelon, 1065
  - test\_rowechelon, 1065
- test-fadd.C, 1066
  - main, 1067
  - test\_fadd, 1066
  - test\_faddin, 1066
  - test\_fsub, 1066
  - test\_fsubin, 1067
- test-fdot.C, 1067
  - check\_fdot, 1068
  - ENABLE\_ALL\_CHECKINGS, 1067
  - main, 1068
  - run\_with\_field, 1068
  - run\_with\_Integer, 1068
- test-fgemm-check.C, 1068
  - ENABLE\_ALL\_CHECKINGS, 1069
  - launch\_MM\_dispatch, 1069
  - main, 1069
  - run\_with\_field, 1069
- test-fgemm.C, 1069
  - check\_MM, 1070
  - ENABLE\_CHECKER\_fgemm, 1070
  - launch\_MM, 1070
  - launch\_MM\_dispatch, 1071
  - main, 1071
  - run\_with\_field, 1071
- test-fgemv.C, 1072
  - check\_MV, 1072
  - launch\_MV, 1072
  - launch\_MV\_dispatch, 1073
  - main, 1073
  - run\_with\_field, 1073
- test-fger.C, 1073
  - check\_fger, 1074
  - launch\_fger, 1074
  - launch\_fger\_dispatch, 1074
- main, 1075
- run\_with\_field, 1075
- TIME, 1074
- test-fgesv.C, 1075
  - main, 1076
  - run\_with\_field, 1076
  - test\_rect\_fgesv, 1076
  - test\_square\_fgesv, 1076
- test-finit.C, 1076
  - main, 1077
  - run\_with\_field, 1077
  - test\_freduce, 1077
- test-fscal.C, 1077
  - main, 1079
  - test\_fscal, 1078
  - test\_fscaln, 1078
- test-fsyr2k.C, 1079
  - check\_fsyr2k, 1079
  - ENABLE\_ALL\_CHECKINGS, 1079
  - main, 1080
  - run\_with\_field, 1079
- test-fsyrk.C, 1080
  - check\_computeS1S2, 1081
  - check\_fsyrk, 1081
  - check\_fsyrk\_bkdiag, 1081
  - check\_fsyrk\_diag, 1081
  - ENABLE\_ALL\_CHECKINGS, 1081
  - main, 1082
  - run\_with\_field, 1081
- test-fsytrf.C, 1082
  - main, 1083
  - operator<<, 1082
  - run\_with\_field, 1083
  - test\_generic\_fsytrf, 1083
  - test\_RPM\_fsytrf, 1082
- test-ftmm.C, 1083
  - \_\_FFLASFFPACK\_SEQUENTIAL, 1084
  - check\_ftmm, 1084
  - main, 1084
  - run\_with\_field, 1084
- test-ftmv.C, 1084
  - \_\_FFLASFFPACK\_SEQUENTIAL, 1085
  - check\_ftmv, 1085
  - ENABLE\_ALL\_CHECKINGS, 1085
  - main, 1085
  - run\_with\_field, 1085
- test-ftsm-check.C, 1086
  - ENABLE\_ALL\_CHECKINGS, 1086
  - main, 1086
- test-ftsm.C, 1086
  - \_\_FFLASFFPACK\_SEQUENTIAL, 1087
  - check\_ftsm, 1087
  - ENABLE\_ALL\_CHECKINGS, 1087
  - main, 1087
  - run\_with\_field, 1087
- test-ftssyr2k.C, 1087
  - check\_ftssyr2k, 1088
  - ENABLE\_ALL\_CHECKINGS, 1088

- main, 1088
- run\_with\_field, 1088
- test-ftrstr.C, 1089
  - check\_ftrstr, 1089
  - ENABLE\_ALL\_CHECKINGS, 1089
  - main, 1089
  - run\_with\_field, 1089
- test-ftrsv.C, 1090
  - \_\_FFLASFFPACK\_SEQUENTIAL, 1090
  - check\_ftrsv, 1090
  - ENABLE\_ALL\_CHECKINGS, 1090
  - main, 1091
  - run\_with\_field, 1090
- test-ftrtri.C, 1091
  - \_\_FFLASFFPACK\_SEQUENTIAL, 1091
  - check\_ftrtri, 1091
  - ENABLE\_ALL\_CHECKINGS, 1091
  - main, 1092
  - run\_with\_field, 1092
- test-interfaces-c.c, 1092
  - main, 1092
- test-invert-check.C, 1092
  - ENABLE\_ALL\_CHECKINGS, 1093
  - main, 1093
- test-io.C, 1093
  - main, 1093
  - run\_with\_field, 1093
- test-lu.C, 1094
  - \_\_FFLASFFPACK\_SEQUENTIAL, 1094
  - \_\_LUDIVINE\_CUTOFF, 1095
  - BASECASE\_K, 1094
  - launch\_test, 1096
  - main, 1097
  - mvcnt, 1097
  - run\_with\_field, 1097
  - tBC, 1097
  - test\_LUdivine, 1095
  - test\_pluq, 1096
  - tgemm, 1097
  - timtot, 1097
  - tperm, 1097
  - trest, 1097
  - ttrsm, 1097
  - verifPLUQ, 1095
- test-maxdelayeddim.C, 1098
  - main, 1098
  - MAX\_WITH\_SIZE\_T, 1098
  - test, 1098
- test-minpoly.C, 1098
  - check\_minpoly, 1099
  - main, 1099
  - run\_with\_field, 1099
- test-multifile1.C, 1099
- test-multifile2.C, 1099
  - main, 1099
- test-nullspace.C, 1100
  - checkingMessage, 1100
  - main, 1101
  - readOrRandomMatrixWithRankAndRandomRPM, 1100
  - run\_with\_field, 1101
  - test\_nullspace, 1100
- test-permutations.C, 1101
  - checkMonotonicApplyP, 1101
  - main, 1101
  - tBC, 1102
  - tgemm, 1102
  - timtot, 1102
  - tperm, 1102
  - trest, 1102
  - ttrsm, 1102
- test-pluq-check.C, 1102
  - ENABLE\_ALL\_CHECKINGS, 1102
  - main, 1102
- test-quasisep.C, 1103
  - launch\_test, 1103
  - main, 1104
  - run\_with\_field, 1104
  - test\_BruhatGenerator, 1103
  - testLTQSRPM, 1103
- test-rankprofiles.C, 1104
  - \_\_FFLASFFPACK\_SEQUENTIAL, 1104
  - main, 1105
  - run\_with\_field, 1104
- test-rpm.C, 1105
  - checkRPM, 1105
  - checkSymmetricRPM, 1105
  - main, 1105
- test-simd.C, 1105
  - \_TEST\_ONE, 1107
  - check\_eq, 1107, 1108
  - cmp, 1108
  - eval\_func\_on\_array, 1108
  - main, 1108
  - operator<<, 1108
  - TEST\_IMPL, 1107
  - test\_impl, 1108
  - test\_impl\_base, 1108
  - TEST\_ONE\_OP, 1107
  - TEST\_ONE\_OP\_WZ, 1107
- test-solve.C, 1109
  - check\_solve, 1109
  - main, 1109
  - run\_with\_field, 1109
- test-storage-transpose.C, 1109
  - main, 1110
- test-utils.h, 1055
- test\_BruhatGenerator
  - test-quasisep.C, 1103
- test\_colechelon
  - test-echelon.C, 1064
- test\_det
  - test-det.C, 1063
- test\_fadd
  - test-fadd.C, 1066
- test\_faddin



- test-fadd.C, 1066
- test\_freduce
  - test-finit.C, 1077
- test\_fscal
  - test-fscal.C, 1078
- test\_fscalin
  - test-fscal.C, 1078
- test\_fsub
  - test-fadd.C, 1066
- test\_fsubin
  - test-fadd.C, 1067
- test\_ftranspose
  - Test< Elt >, 767
- test\_generic\_fsytrf
  - test-fsytrf.C, 1083
- TEST\_IMPL
  - test-simd.C, 1107
- test\_impl
  - test-simd.C, 1108
- test\_impl\_base
  - test-simd.C, 1108
- test\_LUdivine
  - test-lu.C, 1095
- test\_nullspace
  - test-nullspace.C, 1100
- TEST\_ONE\_OP
  - test-simd.C, 1107
- TEST\_ONE\_OP\_WZ
  - test-simd.C, 1107
- test\_pluq
  - test-lu.C, 1096
- test\_rect\_fgesv
  - test-fgesv.C, 1076
- test\_redcoechelon
  - test-echelon.C, 1065
- test\_redrowechelon
  - test-echelon.C, 1065
- test\_rowechelon
  - test-echelon.C, 1065
- test\_RPM\_fsytrf
  - test-fsytrf.C, 1082
- test\_square\_fgesv
  - test-fgesv.C, 1076
- testLTQSRPM
  - test-quasisep.C, 1103
- TestOneMethod
  - TestOneMethod< Simd >, 770
- TestOneMethod< Simd >, 768
  - Element, 769
  - enable\_if\_t, 769
  - evaluate\_scalar\_method, 770
  - evaluate\_simd\_method, 770
  - getStatus, 771
  - getTestName, 771
  - inputs, 771
  - name, 771
  - nb\_lref, 771
  - outputs\_scalar, 771
  - outputs\_simd, 771
  - TestOneMethod, 770
  - vect\_size, 771
  - vect\_t, 769
  - vectElt, 769
  - writeDebugData, 771
  - writeResultLine, 771
- tfn\_minus, 772
  - operator(), 772
- tfn\_minus\_eq, 772
  - operator(), 772
- tfn\_mul, 772
  - operator(), 772
- tfn\_mul\_eq, 773
  - operator(), 773
- tfn\_plus, 773
  - operator(), 773
- tfn\_plus\_eq, 773
  - operator(), 773
- tgemm
  - test-lu.C, 1097
  - test-permutations.C, 1102
- THREAD\_INDEX
  - parallel.h, 1040
- THREADS
  - benchmark-fgemm-rns.C, 793
- Threads, 774
- threads\_fgemm
  - FFPACK, 368
- threads\_frsm
  - FFPACK, 368
- THREED
  - benchmark-fgemm-rns.C, 793
- ThreeD, 774
- THREEDA
  - benchmark-fgemm-rns.C, 794
- ThreeDAdaptive, 774
- ThreeDInPlace, 774
- THREEDIP
  - benchmark-fgemm-rns.C, 794
- TIME
  - test-fger.C, 1074
- TIME\_CHECKER\_CHARPOLY
  - test-charpoly-check.C, 1060
- TIME\_CHECKER\_Det
  - test-det-check.C, 1062
- Timer
  - FFLAS, 74
- timer.h, 1056
- timtot
  - test-lu.C, 1097
  - test-permutations.C, 1102
- TInverter
  - FFPACK, 351, 353
- tmain
  - benchmark-fgemm-mp.C, 792
  - benchmark-fgemv-mp.C, 795
- Todo List, 9



## tperm

test-lu.C, [1097](#)test-permutations.C, [1102](#)

## transpose

BlockTransposeSIMD< Field, Simd, >, [414](#)Simd128\_impl< true, true, false, 2 >, [575](#)Simd128\_impl< true, true, false, 4 >, [585](#)Simd128\_impl< true, true, false, 8 >, [595](#)Simd128\_impl< true, true, true, 2 >, [603](#)Simd128\_impl< true, true, true, 4 >, [612](#)Simd128\_impl< true, true, true, 8 >, [621](#)Simd256\_impl< true, false, true, 8 >, [631](#)Simd256\_impl< true, true, false, 2 >, [643](#)Simd256\_impl< true, true, false, 4 >, [659](#)Simd256\_impl< true, true, false, 8 >, [671](#)Simd256\_impl< true, true, true, 2 >, [678](#)Simd256\_impl< true, true, true, 4 >, [689](#), [696](#)Simd256\_impl< true, true, true, 8 >, [705](#)Simd512\_impl< true, false, true, 8 >, [714](#)Simd512\_impl< true, true, false, 8 >, [725](#)Simd512\_impl< true, true, true, 8 >, [733](#)

## trest

test-lu.C, [1097](#)test-permutations.C, [1102](#)

## trinv\_left

FFPACK, [314](#), [372](#)

## trinv\_left\_modular\_double

ffpack.C, [998](#)ffpack\_c.h, [1019](#)

## TRSMBound

FFLAS::Protected, [216](#), [217](#)

## TRSMHelper

TRSMHelper< ReclterTrait, ParSeqTrait >, [775](#)TRSMHelper< ReclterTrait, ParSeqTrait >, [774](#)parseq, [776](#)pMMH, [775](#)TRSMHelper, [775](#)

## TTimer

arithprog.C, [779](#)autotune/charpoly.C, [816](#)autotune/pluq.C, [818](#)benchmark-dgemm.C, [786](#)benchmark-dgetrf.C, [787](#)benchmark-dgetri.C, [788](#)benchmark-dsytrf.C, [788](#)benchmark-dtrsm.C, [789](#)benchmark-dtrtri.C, [790](#)fsyrk.C, [780](#)fsytrf.C, [781](#)ftrtri.C, [782](#)winograd.C, [783](#)

## ttrsm

test-lu.C, [1097](#)test-permutations.C, [1102](#)Tutorial, [2](#)

## TWOD

benchmark-fgemm-rns.C, [793](#)TwoD, [776](#)

## TWODA

benchmark-fgemm-rns.C, [793](#)TwoDAdaptive, [776](#)

## type

Argument, [408](#)associatedDelayedField< const FFPACK::RNSIntegerMod< RNS > >, [408](#)associatedDelayedField< const Givaro::Modular< T, X > >, [409](#)associatedDelayedField< const Givaro::ModularBalanced< T > >, [409](#)associatedDelayedField< const Givaro::ZRing< T > >, [410](#)associatedDelayedField< Field >, [408](#)CompactElement< double >, [425](#)CompactElement< Element >, [425](#)CompactElement< float >, [426](#)CompactElement< int16\_t >, [426](#)CompactElement< int32\_t >, [426](#)CompactElement< int64\_t >, [426](#)is\_simd< T >, [485](#)

## TYPE\_BOOL

args-parser.h, [1047](#)

## TYPE\_DOUBLE

args-parser.h, [1047](#)

## TYPE\_INT

args-parser.h, [1047](#)

## TYPE\_INTEGER

args-parser.h, [1047](#)

## type\_integer

args-parser.h, [1047](#)

## TYPE\_INTLIST

args-parser.h, [1047](#)

## TYPE\_LONGLONG

args-parser.h, [1047](#)

## TYPE\_NONE

args-parser.h, [1047](#)

## TYPE\_STR

args-parser.h, [1047](#)

## type\_string

NoSimd< T >, [525](#)Simd128\_impl< true, true, false, 2 >, [571](#)Simd128\_impl< true, true, false, 4 >, [581](#)Simd128\_impl< true, true, false, 8 >, [591](#)Simd128\_impl< true, true, true, 2 >, [601](#)Simd128\_impl< true, true, true, 4 >, [610](#)Simd128\_impl< true, true, true, 8 >, [619](#)Simd256\_impl< true, false, true, 8 >, [629](#)Simd256\_impl< true, true, false, 2 >, [638](#)Simd256\_impl< true, true, false, 4 >, [650](#), [652](#)Simd256\_impl< true, true, false, 8 >, [666](#)Simd256\_impl< true, true, true, 2 >, [676](#)Simd256\_impl< true, true, true, 4 >, [687](#), [693](#)Simd256\_impl< true, true, true, 8 >, [702](#)Simd512\_impl< true, false, true, 8 >, [711](#)Simd512\_impl< true, true, false, 8 >, [719](#)Simd512\_impl< true, true, true, 8 >, [730](#)

## TYPE\_UINT64

- args-parser.h, [1047](#)
- unfit
  - FFLAS::Protected, [225](#), [226](#)
- unpackhi
  - ScalFunctions< Element >, [561](#)
  - Simd128\_impl< true, true, false, 2 >, [575](#)
  - Simd128\_impl< true, true, false, 4 >, [585](#)
  - Simd128\_impl< true, true, false, 8 >, [595](#)
  - Simd128\_impl< true, true, true, 2 >, [603](#)
  - Simd128\_impl< true, true, true, 4 >, [611](#)
  - Simd128\_impl< true, true, true, 8 >, [621](#)
  - Simd256\_impl< true, false, true, 8 >, [631](#)
  - Simd256\_impl< true, true, false, 2 >, [642](#)
  - Simd256\_impl< true, true, false, 4 >, [658](#)
  - Simd256\_impl< true, true, false, 8 >, [670](#)
  - Simd256\_impl< true, true, true, 2 >, [678](#)
  - Simd256\_impl< true, true, true, 4 >, [689](#), [695](#)
  - Simd256\_impl< true, true, true, 8 >, [704](#)
  - Simd512\_impl< true, false, true, 8 >, [713](#)
  - Simd512\_impl< true, true, false, 8 >, [724](#)
  - Simd512\_impl< true, true, true, 8 >, [732](#)
- unpackhi\_intrinsic
  - Simd128\_impl< true, true, false, 2 >, [575](#)
  - Simd128\_impl< true, true, false, 4 >, [584](#)
  - Simd128\_impl< true, true, false, 8 >, [595](#)
  - Simd128\_impl< true, true, true, 2 >, [602](#)
  - Simd128\_impl< true, true, true, 4 >, [611](#)
  - Simd128\_impl< true, true, true, 8 >, [620](#)
  - Simd256\_impl< true, false, true, 8 >, [631](#)
  - Simd256\_impl< true, true, false, 2 >, [642](#)
  - Simd256\_impl< true, true, false, 4 >, [657](#)
  - Simd256\_impl< true, true, false, 8 >, [670](#)
  - Simd256\_impl< true, true, true, 2 >, [678](#)
  - Simd256\_impl< true, true, true, 4 >, [689](#), [695](#)
  - Simd256\_impl< true, true, true, 8 >, [704](#)
  - Simd512\_impl< true, false, true, 8 >, [713](#)
  - Simd512\_impl< true, true, false, 8 >, [724](#)
  - Simd512\_impl< true, true, true, 8 >, [732](#)
- unpacklo
  - ScalFunctions< Element >, [561](#)
  - Simd128\_impl< true, true, false, 2 >, [575](#)
  - Simd128\_impl< true, true, false, 4 >, [585](#)
  - Simd128\_impl< true, true, false, 8 >, [595](#)
  - Simd128\_impl< true, true, true, 2 >, [602](#)
  - Simd128\_impl< true, true, true, 4 >, [611](#)
  - Simd128\_impl< true, true, true, 8 >, [621](#)
  - Simd256\_impl< true, false, true, 8 >, [631](#)
  - Simd256\_impl< true, true, false, 2 >, [642](#)
  - Simd256\_impl< true, true, false, 4 >, [657](#)
  - Simd256\_impl< true, true, false, 8 >, [670](#)
  - Simd256\_impl< true, true, true, 2 >, [678](#)
  - Simd256\_impl< true, true, true, 4 >, [689](#), [695](#)
  - Simd256\_impl< true, true, true, 8 >, [704](#)
  - Simd512\_impl< true, false, true, 8 >, [713](#)
  - Simd512\_impl< true, true, false, 8 >, [724](#)
  - Simd512\_impl< true, true, true, 8 >, [732](#)
- unpacklo\_intrinsic
  - Simd128\_impl< true, true, false, 2 >, [574](#)
- Simd128\_impl< true, true, false, 4 >, [584](#)
- Simd128\_impl< true, true, false, 8 >, [594](#)
- Simd128\_impl< true, true, true, 2 >, [602](#)
- Simd128\_impl< true, true, true, 4 >, [611](#)
- Simd128\_impl< true, true, true, 8 >, [620](#)
- Simd256\_impl< true, false, true, 8 >, [631](#)
- Simd256\_impl< true, true, false, 2 >, [642](#)
- Simd256\_impl< true, true, false, 4 >, [657](#)
- Simd256\_impl< true, true, false, 8 >, [670](#)
- Simd256\_impl< true, true, true, 2 >, [678](#)
- Simd256\_impl< true, true, true, 4 >, [689](#), [695](#)
- Simd256\_impl< true, true, true, 8 >, [704](#)
- Simd512\_impl< true, false, true, 8 >, [713](#)
- Simd512\_impl< true, true, false, 8 >, [724](#)
- Simd512\_impl< true, true, true, 8 >, [732](#)
- unpacklohi
  - ScalFunctions< Element >, [562](#)
  - Simd128\_impl< true, true, false, 2 >, [575](#)
  - Simd128\_impl< true, true, false, 4 >, [585](#)
  - Simd128\_impl< true, true, false, 8 >, [595](#)
  - Simd128\_impl< true, true, true, 2 >, [603](#)
  - Simd128\_impl< true, true, true, 4 >, [612](#)
  - Simd128\_impl< true, true, true, 8 >, [621](#)
  - Simd256\_impl< true, false, true, 8 >, [631](#)
  - Simd256\_impl< true, true, false, 2 >, [642](#)
  - Simd256\_impl< true, true, false, 4 >, [658](#)
  - Simd256\_impl< true, true, false, 8 >, [671](#)
  - Simd256\_impl< true, true, true, 2 >, [678](#)
  - Simd256\_impl< true, true, true, 4 >, [689](#), [695](#)
  - Simd256\_impl< true, true, true, 8 >, [704](#)
  - Simd512\_impl< true, false, true, 8 >, [713](#)
  - Simd512\_impl< true, true, false, 8 >, [724](#)
  - Simd512\_impl< true, true, true, 8 >, [732](#)
- UnparametricTag, [776](#)
- updateD
  - FFPACK::Protected, [401](#)
- USE\_OPENMP
  - config.h, [812](#)
- UserTimer
  - FFLAS, [74](#)
- utils.h, [920](#)
- v
  - Simd128\_impl< true, true, false, 2 >::Converter, [429](#)
  - Simd128\_impl< true, true, false, 4 >::Converter, [429](#)
  - Simd128\_impl< true, true, false, 8 >::Converter, [429](#)
  - Simd128\_impl< true, true, true, 2 >::Converter, [430](#)
  - Simd128\_impl< true, true, true, 4 >::Converter, [430](#)
  - Simd128\_impl< true, true, true, 8 >::Converter, [430](#)
  - Simd256\_impl< true, false, true, 8 >::Converter, [431](#)
  - Simd256\_impl< true, true, false, 2 >::Converter, [431](#)

- Simd256\_impl< true, true, false, 4 >::Converter, [431](#)
- Simd256\_impl< true, true, false, 8 >::Converter, [432](#)
- Simd256\_impl< true, true, true, 2 >::Converter, [432](#)
- Simd256\_impl< true, true, true, 4 >::Converter, [432](#)
- Simd256\_impl< true, true, true, 8 >::Converter, [433](#)
- Simd512\_impl< true, true, false, 8 >::Converter, [433](#)
- Simd512\_impl< true, true, true, 8 >::Converter, [433](#)
- val
  - Coo< Field >, [436](#)
  - Coo< ValT, IdxT >, [435](#), [438](#)
- valid
  - NoSimd< T >, [525](#)
  - Simd128\_impl< true, true, false, 2 >, [573](#)
  - Simd128\_impl< true, true, false, 4 >, [583](#)
  - Simd128\_impl< true, true, false, 8 >, [593](#)
  - Simd128\_impl< true, true, true, 2 >, [601](#)
  - Simd128\_impl< true, true, true, 4 >, [610](#)
  - Simd128\_impl< true, true, true, 8 >, [619](#)
  - Simd256\_impl< true, false, true, 8 >, [629](#)
  - Simd256\_impl< true, true, false, 2 >, [640](#)
  - Simd256\_impl< true, true, false, 4 >, [655](#)
  - Simd256\_impl< true, true, false, 8 >, [669](#)
  - Simd256\_impl< true, true, true, 2 >, [676](#)
  - Simd256\_impl< true, true, true, 4 >, [687](#), [693](#)
  - Simd256\_impl< true, true, true, 8 >, [702](#)
  - Simd512\_impl< true, false, true, 8 >, [711](#)
  - Simd512\_impl< true, true, false, 8 >, [722](#)
  - Simd512\_impl< true, true, true, 8 >, [730](#)
- VALUE
  - parallel.h, [1040](#)
- value
  - AlgoChooser< ModeCategories::ConvertTo< ElementCategories::RNSElementTag >, ParSeq >, [405](#)
  - AlgoChooser< ModeT, ParSeq >, [405](#)
  - ALL< false, v... >, [406](#)
  - ALL< true, v... >, [406](#)
  - ALL<>, [406](#)
  - AreEqual< X, X >, [407](#)
  - AreEqual< X, Y >, [407](#)
  - compatible\_data\_type< Field >, [427](#)
  - compatible\_data\_type< Givaro::ZRing< double > >, [427](#)
  - compatible\_data\_type< Givaro::ZRing< float > >, [427](#)
  - ElementTraits< double >, [443](#)
  - ElementTraits< Element >, [442](#)
  - ElementTraits< FFPACK::rns\_double\_elt >, [443](#)
  - ElementTraits< float >, [443](#)
  - ElementTraits< Givaro::Integer >, [443](#)
  - ElementTraits< int16\_t >, [444](#)
  - ElementTraits< int32\_t >, [444](#)
  - ElementTraits< int64\_t >, [444](#)
  - ElementTraits< int8\_t >, [445](#)
  - ElementTraits< RecInt::rint< K > >, [445](#)
  - ElementTraits< RecInt::rmint< K, MG > >, [445](#)
  - ElementTraits< RecInt::ruint< K > >, [446](#)
  - ElementTraits< uint16\_t >, [446](#)
  - ElementTraits< uint32\_t >, [446](#)
  - ElementTraits< uint64\_t >, [446](#)
  - ElementTraits< uint8\_t >, [447](#)
  - has\_minus\_eq\_impl< C >, [476](#)
  - has\_minus\_impl< C >, [476](#)
  - has\_mul\_eq\_impl< C >, [476](#)
  - has\_mul\_impl< C >, [477](#)
  - has\_operation< T >, [477](#)
  - has\_plus\_eq\_impl< C >, [477](#)
  - has\_plus\_impl< C >, [478](#)
  - is\_all\_same< T, Args... >, [484](#)
  - is\_all\_same<>, [485](#)
  - is\_simd< T >, [485](#)
  - ModeTraits< Field >, [516](#)
  - ModeTraits< Givaro::Modular< Element, Compute > >, [517](#)
  - ModeTraits< Givaro::Modular< Givaro::Integer, Compute > >, [517](#)
  - ModeTraits< Givaro::Modular< int16\_t, Compute > >, [517](#)
  - ModeTraits< Givaro::Modular< int32\_t, Compute > >, [518](#)
  - ModeTraits< Givaro::Modular< int64\_t, uint64\_t > >, [518](#)
  - ModeTraits< Givaro::Modular< int8\_t, Compute > >, [518](#)
  - ModeTraits< Givaro::Modular< RecInt::ruint< K >, Compute > >, [519](#)
  - ModeTraits< Givaro::Modular< uint16\_t, Compute > >, [519](#)
  - ModeTraits< Givaro::Modular< uint32\_t, Compute > >, [519](#)
  - ModeTraits< Givaro::Modular< uint8\_t, Compute > >, [520](#)
  - ModeTraits< Givaro::ModularBalanced< Element > >, [520](#)
  - ModeTraits< Givaro::ModularBalanced< Givaro::Integer > >, [520](#)
  - ModeTraits< Givaro::ModularBalanced< int16\_t > >, [521](#)
  - ModeTraits< Givaro::ModularBalanced< int32\_t > >, [521](#)
  - ModeTraits< Givaro::ModularBalanced< int8\_t > >, [521](#)
  - ModeTraits< Givaro::Montgomery< T > >, [522](#)
  - ModeTraits< Givaro::ZRing< double > >, [522](#)
  - ModeTraits< Givaro::ZRing< float > >, [522](#)
  - ModeTraits< Givaro::ZRing< Givaro::Integer > >, [523](#)
  - need\_field\_characteristic< Field >, [523](#)
  - need\_field\_characteristic< Givaro::Modular< Field

- [> >, 524](#)
- [need\\_field\\_characteristic< Givaro::ModularBalanced< Field > >, 524](#)
- [SimdChooser< T, false, b >, 739](#)
- [SimdChooser< T, true, false >, 739](#)
- [SimdChooser< T, true, true >, 739](#)
- [width< double >, 777](#)
- [width< float >, 777](#)
- [width< T >, 776](#)
- [vand](#)
  - [ScalFunctions< Element >, 559](#)
  - [Simd128\\_impl< true, true, false, 2 >, 578](#)
  - [Simd128\\_impl< true, true, false, 4 >, 587](#)
  - [Simd128\\_impl< true, true, false, 8 >, 598](#)
  - [Simd128\\_impl< true, true, true, 2 >, 607](#)
  - [Simd128\\_impl< true, true, true, 4 >, 616](#)
  - [Simd128\\_impl< true, true, true, 8 >, 625](#)
  - [Simd128i\\_base, 627](#)
  - [Simd256\\_impl< true, false, true, 8 >, 634](#)
  - [Simd256\\_impl< true, true, false, 4 >, 663](#)
  - [Simd256\\_impl< true, true, true, 4 >, 699](#)
  - [Simd512\\_impl< true, true, false, 8 >, 727](#)
  - [Simd512\\_impl< true, true, true, 8 >, 737](#)
  - [Simd512i\\_base, 738](#)
- [vandnot](#)
  - [ScalFunctions< Element >, 559](#)
  - [Simd128\\_impl< true, true, false, 2 >, 578](#)
  - [Simd128\\_impl< true, true, false, 4 >, 588](#)
  - [Simd128\\_impl< true, true, false, 8 >, 598](#)
  - [Simd128\\_impl< true, true, true, 2 >, 607](#)
  - [Simd128\\_impl< true, true, true, 4 >, 616](#)
  - [Simd128\\_impl< true, true, true, 8 >, 625](#)
  - [Simd128i\\_base, 627](#)
  - [Simd256\\_impl< true, false, true, 8 >, 634](#)
  - [Simd256\\_impl< true, true, false, 4 >, 663](#)
  - [Simd256\\_impl< true, true, true, 4 >, 700](#)
  - [Simd512\\_impl< true, true, false, 8 >, 727](#)
  - [Simd512\\_impl< true, true, true, 8 >, 737](#)
  - [Simd512i\\_base, 738](#)
- [VEC\\_ADD](#)
  - [FFLAS::vectorised, 284](#)
- [VEC\\_SUB](#)
  - [FFLAS::vectorised, 284](#)
- [vect\\_size](#)
  - [FieldSimd< \\_Field >, 456](#)
  - [NoSimd< T >, 525](#)
  - [Simd128\\_impl< true, true, false, 2 >, 578](#)
  - [Simd128\\_impl< true, true, false, 4 >, 588](#)
  - [Simd128\\_impl< true, true, false, 8 >, 598](#)
  - [Simd128\\_impl< true, true, true, 2 >, 607](#)
  - [Simd128\\_impl< true, true, true, 4 >, 616](#)
  - [Simd128\\_impl< true, true, true, 8 >, 626](#)
  - [Simd256\\_impl< true, false, true, 8 >, 635](#)
  - [Simd256\\_impl< true, true, false, 2 >, 645](#)
  - [Simd256\\_impl< true, true, false, 4 >, 664](#)
  - [Simd256\\_impl< true, true, false, 8 >, 673](#)
  - [Simd256\\_impl< true, true, true, 2 >, 682](#)
  - [Simd256\\_impl< true, true, true, 4 >, 700](#)
- [Simd256\\_impl< true, true, true, 8 >, 709](#)
- [Simd512\\_impl< true, false, true, 8 >, 716](#)
- [Simd512\\_impl< true, true, false, 8 >, 727](#)
- [Simd512\\_impl< true, true, true, 8 >, 737](#)
- [TestOneMethod< Simd >, 771](#)
- [vect\\_t](#)
  - [FieldSimd< \\_Field >, 451](#)
  - [NoSimd< T >, 524](#)
  - [Simd128\\_impl< true, true, false, 2 >, 570](#)
  - [Simd128\\_impl< true, true, false, 4 >, 581](#)
  - [Simd128\\_impl< true, true, false, 8 >, 591](#)
  - [Simd128\\_impl< true, true, true, 2 >, 600](#)
  - [Simd128\\_impl< true, true, true, 4 >, 609](#)
  - [Simd128\\_impl< true, true, true, 8 >, 618](#)
  - [simd128\\_int64.inl, 883](#)
  - [Simd128i\\_base, 626](#)
  - [Simd256\\_impl< true, false, true, 8 >, 629](#)
  - [Simd256\\_impl< true, true, false, 2 >, 638](#)
  - [Simd256\\_impl< true, true, false, 4 >, 649](#)
  - [Simd256\\_impl< true, true, false, 8 >, 666](#)
  - [Simd256\\_impl< true, true, true, 2 >, 675](#)
  - [Simd256\\_impl< true, true, true, 4 >, 686](#)
  - [Simd256\\_impl< true, true, true, 8 >, 702](#)
  - [simd256\\_int64.inl, 885](#)
  - [Simd256i\\_base, 709](#)
  - [Simd512\\_impl< true, false, true, 8 >, 711](#)
  - [Simd512\\_impl< true, true, false, 8 >, 719](#)
  - [Simd512\\_impl< true, true, true, 8 >, 730](#)
  - [simd512\\_int64.inl, 888](#)
  - [Simd512i\\_base, 738](#)
  - [TestOneMethod< Simd >, 769](#)
- [vectElt](#)
  - [ScalFunctions< Element >, 558](#)
  - [TestOneMethod< Simd >, 769](#)
- [verification\\_PLUQ](#)
  - [benchmark-pluq.C, 806](#)
- [verifPLUQ](#)
  - [test-lu.C, 1095](#)
- [VERSION](#)
  - [config.h, 812](#)
- [vor](#)
  - [ScalFunctions< Element >, 559](#)
  - [Simd128\\_impl< true, true, false, 2 >, 578](#)
  - [Simd128\\_impl< true, true, false, 4 >, 588](#)
  - [Simd128\\_impl< true, true, false, 8 >, 598](#)
  - [Simd128\\_impl< true, true, true, 2 >, 607](#)
  - [Simd128\\_impl< true, true, true, 4 >, 616](#)
  - [Simd128\\_impl< true, true, true, 8 >, 625](#)
  - [Simd128i\\_base, 627](#)
  - [Simd256\\_impl< true, false, true, 8 >, 634](#)
  - [Simd256\\_impl< true, true, false, 4 >, 663](#)
  - [Simd256\\_impl< true, true, true, 4 >, 699](#)
  - [Simd512\\_impl< true, true, false, 8 >, 727](#)
  - [Simd512\\_impl< true, true, true, 8 >, 737](#)
  - [Simd512i\\_base, 738](#)
- [vxor](#)
  - [ScalFunctions< Element >, 559](#)
  - [Simd128\\_impl< true, true, false, 2 >, 578](#)

- Simd128\_impl< true, true, false, 4 >, [588](#)
- Simd128\_impl< true, true, false, 8 >, [598](#)
- Simd128\_impl< true, true, true, 2 >, [607](#)
- Simd128\_impl< true, true, true, 4 >, [616](#)
- Simd128\_impl< true, true, true, 8 >, [625](#)
- Simd128i\_base, [627](#)
- Simd256\_impl< true, false, true, 8 >, [634](#)
- Simd256\_impl< true, true, false, 4 >, [663](#)
- Simd256\_impl< true, true, true, 4 >, [699](#)
- Simd512\_impl< true, true, false, 8 >, [727](#)
- Simd512\_impl< true, true, true, 8 >, [737](#)
- Simd512i\_base, [738](#)
- WAIT
  - parallel.h, [1039](#)
- width< double >, [776](#)
  - value, [777](#)
- width< float >, [777](#)
  - value, [777](#)
- width< T >, [776](#)
  - value, [776](#)
- Winograd, [777](#)
  - FFLAS::BLAS3, [197](#)
- winograd.C, [782](#)
  - balanced, [783](#)
  - DOUBLE\_TO\_FLOAT\_CROSSOVER, [783](#)
  - GFOPS, [783](#)
  - main, [783](#)
  - TTimer, [783](#)
- Winograd\_L\_S
  - FFLAS::BLAS3, [200](#)
- Winograd\_LR\_S
  - FFLAS::BLAS3, [200](#)
- Winograd\_R\_S
  - FFLAS::BLAS3, [201](#)
- WinogradAcc\_2\_24
  - FFLAS::BLAS3, [198](#)
- WinogradAcc\_2\_27
  - FFLAS::BLAS3, [198](#)
- WinogradAcc\_3\_21
  - FFLAS::BLAS3, [198](#)
- WinogradAcc\_3\_23
  - FFLAS::BLAS3, [197](#)
- WinogradAcc\_L\_S
  - FFLAS::BLAS3, [200](#)
- WinogradAcc\_LR
  - FFLAS::BLAS3, [199](#)
- WinogradAcc\_R\_S
  - FFLAS::BLAS3, [199](#)
- WinogradCalc
  - FFLAS::Protected, [222](#)
- WinogradPar, [777](#)
- WinogradSteps
  - FFLAS::Protected, [221](#)
- WinogradThreshold
  - FFLAS::Protected, [220](#)
- WinoPar
  - FFLAS::BLAS3, [197](#)
- WINOTHRESHOLD
  - fflas.h, [834](#)
- WRITE
  - parallel.h, [1040](#)
- write
  - RNSInteger< RNS >, [549](#)
  - RNSIntegerMod< RNS >, [554](#)
- write\_field
  - Matio.h, [1055](#)
- write\_matrix
  - benchmark-fgemv-mp.C, [795](#)
  - RNSIntegerMod< RNS >, [554](#)
- write\_matrix\_long
  - RNSIntegerMod< RNS >, [555](#)
- writeCommandString
  - FFLAS, [188](#)
- writeDebugData
  - TestOneMethod< Simd >, [771](#)
- writeDnsFormat
  - FFLAS, [154](#)
- WriteMatrix
  - FFLAS, [188](#), [191](#)
- WritePermutation
  - FFLAS, [191](#)
- writeResultLine
  - TestOneMethod< Simd >, [771](#)
- zero
  - FFLAS, [76](#)
  - FieldSimd< \_Field >, [454](#)
  - RNSInteger< RNS >, [549](#)
  - RNSIntegerMod< RNS >, [556](#)
  - ScalFunctions< Element >, [559](#)
  - Simd128\_impl< true, true, false, 2 >, [577](#)
  - Simd128\_impl< true, true, false, 4 >, [587](#)
  - Simd128\_impl< true, true, false, 8 >, [597](#)
  - Simd128\_impl< true, true, true, 2 >, [607](#)
  - Simd128\_impl< true, true, true, 4 >, [615](#)
  - Simd128\_impl< true, true, true, 8 >, [625](#)
  - Simd128i\_base, [626](#)
  - Simd256\_impl< true, false, true, 8 >, [630](#)
  - Simd256\_impl< true, true, false, 2 >, [645](#)
  - Simd256\_impl< true, true, false, 4 >, [663](#)
  - Simd256\_impl< true, true, false, 8 >, [673](#)
  - Simd256\_impl< true, true, true, 2 >, [682](#)
  - Simd256\_impl< true, true, true, 4 >, [699](#)
  - Simd256\_impl< true, true, true, 8 >, [708](#)
  - Simd256i\_base, [709](#)
  - Simd512\_impl< true, false, true, 8 >, [712](#)
  - Simd512\_impl< true, true, false, 8 >, [727](#)
  - Simd512\_impl< true, true, true, 8 >, [737](#)
  - Simd512i\_base, [738](#)
- ZOSparseMatrix
  - FFLAS, [72](#)